Performance-Guaranteed ODE Solvers with Complexity-Informed Neural Networks

Abstract

Traditionally, we provide technical parameters for ODE solvers, such as the order, the stepsize and the local error threshold. However, there is no guarantee for performance metrics that users care about, such as the time consumption and the global error. In this paper, we provide such a user-oriented guarantee by using neural networks to fit the complex relationship between the technical parameters and performance metrics. The form of the neural network is carefully designed to incorporate the prior knowledge from time complexity analysis of ODE solvers, which has better performance than purely data-driven approaches. We test our strategy on some parametrized ODE problems, and experimental results show that the fitted model can achieve high accuracy, thus providing error guarantee for fixed methods and time guarantee for adaptive stepsize methods.

1 Introduction

The choice of stepsize for ODE solvers has great influences on the computational time and error, which are two fundamental performance metrics when solving differential equations. Existing approaches to choose the stepsize usually make the solver satisfy either the time or error constraint by providing some technical parameters. On the one hand, fixed stepsize method like forward Euler is often used in real-time simulator of complex system [1], which requires strict time guarantee of the method. On the other hand, adaptive stepsize method with error control strategy is used in settings when the precision of the solution is given priority. In both cases, no convenient method has been developed to choose the appropriate solvers to satisfy the requirements. In recent years, artificial neural networks have been used to design new ODE solvers [2] or construct differentiable integrators [3] to facilitate the parameter identification of dynamic systems. To our best knowledge, no efforts have been spared to use neural networks for the purpose of guaranteeing the user-oriented performance. In our work, we will fill this gap by selecting ODE solvers with complexity-informed neural networks, which is a combination of the mathematical model and the data-driven approach. To unify the two control goals, we utilize neural network to fit the complex relationship between user-oriented metrics (the error or time) and technical parameters for given ODE problems. Using our approach, we can provide strict global error control for fixed stepsize method and approximated time guarantee for adaptive stepsize method, which enlarges the usability for existing ODE solvers.

2 Methodology

We consider solving the initial value problem for a given ODE:

$$\frac{du}{dt} = f(t, u)$$
$$u(t_0) = u_0 \tag{1}$$

Many solvers are available to obtain numerical solutions of $u(t)$ for an interval $[t_0, t_{\max}]$. For explicit Runge-Kutta (RK) methods, u_n is updated with the following scheme to approximate the value $u(t_n)$.

$$u_{n+1} = u_n + h_n \psi(t_n, u_n, h_n)$$
$$t_{n+1} = t_n + h_n \tag{2}$$

In the above formula, $\psi(t, u, h)$ is a scheme-specific function for different RK methods. For example, forward Euler method has $\psi(t, u, h) = f(t, u)$. Depending on whether h_n changes or not, the methods can be divided by the fixed stepsize method ($h_n = h$ is pre-specified) and the adaptive stepsize method (h_n is adjusted at each step).

In the above, we have described the numerical routine to provide the values of two performance metrics Q_1 and Q_2. For these two metrics, our goal is to find their optimal tradeoff, which is controlled by varying the threshold (abbreviated as th). Let g_{th} be a function which maps a problem (parametrized by p) to the most suitable solver (parametrized by s, which is specified by a certain integration method and stepsize control strategy). Then for a given th, g_{th} is determined by

$$\max_{g_{\text{th}}: p \to s} \quad Q_1(p, g_{\text{th}}(p))$$
$$\text{s.t.} \quad Q_2(p, g_{\text{th}}(p)) \geq \text{th} \tag{3}$$

The optimal g_{th} for (3) makes us achieve the best for the first performance metric Q_1, while satisfying the threshold requirement for the second performance metric Q_2. Within this article, we focus on two performance metrics: accuracy (global error) and efficiency (time complexity).

The function g_{th} should be pre-trained and well generalized on problems, so that in usage, we don't need to spend extra computational cost.

2.1 Global error control for fixed stepsize method

The time complexity for fixed stepsize method is inverse proportional to the adopted stepsize h while the relationship between the error and h is unknown. To provide error control in such a case, we replace abstract variables of (3) in the following way: Q_1 specially means T_1, Q_2 means the global error (abbreviated as err), and th means the error tolerance (abbreviated as tol).

$$\min_h \quad T(p, \text{RK}, h)$$
$$\text{s.t.} \quad \text{err}(p, \text{RK}, h) \leq \text{tol} \tag{4}$$

Once we fix the p and RK method in use, the minimal T is reached when the equality constraint is satisfied. We then need to find an inverse mapping from tol to h such that $\text{err}(p, \text{RK}, h) = \text{tol}$. Since the local truncation error is of the order $O(h^q)$ where q is the order of the RK method, the relationship between $\log h$ and $\log(\text{err})$ is approximately linear. Therefore, we assume the inverse mapping has the following form

$$\log h = k \log(\text{err}) + C(p) \tag{5}$$

For a given problem parametrized by p, the intercept function $C(p)$ (represented by a neural network) and slope k can be learned after obtaining multiple triads of (p_i, h_i, err_i). The loss function can be constructed by MSE or the quantile loss. When more strict error control is preferred, the latter loss is adopted for a small quantile value q. In inference stage, the learned model is used directly to obtain the step h given the prescribed error level tol for fixed stepsize method.

To interpret the learned model visually, we consider solving a simple ODE problem by classical RK with order 4 [4]. The integration interval is $[0, t_{\max}]$, and the solution is a two-dimensional spiral.

$$\frac{du_1}{dt} = b \cos t - u_2 + u_2(t_0), u_1(t_0) = x_0$$
$$\frac{du_2}{dt} = b \sin t + u_1 - u_1(t_0), u_2(t_0) = y_0 \tag{6}$$

For this ODE problem, parameters p is concatenated by $\{b, x_0, y_0, t_{\max}\}$. To train the model described by (5), we first sample multiple data of (p, h) from bounded intervals and obtain the corresponding global errors in ℓ_∞ norm. Using an MLP with one hidden layer to describe $C(p)$, we obtain the

model illustrated in Figure 1 by varying one input variable at each time. Since (5) captures the order condition, the fitted curve matches the true relationship exactly as shown in (a). For other inputs, (5) differs not far from the numerical approximation of the true relationship, as shown in (b,c). All the fitted curves lie below the corresponding true one, which shows that the strict error control is achieved for this example problem.

(a) $t_{\max} = 2\pi, b = 1$ (b) $\log(\mathrm{err}) = -8, b = 1$ (c) $t_{\max} = 2\pi, \log(\mathrm{err}) = -8$

Figure 1: Illustration for how $\log h$ changes with respect to different inputs at $x_0 = 0, y_0 = 0$

2.2 Time control for adaptive stepsize method

In this subsection, our goal is to provide time guarantee for adaptive stepsize method. We focus on the proportional-integral stepsize controller (PIController) [5], which is a classical control strategy for explicit RK methods. PIController uses the following formula to obtain the new step size h_{n+1}

$$h_{n+1} = h_n \left(\frac{\mathrm{sc}}{\mathrm{err}_n} \right)^{\beta_1} \left(\frac{\mathrm{err}_{n-1}}{\mathrm{sc}} \right)^{\beta_2} \tag{7}$$

β_1, β_2 and sc (abbreviation of step control) are three parameters while sc has the greatest influence on the computational time. When $\beta_2 = 0$, the controller is called the integral controller (IController), which only uses err_n, the local error estimation at at $t = t_n$, to determine the new stepsize h_{n+1}.

To provide time control for a given controller, let Q_1 be the global error and Q_2 be the computational time T in (3), then

$$\begin{aligned} \min_{\mathrm{sc}} \quad & \mathrm{err}(p, \mathrm{RK}, \mathrm{sc}) \\ \text{s.t.} \quad & T(p, \mathrm{RK}, \mathrm{sc}) \leq T^* \end{aligned} \tag{8}$$

In (8), T^* is the threshold number of times to evaluate $f(t, u)$ in (1), which is proportional to the computational time approximately.

Similar to the methodology used in subsection 2.1, once p and RK are chosen, an inverse mapping from T^* to sc is required to provide computational time guarantee for adaptive stepsize method. Though adaptive strategy is adopted, by experiments we find the error order is still Ch^q approximately. Therefore, our goal is to fit the model with the following form

$$\log(\mathrm{sc}) = -k \log T + C(p) \tag{9}$$

After obtaining triples of $(p_i, \mathrm{sc}_i, T_i)$, we can learn the model (9) in training stage and infer the sc given the evaluation times T for adaptive stepsize method.

3 Experiments

3.1 Fixed stepsize methods

We consider fixed stepsize RK methods with order 2 (Midpoint), 3 (BS3), 4 (RKF4 [6]) and 5 (DP5 [7]). Besides, three different ODE problems are considered: Spiral(6), LotkaVolterra [8] and Brusselator[9]. We generate 6400 data for training, and the size of the test dataset is 1280. The evaluation metric is R^2 (coefficient of determination) on test dataset. The quantile loss with quantile value 10% is used to guarantee the error does not surpass the prescribed error level with

larger probability. From Table 1 we see that using the complexity-informed model in (5) performs better than using MLP or decision-tree based fitting with the significance level around 5%. Another observation is that incorporating the different RK methods as input to the network model does not decrease the performance of the fitting, as shown in the column of "All" of Table 1. The RK methods are treated as categorical features and pre-processed by one-hot embedding before training.

(a) Fixed stepsize RK methods with different orders on the Spiral problem

(b) Time guarantee verification for adaptive stepsize method on the Spiral problem

Figure 2

Table 1: R^2 value for different models

Problem	Model	RK Methods				
		Midpoint	BS3	RKF4	DP5	All
Spiral	MLP (baseline)	0.960	0.977	0.946	0.944	0.974
	decision-tree	0.978	0.983	0.991	0.994	0.966
	complexity-informed	**0.993**	**0.993**	**0.996**	**0.998**	**0.989**
LotkaVolterra	MLP (baseline)	0.889	0.893	0.921	0.939	0.923
	decision-tree	0.623	0.689	0.817	0.798	0.690
	complexity-informed	**0.896**	**0.914**	**0.936**	**0.933**	**0.927**
Brusselator	MLP (baseline)	0.930	0.952	0.966	0.892	0.933
	decision-tree	0.920	0.893	0.906	0.839	0.865
	complexity-informed	**0.972**	**0.972**	**0.964**	**0.929**	**0.962**

To verify that the predicted stepsize can achieve the desirable error level, we integrate the model into existing ODE solvers and obtain the work-precision diagram for different RK methods with fixed stepsize strategy. From Figure 2a, we see that for each error level (10^{-5} to 10^{-2}), the actual error (shown in each mark on the curve) is near the left hand side of the corresponding dotted grey line.

3.2 Adaptive stepsize methods

Using the same network architecture as **complexity-informed** in 3.1 and MSE loss, we obtain the fitting results for adaptive stepsize methods with different controllers, which are listed in Table 2.

Table 2: R^2 value for different controllers

Problem	Controller	RK Methods				
		Midpoint	BS3	RKF4	DP5	All
Spiral	IController	0.995	0.999	0.988	0.953	0.996
	PIController	0.995	0.994	0.983	0.931	0.985
LotkaVolterra	IController	0.968	0.932	0.873	0.729	0.926
	PIController	0.978	0.927	0.909	0.853	0.942

From Table 2, we see that the model (9) has similar fitting ability for different controllers and fits better for lower order RK methods.

Furthermore, given the expected time T^*, we can use the model (9) to get sc and solve the ODE problem to obtain the actual T. Then we verify whether the actual evaluation time is equal to the expected time by plotting Figure 2b. We see that all lines are near $T = T^*$ approximately, thus demonstrating the feasibility of our method.

References

[1]   et al. Chaudron Jean-Baptiste. "How to solve ODEs in real-time HLA distributed simulation". In: *Simulation Innovation Workshop*. 2016.

[2]   J. C. Chedjou and K. Kyamakya. "CNN-based ultrafast solver of stiff ODEs and PDEs for enabling realtime Computational Engineering". In: *Compel* 30.4 (2011), p.1333–1349.

[3]   Ricky T. Q. Chen et al. "Neural Ordinary Differential Equations". In: *Advances in Neural Information Processing Systems* (2018).

[4]   E. Hairer. *Solving Ordinary Differential Equations I*. Springer, 1993.

[5]   Kjell Gustafsson. "Control theoretic techniques for stepsize selection in explicit Runge-Kutta methods". In: *ACM Transactions on Mathematical Software (TOMS)* 17.4 (1991), pp. 533–554.

[6]   Erwin Fehlberg. *Low-order classical Runge-Kutta formulas with stepsize control and their application to some heat transfer problems*. Vol. 315. National aeronautics and space administration, 1969.

[7]   John R Dormand and Peter J Prince. "A family of embedded Runge-Kutta formulae". In: *Journal of computational and applied mathematics* 6.1 (1980), pp. 19–26.

[8]   J. Hofbauer and K. Sigmund. "Evolutionary Games and Population Dynamics: References". In: 1998. Chap. Dynamical Systems and Lotka–Volterra Equations, pp. 1–54.

[9]   Sundarapandian Vaidyanathan. "Dynamics and control of Brusselator chemical reaction". In: *Int J ChemTech Res* 8.6 (2015), pp. 740–749.