Benefits of Permutation-Equivariance in Auction Mechanisms

Abstract

Designing an incentive-compatible auction mechanism that maximizes the auctioneer's revenue while minimizes the bidders' ex-post regret is an important yet intricate problem in economics. Remarkable progresses have been achieved through learning the optimal auction mechanism by neural networks. In this paper, we consider the popular *additive valuation* and *symmetric valuation* setting; *i.e.*, the valuation for a set of items is defined as the sum of all items' valuations in the set, and the valuation distribution is invariant when the bidders and/or the items are permutated. We prove that permutation-equivariant neural networks have significant advantages: the permutation-equivariance decreases the expected ex-post regret, improves the model generalizability, while maintains the expected revenue invariant. This implies that the permutation-equivariance helps approach the theoretically optimal *dominant strategy incentive compatible* condition, and reduces the required sample complexity for desired generalization. Extensive experiments fully support our theory. To our best knowledge, this is the first work towards understanding the benefits of permutation-equivariance in auction mechanisms. Code will be released publicly.

1 Introduction

Optimal auction design [26] has wide applications in economics, including online advertising [16], resource allocation [15], and supply chain [4]. In an auction, every bidder has a private valuation profile over all items, and accordingly, submits her bid profile. An auctioneer collects the bids from all bidders, and determines a feasible item allocation to the bidders as well as the prices the bidders need to pay. Consequently, every bidder receives her utility. From the auctioneer's perspective, the optimal auction mechanism is required to maximize her *revenue*, defined as the sum of all bidders' payments. From the aspect of the bidders, the optimal auction mechanism needs to incentivize every bidder to bid according to their truthful valuation profiles (truthful bidding). This is summarized as the *dominant strategy incentive compatible* (DSIC) condition; *i.e.*, the truthful bidding is always the dominant strategy for every bidder [22].

The optimal auction mechanism can be approximated via neural networks [12, 25, 10]. The "approximation error", or the "distance" to the DSIC condition, is usually measured by the *ex-post regret*, defined as the gap between the bidder's utility of truthful bidding and the utility when her bid profile is only the best to herself (selfish bidding), while the bid profiles of all other bidders are fixed in both cases [12]. When a bidder's ex-post regret is always equal to 0, the truthful bidding is her dominant strategy. Therefore, the optimal auction design can be modeled as a linear programming problem, where the object is to maximize the expected revenue subject to the expected ex-post regret being

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

0 [12]. Another major consideration in learning the optimal mechanism is the generalizability to unseen data, usually measured by the *generalization bound*, *i.e.*, the upper bound of the gap between the expected revenue/ex-post regret and their empirical counterparts on the training data [12].

In this paper, we consider the popular setting of *additive valuation* and *symmetric valuation* [12, 25, 10]. The additive valuation condition defines the valuation for a set of items as the sum of the valuations for all items in this set. The symmetric valuation condition assumes the joint distribution of all bidders' valuation profiles to be invariant when bidders and/or items are permutated. This setting covers many applications in practice. For example, when items are independent, the additive valuation condition holds. Moreover, if the auction is anonymous or the order of the items is not prior-known, the symmetric valuation condition holds.

We demonstrate that permutation-equivariant models have significant advantages in learning the optimal auction mechanism as follows. **(1)** We prove that the permutation-equivariance in auction mechanisms decreases the expected ex-post regret while maintaining the expected revenue invariant. Conversely, and equivalently, the permutation-equivariance promises a larger expected revenue, when the expected ex-post regret is fixed. **(2)** We show that the permutation-equivariance of auction mechanisms reduces the required sample complexity for a desirable generalizability. We prove that the $l_{\infty,1}$-distance between any two mechanisms in the mechanism space decreases when they are projected to the permutation-equivariant mechanism (sub-)space. This smaller distance implies a smaller covering number of the permutation-equivariant mechanism space, which further leads to a small generalization bound [12].

We further provide an explanation for the learning process of non-permutation-equivariant neural networks (NPE-NNs). In learning the optimal auction mechanism by an NPE-NN, we show that an extra positive term exists in the quadratic penalty of the ex-post regret based on the result **(1)**. This term serves as a regularizer to penalize the "non-permutation-equivariance". Moreover, this regularizer also interferes the revenue maximization, and thus affects the learning performance of NPE-NNs. This further explains the advantages of permutation-equivariance in auction design.

Experiments in extensive auction settings are conducted to verify our theory. We design permutation-equivariant versions of RegretNet (RegretNet-test and RegretNet-PE) by projecting the RegretNet [12] to the permutation-equivariant mechanism space in the training and test stage. The empirical results show that permutation-equivariance helps: (1) achieve the optimal performance in the single-item settings; (2) significantly improve the revenue while maintain the same ex-post regret in the multi-item settings; (3) record the same revenue with a significantly lower ex-post regret; and (4) narrow the generalization gaps between the training revenue/ex-post regret and their test counterparts. These results fully support our theory.

Related works. To our best knowledge, this is the first work on explaining the benefits of permutation-equivariance in auction mechanisms. Myerson completely solves the optimal auction design problem in one-item auctions [20]. However, solutions are not clear when the number of bidders/items exceeds one [12]. Initial attempts have been presented on the characterization of optimal auction mechanisms [18, 23, 9] and algorithmic solutions [1, 2, 24]. Remarkable advances have been made on the required sample complexity for learning the optimal auction mechanism in various settings, including single-item auctions [5, 19, 15], multi-item single-bidder auctions [11], combinatorial auctions [3, 28], and allocation mechanisms [21]. Machine learning-based auction design (automated auction design) have obtained considerable progresses [6, 7, 27]. The optimal auction design is modelled as a linear programming problem [6, 7]. However, early works suffer from the scalablility issues that the number of the constraints grows exponentially when the bidder number and the item numbers increase. To address this issue, recent works propose to learn the optimal auction mechanism by deep learning. RegretNet is designed for the multi-bidder and multi-item settings [12]. Then, RegretNet is developed to meet more restrictive constraints, such as the budget condition [14] and the cerifying strategyproof condition [8]. Equivariant models EquivariantNet [25] and TransNet [10] are presented with better performance and better out-of-setting generalization in learning the near-optimal auction mechanism.

2 Notations and Preliminaries

Auction. Suppose n bidders are bidding m items in an auction. Every bidder i has her bidder-context (feature) $x_i \in \mathcal{X}$, while every item j is associated with its item-context (feature) $y_j \in \mathcal{Y}$. The bidder i has a private valuation $v_{ij} \in \mathcal{V} \subset \mathbb{R}_{\geq 0}$ for the item j, which is sampled from a conditioned distribution $\mathbb{P}(\cdot|x_i, y_j)$. The value profile $v_i = (v_{i1}, \ldots, v_{im})$ is unknown to the auctioneer. For the simplicity, we define $x = (x_1^T, \ldots, x_n^T)^T$, $y = (y_1, \ldots, y_m)$, $v = (v_1^T, \ldots, v_n^T)^T$, $v_{-i} = (v_1^T, \ldots, v_{i-1}^T, v_{i+1}^T, \ldots, v_n^T)^T$, and $(v_i', v_{-i}) = (v_1^T, \ldots, (v_i')^T \ldots, v_n^T)^T$.

Every bidder submits a bid profile b_i to the auctioneer according to her valuation profile. Then, the auctioneer determines a feasible item allocation $g(b, x, y)$ and corresponding payments $p(b, x, y)$ as per an auction mechanism (g, p). Consequently, every bidder receives her utility $u_i(v_i, b, x, y) = \sum_{j=1}^m g_{ij}(b, x, y) \cdot v_{ij} - p_i(b, x, y)$. The auction mechanism (g, p) consists of an allocation rule $g : \mathbb{R}^{n \times m} \times \mathcal{X}^n \times \mathcal{Y}^m \to \mathbb{R}^{n \times m}$ and a payment rule $p : \mathbb{R}^{n \times m} \times \mathcal{X}^n \times \mathcal{Y}^m \to \mathbb{R}^{n \times m}$, where g_{ij} is the probability of allocating item j to the bidder i, and $p_i = \sum_{j=1}^m p_{ij}$ is the price that the bidder i should pay. To avoid allocating an item over once, the allocation rule is constrained such that $\sum_{i=1}^n g_{ij}(b, x, y) \leq 1$ for all $j \in [m]$. Every v_i in our notations can be replaced by b_i. Thus, we can define the similar notations: $b_{-i} = (b_1^T, \ldots, b_{i-1}^T, b_{i+1}^T, \ldots, b_n^T)^T$, $(b_i, v_{-i}) = (v_1^T, \ldots, (b_i)^T \ldots, v_n^T)^T$ and $(v_i, b_{-i}) = (b_1^T, \ldots, (v_i)^T \ldots, b_n^T)^T$.

Optimal auction mechanism. An auction mechanism (g, p) is defined to be *dominant strategy incentive compatible* (DSIC), if truthful bidding is always a dominant strategy of every bidder; *i.e.*, $u_i(v_i, (v_i, b_{-i}), x, y) \geq u_i(v_i, b, x, y)$ for all $i \in [n]$, $v, b \in \mathcal{V}^{n \times m}$, $x \in \mathcal{X}^n$ and $y \in \mathcal{Y}^m$. In addition, an auction mechanism (g, p) is called *individually rational* (IR), if for any bidder-contexts $x \in \mathcal{X}^n$, any item-contexts $y \in \mathcal{Y}^m$, and any bidder $i \in [n]$ $x \in \mathcal{X}^n$, valuation profile and bid profile $v, b \in \mathcal{V}^{n \times m}$, truthful bidding always leads to a non-negative utility; *i.e.*, $u_i(v_i, (v_i, b_{-i}), x, y) \geq 0$. If an auction mechanism is DSIC and IR, a rational bidder with an obvious dominant strategy will play it (bidding truthfully). Moreover, an optimal auction mechanism is required to maximize the auctioneer's expected revenue $rev = \mathbb{E}_{(v, x, y)}\big[\sum_{i=1}^n p_i(v, x, y) \big]$.

Auction design. The ex-post regret $reg_i(v, x, y)$ for the bidder i is defined as $\max_{b_i' \in \mathcal{V}^m} u_i(v_i, (b_i', v_{-i}), x, y) - u_i(v_i, v, x, y)$. An auction mechanism (g, p) is DSIC, if and only if $\sum_{i=1}^n reg_i(v, x, y) = 0$ for any value profile $v \in \mathcal{V}^{n \times m}$, bidder-context $x \in \mathcal{X}^n$, and item-context $y \in \mathcal{Y}^m$. Suppose the payment rule p satisfy $p(b, x, y) \leq \sum_{j=1}^m g_{ij}(b, x, y)b_{ij}$. Then, the auction design can be modeled as a linear programming problem that maximizes the expected revenue $\mathbb{E}_{(v, x, y)}[\sum_{i=1}^n p_i(v, x, y)]$ subject to the expected ex-post regret $\mathbb{E}_{(v, x, y)}[\sum_{i=1}^n reg_i(v, x, y)] = 0$. Without loss of generality, the ex-post regret may refer to the sum of all bidders' ex-post regrets. We define the mechanism space as the space of all possible learned mechanisms and the permutation-equivariant mechanism space as the space of all possible learned permutation-equivairant mechanisms.

Equivariant mapping. We define a mapping f as *G-equivariant* if $\psi_g \circ f = f \circ \rho_g$ for two chosen group linear representations ρ and ψ and any g in group G. In particular, for identical permutation reresentations ρ and ψ, we define such f as permutation-equivariant. In this paper, we consider the bidder-permutation $\sigma_n \in S_n$ and item-permutation $\sigma_m \in S_m$. Specifically, we define a mapping f is bidder-symmetric or item-symmetric, if $f(\sigma_n x) = \sigma_n f(x)$ or $f(x \sigma_m) = f(x) \sigma_m$, respectively. Moreover, we call an auction mechanism (g, p) as bidder-symmetric or item-symmetric, if the allocation rule g and the payment rule p are both bidder-symmetric or item-symmetric.

Orbit averaging. For any feature mapping $f : \mathcal{F} \to \mathcal{G}$, the orbit averaging $\mathcal{Q}$ on f is defined as $\mathcal{Q}f = \frac{1}{|G|} \sum_{g \in G} \psi_g^{-1} \circ f \circ \rho_g$, where ρ and ψ are two chosen group representations acting on the feature spaces $\mathcal{F}$ and $\mathcal{G}$, respectively. Orbit averaging can project any mapping to be equivariant: $\mathcal{Q}$ is a projection to the space consisting of all equivariant mappings $\{f : \psi \circ f = f \circ \rho\}$, *i.e.*, $\psi_g \circ \mathcal{Q}f = \mathcal{Q}f \circ \rho_g$ for any $g \in G$ [13]. Moreover, $\mathcal{Q}u$ and $\mathcal{Q}reg$ refer to the utility and the ex-post regret induced by $\mathcal{Q}g$ and $\mathcal{Q}p$). For the simplicity, we denote the orbit averagings that modify the auction mechanism to be bidder-symmetric, item-symmetric, and bidder/item-symmetric by bidder averaging $\mathcal{Q}_1$, item averaging $\mathcal{Q}_2$, and bidder-item aggregated averaging $\mathcal{Q}_3$.

3   Theoretical Results

This section presents the theoretical results. We first prove that the permutation-equivariance induces a same expected revenue and a smaller expected ex-post regret in Section 3.1. Next in Section 3.2, we prove that the permutation-equivariant mechanism space has a smaller covering number, which promises a smaller required sample complexity and a better generalization. Detailed proofs are omitted from the main text and given in supplementary materials due to space limitation.

3.1   Benefits for Revenue and Ex-Post Regret

In this section, we discuss the benefits for the revenue and the ex-post regret in the conditions of bidder-symmetry and item-symmetry separately, and then discuss the benefits when both of them hold. Based on these results, we also study the learning process of non-permutation-equivariant neural networks for auction design.

3.1.1   Benefits in the Bidder/Item-Symmetry Condition

When the bidders come from the same distribution, the joint valuation distribution f is invariant under bidder-permutation, *i.e.* $f(\sigma_n v, \sigma_n x, y) = f(v, x, y)$ for any $\sigma_n \in S_n$. Meanwhile, when the items are indistinguishable, the joint distribution f is invariant under item-permutation, *i.e.*, $f(v\sigma_m, x, y\sigma_m) = f(v, x, y)$ for any $\sigma_m \in S_m$. Both conditions do not always hold simultaneously. In this section, we study them separately.

To measure the "non-permutation-equivariance" of the mechanism, we introduce the conception of *regret gap* between the projected mechanism and the original mechanism for as below,

$$\Delta_{\cdot}(g, p; v, x, y) = \max_{v' \in \mathcal{V}^{n \times m}} \sum_{i=1}^{n} u_i(v_i, (v'_i, v_{-i}), x, y) - \max_{v' \in \mathcal{V}^{n \times m}} \sum_{i=1}^{n} [\mathcal{Q}.u]_i(v_i, (v'_i, v_{-i}), x, y),$$

where v is the valuation profiles, v_i is valuation profile of bidder i, x is the bidder-context, y is the item-context, and the orbit averaging $\mathcal{Q}_{\cdot}$ can be the bidder averaging $\mathcal{Q}_1$ or the item averaging $\mathcal{Q}_2$.

The bidder averaging $\mathcal{Q}_1$ and the item averaging $\mathcal{Q}_2$ acting on the allocation rule g and the payment rule p, respectively, are as below,

$$\mathcal{Q}_1 g(v, x, y) = \frac{1}{n!} \sum_{\sigma_n \in S_n} \sigma_n^{-1} g(\sigma_n v, \sigma_n x, y), \quad \mathcal{Q}_1 p(v, x, y) = \frac{1}{n!} \sum_{\sigma_n \in S_n} \sigma_n^{-1} p(\sigma_n v, \sigma_n x, y),$$

$$\mathcal{Q}_2 g(v, x, y) = \frac{1}{m!} \sum_{\sigma_m \in S_m} g(v\sigma_m, x, y\sigma_m)\sigma_m^{-1}, \text{ and } \mathcal{Q}_2 p(v, x, y) = \frac{1}{m!} \sum_{\sigma_m \in S_m} p(v\sigma_m, x, y\sigma_m).$$

We thus can prove the following theorem that characterizes the benefits of permutation-equivariance for revenue and ex-post regret in the condition of bidder/item-symmetry.

Theorem 3.1 (Benefits for revenue and ex-post regret in the condition of bidder/item-symmetry)**.** *When the valuation distribution is invariant under permutations of bidders/items, the projected mechanism has the same expected revenue and a smaller expected ex-post regret, that is,*

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}.p]_i(v, x, y)\right] = \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}p_i(v, x, y)\right], \text{ and} \tag{1}$$

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}rgt_i(v, x, y)\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}.rgt]_i(v, x, y)\right] = \mathbb{E}_{(v,x,y)}\left[\Delta_{\cdot}(g, p; v, x, y)\right] \geq 0, \tag{2}$$

where p is the payment rule, reg is the ex-post regret, and $\mathcal{Q}_{\cdot}$ is the bidder/item averaging and can be $\mathcal{Q}_1$ or $\mathcal{Q}_2$.

Proof Sketch.

The proof of Theorem 3.1 have the following three steps. The first step is to prove the equation 1, and the second and third steps are to prove the inequality 2. We consider the two conditions at the same time and use $\mathcal{Q}$ to replace $\mathcal{Q}_1$ and $\mathcal{Q}_2$.

Step 1: We prove that the permutation-equivariance maintains the expected revenue, *i.e.*,

$$\mathbb{E}[\sum_{i=1}^{n}[\mathcal{Q}p]_i(v,x,y)] = \mathbb{E}[\sum_{i=1}^{n}p_i(v,x,y)].$$

By the definition of $\mathcal{Q}$, the left-hand side equals

$$(n!)^{-1}\sum_{i=1}^{n}\sum_{\sigma_n\in S_n}\mathbb{E}[p_i(\sigma_n v,\sigma_n x,y)] \ , or \ (m!)^{-1}\sum_{i=1}^{n}\sum_{\sigma_m\in S_m}\mathbb{E}[p_i(v\sigma_m,x,y\sigma_m)].$$

Notice that the distribution of (v,x,y) is invariant under bidder/item-permutation, and therefore for each σ_n and σ_m, we have

$$\mathbb{E}[p_i(\sigma_n v,\sigma_n x,y)] = \mathbb{E}[p_i(v\sigma_m,x,y\sigma_m)] = \mathbb{E}[p_i(v,x,y)].$$

The proof is finished.

Step 2: We prove that permutation-equivariance maintains the sum of all bidders' utilities, *i.e.*,

$$\mathbb{E}[\sum_{i=1}^{n}[\mathcal{Q}u]_i(v_i,v,x,y)] = \mathbb{E}[\sum_{i=1}^{n}u_i(v_i,v,x,y)].$$

The proof can be similar with that in Step 1 if we define $\tilde{u}$ as $\tilde{u}_i(v,x,y) = u_i(v_i,v,x,y)$. One can check that $[\mathcal{Q}u]_i(v_i,v,x,y) = \sum_{j=1}^{m}[\mathcal{Q}g]_{ij}(v,x,y)v_{ij} - [\mathcal{Q}p]_i(v,x,y) = [\mathcal{Q}\tilde{u}]_i(v,x,y)$ immediately. Then using $\tilde{u}_i$ to replace p_i, we can get the result.

Step 3: We prove that permutation-equivariance decreases the utility of the besting bidding:

$$\mathbb{E}\left[\max_{v'}\sum_{i=1}^{n}[\mathcal{Q}u]_i(v_i,(v_i',v_{-i}),x,y)\right] \leq \mathbb{E}\left[\max_{v'}\sum_{i=1}^{n}u(v_i,(v_i',v_{-i}),x,y)\right].$$

We use another definition $\overline{u}$ as $\overline{u}_i(v,x,y) = \max_{v_i'}u_i(v_i,(v_i',v_{-i}),x,y)$ for the proof easier to understand. Then the right-hand side becomes $\mathbb{E}[\sum_{i=1}^{n}\overline{u}_i(v,x,y)]$.

For bidder averaging $\mathcal{Q}_1$, the left-hand side becomes

$$\frac{1}{n!}\max_{v'}\sum_{\sigma_n\in S_n}\mathbb{E}\left[\sum_{i=1}^{n}u_{\sigma_n^{-1}(i)}(v_i,\sigma_n(v_i',v_{-i}),\sigma_n x,y)\right],$$

which is not larger than

$$(n!)^{-1}\sum_{\sigma_n\in S_n}\max_{v'}\mathbb{E}[\sum_{i=1}^{n}u_{\sigma_n^{-1}(i)}(v_i,\sigma_n(v_i',v_{-i}),\sigma_n x,y)].$$

It can be checked that the latter equals $(n!)^{-1}\sum_{\sigma_n\in S_n}\mathbb{E}[\sum_{i=1}^{n}\overline{u}_i(\sigma_n v,\sigma_n x,y)]$. According to the same process in Step 1, we know for each σ_n, $\mathbb{E}[\sum_{i=1}^{n}\overline{u}_i(\sigma_n v,\sigma_n x,y)] = \mathbb{E}[\sum_{i=1}^{n}\overline{u}_i(v,x,y)]$. The proof process is similar for $\mathcal{Q}_2$. Combining the results in Step 2 and in Step 3, we obtain the inequality 2.

A smaller expected ex-post regret implies this mechanism is closer to the *dominant strategy incentive compatible* condition. Conversely, and equivalently, when the expected ex-post regrets are fixed, the projected bidder-symmetric auction mechanism has a larger expected revenue. If there has already an auction mechanism, in the bidder/item-symmetry condition, we cen project it through the bidder/item averaging.

Remark 3.2. The mechanism space can be decompose into the direct sum of the permutation-equivariant mechanism space $\{\mathcal{M} : \mathcal{Q}\mathcal{M} = \mathcal{M}\}$ and the complementary space $\{\mathcal{N} : \mathcal{Q}\mathcal{N} = 0\}$ [13]. Thus, an mechanism $\mathcal{M}$ has an unique decomposition: $\mathcal{M} = \mathcal{Q}\mathcal{M} + \mathcal{N}$. The pure permutation-equivariant part $\mathcal{Q}\mathcal{M}$ contains all and only the "permutation-equivariance" of the mechanism $\mathcal{M}$. The pure non-permutation-equivariant part $\mathcal{N}$ is independent from the permutation-equivairance. In this way, we may study the influence of permutation-equivariance by comparing the mechanism $\mathcal{M}$ and its permutation equivariant part $\mathcal{Q}\mathcal{M}$.

3.1.2 Interplay between Bidder-Symmetry and Item-Symmetry.

If the valuation distribution is invariant under both bidder-permutation and item-permutation, we can project the mechanism to be permutation-equivariant with respect to both bidder and item in two steps (by mapping $\mathcal{Q}_1 \circ \mathcal{Q}_2$ or mapping $\mathcal{Q}_2 \circ \mathcal{Q}_1$). Consequently, the projected mechanism has the same expected revenue and a smaller expected ex-post regret. Equivalently, we can also project an auction mechanism to be bidder-symmetric and item-symmetric immediately by the bidder-item aggregated averaging $\mathcal{Q}_3$ as below,

$$\mathcal{Q}_3 g(v, x, y) = \frac{1}{n!m!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} \sigma_n^{-1} g(\sigma_n v \sigma_m, \sigma_n x, y \sigma_m) \sigma_m^{-1}, \text{ and}$$

$$\mathcal{Q}_3 p(v, x, y) = \frac{1}{n!m!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} \sigma_n^{-1} p(\sigma_n v \sigma_m, \sigma_n x, y \sigma_m).$$

We can prove that the bidder-item aggregated averaging $\mathcal{Q}_3$ is the composition of the orbit averaging operators $\mathcal{Q}_1$ and $\mathcal{Q}_2$, as shown in the following lemma. This lemma shows that the order of $\mathcal{Q}_1$ and $\mathcal{Q}_2$ would not influence their composition.

Lemma 3.3. *The bidder-item aggregated averaging is the composition of bidder averaging and item averaging:*

$$\mathcal{Q}_3 = \mathcal{Q}_1 \circ \mathcal{Q}_2 = \mathcal{Q}_2 \circ \mathcal{Q}_1.$$

Based on this lemma, we can prove the following theorem on the benefits of permutation-equivariance for revenue and ex-post regret in the condition of both bidder-symmetry and item-symmetry.

Theorem 3.4 (Benefits for revenue and ex-post regret in the condition of both bidder-symmetry and item-symmetry)**.** *When the valuation distribution is invariant under both item-permutation and item-permutation, then the projected mechanism has a same expected revenue and a smaller expected ex-post regret, that is,*

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} \mathcal{Q}_3 p_i(v, x, y)\right] = \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i(v, x, y)\right] \text{ and}$$

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} rgt_i(v, x, y)\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} [\mathcal{Q}_3 rgt]_i(v, x, y)\right] = \mathbb{E}_{(v,x,y)}\left[\Delta_3(g, p; v, x, y)\right] \geq 0,$$

where p is the payment rule, reg is the ex-post regret, and $\mathcal{Q}_3$ is the bidder-item aggregated averaging.

The difference between bidder-symmetry and item-symmetry is significant in practice. For example, for a symmetric valuation distribution, when the mechanism is already bidder-symmetric but not item-symmetric, we can project it to be item-symmetric to gain an extra benefit from item-symmetry. That means, the two regret gaps induced by $\mathcal{Q}_1$ and $\mathcal{Q}_2$ are "additive" as below,

$$\Delta_3(g, p; v, x, y) = \Delta_1(g, p; v, x, y) + \Delta_2(\mathcal{Q}_1 g, \mathcal{Q}_1 p; v, x, y).$$

In general,

$$\mathbb{E}[\Delta_2(g, p; v, x, y)] \neq \mathbb{E}[\Delta_2(\mathcal{Q}_1 g, \mathcal{Q}_1 p; v, x, y)]$$

and thus

$$\mathbb{E}[\Delta_3(g, p; v, x, y)] \neq \mathbb{E}[\Delta_1(g, p; v, x, y)] + \mathbb{E}[\Delta_2(g, p; v, x, y)].$$

That means, the benefits from bidder-symmetry and item-symmetry are "additive" but not "independent".

3.1.3 Insights on Training Non-Permutation-Equivariant Mechanism

Because the expected revenue is always same for the original mechanism and the projected permutation-equivariant mechanism, we only consider the gredient caused by the expected ex-post regret. We can decompose the original expected ex-post regret into the sum of the expected ex-post regret of the projected mechanism and the expectation of the regret gap as below,

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} rgt_i(v,x,y)\right] = \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_3 rgt]_i(v,x,y)\right] + \mathbb{E}_{(v,x,y)}\left[\Delta_3(g,p;v,x,y)\right].$$

The regret gap $\Delta_3(g,p;\cdot)$ follows from the "non-permutation-equivariance" of the mechanism $\mathcal{M}$. When the distance $l(\mathcal{M},\mathcal{QM})$ tends to 0, the regret gap converges to 0. When the auction mechanism has a negligible ex-post regret, the expectation of the regret gap is also close to 0. That means, the mechanism is closing to being permutation-equivariant. However, even using symmetric dataset or adopting data augmentation in training, the learned mechanism will not be permutation-equivariant in general [17]. As a result, to achieve negligible ex-post regret, the non-permutation-equivariant models need to learn more samples to approach permutation-equivariance. That is because the non-permutation-equivariant part (expected regret gap) would mislead the gradient of the expected regret but have no benefit to the expected revenue and the ex-post expected regret.

On the other hand, the regret gap can be viewed as a regularizer in the ex-post regret to penalize the "non-permutation-equivariance" of the mechanism. When the optimizer tries to minimize the ex-post regret, the auction mechanism approaches to be permutation-equivariant. Therefore, if the mechanism achieves a negligible ex-post regret, it is almost to be permutationn-equivariant. This result can explain why RegretNet struggles to find permutation-equivariant auction mechanisms [25]. However, in complex settings, it will be harder for non-permutation-equivariant models to approach the negligible ex-post regret. It can explain why the permutation-equivariant models show a significant improvement in complex setting, compared with that they have similar performances in simple settings [10], which shows the great importance of adopting permutation-equivariant models in complex settings.

3.2 Benefits for Generalization

In this section, we studies permutation-equivariance from the aspect of generalizability, which characterizes the performance gap of a learned mechanism on collected training data and unseen data.

We first study the covering number of the permutation-equivariant mechanism space. Let $\mathcal{Q}_1\mathcal{U} = \{\mathcal{Q}_1 u : u \in \mathcal{U}\}$ and $\mathcal{Q}_1\mathcal{P} = \{\mathcal{Q}_1 p : p \in \mathcal{P}\}$ be the spaces of all projected utilities and payment rules. We can obtain the following result, which indicates that the projected permutation-equivariant mechanism space has a smaller covering number.

Theorem 3.5 (Covering number of the permutation-equivariant mechanism space)**.** *The space of all projected bidder-symmetric mechanisms has smaller covering numbers, that is,*

$$\mathcal{N}_{\infty,1}(\mathcal{Q}_1\mathcal{U},r) \leq \mathcal{N}_{\infty,1}(\mathcal{U},r) \quad and \quad \mathcal{N}_{\infty,1}(\mathcal{Q}_1\mathcal{P},r) \leq \mathcal{N}_{\infty,1}(\mathcal{P},r).$$

The space of all projected item-symmetric mechanisms has smaller covering numbers, that is,

$$\mathcal{N}_{\infty,1}(\mathcal{Q}_2\mathcal{U},r) \leq \mathcal{N}_{\infty,1}(\mathcal{U},r) \quad and \quad \mathcal{N}_{\infty,1}(\mathcal{Q}_2\mathcal{P},r) \leq \mathcal{N}_{\infty,1}(\mathcal{P},r).$$

Intuitively, the orbit averaging $\mathcal{Q}$ narrows the distance between two mechanisms: $l(\mathcal{QM},\mathcal{QM}') \leq l(\mathcal{M},\mathcal{M}')$, for any two mechanisms. Then, any r-cover $r > 0$ $\mathcal{A}$ for space $\mathcal{U}$ or space $\mathcal{P}$ induces an r-cover $\mathcal{QA}$ for space $\mathcal{QU}$ or space $\mathcal{QP}$.

Combining with Lemma 3.3, we have the following results,

$$\mathcal{N}_{\infty,1}(\mathcal{Q}_3\mathcal{U},r) = \mathcal{N}_{\infty,1}(\mathcal{Q}_1\mathcal{Q}_2\mathcal{U},r) \leq \mathcal{N}_{\infty,1}(\mathcal{Q}_2\mathcal{U},r) \leq \mathcal{N}_{\infty,1}(\mathcal{U},r) \text{ and}$$
$$\mathcal{N}_{\infty,1}(\mathcal{Q}_3\mathcal{P},r) = \mathcal{N}_{\infty,1}(\mathcal{Q}_1\mathcal{Q}_2\mathcal{P},r) \leq \mathcal{N}_{\infty,1}(\mathcal{Q}_2\mathcal{P},r) \leq \mathcal{N}_{\infty,1}(\mathcal{P},r).$$

We then prove that two generalization bounds of permutation-equivariant mechanisms which characterize the gap between the expected revenue/ex-post regret and their empirical counterparts.

267 **Theorem 3.6** (Generalization bounds of permutation-equivariant mechanisms)**.** *If for any bidder, her*
268 *valuation satisfies that $v_i(S) \leq 1$ for any $S \subset [m]$, then with probability at least $1 - \delta$, we have the*
269 *following inequalities with $\epsilon = \sqrt{\frac{9n^2}{2L}(\log \frac{4}{\delta} + \max\{\log \mathcal{N}_{\infty,1}(\mathcal{P}, \frac{\epsilon}{3}), log\mathcal{N}_{\infty,1}(\mathcal{U}, \frac{\epsilon}{6})\})}$,*

$$\left| \mathbb{E}\left[\sum_{i=1}^{n} p_i^{\omega}(v, x, y) \right] - \frac{1}{L} \sum_{l=1}^{L} \sum_{i=1}^{n} p_i^{\omega}(v^{(l)}, x^{(l)}, y^{(l)}) \right| \leq \epsilon, \ \ and \tag{3}$$

$$\left| \mathbb{E}\left[\sum_{i=1}^{n} reg_i^{\omega}(v, x, y) \right] - \sum_{i=1}^{n} \widehat{reg}_i(\omega) \right| \leq \epsilon, \tag{4}$$

270 *where L is the number of samples, $\mathcal{U}$ and $\mathcal{P}$ are the spaces of all possible utilities and payment rules.*
271 *$\mathcal{N}_{\infty,1}(\mathcal{U}, r)$ and $\mathcal{N}_{\infty,1}(\mathcal{P}, r)$ are the minimum numbers of balls with radius r that can cover $\mathcal{U}$ and*
272 *$\mathcal{P}$ under $l_{\infty,1}$-distance, respectively.*

273 Equivalently, we can rewrite this result in the form of the sample complexity,

274 **Corollary 3.7.** *For any $\epsilon > 0$, $\delta \in (0, 1)$, and mechanism parameter ω, when the sample complexity*
275 *$L \geq \frac{9n^2}{2\epsilon^2}\Big(\log \frac{4}{\delta} + \max\Big\{ \log \mathcal{N}_{\infty,1}(\mathcal{P}, \frac{\epsilon}{3}), log\mathcal{N}_{\infty,1}(\mathcal{U}, \frac{\epsilon}{6}) \Big\} \Big)$, with probability at least $1 - \delta$, the*
276 *generalization bounds, eqs. (3) and (4), hold.*

277 **Remark 3.8.** Combining Theorem 3.5, we have proved that the permutation-equivariance can
278 improve the generalizability.

4 Experiments

280 This section presents our experimental results. More details and results are presented in the supple-
281 mentary materails. Code will be released publicly.

282 **Model architecture.** We project RegretNet [12] to the permutation-equivariant mechanism space
283 via orbit averaging: using bidder averaging for the bidder-symmetry condition, item averaging
284 for the item-symmetry condition, bidder-item aggregated averaging for the bidder-symmetry and
285 item-symmetry condition. Specifically, RegretNet is an auction mechanism defined as (g^{ω}, p^{ω}), in
286 which both of the allocation rule g^{ω} and the payment rule p^{ω} are neural networks that consist of three
287 fully-connected layers, and ω is the overall model parameter of the auction mechanism. The detailed
288 architecture is given in the supplementary materials.

289 **Auction settings.** We adopt two families of auction settings in our experiments: single-item auctions
290 and multi-item auctions. The optimal auction mechanism for any single-item auction is known
291 [20]. We thus compare our method with the optimal auction mechanisms in the single-item settings.
292 Besides, we employ a multivariate uniform distribution $U[0, 1]^m$ to model the bidder valuation
293 profiles. We sample 5,000 data points for training and 100 data batches of size 100 (totally 10,000
294 data points) for test in every setting.

295 **Model training.** We optimize the auction mechanism model via solving the following optimization
296 problem, following the standard settings [12, 25, 10],

$$\mathcal{L}_{\rho}(\omega, \lambda) = -\frac{1}{L} \sum_{l=1}^{L} \sum_{i=1}^{n} p_i^{\omega}(v^{(l)}, x^{(l)}, y^{(l)}) + \sum_{i=1}^{n} \lambda_i \widehat{reg}_i(\omega) + \frac{\rho}{2} \Big(\sum_{i=1}^{n} \widehat{reg}_i(\omega) \Big)^2,$$

297 where $\lambda \in \mathbb{R}^n$ is the Lagrange multiplier and $\rho > 0$ is the factor of the quadratic regularization term.
298 During the training process, the objective function $\mathcal{L}_{\rho}(\omega, \lambda)$ is minimized via Adam with learning
299 rate 0.001 with respect to the model parameter ω and the Largrange multiplier λ is updated via SGD
300 once in every 100 iterations, until the ex-post regret is smaller than 0.001. The regularization factor ρ
301 is is set to 1000 and 5 initially for single-item settings and multiple and gradually increased along the
302 training process. In calculating the best bid profile v_i' of every bidder i, we first randomly initialize
303 the bid profiles for 1,000 times, optimize each of them individually via Adam with the same settings,
304 and take the best one as the approximated best bidding.

Table 1: Experimental results. To simplify, we multiply all results by a factor of 10^5 for the regret and generalization error (GE).

Method	$2 \times 1\, Uniform$			$3 \times 1\, Uniform$			$5 \times 1\, Uniform$		
	Revenue	Regret	GE	Revenue	Regret	GE	Revenue	Regret	GE
Optimal	0.333	0	-	0.500	0	-	0.667	0	-
RegretNet	0.324	1.10	0.400	0.512	4.60	3.60	0.630	22.7	1.70
RegretNet-Test	0.324	0.600	-	0.512	3.20	-	0.630	12.8	-
RegretNet-PE	0.334	0.900	0.100	0.515	2.70	2.00	0.633	18.2	1.00

Method	$2 \times 2\, Uniform$			$2 \times 5\, Uniform$			$5 \times 3\, Uniform$		
	Revenue	Regret	GE	Revenue	Regret	GE	Revenue	Regret	GE
RegretNet	0.870	70.2	31.0	2.24	104	86.4	1.56	28.4	19.4
RegretNet-Test	0.870	53.8	-	2.24	74.0	-	1.56	8.60	-
RegretNet-PE	0.913	67.3	15.1	2.38	89.9	24.9	2.08	31.2	15.5

Evaluation. We leverage three metrics to evaluate the performance of the auction mechanism, which are: (1) the empirical revenue $\widehat{rev}$, (2) the empirical ex-post regret across all bidders, *i.e.*, $\sum_{i=1}^{n} \widehat{reg}_i$, and (3) the generalization error defined on top of regrets, *i.e.*, $GE = |\widehat{reg}_{test} - \widehat{reg}_{train}|$.

Computing resource. The experiments are conducted on 1 GPU (NVIDIA® Tesla® V100 16GB) and 10 CPU cores (Intel® Xeon® Processor E5-2650 v4 @ 2.20GHz).

Experimental results. We train an RegretNet and an RegretNet-PE on the training data. The well-trained RegretNet is then projected to be permutation-equivariant, denoted as "RegretNet-Test". The results are collected in Table 1. From the table, we observe that (1) RegretNet-PE records larger revenue than the theoretical optimal mechanism performance at the cost of a negligible ex-post regret in the single-item settings; (2) RegretNet-PE significantly improve the revenue while maintain or decrease the ex-post regret in the multi-item settings; (3) RegretNet-Test receives the same revenue with a significantly lower ex-post regret; and (4) RegretNet-PE narrows the generalization gaps between the training revenue/ex-post regret and their test counterparts. These results fully supports our theoretical findings.

5 Conclusion and future works

In this paper, under *additive valuation* and *symmetric valuation* setting, we study the benefits of permutation-equivariance in auction mechanisms in two aspects: a better performance and a better generalization. First, we prove a smaller expected ex-post regret and a same expected revenue when projecting an mechanism to be permutation-equivariant. Next, we propose the permutation-equivariant mechanism space has a smaller covering number, which promises the permutation-equivariant models a better generalization. Extensive experiments are conducted to verify our theoretical results. Our results help understand the optimal auction mechanisms' characterization and the learning processes' difference between non-equivariant models and equivaraint models.

Beyond the additive valuation setting, an interesting direction is to extend our results to other conditions, including the combinatorial and the unit-demand auctions. Meanwhile, the understanding of the difference in the aspect of the training process between non-equivariant models and equivariant models is still elusive.

Social impact. Our results can help understand and design optimal auction mechanisms for symmetric valuation distribution. As a result, our work could inspire more near-optimal auction mechanisms and promote economic growth. No potential negative social impact is identified.

References

[1] S. Alaei. Bayesian combinatorial auctions: Expanding single buyer mechanisms to many buyers. *The 16th Annual Symposium on Foundations of Computer Science*, 2011.

[2] S. Alaei, H. Fu, N. Haghpanah, and J. Hartline. The simple economics of approximately optimal auctions. *The 16th Annual Symposium on Foundations of Computer Science,*, 2013.

[3] M.-F. F. Balcan, T. Sandholm, and E. Vitercik. Sample complexity of automated mechanism design. *Neural Information Processing Systems (NeurIPS)*, 2016.

[4] L. Chen, L. Wang, and Y. Lan. Auction models with resource pooling in modern supply chain management. *Modern Supply Chain Research and Applications*, 2019.

[5] R. Cole and T. Roughgarden. The sample complexity of revenue maximization. In *ACM symposium on Theory of computing*, 2014.

[6] V. Conitzer and T. Sandholm. Complexity of mechanism design. *Proceedings of the Eighteenth Conference on Uncertainty in Artificial Intelligence (UAI)*, 2002.

[7] V. Conitzer and T. Sandholm. Self-interested automated mechanism design and implications for optimal combinatorial auctions. In *ACM Conference on Electronic Commerce*, 2004.

[8] M. Curry, P.-Y. Chiang, T. Goldstein, and J. Dickerson. Certifying strategyproof auction networks. *Neural Information Processing Systems (NeurIPS)*, 2020.

[9] C. Daskalakis, A. Deckelbaum, and C. Tzamos. Strong duality for a multiple-good monopolist. *Econometrica*, 2017.

[10] Z. Duan, J. Tang, Y. Yin, Z. Feng, X. Yan, M. Zaheer, and X. Deng. A context-integrated transformer-based neural network for auction design. *arXiv preprint arXiv:2201.12489*, 2022.

[11] S. Dughmi, L. Han, and N. Nisan. Sampling and representation complexity of revenue maximization. *Web and Internet Economic*, 2014.

[12] P. Dütting, Z. Feng, H. Narasimhan, D. Parkes, and S. S. Ravindranath. Optimal auctions through deep learning. In *International Conference on Machine Learning (ICML)*, 2019.

[13] B. Elesedy and S. Zaidi. Provably strict generalisation benefit for equivariant models. In *International Conference on Machine Learning (ICML)*, 2021.

[14] Z. Feng, H. Narasimhan, and D. C. Parkes. Deep learning for revenue-optimal auctions with budgets. In *the 17th International Conference on Autonomous Agents and Multiagent Systems*, 2018.

[15] J. Huang, Z. Han, M. Chiang, and H. V. Poor. Auction-based resource allocation for cooperative communications. *IEEE Journal on Selected Areas in Communications*, 2008.

[16] B. J. Jansen and T. Mullen. Sponsored search: an overview of the concept, history, and technology. *International Journal of Electronic Business*, 2008.

[17] C. Lyle, M. van der Wilk, M. Kwiatkowska, Y. Gal, and B. Bloem-Reddy. On the benefits of invariance in neural networks. *arXiv preprint arXiv:2005.00178*, 2020.

[18] A. M. Manelli and D. R. Vincent. Bundling as an optimal selling mechanism for a multiple-good monopolist. *Journal of Economic Theory*, 2006.

[19] M. Mohri and A. M. Medina. Learning theory and algorithms for revenue optimization in second-price auctions with reserve. *International Conference on Machine Learning (ICML)*, 2013.

[20] R. B. Myerson. Optimal auction design. *Mathematics of operations research*, 1981.

[21] H. Narasimhan and D. C. Parkes. A general statistical framework for designing strategy-proof assignment mechanisms. *Uncertainty in Artificial Intelligence (UAI)*, 2016.

[22] N. Nisan, T. Roughgarden, E. Tardos, and V. V. Vazirani. Algorithmic game theory. Cambridge University Press, 2007.

[23] G. Pavlov. Optimal mechanism for selling two goods. *The BE Journal of Theoretical Economics*, 2011.

[24] G. Popescu. An algorithmic characterization of multi-dimensional mechanisms. *Computing Reviews*, 2012.

[25] J. Rahme, S. Jelassi, J. Bruna, and S. M. Weinberg. A permutation-equivariant neural network architecture for auction design. *arXiv preprint arXiv:2003.01497*, 2020.

[26] T. Roughgarden. Twenty lectures on algorithmic game theory. *Cambridge Books*, 2016.

[27] T. Sandholm and A. Likhodedov. Automated design of revenue-maximizing combinatorial auctions. *Operations Research*, 2015.

[28] V. Syrgkanis. A sample complexity measure with applications to learning optimal auctions. *Neural Information Processing Systems (NeurIPS)*, 2017.