Benefits of Permutation-Equivariance in Auction Mechanisms

Abstract

Designing an incentive-compatible auction mechanism that maximizes the auctioneer's revenue while minimizes the bidders' ex-post regret is an important yet intricate problem in economics. Remarkable progresses have been achieved through learning the optimal auction mechanism by neural networks. In this paper, we consider the popular *additive valuation* and *symmetric valuation* setting; *i.e.*, the valuation for a set of items is defined as the sum of all items' valuations in the set, and the valuation distribution is invariant when the bidders and/or the items are permutated. We prove that permutation-equivariant neural networks have significant advantages: the permutation-equivariance decreases the expected ex-post regret, improves the model generalizability, while maintains the expected revenue invariant. This implies that the permutation-equivariance helps approach the theoretically optimal *dominant strategy incentive compatible* condition, and reduces the required sample complexity for desired generalization. Extensive experiments fully support our theory. To our best knowledge, this is the first work towards understanding the benefits of permutation-equivariance in auction mechanisms. Code will be released publicly.

1 Introduction

Optimal auction design [26] has wide applications in economics, including online advertising [16], resource allocation [15], and supply chain [4]. In an auction, every bidder has a private valuation profile over all items, and accordingly, submits her bid profile. An auctioneer collects the bids from all bidders, and determines a feasible item allocation to the bidders as well as the prices the bidders need to pay. Consequently, every bidder receives her utility. From the auctioneer's perspective, the optimal auction mechanism is required to maximize her *revenue*, defined as the sum of all bidders' payments. From the aspect of the bidders, the optimal auction mechanism needs to incentivize every bidder to bid according to their truthful valuation profiles (truthful bidding). This is summarized as the *dominant strategy incentive compatible* (DSIC) condition; *i.e.*, the truthful bidding is always the dominant strategy for every bidder [22].

The optimal auction mechanism can be approximated via neural networks [12, 25, 10]. The "approximation error", or the "distance" to the DSIC condition, is usually measured by the *ex-post regret*, defined as the gap between the bidder's utility of truthful bidding and the utility when her bid profile is only the best to herself (selfish bidding), while the bid profiles of all other bidders are fixed in both cases [12]. When a bidder's ex-post regret is always equal to 0, the truthful bidding is her dominant strategy. Therefore, the optimal auction design can be modeled as a linear programming problem, where the object is to maximize the expected revenue subject to the expected ex-post regret being

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

0 [12]. Another major consideration in learning the optimal mechanism is the generalizability to unseen data, usually measured by the *generalization bound*, *i.e.*, the upper bound of the gap between the expected revenue/ex-post regret and their empirical counterparts on the training data [12].

In this paper, we consider the popular setting of *additive valuation* and *symmetric valuation* [12, 25, 10]. The additive valuation condition defines the valuation for a set of items as the sum of the valuations for all items in this set. The symmetric valuation condition assumes the joint distribution of all bidders' valuation profiles to be invariant when bidders and/or items are permutated. This setting covers many applications in practice. For example, when items are independent, the additive valuation condition holds. Moreover, if the auction is anonymous or the order of the items is not prior-known, the symmetric valuation condition holds.

We demonstrate that permutation-equivariant models have significant advantages in learning the optimal auction mechanism as follows. **(1)** We prove that the permutation-equivariance in auction mechanisms decreases the expected ex-post regret while maintaining the expected revenue invariant. Conversely, and equivalently, the permutation-equivariance promises a larger expected revenue, when the expected ex-post regret is fixed. **(2)** We show that the permutation-equivariance of auction mechanisms reduces the required sample complexity for a desirable generalizability. We prove that the $l_{\infty,1}$-distance between any two mechanisms in the mechanism space decreases when they are projected to the permutation-equivariant mechanism (sub-)space. This smaller distance implies a smaller covering number of the permutation-equivariant mechanism space, which further leads to a small generalization bound [12].

We further provide an explanation for the learning process of non-permutation-equivariant neural networks (NPE-NNs). In learning the optimal auction mechanism by an NPE-NN, we show that an extra positive term exists in the quadratic penalty of the ex-post regret based on the result **(1)**. This term serves as a regularizer to penalize the "non-permutation-equivariance". Moreover, this regularizer also interferes the revenue maximization, and thus affects the learning performance of NPE-NNs. This further explains the advantages of permutation-equivariance in auction design.

Experiments in extensive auction settings are conducted to verify our theory. We design permutation-equivariant versions of RegretNet (RegretNet-test and RegretNet-PE) by projecting the RegretNet [12] to the permutation-equivariant mechanism space in the training and test stage. The empirical results show that permutation-equivariance helps: (1) significantly improve the revenue while maintain the same ex-post regret; (2) record the same revenue with a significantly lower ex-post regret; and (3) narrow the generalization gaps between the training ex-post regret and its test counterpart. These results fully support our theory.

Related works. Myerson completely solves the optimal auction design problem in one-item auctions [20]. However, solutions are not clear when the number of bidders/items exceeds one [12]. Initial attempts have been presented on the characterization of optimal auction mechanisms [18, 23, 9] and algorithmic solutions [1, 2, 24]. Remarkable advances have been made on the required sample complexity for learning the optimal auction mechanism in various settings, including single-item auctions [5, 19, 15], multi-item single-bidder auctions [11], combinatorial auctions [3, 29], and allocation mechanisms [21]. Machine learning-based auction design (automated auction design) have obtained considerable progresses [6, 7, 27]. The optimal auction design is modelled as a linear programming problem [6, 7]. However, early works suffer from the scalablility issues that the number of the constraints grows exponentially when the bidder number and the item numbers increase. To address this issue, recent works propose to learn the optimal auction mechanism by deep learning. RegretNet is designed for the multi-bidder and multi-item settings [12]. Then, RegretNet is developed to meet more restrictive constraints, such as the budget condition [14] and the cerifying strategyproof condition [8]. Rahme *et al.* [25] propose the first equivariant neural network-based auction mechanism design method with significant empirical advantages. Duan *et al.* [10] extend the applicable domain to contextual settings. Both works make remarkable contributions in designing new algorithms from the empirical aspect only. However, the theoretical foundations are still elusive. To our best knowledge, our paper is the first work on theoretically studying the benefits of permutation equivariance in auction design via deep learning.

2 Notations and Preliminaries

Auction. Suppose n bidders are bidding m items in an auction. Every bidder i has her bidder-context (feature) $x_i \in \mathcal{X}$, while every item j is associated with its item-context (feature) $y_j \in \mathcal{Y}$. The bidder i has a private valuation $v_{ij} \in \mathcal{V} \subset \mathbb{R}_{\geq 0}$ for the item j, which is sampled from a conditioned distribution $\mathbb{P}(\cdot | x_i, y_j)$. The value profile $v_i = (v_{i1}, \ldots, v_{im})$ is unknown to the auctioneer. For the simplicity, we define $x = (x_1^T, \ldots, x_n^T)^T$, $y = (y_1, \ldots, y_m)$, $v = (v_1^T, \ldots, v_n^T)^T$, $v_{-i} = (v_1^T, \ldots, v_{i-1}^T, v_{i+1}^T, \ldots, v_n^T)^T$, and $(v_i', v_{-i}) = (v_1^T, \ldots, (v_i')^T \ldots, v_n^T)^T$.

Every bidder submits a bid profile b_i to the auctioneer according to her valuation profile. Then, the auctioneer determines a feasible item allocation $g(b, x, y)$ and corresponding payments $p(b, x, y)$ as per an auction mechanism (g, p). Consequently, every bidder receives her utility $u_i(v_i, b, x, y) = \sum_{j=1}^m g_{ij}(b, x, y) \cdot v_{ij} - p_i(b, x, y)$. The auction mechanism (g, p) consists of an allocation rule $g : \mathbb{R}^{n \times m} \times \mathcal{X}^n \times \mathcal{Y}^m \to \mathbb{R}^{n \times m}$ and a payment rule $p : \mathbb{R}^{n \times m} \times \mathcal{X}^n \times \mathcal{Y}^m \to \mathbb{R}^{n \times m}$, where g_{ij} is the probability of allocating item j to the bidder i, and $p_i = \sum_{j=1}^m p_{ij}$ is the price that the bidder i should pay. To avoid allocating an item over once, the allocation rule is constrained such that $\sum_{i=1}^n g_{ij}(b, x, y) \leq 1$ for all $j \in [m]$. Every v_i in our notations can be replaced by b_i. Thus, we can define the similar notations: $b_{-i} = (b_1^T, \ldots, b_{i-1}^T, b_{i+1}^T, \ldots, b_n^T)^T$, $(b_i, v_{-i}) = (v_1^T, \ldots, (b_i)^T \ldots, v_n^T)^T$ and $(v_i, b_{-i}) = (b_1^T, \ldots, (v_i)^T \ldots, b_n^T)^T$.

Optimal auction mechanism. An auction mechanism (g, p) is defined to be *dominant strategy incentive compatible* (DSIC), if truthful bidding is always a dominant strategy of every bidder; *i.e.*, $u_i(v_i, (v_i, b_{-i}), x, y) \geq u_i(v_i, b, x, y)$ for all $i \in [n]$, $v, b \in \mathcal{V}^{n \times m}$, $x \in \mathcal{X}^n$ and $y \in \mathcal{Y}^m$. In addition, an auction mechanism (g, p) is called *individually rational* (IR), if for any bidder-contexts $x \in \mathcal{X}^n$, any item-contexts $y \in \mathcal{Y}^m$, and any bidder $i \in [n]$ $x \in \mathcal{X}^n$, valuation profile and bid profile $v, b \in \mathcal{V}^{n \times m}$, truthful bidding always leads to a non-negative utility; *i.e.*, $u_i(v_i, (v_i, b_{-i}), x, y) \geq 0$. If an auction mechanism is DSIC and IR, a rational bidder with an obvious dominant strategy will play it (bidding truthfully). Moreover, an optimal auction mechanism is required to maximize the auctioneer's expected revenue $rev = \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^n p_i(v, x, y)\right]$.

Auction design. The ex-post regret $reg_i(v, x, y)$ for the bidder i is defined as $\max_{b_i' \in \mathcal{V}^m} u_i(v_i, (b_i', v_{-i}), x, y) - u_i(v_i, v, x, y)$. An auction mechanism (g, p) is DSIC, if and only if $\sum_{i=1}^n reg_i(v, x, y) = 0$ for any value profile $v \in \mathcal{V}^{n \times m}$, bidder-context $x \in \mathcal{X}^n$, and item-context $y \in \mathcal{Y}^m$. Suppose the payment rule p satisfy $p_i(b, x, y) \leq \sum_{j=1}^m g_{ij}(b, x, y)b_{ij}$. Then, the auction design can be modeled as a linear programming problem that maximizes the expected revenue $\mathbb{E}_{(v,x,y)}[\sum_{i=1}^n p_i(v, x, y)]$ subject to the expected ex-post regret $\mathbb{E}_{(v,x,y)}[\sum_{i=1}^n reg_i(v, x, y)] = 0$. Without loss of generality, the ex-post regret may refer to the sum of all bidders' ex-post regrets.

Definition 2.1. Suppose the network's parameter is ω, and the bidder i's empirical payment and ex-post regret are defined as $\frac{1}{L}\sum_{l=1}^L p_i^\omega(v^{(l)}, x^{(l)}, y^{(l)})$, and $\widehat{reg}_i(\omega) = \frac{1}{L}\sum_{l=1}^L reg_i^\omega(v^{(l)}, x^{(l)}, y^{(l)})$, where the sample set $\{(v^{(l)}, x^{(l)}, y^{(l)})\}_{l=1}^L$ is *i.i.d.* sampled from the following prior distribution, $\mathbb{P}(v, x, y) = \prod_{i,j=1}^{n,m} \mathbb{P}(v_{ij}|x_i, y_j)\mathbb{P}_{X_i}(x_i)\mathbb{P}_{Y_j}(y_j)$.

Equivariant mapping. We define a mapping f as *G-equivariant* if $\psi_g \circ f = f \circ \rho_g$ for two chosen group linear representations ρ and ψ and any g in group G.

Definition 2.2. (Permutaion-Equivariant Mapping) A permutation-equivariant mapping is defined to be $f : \mathbb{R}^{n \times m} \to \mathbb{R}^{n \times m}$ that for any instance $x \in \mathbb{R}^{n \times m}$, and permutation matrices $\sigma_n \in \mathbb{R}^{n \times n}$ and $\sigma_m \in \mathbb{R}^{m \times m}$, we have $f(\sigma_n x \sigma_m) = \sigma_n f(x) \sigma_m$.

In this paper, we consider the bidder-permutation $\sigma_n \in \mathbb{R}^{n \times n}$ and item-permutation $\sigma_m \in \mathbb{R}^{m \times m}$. Specifically, we define a mapping f is bidder-symmetric or item-symmetric, if $f(\sigma_n x) = \sigma_n f(x)$ or $f(x\sigma_m) = f(x)\sigma_m$, respectively. Moreover, we define an auction mechanism (g, p) as bidder-symmetric or item-symmetric, if the allocation rule g and the payment rule p are both bidder-symmetric or item-symmetric.

Orbit averaging. For any feature mapping $f : \mathcal{F} \to \mathcal{G}$, the orbit averaging $\mathcal{Q}$ on f is defined as $\mathcal{Q}f = \frac{1}{|G|} \sum_{g \in G} \psi_g^{-1} \circ f \circ \rho_g$, where ρ and ψ are two chosen group representations acting on the feature spaces $\mathcal{F}$ and $\mathcal{G}$, respectively. Orbit averaging can project any mapping to be equivariant:

Proposition 2.3. *Orbit averaging $\mathcal{Q}$ is a projection to the equivariant mapping space $\{f : \psi \circ f = f \circ \rho\}$, i.e., $\psi \circ \mathcal{Q}f = \mathcal{Q}f \circ \rho$ and $\mathcal{Q}^2 = \mathcal{Q}$. In particular, if f is already equivariant, then $\mathcal{Q}f = f$.*

Moreover, $\mathcal{Q}u$ and $\mathcal{Q}reg$ refer to the utility and the ex-post regret induced by $\mathcal{Q}g$ and $\mathcal{Q}p$. For the simplicity, we denote the orbit averagings that modify the auction mechanism to be bidder-symmetric, item-symmetric, and bidder/item-symmetric by bidder averaging $\mathcal{Q}_1$, item averaging $\mathcal{Q}_2$, and bidder-item aggregated averaging $\mathcal{Q}_3$. The proof of the feasibility can be found in Appendix A.1.

Hypothesis complexity. The generalizatbility to unseen data is usually measured by the generalization bound, which depends on the hypothesis set's complexity. To characterize the complexity of the hypothesis set, we introduce the following definitions of *covering number* $\mathcal{N}_{\infty,1}$ and its corresponding distance $l_{\infty,1}$. Based on the covering number, we can obtain a generalization bound in Theorem 3.6.

Definition 2.4. ($l_{\infty,1}$-distance) Let $\mathcal{X}$ be a feature space and $\mathcal{F}$ a space of some functions from $\mathcal{X}$ to $\mathbb{R}^n$. The $l_{\infty,1}$-distance on the space $\mathcal{F}$ is defined as $l_{\infty,1}(f,g) = \max_{x \in \mathcal{X}}(\sum_{i=1}^n |f_i(x) - g_i(x)|)$.

Definition 2.5. (Covering number) Covering number $\mathcal{N}_{\infty,1}(\mathcal{F}, r)$ is the minimum number of balls with radius r that can cover $\mathcal{F}$ under $l_{\infty,1}$-distance.

3 Theoretical Results

This section presents the theoretical results. For simplicity, we view $p = (p_1, \ldots, p_n)^T$ as a $n \times 1$ matrix to present the prices the bidders should pay. We first prove that the permutation-equivariance induces a same expected revenue and a smaller expected ex-post regret in Section 3.1. Next in Section 3.2, we prove that the permutation-equivariant mechanism space has a smaller covering number, which promises a smaller required sample complexity and a better generalization. Detailed proofs are omitted from the main text and given in supplementary materials due to space limitation.

3.1 Benefits for Revenue and Ex-Post Regret

In this section, we discuss the benefits for the revenue and the ex-post regret in the conditions of bidder-symmetry and item-symmetry separately, and then discuss the benefits when both of them hold. Based on these results, we also study the learning process of non-permutation-equivariant neural networks for auction design.

3.1.1 Benefits in the Bidder/Item-Symmetry Condition

When the bidders come from the same distribution, the joint valuation distribution f is invariant under bidder-permutation, *i.e.* $f(\sigma_n v, \sigma_n x, y) = f(v, x, y)$ for any $\sigma_n \in S_n$. Meanwhile, when the items are indistinguishable, the joint distribution f is invariant under item-permutation, *i.e.*, $f(v\sigma_m, x, y\sigma_m) = f(v, x, y)$ for any $\sigma_m \in S_m$. Both conditions do not always hold simultaneously. In this section, we study them separately.

To measure the "non-permutation-equivariance" of the mechanism, we introduce the conception of *regret gap* between the projected mechanism and the original mechanism for as below,

$$\Delta.(g, p; v, x, y) = \max_{v' \in \mathcal{V}^{n \times m}} \sum_{i=1}^n u_i(v_i, (v_i', v_{-i}), x, y) - \max_{v' \in \mathcal{V}^{n \times m}} \sum_{i=1}^n [\mathcal{Q}.u]_i(v_i, (v_i', v_{-i}), x, y),$$

where v is the valuation profiles, v_i is valuation profile of bidder i, x is the bidder-context, y is the item-context, and the orbit averaging $\mathcal{Q}.$ can be the bidder averaging $\mathcal{Q}_1$ or the item averaging $\mathcal{Q}_2$.

The bidder averaging $\mathcal{Q}_1$ and the item averaging $\mathcal{Q}_2$ acting on the allocation rule g and the payment rule p, respectively, are as below,

$$\mathcal{Q}_1 g(v,x,y) = \frac{1}{n!} \sum_{\sigma_n \in S_n} \sigma_n^{-1} g(\sigma_n v, \sigma_n x, y), \quad \mathcal{Q}_1 p(v,x,y) = \frac{1}{n!} \sum_{\sigma_n \in S_n} \sigma_n^{-1} p(\sigma_n v, \sigma_n x, y),$$

$$\mathcal{Q}_2 g(v,x,y) = \frac{1}{m!} \sum_{\sigma_m \in S_m} g(v\sigma_m, x, y\sigma_m)\sigma_m^{-1}, \quad \text{and} \quad \mathcal{Q}_2 p(v,x,y) = \frac{1}{m!} \sum_{\sigma_m \in S_m} p(v\sigma_m, x, y\sigma_m).$$

We thus can prove the following theorem that characterizes the benefits of permutation-equivariance for revenue and ex-post regret in the condition of bidder/item-symmetry.

Theorem 3.1 (Benefits for revenue and ex-post regret in the condition of bidder/item-symmetry)**.**
When the valuation distribution is invariant under permutations of bidders/items, the projected mechanism has the same expected revenue and a smaller expected ex-post regret, that is,

$$\mathbb{E}_{(v,x,y)} \left[\sum_{i=1}^{n} [\mathcal{Q}.p]_i(v,x,y) \right] = \mathbb{E}_{(v,x,y)} \left[\sum_{i=1}^{n} p_i(v,x,y) \right], \quad \text{and} \tag{1}$$

$$\mathbb{E}_{(v,x,y)} \left[\sum_{i=1}^{n} reg_i(v,x,y) \right] - \mathbb{E}_{(v,x,y)} \left[\sum_{i=1}^{n} [\mathcal{Q}.reg]_i(v,x,y) \right] = \mathbb{E}_{(v,x,y)} \left[\Delta.(g,p;v,x,y) \right] \geq 0, \tag{2}$$

where p is the payment rule, reg is the ex-post regret, and $\mathcal{Q}.$ is the bidder/item averaging.

A smaller expected ex-post regret implies this mechanism is closer to the *dominant strategy incentive compatible* condition. Conversely, and equivalently, when the expected ex-post regrets are fixed, the projected auction mechanism has a larger expected revenue. For any auction mechanism, in the bidder/item-symmetry condition, we can project it through the bidder/item averaging.

Remark 3.2. The mechanism space can be decompose into the direct sum of the permutation-equivariant mechanism space $\{\mathcal{M} : \mathcal{QM} = \mathcal{M}\}$ and the complementary space $\{\mathcal{N} : \mathcal{QN} = 0\}$ [13]. Thus, an mechanism $\mathcal{M}$ has an unique decomposition: $\mathcal{M} = \mathcal{QM} + \mathcal{N}$. The pure permutation-equivariant part $\mathcal{QM}$ contains all and only the "permutation-equivariance" of the mechanism $\mathcal{M}$. The pure non-permutation-equivariant part $\mathcal{N}$ is independent from the permutation-equivairance. In this way, we may study the influence of permutation-equivariance by comparing the mechanism $\mathcal{M}$ and its permutation equivariant part $\mathcal{QM}$.

3.1.2 Interplay between Bidder-Symmetry and Item-Symmetry.

If the valuation distribution is invariant under both bidder-permutation and item-permutation, we can project the mechanism to be permutation-equivariant with respect to both bidder and item in two steps (by mapping $\mathcal{Q}_1 \circ \mathcal{Q}_2$ or mapping $\mathcal{Q}_2 \circ \mathcal{Q}_1$). Consequently, the projected mechanism has the same expected revenue and a smaller expected ex-post regret. Equivalently, we can also project an auction mechanism to be bidder-symmetric and item-symmetric immediately by the bidder-item aggregated averaging $\mathcal{Q}_3$ as below,

$$\mathcal{Q}_3 g(v,x,y) = \frac{1}{n!m!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} \sigma_n^{-1} g(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m)\sigma_m^{-1}, \quad \text{and}$$

$$\mathcal{Q}_3 p(v,x,y) = \frac{1}{n!m!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} \sigma_n^{-1} p(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m).$$

We can prove that the bidder-item aggregated averaging $\mathcal{Q}_3$ is the composition of the orbit averaging operators $\mathcal{Q}_1$ and $\mathcal{Q}_2$, as shown in the following lemma. This lemma shows that the order of $\mathcal{Q}_1$ and $\mathcal{Q}_2$ would not influence their composition.

Lemma 3.3. *The bidder-item aggregated averaging is the composition of bidder averaging and item averaging: $\mathcal{Q}_3 = \mathcal{Q}_1 \circ \mathcal{Q}_2 = \mathcal{Q}_2 \circ \mathcal{Q}_1$.*

Based on this lemma, we can prove the following theorem on the benefits of permutation-equivariance for revenue and ex-post regret in the condition of both bidder-symmetry and item-symmetry.

Theorem 3.4 (Benefits for revenue and ex-post regret in the condition of both bidder-symmetry and item-symmetry). *When the valuation distribution is invariant under both item-permutation and item-permutation, then the projected mechanism has a same expected revenue and a smaller expected ex-post regret, that is,*

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\mathcal{Q}_3 p_i(v,x,y)\right] = \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i(v,x,y)\right] \ and$$

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} reg_i(v,x,y)\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_3 reg]_i(v,x,y)\right] = \mathbb{E}_{(v,x,y)}\Big[\Delta_3(g,p;v,x,y)\Big] \geq 0,$$

where p is the payment rule, reg is the ex-post regret, and $\mathcal{Q}_3$ is the bidder-item aggregated averaging.

The difference between bidder-symmetry and item-symmetry is significant in practice. For example, for a symmetric valuation distribution, when the mechanism is already bidder-symmetric but not item-symmetric, we can project it to be item-symmetric to gain an extra benefit from item-symmetry. That means, the two regret gaps induced by $\mathcal{Q}_1$ and $\mathcal{Q}_2$ are "additive" as below,

$$\Delta_3(g,p;v,x,y) = \Delta_1(g,p;v,x,y) + \Delta_2(\mathcal{Q}_1 g, \mathcal{Q}_1 p; v,x,y).$$

In general, $\mathbb{E}[\Delta_2(g,p;v,x,y)] \neq \mathbb{E}[\Delta_2(\mathcal{Q}_1 g, \mathcal{Q}_1 p; v,x,y)]$ and thus $\mathbb{E}[\Delta_3(g,p;v,x,y)] \neq \mathbb{E}[\Delta_1(g,p;v,x,y)] + \mathbb{E}[\Delta_2(g,p;v,x,y)]$. That means, the benefits from bidder-symmetry and item-symmetry are "additive" but not "independent".

3.1.3 Insights on Training Non-Permutation-Equivariant Mechanism

Because the expected revenue is always same for the original mechanism and the projected permutation-equivariant mechanism, we only consider the gredient caused by the expected ex-post regret. We can decompose the original expected ex-post regret into the sum of the expected ex-post regret of the projected mechanism and the expectation of the regret gap as below,

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} reg_i(v,x,y)\right] = \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_3 reg]_i(v,x,y)\right] + \mathbb{E}_{(v,x,y)}\Big[\Delta_3(g,p;v,x,y)\Big].$$

The regret gap $\Delta_3(g,p;\cdot)$ follows from the "non-permutation-equivariance" of the mechanism $\mathcal{M}$. When the distance $l(\mathcal{M},\mathcal{QM})$ tends to 0, the regret gap converges to 0. When the auction mechanism has a negligible ex-post regret, the expectation of the regret gap is also close to 0. That means, the mechanism is closing to being permutation-equivariant. However, even using symmetric dataset or adopting data augmentation in training, the learned mechanism will not be permutation-equivariant in general [17]. As a result, to achieve negligible ex-post regret, the non-permutation-equivariant models need to learn more samples to approach permutation-equivariance. That is because the non-permutation-equivariant part (expected regret gap) would mislead the gradient of the expected regret but have no benefit to the expected revenue and the expected ex-post regret.

On the other hand, the regret gap can be viewed as a regularizer in the ex-post regret to penalize the "non-permutation-equivariance" of the mechanism. When the optimizer tries to minimize the ex-post regret, the auction mechanism approaches to be permutation-equivariant. Therefore, if the mechanism achieves a negligible ex-post regret, it is almost to be permutationn-equivariant. This result can explain why RegretNet struggles to find permutation-equivariant auction mechanisms [25]. However, in complex settings, it will be harder for non-permutation-equivariant models to approach the negligible ex-post regret. It can explain why the permutation-equivariant models show a significant improvement in complex setting, compared with that they have similar performances in simple settings [10], which shows the great importance of adopting permutation-equivariant models in complex settings.

3.2 Benefits for Generalization

In this section, we studies permutation-equivariance from the aspect of generalizability [28], which characterizes the performance gap of a learned mechanism on collected training data and unseen data.

We first study the covering number of the permutation-equivariant mechanism space. Let $\mathcal{U} = \{u^\omega : \omega \in \Omega\}$ and $\mathcal{P} = \{p^\omega : \omega \in \Omega\}$ be the sets of all possible utilities and payment rules, and $\mathcal{Q}.\mathcal{U} = \{\mathcal{Q}.u : u \in \mathcal{U}\}$ and $\mathcal{Q}.\mathcal{P} = \{\mathcal{Q}.p : p \in \mathcal{P}\}$ the spaces of all projected utilities and payment rules. In addition, let $\mathcal{N}_{\infty,1}(\mathcal{U}, r)$ and $\mathcal{N}_{\infty,1}(\mathcal{P}, r)$ be the minimum numbers of balls with radius r that can cover $\mathcal{U}$ and $\mathcal{P}$ under $l_{\infty,1}$-distance, respectively. We obtain the following result, which indicates the projected permutation-equivariant mechanism space has smaller covering numbers.

Theorem 3.5 (Covering number of the permutation-equivariant mechanism space). *The space of all projected bidder-symmetric mechanisms has smaller covering numbers, that is,*

$$\mathcal{N}_{\infty,1}(\mathcal{Q}_1\mathcal{U}, r) \leq \mathcal{N}_{\infty,1}(\mathcal{U}, r) \quad and \quad \mathcal{N}_{\infty,1}(\mathcal{Q}_1\mathcal{P}, r) \leq \mathcal{N}_{\infty,1}(\mathcal{P}, r).$$

The space of all projected item-symmetric mechanisms has smaller covering numbers, that is,

$$\mathcal{N}_{\infty,1}(\mathcal{Q}_2\mathcal{U}, r) \leq \mathcal{N}_{\infty,1}(\mathcal{U}, r) \quad and \quad \mathcal{N}_{\infty,1}(\mathcal{Q}_2\mathcal{P}, r) \leq \mathcal{N}_{\infty,1}(\mathcal{P}, r).$$

Intuitively, the orbit averaging $\mathcal{Q}$ narrows the distance between two mechanisms: $l(\mathcal{Q}\mathcal{M}, \mathcal{Q}\mathcal{M}') \leq l(\mathcal{M}, \mathcal{M}')$, for any two mechanisms. Then, any r-cover $r > 0$ $\mathcal{A}$ for space $\mathcal{U}$ or space $\mathcal{P}$ induces an r-cover $\mathcal{Q}\mathcal{A}$ for space $\mathcal{Q}\mathcal{U}$ or space $\mathcal{Q}\mathcal{P}$.

Combining with Lemma 3.3, we have the following results,

$$\mathcal{N}_{\infty,1}(\mathcal{Q}_3\mathcal{U}, r) = \mathcal{N}_{\infty,1}(\mathcal{Q}_1\mathcal{Q}_2\mathcal{U}, r) \leq \mathcal{N}_{\infty,1}(\mathcal{Q}_2\mathcal{U}, r) \leq \mathcal{N}_{\infty,1}(\mathcal{U}, r) \quad \text{and}$$
$$\mathcal{N}_{\infty,1}(\mathcal{Q}_3\mathcal{P}, r) = \mathcal{N}_{\infty,1}(\mathcal{Q}_1\mathcal{Q}_2\mathcal{P}, r) \leq \mathcal{N}_{\infty,1}(\mathcal{Q}_2\mathcal{P}, r) \leq \mathcal{N}_{\infty,1}(\mathcal{P}, r).$$

We then prove that two generalization bounds of permutation-equivariant mechanisms which characterize the gap between the expected revenue/ex-post regret and their empirical counterparts.

Theorem 3.6 (Generalization bounds of permutation-equivariant mechanisms). *If for any bidder, her valuation satisfies that $v_i(S) \leq 1$ for any $S \subset [m]$, then with probability at least $1 - \delta$, we have the following inequalities with $\epsilon \geq \sqrt{\frac{9n^2}{2L}(\log\frac{4}{\delta} + \max\{\log\mathcal{N}_{\infty,1}(\mathcal{P}, \frac{\epsilon}{3}), log\mathcal{N}_{\infty,1}(\mathcal{U}, \frac{\epsilon}{6})\})}$,*

$$\left| \mathbb{E}\left[\sum_{i=1}^n p_i^\omega(v, x, y) \right] - \frac{1}{L}\sum_{l=1}^L \sum_{i=1}^n p_i^\omega(v^{(l)}, x^{(l)}, y^{(l)}) \right| \leq \epsilon, \quad and \tag{3}$$

$$\left| \mathbb{E}\left[\sum_{i=1}^n reg_i^\omega(v, x, y) \right] - \sum_{i=1}^n \widehat{reg}_i(\omega) \right| \leq \epsilon, \tag{4}$$

where L is the number of samples, $\mathcal{U}$ and $\mathcal{P}$ are the spaces of all possible utilities and payment rules.

Equivalently, we can rewrite this result in the form of the sample complexity,

Corollary 3.7. *For any $\epsilon > 0$, $\delta \in (0, 1)$, and mechanism parameter ω, when the sample complexity $L \geq \frac{9n^2}{2\epsilon^2}\left(\log\frac{4}{\delta} + \max\left\{ \log\mathcal{N}_{\infty,1}(\mathcal{P}, \frac{\epsilon}{3}), log\mathcal{N}_{\infty,1}(\mathcal{U}, \frac{\epsilon}{6}) \right\} \right)$, with probability at least $1 - \delta$, the generalization bounds, eqs. (3) and (4), hold.*

Remark 3.8. Combining Theorem 3.5, we have proved that the permutation-equivariance can improve the generalizability.

4 Experiments

This section presents our experimental results. More details and results are presented in the supplementary materails. Code will be released publicly.

Model architecture. We project RegretNet [12] to the permutation-equivariant mechanism space via orbit averaging: (1) using bidder averaging for the bidder-symmetry condition, (2) applying item

Table 1: Experimental results. "$n \times m \, Uniform$" refers that there are n bidders and m items, and the valuations are i.i.d. drawn from the uniform distribution $U[0,1]$. To simplify, we multiply all results by a factor of 10^5 for the ex-post regret and generalization error (GE).

Method	$2 \times 1 \, Uniform$			$3 \times 1 \, Uniform$			$5 \times 1 \, Uniform$		
	Revenue	Regret	GE	Revenue	Regret	GE	Revenue	Regret	GE
Optimal	0.417	0	-	0.531	0	-	0.672	0	-
RegretNet	0.415	17.4	6.00	0.535	18.3	11.4	0.658	15.9	6.40
RegretNet-Test	0.415	16.3	-	0.535	13.3	-	0.658	6.50	-
RegretNet-PE	0.420	14.6	3.90	0.541	16.4	10.2	0.677	13.2	5.10
Method	$2 \times 2 \, Uniform$			$2 \times 5 \, Uniform$			$5 \times 3 \, Uniform$		
	Revenue	Regret	GE	Revenue	Regret	GE	Revenue	Regret	GE
RegretNet	0.870	70.2	31.0	2.24	104	86.4	1.56	28.4	19.4
RegretNet-Test	0.870	53.8	-	2.24	74.0	-	1.56	8.60	-
RegretNet-PE	0.913	67.3	15.1	2.38	89.9	24.9	1.85	20.1	11.8

Table 2: Experimental results. "$n \times m \, Uniform$" refers that there are n bidders and m items, and the valuations are i.i.d. sampled from the uniform distribution $U[0,1]$.

Method	$1 \times 2 \, Uniform$		$2 \times 2 \, Uniform$	
	Revenue	Regret	Revenue	Regret
RegretNet	0.549	0.00069	0.870	0.00070
EquivariantNet	0.551	0.00013	0.873	0.00100
RegretNet-Test	0.549	0.00062	0.870	0.00054
RegretNet-PE	0.643	0.00022	0.913	0.00067

averaging for the item-symmetry condition, and (3) employing bidder-item aggregated averaging for the bidder-symmetry and item-symmetry condition. The projected model is called RegretNet-PE. Specifically, RegretNet is an auction mechanism defined as (g^ω, p^ω), in which both of the allocation rule g^ω and the payment rule p^ω are neural networks that consist of three fully-connected layers, and ω is the overall model parameter of the auction mechanism. The detailed architecture is given in the supplementary materials.

Comparison with EquivariantNet. RegretNet uses two feed-forward full-connected networks to learn the allocation rule and payment rule, respectively. We denote the weight matrix in the layer ℓ as $W^{(\ell)}$. Both EquivariantNet and RegretNet-PE inherit the architecture of RegretNet (with some modifications), but utilize different approaches to realize the permutation-equivariance. EquivariantNet applies parameter-sharing in every layer during training, to constrain $W^{(\ell)}$ to be equivariant. In contrast, RegretNet-PE employs orbit averaging to be permutation-equivariant. Specifically, RegretNet-PE adopts a weight matrix $I_K \otimes W^{(\ell)} (\rho_{g_1}^T \ldots \rho_{g_K}^T)^T$ in the first layer, weight matrices $I_K \otimes W^{(\ell)}$ in the following layers, and multiples a matrix $(\rho_{g_1}^{-1}, \ldots, \rho_{g_K}^{-1})$ to the output layer, where K is the scale of the group $G = \{g_1, \ldots, g_K\}$, ρ_{g_k} represents the permutation operator on bidders and items, I_K is an identity matrix, and $\otimes$ is the Kronecker product.

Auction settings. We adopt two families of auction settings in our experiments: (1) single-item auctions, including two-bidder, three-bidder and five-bidder settings; and (2) multi-item auctions, including two-bidder and two-item, two-bidder and five-item, and five-bidder and three-item settings. The optimal auction mechanism for any single-item auction is known [20]. We thus compare our method with the optimal auction mechanisms in the single-item settings. Also, we compare RegretNet-PE and EquivariantNet in the one-bidder, two-item setting, and the two-bidder, two-item setting. Besides, we employ a multivariate uniform distribution $U[0,1]^m$ to model the bidder valuation

profiles. We sample 5,000 data points for training and 100 data batches of size 100 (totally 10,000 data points) for test in every setting.

Model training. We optimize the auction mechanism model via solving the following optimization problem, following the standard settings [12, 25, 10],

$$\mathcal{L}_\rho(\omega, \lambda) = -\frac{1}{L} \sum_{l=1}^{L} \sum_{i=1}^{n} p_i^\omega(v^{(l)}, x^{(l)}, y^{(l)}) + \sum_{i=1}^{n} \lambda_i \widehat{reg}_i(\omega) + \frac{\rho}{2} \Big(\sum_{i=1}^{n} \widehat{reg}_i(\omega) \Big)^2,$$

where $\lambda \in \mathbb{R}^n$ is the Lagrange multiplier and $\rho > 0$ is the factor of the quadratic regularization term. During the training process, the objective function $\mathcal{L}_\rho(\omega, \lambda)$ is minimized via Adam with learning rate 0.001 with respect to the model parameter ω and the Largrange multiplier λ is updated via SGD once in every 100 iterations, until the ex-post regret is smaller than 0.001. The regularization factor ρ is is set to 1000 and 5 initially for single-item settings and multiple and gradually increased along the training process. In calculating the best bid profile v_i' of every bidder i, we first randomly initialize the bid profiles for 1,000 times, optimize each of them individually via Adam with the same settings, and take the best one as the approximated best bidding.

Evaluation. We leverage three metrics to evaluate the performance of the auction mechanism, which are: (1) the empirical revenue $\widehat{rev}$, (2) the empirical ex-post regret across all bidders, *i.e.*, $\sum_{i=1}^{n} \widehat{reg}_i$, and (3) the generalization error defined on top of regrets, *i.e.*, $GE = |\widehat{reg}_{test} - \widehat{reg}_{train}|$.

Computing resource. The experiments are conducted on 1 GPU (NVIDIA® Tesla® V100 16GB) and 10 CPU cores (Intel® Xeon® Processor E5-2650 v4 @ 2.20GHz).

Experimental results. We train a RegretNet and a RegretNet-PE on the training data. The well-trained RegretNet is then projected to be permutation-equivariant, denoted as "RegretNet-Test". The results are collected in Tables 1 and 2.

From Tables 1 and 2, we observe that (1) compared to RegretNet, RegretNet-PE has a significantly higher revenue with a lower ex-post regret, and narrows the generalization gap between the training ex-post regret and its test counterpart; (2) compared to RegretNet, RegretNet-Test receives the same revenue with a significantly lower ex-post regret; and (3) under comparable ex-post regrets, RegretNet-PE has a considerably higher revenue than EquivariantNet, while all permutation-equivariant models (EquivariantNet, RegretNet-Test, and RegretNet-PE) can outperform RegretNet. These results show significant benefits of permutation-equivariance on revenue, ex-post regret, and generalizability, which fully supports our theoretical findings in Theorems 3.1, 3.4, and 3.5.

5   Conclusion and future works

In this paper, under *additive valuation* and *symmetric valuation* setting, we study the benefits of permutation-equivariance in auction mechanisms in two aspects: a better performance and a better generalization. First, we prove a smaller expected ex-post regret and a same expected revenue when projecting an mechanism to be permutation-equivariant. Next, we propose the permutation-equivariant mechanism space has a smaller covering number, which promises the permutation-equivariant models a better generalization. Extensive experiments are conducted to verify our theoretical results. Our results help understand the optimal auction mechanisms' characterization and the learning processes' difference between non-equivariant models and equivaraint models.

Beyond the additive valuation setting, an interesting direction is to extend our results to other conditions, including the combinatorial and the unit-demand auctions. Meanwhile, the understanding of the difference in the aspect of the training process between non-equivariant models and equivariant models is still elusive.

Social impact. Our results can help understand and design optimal auction mechanisms for symmetric valuation distribution. As a result, our work could inspire more near-optimal auction mechanisms and promote economic growth. No potential negative social impact is identified.

References

[1] S. Alaei. Bayesian combinatorial auctions: Expanding single buyer mechanisms to many buyers. *The 16th Annual Symposium on Foundations of Computer Science*, 2011.

[2] S. Alaei, H. Fu, N. Haghpanah, and J. Hartline. The simple economics of approximately optimal auctions. *The 16th Annual Symposium on Foundations of Computer Science,*, 2013.

[3] M.-F. F. Balcan, T. Sandholm, and E. Vitercik. Sample complexity of automated mechanism design. *Neural Information Processing Systems (NeurIPS)*, 2016.

[4] L. Chen, L. Wang, and Y. Lan. Auction models with resource pooling in modern supply chain management. *Modern Supply Chain Research and Applications*, 2019.

[5] R. Cole and T. Roughgarden. The sample complexity of revenue maximization. In *ACM symposium on Theory of computing*, 2014.

[6] V. Conitzer and T. Sandholm. Complexity of mechanism design. *Proceedings of the Eighteenth Conference on Uncertainty in Artificial Intelligence (UAI)*, 2002.

[7] V. Conitzer and T. Sandholm. Self-interested automated mechanism design and implications for optimal combinatorial auctions. In *ACM Conference on Electronic Commerce*, 2004.

[8] M. Curry, P.-Y. Chiang, T. Goldstein, and J. Dickerson. Certifying strategyproof auction networks. *Neural Information Processing Systems (NeurIPS)*, 2020.

[9] C. Daskalakis, A. Deckelbaum, and C. Tzamos. Strong duality for a multiple-good monopolist. *Econometrica*, 2017.

[10] Z. Duan, J. Tang, Y. Yin, Z. Feng, X. Yan, M. Zaheer, and X. Deng. A context-integrated transformer-based neural network for auction design. *arXiv preprint arXiv:2201.12489*, 2022.

[11] S. Dughmi, L. Han, and N. Nisan. Sampling and representation complexity of revenue maximization. *Web and Internet Economic*, 2014.

[12] P. Dütting, Z. Feng, H. Narasimhan, D. Parkes, and S. S. Ravindranath. Optimal auctions through deep learning. In *International Conference on Machine Learning (ICML)*, 2019.

[13] B. Elesedy and S. Zaidi. Provably strict generalisation benefit for equivariant models. In *International Conference on Machine Learning (ICML)*, 2021.

[14] Z. Feng, H. Narasimhan, and D. C. Parkes. Deep learning for revenue-optimal auctions with budgets. In *the 17th International Conference on Autonomous Agents and Multiagent Systems*, 2018.

[15] J. Huang, Z. Han, M. Chiang, and H. V. Poor. Auction-based resource allocation for cooperative communications. *IEEE Journal on Selected Areas in Communications*, 2008.

[16] B. J. Jansen and T. Mullen. Sponsored search: an overview of the concept, history, and technology. *International Journal of Electronic Business*, 2008.

[17] C. Lyle, M. van der Wilk, M. Kwiatkowska, Y. Gal, and B. Bloem-Reddy. On the benefits of invariance in neural networks. *arXiv preprint arXiv:2005.00178*, 2020.

[18] A. M. Manelli and D. R. Vincent. Bundling as an optimal selling mechanism for a multiple-good monopolist. *Journal of Economic Theory*, 2006.

[19] M. Mohri and A. M. Medina. Learning theory and algorithms for revenue optimization in second-price auctions with reserve. *International Conference on Machine Learning (ICML)*, 2013.

[20] R. B. Myerson. Optimal auction design. *Mathematics of operations research*, 1981.

[21] H. Narasimhan and D. C. Parkes. A general statistical framework for designing strategy-proof assignment mechanisms. *Uncertainty in Artificial Intelligence (UAI)*, 2016.

[22] N. Nisan, T. Roughgarden, E. Tardos, and V. V. Vazirani. Algorithmic game theory. Cambridge University Press, 2007.

[23] G. Pavlov. Optimal mechanism for selling two goods. *The BE Journal of Theoretical Economics*, 2011.

[24] G. Popescu. An algorithmic characterization of multi-dimensional mechanisms. *Computing Reviews*, 2012.

[25] J. Rahme, S. Jelassi, J. Bruna, and S. M. Weinberg. A permutation-equivariant neural network architecture for auction design. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2021.

[26] T. Roughgarden. Twenty lectures on algorithmic game theory. *Cambridge Books*, 2016.

[27] T. Sandholm and A. Likhodedov. Automated design of revenue-maximizing combinatorial auctions. *Operations Research*, 2015.

[28] A. Sannai, M. Imaizumi, and M. Kawano. Improved generalization bounds of group invariant/equivariant deep networks via quotient feature spaces. In *International Conference on Machine Learning (ICML)*, 2021.

[29] V. Syrgkanis. A sample complexity measure with applications to learning optimal auctions. *Neural Information Processing Systems (NeurIPS)*, 2017.

Supplementary Materials

The supplementary materials collect proofs and additional experimental details omitted from the main text due to the space limitation.

A   Proofs

This appendix collects all proofs omitted from the main text due to space limitation.

A.1   Proofs about Orbit Averaging

In this section, we prove Proposition 2.3 and the feasibility of the projected mechanisms.

Proof of Proposition 2.3.   By the definition of orbit averaging $\mathcal{Q}$, we have

$$\mathcal{Q}f \circ \rho_g(x) = \frac{1}{|G|} \sum_{h \in G} \psi_h^{-1} f(\rho_h \rho_g x) = \psi_g \circ \frac{1}{|G|} \sum_{h \in G} \psi_{hg}^{-1} f(\rho_{hg} x) = \psi_g \circ \mathcal{Q}f(x).$$

In addition, if f is equivariant, then we have

$$\mathcal{Q}f = \frac{1}{|G|} \sum_{g \in G} \psi_g^{-1} \circ f \circ \rho_g = \frac{1}{|G|} \sum_{g \in G} \psi_g^{-1} \circ \psi_g \circ f = \frac{1}{|G|} \sum_{g \in G} f = f.$$

Thus, orbit averaging is a projection to equivariant function space and fixes all equivariant functions.

Proof of the feasibility of projected mechanisms.   We verify all feasibility conditions for the projected mechanisms as follows.

Firstly, for the allocation rule, we have

$$\sum_{i=1}^{n} (\mathcal{Q}_1 g)_{ij}(v, x, y) = \frac{1}{n!} \sum_{i=1}^{n} \sum_{\sigma_n \in S_n} g_{\sigma_n^{-1}(i)j}(\sigma_n v, \sigma_n x, y)$$

$$= \frac{1}{n!} \sum_{\sigma_n \in S_n} \left[\sum_{i=1}^{n} g_{\sigma_n^{-1}(i)j}(\sigma_n v, \sigma_n x, y) \right] \leq \frac{1}{n!} \sum_{\sigma_n \in S_n} 1 = 1,$$

$$\sum_{i=1}^{n} (\mathcal{Q}_2 g)_{ij}(v, x, y) = \frac{1}{m!} \sum_{i=1}^{n} \sum_{\sigma_m \in S_m} g_{i\sigma_m^{-1}(j)}(v\sigma_m, x, y\sigma_m)$$

$$= \frac{1}{m!} \sum_{\sigma_m \in S_m} \left[\sum_{i=1}^{n} g_{i\sigma_m^{-1}(j)}(v\sigma_m, x, y\sigma_m) \right] \leq \frac{1}{m!} \sum_{\sigma_m \in S_m} 1 = 1,$$

and

$$\sum_{i=1}^{n} (\mathcal{Q}_3 g)_{ij}(v, x, y) = \frac{1}{n!m!} \sum_{i=1}^{n} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} g_{\sigma_n^{-1}(i)\sigma_m^{-1}(j)}(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m)$$

$$= \frac{1}{n!m!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} \left[\sum_{i=1}^{n} g_{\sigma_n^{-1}(i)\sigma_m^{-1}(j)}(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m) \right] \leq \frac{1}{n!m!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} 1 = 1,$$

thus we know the projected allocation rule is also feasible, which will never allocate one item more than twice.

In addition, for the payment rule, we have

$$(\mathcal{Q}_1 p)_i(v, x, y) = \frac{1}{n!} \sum_{\sigma_n \in S_n} p_{\sigma_n^{-1}(i)}(\sigma_n v, \sigma_n x, y)$$

$$\leq \frac{1}{n!} \sum_{\sigma_n \in S_n} \left[\sum_{j=1}^{m} g_{\sigma_n^{-1}(i)j}(\sigma_n v, \sigma_n x, y)(\sigma_n v)_{\sigma_n^{-1}(i)j} \right]$$

$$= \sum_{j=1}^{m} \left[\frac{1}{n!} \sum_{\sigma_n \in S_n} g_{\sigma_n^{-1}(i)j}(\sigma_n v, \sigma_n x, y) v_{ij} \right] \leq \sum_{j=1}^{m} (\mathcal{Q}_1 g)_{ij} v_{ij},$$

$$(\mathcal{Q}_2 p)_i(v, x, y) = \frac{1}{m!} \sum_{\sigma_m \in S_m} p_i(v\sigma_m, x, y\sigma_m)$$

$$\leq \frac{1}{m!} \sum_{\sigma_m \in S_m} \left[\sum_{j=1}^{m} g_{ij}(v\sigma_m, x, y\sigma_m)(v\sigma_m)_{ij} \right]$$

$$= \sum_{j=1}^{m} \left[\frac{1}{m!} \sum_{\sigma_m \in S_m} g_{i\sigma_m^{-1}(j)}(v\sigma_m, x, y\sigma_m) v_{ij} \right] \leq \sum_{j=1}^{m} (\mathcal{Q}_2 g)_{ij} v_{ij},$$

and

$$(\mathcal{Q}_3 p)_i(v, x, y) = \frac{1}{n!m!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} p_{\sigma_n^{-1}(i)}(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m)$$

$$\leq \frac{1}{n!m!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} \left[\sum_{j=1}^{m} g_{\sigma_n^{-1}(i)j}(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m)(\sigma_n v\sigma_m)_{\sigma_n^{-1}(i)j} \right]$$

$$= \sum_{j=1}^{m} \left[\frac{1}{n!m!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} g_{\sigma_n^{-1}(i)\sigma_m^{-1}(j)}(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m) v_{ij} \right] \leq \sum_{j=1}^{m} (\mathcal{Q}_3 g)_{ij} v_{ij},$$

thus, we have completed this proof.

If f is an equivariant function, then $\mathcal{Q}f = f$. That means, every equivariant function can be obtained by orbit averaging. In this sense, every equivariant models are contained in the orbit averaging framework.

A.2 Proof of Theorem 3.1

In this section, we proves Theorem 3.1.

Proof of Theorem 3.1. We first study the part in the condition of bidder-symmetry; *i.e.*, the orbit averaging $\mathcal{Q}.$ is the bidder averaging $\mathcal{Q}_1$, acting on the allocation rule g and the payment rule p as below,

$$\mathcal{Q}_1 g(v, x, y) = \frac{1}{n!} \sum_{\sigma_n \in S_n} \sigma_n^{-1} g(\sigma_n v, \sigma_n x, y),$$

and

$$\mathcal{Q}_1 p(v, x, y) = \frac{1}{n!} \sum_{\sigma_n \in S_n} \sigma_n^{-1} p(\sigma_n v, \sigma_n x, y).$$

Step 1: We first prove that the auction mechanism has the same expected revenue after projection, *i.e.*,

$$\mathbb{E}_{(v,x,y)} \left[\sum_{i=1}^{n} [\mathcal{Q}_1 p]_i(v, x, y) \right] = \mathbb{E}_{(v,x,y)} \left[\sum_{i=1}^{n} p_i(v, x, y) \right].$$

Given that for all permutation π,

$$\sum_{i=1}^{n} p_i = \sum_{i=1}^{n} p_{\pi(i)},$$

we have the following equation,

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} \mathcal{Q}_1 p_i(v, x, y)\right] = \mathbb{E}_{(v,x,y)}\left[\frac{1}{n!}\sum_{i=1}^{n}\sum_{\sigma_n \in S_n} p_{\sigma_n^{-1}(i)}(\sigma_n v, \sigma_n x, y)\right]$$

$$= \mathbb{E}_{(v,x,y)}\left[\frac{1}{n!}\sum_{i=1}^{n}\sum_{\sigma_n \in S_n} p_i(\sigma_n v, \sigma_n x, y)\right] = \frac{1}{n!}\sum_{i=1}^{n}\sum_{\sigma_n \in S_n}\mathbb{E}_{(v,x,y)}\left[p_i(\sigma_n v, \sigma_n x, y)\right]$$

$$= \frac{1}{n!}\sum_{i=1}^{n}\sum_{\sigma_n \in S_n}\mathbb{E}_{(v,x,y)}\left[p_i(v, x, y)\right] = \sum_{i=1}^{n}\mathbb{E}_{(v,x,y)}\left[p_i(v, x, y)\right].$$

Thus, we complete the first step.

Step 2: We then prove that the sum of all bidders' utilities remains the same after projection, *i.e.*,

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_1 u]_i(v_i, v, x, y)\right] = \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} u_i(v_i, v, x, y)\right].$$

Given that

$$\sum_{i=1}^{n} g_{\pi(i)j} v_{\pi(i)j} = \sum_{i=1}^{n} g_{ij} v_{ij},$$

we have the following equation,

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_1 u]_i(v_i, v, x, y)\right]$$

$$= \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\left[\sum_{j=1}^{m}[\mathcal{Q}_1 g]_{ij}(v, x, y)v_{ij} - [\mathcal{Q}_1 p]_i(v, x, y)\right]\right]$$

$$= \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\sum_{j=1}^{m}[\mathcal{Q}_1 g]_{ij}(v, x, y)v_{ij}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i(v, x, y)\right]$$

$$= \mathbb{E}_{(v,x,y)}\left[\frac{1}{n!}\sum_{i=1}^{n}\sum_{j=1}^{m}\sum_{\sigma_n \in S_n} g_{\sigma_n^{-1}(i)j}(\sigma_n v, \sigma_n x, y)v_{ij}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i(v, x, y)\right]$$

$$= \frac{1}{n!}\sum_{\sigma_n \in S_n}\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\sum_{j=1}^{m} g_{\sigma_n^{-1}(i)j}(\sigma_n v, \sigma_n x, y)[\sigma_n v]_{\sigma_n^{-1}(i)j}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i(v, x, y)\right]$$

$$= \frac{1}{n!}\sum_{\sigma_n \in S_n}\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\sum_{j=1}^{m} g_{ij}(\sigma_n v, \sigma_n x, y)[\sigma_n v]_{ij}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i(v, x, y)\right]$$

$$= \frac{1}{n!}\sum_{\sigma_n \in S_n}\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\sum_{j=1}^{m} g_{ij}(v, x, y)v_{ij}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i(v, x, y)\right]$$

$$= \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\sum_{j=1}^{m} g_{ij}(v, x, y)v_{ij}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i(v, x, y)\right]$$

$$= \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n} u_i(v_i, v, x, y)\right].$$

Thus, we have completed the second step.

Step 3: We lastly prove that the auction mechanism has a smaller ex-post regret after projection, *i.e.*,

$$\mathbb{E}\left[\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}[\mathcal{Q}_1 u]_i(v_i,(v_i',v_{-i}),x,y)\right]\leq\mathbb{E}\left[\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}u(v_i,(v_i',v_{-i}),x,y)\right].$$

For the simplicity, we denote $\sum_{j=1}^{m}g_{ij}v_{ij}$ by $\langle g_i,v_i\rangle$. Then, we have,

$$\mathbb{E}_{(v,x,y)}\left[\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}[\mathcal{Q}_1 u]_i\big(v_i,(v_i',v_{-i}),x,y\big)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}\sum_{j=1}^{m}[\mathcal{Q}_1 g]_{ij}\big((v_i',v_{-i}),x,y\big)v_{ij}-[\mathcal{Q}_1 p]_i\big((v_i',v_{-i}),x,y\big)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}\big\langle[\mathcal{Q}_1 g]_i\big((v_i',v_{-i}),x,y\big),v_i\big\rangle-[\mathcal{Q}_1 p]_i\big((v_i',v_{-i}),x,y\big)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}\frac{1}{n!}\sum_{\sigma_n\in S_n}\big\langle g_{\sigma_n^{-1}(i)}\big(\sigma_n(v_i',v_{-i}),\sigma_n x,y\big),v_i\big\rangle-p_{\sigma_n^{-1}(i)}\big(\sigma_n(v_i',v_{-i}),\sigma_n x,y\big)\right].$$

Combining the following inequality,

$$\max_{z}\sum_{k=1}^{K}f_k(z)\leq\sum_{k=1}^{K}\max_{z}f_k(z),$$

we have that

$$\mathbb{E}_{(v,x,y)}\left[\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}\frac{1}{n!}\sum_{\sigma_n\in S_n}\big\langle g_{\sigma_n^{-1}(i)}\big(\sigma_n(v_i',v_{-i}),\sigma_n x,y\big),v_i\big\rangle-p_{\sigma_n^{-1}(i)}\big(\sigma_n(v_i',v_{-i}),\sigma_n x,y\big)\right]$$

$$\leq\mathbb{E}_{(v,x,y)}\left[\frac{1}{n!}\sum_{\sigma_n\in S_n}\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}\big\langle g_{\sigma_n^{-1}(i)}\big(\sigma_n(v_i',v_{-i}),\sigma_n x,y\big),v_i\big\rangle-p_{\sigma_n^{-1}(i)}\big(\sigma_n(v_i',v_{-i}),\sigma_n x,y\big)\right]$$

$$=\frac{1}{n!}\sum_{\sigma_n\in S_n}\mathbb{E}_{(v,x,y)}\left[\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}\big\langle g_{\sigma_n^{-1}(i)}\big(\sigma_n(v_i',v_{-i}),\sigma_n x,y\big),v_i\big\rangle-p_{\sigma_n^{-1}(i)}\big(\sigma_n(v_i',v_{-i}),\sigma_n x,y\big)\right]$$

$$=\frac{1}{n!}\sum_{\sigma_n\in S_n}\mathbb{E}_{(v,x,y)}\left[\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}u_i\big(v_i,(v_i',v_{-i}),x,y\big)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\max_{v'\in\mathcal{V}^{n\times m}}\sum_{i=1}^{n}u_i\big(v_i,(v_i',v_{-i}),x,y\big)\right].$$

We thus have completed the proof of eqs. (1) and (2) when the orbit averaging $\mathcal{Q}$. is the condition of bidder-symmetry.

Then, we prove this theorem in the condition of item-symmetry; *i.e.*, the orbit averaging $\mathcal{Q}$. is the item averaging $\mathcal{Q}_2$, acting on the allocation rule g and the payment rule p as shown below,

$$\mathcal{Q}_2 g(v,x,y)=\frac{1}{m!}\sum_{\sigma_m\in S_m}g(v\sigma_m,x,y\sigma_m)\sigma_m^{-1},$$

and,

$$\mathcal{Q}_2 p(v,x,y)=\frac{1}{m!}\sum_{\sigma_m\in S_m}p(v\sigma_m,x,y\sigma_m).$$

Step 1: We first prove that the auction mechanism has the same expected revenue after projection, *i.e.*,

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_2 p]_i(v,x,y)\right] = \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}p_i(v,x,y)\right].$$

Notice that

$$\mathbb{E}_{(v,x,y)}[f(v\sigma_m, x, y\sigma_m)] = \mathbb{E}_{(v,x,y)}[f(v,x,y)].$$

Then, we have

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_2 p]_i(v,x,y)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\frac{1}{m!}\sum_{i=1}^{n}\sum_{\sigma_m\in S_m}p_i(v\sigma_m, x, y\sigma_m)\right]$$

$$=\frac{1}{m!}\sum_{i=1}^{n}\sum_{\sigma_m\in S_m}\mathbb{E}_{(v,x,y)}\left[p_i(v\sigma_m, x, y\sigma_m)\right]$$

$$=\frac{1}{m!}\sum_{i=1}^{n}\sum_{\sigma_m\in S_m}\mathbb{E}_{(v,x,y)}\left[p_i(v,x,y)\right] = \sum_{i=1}^{n}\mathbb{E}_{(v,x,y)}\left[p_i(v,x,y)\right].$$

We have thus completed the first step.

Step 2: We then prove that the sum of all bidders' utilities remains same after projection, *i.e.*,

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_2 u]_i(v_i, v, x, y)\right] = \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}u_i(v_i, v, x, y)\right].$$

Given that for all permutation π,

$$\sum_{j=1}^{m}g_{i\pi(j)}v_{i\pi(j)} = \sum_{j=1}^{m}g_{ij}v_{ij},$$

we have the following equation,

$$\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_2 u]_i(v_i, v, x, y)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\left[\sum_{j=1}^{m}[\mathcal{Q}_2 g]_{ij}(v, x, y)v_{ij} - [\mathcal{Q}_2 p]_i(v, x, y)\right]\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\sum_{j=1}^{m}[\mathcal{Q}_2 g]_{ij}(v, x, y)v_{ij}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}p_i(v, x, y)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\frac{1}{m!}\sum_{i=1}^{n}\sum_{j=1}^{m}\sum_{\sigma_m \in S_m}g_{i\sigma_m^{-1}(j)}(v\sigma_m, x, y\sigma_m)v_{ij}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}p_i(v, x, y)\right]$$

$$=\frac{1}{m!}\sum_{\sigma_m \in S_m}\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\sum_{j=1}^{m}g_{i\sigma_m^{-1}(j)}(v\sigma_m, x, y\sigma_m)[v\sigma_m]_{i\sigma_m^{-1}(j)}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}p_i(v, x, y)\right]$$

$$=\frac{1}{m!}\sum_{\sigma_m \in S_m}\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\sum_{j=1}^{m}g_{ij}(v\sigma_m, x, y\sigma_m)[v\sigma_m]_{ij}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}p_i(v, x, y)\right]$$

$$=\frac{1}{m!}\sum_{\sigma_m \in S_m}\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\sum_{j=1}^{m}g_{ij}(v, x, y)v_{ij}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}p_i(v, x, y)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}\sum_{j=1}^{m}g_{ij}(v, x, y)v_{ij}\right] - \mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}p_i(v, x, y)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\sum_{i=1}^{n}u_i(v_i, v, x, y)\right].$$

Thus, we have completed the second step.

Step 3: We lastly prove that the auction mechanism have a smaller ex-post regret after projection, *i.e.*,

$$\mathbb{E}\left[\max_{v' \in \mathcal{V}^{n \times m}}\sum_{i=1}^{n}[\mathcal{Q}_2 u]_i(v_i, (v_i', v_{-i}), x, y)\right] \leq \mathbb{E}\left[\max_{v' \in \mathcal{V}^{n \times m}}\sum_{i=1}^{n}u(v_i, (v_i', v_{-i}), x, y)\right].$$

By the definition of the utility u and the item averaging $\mathcal{Q}_2$, we have

$$\mathbb{E}_{(v,x,y)}\left[\max_{v' \in \mathcal{V}^{n \times m}}\sum_{i=1}^{n}[\mathcal{Q}_2 u]_i\big(v_i, (v_i', v_{-i}), x, y\big)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\max_{v' \in \mathcal{V}^{n \times m}}\sum_{i=1}^{n}\sum_{j=1}^{m}[\mathcal{Q}_2 g]_{ij}\big((v_i', v_{-i}), x, y\big)v_{ij} - [\mathcal{Q}_2 p]_i\big((v_i', v_{-i}), x, y\big)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\max_{v' \in \mathcal{V}^{n \times m}}\sum_{i=1}^{n}\big\langle[\mathcal{Q}_2 g]_i\big((v_i', v_{-i}), x, y\big), v_i\big\rangle - [\mathcal{Q}_2 p]_i\big((v_i', v_{-i}), x, y\big)\right]$$

$$=\mathbb{E}_{(v,x,y)}\left[\max_{v' \in \mathcal{V}^{n \times m}}\sum_{i=1}^{n}\frac{1}{m!}\sum_{\sigma_m \in S_m}\big\langle g_i\big((v_i', v_{-i})\sigma_m, x, y\sigma_m\big)\sigma_m^{-1}, v_i\big\rangle - p_i\big((v_i', v_{-i})\sigma_m, x, y\sigma_m\big)\right].$$

Combining the following inequality

$$\max_{z}\sum_{k=1}^{K}f_k(z) \leq \sum_{k=1}^{K}\max_{z}f_k(z),$$

520 we have

$$
\mathbb{E}_{(v,x,y)} \left[\max_{v' \in \mathcal{V}^{n \times m}} \sum_{i=1}^{n} \frac{1}{m!} \sum_{\sigma_m \in S_m} \left\langle g_i\big((v_i', v_{-i})\sigma_m, x, y\sigma_m\big)\sigma_m^{-1}, v_i \right\rangle - p_i\big((v_i', v_{-i})\sigma_m, x, y\sigma_m\big) \right]
$$

$$
\leq \mathbb{E}_{(v,x,y)} \left[\frac{1}{m!} \sum_{\sigma_m \in S_m} \sum_{i=1}^{n} \max_{v' \in \mathcal{V}^{n \times m}} \left\langle g_i\big((v_i', v_{-i})\sigma_m, x, y\sigma_m\big)\sigma_m^{-1}, v_i \right\rangle - p_i\big((v_i', v_{-i})\sigma_m, x, y\sigma_m\big) \right]
$$

$$
= \frac{1}{m!} \sum_{\sigma_m \in S_m} \mathbb{E}_{(v,x,y)} \left[\max_{v' \in \mathcal{V}^{n \times m}} \sum_{i=1}^{n} \left\langle g_i\big((v_i', v_{-i})\sigma_m, x, y\sigma_m\big), v_i\sigma_m \right\rangle - p_i\big((v_i', v_{-i})\sigma_m, x, y\sigma_m\big) \right]
$$

$$
= \frac{1}{m!} \sum_{\sigma_m \in S_m} \mathbb{E}_{(v,x,y)} \left[\max_{v' \in \mathcal{V}^{n \times m}} \sum_{i=1}^{n} u_i\big(v_i, (v_i', v_{-i}), x, y\big) \right]
$$

$$
= \mathbb{E}_{(v,x,y)} \left[\max_{v' \in \mathcal{V}^{n \times m}} \sum_{i=1}^{n} u_i\big(v_i, (v_i', v_{-i}), x, y\big) \right].
$$

521 We thus have proved this theorem in the condition of item-symmetry.

522 The proofs are completed. □

A.3 Proof of Lemma 3.3

524 In this section, we present the proof of Lemma 3.3.

525 *Proof of Lemma 3.3.* Both the bidder averaging and the item averaging are linear. Thus, we have the
526 following results,

$$
\mathcal{Q}_1 \circ \mathcal{Q}_2 f(v, x, y)
$$

$$
= \mathcal{Q}_1 \left[\frac{1}{m!} \sum_{\sigma_m \in S_m} f(v\sigma_m, x, y\sigma_m)\sigma_m^{-1} \right]
$$

$$
= \frac{1}{n!} \sum_{\sigma_n \in S_n} \sigma_n^{-1} \left[\frac{1}{m!} \sum_{\sigma_m \in S_m} f(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m)\sigma_m^{-1} \right]
$$

$$
= \frac{1}{n!m!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} \sigma_n^{-1} f(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m)\sigma_m^{-1} = \mathcal{Q}_3 f(v, x, y),
$$

527 and

$$
\mathcal{Q}_2 \circ \mathcal{Q}_1 f(v, x, y)
$$

$$
= \mathcal{Q}_2 \left[\frac{1}{n!} \sum_{\sigma_n \in S_n} \sigma_n^{-1} f(\sigma_n v, \sigma_n x, y) \right]
$$

$$
= \frac{1}{m!} \sum_{\sigma_m \in S_m} \left[\frac{1}{n!} \sum_{\sigma_n \in S_n} \sigma_n^{-1} f(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m) \right] \sigma_m^{-1}
$$

$$
= \frac{1}{m!n!} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} \sigma_n^{-1} f(\sigma_n v\sigma_m, \sigma_n x, y\sigma_m)\sigma_m^{-1} = \mathcal{Q}_3 f(v, x, y).
$$

528 The above two equations hold for any f. Then, we may prove that

$$
\mathcal{Q}_3 = \mathcal{Q}_1 \circ \mathcal{Q}_2 = \mathcal{Q}_2 \circ \mathcal{Q}_1,
$$

529 which is exactly the claim of this theorem.

530 The proof is completed. □

 ## A.4 Proof of Theorem 3.4

532 In this section, we apply our Lemma 3.3 and Theorem 3.1 to prove Theorem 3.4.

533 *Proof of Theorem 3.4.* For the simplicity, we rewrite $\mathcal{Q}_3 p$ and $\mathcal{Q}_3 reg$ as $\mathcal{Q}_2(\mathcal{Q}_1 p)$ and $\mathcal{Q}_2(\mathcal{Q}_1 reg)$,
534 respectively. Then, for a payment rule p, we have that,

$$\mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_3 p]_i(v,x,y)\right]$$

$$= \mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_2(\mathcal{Q}_1 p)]_i(v,x,y)\right] = \mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_1 p]_i(v,x,y)\right]$$

$$= \mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n}p_i(v,x,y)\right].$$

535 Also, we have the following result,

$$\mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_3 reg]_i(v,x,y)\right]$$

$$= \mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_2(\mathcal{Q}_1 reg)]_i(v,x,y)\right] \leq \mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n}[\mathcal{Q}_1 reg]_i(v,x,y)\right]$$

$$\leq \mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n}reg_i(v,x,y)\right].$$

536 Moreover, we have the following result on the regret gap Δ_3,

$$\mathop{\mathbb{E}}_{(v,x,y)}[\Delta_3(g,p;v,x,y)] = \mathop{\mathbb{E}}_{(v,x,y)}[\Delta_1(g,p;v,x,y)] + \mathop{\mathbb{E}}_{(v,x,y)}[\Delta_2(\mathcal{Q}_1 g, \mathcal{Q}_1 p; v,x,y)] \geq 0.$$

537 This proof is completed. $\qquad\qquad\square$

A.5 Proof of Theorem 3.5

539 In this section, we present the proof of Theorem 3.5.

540 We start with the definitions or notations necessary for our proof. We define the allocation rule space
541 and the payment rule space as follows,

$$\mathcal{G} = \{g^\omega : \omega \in \Omega\} \text{ and } \mathcal{P} = \{p^\omega : \omega \in \Omega\},$$

542 where ω is the auction mechanism parameter and Ω is the set of all feasible parameters. We then
543 define the induced utility and ex-post regret spaces as follows,

$$\mathcal{U} = \left\{u^\omega : u_i^\omega(v_i', v, x, y) = \sum_{j=1}^{m}g_{ij}^\omega(v,x,y)v_{ij}' - p_i^\omega(v,x,y)\right\},$$

544 and

$$\mathcal{R} = \left\{reg^\omega : reg_i^\omega(v,x,y) = \max_{v_i'}u^\omega(v_i,(v_i',v_{-i}),x,y) - u^\omega(v_i,v,x,y)\right\}.$$

545 Then, the $l_{\infty,1}$-distance on $\mathcal{U}$ and $\mathcal{P}$ is defined as below,

$$l_{\infty,1}(u,u') = \max_{(v,v_i',x,y)}\left(\sum_{i=1}^{n}|u_i(v_i,(v_i',v_{-i}),x,y) - u_i'(v_i,(v_i',v_{-i}),x,y)|\right),$$

546 and

$$l_{\infty,1}(p,p') = \max_{(v,x,y)}\left(\sum_{i=1}^{n}|p_i(v,x,y) - p_i'(v,x,y)|\right).$$

547 We now present the proof of Theorem 3.5.

548 *Proof of Theorem 3.5.* We prove Theorem 3.5 in two steps: (1) we first prove that the distance
549 between any two mechanisms is smaller when we project them to be permutation-equivariant; (2)
550 then, we prove that the smaller distance implies a smaller covering number.

551 **Step 1:** We prove that the distance between two mechanisms becomes smaller after projection, *i.e.*,
$$l_{\infty,1}(\mathcal{Q}.p, \mathcal{Q}.p') \leq l_{\infty,1}(p, p'),$$

552 and
$$l_{\infty,1}(\mathcal{Q}.u, \mathcal{Q}.u') \leq l_{\infty,1}(u, u'),$$

553 where $u, u' \in \mathcal{U}$, $p, p' \in \mathcal{P}$, and $\mathcal{Q}. = \mathcal{Q}_1$ or $\mathcal{Q}_2$.

554 When $\mathcal{Q}.$ is $\mathcal{Q}_1$, we have that

$$l_{\infty,1}(\mathcal{Q}_1 p, \mathcal{Q}_1 p')$$

$$= \max_{(v,x,y)} \sum_{i=1}^{n} |\mathcal{Q}_1 p_i(v,x,y) - \mathcal{Q}_1 p_i'(v,x,y)|$$

$$= \max_{(v,x,y)} \sum_{i=1}^{n} \left| \frac{1}{n!} \sum_{\sigma_n \in S_n} \left[p_{\sigma_n^{-1}(i)}(\sigma_n v, \sigma_n x, y) - p_{\sigma_n^{-1}(i)}'(\sigma_n v, \sigma_n x, y) \right] \right|$$

$$\leq \max_{(v,x,y)} \sum_{i=1}^{n} \frac{1}{n!} \sum_{\sigma_n \in S_n} \left| p_{\sigma_n^{-1}(i)}(\sigma_n v, \sigma_n x, y) - p_{\sigma_n^{-1}(i)}'(\sigma_n v, \sigma_n x, y) \right|$$

$$\leq \sum_{\sigma_n \in S_n} \frac{1}{n!} \max_{(v,x,y)} \sum_{i=1}^{n} \left| p_{\sigma_n^{-1}(i)}(\sigma_n v, \sigma_n x, y) - p_{\sigma_n^{-1}(i)}'(\sigma_n v, \sigma_n x, y) \right|$$

$$= \sum_{\sigma_n \in S_n} \frac{1}{n!} \max_{(v,x,y)} \sum_{i=1}^{n} \left| p_i(\sigma_n v, \sigma_n x, y) - p_i'(\sigma_n v, \sigma_n x, y) \right|$$

$$= \sum_{\sigma_n \in S_n} \frac{1}{n!} \max_{(v,x,y)} \sum_{i=1}^{n} \left| p_i(v, x, y) - p_i'(v, x, y) \right|$$

$$= \max_{(v,x,y)} \sum_{i=1}^{n} \left| p_i(v, x, y) - p_i'(v, x, y) \right|$$

$$= l_{\infty,1}(p, p'),$$

555 and

$$l_{\infty,1}(\mathcal{Q}_1 u, \mathcal{Q}_1 u')$$

$$= \max_{v,v',x,y} \sum_{i=1}^{n} |[\mathcal{Q}_1 u]_i(v_i, (v_i', v_{-i}), x, y) - [\mathcal{Q}_1 u']_i(v_i, (v_i', v_{-i}), x, y)|$$

$$= \max_{v,v',x,y} \sum_{i=1}^{n} \left| \frac{1}{n!} \sum_{\sigma_n \in S_n} u_{\sigma_n^{-1}(i)}(v_i, \sigma_n(v_i', v_{-i}), \sigma_n x, y) - u_{\sigma_n^{-1}(i)}'(v_i, \sigma_n(v_i', v_{-i}), \sigma_n x, y) \right|$$

$$\leq \max_{v,v',x,y} \sum_{i=1}^{n} \frac{1}{n!} \sum_{\sigma_n \in S_n} |u_{\sigma_n^{-1}(i)}(v_i, \sigma_n(v_i', v_{-i}), \sigma_n x, y) - u_{\sigma_n^{-1}(i)}'(v_i, \sigma_n(v_i', v_{-i}), \sigma_n x, y)|$$

$$\leq \frac{1}{n!} \sum_{\sigma_n \in S_n} \max_{v,v',x,y} \sum_{i=1}^{n} |u_{\sigma_n^{-1}(i)}(v_i, \sigma_n(v_i', v_{-i}), \sigma_n x, y) - u_{\sigma_n^{-1}(i)}'(v_i, \sigma_n(v_i', v_{-i}), \sigma_n x, y)|$$

$$= \frac{1}{n!} \sum_{\sigma_n \in S_n} \max_{v,v',x,y} \sum_{i=1}^{n} |u_i(v_i, (v_i', v_{-i}), x, y) - u_i'(v_i, (v_i', v_{-i}), x, y)|$$

$$= \max_{v,v',x,y} \sum_{i=1}^{n} |u_i(v_i, (v_i', v_{-i}), x, y) - u_i'(v_i, (v_i', v_{-i}), x, y)|$$

$$= l_{\infty,1}(u, u').$$

556 Then, when $\mathcal{Q}.$ is $\mathcal{Q}_2$, we prove the result as below,

$$l_{\infty,1}(\mathcal{Q}_2 p, \mathcal{Q}_2 p')$$

$$= \max_{(v,x,y)} \sum_{i=1}^{n} |\mathcal{Q}_2 p_i(v,x,y) - \mathcal{Q}_2 p'_i(v,x,y)|$$

$$= \max_{(v,x,y)} \sum_{i=1}^{n} \left| \frac{1}{m!} \sum_{\sigma_m \in S_m} \left[p_i(v\sigma_m, x, y\sigma_m) - p'_i(v\sigma_m, x, y\sigma_m) \right] \right|$$

$$\leq \max_{(v,x,y)} \sum_{i=1}^{n} \frac{1}{m!} \sum_{\sigma_m \in S_m} |p_i(v\sigma_m, x, y\sigma_m) - p'_i(v\sigma_m, x, y\sigma_m)|$$

$$\leq \sum_{\sigma_m \in S_m} \frac{1}{m!} \max_{(v,x,y)} \sum_{i=1}^{n} |p_i(v\sigma_m, x, y\sigma_m) - p'_i(v\sigma_m, x, y\sigma_m)|$$

$$= \sum_{\sigma_m \in S_m} \frac{1}{m!} \max_{(v,x,y)} \sum_{i=1}^{n} |p_i(v, x, y) - p'_i(v, x, y)|$$

$$= \max_{(v,x,y)} \sum_{i=1}^{n} |p_i(v, x, y) - p'_i(v, x, y)|$$

$$= l_{\infty,1}(p, p'),$$

557 and

$$l_{\infty,1}(\mathcal{Q}_2 u, \mathcal{Q}_2 u')$$

$$= \max_{v,v',x,y} \sum_{i=1}^{n} |[\mathcal{Q}_2 u]_i(v_i, (v'_i, v_{-i}), x, y) - [\mathcal{Q}_2 u']_i(v_i, (v'_i, v_{-i}), x, y)|$$

$$= \max_{v,v',x,y} \sum_{i=1}^{n} \left| \frac{1}{m!} \sum_{\sigma_m \in S_m} |u_i(v_i\sigma_m, (v'_i, v_{-i})\sigma_m, x, y\sigma_m) - u'_i(v_i\sigma_m, (v'_i, v_{-i})\sigma_m, x, y\sigma_m)| \right|$$

$$\leq \max_{v,v',x,y} \sum_{i=1}^{n} \frac{1}{m!} \sum_{\sigma_m \in S_m} |u_i(v_i\sigma_m, (v'_i, v_{-i})\sigma_m, x, y\sigma_m) - u'_i(v_i\sigma_m, (v'_i, v_{-i})\sigma_m, x, y\sigma_m)|$$

$$\leq \frac{1}{m!} \sum_{\sigma_m \in S_m} \max_{v,v',x,y} \sum_{i=1}^{n} |u_i(v_i\sigma_m, (v'_i, v_{-i})\sigma_m, x, y\sigma_m) - u'_i(v_i\sigma_m, (v'_i, v_{-i})\sigma_m, x, y\sigma_m)|$$

$$= \frac{1}{m!} \sum_{\sigma_m \in S_m} \max_{v,v',x,y} \sum_{i=1}^{n} |u_i(v_i, (v'_i, v_{-i}), x, y) - u'_i(v_i, (v'_i, v_{-i}), x, y)|$$

$$= \max_{v,v',x,y} \sum_{i=1}^{n} |u_i(v_i, (v'_i, v_{-i}), x, y) - u'_i(v_i, (v'_i, v_{-i}), x, y)|$$

$$= l_{\infty,1}(u, u').$$

558 Thus, we have completed Step 1.

559 **Step 2:** We prove that a smaller distance implies a smaller covering number.

560 Let $\mathcal{X}$ and $\mathcal{Y}$ be two metric spaces with two different distances l_1 and l_2, respectively. There exists
561 a surjective mapping f from $\mathcal{Y}$ to $\mathcal{X}$, such that $l_1(f(x), f(y)) \leq l_2(x, y)$ for all $x, y \in \mathcal{Y}$. The
562 covering numbers $\mathcal{N}_1(\mathcal{X}, r)$ and $\mathcal{N}_2(\mathcal{Y}, r)$ are defined as the minimum numbers of balls with radius r
563 that can cover $\mathcal{X}$ and $\mathcal{Y}$ under l_1 and l_2, respectively.

564 By the definition of the covering number $\mathcal{N}_2(\mathcal{Y}, r)$, there exists a set $\mathcal{A}$ of scale $\mathcal{N}_2(\mathcal{Y}, r)$, such that

$$l_2(x, \mathcal{A}) = \inf_{y \in \mathcal{A}} l_2(x, y) < r, \forall x \in \mathcal{Y}.$$

Then, $f(\mathcal{A})$ is also a r-cover for $\mathcal{X}$ under distance l_1, *i.e.*, for any $x \in \mathcal{Y}$, we have

$$l_1(f(x), f(\mathcal{A})) = \inf_{y \in \mathcal{A}} l_1(f(x), f(y)) \le \inf_{y \in \mathcal{A}} l_2(x, y) = l_2(x, \mathcal{A}) < r.$$

Because f is surjective, for any $x' \in \mathcal{X}$, there exists an $x \in \mathcal{Y}$, such that $x' = f(x)$. Then, for any $x' \in \mathcal{X}$, we have that

$$l_1(x', f(\mathcal{A})) = l_1(f(x), f(\mathcal{A})) < r.$$

By the definition of $\mathcal{N}_1(\mathcal{X}, r)$, we have

$$\mathcal{N}_1(\mathcal{X}, r) \le |f(\mathcal{A})| \le |\mathcal{A}| = \mathcal{N}_2(\mathcal{Y}, r).$$

Eventually, combining the results in Step 1 and in Step 2, we have that

$$\mathcal{N}_{\infty,1}(\mathcal{Q}.\mathcal{U}, r) \le \mathcal{N}_{\infty,1}(\mathcal{U}, r),$$

and

$$\mathcal{N}_{\infty,1}(\mathcal{Q}.\mathcal{P}, r) \le \mathcal{N}_{\infty,1}(\mathcal{P}, r),$$

for both the bidder averaging $\mathcal{Q}_1$ and the item averaging $\mathcal{Q}_2$. $\qquad\square$

A.6 Proof of Theorem 3.6 and Corollary 3.7

We first introduce two lemmas. The first lemma gives a concentration inequality via the covering number. This result can be used to bound the gap between expected revenue/ex-post regret and empirical revenue/ex-post regret. The second lemma bounds the covering number $\mathcal{N}_{\infty,1}(\mathcal{R}, 2r)$ by the covering number $\mathcal{N}_{\infty,1}(\mathcal{U}, r)$. Both lemmas has been proved by [10]. We recall them here to make our paper completed.

Lemma A.1 (cf. Lemma E.1, [10]). *Let $\mathcal{S} = \{z_1, \ldots, z_L\}$ be a set of i.i.d. sample points drawn from a distribution $\mathcal{D}$ over $\mathcal{Z}$. Suppose $\mathcal{F}$ is a set of functions from $\mathcal{Z}$ to $\mathbb{R}$ such that $f(z) \in [a, b]$ for all $f \in \mathcal{F}$ and $z \in \mathcal{Z}$. We define l_∞ on $\mathcal{F}$ as*

$$l_\infty(f, f') = \max_{z \in \mathcal{Z}} |f(z) - f'(z)|,$$

and $\mathcal{N}_\infty(\mathcal{F}, r)$ as the minimum number of balls with radius r that can cover $\mathcal{F}$ under l_∞-distance. Then, we have the following concentration inequality,

$$\mathbb{P}\left[\exists f \in \mathcal{F} : \left|\frac{1}{L}\sum_{i=1}^{L} f(z_i) - \mathbb{E}[f(z)]\right| > \epsilon\right] \le 2\mathcal{N}_\infty\left(\mathcal{F}, \frac{\epsilon}{3}\right) \exp\left(-\frac{2L\epsilon^2}{9(b-a)^2}\right).$$

Proof. By the definition of $\mathcal{N}_\infty(\mathcal{F}, r)$, for any $f \in \mathcal{F}$, there exists an $f_r \in \mathcal{F}_r$ such that $\mathcal{F}_r$ is an r-cover for $\mathcal{F}$ and $l_\infty(f, f_r) < r$. Denote $\frac{1}{L}\sum_{i=1}^{L} f(z_i)$ by $\mathbb{E}_{\mathcal{S}}[f(z)]$. Then, we have

$$\mathbb{P}\left[\exists f \in \mathcal{F} : \left|\mathbb{E}_{\mathcal{S}}[f(z)] - \mathbb{E}[f(z)]\right| > \epsilon\right]$$

$$= \mathbb{P}\left[\exists f \in \mathcal{F} : \left|\mathbb{E}_{\mathcal{S}}[f(z)] - \mathbb{E}_{\mathcal{S}}[f_r(z)] + \mathbb{E}_{\mathcal{S}}[f_r(z)] - \mathbb{E}[f_r(z)] + \mathbb{E}[f_r(z)] - \mathbb{E}[f(z)]\right| > \epsilon\right]$$

$$\le \mathbb{P}\left[\exists f \in \mathcal{F} : \left|\mathbb{E}_{\mathcal{S}}[f(z)] - \mathbb{E}_{\mathcal{S}}[f_r(z)]\right| + \left|\mathbb{E}_{\mathcal{S}}[f_r(z)] - \mathbb{E}[f_r(z)]\right| + \left|\mathbb{E}[f_r(z)] - \mathbb{E}[f(z)]\right| > \epsilon\right]$$

$$\le \mathbb{P}\left[\exists f_r \in \mathcal{F}_{\frac{\epsilon}{3}} : \left|\mathbb{E}_{\mathcal{S}}[f_r(z)] - \mathbb{E}[f_r(z)]\right| > \frac{\epsilon}{3}\right]$$

$$\le \mathcal{N}_\infty\left(\mathcal{F}, \frac{\epsilon}{3}\right)\mathbb{P}\left[\left|\mathbb{E}_{\mathcal{S}}[f(z)] - \mathbb{E}[f(z)]\right| > \frac{\epsilon}{3}\right]$$

$$\le 2\mathcal{N}_\infty\left(\mathcal{F}, \frac{\epsilon}{3}\right) \exp\left(-\frac{2L\epsilon^2}{9(b-a)^2}\right).$$

585 The third inequality follows from the fact that when $r = \frac{\epsilon}{3}$, we have
$$|f(z) - f_r(z)| < \frac{\epsilon}{3},$$
586 for all $z \in \mathcal{Z}$ and $f \in \mathcal{F}$. Then, from the Hoeffding's inequality, we have
$$\left| \frac{1}{L} \sum_{i=1}^{L} f(z_i) - \frac{1}{L} \sum_{i=1}^{L} f_r(z_i) \right| < \frac{\epsilon}{3} \text{ and } \left| \mathbb{E}[f(z)] - \mathbb{E}[f_r(z)] \right| < \frac{\epsilon}{3}.$$

587 The proof is completed. □

588 The following lemma bounds the covering number $\mathcal{N}_{\infty,1}(\mathcal{R}, 2r)$ by the covering number $\mathcal{N}_{\infty,1}(\mathcal{U}, r)$.
589 Then the gap between expected ex-post regret and empirical ex-post regret can be bounded by the
590 covering number $\mathcal{N}_{\infty,1}(\mathcal{U}, r)$.

591 **Lemma A.2** (cf. Lemma E.3, [10]). *We define $\mathcal{N}_{\infty,1}(\mathcal{R}, r)$ and $\mathcal{N}_{\infty,1}(\mathcal{U}, r)$ as the minimum numbers*
592 *of balls with radius r that can cover spaces $\mathcal{R}$ and $\mathcal{U}$ under distance $l_{\infty,1}$, respectively. Then, we*
593 *have that*
$$\mathcal{N}_{\infty,1}(\mathcal{R}, 2r) \leq \mathcal{N}_{\infty,1}(\mathcal{U}, r)$$

594 *Proof.* By the definition of $\mathcal{N}_{\infty,1}(\mathcal{U}, r)$, there exists an r-cover $\mathcal{U}_r$ for $\mathcal{U}$, such that $|\mathcal{U}_r| = \mathcal{N}_{\infty,1}(\mathcal{U}, r)$
595 and for any $u \in \mathcal{U}$,
$$l_{\infty,1}(u, \mathcal{U}_r) = \inf_{u' \in \mathcal{U}_r} l_{\infty,1}(u, u') < r.$$
596 We define $\mathcal{R}_r$ as
$$\{reg \in \mathcal{R} : reg_i(v, x, y) = \max_{v_i'} u_i(v_i, (v_i', v_{-i}), x, y) - u_i(v_i, v, x, y) \text{ for some } u_i \in \mathcal{U}_r\}.$$
597 Then, we can prove that $\mathcal{R}_r$ is a $2r$-cover for the space $\mathcal{R}$, *i.e.*,
$$l_{\infty,1}(reg, \mathcal{R}_r)$$
$$= \inf_{reg' \in \mathcal{R}_r} l_{\infty,1}(reg, reg')$$
$$= \inf_{reg' \in \mathcal{R}_r} \max_{v,x,y} \sum_{i=1}^{n} |reg_i(v, x, y) - reg_i'(v, x, y)|$$
$$= \inf_{u' \in \mathcal{U}_r} \max_{v,x,y} \sum_{i=1}^{n} \left| [\max_{v_i'} u_i(v_i, (v_i', v_{-i}), x, y) - u_i(v_i, v, x, y)] \right.$$
$$\left. - [\max_{v_i'} u_i'(v_i, (v_i', v_{-i}), x, y) - u_i'(v_i, v, x, y)] \right|$$
$$\leq \inf_{u' \in \mathcal{U}_r} \max_{v,x,y} \left[\sum_{i=1}^{n} \left| \max_{v_i'} u_i(v_i, (v_i', v_{-i}), x, y) - \max_{v_i'} u_i'(v_i, (v_i', v_{-i}), x, y) \right| \right.$$
$$\left. + \left| u_i(v_i, v, x, y) - u_i'(v_i, v, x, y) \right| \right]$$
$$\leq \max_{v,x,y} \left[\sum_{i=1}^{n} \left| \max_{v_i'} u_i(v_i, (v_i', v_{-i}), x, y) - \max_{v_i'} u_i^*(v_i, (v_i', v_{-i}), x, y) \right| \right.$$
$$\left. + \left| u_i(v_i, v, x, y) - u_i^*(v_i, v, x, y) \right| \right] \quad (\text{where } l_{\infty,1}(u, u^*) < r)$$
$$\leq \max_{v,x,y} \sum_{i=1}^{n} \left| \max_{v_i'} u_i(v_i, (v_i', v_{-i}), x, y) - \max_{v_i'} u_i^*(v_i, (v_i', v_{-i}), x, y) \right| + r$$
$$\leq \max_{v,x,y} \sum_{i=1}^{n} \max_{v_i'} |u_i(v_i, (v_i', v_{-i}), x, y) - u_i^*(v_i, (v_i', v_{-i}), x, y)| + r$$
$$= \max_{v,v_i',x,y} \sum_{i=1}^{n} |u_i(v_i, (v_i', v_{-i}), x, y) - u_i^*(v_i, (v_i', v_{-i}), x, y)| + r < 2r.$$

598 Eventually, we have

$$\mathcal{N}_{\infty,1}(\mathcal{R}, 2r) \le |\mathcal{R}_r| \le |\mathcal{U}_r| = \mathcal{N}_{\infty,1}(\mathcal{U}, r).$$

599 The proof is completed. □

600 We now prove Theorem 3.6 and Corollary 3.7.

601 *Proof of Theorem 3.6 and Corollary 3.7.* Applying Lemma A.1 to the spaces $\mathcal{P}$ and $\mathcal{U}$, we have that

$$\mathbb{P}\left[\exists \omega \in \Omega : \left|\mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i^\omega(v, x, y)\right] - \frac{1}{L}\sum_{l=1}^{L}\sum_{i=1}^{n} p_i^\omega(v^{(l)}, x^{(l)}, y^{(l)})\right| > \epsilon\right]$$
$$\le 2\mathcal{N}_{\infty,1}\left(\mathcal{P}, \frac{\epsilon}{3}\right)\exp\left(-\frac{2L\epsilon^2}{9n^2}\right),$$

602 and

$$\mathbb{P}\left[\exists \omega \in \Omega : \left|\mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n} reg_i^\omega(v, x, y)\right] - \frac{1}{L}\sum_{l=1}^{L}\sum_{i=1}^{n} reg_i^\omega(v^{(l)}, x^{(l)}, y^{(l)})\right| > \epsilon\right]$$
$$\le 2\mathcal{N}_{\infty,1}\left(\mathcal{R}, \frac{\epsilon}{3}\right)\exp\left(-\frac{2L\epsilon^2}{9n^2}\right)$$
$$\le 2\mathcal{N}_{\infty,1}\left(\mathcal{U}, \frac{\epsilon}{6}\right)\exp\left(-\frac{2L\epsilon^2}{9n^2}\right),$$

603 where the last inequality follows from Lemma A.2.

604 Further, we assume that

$$\epsilon \ge \sqrt{\frac{9n^2}{2L}\left(\log\frac{4}{\delta} + \max\left\{\log\mathcal{N}_{\infty,1}\left(\mathcal{P}, \frac{\epsilon}{3}\right), log\mathcal{N}_{\infty,1}\left(\mathcal{U}, \frac{\epsilon}{6}\right)\right\}\right)}.$$

605 Then, we have the following inequalities,

$$\mathbb{P}\left[\exists \omega \in \Omega : \left|\mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i^\omega(v, x, y)\right] - \frac{1}{L}\sum_{l=1}^{L}\sum_{i=1}^{n} p_i^\omega(v^{(l)}, x^{(l)}, y^{(l)})\right| > \epsilon\right] \le \frac{\delta}{2},$$

606 and

$$\mathbb{P}\left[\exists \omega \in \Omega : \left|\mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n} reg_i^\omega(v, x, y)\right] - \frac{1}{L}\sum_{l=1}^{L}\sum_{i=1}^{n} reg_i^\omega(v^{(l)}, x^{(l)}, y^{(l)})\right| > \epsilon\right] \le \frac{\delta}{2}.$$

607 Thus, with probability at least $1 - \delta$, for any $\omega \in \Omega$, we have that

$$\left|\mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n} p_i^\omega(v, x, y)\right] - \frac{1}{L}\sum_{l=1}^{L}\sum_{i=1}^{n} p_i^\omega(v^{(l)}, x^{(l)}, y^{(l)})\right| < \epsilon, \tag{5}$$

608 and

$$\left|\mathop{\mathbb{E}}_{(v,x,y)}\left[\sum_{i=1}^{n} reg_i^\omega(v, x, y)\right] - \frac{1}{L}\sum_{l=1}^{L}\sum_{i=1}^{n} reg_i^\omega(v^{(l)}, x^{(l)}, y^{(l)})\right| < \epsilon. \tag{6}$$

609 Equivalently, when the number of samples L is large enough, *i.e.*,

$$L \ge \frac{9n^2}{2\epsilon^2}\left(\log\frac{4}{\delta} + \max\left\{\log\mathcal{N}_{\infty,1}\left(\mathcal{P}, \frac{\epsilon}{3}\right), log\mathcal{N}_{\infty,1}\left(\mathcal{U}, \frac{\epsilon}{6}\right)\right\}\right),$$

610 then, the eqs. (5) and (6) both hold with probability at least $1 - \delta$.

611 The proof is completed. □

A.7 Proof of the Generalization Bound for Myerson Auctions

Denote $rev(v, x, y)$ as $\sum_{i=1}^{n} p_i(v, x, y)$, then we have the following theorem,

Theorem A.3. *Assume the item valuation for each bidder is not larger than* 1. *When the sample complexity satisfies* $L \geq \frac{1}{2\epsilon^2} \log \frac{2}{\delta}$, *with probability at least* $1 - \delta$, *we have*

$$\left| \frac{1}{L} \sum_{\ell=1}^{L} rev(v^{(\ell)}, x^{(\ell)}, y^{(\ell)}) - \mathbb{E}_{(v,x,y)} \left[rev(v, x, y) \right] \right| \leq \epsilon.$$

Proof. Since $v_i \leq 1$, we have

$$rev(v, x, y) = \sum_{i=1}^{n} p_i(v, x, y) \leq \sum_{i=1}^{n} b_i(v, x, y) v_i \leq \sum_{i=1}^{n} b_i(v, x, y) \leq 1.$$

According to the Hoeffding's inequality, we have

$$\mathbb{P}\left[\left| \frac{1}{L} \sum_{\ell=1}^{L} rev(v^{(\ell)}, x^{(\ell)}, y^{(\ell)}) - \mathbb{E}_{(v,x,y)} \left[rev(v, x, y) \right] \right| \geq \epsilon \right] \leq 2 \exp(-2L\epsilon^2).$$

Let $2\exp(-2L\epsilon^2) \leq \delta$, then we obtain what we need. The proof is completed. $\square$

A.8 Orbit Averaging over Subsets of Bidders/Items

In addition, we can extended our theory to orbit averaging over the subset of the bidders/items.

Theorem A.4. *Let* $\mathcal{Q}$ *be the orbit averaging over any subset of bidders and items, and* (g, p) *be any mechanism. Then we have*

$$\mathbb{E}_{(v,x,y)} \left[\sum_{i=1}^{n} [\mathcal{Q}p]_i(v, x, y) \right] = \mathbb{E}_{(v,x,y)} \left[\sum_{i=1}^{n} p_i(v, x, y) \right],$$

and

$$\mathbb{E}_{(v,x,y)} \left[\sum_{i=1}^{n} reg_i(v, x, y) \right] \geq \mathbb{E}_{(v,x,y)} \left[\sum_{i=1}^{n} [\mathcal{Q}reg]_i(v, x, y) \right],$$

where reg_i *is the ex-post regret of bidder* i.

Proof. Without loss of generality, we assume that $\mathcal{Q}_1$ takes average over the first $\tilde{n}$ bidders, $\mathcal{Q}_2$ takes average over the first $\tilde{m}$ items and $\mathcal{Q}_3$ takes average over the first $\tilde{n}$ bidders and $\tilde{m}$ items. Denote Z_1 as $(v_{ij}, x_i : i > \tilde{n}, j \in [m])$ and Z_2 as $(v_{ij}, y_j : i \in [n], j > \tilde{m})$. Following Theorem 3.1, we have

$$\mathbb{E}\left[\sum_{i=1}^{n} [\mathcal{Q}_1 p]_i(v, x, y) \middle| Z_1 \right] = \mathbb{E}\left[\sum_{i=1}^{n} p_i(v, x, y) \middle| Z_1 \right],$$

and

$$\mathbb{E}\left[\sum_{i=1}^{n} reg_i(v, x, y) \middle| Z_1 \right] \geq \mathbb{E}\left[\sum_{i=1}^{n} [\mathcal{Q}_1 reg]_i(v, x, y) \middle| Z_1 \right].$$

Then, combining the fact that $\mathbb{E}[\mathbb{E}[X|Y]] = \mathbb{E}[X]$, we have

$$\mathbb{E}\left[\sum_{i=1}^{n} [\mathcal{Q}_1 p]_i(v, x, y) \right] = \mathbb{E}\left[\sum_{i=1}^{n} p_i(v, x, y) \right],$$

and

$$\mathbb{E}\left[\sum_{i=1}^{n} reg_i(v, x, y) \right] \geq \mathbb{E}\left[\sum_{i=1}^{n} [\mathcal{Q}_1 reg]_i(v, x, y) \right].$$

Similarly, replace Z_1 by Z_2, we can obtain the equations all hold for $\mathcal{Q}_2$.

Finally, we prove that $\mathcal{Q}_3 = \mathcal{Q}_1 \mathcal{Q}_2 = \mathcal{Q}_2 \mathcal{Q}_1$. The proof is same with the proof of Lemma 3.3. Only replace n and m by $\tilde{n}$ and $\tilde{m}$ respectively, and we obtain the result.

The proof is completed. $\square$

Theorem A.5. *Let $\mathcal{Q}$ be the orbit averaging over any subset of bidders and items, and $\mathcal{U} = \{u^\omega : \omega \in \Omega\}$ and $\mathcal{P} = \{p^\omega : \omega \in \Omega\}$ the sets of all possible utilities and payment rules. Then we have*

$$\mathcal{N}_{\infty,1}(\mathcal{QU}, r) \leq \mathcal{N}_{\infty,1}(\mathcal{U}, r) \ \ and \ \ \mathcal{N}_{\infty,1}(\mathcal{QP}, r) \leq \mathcal{N}_{\infty,1}(\mathcal{P}, r),$$

where $\mathcal{N}_{\infty,1}(\mathcal{U}, r)$ and $\mathcal{N}_{\infty,1}(\mathcal{P}, r)$ are the minimum numbers of balls with radius r that can cover $\mathcal{U}$ and $\mathcal{P}$ under $l_{\infty,1}$-distance, respectively.

Proof. Without loss of generality, we assume that $\mathcal{Q}_1$ takes average over the first $\tilde{n}$ bidders, $\mathcal{Q}_2$ takes average over the first $\tilde{m}$ items and $\mathcal{Q}_3$ takes average over the first $\tilde{n}$ bidders and $\tilde{m}$ items.

We can only prove the distance between two mechanisms becomes smaller after orbit averaging, *i.e.*,

$$l_{\infty,1}(\mathcal{Q}p, \mathcal{Q}p') \leq l_{\infty,1}(p, p') \ \ and \ \ l_{\infty,1}(\mathcal{Q}u, \mathcal{Q}u') \leq l_{\infty,1}(u, u').$$

Only replace n and m by $\tilde{n}$ and $\tilde{m}$ in the proof of Theorem 3.5, and we obtain the results.

The proof is completed. $\qquad\square$

Remark A.6. Our results are not limited to the permutation group. When taking average over any subgroup of the permutation group G, Theorem 3.1, 3.4, and 3.5 also hold.

B Additional Experimental Details

This section presents additional experimental details and results omitted from the main text due to space limitation.

B.1 Additional Experimental Settings

In this section, we present detailed experimental settings.

B.1.1 Network Architectures

We first describe the RegretNet's architecture [12]. A RegretNet consists of two parts: the allocation network $g^\omega : \mathbb{R}^{nm} \to [0,1]^{nm}$ and the payment network $p^\omega : \mathbb{R}^{nm} \to \mathbb{R}^n_{\geq 0}$, both of which are modeled as three-layer full-connected networks with *tanh* activations. Every layer in the two networks includes 100 nodes.

For each item j, the payment network outputs a probability vector $(g^\omega_{1j}(b), \ldots, g^\omega_{nj}(b))$, where $g^\omega_{ij}(b)$ is the probability of allocating the item j to the bidder i. To avoid allocating one item over once, a feasible allocation network needs to satisfy $\sum_{i=1}^n g^\omega_{ij}(b) \leq 1$ for all $j \in [m]$, $\omega \in \Omega$, and $b \in \mathcal{V}^{nm}$. Therefore, we compute the allocation via a *softmax activation function*. In addition, to present the probability that the item is preserved, an extra dummy node is included in the softmax computation.

To ensure the *individual rational* condition, the payment network p^ω is required to output a payment vector $p^\omega(b)$, such that $p^\omega_i(b) \leq \sum_{j=1}^m g^\omega_{ij}(b)b_{ij}$ for all $i \in [n]$. Therefore, the payment network first computes a fractional payment $\overline{p}^\omega_i(b)$ for each bidder i using a sigmoidal unit. Then, the final payment of the bidder i is

$$p^\omega_i(b) = \overline{p}^\omega_i(b) \sum_{j=1}^m g^\omega_{ij}(b)b_{ij} \leq \sum_{j=1}^m g^\omega_{ij}(b)b_{ij}.$$

An overview of the RegretNet's architecture is illustrated in the following Figure 1.

RegretNet-PE is designed by modifying RegretNet. We adopt the allocation rule as $\widetilde{g}^\omega = \mathcal{Q}_3 g^\omega$ and the payment rule as $\widetilde{p}^\omega = \mathcal{Q}_3 p^\omega$, respectively. In this way, we may guarantee that in RegretNet-PE, the allocation is feasible and the mechanism is *individual rational*, *i.e.*, $\sum_{i=1}^n \widetilde{g}^\omega_{ij}(b) \leq 1$, and $\widetilde{p}^\omega_i(b) \leq \sum_{j=1}^m \widetilde{g}^\omega_{ij}(b)b_{ij}$. We may also show that the RegretNet-PE is always permutation-equivariant and has the same number of coefficients as the RegretNet. The proof can be found in Appendix A.1.

Figure 1: The allocation network g^ω and the payment network p^ω of the RegretNet with the overall mechanism parameter $\omega = (\omega_g, \omega_p)$.

B.1.2 Training Procedures

We adopt the augmented Lagrangian method to minimize the following object function with a quadratic penalty term for violating the constraints,

$$\mathcal{L}_\rho(\omega, \lambda) = -\frac{1}{L}\sum_{l=1}^{L}\sum_{i=1}^{n} p_i^\omega(v^{(l)}) + \sum_{i=1}^{n} \lambda_i \widehat{reg}_i(\omega) + \frac{\rho}{2}\Big(\sum_{i=1}^{n} \widehat{reg}_i\Big)^2,$$

where L is the number of samples, λ is a vector of Lagrange multipliers, and $\rho > 0$ is a parameter to control the weight of the quadratic penalty. We alternately update the overall mechanism parameter ω and the Lagrange multiplier λ as follows:

(a) $\omega^{new} \in \arg\min_\omega \mathcal{L}_\rho(\omega^{old}, \lambda^{old})$ (every iteration);

(b) $\lambda_i^{new} = \lambda_i^{old} + \rho \cdot \widehat{reg}_i(\omega^{new}), \forall i \in [n]$ (every T_λ iterations).

The training procedure is described in the following Algorithm 1.

We divide all training samples $\mathcal{S}$ into T batches $\mathcal{S}_1, \ldots, \mathcal{S}_T$ of size B. At iteration t, we use the batch $\mathcal{S}_t = \{v^{(1)}, \ldots, v^{(B)}\}$.

The update (a) is computed via Adam. The gradient of $\mathcal{L}_\rho$ *w.r.t.* ω for a fixed λ^t is as below,

$$\nabla_\omega \mathcal{L}_\rho(\omega, \lambda^t) = -\frac{1}{B}\sum_{l=1}^{B}\sum_{i=1}^{n} \nabla_\omega p_i^\omega(v^{(l)}) + \sum_{l=1}^{B}\sum_{i=1}^{n} \lambda_i^t g_{l,i}^t + \rho \sum_{l=1}^{B}\sum_{i=1}^{n} \widehat{reg}_i(\omega) g_{l,i}^t,$$

where

$$\widehat{reg}_i(\omega) = \frac{1}{B}\sum_{l=1}^{B} \max_{v_i' \in \mathcal{V}^m} u_i^\omega(v_i^{(l)}, (v_i', v_{-i}^{(l)})) - u_i^\omega(v_i^{(l)}, v^{(l)}),$$

and

$$g_{l,i}^t = \nabla_\omega \Big[\max_{v_i' \in \mathcal{V}^m} u_i^\omega(v_i^{(l)}, (v_i', v_{-i}^{(l)})) - u_i^\omega(v_i^{(l)}, v^{(l)})\Big]\Big|_{\omega=\omega^t}.$$

Because $\widehat{reg}_i(\omega)$ and $g_{l,i}^t$ both contain a "max" over misreports[1], we use another Adam to compute the approximated best biddings $v'^{(l)}$. In each update on ω^t, we perform R updates to compute a best bidding $v_i'^{(l)}$ for each $i \in [n]$. In particular, we maintain the misreports $v'^{(l)}$ for each sample l as the initial value in the next iteration. Then, we use these biddings $v'^{(l)}$ to compute the gradient $\nabla_\omega \mathcal{L}_\rho(\omega, \lambda^t)$ and then, update ω^t as $\omega^{t+1} = \omega^t - \eta \nabla_\omega \mathcal{L}_\rho(\omega^t, \lambda^t)$. After every T_λ iterations, we update λ^t as $\lambda^{t+1} = \lambda^t + \rho \widehat{reg}(\omega^{t+1})$. In addition, we increase the value of ρ every a certain number of iterations, where we set the value of ρ_t in each iteration t prior to training.

---

[1]The misreport refers to an arbitrary bid, rather than restricted to be a truthful bid [12].

Algorithm 1: RegretNet and RegretNet-PE Training

Input: Batches $\mathcal{S}_1, \ldots, \mathcal{S}_T$ of size B
Parameters: $\forall t \in [T], \rho_t > 0, \gamma > 0, \eta > 0, T \in \mathbb{N}, R \in \mathbb{N}, T_\lambda \in \mathbb{N}$
Initialize: $\omega^0 \in \mathbb{R}^d, \lambda^0 \in \mathbb{R}^n$
for $t = 0$ **to** T **do**
$\quad$ Receive batch $S_t = \{v^{(1)}, \ldots, v^{(B)}\}$
$\quad$ Initialize misreports $v'^{(l)}_i \in \mathcal{V}^m, \forall l \in [B], i \in [n]$
$\quad$ **for** $r = 0$ **to** R **do**
$\quad\quad | \quad \forall l \in [B], i \in [n]:$
$\quad\quad | \quad\quad v'^{(l)}_i \leftarrow v'^{(l)}_i + \gamma \nabla_{v'_i} u_i^\omega \big(v_i^{(l)}, (v'^{(l)}_i, v_{-i}^{(l)})\big)$
$\quad$ **end**
$\quad$ Compute ex-post regret gradient : $\forall l \in [B], i \in [n]:$
$\quad\quad g_{l,i}^t \leftarrow \nabla_\omega \Big[u_i^\omega \big(v_i^{(l)}, (v'^{(l)}_i, v_{-i}^{(l)})\big) - u_i^\omega \big(v_i^{(l)}, v^{(l)}\big) \Big]\Big|_{\omega = \omega^t}$
$\quad$ Compute Lagrangian gradient using Equation 4 and update ω^t:
$\quad\quad \omega^{t+1} \leftarrow \omega^t - \eta \nabla_\omega \mathcal{L}_{\rho_t}(\omega^t, \lambda^t)$
$\quad$ Update Lagrange multipliers λ once in T_λ iterations:
$\quad$ **if** *t is a multiple of* T_λ **then**
$\quad\quad | \quad \lambda_i^{t+1} = \lambda_i^t + \rho_t \widehat{reg}_i(\omega^{t+1}), \forall i \in [n]$
$\quad$ **else**
$\quad\quad | \quad \lambda^{t+1} = \lambda^t$
$\quad$ **end**
end

Table 3: Additional experimental results. "$n \times m\ Normal$" refers that there are n bidders and m items, and the valuation is drawn from the truncated normal distribution $\mathcal{N}(0.3, 0.1)$ in [0,1]. The true values of the ex-post regret and the generalization error (GE) are the products of the values in the table and a factor of 10^{-5}.

Method	$2 \times 1\ Normal$			$3 \times 1\ Normal$		
	Revenue	Regret	GE	Revenue	Regret	GE
Optimal	0.305	0	-	0.389	0	-
RegretNet	0.275	97.0	8.50	0.321	84.0	45.5
RegretNet-Test	0.275	95.2	-	0.321	75.0	-
RegretNet-PE	0.276	85.4	8.40	0.382	69.7	27.6

Method	$2 \times 2\ Normal$			$5 \times 3\ Normal$		
	Revenue	Regret	GE	Revenue	Regret	GE
RegretNet	0.577	343	246	1.05	114	77.0
RegretNet-Test	0.577	327	-	1.05	32.0	-
RegretNet-PE	0.577	318	77.0	1.09	75.0	70.0

B.1.3 Test Settings

To verify our Theorem 3.1 and Theorem 3.4, we first train a RegretNet and then project the will-trained RegretNet to be permutation-equivariant through bidder-item aggregated averaging $\mathcal{Q}_3$, denoted as "RegretNet-Test". To meet the *symmetric valuation* condition in Theorem 3.1 and Theorem 3.4, we sample a set of valuations from the distribution, which is denoted by $\mathcal{S}$, and then, induce a set of symmetric samples $\widetilde{\mathcal{S}} = \{\sigma_n v \sigma_m : \sigma_n \in S_n, v \in \mathcal{S}, \sigma_m \in S_m\}$ for test.

Table 4: Additional experimental result, where "$n \times m$ *Compound*" refers that there are n bidders and m items, and the valuations are i.i.d. sampled from the compound distribution.

Method	3×1 *Compound*		5×1 *Compound*	
	Revenue	Regret	Revenue	Regret
RegretNet	0.516	< 0.001	0.329	< 0.001
EquivariantNet	0.498	< 0.001	0.311	< 0.001
RegretNet-PE	0.539	< 0.001	0.356	< 0.001

Figure 2: Allocation rule learned by RegretNet (up) and RegretNet-PE (down) for two-bidder and one-item setting. The solid regions describe the probability to allocating the item to bidder 1 (left) and bidder 2 (right). The optimal auction mechanism is described by the regions separated by the dashed black lines, where the number 0 or 1 is the probability of optimal allocation rule in the region.

For a RegretNet-PE, there is no difference between test on $\tilde{\mathcal{S}}$ and on $\mathcal{S}$, because

$$\frac{1}{n!m!L} \sum_{l=1}^{L} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} f(\sigma_n v_i \sigma_m) = \frac{1}{n!m!L} \sum_{l=1}^{L} \sum_{\sigma_n \in S_n} \sum_{\sigma_m \in S_m} f(v_i) = \frac{1}{L} \sum_{l=1}^{L} f(v_i),$$

for any permutation-equivariant function f and a RegretNet-PE is always permutation-equivariant.

To compute the best bidding v_i' for each bidder i, we first randomly initialize $\{120, 1{,}000\}$ misreports for the 5×3 settings and others, respectively, and then, perform 2,000 updates on each misreport via Adam with the same settings. Finally, we choose the best one (which induces a maximal utility of the bidder i) as the approximated best bidding v_i'.

Figure 3: Allocation rule learned by RegretNet (up) and RegretNet-PE (down) for one-bidder and two-item setting. The solid regions describe the probability of allocating the first item (left) and the second item (right). The optimal auction mechanism is described by the regions separated by the dashed black lines, where the number 0 or 1 is the probability of optimal allocation rule in the region.

B.1.4 Implementation Details

For all settings, we generate 640,000 valuations for training and 5,040 valuations for test. We train the models (RegretNet and RegretNet-PE) for up to 100 epochs with a batch size of 128 ($B = 128$) and report the early-stop results. The value of ρ is initialized as 1.0 and increased by 5 every 200 batches. For each update on ω^t, we initialize one misreport and update the misreport by Adam for each bidder with 25 steps ($R = 25$) and learning rate 0.1 ($\gamma = 0.1$). The final optimal misreports will be used to initialize the misreports for the same batch in the next epoch. We update ω^t via Adam for every batch with a learning rate of 0.001. Besides, we update λ^t every 200 batches.

B.2 Additional Experiment Results

We present additional experimental results. Each valuation v_{ij} is sampled independently from (1) a truncated normal distribution $\mathcal{N}(0.3, 0.1)$ in $[0, 1]$; (2) a compound distribution $\mathcal{N}(\frac{x_i}{6}, 0.1)$ truncated in $[0, 1]$, where x_i is sampled independently and uniformly from $\{1, 2, 3, 4, 5\}$ (cf. Setting A, [10]); and (3) a compound distribution $U[0, Sigmoid(x_i^T y_j)]$, where x_i and y_j are sampled independently and uniformly from $[-1, 1]$ (Setting C, [10]). All results are shown in Table 3 and Table 4. The revenue and ex-post regret of RegretNet and EquivariantNet in Table 4 come from the previous work [10]. In Table 4, we report the ex-post regret as "< 0.001" following the previous works.

B.3 Allocation Rules Learned by RegretNet and RegretNet-PE

In this section, we show the allocation rules learnt by RegretNet and RegretNet-PE in two-bidder, one-item setting and one-bidder, two-item setting, where the valuation is drawn from the uniform distribution $U[0, 1]$. The optimal auction mechanisms are both known.

B.3.1 Two-bidder and One-item Setting

For the two-bidder, one-item setting, the optimal mechanism is well-known as Myerson auction [20], which allocates the item to the highest bidder with receiving a payment of the maximum of the second price and the preserve price 0.5, whenever the highest bid is bigger than the preserve. The allocation rule learned by RegretNet is shown as Figure 2,

We can see the learnt allocation rule is near the optimal mechanism. Besides, the allocation rule learned by RegretNet-PE is also shown in Figure 2. The allocation rule is also near the optimal. Since they are both enough close to the optimal solution. The improvement is not significant.

B.3.2 One-bidder and Two-item Setting

The optimal mechanism is given by [18]. Same with above, we show the allocation rules that learned by RegretNet and that learned by RegretNet-PE in Figure 3. The improvement is significant. When one of the valuations is close to 0 and another is close to 1, the mechanism learned by RegretNet allocate the lower valuation item to the bidder, while the mechanism learned by RegretNet-PE and the optimal mechanism do not. This result shows RegretNet-PE is more sample-efficient.