Reinforcement Learning with a Terminator

Abstract

We present the problem of reinforcement learning with exogenous termination. We define the Termination Markov Decision Process (TerMDP), an extension of the MDP framework, in which episodes may be interrupted by an external non-Markovian observer. This formulation accounts for numerous real-world situations, such as a human interrupting an autonomous driving agent for reasons of discomfort. We learn the parameters of the TerMDP and leverage the structure of the estimation problem to provide state-wise confidence bounds. We use these to construct a provably-efficient algorithm, which accounts for termination, and bound its regret. Motivated by our theoretical analysis, we design and implement a scalable approach, which combines optimism (w.r.t. termination) and a dynamic discount factor, incorporating the termination probability. We deploy our method on high-dimensional driving and MinAtar benchmarks. Additionally, we test our approach on human data in a driving setting. Our results demonstrate fast convergence and significant improvement over various baseline approaches.

1 Introduction

The field of reinforcement learning (RL) involves an agent interacting with an environment, maximizing a cumulative reward [Puterman, 2014]. As RL becomes more instrumental in real-world applications [Lazic et al., 2018, Kiran et al., 2021, Mandhane et al., 2022], exogenous inputs beyond the prespecified reward pose a new challenge. Particularly, an external authority (e.g., a human operator) may decide to terminate the agent's operation when it detects undesirable behavior. In this work, we generalize the basic RL framework to accommodate such external feedback.

We propose a generalization of the standard Markov Decision Process (MDP), in which external termination can occur due to a non-Markovian observer. When terminated, the agent stops interacting with the environment and cannot collect additional rewards. This setup describes various real-world scenarios, including: passengers in autonomous vehicles [Le Vine et al., 2015, Zhu et al., 2020], users in recommender systems [Wang et al., 2009], employees terminating their contracts (churn management) [Sisodia et al., 2017], and operators in factories; particularly, datacenter cooling systems, or other safety-critical systems, which require constant monitoring and rare, though critical, human takeovers [Modares et al., 2015]. In these tasks, human preferences, incentives, and constraints play a central role, and designing a reward function to capture them may be highly complex. Instead, we propose to let the agent itself learn these latent human utilities by leveraging the termination events.

We introduce the Termination Markov Decision Process (TerMDP), depicted in Figure 1. We consider a terminator, observing the agent, which aggregates penalties w.r.t. a predetermined, state-dependent, yet *unknown*, cost function. As the agent progresses, unfavorable states accumulate costs that gradually increase the terminator's inclination to stop the agent and end the current episode. Receiving merely the sparse termination signals, the agent must learn to behave in the environment, adhering to the terminator's preferences while maximizing reward.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: A block diagram of the TerMDP framework. An agent interacts with an environment while an exogenous observer (i.e., terminator) can choose to terminate the agent based on previous interactions. If the agent is terminated, it transitions to a sink state where a reward of 0 is given until the end of the episode.

Our contributions are as follows. **(1)** We introduce a novel history-dependent termination model, a natural extension of the MDP framework which incorporates non-trivial termination (Section 2). **(2)** We learn the unknown costs from the implicit termination feedback (Section 3), and provide local guarantees w.r.t. every visited state. We leverage our results to construct a tractable algorithm and provide regret guarantees. **(3)** Building upon our theoretical results, we devise a practical approach that combines optimism with a cost-dependent discount factor, which we test on MinAtar [Young and Tian, 2019] and a new driving benchmark. **(4)** We demonstrate the efficiency of our method on these benchmarks as well as on human-collected termination data (Section 5). Our results show significant improvement over other candidate solutions, which involve direct termination penalties and history-dependent approaches. We also introduce a new task for RL – a driving simulation game which can be easily deployed on mobile phones, consoles, and PC [Anonymous-Authors, 2022].

2 Termination Markov Decision Process

We begin by presenting the termination framework and the notation used throughout the paper. Informally, we model the termination problem using a logistic model of past "bad behaviors". We use an unobserved state-dependent cost function to capture these external preferences. As the overall cost increases throughout time, so does the probability of termination.

For a positive integer n, we denote $[n] = \{1, \ldots, n\}$. We define the Termination Markov Decision Process (TerMDP) by the tuple $\mathcal{M}_T = (\mathcal{S}, \mathcal{A}, P, R, H, c)$, where $\mathcal{S}$ and $\mathcal{A}$ are state and action spaces with cardinality S and A, respectively, and $H \in \mathbb{N}$ is the maximal horizon. We consider the following protocol, which proceeds in discrete episodes $k = 1, 2, \ldots, K$. At the beginning of each episode k, an agent is initialized at state $s_1^k \in \mathcal{S}$. At every time step h of episode k, the agent is at state $s_h^k \in \mathcal{S}$, takes an action $a_h^k \in \mathcal{A}$ and receives a random reward $R_h^k \in [0, 1]$ generated from a fixed distribution with mean $r_h(s_h^k, a_h^k)$. A terminator overseeing the agent utilizes a cost function $c : [H] \times \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}$ that is unobserved and *unknown to the agent*. At time step h, the episode terminates with probability

$$\rho_h^k(c) = \rho\left(\sum_{t=1}^h c_t(s_t^k, a_t^k) - b\right),$$

where $\rho(x) = (1 + \exp(-x))^{-1}$ is the logistic function and $b \in \mathbb{R}$ is a bias term which determines the termination probability when no costs are aggregated. Upon termination, the agent transitions to a terminal state s_{term} which yields no reward, i.e., $r_h(s_{\text{term}}, a) = 0$ for all $h \in [H], a \in \mathcal{A}$. If no termination occurs, the agent transitions to a next state s_{h+1}^k with probability $P_h(s_{h+1}^k|s_h^k, a_h^k)$. Let $t_k^* = \min\{h : s_h^k = s_{\text{term}}\} - 1$ be the time step when the k^{th} episode was terminated. Notice that the termination probability is non-Markovian, as it depends on the entire trajectory history. We also note that, when $c \equiv 0$, the TerMDP reduces to a finite horizon MDP with discount factor $\gamma = \rho(-b)$. Finally, we note that our model allows for negative costs. Indeed, these may capture satisfactory behavior, diminishing the effect of previous mistakes, and decreasing the probability of termination.

We define a stochastic, history dependent policy $\pi_h(s_h, \tau_{1:h})$ which maps trajectories $\tau_{1:h} = (s_1, a_1, \ldots, s_{h-1}, a_{h-1})$ up to time step h (excluding) and the h^{th} states s_h to probability distributions over $\mathcal{A}$. Its value is defined by $V_h^\pi(s, \tau) = \mathbb{E}\left[\sum_{t=h}^H r_t(s_t, a_t) \,\middle|\, s_h = s, \tau_{1:h} = \tau, a_t \sim \pi_t(s_t, \tau_{1:t})\right]$.

74 With slight abuse of notation, we denote the value at the initial time step by $V_1^\pi(s)$. An optimal policy
75 π^* maximizes the value for all states and histories simultaneously [1]; we denote its value function by
76 V^*. We measure the performance of an agent by its *regret*; namely, the difference between the cumu-
77 lative value it achieves and the value of an optimal policy, $\text{Reg}(K) = \sum_{k=1}^{K} V_1^*(s_1^k) - V_1^{\pi^k}(s_1^k)$.

78 **Notations.** We denote the Euclidean norm by $\|\cdot\|_2$ and the Mahalanobis norm induced by the
79 positive definite matrix $A \succ 0$ by $\|x\|_A = \sqrt{x^T A x}$. We denote by $n_h^k(s,a)$ the number of times
80 that a state action pair (s,a) was visited at the h^{th} time step before the k^{th} episode. Similarly, we
81 denote by $\hat{X}_h^k(s,a)$ the empirical average of a random variable X (e.g., reward and transition kernel)
82 at (s,a) in the h^{th} time step, based on all samples before the k^{th} episode.

83 We assume there exists a known constant L that bounds the norm of the costs; namely,
84 $\sqrt{\sum_{s,a} \sum_{t=1}^{H} c_t^2(s_t, a_t)} \leq L$. We also denote the maximal reciprocal derivative of the logistic
85 function by $\kappa = \max_{h \in [H]} \ \max_{\{(s_t,a_t)\}_{t=1}^h \in (\mathcal{S} \times \mathcal{A})^h} \left(\dot{\rho}\left(\sum_{t=1}^{h} c_t(s_t, a_t) - b \right) \right)^{-1}$. This factor will
86 be evident in our theoretical analysis in the next section, as estimating the costs in regions of saturation
87 of the sigmoid is more difficult when the derivative nears zero. Finally, we use $\mathcal{O}(x)$ to refer to a
88 quantity that depends on x up to a poly-log expression in S, A, K, H, L, κ and $\log\left(\frac{1}{\delta}\right)$.

3 An Optimistic Approach to Overcoming Termination

90 Unlike the standard MDP setup, in the TerMDP model, the agent can potentially be terminated at
91 any time step. Consider the TerMDP model for which the costs are *known*. We can define a Markov
92 policy π_h mapping augmented states $\mathcal{S} \times \mathbb{R}$ to a probability distribution over actions, where here, the
93 state space is augmented by the accumulated costs $\sum_{t=1}^{h-1} c_t(s_t, a_t)$. There exists a policy, which
94 does not use historical information, besides the accumulated costs, and achieves the value of the
95 optimal history-dependent policy (see Appendix B). Therefore, when solving for an optimal policy
96 (e.g., by planning), one can use the current accumulated cost instead of the full trajectory history.

97 This suggests a plausible approach for solving the TerMDP – first learn the cost function, and then
98 solve the state-augmented MDP for which the costs are known. This, in turn, leads to the following
99 question: **can we learn the costs c from the termination signals?** In what follows, we answer this
100 question affirmatively. We show that by using the termination structure, one can efficiently converge
101 to the true cost function *locally* – for every state and action. We provide uncertainty estimates for the
102 state-wise costs, which allow us to construct an efficient optimistic algorithm for solving the problem.

103 **Learning the Costs.** To learn the costs, we show that the agent can effectively gain information
104 about costs even in time steps where no termination occurs. Recall that at any time step $h \in$
105 $[H-1]$, the agent acquires a sample from a Bernoulli random variable with parameter $p = \rho_h^k(c) =$
106 $\rho\left(\sum_{t=1}^{h} c_t(s_t^k, a_t^k) - b \right)$. Notably, a lack of termination, which occurs with probability $1 - \rho_h^k(c)$,
107 is also an informative signal of the unknown costs. We propose to leverage this information by
108 recognizing the costs c as parameters of a probabilistic model, maximizing their likelihood. We use
109 the regularized cross-entropy, defined for some $\lambda > 0$ by

$$\mathcal{L}_\lambda^k(c) = \sum_{k'=1}^{k} \sum_{h=1}^{H-1} \left[\mathbb{1}\{h < t_{k'}^*\} \log\left(1 - \rho_h^k(c)\right) + \mathbb{1}\{h = t_{k'}^*\} \log\left(\rho_h^k(c)\right) \right] - \lambda \|c\|_2^2. \quad (1)$$

110 By maximizing the cost likelihood in Equation (1), global guarantees of the cost can be achieved,
111 similar to previous work on logistic bandits [Zhang et al., 2016, Abeille et al., 2021]. Particularly,
112 denoting by $\hat{c}^k \in \arg\max \mathcal{L}_\lambda^k(c)$ the maximum likelihood estimates of the costs, it can be shown that
113 for any history, a global upper bound on $\left\| \hat{c}^k - c \right\|_{\Sigma_k}$ can be obtained, where the history-dependent
114 design matrix Σ_k captures the empirical correlations of visitation frequencies (see Appendix J for
115 details). Unfortunately, using $\left\| \hat{c}^k - c \right\|_{\Sigma_k}$ amounts to an intractable algorithm [Chatterji et al., 2021],
116 and thus to an undesirable result.

---

[1]Such a policy always exists; we can always augment the state space with the history, which would make the
environment Markovian and imply the existence of an optimal history-dependent policy [Puterman, 2014].

Algorithm 1 TermCRL: Termination Confidence Reinforcement Learning

---
1: **require:** $\lambda > 0$
2: **for** $k = 1, \ldots, K$ **do**
3:     **for** $(h, s, a) \in [H] \times \mathcal{S} \times \mathcal{A}$ **do**
4:       $\bar{r}_h^k(s, a) = \hat{r}_h^k(s, a) + b_k^r(h, s, a) + b_k^p(h, s, a)$
5:       $\bar{c}_h^k(s, a) = \hat{c}_h^k(s, a) - b_k^c(h, s, a)$ // Appendix H.1
6:     **end for**
7:     $\pi^k \leftarrow \text{TerMDP-Plan}\Big(\mathcal{M}_T\big(\mathcal{S}, \mathcal{A}, H, \bar{r}^k, \hat{P}^k, \bar{c}^k\big)\Big)$ // Appendix G
8:     Rollout a trajectory by acting π_k
9:     $\hat{c}^{k+1} \in \arg\max_c \mathcal{L}_\lambda^k(c)$ // Equation (1)
10:     Update $\hat{P}^{k+1}(s, a), \hat{r}^{k+1}(s, a), n^{k+1}(s, a)$ over rollout trajectory
11: **end for**

Instead, as terminations are sampled on *every time step* (i.e., non-terminations are informative signals as well), we show we can obtain a *local* bound on the cost function c. Specifically, we show that the error $\big|\hat{c}_h^k(s, a) - c_h(s, a)\big|$ diminishes with $n_h^k(s, a)$. The following result is a main contribution of our work, and the crux of our regret guarantees later on (see Appendix J for proof).

Theorem 1 (Local Cost Estimation Confidence Bound). *Let $\hat{c}^k \in \arg\max \mathcal{L}_\lambda^k(c)$ be the maximum likelihood estimate of the costs. Then, for any $\delta > 0$, with probability of at least $1 - \delta$, for all episodes $k \in [K]$, timesteps $h \in [H - 1]$ and state-actions $(s, a) \in \mathcal{S} \times \mathcal{A}$, it holds that*

$$\big|\hat{c}_h^k(s, a) - c_h(s, a)\big| \leq \mathcal{O}\bigg(\big(n_h^k(s, a)\big)^{-0.5}\sqrt{\kappa SAHL^3}\log\bigg(\frac{1}{\delta}\bigg(1 + \frac{kL}{S^2 A^2 H}\bigg)\bigg)\bigg).$$

We note the presence of κ in our upper bound, a common factor [Chatterji et al., 2021], which is fundamental to our analysis, capturing the complexity of estimating the costs. Trajectories that saturate the logistic function lead to more difficult credit assignment. Specifically, when the accumulated costs are high, any additional penalty would only marginally change the termination probability, making its estimation harder. A similar argument can be made when the termination probability is low.

3.1 Termination Confidence Reinforcement Learning

We are now ready to present our method for solving TerMDPs with unknown costs. Our proposed approach, which we call Termination Confidence Reinforcement Learning (TermCRL), is shown in Algorithm 1. Leveraging the local convergence guarantees of Theorem 1, we estimate the costs by maximizing the likelihood in Equation (1). We compensate for uncertainty in the reward, transitions, and costs by incorporating optimism. We define bonuses for the reward, transition, and cost function by $b_k^r(h, s, a) = \mathcal{O}\Big(\sqrt{\frac{\log(1/\delta)}{n_h^k(s,a)\vee 1}}\Big), b_k^p(h, s, a) = \mathcal{O}\Big(\sqrt{\frac{SH^2\log(1/\delta)}{n_h^k(s,a)\vee 1}}\Big)$, and $b_k^c(h, s, a) = \mathcal{O}\Big(\sqrt{\frac{\kappa SAHL^3}{n_h^k(s,a)\vee 1}}\log\big(\frac{1}{\delta}\big)\Big)$ for some $\delta > 0$ (see Appendix H.1 for explicit definitions).

We add the reward and transition bonuses to the estimated reward (line 4), while the optimistic cost bonus is applied directly to the estimated costs (line 5). Then, a planner (line 7) solves the optimistic MDP for which the costs are known and are given by their optimistic counterparts. We refer the reader to Appendix G for further discussion on planning in TerMDPs. The following theorem provides regret guarantees for Algorithm 1. Its proof is given in Appendix I and relies on Theorem 1 and the analysis of UCRL [Auer et al., 2008, Efroni et al., 2019].

Theorem 2. *[Regret of TermCRL] With probability at least $1 - \delta$, the regret of Algorithm 1 is*

$$\text{Reg}(K) \leq \mathcal{O}\bigg(\sqrt{\kappa S^2 A^2 H^7 L^3 K \log^2\bigg(\frac{SAHK}{\delta}\bigg)}\bigg).$$

Compared to the standard regret of UCRL [Auer et al., 2008], an additional $\sqrt{\kappa AH^4 L^3}$ multiplicative factor is evident in our result, which is due to the convergence rates of the costs in Theorem 1. Motivated by our theoretical results, in what follows we propose a practical approach, inspired by Algorithm 1, which utilizes local cost confidence intervals in a deep RL framework.

Algorithm 2 TermPG

1: **require:** window w, number of ensembles M, number of rollouts N, number of iterations K, policy gradient algorithm `ALG-PG`
2: **initialize:** $\mathcal{B}_{\text{pos}} \leftarrow \emptyset, \mathcal{B}_{\text{neg}} \leftarrow \emptyset, \pi_\theta \leftarrow$ random initialization
3: **for** $k = 1, \ldots, K$ **do**
4:     Rollout N trajectories using π_θ, $\mathcal{R} = \left\{ s_1^i, a_1^i, r_1^i, \ldots, s_{t_i^*}^i, a_{t_i^*}^i, r_{t_i^*}^i \right\}_{i=1}^N$.
5:     **for** $i = 1, \ldots, N$ **do**
6:         Add $t_i^* - 1$ negative examples $\left(s_{\max\{1, l-w+1\}}, a_{\max\{1, l-w+1\}}, \ldots, s_l, a_l \right)_{l=1}^{t^*-1}$ to $\mathcal{B}_{\text{neg}}$.
7:         Add one positive example $\left(s_{\max\{1, t^*-w+1\}}, a_{t^*-\max\{1, t^*-w+1\}}, \ldots, s_{t^*}, a_{t^*} \right)$.
8:     **end for**
9:     Train bootstrap ensemble $\{c_{\phi_m}\}_{m=1}^M$ using binary cross entropy over data $\mathcal{B}_{\text{neg}}, \mathcal{B}_{\text{pos}}$.
10:    Augment states in $\mathcal{R}$ by $s_l^i \leftarrow s_l^i \cup \sum_{j=1}^{\min\{w,l\}} \min_m c_{\phi_m}(s_{l-j}^i, a_{l-j}^i)$.
11:    Update policy $\pi_\theta \leftarrow$ `ALG-PG`$(\mathcal{R})$ with dynamic discount (see Section 4.2).
12: **end for**

---

4 Termination Policy Gradient

Following the theoretical analysis in the previous section, we propose a practical approach for solving TerMDPs. Particularly, in this section, we devise a policy gradient method that accounts for the unknown costs leading to termination. We assume a stationary setup for which the transitions, rewards, costs, and policy are time-homogeneous. Our approach consists of three key elements: learning the costs, leveraging uncertainty estimates over costs, and constructing efficient value estimates through a dynamic cost-dependent discount factor.

Algorithm 2 describes the Termination Policy Gradient (TermPG) method, which trains an ensemble of cost networks (to estimate the costs and uncertainty) over rollouts in a policy gradient framework. We represent our policy and cost networks using neural networks with parameters $\theta, \{\phi_m\}_{m=1}^M$. At every iteration, the agent rollouts N trajectories in the environment using a parametric policy, π_θ. The rollouts are split into subtrajectories which are labeled w.r.t. the termination signal, where positive labels are used for examples that end with termination. Particularly, we split the rollouts into "windows" (i.e., subtrajectories of length w), where a rollout of length t^*, which ends with termination, is split into $t^* - 1$ negative examples $\left(s_{\max\{1, l-w+1\}}, a_{\max\{1, l-w+1\}}, \ldots, s_l, a_l \right)_{l=1}^{t^*-1}$, and one positive example $\left(s_{\max\{1, t^*-w+1\}}, a_{t^*-\max\{1, t^*-w+1\}}, \ldots, s_{t^*}, a_{t^*} \right)$. Similarly, a rollout of length H which does not end with termination contains H negative examples. We note that by taking finite windows, we assume the terminator "forgets" accumulated costs that are not recent - a generalization of the theoretical TerMDP model in Section 2, for which $w = H$. In Section 5, we provide experiments of misspecification of the true underlying window width, where this model assumption does not hold.

4.1 Learning the Costs

Having collected a dataset of positive and negative examples, we train a logistic regression model consisting of an ensemble of M cost networks $\{c_{\phi_m}\}_{m=1}^M$, shared across timesteps, as depicted in Figure 2. Specifically, for an example $\left(s_{\max\{1, l-w+1\}}, a_{\max\{1, l-w+1\}}, \ldots, s_l, a_l \right)$ we estimate the termination probability by $\rho\left(\sum_{j=1}^{\min\{w,l\}} c_{\phi_m}(s_{l-j+1}, a_{l-j+1}) - b_m \right)$, where $\{b_m\}_{m=1}^M$ are learnable bias parameters. The parameters are then learned end-to-end using the cross entropy loss. We use the bootstrap method [Bickel and Freedman, 1981, Chua et al., 2018] over the ensemble of cost networks. This ensemble is later used in Algorithm 2 to produce optimistic estimates of the costs. Particularly, the agent policy π_θ uses the current state augmented by the optimistic cummulative predicted cost, i.e., $s_l^{\text{aug}} = (s_l, C_{\text{optimistic}})$, where $C_{\text{optimistic}} = \sum_{j=1}^{\min\{w,l\}} \min_m c_{\phi_m}(s_{l-j+1}, a_{l-j+1})$. Finally, the agent is trained with the augmented states using a policy gradient algorithm `ALG-PG` (e.g., PPO [Schulman et al., 2017], IMPALA [Espeholt et al., 2018]).

Figure 2: Block diagram of the cost training procedure. Rollouts are split into subtrajectories, labeled according to whether they end in termination. Given the dataset of labeled subtrajectories, an ensemble of M cost networks is trained end-to-end using cross-entropy with bootstrap samples (all time steps share the same ensemble).

4.2 Optimistic Dynamic Discount Factor

While augmenting the state with the optimistic accumulated costs is sufficient for obtaining optimality, we propose to further leverage these estimates more explicitly – noticing that the finite horizon objective we are solving can be cast to a discounted problem. Particularly, it is well known that the discount factor $\gamma \in (0,1)$ can be equivalently formulated as the probability of "staying alive" (see the discounted MDP framework, Puterman [2014]). Similarly, by augmenting the state s with the accumulated cost $C_h = \sum_{t=1}^{h} c(s_t, a_t)$, we view the probability $1 - \rho(C_h)$ as a state-dependent discount factor, capturing the probability of an agent in a TerMDP to not be terminated.

We define a dynamic, cost-dependent discount factor for value estimation. We use the state-action value function $Q(s, a, C)$ over the augmented states, defined for any s, a, C by $Q^\pi(s, a, C) = \mathbb{E}_\pi \Big[\sum_{t=1}^{H} \Big(\prod_{h=1}^{t} \gamma_h \Big) r(s_t, a_t) \,\Big|\, s_1 = s, a_1 = a, C_1 = C \Big]$, where $\gamma_h = 1 - \rho\Big(C + \sum_{i=2}^{h-1} c(s_i, a_i) - b\Big)$. This yields the Termination Bellman Equations $Q^\pi(s, a, C) = r(s, a) + (1 - \rho(C))\mathbb{E}_{s' \sim P(\cdot|s,a), a' \sim \pi(s')}[Q^\pi(s', a', C + c(s', a'))]$ (see Appendix C for derivation). To incorporate uncertainty in the estimated costs, we use the optimistic accumulated costs $C_{\text{optimistic}} = \sum_{j=1}^{\min\{w,l\}} \min_m c_{\phi_m}(s_{l-j+1}, a_{l-j+1})$. Then, the discount factor becomes $\gamma(C_{\text{optimistic}}) = 1 - \rho(C_{\text{optimistic}} - b)$. Assuming that, w.h.p., optimistic costs are smaller than the true costs, the discount factor decreases as the agent exploits previously visited states.

The dynamic discount factor allows us to obtain a more accurate value estimator. In particular, we leverage the optimistic cost-dependent discount factor $\gamma(C_{\text{optimistic}})$ in our value estimation procedure, using Generalized Advantage Estimation (GAE, Schulman et al. [2015]). As we will show in the next section, using the optimistic discount factor significantly improves overall performance.

5 Experiments

In this section we evaluate the strength of our approach, comparing it to several baselines, including: **(1) PG (naive):** The standard policy gradient without additional assumptions, which ignores termination. **(2) Recurrent PG:** The standard policy gradient with a history-dependent recurrent policy (without cost estimation or dynamic discount factor). As the history is a sufficient statistic of the costs, the optimal policy is realizable. **(3) PG with Reward Shaping (RS):** We penalize the reward upon termination by a constant value, i.e., $r(s, a) - p\mathbb{1}\{s_{\text{term}}\}$, for some $p > 0$. This approach can be applied to any variant of Algorithm 2 or the methods listed above. **(4) TermPG:** Described in Algorithm 2. We additionally implemented two variants of TermPG, including: **(5) TermPG with Reward Shaping:** We penalize the reward with a constant value upon termination. **(6) TermPG with Cost Penalty:** We penalize the reward at every time step by the optimistic cost estimator, i.e., $r - \alpha C_{\text{optimistic}}$ for some $\alpha > 0$. All TermPG variants used an ensemble of three cost networks, and a

Figure 4: Mean reward with std. over five seeds of "Backseat Driver". Left: coin avoidance; right: human termination. Variants with reward shaping (RS, orange and brown) penalize the agent with a constant value upon termination. The recurrent PG variant (green) uses a history-dependent policy without learning costs. The TermPG+Penalty variant (purple) penalizes the reward at every time step using the estimated costs.

dynamic cost-dependent discount factor, as described in Section 4.2. We report mean and std. of the total reward (without penalties) for all our experiments.

Backseat Driver (BDr). We simulated a driving applica-
tion, using MLAgents [Juliani et al., 2018], by developing
a new driving benchmark, "Backseat Driver" [Anonymous-
Authors, 2022] (depicted in Figure 3), where we tested
both synthetic and human terminations. The game consists
of a five lane never-ending road, with randomly instanti-
ating vehicles and coins. The agent can switch lanes and
is rewarded for overtaking vehicles. In our experiments,
states were represented as top view images containing the
position of the agent, nearby cars, and coins with four
stacked frames. We used a finite window of length 120
for termination (30 agent decision steps), mimicking a
passenger forgetting mistakes of the past.

Figure 3: Backseat Driver

BDr Experiment 1: Coin Avoidance. In the first experiment of Backseat Driver, coins are considered
as objects the driver must avoid. The coins signify unknown preferences of the passenger, which are
not explicitly provided to the agent. As the agent collects coins, a penalty is accumulated, and the
agent is terminated probabilistically according to the logistic cost model in Section 2. We emphasize
that, while the coins are visible to the agent (i.e., part of the agent's state), the agent only receives
feedback from collecting coins through implicit terminations.

Results for Backseat Driver with coin-avoidance termination are depicted in Figure 4. We compared
TermPG (pink) and its two variants (brown, purple) to the PG (blue), recurrent PG (green), and
reward shaping (orange) methods described above. Our results demonstrate that TermPG significantly
outperforms the history-based and penalty-based baselines. We found TermPG (pink) to perform
significantly better, doubling the reward of the best PG variant. All TermPG variants converged
quickly to a good solution, suggesting fast convergence of the costs (see Appendix E).

BDr Experiment 2: Human Termination. To complement our results, we evaluated human
termination on Backseat Driver. For this, we generated data of termination sequences from agents of
varying quality (ranging from random to expert performance). We asked five human supervisors to
label subsequences of this data by terminating the agent in situations of "continual discomfort". This
guideline was kept ambiguous to allow for diverse termination signals. The final dataset consisted of
512 termination examples. We then trained a model to predict human termination and implemented
it into Backseat Driver to simulate termination. We refer the reader to Appendix D for specific
implementation details. Figure 4 shows results for human termination in Backseat Driver. As before,
a significant performance increase was evident in our experiments. Additionally, we found that using
a cost penalty (purple) or termination penalty (brown) for TermPG did not greatly affect performance.

MinAtar. We further compared our method to the PG, recurrent PG, and reward shaping methods,
on MinAtar [Young and Tian, 2019]. For each environment, we defined cost functions that do not

Figure 5: Results for MinAtar benchmarks. All runs were averaged over five seeds. Comparison of best performing TermPG variant to best performing PG variant (relative improvement percentage): 80% in Space Invaders, 150% in Seaquest, 410% in Breakout, and 90% in Asterix.

Table 1: Summary of results (top) and ablations for TermPG (bottom). Standard deviation optimism did not have significant impact on performance. Removing optimism or the dynamic discount factor had negative impact on performance. TermPG was found to be robust to model misspecifcations of the accumulated cost window.

	Backseat Driver		MinAtar			
Experiment	Coin Avoid.	Human	Space Inv.	Seaquest	Breakout	Asterix
PG	5.3 ± 0.8	4.9 ± 1.5	5.2 ± 1.8	0.6 ± 0.4	1.4 ± 2.8	0.8 ± 0.3
Recurrent PG	3.4 ± 0.21	5 ± 1.8	2.8 ± 0.05	0.1 ± 0.3	0.7 ± 0.6	0.7 ± 0.2
PG + RS	5.9 ± 1.4	7.4 ± 1.7	7.6 ± 2.3	0.4 ± 0.2	0.5 ± 0.03	0.9 ± 0.2
TermPG (ours)	$\mathbf{8.7 \pm 1.4}$	8.3 ± 1.3	$\mathbf{9.7 \pm 1.1}$	$\mathbf{1.4 \pm 0.8}$	$\mathbf{8.2 \pm 0.3}$	1 ± 0.2
TermPG + RS (ours)	$\mathbf{8.4 \pm 1.3}$	7.7 ± 0.3	$\mathbf{11.8 \pm 0.8}$	0.3 ± 0.6	5.1 ± 1	0.8 ± 0.1
TermPG + Penalty (ours)	6 ± 0.8	$\mathbf{11.8 \pm 1.5}$	7.7 ± 1.4	$\mathbf{2.4 \pm 1}$	2.3 ± 2.3	$\mathbf{1.7 \pm 0.1}$
Ablation Test	Coin Avoid.	Human	Space Inv.	Seaquest	Breakout	Asterix
Optimism with Ensemble Std.	7.6 ± 2.1	7.5 ± 1.1	2.8 ± 0.02	0.9 ± 0.6	10.9 ± 1	1 ± 0.1
No Optimism	7.8 ± 1.3	8.8 ± 1.2	5.2 ± 1.6	0.7 ± 0.3	1.3 ± 0.7	1 ± 0.1
No Dynamic Discount	6.9 ± 0.6	5.9 ± 0.7	4.4 ± 1.8	0.4 ± 0.1	0.5 ± 0.02	0.8 ± 0.1
$\times 0.5$ Window Misspecification	7.2 ± 1.1	7.2 ± 0.5	9.7 ± 3.1	2.4 ± 0.4	7.9 ± 0.8	0.8 ± 0.1
$\times 2$ Window Misspecification	8.3 ± 0.1	8.4 ± 0.2	11.1 ± 3	2.2 ± 0.2	10.3 ± 0.8	1 ± 0.1

necessarily align with the pre-specified reward, to mimic uncanny behavior that humans are expected to dislike. For example, in Breakout, the agent was penalized whenever the paddle remained in specific regions (e.g., sides of the screen), whereas in Space Invaders, the agent was penalized for "near misses" of enemy bullets. We refer the reader to Appendix D for specific details of the different termination cost functions.

Figure 5 depicts results on MinAtar. As with Backseat Driver, TermPG lead to significant improvement, often achieving a magnitude order as much reward as Recurrent PG. We found that adding a termination penalty and cost penalty produced mixed results, with them being sometimes useful (e.g., Space Invaders, Sequest, Asterix), yet other times harmful to performance (e.g., Breakout). Therefore, we propose to fine-tune these penalties in Algorithm 2. Finally, we note that training TermPG was, on average, 67% slower than PG, on the same machine. Nevertheless, though TermPG was somewhat more computationally expensive, it showed a significant increase in overall performance. A summary of all of our results is presented in Table 1 (top).

Ablation Studies. We present various ablations for TermPG in Table 1 (bottom). First, we tested the effect replacing the type of cost optimism in TermPG. In Section 4, cost optimism was defined

using the minimum of the cost ensemble, i.e., $\min\{c_{\phi_m}\}$. Instead, we replaced the cost optimism to $C_{\text{optimistic}} = \text{mean}\{c_{\phi_m}\} - \alpha\text{std}\{c_{\phi_m}\}$, testing different values of α. Surprisingly, this change mostly decreased performance, except for Breakout, where it performed significantly better. Other ablations included removing optimism altogether (i.e., only using the mean of the ensemble), and removing the dynamic discount factor. In both cases we found a significant decrease in performance, suggesting that both elements are essential for TermPG to work properly and utilize the estimator of the unknown costs. Finally, we tested misspecifications of our model by learning with windows that were different from the environment's real cost accumulation window. In both cases, TermPG was suprisingly robust to window misspecification, as performance remained almost unaffected by it.

6 Related Work

Our setup can be linked to various fields, as listed below.

Constrained MDPs. Perhaps the most straightforward motivations for external termination stems from constraint violation [Chow et al., 2018, Efroni et al., 2020a, HasanzadeZonuzy et al., 2020], where strict or soft constraints are introduced to the agent, who must learn to satisfy them. In these setups, which are often motivated by safety [Garcıa and Fernández, 2015], the constraints are usually known. In contrast, in this work, the costs are *unknown* and only implicit termination is provided.

Reward Design. Engineering a good reward function is a hard task, for which frequent design choices may drastically affect performance [Oh et al., 2021]. Moreover, for tasks where humans are involved, it is rarely clear how to engineer a reward, as human preferences are not necessarily known, and humans are non-Markovian by nature [Clarke et al., 2013, Christiano et al., 2017]. Termination can thus be viewed as an efficient mechanism to elicit human input, allowing us to implicitly interpret human preferences and utility more robustly than trying to specify a reward.

Global Feedback in RL. Recent work considered once-per-trajectory reward feedback in RL, observing either the cumulative rewards at the end of an episode [Efroni et al., 2020b, Cohen et al., 2021] or a logistic function of trajectory-based features Chatterji et al. [2021]. While these works are based on a similar solution mechanism, our work concentrates on a new framework, which accounts for non-Markovian termination. Additionally, we provide per-state concentration guarantees of the unknown cost function, compared to global concentration bounds in previous work [Abbasi-Yadkori et al., 2011, Zhang et al., 2016, Qi et al., 2018, Abeille et al., 2021]. Using our local guarantees, we are able to construct a scalable policy gradient solution, with significant improvement over recurrent and reward shaping based approaches.

Preference-based RL. In contrast to traditional reinforcement learning, preference-based reinforcement learning (PbRL) relies on subjective opinions rather than numerical rewards. In PbRL, preferences are captured through probabilistic rankings of trajectories [Wirth et al., 2016, 2017, Xu et al., 2020]. Similar to our work, Christiano et al. [2017] use a regression model to learn a reward function that could account for the preference feedback. Our work considers a different setting in which human feedback is provided through termination, where termination and reward may not align.

7 Limitations and Negative Societal Impact

A primary limitation of our work involves the linear dependence of the logistic termination model. In some settings, it might be hard to capture true human preferences and behaviors using a linear model. Nevertheless, when measured across the full trajectory, our empirical findings show that this model is highly expressive, as we demonstrated on real human termination data (Section 5). Additionally, we note that work in inverse RL [Arora and Doshi, 2021] also assumes such linear dependence of human decisions w.r.t. reward. Future work can consider more involved hypothesis classes, building upon our work to identify the optimal tradeoff between expressivity and convergence rate.

Finally, we note a possible negative societal impact of our work. Termination is strongly motivated by humans interacting with the agent. This may be harmful if not carefully controlled, as learning incorrect or biased preferences may, in turn, result in unfavorable consequences, or if humans engage in adversarial behavior in order to mislead an agent. Our work discusses initial research in this domain. We encourage caution in real-world applications, carefully considering the possible effects of model errors, particularly in applications that affect humans.

References

Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. *Advances in neural information processing systems*, 24, 2011.

Marc Abeille, Louis Faury, and Clément Calauzènes. Instance-wise minimax-optimal algorithms for logistic bandits. In *International Conference on Artificial Intelligence and Statistics*, pages 3691–3699. PMLR, 2021.

Anonymous-Authors. Backseat driver. `https://github.com/will/be/included/in/final/print`, 2022.

Saurabh Arora and Prashant Doshi. A survey of inverse reinforcement learning: Challenges, methods and progress. *Artificial Intelligence*, 297:103500, 2021.

Peter Auer, Thomas Jaksch, and Ronald Ortner. Near-optimal regret bounds for reinforcement learning. *Advances in neural information processing systems*, 21, 2008.

KV Bhagwat and R Subramanian. Inequalities between means of positive operators. In *Mathematical Proceedings of the Cambridge Philosophical Society*, volume 83, pages 393–401. Cambridge University Press, 1978.

Peter J Bickel and David A Freedman. Some asymptotic theory for the bootstrap. *The annals of statistics*, 9(6):1196–1217, 1981.

Niladri Chatterji, Aldo Pacchiano, Peter Bartlett, and Michael Jordan. On the theory of reinforcement learning with once-per-episode feedback. *Advances in Neural Information Processing Systems*, 34, 2021.

Yinlam Chow, Ofir Nachum, Edgar Duenez-Guzman, and Mohammad Ghavamzadeh. A Lyapunov-based approach to safe reinforcement learning. *Advances in neural information processing systems*, 31, 2018.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30, 2017.

Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. *Advances in neural information processing systems*, 31, 2018.

AM Clarke, Johannes Friedrich, Walter Senn, EM Tartaglia, Silvia Marchesotti, and Michael H Herzog. Human learning in non-markovian decision making, 2013.

Alon Cohen, Haim Kaplan, Tomer Koren, and Yishay Mansour. Online markov decision processes with aggregate bandit feedback. In *Conference on Learning Theory*, pages 1301–1329. PMLR, 2021.

Christoph Dann, Tor Lattimore, and Emma Brunskill. Unifying pac and regret: Uniform pac bounds for episodic reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 5713–5723, 2017.

Yonathan Efroni, Nadav Merlis, Mohammad Ghavamzadeh, and Shie Mannor. Tight regret bounds for model-based reinforcement learning with greedy policies. *Advances in Neural Information Processing Systems*, 32, 2019.

Yonathan Efroni, Shie Mannor, and Matteo Pirotta. Exploration-exploitation in constrained mdps. *arXiv preprint arXiv:2003.02189*, 2020a.

Yonathan Efroni, Nadav Merlis, and Shie Mannor. Reinforcement learning with trajectory feedback. *arXiv preprint arXiv:2008.06036*, 2020b.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Vlad Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. In *International Conference on Machine Learning*, pages 1407–1416. PMLR, 2018.

Javier Garcıa and Fernando Fernández. A comprehensive survey on safe reinforcement learning. *Journal of Machine Learning Research*, 16(1):1437–1480, 2015.

Aria HasanzadeZonuzy, Dileep M Kalathil, and Srinivas Shakkottai. Learning with safety constraints: Sample complexity of reinforcement learning for constrained mdps. *arXiv preprint arXiv:2008.00311*, 2020.

Arthur Juliani, Vincent-Pierre Berges, Ervin Teng, Andrew Cohen, Jonathan Harper, Chris Elion, Chris Goy, Yuan Gao, Hunter Henry, Marwan Mattar, et al. Unity: A general platform for intelligent agents. *arXiv preprint arXiv:1809.02627*, 2018.

B Ravi Kiran, Ibrahim Sobh, Victor Talpaert, Patrick Mannion, Ahmad A Al Sallab, Senthil Yogamani, and Patrick Pérez. Deep reinforcement learning for autonomous driving: A survey. *IEEE Transactions on Intelligent Transportation Systems*, 2021.

Nevena Lazic, Craig Boutilier, Tyler Lu, Eehern Wong, Binz Roy, MK Ryu, and Greg Imwalle. Data center cooling using model-predictive control. *Advances in Neural Information Processing Systems*, 31, 2018.

Scott Le Vine, Alireza Zolfaghari, and John Polak. Autonomous cars: The tension between occupant experience and intersection capacity. *Transportation Research Part C: Emerging Technologies*, 52: 1–14, 2015.

Amol Mandhane, Anton Zhernov, Maribeth Rauh, Chenjie Gu, Miaosen Wang, Flora Xue, Wendy Shang, Derek Pang, Rene Claus, Ching-Han Chiang, et al. Muzero with self-competition for rate control in vp9 video compression. *arXiv preprint arXiv:2202.06626*, 2022.

Hamidreza Modares, Isura Ranatunga, Frank L Lewis, and Dan O Popa. Optimized assistive human–robot interaction using reinforcement learning. *IEEE transactions on cybernetics*, 46(3):655–667, 2015.

Inseok Oh, Seungeun Rho, Sangbin Moon, Seongho Son, Hyoil Lee, and Jinyun Chung. Creating pro-level ai for a real-time fighting game using deep reinforcement learning. *IEEE Transactions on Games*, 2021.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Yi Qi, Qingyun Wu, Hongning Wang, Jie Tang, and Maosong Sun. Bandit learning with implicit feedback. *Advances in Neural Information Processing Systems*, 31, 2018.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Dilip Singh Sisodia, Somdutta Vishwakarma, and Abinash Pujahari. Evaluation of machine learning models for employee churn prediction. In *2017 international conference on inventive computing and informatics (icici)*, pages 1016–1020. IEEE, 2017.

Yi-Fan Wang, Ding-An Chiang, Mei-Hua Hsu, Cheng-Jung Lin, and I-Long Lin. A recommender system to avoid customer churn: A case study. *Expert Systems with Applications*, 36(4):8071–8075, 2009.

Tsachy Weissman, Erik Ordentlich, Gadiel Seroussi, Sergio Verdu, and Marcelo J Weinberger. Inequalities for the l1 deviation of the empirical distribution. *Hewlett-Packard Labs, Tech. Rep*, 2003.

Christian Wirth, Johannes Fürnkranz, and Gerhard Neumann. Model-free preference-based reinforcement learning. In *Thirtieth AAAI Conference on Artificial Intelligence*, 2016.

Christian Wirth, Riad Akrour, Gerhard Neumann, Johannes Fürnkranz, et al. A survey of preference-based reinforcement learning methods. *Journal of Machine Learning Research*, 18(136):1–46, 2017.

Yichong Xu, Ruosong Wang, Lin Yang, Aarti Singh, and Artur Dubrawski. Preference-based reinforcement learning with finite-time guarantees. *Advances in Neural Information Processing Systems*, 33:18784–18794, 2020.

Kenny Young and Tian Tian. Minatar: An atari-inspired testbed for thorough and reproducible reinforcement learning experiments. *arXiv preprint arXiv:1903.03176*, 2019.

Lijun Zhang, Tianbao Yang, Rong Jin, Yichi Xiao, and Zhi-Hua Zhou. Online stochastic linear optimization under one-bit feedback. In *International Conference on Machine Learning*, pages 392–401. PMLR, 2016.

Meixin Zhu, Yinhai Wang, Ziyuan Pu, Jingyun Hu, Xuesong Wang, and Ruimin Ke. Safe, efficient, and comfortable velocity control based on reinforcement learning for autonomous driving. *Transportation Research Part C: Emerging Technologies*, 117:102662, 2020.