Hijacking Robot Teams Through Adversarial Communication

Abstract:

Communication is often necessary for robot teams to collaborate and complete a decentralized task. Multi-agent reinforcement learning (MARL) systems allow agents to learn how to collaborate and communicate to complete a task. These domains are ubiquitous and include safety-critical domains such as wildfire fighting, traffic control, or search and rescue missions. However, critical vulnerabilities may arise in communication systems as jamming the signals can interrupt the robot team. This work presents a framework for applying black-box adversarial attacks to learned MARL policies by manipulating only the communication signals between agents. Our system only requires observations of MARL policies after training is complete, as this is more realistic than attacking the training process. To this end, we imitate a learned policy of the targeted agents without direct interaction with the environment or ground truth rewards. Instead, we infer the rewards by only observing the behavior of the targeted agents. Our framework reduces reward by 201% compared to an equivalent baseline method and also shows favorable results when deployed in real swarm robots. Our novel attack methodology within MARL systems contributes to the field by enhancing our understanding on the reliability of multi-agent systems.

Keywords: Adversarial Attacks, Multi-Agent Reinforcement Learning

1 Introduction

Effective communication among robots is essential for information exchange, collaboration, and collective decision-making. It plays a vital role in various robotics domains, including collaborative manipulation [1] and multi-robot navigation [2]. Ensuring reliable and secure communication is crucial for maintaining the overall system's performance, safety, and integrity.

Multi-agent reinforcement learning (MARL) has been a powerful tool to train agents in complex domains but the literature is lacking in studies about the vulnerabilities and defenses of these systems. MARL techniques that utilize communication have been widely applied to scenarios where multiple agents need to collaborate for a shared goal in robotics tasks such as autonomous driving [3, 4, 5] and path planning [2, 6, 7]. Researchers examined various aspects of communication in MARL, including when to communicate [8], who to communicate with [9], and different types of graph-structured communication [10, 11]. Some of these frameworks use binarized communication to pursue Low-Size, -Weight, and -Power (Low-SWAP) systems [11] which causes agents to communicate in a highly efficient manner. Malicious actors can compromise these systems and endanger the lives of many [12].

There are only a few works that assume the communication channel can be imperfect [13] or can be attacked [14] paralleling with its computer vision counterpart [15, 16, 17, 18, 19], which makes it crucial to understand these weaknesses such that we can create appropriate defense mechanisms.

Figure 1: How does the communication channel work?

In this work, we learn to attack the communication signals within a multi-robot team discretely without any trace of the training process on the target robots. First, we learn surrogate policies from observing the observation, messages, and actions of the target robots. Second, we estimate the agent rewards from their behaviors instead of using rewards from the environment. Finally, we use an actor-critic framework completely offline to learn how to hijack the targeted system. Our method requires the least prior knowledge as compared to prior work and results in robots traversing to the wrong location and drastically hindering team performance.

Contributions:

1. We propose an actor-critic framework that enables our adversarial policy to learn without direct interaction with the target agents or the environment nor the ground truth agent reward. Our framework manipulates the behaviors of target robots by attacking the communication through learned surrogate policies. Additionally, we introduce a differentiable framework for training adversarial communication policies that can modify digital communication signals [10, 11].

2. We demonstrate the effectiveness of our algorithm in three distinct multi-agent domains: predator-capture-prey, partially observable predator-prey, and speaker-listener. Across these domains, our method surpasses the baseline approach by reducing the reward of the target agents by 465% compared to a baseline approach.

3. We validate the applicability of our algorithm on physical swarm robots in the Robotarium [20]. By acting as a strong adversary, our method reduces the reward achieved by the target agents by an average of 201% across all three environments compared to a baseline strategy, which employs an equivalent random flipping approach.

2   Related Work

We describe how multi-agent reinforcement learning can be used to control robots in a Dec-POMDP setting. We provide an overview of the role of communication in a MARL framework and highlight the vulnerability of communication to adversarial attacks, leading to potential system failures and safety risks.

2.1   Multi-Agent Reinforcement Learning

In recent years, communication has played a crucial role in enhancing coordination and collaboration among robots in multi-agent reinforcement learning (MARL) frameworks [8, 9, 10, 21, 11, 22, 23]. Compared to previous works in learning policies [24, 25], recent MARL frameworks have enabled learning in more complex environments and train multiple agents. These MARL communication frameworks have been used in several robotics applications such as multi-robot path planning [2] and cooperative driving [26]. Various approaches have been proposed, including trainable differentiable communication channels [21, 22], partially observable environments [23], and soft-attention networks for selective communication [8, 9]. However, the effectiveness of communication is threatened by adversarial attacks, which can lead to system failures and safety risks, particularly in domains like self-driving vehicles [27]. This paper aims to evaluate the robustness of communication in MARL systems, building upon prior advancements in communication techniques of the binarized

communication approach [11] that improves bandwidth efficiency. Key to note is that our adversarial policy does not make any assumptions on targets other than inter-agent binarized communication. Our adversarial attack can hypothetically be utilized in any framework as long as we can learn good surrogate policies of target agents. We aim to show the generality of our approach in future work.

2.2 Adversarial Attacks in MARL and Communication

Adversarial attacks were first studied within the context of computer vision, where small perturbations to the input could induce faulty outputs [18]. Adversarial attacks aim to deteriorate model performance in tasks like classification [16, 17, 19], segmentation [28, 29, 30], or object detection [31, 32]. These ideas were later extended to reinforcement learning [33, 34], altering agent actions through perturbations in environment observations [35].

In adversarial attacks, two common categories are white-box attacks, which assume knowledge of neural network weights, and black-box attacks, which assume limited model parameter information. White-box attacks typically optimize objectives using methods such as Fast Gradient Sign Method (FGSM) [16, 17] or Projected Gradient Descent (PGD) [19]. Meanwhile, black-box attacks rely on surrogate models that approximate decision boundaries such that the adversarial attacking targeting on it could be transferred to the original models. Input-output pairs in black-box scenarios can also be augmented by FGSM [18] or PGD [19] to generate a synthetic dataset that induces similar decision boundaries. We utilize black box attacks with augmentation similar to FGSM for first-order approximation of our surrogate models.

Prior work [36] has trained an adversarial communication protocol in a multi-agent setting by using a reinforcement learning agent to optimize the adversarial policy. However, this approach requires direct interaction with the environment and is impractical as the training process would be easily detected by observers of the system. To address this limitation, we propose a black box setting and employ transfer attacks [37], training a surrogate model to mimic the target model. Furthermore, our work distinguishes itself by assuming a "man-in-the-middle" attack, where an interceptor subtly flips the aggregated binarized communication vectors. This is in contrast to previous assumptions of a single target victim agent with a limited number ($\leq \frac{N-1}{2}$) of potentially malicious messages [14].

3   Problem Formulation

We ground our problem in a Decentralized Partially Observable Markov Decision Process (Dec-POMDP) formalism which is a 10-tuple of $\langle S, M, A, P, R, \Upsilon, O, C, N, \gamma \rangle$. S is the state set of the environment and M is the message state set. For each agent $i \in N := 1, ..., N$, the agent chooses an action $a_i \in A$ at state $s_i \in S$. The transition function is denoted by $P(S'|S, A)$. Each agent has its own reward based on global state-actions $r_i = R_i(S, A)$ and $\gamma \in [0, 1)$ as the discount factor. Since the environment is partially observable, each agent also has its own individual partial observation $v_i \in \Upsilon$ which is produced by the observation function $\Upsilon = O(S)$. Agents can have two policies: an action policy $\pi_i^a(a_i|\tau_i)$ and a message policy $\pi_i^c(m_i^{out}|\tau_i)$. These are both conditioned on their own partial observations and the messages received from other communicative agents $\tau_i = \{v_i, M \backslash m_i\}$.

Figure 2: Overview of our adversarial attack during test-time.

114 We model a single adversarial policy $\pi^{adv}(\delta|\Upsilon, M^{out})$ that has access to the partial observations Υ,
115 message outputs M^{out} of all agents and produces adversarial signal δ. The partial observations could
116 be gathered by the adversary by shadowing the relevant targeted agents. Then we get a malicious
117 revised communication M^{adv} by compounding δ with the original messages M^{out} that are sent to
118 each agent in some way: $M^{adv} = \delta \odot M^{out}$. Figure 2 shows how the adversarial policy π^{adv}
119 influences the target policies. Here we consider the transition and policies as deterministic ones:
120 $S' = P(S, A)$, $a_i = \pi_i^a(\tau_i)$, $m_i^{out} = \pi_i^c(\tau_i)$ and $\delta = \pi^{adv}(\Upsilon, M^{out})$.

4 Methodology

122 In this section, we define the design choices for training our adversarial communication policy. The
123 goal of the policy is to minimize the reward of the victim agents while minimizing the difference
124 between the original and tampered communication vector. Algorithm 1 provides an overview of our
125 overall training procedure: 1) Learning a surrogate policy, 2) Learning an actor-critic for the ad-
126 versarial policy, and 3) Updating the actor with differentiable binary communication. We presume
127 access to the observations, messages, and actions of the target agents, assuming that we have suc-
128 cessfully intercepted the communication protocol of the multi-agent system. However, we do not
129 assume access to ground truth rewards. We also assume a binary communication channel but further
130 studies could extend our work to remove this assumption.

Algorithm 1: Adversarial Communication Pseudocode

Input: $\mathcal{D}(\Upsilon, M, A)$
for $i = 0, 1, 2 ...$ **do**
    for *agent j=1 to N* **do**
        Sample batch $v_j, m_j, a_j, v'_j, m'_j, d \sim \mathcal{D}$
        Update the surrogate policy $\pi_j^{surr}(a_j|v_j, m_j)$
    end
    Compute targets

$$R^{adv} = -\frac{1}{N} \sum_j log(\pi_j^{surr}(a_j|v_j, m_j)) \tag{1}$$

$$y = R^{adv} + \gamma Q_{\phi, trgt}(\Upsilon', A')|_{A'=\Pi_{trgt, surr}^a(\tau_i')} \tag{2}$$

    Update the adversarial critic with one step of gradient descent

$$\phi \leftarrow \phi - \nabla_\phi (Q_\phi(\Upsilon, A) - y)^2) \tag{3}$$

    Update the adversarial policy with one step of gradient descent

$$\theta \leftarrow \theta + \nabla_\theta (Q_\phi(\Upsilon, A^{adv}) - \mathcal{C}_{flip})|_{A^{adv}=\Pi_{\theta, surr}^a(v_j, m_j^{adv}), M^{adv}=\delta \odot M^{out}, \delta=\pi^{adv}(\Upsilon, M^{out})} \tag{4}$$

end

---

131 First, we train surrogate policies to imitate the real policies (Section 4.1). We can then learn a Q-
132 function for the adversarial policy by assigning rewards based upon the surrogate policies (Eq. 1)
133 and using the Bellman equation to update the critic (Eq. 2, 3). Details are described in Section 4.3.
134 Finally, the adversarial policy is updated with the differentiable binary flipping mechanism (Eq. 4)
135 and described in Section 4.2.

4.1 Learning a Surrogate Policy

137 As our method is a black-box attack, we assume we do not have access to the ground truth policies
138 of the agents we are attacking. To this end, we learn a *surrogate policy (π^{surr})* for each agent
139 we are attacking, where we assume access to a dataset $\mathcal{D}(\Upsilon, M, A)$ consisting of observations,

communication, action pairs from victim agents. The surrogate policies are used in two ways as described in the next section: 1) as a reward signal to learn a critic and 2) as a mechanism to simulate the adversarial output into real agent actions. To obtain a similar first-order approximation of our surrogate policies to the real policies, we augment our dataset with neighboring data by adding small Gaussian noise to each input to produce augmented input-output pairs. We find that this augmentation is enough to obtain a useful surrogate policy and thus there is no need to achieve higher precision using much more complicated methods like FSGM augmenting [18]. We use behavioral cloning methods to minimize the log-likelihood between actions given the agent observations and messages from other agents ($\log p(a|v, m)$).

4.2 Differentiable Targeting of Binary Communication Channels

In binary communication, each bit has two states: 0 and 1. Modifying a bit involves flipping it to the other state. To make this process differentiable, we need to parameterize it similarly to its continuous counterpart. We define the adversarial modification M^{adv} as the sum of the original communication vector M^{out} and the parameterized modification δ [36].

Two methods are available to parameterize the adversarial policy. One method is to directly output the adversarially revised communication vector as $M^{adv} = \delta = \pi^{adv}(M^{out}, v)$, which we call the "direct" form. The second method is called "flipping" whose adversarial policy output δ is used to indicate which digit to flip such that we can write it in an XOR form using boolean algebra as in Equation 5 where $\cdot$ means pointwise multiplication.

$$M^{adv} = \delta \cdot \overline{M^{out}} + \overline{\delta} \cdot M^{out} = \delta \cdot (1 - M^{out}) + (1 - \delta) \cdot M^{out} \tag{5}$$

We translate the flipping process into a basic algebraic form, which can be implemented with Gumbel Softmax.

4.3 Learning an Actor-Critic for Adversarial Communication

Our goal for the adversarial policy is to **secretly** train itself without any interaction with the environment in a black-box setting such that the adversarial training process does not induce any abnormalities and cannot be detected. This requirement raises a higher standard than recent work [36], where the adversarial policy is trained with reinforcement learning and requires environment interactions of the adversarial policy's actions. We adapt the actor-critic framework to learn 1) a critic ($Q_\phi(\Upsilon, A)$) that is learned within the observation-action (Υ, A) space of the target agents and 2) an actor policy that distorts the communication messages. We use the actor-critic framework as it allows us to utilize the original Dec-POMDP of the target agents for the critic rather than building a new separate MDP within the space of the observations and messages as actions. We train our Q-function $Q_\phi(\Upsilon, A)$ to use the observation-actions of all agents in the environment based on the Bellman equation and TD error as shown in Equation 6.

$$\mathcal{L}(\phi_i) = \mathbf{E}_{\Upsilon, A, R^{adv}, \Upsilon'}[(Q(\Upsilon, A) - y)^2], \ y = R^{adv} + \gamma Q_{\phi, targ}(\Upsilon', A')|_{A' = \Pi^a_{trgt, surr}(\tau'_i)}. \tag{6}$$

A question naturally arises: how do we get the reward R^{adv} to train this Q-function? Because we do not assume access to ground-truth rewards as previous literature does, we cannot utilize the negative mean of all agent reward $R^{adv} = -\frac{1}{N}\sum_{i=1}^{N} r_i$ to optimally degrade performance on their own metrics. Instead, we assign the reward for a certain state-action pair of all agents to be the inverse of the log probability of the optimal action from the surrogate policy (Eq. 7).

$$R^{adv} = -\frac{1}{N}\sum_j log(\pi_j^{surr}(a_j|v_j, m_j)) \tag{7}$$

Intuitively, we are driving the critic to punish state-action pairs visited by the target policies. Another interpretation is that the probability of the samples' appearance is proportional to the exponential of the reward in inverse reinforcement learning (IRL) theory [38, 39].

Given a well-trained critic, we can learn the adversarial policy $\pi^{adv}(\delta|\Upsilon, M^{out})$ to modify the communication messages to maximize the Q-function minus a bit flipping penalty $C_{flip} = L_1(\delta)$. We

utilize the surrogate policies again to produce hypothetical actions given the modified communication vectors.

$$\delta = \pi^{adv}(\Upsilon, M^{out}), \ M^{adv} = \delta \cdot (1 - M^{out}) + (1 - \delta) \cdot M^{out}, \ A^{adv} = \Pi^a_{surr}(\upsilon_j, m_j^{adv}) \quad (8)$$

The adversarial policy can then be updated through automatic differentiation to produce messages that disturb the surrogate policies. With our method, we can train the adversarial communication policy completely offline with the only assumption being that we have intercepted some observation, message, and action pairs from the target policies.

5 Results and Discussion

5.1 Environments

We utilize three domains originally proposed by the MADDPG [23] paper and modified for our use: Predator-Capture-Prey, Partially Observable Predator-Prey, and Speaker-Listener. Further details of these environments are included in the supplementary.

Predator-Capture-Prey (PCP) In this environment, a team of agents must capture an adversary prey opponent. To emphasize the role of communication in this domain, we create predator (perception) agents and capture (action) agents. Capture agents cannot see any other agents and have to make decisions based on the received messages from all observing agents. The Prey moves randomly.

Partially Observable Predator-Prey (PO-PP) We modify the predator-prey environment such that all predator agents can only receive the location of the prey when they are within a distance d of the prey. The agents must communicate with each other to locate the position of to the prey. We remove the capture agents from this environment.

Speaker-Listener (SL) In speaker-listener, a team of two agents, consisting of a *speaker* and a *listener* must work together for the listener to reach a target color destination. The speaker must communicate the target color to the listener and the listener must then go to the color destination.

5.2 Adversarial Communication Validation

In this section, we validate our secret adversarial communication channel performance by comparing it with a random flipping method where we flip the same number of bits as the adversarial communication. We ensure that these two methods are always flipping the same number of bits in the communication and compare the results across various numbers of bits flipped. Therefore, we rewrite the adversarial policy loss function with the regularization term as $\mathcal{L} = -Q(v, a, m) + \alpha \cdot 1/N_c \cdot \mathbf{L}_1(\delta)$ which means the policy loss is regularized by the average sum of bits flipped. The coefficient α is used to balance the adversarial policy performance with the bits flipped and we control the regularization speed by annealing $\alpha = \alpha_0 \cdot \max(n_e - \beta, 0)/\epsilon$ (where n_e is the training episode number) to fine-tune the bits flipped. We evaluate the reward and collision statistics by running 50 episodes for each adversarial policy checkpoint.

Figure 3 shows the rewards and collisions versus the episodes from which we get our adversarial policy in the three environments. Agents' reward and collisions from the adversarial communication increase as the number of bits flipped decreases but are always less than those from random flipping. This result validates the adversary property of our method and distinguishes it from random noise with the same magnitude. We also find that the gap between the two methods is lower when the number of bits flipped is lower, which is reasonable since it is difficult for adversarial policy to attack the critical combinations of the communication digits in such a limitation. Interestingly, the random flipping curve nearly remains horizontal in the PO-PP environment, which means that random attack does not work at all regardless of the number of bits flipped. This is because the predators do not only rely on communication but also on their own observations to take actions, therefore, irregularly changing the communication will not confuse agents much, compared to the adversarial policy which flips crucial bits and guides the agents to low-reward regions.

(a) Average Rewards in PO-PP, PCP and SL respectively

(b) Average Number of Collisions in PO-PP, PCP and SL respectively

Figure 3: The average reward and number of collisions are displayed for the adversarial policy (blue) and random flipping (red), respectively. The regularization term $\mathcal{C}_{flip}$ pushes the adversarial policy to flip fewer bits as training progresses such that adversarial effect is weak. The resulting number of bits flipped is represented as the black curve (using right y-axis). Our adversarial communication policy consistently outperforms the random policy.

5.3 Comparison of Adversarial Message Parameterization

In this section, we compare our adversarial policy, between the "flipping" regularization strategy (as described in Section 4.2), and the "direct" strategy in terms of the normalized adversarial policy performance score (S) which denotes how much worse an agent performs per flipping a single digit (Details in Supplementary). The training and testing settings are the same as section 5.2 and we record the maximum normalized score of the flipping method (ours) to the direct method (Table 1).

Table 1: Reward and Collision Normalized Scores

	PCP		PO-PP		SL	
	Reward	**Collision**	**Reward**	**Collision**	**Reward**	**Collision**
Adv[Ours]	**0.11±0.05**	**4.58±2.23**	**0.04±0.02**	**1.45±0.55**	**0.13±0.06**	**31.38±6.51**
Adv[Direct]	0.01±0.01	1.07±0.14	0.02±0.01	0.80±0.07	0.11±0.05	30.72±6.19
Random	0.01±0.01	0.96±0.29	0.00±0.01	0.30±0.88	0.04±0.02	13.68±3.19

In the PCP and PO-PP environments, the direct strategy exhibits significantly worse reward and collision scores, performing at 90.9% and 76.64% lower, respectively, compared to our approach. This discrepancy arises from the failure of the direct strategy to effectively balance lowering agent performance and reducing flipped bits. In these environments, the direct strategy results in 38.7% and 65% bits flipped, whereas our approach achieves 7.5% and 28.3% of bits flipped. Interestingly, in the SL environment, where there is a single message sender, one receiver, and 16 bits of communication, the direct strategy performs relatively better due to the simpler balancing of performance and regularization terms. Nevertheless, our approach still outperforms the direct strategy by 18.18% and 2.15% in terms of reward and collision, with 8.15% and 8.29% of bits flipped, respectively. These findings highlight the critical importance of the flipping representation in facilitating backward gradient computation.

5.4 Robotarium Physical Robot Demonstration

We demonstrate our results on a physical swarm robotics system. We utilize state-based position control to drive each robot according to their policies both with the adversarial communication

Table 2: Attacked Agents Reward and Collision

	PCP		PO-PP		SL	
	Reward	**Collision**	**Reward**	**Collision**	**Reward**	**Collision**
Adv[Ours]	**-0.71±0.34**	**0.05±0.23**	**-0.71±0.34**	**0.05±0.23**	**-0.43±0.14**	**0.00±0.00**
Random	-0.18±0.33	0.29±0.45	0.02±0.56	0.20±0.40	-0.21±0.15	0.34±0.47

intervention and random flipping intervention. We show that our adversarial communication policy drastically reduces reward in all three environment settings (Table 2) with the same number of bits flipped per episode and averaged over three episodes.

Figure 4: PCP Demonstration: Adversarial Communication (top) vs Random Flipping (bottom)

6 Limitations and Future Work

Our work relies on the assumption that the surrogate policies can accurately model the behaviors of the true policies. Our method depends on using the agent policies to estimate the ground-truth reward function. However, IRL methods [39] could be used to learn a reward function that better reflects the ground truth reward.

Our work has important ethical implications as it could be used to attack important systems but can improve the community's ability to help improve the robustness of these systems by characterizing the vulnerabilities. This work does not assume any strategies for the target agents to defend against adversarial attacks. A defender may include a parity bit indicating whether the total number of 1-bits is even or odd to defend against our suggested attacks on their binarized communication systems. Also, if we allow the defender to have access to previous experiences with the attackers, the defender could learn a response strategy by either adjusting its communication scheme or altering its behavior to operate in a fashion not vulnerable to affected communication channels.

7 Conclusion

We introduce a practical adversarial communication policy that does not need direct environment interaction, enhancing the feasibility of adversarial attacks. Our method also utilizes a robust approach for estimating agent rewards from observing behaviors only, without reward information. Lastly, we pioneer a differentiable method for adversarial communication in discrete binary channels, flipping bits for improved attack efficacy. Our algorithm is validated on real swarm robots in Robotarium platform. This showcases the versatility and real-world applicability of our approach. Our framework opens new avenues for enhanced security and robustness in multi-agent systems, with potential implications across various domains.

References

[1] L. E. Parker, D. Rus, and G. S. Sukhatme. Multiple mobile robot systems. *Springer handbook of robotics*, pages 1335–1384, 2016.

[2] Q. Li, W. Lin, Z. Liu, and A. Prorok. Message-aware graph attention networks for large-scale multi-robot path planning. *IEEE Robotics and Automation Letters*, 6(3):5533–5540, 2021. doi:10.1109/LRA.2021.3077863.

[3] Q. Jiang, M. Qin, S. Shi, W. Sun, and B. Zheng. Multi-agent reinforcement learning for traffic signal control through universal communication method, 2022.

[4] E. Van der Pol and F. A. Oliehoek. Coordinated deep reinforcement learners for traffic light control. *Proceedings of learning, inference and control of multi-agent systems (at NIPS 2016)*, 8:21–38, 2016.

[5] B. Liu and Z. Ding. A distributed deep reinforcement learning method for traffic light control. *Neurocomputing*, 490:390–399, 2022. ISSN 0925-2312. doi:https://doi.org/10.1016/j.neucom.2021.11.106.

[6] H. Qie, D. Shi, T. Shen, X. Xu, Y. Li, and L. Wang. Joint optimization of multi-uav target assignment and path planning based on multi-agent reinforcement learning. *IEEE access*, 7:146264–146272, 2019.

[7] M. Zolfpour-Arokhlo, A. Selamat, S. Z. Mohd Hashim, and H. Afkhami. Modeling of route planning system based on q value-based dynamic programming with multi-agent reinforcement learning algorithms. *Engineering Applications of Artificial Intelligence*, 29:163–177, 2014. ISSN 0952-1976. doi:https://doi.org/10.1016/j.engappai.2014.01.001.

[8] A. Singh, T. Jain, and S. Sukhbaatar. Learning when to communicate at scale in multiagent cooperative and competitive tasks. *CoRR*, abs/1812.09755, 2018.

[9] A. Das, T. Gervet, J. Romoff, D. Batra, D. Parikh, M. Rabbat, and J. Pineau. TarMAC: Targeted multi-agent communication. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 1538–1546. PMLR, 09–15 Jun 2019.

[10] Y. Niu, R. R. Paleja, and M. C. Gombolay. Multi-agent graph-attention communication and teaming. In *AAMAS*, pages 964–973, 2021.

[11] E. Seraj, Z. Wang, R. Paleja, D. Martin, M. Sklar, A. Patel, and M. Gombolay. Learning efficient diverse communication for cooperative heterogeneous teaming. In *Proceedings of the 21st international conference on autonomous agents and multiagent systems*, pages 1173–1182, 2022.

[12] S. Strunsky. N.j. man fined $32k for illegal gps device that disrupted newark airport system, 2013.

[13] S. Konan, E. Seraj, and M. Gombolay. Iterated reasoning with mutual information in cooperative and byzantine decentralized teaming, 2022.

[14] Y. Sun, R. Zheng, P. Hassanzadeh, Y. Liang, S. Feizi, S. Ganesh, and F. Huang. Certifiably robust policy learning against adversarial communication in multi-agent systems. *arXiv preprint arXiv:2206.10158*, 2022.

[15] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative adversarial networks. *Communications of the ACM*, 63(11):139–144, 2020.

[16] C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. Goodfellow, and R. Fergus. Intriguing properties of neural networks. In Y. Bengio and Y. LeCun, editors, *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014.

[17] I. J. Goodfellow, J. Shlens, and C. Szegedy. Explaining and harnessing adversarial examples, 2015.

[18] N. Papernot, P. McDaniel, I. Goodfellow, S. Jha, Z. B. Celik, and A. Swami. Practical black-box attacks against machine learning. In *Proceedings of the 2017 ACM on Asia conference on computer and communications security*, pages 506–519, 2017.

[19] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu. Towards deep learning models resistant to adversarial attacks, 2019.

[20] S. Wilson, P. Glotfelter, L. Wang, S. Mayya, G. Notomista, M. Mote, and M. Egerstedt. The robotarium: Globally impactful opportunities, challenges, and lessons learned in remote-access, distributed control of multirobot systems. *IEEE Control Systems Magazine*, 40(1): 26–44, 2020. doi:10.1109/MCS.2019.2949973.

[21] J. N. Foerster, Y. M. Assael, N. de Freitas, and S. Whiteson. Learning to communicate with deep multi-agent reinforcement learning. *CoRR*, abs/1605.06676, 2016.

[22] S. Sukhbaatar, A. Szlam, and R. Fergus. Learning multiagent communication with backpropagation. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, NIPS'16, page 2252–2260, Red Hook, NY, USA, 2016. Curran Associates Inc. ISBN 9781510838819.

[23] R. Lowe, Y. I. Wu, A. Tamar, J. Harb, O. Pieter Abbeel, and I. Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. *Advances in neural information processing systems*, 30, 2017.

[24] L. P. Kaelbling, M. L. Littman, and A. R. Cassandra. Planning and acting in partially observable stochastic domains. *Artificial Intelligence*, 101(1):99–134, 1998. ISSN 0004-3702. doi:https://doi.org/10.1016/S0004-3702(98)00023-X.

[25] C. Amato, D. S. Bernstein, and S. Zilberstein. Solving pomdps using quadratically constrained linear programs. In *Proceedings of the Fifth International Joint Conference on Autonomous Agents and Multiagent Systems*, AAMAS '06, page 341–343, New York, NY, USA, 2006. Association for Computing Machinery. ISBN 1595933034. doi:10.1145/1160633.1160694.

[26] N. Hyldmar, Y. He, and A. Prorok. A fleet of miniature cars for experiments in cooperative driving. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 3238–3244, 2019. doi:10.1109/ICRA.2019.8794445.

[27] A. Chowdhury, G. Karmakar, J. Kamruzzaman, A. Jolfaei, and R. Das. Attacks on self-driving cars and their countermeasures: A survey. *IEEE Access*, 8:207308–207342, 2020. doi:10.1109/ACCESS.2020.3037705.

[28] A. Arnab, O. Miksik, and P. H. S. Torr. On the robustness of semantic segmentation models to adversarial attacks. In *CVPR*, 2018.

[29] Adversarial attacks on yolact instance segmentation. *Computers & Security*, 116:102682, 2022.

[30] J. Gu, H. Zhao, V. Tresp, and P. H. Torr. Segpgd: An effective and efficient adversarial attack for evaluating and boosting segmentation robustness. In *ECCV*, pages 308–325. Springer, 2022.

[31] C. Xie, J. Wang, Z. Zhang, Y. Zhou, L. Xie, and A. Yuille. Adversarial examples for semantic segmentation and object detection. In *2017 IEEE International Conference on Computer Vision (ICCV)*, pages 1378–1387, 2017. doi:10.1109/ICCV.2017.153.

[32] M. Yin, S. Li, C. Song, M. S. Asif, A. K. Roy-Chowdhury, and S. V. Krishnamurthy. Adc: Adversarial attacks against object detection that evade context consistency checks. In *2022 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, 2022.

[33] T. Chen, J. Liu, Y. Xiang, W. Niu, E. Tong, and Z. Han. Adversarial attack and defense in reinforcement learning-from ai security view. *Cybersecurity*, 2:1–22, 2019.

[34] H. Zhang, H. Chen, C. Xiao, B. Li, M. Liu, D. Boning, and C.-J. Hsieh. Robust deep reinforcement learning against adversarial perturbations on state observations. *Advances in Neural Information Processing Systems*, 33:21024–21037, 2020.

[35] R. Jiao, H. Liang, T. Sato, J. Shen, Q. A. Chen, and Q. Zhu. End-to-end uncertainty-based mitigation of adversarial attacks to automated lane centering, 2021.

[36] W. Xue, W. Qiu, B. An, Z. Rabinovich, S. Obraztsova, and C. K. Yeo. Mis-spoke or mis-lead: Achieving robustness in multi-agent communicative reinforcement learning. In *Proceedings of the 21st International Conference on Autonomous Agents and Multiagent Systems*, pages 1418–1426, 2022.

[37] A. Demontis, M. Melis, M. Pintor, M. Jagielski, B. Biggio, A. Oprea, C. Nita-Rotaru, and F. Roli. Why do adversarial attacks transfer? explaining transferability of evasion and poisoning attacks. In *28th USENIX Security Symposium (USENIX Security 19)*, pages 321–338, Santa Clara, CA, Aug. 2019. USENIX Association. ISBN 978-1-939133-06-9.

[38] B. D. Ziebart, A. L. Maas, J. A. Bagnell, A. K. Dey, et al. Maximum entropy inverse reinforcement learning. In *Aaai*, volume 8, pages 1433–1438. Chicago, IL, USA, 2008.

[39] J. Fu, K. Luo, and S. Levine. Learning robust rewards with adverserial inverse reinforcement learning. In *International Conference on Learning Representations*, 2018.