Unbiased learning with State-Conditioned Rewards in Adversarial Imitation Learning

Abstract

Adversarial imitation learning has emerged as a general and scalable framework for automatic reward acquisition. However, we point out that previous methods commonly exploited occupancy-dependent reward learning formulation. Despite the theoretical justification, the occupancy measures tend to cause issues in practice because of high variance and low vulnerability to domain shifts. Another reported problem is termination biases induced by provided rewarding and regularization schemes around terminal states. In order to deal with these issues, this work presents a novel algorithm called causal adversarial inverse reinforcement learning. The framework employs a dual discriminator architecture for decoupling state densities from rewards formulation. We investigate the reward shaping theory to deal with the finite horizon problem and address the reward function's optimality. The formulation draws a strong connection between adversarial learning and energy-based reinforcement learning; thus, the architecture is capable of recovering a reward function that induces a multi-modal policy. In experiments, we demonstrate that our approach outperforms prior methods in challenging continuous control tasks, even under significant variation in the environments.

1 Introduction

Inverse reinforcement learning (IRL) is an algorithm of recovering the ground truth reward function from observed behavior (Ng & Russell, 2000). IRL algorithms—followed by appropriate reinforcement learning (RL) algorithms—can optimize policy through farsighted cumulative value measures in the given system (Sutton & Barto, 2018); hence it can usually achieve more satisfying results than mere supervision. While a few studies have investigated recovering reward functions to continuous spaces (Babes et al., 2011; Levine & Koltun, 2012), IRL algorithms often fail to find the ground-truth reward function in high-dimensional complex domains (Ziebart et al., 2010; Finn et al., 2016).

The notion of the ground-truth reward requires elaboration since IRL is an ill-posed problem; there can be numerous solutions to the reward function inducing the same optimal policy (Ng et al., 1999; Ng & Russell, 2000). Recently, adversarial imitation learning (AIL) as a reward acquisition method has shown promising results (Ho & Ermon, 2016). One of the distinctive strengths of AIL is the scalability through parameterized non-linear functions such as neural networks.

This work points out that there still remains two kinds of biases in AIL. The established algorithms are typically formalized by the cumulative densities called *occupancy measure*. Theoretically, we claim that the accumulated measures contain biases that are not related to modeling purposeful behavior, and the formulation is vulnerable to distributional shifts of an MDP. Empirically, they work as dominant noises in training because of their innate high variance. The other bias is implicit survival or early termination bias caused by reward formulation. For example, a non-negative reward function without normalizing its value may lead to sub-optimal behaviors where the agent learns to move around goals to accumulate rewards instead of completing the tasks.

This paper proposes an adversarial IRL method called causal adversarial inverse reinforcement learning (CAIRL). We primarily associate the reward acquisition method with approaches for energy-based RL policies (Haarnoja et al., 2017; 2018) and maximum entropy IRL algorithms (Ziebart et al., 2008; 2010). Therefore, the CAIRL reward function can efficiently induce probabilistic behaviors with multiple modalities. The methodology of this work focuses on the fact that the discriminator network's logit score defines an energy function and that it can be decomposable. We

then show that learning with a dual discriminator architecture provides stepwise, state-conditioned rewards. For handling biases induced by finite-horizon episodes, CAIRL makes the reward function satisfy a regularized Bellman equation (Geist et al., 2019; Yang et al., 2019), including "self-looping" terminal states. As a result, the model learns the reward function satisfying the necessary properties of ground-truth rewards even after episodes reach the terminal states without additional preprocessing or learning.

Noteworthy contributions of this work are 1) a model-free IRL algorithm that is effective in high-dimensional environments, 2) a dual discriminator architecture for recovering a robust state-conditioned reward function, 3) a simple and effective approach for handling terminal states, and 4) meaningful experiments and comparison studies with state-of-the-art algorithms in various topics.

2 RELATED WORKS

Imitation learning is a fundamental approach for modeling intellectual behavior from an expert at certain tasks, such as autonomous driving and manipulation tasks (Pomerleau, 1991; Zhang et al., 2018). In this perspective, IRL is a branch of imitation learning, specialized in dealing with sequential decision-making problems. We assume that the expert behavior under uncertainty is closely related to a Boltzmann exploration strategy (Konda & Borkar, 1999; Cesa-Bianchi et al., 2017) and entropy-augmented RL agents (Haarnoja et al., 2017; 2018; Shi et al., 2019). Assuming an expert policy is an energy-based model, the IRL objective becomes finding a reward function that rationalizes the behaviors across all states and actions with the maximum entropy principle.

In order to study stochastic expert policies, Boltzmann distributions appeared in early IRL research, such as Bayesian IRL, natural gradient IRL, and maximum likelihood IRL (Ramachandran & Amir, 2007; Neu & Szepesvári, 2012; Babes et al., 2011). Notably, maximum entropy IRL (Ziebart et al., 2008) is explicitly formulated as an energy-based modeling problem. The framework had also been derived from the maximum causal entropy principle, which can model the purposeful distribution of optimal policy into a reward function (Ziebart et al., 2010). Our work draws significant inspirations from these prior works and aims to redeem the perspective of probabilistic causality.

AIL algorithms (Ho & Ermon, 2016; Fu et al., 2017; Ghasemipour et al., 2020) can be viewed as divergence minimization between state-action distributions. Each of the methods provides a unique divergence minimization scheme derived by its architecture. In specific, our work shares major components with the AIRL algorithm. However, Liu et al. (2020) argued that AIRL does not recover the energy of the expert policy. We emphasize that our work introduces additional concepts for discarding overlapping state densities to correctly draw energy-based model of the expert policies. The decoupling formulation is inspired by the rich energy-based interpretation of GANs (Zhao et al., 2016; Che et al., 2020; Azadi et al., 2018) and by studies with multiple discriminators (Chongxuan et al., 2017; Gan et al., 2017; Choi et al., 2018).

The issues of finite-horizon tasks were initially raised in RL during the discussion of time limits in MDP benchmarks (Pardo et al., 2017; Tucker et al., 2018). It turned out that time limits, or even the existence of terminal states, would significantly affect the value learning procedure of RL compared to that generated in infinite horizon MDPs. IRL suffers from the identical problem that reward learning of finite episodes is not really stable for tasks outside of appropriate benchmarks. Kostrikov et al. (2018) tried to solve the problem by explicitly adding a self-repeating *absorbing* state (Sutton & Barto, 2018) after the terminal state; consequently, all episodes virtually have the properties of the infinite horizon.

3 BACKGROUND

Markov Decision Process (MDP). We consider an MDP, defined as a tuple $M = (\mathcal{S}, \mathcal{A}, \mathcal{P}, r, p_0, \gamma)$ where $\mathcal{S}$ and $\mathcal{A}$ denote state and action spaces, and γ is the discount factor. The transition distribution $\mathcal{P}$, the deterministic state-action reward function r, and the initial state distribution p_0 are unknown. Let τ_π and τ_E be sequences of finite states and actions $(s_0, a_0, \ldots, a_{T-1}, s_T)$ obtained by a stochastic policy π and the expert policy π_E, respectively. The term ρ_π denotes the occupancy measures (Syed et al., 2008; Ho & Ermon, 2016) derived by π, and is defined as

Table 1: The objectives for AIL algorithms in a form as the minimization of statistical divergences.

Method	Optimized Objective (Minimization)
GAIL (Ho & Ermon, 2016)	$\mathbb{E}_\pi\big[\mathrm{D_{JS}}\big(\rho_\pi(s,a),\rho_E(s,a)\big) - \mathcal{H}(\pi(\cdot|s))\big]$
AIRL (Fu et al., 2017)	$\mathbb{E}_\pi\big[\mathrm{D_{KL}}\big(\rho_\pi(s,a)\big\|\rho_E(s,a)\big)\big] = -\mathbb{E}_\pi\big[\log\rho_E(s,a) + \mathcal{H}(\rho_E)\big]$
FAIRL (Ghasemipour et al., 2020)	$\mathbb{E}_\pi\big[\mathrm{D_{KL}}\big(\rho_E(s,a)\big\|\rho_\pi(s,a)\big)\big] = -\mathbb{E}_{\pi_E}\big[\log\rho_\pi(s,a) + \mathcal{H}(\rho_\pi)\big]$
CAIRL (this work)	$\mathbb{E}_\pi\big[\mathrm{D_{KL}}\big(\pi(a|s)\big\|\pi_E(a|s)\big)\big] = -\mathbb{E}_\pi[\mathbf{r}(s,a) + \mathcal{H}(\pi(\cdot|s))] + \mathrm{const}$

$\rho_\pi(s,a) = \pi(a|s)\sum_{t=0}^\infty \gamma^t \Pr(s_t = s|\pi)$. The expectation of π for an arbitrary function c denotes an expected return for infinite-horizon: $\mathbb{E}_\pi[c(s,a)] \triangleq \mathbb{E}[\sum_{t=0}^\infty \gamma^t c(s,a)|\pi]$.

Potential-based Reward Shaping. Ng et al. (1999) explored the idea of making the convergence of RL faster with more instructive rewards. They showed that the transformed MDP $M' = (\mathcal{S}, \mathcal{A}, \mathcal{P}, r' = r + F, p_0, \gamma)$, by adding a shaping function $F : \mathcal{S} \times \mathcal{S} \to \mathbb{R}$ to the original reward function, retains the identical optimal policy if F is a potential-based shaping function.

Definition 3.1 (Potential-based shaping function). *$F : \mathcal{S} \times \mathcal{S} \to \mathbb{R}$ is a potential-based shaping function if there exists a function $\Psi : \mathcal{S} \to \mathbb{R}$, such that $\forall (s, s') \in \mathcal{S} \times \mathcal{S}, F(s, s') = \gamma\Psi(s') - \Psi(s)$.*

Proposition 3.1 (Policy Invariance under Reward Shaping). *The condition of potential-based shaping functions is necessary and sufficient for it to guarantee consistency with the optimal policy.*

When the potential function Ψ is "optimal," the amount of learning will be significantly reduced. It has been suggested that shaping rewards with the optimal value function, i.e., $\Psi(s) = V^\star(s)$, helps efficient value updates and credit assignment (Ng et al., 1999; Zou et al., 2019).

Maximum Entropy IRL (MaxEnt IRL). Ziebart (2010) and Haarnoja et al. (2017) defined the optimality of stochastic policy with an entropy-regularized RL objective as follows:

$$\pi^\star = \arg\max_{\pi\in\Pi} \sum_t \mathbb{E}_{(s_t,a_t)\sim\rho_\pi}\big[r(s_t, a_t) + \alpha\mathcal{H}(a_t|s_t)\big],$$

where $\mathcal{H}$ denotes the causal entropy function.[1] If π_E is the MaxEnt RL policy, the softmax Bellman optimality equations can be defined by the following recursive logic:

$$\begin{aligned}
Q^\star(s_t, a_t) &= r(s_t, a_t) + \gamma\mathbb{E}_{s_{t+1}\sim\mathcal{P}(\cdot|s_t,a_t)}\big[V^\star(s_{t+1})\big] \\
V^\star(s_t) &= \mathbb{E}_{a_t\sim\pi_E(\cdot|s_t)}\big[Q^\star(s_t, a_t) - \log\pi_E(a_t|s_t)\big].
\end{aligned} \tag{1}$$

MaxEnt IRL algorithms (Ziebart et al., 2008; 2010) are the energy-based interpretations of IRL. However, such algorithms are difficult to compute when the given spaces are large or continuous.

Adversarial Imitation Learning. Ho & Ermon (2016) considered adversarial learning as a model-free, sampling-based approximation to MaxEnt IRL. Instead of exhaustively solving the problem, GAIL performs imitation learning by minimizing the divergence between the state-action occupancy measures from the expert and learner through the following logistic objective:

$$\min_{\pi\in\Pi} \max_D \mathbb{E}_{\pi_E}\big[\log D(s,a)\big] + \mathbb{E}_\pi\big[\log\big(1 - D(s,a)\big)\big] - \mathcal{H}(\pi), \tag{2}$$

where $D \in (0,1)^{|\mathcal{S}||\mathcal{A}|}$ indicates a binary classifier trained to distinguish between τ_π and τ_E. The AIRL discriminator tries to disentangle a reward function that is invariant to dynamics. It takes a particular form: $D_\theta(s,a) = \exp(f_{\theta,\psi}(s,a))/(\exp(f_{\theta,\psi}(s,a)) + \pi_\phi(a|s))$, and models the function $f_{\theta,\psi}$ as well: $f_{\theta,\psi}(s,a,s') = r_\theta(s,a) + \gamma h_\psi(s') - h_\psi(s)$. Learning with the AIRL can be considered as the reverse KL divergence between occupancy measures. Ghasemipour et al. (2020) proposed FAIRL algorithm as an method for the forward KL divergence (see Table 1).

4 LEARNING UNBIASED REINFORCEMENT SIGNALS

Even though AIL methods are generally assured for convergence, most of the theoretical arguments implicitly assume imitation learning would only be conducted between the exactly same, infinite

---

[1]For the rest of the paper, we omit the parameter with $\alpha = 1$ for simplicity of derivation.

Figure 1: Visualization of entropy regularization methods and biases around terminal states. The red vertices and edges represent absorbing states and maximum entropy action selection. Each regularization is defined as $\mathcal{H}_t = \mathcal{H}\big(\pi(\cdot|s_t)\big)$ and $\mathrm{KL}_t = -\mathrm{D}_{\mathrm{KL}}[\pi(\cdot|s_t)\|p_{\mathrm{unif}}(\cdot)]$ respectively.

horizon MDPs. Consider a case that the initial state or transition distributions retain misalignment. Then, the one-to-one correspondence between the occupancy derived from expert trajectories and the optimal policy will no longer hold. Moreover, catastrophic failure of learning can occur since the measure is defined as infinite accumulation of misaligned likelihoods. In real-world problems such as sim-to-real transfer learning and robotics problems, an algorithm that is robust to domain shifts is heavily preferred; otherwise, extensive data augmentation techniques are needed to succeed (Tobin et al., 2017; Zhu et al., 2018). We hypothesize that the fundamental issues of AIL mainly comes from exploitation of occupancy measures and absence of handling terminal states. Therefore, our aim is to investigate an unbiased modeling of causality of actions from finite episode trajectories.

4.1 STATE-CONDITIONED REWARDS ON THE PRINCIPLE OF MAXIMUM ENTROPY

We clarify a valid candidate set of reward functions in the case when entropy-regularization is applied. Substituting the soft Q-value with $r(s,a) + \gamma\mathbb{E}_{s'\sim\mathcal{P}(\cdot|s,a)}\big[V^\star(s')\big]$ in Eqn. 1, one trivial solution of the reward function is the log-likelihood of expert $\mathbf{r}^\star(s,a) = \log\pi_E(a|s)$ in the condition of $V^\star(s) = 0$. The 1-step expectation of $\mathbf{r}^\star$ draws an immediate conditional KL divergence:

$$\mathbb{E}_{a\sim\pi(\cdot|s)}\big[\mathbf{r}^\star(s,a) + \mathcal{H}(\pi(\cdot|s))\big] = -\mathrm{D}_{\mathrm{KL}}\big[\pi(\cdot|s)\big\|\pi_E(\cdot|s)\big]. \tag{3}$$

By the property of KL divergence, the above expression is less than or equal to 0 where the equality holds if and only if $\pi(a|s) = \pi_E(a|s), \forall a \in \mathcal{A}$. As a result, the optimality of the 1-step action distribution is instantaneously determined without consideration of future rewards. Therefore, the potential-based shaping of $\mathbf{r}^\star$ is not required as the soft optimal value function outputs 0.

Remark 4.1. *For arbitrary discounted rates, $\mathbf{r}^\star(s,a) = \log\pi_E(a|s)$ is the optimally shaped reward function for learning efficiency in the Shannon entropy-regularization.*

From this insight, the log-likelihood of expert policy can be understood as a desirable state-conditioned reward function for energy-based RL. However, oftentimes directly modeling the log density (Pomerleau, 1991) is not a practical method due to the limited number of samples and the safety of learning. An alternative reward function is defined using the concept of reward shaping:

$$\mathfrak{R} = \big\{\mathbf{r}\big|\mathbf{r}(s,a) + \gamma\Psi(s') - \Psi(s) = \log\pi_E(a|s), \ \Psi : \mathcal{S} \to \mathbb{R}, \ \forall s,a,s' \in \mathcal{S} \times \mathcal{A} \times \mathcal{S}\big\}. \tag{4}$$

The formulation relaxes likelihood estimation by the state potential function Ψ. Akin to Prop. 3.1, we formalize a claim that learning with Eqn. 4 does not change the learning objective.

Proposition 4.1. *Let $\mathbf{r}$ be a function satisfying Eqn. 4. Then the expected cumulative reward of π has following property: $\mathbb{E}_\pi\big[\mathbf{r}(s,a) + \mathcal{H}(\pi(a|s))\big] = -\mathbb{E}_\pi\big[\mathrm{D}_{\mathrm{KL}}\big(\pi(\cdot|s)\big\|\pi_E(\cdot|s)\big)\big] + \mathbb{E}_{s\sim p_0}\big[\Psi(s)\big]$.*

Note that the last term $\mathbb{E}_{s\sim p_0}[\Psi(s)]$ is independent of π. Compared to the AIRL, where the reward function is formulated as $\log{\rho_E(s,a)}/{\rho_\pi(s,a)}$, a reward function $\mathbf{r} \in \mathfrak{R}$ can be universally applied for training arbitrary policies since the agent-specific occupancy measure $\rho_\pi(s,a)$ is detached.

4.2 HANDLING FINITE-HORIZON BIASES WITH A KL REGULARIZATION ASSUMPTION

Without proper consideration of reward and regularization methods around terminal states, termination biases can occur as depicted in Fig. 1 (a). Kostrikov et al. (2018) highlighted the concept of absorbing states and suggested adding synthetic transitions $\{(s_T, \cdot, s_a), (s_a, \cdot, s_a)\}$ into the trajectory (see Fig. 1 (b)), which explicitly promotes learning for termination frequencies. They claimed that AIL formulation can estimate returns for the final transitions so that it mitigates the issue.

Fig. 1 (c) and (d) illustrate two possible simpler extensions to make finite-length episodes into infinite-horizon episodes by including self-looping terminal states. The key idea is to assume that the expert represents maximum-entropy behavior when a self-loop state is encountered since it can change neither reward nor transition state by the action selection. Therefore, the expert policy is equivalent to uniform action distribution p_{unif}. Fig. 1 (c) and (d) are alike for handling the biases as $\mathcal{H}_t = \text{KL}_t + \text{const}$, but the KL regularization has a slight advantage because terminal state value is always 0 instead of $\mathcal{H}_{\max}/(1-\gamma)$. Consequently, KL penalties can be seamlessly integrated in the finite-Horizon MDPs without preprocessing.

With the same reasoning as in Sec. 4.1, the term $\log{\pi_E(a|s)}/u$ can be understood as the optimal shaping under the KL regularization. The constant u denotes the value of p_{unif} (i.e. $u \triangleq p_{\text{unif}}(a), \forall a \in \mathcal{A}$). Therefore, we set the learning objective of the shaped reward function:

$$f_{\theta,\psi}(s, a, s') = r_\theta(s, a) + \gamma h_{\bar{\psi}}(s') - h_\psi(s) = \log \frac{\pi_E(a|s)}{u}, \tag{5}$$

where r_θ and h_ψ denote reward and potential networks. $h_{\bar{\psi}}$ denotes a target potential network with the identical parameter of ψ, yet the gradient computation is disconnected while training, which is analogous to constructing target value networks in the deep RL domain (Mnih et al., 2015). For every terminal state, we fixed the output to the optimal solution: $r_\theta(s_T, a) = h_\psi(s_T) = 0, \forall a \in \mathcal{A}$.

5 CAUSAL ADVERSARIAL INVERSE REINFORCEMENT LEARNING

5.1 A DUAL DISCRIMINATOR ARCHITECTURE

The reward modeling of CAIRL is based on the perspective that an AIL discriminator is an energy-based model (EBM), and the property that an EBM on joint densities can be decomposed into multiple EBMs. Suppose that the GAIL discriminator is nearly optimal, namely (Ho & Ermon):

$$D(s, a) = \frac{1}{1 + \exp(-d(s, a))} \approx \frac{\rho_E(s, a)}{\rho_E(s, a) + \rho_\pi(s, a)},$$

where $d(s, a)$ denotes the logit of $D(s, a)$. With a slight abuse of notation, we refer to the occupancy measures of states as $\rho_E(s)$ and $\rho_\pi(s)$. We disentangle the logit function to the following form:

$$d(s, a) \approx \log \frac{\rho_E(s, a)}{\rho_\pi(s, a)} = \log \frac{\rho_E(s)}{\rho_\pi(s)} + \log \frac{\pi_E(a|s)}{\pi(a|s)}, \tag{6}$$

and then we have two log-ratios of state occupancy measures and policy distributions.

The model substitutes the log-ratio of state occupancy measures using a state-only discriminator D_φ with a nearly optimal logit score of $d_\varphi(s) \approx \log(\rho_E(s)/\rho_\pi(s))$. The role of D_φ is to nullify the difference between state densities by pre-applying it. We propose an architecture of discriminator:

$$D_{\theta,\psi}(s, a, s') = \frac{\exp[f_{\theta,\psi}(s, a, s')]}{\exp[f_{\theta,\psi}(s, a, s')] + \exp[-d_\varphi(s) + \log \frac{\pi_\phi(a|s)}{u}]}, \tag{7}$$

where $d_\varphi(s)$ and $\pi_\phi(a|s)$ are pre-computed. Using D_φ and π_ϕ as scaffolds, the shaped reward function $f_{\theta,\psi}$ converges to Eqn. 5 and becomes specialized in evaluating conditional decisions.

5.2 ALGORITHM DETAILS

The discriminators D_φ and $D_{\theta,\psi}$ are trained for maximizing the following objectives, respectively:

$$\mathcal{J}(D_\varphi) = \mathbb{E}_{\pi_E}\big[\log D_\varphi(s)\big] + \mathbb{E}_{\pi_\phi}\big[\log(1 - D_\varphi(s))\big],$$
$$\mathcal{J}(D_{\theta,\psi}) = \mathbb{E}_{\pi_E}\big[\log D_{\theta,\psi}(s, a, s')\big] + \mathbb{E}_{\pi_\phi}\big[\log(1 - D_{\theta,\psi}(s, a, s'))\big] - \lambda\mathbb{E}_{\pi_\phi,\pi_E}\big[\|\chi_\psi(s, s')\|_2^2\big],$$

where $\chi_\psi(s, s') = \gamma h_{\bar{\psi}}(s') - h_\psi(s)$ denotes the shaping function. In order to make the overall algorithm well-defined and r_θ to reach the optimally shaped reward function, we regularize the function by minimizing squared L2-norm with $\lambda \in \mathbb{R}^+$. The algorithm provides an IRL reward as $\alpha \cdot r_\theta(s, a)$. Ideally, the performance is invariant to α, if the IRL and RL algorithms share the same temperature. Lastly, we constrained the reward function to output the positive value, i.e., $r_\theta(s, a) = \mathtt{softplus}(g_\theta(s, a))$, where $g_\theta(s, a)$ is a neural network. The reason for this constraint is that unconstrained r_θ will return positive rewards in average when it is converged:

$$\mathbb{E}_{a \sim \pi(\cdot|s)}\left[\frac{\log \pi_E(a|s)}{u}\right] \geq \mathbb{E}_{a \sim \pi(\cdot|s)}\left[\frac{\log \pi(a|s)}{u}\right] = \mathrm{D}_{\mathrm{KL}}\big[\pi(\cdot|s)\big\|p_{\mathrm{unif}}(\cdot)\big] \geq 0.$$

Also, the lower-bound has the practical advantage of preventing overly pessimistic rewards when the function is not sufficiently trained. We defer additional implementation details to Appendix E.

5.3 ANALYSES ON THE CAUSAL AIRL ALGORITHM

Entropy-regularized IRL. We draw a connection between entropy-regularized policy gradient algorithms and our method as an adversarial training method for the policy network.

Proposition 5.1. *If Eqn. 5 is satisfied, the following equality holds.*

$$\nabla_\phi \mathbb{E}_{\pi_\phi}\big[\mathrm{D}_{\mathrm{KL}}\big(\pi_\phi(\cdot|s)\big\|\pi_E(\cdot|s)\big)\big] = -\mathbb{E}_{\pi_\phi}\big[Q^{\pi_\phi}(s, a)\nabla_\phi \log \pi_\phi(a|s) + \nabla_\phi \mathcal{H}(\cdot|s)\big], \qquad (8)$$

where $Q^\pi(s, a) \triangleq r_\theta(s, a) + \mathbb{E}\big[\sum_{t=1}^\infty \gamma^t(r_\theta(s_t, a_t) - \log \pi_\phi(a_t|s_t))\big|s_0 = s, a_0 = a, \pi\big].$

The proposition shows the equivalence between entropy-regularized RL and AIL. Unlike traditional RL, the policy of entropy-regularized RL is proved to be converged to a unique fixed point in a regularized condition (Geist et al., 2019; Yang et al., 2019). Thus, we deduce that the adversarial learning scheme leads the agent policy to be converged to the fixed point of the expert policy.

Application to Transfer Learning. Suppose that the expert resides in a different MDP: $M_E = (\mathcal{S}, \mathcal{A}, \mathcal{P}_E, r, \bar{p}_0, \gamma)$. If one of the distributions $\bar{p}_0$ and $\mathcal{P}_E$ is different, the optimal behavior has to adapt to the gap between domains. By extending AIL formulation, we can induce the shaped reward function as $f_{\theta,\psi}(s, a, s') \approx \log\big(\frac{\mathcal{P}_E(s'|s,a)}{\mathcal{P}(s'|s,a)} \cdot \frac{\pi_E(a|s)}{u}\big)$. Therefore, the expectation of $f_{\theta,\psi}(s, a, s')$ with the KL penalty gives a conditional divergence metric as follows:

$$\mathbb{E}_{a \sim \pi(\cdot|s), s' \sim \mathcal{P}(\cdot|s,a)}\big[f_{\theta,\psi}(s, a, s') - \mathrm{D}_{\mathrm{KL}}(\pi(\cdot|s)\|p_{\mathrm{unif}}(\cdot))\big] = -\mathrm{D}_{\mathrm{KL}}\big[p_{\pi_\phi}(a, s'|s)\big\|p_E(a, s'|s)\big], \tag{9}$$

where $p_{\pi_\phi}(a, s'|s)$ and $p_E(a, s'|s)$ denote the agent's and the expert's conditional probability distributions of action and transition state. By Prop. 3.1, learning with $r_\theta(s, a)$ also promotes the agent to be trained with consideration of dynamics misalignment.

Objective of Potential Networks. The reward shaping can be viewed as a value iteration scheme. We relate Eqn. 5 to an entropy-regularized operator called *mellowmax* defined as $mm_\alpha(X) = \log\big(\frac{1}{n}\sum_{i=1}^n \exp(\alpha x_i)\big)/\alpha$, and show that r_θ and h_ψ satisfy the mellowmax Bellman optimality.

Proposition 5.2. *If* $f_{\theta,\psi}(s, a, s') = \log \pi_E(a|s)/u$ *for all states, actions, and transition states, then*

$$h_\psi(s) = \log\left[u \cdot \int_{\mathcal{A}} \exp\big\{r_\theta(s, a) + \gamma \mathbb{E}_{s'|s,a}\big[h_\psi(s')\big]\big\}\mathrm{d}a\right].$$

Thus h_ψ *corresponds to the mellowmax optimal value function of* r_θ *with* $\alpha = 1$.

According to analyses of Asadi & Littman (2017), the standard softmax operator may lead the value learning to multiple fixed-points when $\gamma \approx 1$. As the mellowmax is a non-expansion operator, the use of the KL penalties achieves relatively stable potential function optimization.

6 EXPERIMENTAL RESULTS

Our experiments aim to understand CAIRL and verify the effectiveness of the algorithm in the sense of our claims. We evaluate our approach on three topics, whose settings are motivated by the previous works (Haarnoja et al., 2017; 2018; Fu et al., 2017). For the RL algorithms, we implemented an

Figure 2: IRL trajectories of 2D Multi-goal environments.

Figure 3: Ant robot trajectories.

Figure 4: Training curves of stochastic policies on imitation learning benchmarks.

algorithm based on `OpenAI-PPO2` (Schulman et al., 2017) and use the KL regularization in order to eliminate the survival biases in MaxEnt RL as addressed in Sec. 4.2.

Multi-Modal Behavior. The first experiment setting is a multi-goal environment. From the initial agent position, four goals are located at the four cardinal directions. While a deterministic policy commits to a single goal at the earliest attempt, we hypothesize that the optimal MaxEnt policy distribution represents a multi-modal behavior, which is reaching all the four goals at the same rate.

We evaluated algorithms on two settings. In the 2D setting, the agent is a point mass. The ground-truth function is defined as the difference between Gaussian mixture model values of points: $\text{GMM}(\mathbf{x}_{t+1}) - \text{GMM}(\mathbf{x}_t)$ where $\mathbf{x}_t$ is a 2D representation of state. In the 3D setting, the agent is a simulated robot where its state is defined by the position and its joint values. 3D environment is a challenging task, where it takes 20 times longer steps than the 2D case to reach the goal.

Fig. 2 visualizes the trajectories obtained by the IRL algorithms. The symmetric multi-goal environment expermient (left) demonstrates that CAIRL is capable of recovering a multi-modal policy resulting to reach all goals. For evaluating survival bias handling, we implemented a similar task where the right side goal is located further than others (right). Table 2 shows episode time steps and ratios that the IRL agent reach the goal in the right-side. The result shows that CAIRL can induce more uniform multi-modal distribution than AIRL and that the algorithm is robust to the survival bias.

Table 2: Statistics of CAIRL and AIRL in the asymmetric multi-goal environment in 1,000 sampled trajectories.

	CAIRL	AIRL
Ep. Timestep	$8.63_{\pm 5.1}$	$10.87_{\pm 5.4}$
Right-side goal	0.255	0.221

Fig. 3 shows a result that CAIRL outperforms AIRL in the quality of generated trajectories. CAIRL searched all the four goals with the robot, which prominently shows that our algorithm can reconstruct rewards from multi-modal policies in the complex control tasks.

Imitation Learning. The second experiment is the imitation learning tasks of continuous domains from the Gym benchmark suite (Brockman et al., 2016). We evaluated our algorithm on five challenging tasks, including Humanoid benchmark with 21 action dimensions.

Figure 5: Illustrations of transfer learning and total distance traveled by transfer learning agents.

In Fig. 4, training curves are visualized with the results of five individual runs where the scores are rescaled with respect to the expert score, and the shaded regions represent the minimum and maximum scores. Since expert policies are uni-modal Gaussian policies, we restricted the number of trajectories to 4 except the Humanoid task. In the figure, CAIRL (blue lines) shows the fast learning speed in the early phase of training and at least the second-best results for all provided experiments. CAIRL clearly outperforms previous methods in the Hopper-v3, Walker2d-v3, and the Humanoid-v3 tasks. These tasks are considered to be challenging due to the harsh termination condition. We note that AIRL shows slower learning when the number of trajectories are realtively small. In our experiments, FAIRL showed the lowest performance. We suspect that the FAIRL reward formulation $r(s,a) = \exp(d(s,a)) \cdot (-d(s,a))$ sometimes give too much penalty for a single step reward, even when the proposed clipping method is applied.

Transfer Learning. The third experiment is the transfer learning tasks. The setup is inspired by Fu et al. (2017), but the settings are quite different. We trained each IRL network in the target (test) environment. To simply put, our experiment aims to measure the flexibility of the reward learning process. The formulation was designed to show that knowledge transfer requires adaptation. We wanted to find out whether each algorithm provides helpful rewards without pretraining. Also, it is natural to think that only a chunk of trajectories is available in a realistic problem. We implemented three transfer learning tasks called SlopeHopper, SlopeWalker2d, and CrippledAnt. In the Slope-Hopper and SlopeWalker task, the agent has the same configuration with the original 3D models but the ground is tilted by certain degree ranges to $[1, 15]$. In the CrippledAnt task, the robot has noticeably shorter forelegs as colored red in Fig. 5. We additionally restricted the joint angles of forelegs in the range of $\{.01,.25,.50,.75,1.0\}$ compared to the original model.

Given the expert trajectories from the source environments, the results of transfer learning tasks are shown in Fig. 5. For each task, we repeated all runs 5 times and report the results which are averaged over scores from the last 0.5 million training steps. In transfer learning setting, CAIRL outperformed other algorithms considerably that it achieved the highest performance for every experiment. The results imply that the algorithm extracted informative rewards for new environments with different dynamics, such that our reward acquisition methods are robust with the variation between tasks. The experiments have also verified that with the proper consideration of temporal dependencies, the AIL algorithms could be extended towards transfer learning problems.

7   CONCLUSION

In this paper, we have proposed a causal AIRL algorithm that recovers a robust reward function. We have provided theoretical analyses, including reward shaping in entropy-regularized MDPs, and the connection between adversarial learning and energy-based RL. We have proposed a novel dual discriminator architecture, which learns a reward and a value function of regularized Bellman optimality equations. Our model can efficiently disentangle biases originated from state occupancy and terminal states. We have verified that the proposed IRL method has clear advantages over AIRL for learning multi-modal behaviors and handling termination biases. The proposed method recovers state-conditioned rewards, which has advantages over AIL algorithms in terms of the robustness of imitation performance in challenging continuous domains. Furthermore, the proposed method outperformed other methods in domain adaptation in the transfer learning experiments.

REFERENCES

Kavosh Asadi and Michael L Littman. An alternative softmax operator for reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 243–252. JMLR. org, 2017.

Samaneh Azadi, Catherine Olsson, Trevor Darrell, Ian Goodfellow, and Augustus Odena. Discriminator rejection sampling. *arXiv preprint arXiv:1810.06758*, 2018.

Monica Babes, Vukosi Marivate, Kaushik Subramanian, and Michael L Littman. Apprenticeship learning about multiple intentions. In *Proceedings of the 28th International Conference on Machine Learning (ICML-11)*, pp. 897–904, 2011.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016.

Nicolò Cesa-Bianchi, Claudio Gentile, Gábor Lugosi, and Gergely Neu. Boltzmann exploration done right. In *Advances in neural information processing systems*, pp. 6284–6293, 2017.

Tong Che, Ruixiang Zhang, Jascha Sohl-Dickstein, Hugo Larochelle, Liam Paull, Yuan Cao, and Yoshua Bengio. Your gan is secretly an energy-based model and you should use discriminator driven latent sampling. *arXiv preprint arXiv:2003.06060*, 2020.

Yunjey Choi, Minje Choi, Munyoung Kim, Jung-Woo Ha, Sunghun Kim, and Jaegul Choo. Stargan: Unified generative adversarial networks for multi-domain image-to-image translation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 8789–8797, 2018.

LI Chongxuan, Taufik Xu, Jun Zhu, and Bo Zhang. Triple generative adversarial nets. In *Advances in neural information processing systems*, pp. 4088–4098, 2017.

Chelsea Finn, Sergey Levine, and Pieter Abbeel. Guided cost learning: Deep inverse optimal control via policy optimization. In *International Conference on Machine Learning*, pp. 49–58, 2016.

Justin Fu, Katie Luo, and Sergey Levine. Learning robust rewards with adversarial inverse reinforcement learning. *arXiv preprint arXiv:1710.11248*, 2017.

Zhe Gan, Liqun Chen, Weiyao Wang, Yuchen Pu, Yizhe Zhang, Hao Liu, Chunyuan Li, and Lawrence Carin. Triangle generative adversarial networks. In *Advances in neural information processing systems*, pp. 5247–5256, 2017.

Matthieu Geist, Bruno Scherrer, and Olivier Pietquin. A theory of regularized Markov decision processes. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2160–2169, Long Beach, California, USA, 09–15 Jun 2019. PMLR.

Seyed Kamyar Seyed Ghasemipour, Richard Zemel, and Shixiang Gu. A divergence minimization perspective on imitation learning methods. In *Conference on Robot Learning*, pp. 1259–1277. PMLR, 2020.

Tuomas Haarnoja, Haoran Tang, Pieter Abbeel, and Sergey Levine. Reinforcement learning with deep energy-based policies. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1352–1361. JMLR. org, 2017.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pp. 1856–1865, 2018.

Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. In *Advances in NIPS*, pp. 4565–4573, 2016.

Vijaymohan R Konda and Vivek S Borkar. Actor-critic–type learning algorithms for markov decision processes. *SIAM Journal on control and Optimization*, 38(1):94–123, 1999.

Ilya Kostrikov, Kumar Krishna Agrawal, Debidatta Dwibedi, Sergey Levine, and Jonathan Tompson. Discriminator-actor-critic: Addressing sample inefficiency and reward bias in adversarial imitation learning. *arXiv preprint arXiv:1809.02925*, 2018.

Gerhard Kramer. *Directed information for channels with feedback*. PhD thesis, ETH Zurich, 1998.

Sergey Levine and Vladlen Koltun. Continuous inverse optimal control with locally optimal examples. In *Proceedings of the 29th International Coference on International Conference on Machine Learning*, ICML'12, pp. 475–482, Madison, WI, USA, 2012. Omnipress. ISBN 9781450312851.

Minghuan Liu, Tairan He, Minkai Xu, and Weinan Zhang. Energy-based imitation learning. *arXiv preprint arXiv:2004.09395*, 2020.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Gergely Neu and Csaba Szepesvári. Apprenticeship learning using inverse reinforcement learning and gradient methods. *arXiv preprint arXiv:1206.5264*, 2012.

Andrew Y Ng and Stuart J Russell. Algorithms for inverse reinforcement learning. In *Proceedings of the Seventeenth International Conference on Machine Learning*, pp. 663–670. Morgan Kaufmann Publishers Inc., 2000.

Andrew Y Ng, Daishi Harada, and Stuart Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *ICML*, volume 99, pp. 278–287, 1999.

Fabio Pardo, Arash Tavakoli, Vitaly Levdik, and Petar Kormushev. Time limits in reinforcement learning. *arXiv preprint arXiv:1712.00378*, 2017.

Dean A Pomerleau. Efficient training of artificial neural networks for autonomous navigation. *Neural computation*, 3(1):88–97, 1991.

Deepak Ramachandran and Eyal Amir. Bayesian inverse reinforcement learning. In *Proceedings of IJCAI*, pp. 2586–2591, 2007.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Wenjie Shi, Shiji Song, and Cheng Wu. Soft policy gradient method for maximum entropy deep reinforcement learning. *arXiv preprint arXiv:1909.03198*, 2019.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. The MIT Press, second edition, 2018.

Umar Syed, Michael Bowling, and Robert E Schapire. Apprenticeship learning using linear programming. In *Proceedings of the 25th international conference on Machine learning*, pp. 1032–1039. ACM, 2008.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 23–30. IEEE, 2017.

George Tucker, Surya Bhupatiraju, Shixiang Gu, Richard E Turner, Zoubin Ghahramani, and Sergey Levine. The mirage of action-dependent baselines in reinforcement learning. *arXiv preprint arXiv:1802.10031*, 2018.

Wenhao Yang, Xiang Li, and Zhihua Zhang. A regularized approach to sparse optimal policy in reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 5938–5948, 2019.

Tianhao Zhang, Zoe McCarthy, Owen Jow, Dennis Lee, Xi Chen, Ken Goldberg, and Pieter Abbeel. Deep imitation learning for complex manipulation tasks from virtual reality teleoperation. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1–8. IEEE, 2018.

Junbo Zhao, Michael Mathieu, and Yann LeCun. Energy-based generative adversarial network. *arXiv preprint arXiv:1609.03126*, 2016.

Zhiming Zhou, Jiadong Liang, Yuxuan Song, Lantao Yu, Hongwei Wang, Weinan Zhang, Yong Yu, and Zhihua Zhang. Lipschitz generative adversarial nets. In *International Conference on Machine Learning*, pp. 7584–7593, 2019.

Yuke Zhu, Ziyu Wang, Josh Merel, Andrei Rusu, Tom Erez, Serkan Cabi, Saran Tunyasuvunakool, János Kramár, Raia Hadsell, Nando de Freitas, et al. Reinforcement and imitation learning for diverse visuomotor skills. *arXiv preprint arXiv:1802.09564*, 2018.

Brian D Ziebart. *Modeling Purposeful Adaptive Behavior with the Principle of Maximum Causal Entropy*. PhD thesis, Carnegie Mellon University, 2010.

Brian D Ziebart, Andrew Maas, J Andrew Bagnell, and Anind K Dey. Maximum entropy inverse reinforcement learning. 3:1433–1438, 2008.

Brian D Ziebart, J Andrew Bagnell, and Anind K Dey. Modeling interaction via the principle of maximum causal entropy. In *Proceedings of the 27th International Conference on International Conference on Machine Learning*, pp. 1255–1262. Omnipress, 2010.

Haosheng Zou, Tongzheng Ren, Dong Yan, Hang Su, and Jun Zhu. Reward shaping via meta-learning. *arXiv preprint arXiv:1901.09330*, 2019.

A   PROOFS

Proposition 4.1. *Let* $\mathbf{r}$ *be a function satisfying Eqn. 4. Then the expected cumulative reward of* π
has following property: $\mathbb{E}_\pi\big[\mathbf{r}(s,a) + \mathcal{H}(\pi(a|s))\big] = -\mathbb{E}_\pi\big[\mathrm{D}_{\mathrm{KL}}\big(\pi(\cdot|s)\big\|\pi_E(\cdot|s)\big)\big] + \mathbb{E}_{s\sim p_0}\big[\Psi(s)\big].$

Proof. $\rho_\pi(s)$ denotes the state-only occuany measure of state s.

$$
\begin{aligned}
\mathbb{E}_\pi[\mathbf{r}(s,a) + \mathcal{H}(\pi(a|s))] &= \mathbb{E}\Big[\sum_{t=0}^{\infty}\gamma^t(\mathbf{r}(s_t,a_t) - \log\pi(a_t|s_t))\Big] \\
&= \mathbb{E}\Big[\sum_{t=0}^{\infty}\gamma^t(\log\pi_E(a_t|s_t) - \log\pi(a_t|s_t) - \gamma\Psi(s_{t+1}) + \Psi(s_t))\Big] \\
&= \mathbb{E}\Big[\sum_{t=0}^{\infty}\gamma^t(\log\frac{\pi_E(a_t|s_t)}{\pi(a_t|s_t)}) - \sum_{t=0}^{\infty}\gamma^{t+1}\Psi(s_{t+1}) + \sum_{t=0}^{\infty}\gamma^t\Psi(s_t)\Big] \\
&= \mathbb{E}\Big[\sum_{t=0}^{\infty}\gamma^t(\log\frac{\pi_E(a_t|s_t)}{\pi(a_t|s_t)}) - \sum_{t=1}^{\infty}\gamma^t\Psi(s_t) + \sum_{t=0}^{\infty}\gamma^t\Psi(s_t)\Big] \\
&= \mathbb{E}\Big[\sum_{t=0}^{\infty}\gamma^t(\log\frac{\pi_E(a_t|s_t)}{\pi(a_t|s_t)}) + \Psi(s_0)\Big] \\
&= \int_\mathcal{S}\int_\mathcal{A}\rho_\pi(s,a)\Big[\log\frac{\pi_E(a|s)}{\pi(a|s)}\Big]\mathrm{d}a\mathrm{d}s + \int_\mathcal{S}p_0(s)\Psi(s)\mathrm{d}s \\
&= \int_\mathcal{S}\rho_\pi(s)\int_\mathcal{A}\pi(a|s)\Big[\log\frac{\pi_E(a|s)}{\pi(a|s)}\Big]\mathrm{d}a\mathrm{d}s + \mathbb{E}_{s\sim p_0}[\Psi(s)] \\
&= -\int_\mathcal{S}\rho_\pi(s)(\mathrm{D}_{\mathrm{KL}}(\pi(\cdot|s)\|\pi_E(\cdot|s)))\mathrm{d}s + \mathbb{E}_{s\sim p_0}[\Psi(s)] \\
&= -\int_\mathcal{S}\rho_\pi(s)\int_\mathcal{A}\pi(a|s)(\mathrm{D}_{\mathrm{KL}}(\pi(\cdot|s)\|\pi_E(\cdot|s)))\mathrm{d}a\mathrm{d}s + \mathbb{E}_{s\sim p_0}[\Psi(s)] \\
&= -\mathbb{E}_\pi\big[\mathrm{D}_{\mathrm{KL}}\big(\pi(\cdot|s)\big\|\pi_E(\cdot|s)\big)\big] + \mathbb{E}_{s\sim p_0}\big[\Psi(s)\big].
\end{aligned}
$$

Therefore, the reward function $\mathbf{r}(s,a)$ also provides the same global objective as the likelihood $\log\pi_E(a|s)$. $\qquad\square$

Proposition 5.1. *If all critic functions are optimal, the following equality holds.*

$$
\nabla_\phi\mathbb{E}_{\pi_\phi}\big[\mathrm{D}_{\mathrm{KL}}\big(\pi_\phi(\cdot|s)\big\|\pi_E(\cdot|s)\big)\big] = -\mathbb{E}_{\pi_\phi}\big[Q^{\pi_\phi}(s,a)\nabla_\phi\log\pi_\phi(a|s) + \nabla_\phi\mathcal{H}(\cdot|s)\big],
$$

where $Q^\pi(s,a) \triangleq r_\theta(s,a) + \mathbb{E}\big[\sum_{t=1}^{\infty}\gamma^t(r_\theta(s_t,a_t) - \log\pi_\phi(a_t|s_t))\big|s_0 = s, a_0 = a, \pi\big].$

Proof. By the policy gradient theorem Sutton & Barto (2018), we can derive the gradient of ϕ when initial state is s.

$$
\begin{aligned}
-\nabla_\phi\mathbb{E}_{\pi_\phi}\Big[\mathrm{D}_{\mathrm{KL}}\big[\pi_\phi(\cdot|s)\big\|\pi_E(\cdot|s)\big]\Big|s_0 = s\Big] &= \nabla_\phi(\mathbb{E}_{\pi_\phi}\big[r_\theta(s,a) - \log\pi_\phi(a|s)\big|s_0 = s\big] + const.) \\
&= \nabla_\phi\mathbb{E}\Big[\sum_{t=0}^{\infty}\gamma^t\big(r_\theta(s_t,a_t) - \log\pi_\phi(a_t|s_t)\big)\Big|s_0 = s\Big] \\
&= \nabla_\phi V^{\pi_\phi}(s)
\end{aligned}
$$

where $V^\pi(s) \triangleq \mathbb{E}\big[\sum_{t=0}^{\infty}\gamma^t\big(r_\theta(s_t,a_t) - \log\pi_\phi(a_t|s_t)\big)\big|s_0 = s, \pi\big]$. By the product rule, we get

$$
\begin{aligned}
\nabla_\phi V^{\pi_\phi}(s) &= \int_\mathcal{A}\nabla_\phi\pi_\phi(a|s)\big(Q^\pi(s,a) - \log\pi_\phi(a|s)\big) + \pi_\phi(a|s)\nabla_\phi\big(Q^\pi(s,a) - \log\pi_\phi(a|s)\big)\mathrm{d}a \\
&= \int_\mathcal{A}\nabla_\phi\pi_\phi(a|s)Q^\pi(s,a) + \pi_\phi(a|s)\nabla_\phi\mathcal{H}(\cdot|s) + \pi_\phi(a|s)\int_\mathcal{S}\gamma\mathcal{P}(s'|s,a)\nabla_\phi V^{\pi_\phi}(s')\mathrm{d}s'\mathrm{d}a.
\end{aligned}
$$

By repeatedly unrolling $\nabla_\phi V^\pi(s_t)$, we can derive the following form:

$$\nabla_\phi V^\pi(s) = \int_\mathcal{S} \sum_{k=0}^\infty \gamma^k \Pr(s \to x, k, \pi_\phi) \int_\mathcal{A} \Big(\nabla_\phi \pi_\phi(a|x) Q^\pi(x,a) + \pi_\phi(a|x) \nabla_\phi \mathcal{H}(\cdot|x) \Big) \mathrm{d}a \mathrm{d}x,$$

where $\Pr(s \to x, k, \pi)$ is the probability of transitioning from state s to state x in k steps under policy π. Thus, using the log derivative trick we can derive the rest of equations as follows

$$\nabla_\phi \mathbb{E}_{\pi_\phi} \big[D_{\mathrm{KL}} \big[\pi_\phi(\cdot|s) \big\| \pi_E(\cdot|s) \big] \big] = \int_\mathcal{S} p_0(s) \nabla_\phi \mathbb{E}_{\pi_\phi} \big[D_{\mathrm{KL}} \big[\pi_\phi(\cdot|s) \big\| \pi_E(\cdot|s) \big] \big| s_0 = s \big] \mathrm{d}s$$

$$= -\int_\mathcal{S} \sum_{t=0}^\infty \gamma^t Pr(s_t = s|\pi) \int_\mathcal{A} \Big(\nabla_\phi \pi_\phi(a|s) Q^\pi(s,a) + \pi_\phi(a|s) \nabla_\phi \mathcal{H}(\cdot|s) \Big) \mathrm{d}a \mathrm{d}s$$

$$= -\int_\mathcal{S} \rho_{\pi_\phi}(s) \int_\mathcal{A} \Big(\nabla_\phi \pi_\phi(a|s) Q^\pi(s,a) + \pi_\phi(a|s) \nabla_\phi \mathcal{H}(\cdot|s) \Big) \mathrm{d}a \mathrm{d}s$$

$$= -\int_\mathcal{S} \rho_{\pi_\phi}(s) \int_\mathcal{A} \pi_\phi(a|s) \Big((Q^\pi(s,a) \nabla_\phi \log \pi_\phi(a|s) + \nabla_\phi \mathcal{H}(\cdot|s) \Big) \mathrm{d}a \mathrm{d}s$$

$$= -\mathbb{E}_{\pi_\phi} \big[Q^\pi(s,a) \nabla_\phi \log \pi_\phi(a|s) + \nabla_\phi \mathcal{H}(\cdot|s) \big].$$

$\square$

Proposition 5.2. *If $f_{\theta,\psi}(s,a,s') = \log \pi_E(a|s)/u$ for all states, actions, and transition states, then*

$$h_\psi(s) = \log \Big[u \cdot \int_\mathcal{A} \exp\big\{ r_\theta(s,a) + \gamma \mathbb{E}_{s'|s,a} \big[h_\psi(s') \big] \big\} \mathrm{d}a \Big].$$

Thus h_ψ corresponds to the optimal value function of the mellowmax regularizer with $\alpha = 1$.

Proof.

$$r_\theta(s,a) + \gamma h_\psi(s') - h_\psi(s) = \log \pi_E(a|s) - \log u \quad \forall s' \in \mathcal{S}$$

$$\implies r_\theta(s,a) + \gamma \mathbb{E}_{s'|s,a}[h_\psi(s')] - h_\psi(s) = \log \pi_E(a|s) - \log u$$

$$\implies u \exp(r_\theta(s,a) + \gamma \mathbb{E}_{s'|s,a}[h_\psi(s')] - h_\psi(s)) = \pi_E(a|s)$$

$$\implies u \frac{\exp(r_\theta(s,a) + \gamma \mathbb{E}_{s'|s,a}[h_\psi(s')])}{\exp(h_\psi(s))} = \pi_E(a|s) \tag{10}$$

$$\implies \int_\mathcal{A} u \cdot \frac{\exp(r_\theta(s,a) + \gamma \mathbb{E}_{s'|s,a}[h_\psi(s')])}{\exp(h_\psi(s))} \mathrm{d}a = \int_\mathcal{A} \pi_E(a|s) \mathrm{d}a$$

$$\implies h_\psi(s) = \log \Big[u \cdot \int_\mathcal{A} \exp\big\{ r_\theta(s,a) + \gamma \mathbb{E}_{s' \sim \mathcal{P}(\cdot|s,a)} \big[h_\psi(s') \big] \big\} \mathrm{d}a \Big].$$

$\square$

B MAXIMUM CAUSAL ENTROPY FRAMEWORK

In Sec. B and Sec. C, we address similarities between frameworks of the maximum causal entropy IRL and the causal AIRL. Following the notation of Kramer (1998), the causal entropy can be defined as

$$\mathcal{H}(\mathbf{A}^T \| \mathbf{S}^T) \triangleq \mathbb{E}_{A,S}[-\log P(\mathbf{A}^T \| \mathbf{S}^T)] = \sum_{t=1}^T \mathcal{H}(A_t | \mathbf{S}_{1:t}, \mathbf{A}_{1:t-1}).$$

The objective of maximum causal entropy IRL can be formulated by the following optimization Ziebart et al. (2010):

$$\arg\max_{P(A_t|S_t)} \mathcal{H}(\mathbf{A}^T \| \mathbf{S}^T)$$

$$\text{such that: } \mathbb{E}_{p(S,A)}[\mathcal{F}(S,A)] = \mathbb{E}_{\hat{p}(S,A)}[\mathcal{F}(S,A)],$$

$$\forall s_t \quad \sum_{a_t} P(A_t | \mathbf{S}_{1:t}, \mathbf{A}_{1:t-1}) = 1,$$

where the overall dynamics $P(\mathbf{S}^T || \mathbf{A}^{T-1}) \triangleq \prod_{t=1}^{T} P(S_t | \mathbf{S}_{t-1}, \mathbf{A}_{t-1})$ are given.

According to Ziebart et al. (2010), the distribution satisfying the constrained optimization problem can be defined as a recurrence relation:

$$p_\theta(a_t | s_t) = \frac{\beta(s_t, a_t)}{\beta(s_t)}$$

$$\log \beta(s_t, a_t) = \theta^\mathsf{T} \mathcal{F}_{s_t, a_t} + \sum_{s_{t+1}} p(s_{t+1} | s_t, a_t) \log \beta(s_{t+1})$$

$$\log \beta(s_t) = \log \sum_{a_t} \beta(s_t, a_t) = \operatorname*{softmax}_{a_t} \log \beta(s_t, a_t).$$

With the perspective of energy-based RL, we draw the following implications from the solution:

- $p_\theta(a_t | s_t)$ can be understood as the unique fixed point of MaxEnt framework, which can be achieved by the optimization via soft RL algorithms.
- $r_\theta(s_t, a_t) = \theta^\mathsf{T} \mathcal{F}_{s_t, a_t}$ can be understood as a reward function which is subject to the linear constraints on feature function.
- $\log \beta(s_t, a_t)$ and $\log \beta(s_t)$ can be understood as the (optimal) soft values satisfying the Bellman equation.

C SOFT ADVERSARIAL INVERSE REINFORCEMENT LEARNING FORMULATION

As a direct interpretation of the maximum causal entropy framework, the goal of CAIRL can be seen as training a parameterized distribution over the expert trajectories as the following maximum-likelihood objective:

$$\max_\theta \mathcal{J}(\theta) = \max_\theta \mathbb{E}_{\pi_E}[\log p_\theta(a|s)], \tag{12}$$

where the conditional distribution $p_\theta(a_t | s_t)$ is parameterized as $p_\theta(a_t | s_t) \propto \exp\left(Q_\theta(s_t, a_t)\right)$. We can compute the gradient with respect to θ as follows:

$$\begin{aligned}
\frac{\partial}{\partial \theta} \mathcal{J}(\theta) &= \mathbb{E}_{\pi_E}\left[\frac{\partial}{\partial \theta} \log p_\theta(a|s)\right] \\
&= \mathbb{E}_{\pi_E}\left[\frac{\partial}{\partial \theta} Q_\theta(s, a) - \frac{\partial}{\partial \theta} \log Z_\theta(s)\right] \\
&= \mathbb{E}_{\pi_E}\left[\frac{\partial}{\partial \theta} Q_\theta(s, a)\right] - \mathbb{E}_{\pi_E}\left[\mathbb{E}_{a' \sim p_\theta(\cdot|s)}\left[\frac{\partial}{\partial \theta} Q_\theta(s, a')\right]\right],
\end{aligned} \tag{13}$$

where $Z_\theta(s)$ is the partition function normalizes the distribution p_θ. Since sampling with π_E and p_θ is difficult, we can think of substituting the formulation with the following adversarial learning form:

$$\mathbb{E}_{\pi_E}\left[\frac{\partial}{\partial \theta} r_\theta(s, a)\right] - \mathbb{E}_\pi\left[\frac{\partial}{\partial \theta} r_\theta(s, a)\right]. \tag{11}$$

Nevertheless the formulation in Eqn. 11 is similar with a standard adversarial framework with i.i.d. data, the approximation is not a safe choice because of unbounded divergences among π, p_θ, and π_E. Therefore, appropriate adversarial learning in sequential decision problems is essentially different to GANs for joint distribution matching.

In CAIRL, we replace the reward learning objective with training a logistic discriminator:

$$D_\theta(s, a) = \frac{\exp[f_\theta(s, a)]}{\exp[f_\theta(s, a)] + \kappa(s, a)},$$

where $\kappa(s, a) = \frac{\rho_\pi(s, a)}{\rho_E(s) \cdot u}$. The objective of the discriminator is to maximize the generalized Jensen-Shannon divergence between of the generated samples:

$$\mathcal{J}(D_\theta) = \mathbb{E}_{\pi_E}[\log D_\theta(s, a)] + \mathbb{E}_\pi[\log(1 - D_\theta(s, a))]$$

For the discriminators, the objective can be written as follows:

$$\mathcal{J}(D_\theta) = \mathbb{E}_{\pi_E}[\log D_\theta(s,a)] + \mathbb{E}_\pi[\log(1 - D_\theta(s,a))]$$

$$= \mathbb{E}_{\pi_E}\Big[\log \frac{\exp[f_\theta(s,a)]}{\exp[f_\theta(s,a)] + \kappa(s,a)}\Big] + \mathbb{E}_\pi\Big[\log \frac{\kappa(s,a)}{\exp[f_\theta(s,a)] + \kappa(s,a)}\Big]$$

$$= \mathbb{E}_{\pi_E}[f_\theta(s,a)] + \mathbb{E}_\pi[\kappa(s,a)] - 2 \cdot \mathbb{E}_{\tilde{\pi}}[\log\{\exp[f_\theta(s,a)] + \kappa(s,a)\}],$$

where the operator $\mathbb{E}_{\tilde{\pi}}$ denote the expectation using an occupancy measure $\rho_{\tilde{\pi}}(s,a) = \frac{\rho_E(s,a) + \rho_\pi(s,a)}{2}$. Taking the derivative with respect to θ,

$$\frac{\partial}{\partial\theta}\mathcal{J}(D_\theta) = \mathbb{E}_{\pi_E}\Big[\frac{\partial}{\partial\theta}f_\theta(s,a)\Big] - 2 \cdot \mathbb{E}_{\tilde{\pi}}\Big[\frac{\exp[f_\theta(s,a)]}{\exp[f_\theta(s,a)] + \kappa(s,a)}\frac{\partial}{\partial\theta}f_\theta(s,a)\Big]$$

$$= \mathbb{E}_{\pi_E}\Big[\frac{\partial}{\partial\theta}f_\theta(s,a)\Big] - \mathbb{E}_{\tilde{\pi}}\Big[\frac{\rho_E(s)\hat{p}_\theta(a|s)}{\frac{1}{2}\rho_E(s)\hat{p}_\theta(a|s) + \frac{1}{2}\rho_\pi(s,a)}\frac{\partial}{\partial\theta}f_\theta(s,a)\Big]$$

$$= \mathbb{E}_{\pi_E}\Big[\frac{\partial}{\partial\theta}f_\theta(s,a)\Big] - \mathbb{E}_{\pi_E}\Big[\sum_{a'\in\mathcal{A}}\hat{p}_\theta(a'|s) \cdot \delta(s,a') \cdot \frac{\partial}{\partial\theta}f_\theta(s,a')\Big],$$

where

$$\hat{p}_\theta(a|s) = u \cdot \exp(f_\theta(s,a)) \quad \text{and} \quad \delta(s,a) = \frac{\rho_E(s,a) + \rho_\pi(s,a)}{\rho_E(s)\hat{p}_\theta(a|s) + \rho_\pi(s,a)}.$$

The optimal θ can be easily found by considering $\frac{\partial}{\partial\theta}\mathcal{J}(D_\theta) = 0$, in condition of $\hat{p}_\theta(a|s) = \pi_E(a|s)$ with $\delta(s,a) = 1$ for all states and actions. Moreover, for the right hand side of the expression, we can draw the following properties of δ:

- If $\rho_\pi(s,a) \gg \rho_E(s,a)$, meaning the supports are disjoint, $\delta(s,a) \approx 1$.
- If $\rho_\pi(s,a) \approx \rho_E(s,a)$, where $\hat{p}_\theta(a|s)$ is normally closer to π_E than π, $\delta(s,a) \approx 1$.

Therefore, the expression matches the Eqn. 13. CAIRL approximates the maximum causal entropy framework without exhaustively computing the recursive equation, and also recovers a plausible reward function on both supports of ρ_π and ρ_E.

D EXPERIMENTAL DETAILS

D.1 MUTL-GOAL ENVIRONMENTS

- 2D Point Environment: Let the 2D coordinate denote the position of a point mass on the environment. The agent is generated according to the normal distribution $\mathcal{N}(\mathbf{0}, (0.1)^2\mathbf{I})$. The four goals are located at $(6,0)$, $(-6,0)$, $(0,6)$, and $(0,-6)$, where the agent can move maximum 1 unit per timestep for each coordinate. The ground-truth reward is given by the difference between successive values of a Gaussian mixture depicted as Fig. 6. The assymetric multi-goal environment has the same setting, except the goal of the east side is further located at $(12,0)$.

- 3D Ant Environment: Let the 2D coordinate representation denotes the orthogonal projection of the position of Ant robot torso. The simulated robot is spawned near the origin. The four goals are located at $(30,0)$, $(-30,0)$, $(0,30)$, and $(0,-30)$, where the agent has to control four legs to reach one of the goals. It requires approximately 150 timesteps for an expert to reach one of the goals from the initial position. A vector of the current position and the robot's joint values represent the state. Since it is hard to train a single expert model to represent the desired multi-modal behavior precisely, we evenly merged 2,000 trajectory samples from 8 uni-modal policies specialized in moving to one of the fixed positions.

D.2 TRANSFER LEARNING ENVIRONMENTS

The experiment setting was designed to show that imitation learning for realistic tasks regardless of domain shifts. We trained each IRL network in the target (test) environment. To simply put, our experiment aims to measure the flexibility of reward learning process. We used 1,000 trajectories from the source task as transfer learning data.

Figure 6: Illustrations of multi-goal environments. From the initial agent position, four goals are symmetrically located at the four cardinal directions. The ground-truth energy function of the 2D environment and the expert trajectory samples for each environment are displayed.

- SlopeHopper & SlopeWalker2d: We used the same 3D model from the Hopper-v3 and Walker2d-v3 Mujoco benchmarks. For each task, the ground is tilted with a certain degree in $[1, 15]$. For computing a state vector, the models' height is adjusted to the vertical distance from the slope.

- CrippledAnt: Compared to the original Ant model, we shortened the length of two forelegs to half. We additionally restricted the joint angles of forward legs in the range of $\{.01, .25, .50, .75, 1.0\}$. While the objective of the agent is for running to the right side, the reward can be calculated by the velocity of robot moving along the x-axis.

E   IMPLEMENTATION DETAILS

E.1   ALGORITHMS

Algorithm 1 summarizes the overall IRL procedures. The term "REG" in Line 7 of the algorithm refers to the shaping regularization minimizing squared L2-norm $\|\gamma h_{\bar{\psi}}(s') - h(s)\|_2^2$ with the regularization parameter $\lambda \in \mathbb{R}^+$ in order to make the overall algorithm well-defined. For stochastic action distributions, the temperature parameter α has to be multiplied for exact matching between conditional distributions. For ensuring Lipschitz continuity, every critic network is regularized by a gradient penalty (Zhou et al., 2019).

Algorithm 1 Causal adversarial inverse reinforcement learning.

1: **Input:** Expert trajectory dataset $\left\{\tau_E^{(i)}\right\}_{i=1}^N$, temperature α.
2: Initialize policy π_ϕ and critic functions $\bar{D}_\varphi$, and $D_{\theta,\psi}$.
3: **for** step i in $\{1, \ldots, N\}$ **do**
4:      Collect τ_π by executing π_ϕ.
5:      $\{(s_t, a_t, \cdot, s'_t)\}_{t=1}^T = \tau_\pi, \{(\bar{s}_t, \bar{a}_t, \cdot, \bar{s}'_t)\}_{t=1}^T = \tau_E^{(i)}$
6:      Update D_φ using $\frac{1}{T}\sum_{t=1}^T \left[\log(1 - D_\varphi(s_t)) + \log D_\varphi(\bar{s}_t)\right]$ with GP.
7:      Update $D_{\theta,\psi}$ using $\frac{1}{T}\sum_{t=1}^T \left[\log(1 - D_{\theta,\psi}(s_t, a_t, s'_t)) + \log D_{\theta,\psi}(\bar{s}_t, \bar{a}_t, \bar{s}'_t)\right]$ with REG+GP.
8:      Update π_ϕ with $\alpha \cdot r_\theta(s, a)$ using a maximum entropy policy optimization method.
9: **return** π_ϕ, r_θ

For a policy optimization in the experiments we used PPO implementation train policy by a clipped surrogate objective function as follows:

$$\mathcal{L}_{\pi_{\text{old}}}^{\text{CLIP}}(\phi) = \mathbb{E}_{\pi_{\text{old}}}\left[\min\left(\frac{\pi_\phi(a|s)}{\pi_{\text{old}}(a|s)}A_\alpha^{\pi_{\text{old}}}(s,a), \text{clip}\left(\frac{\pi_\phi(a|s)}{\pi_{\text{old}}(a|s)}, 1-\varepsilon, 1+\varepsilon\right)A_\alpha^{\pi_{\text{old}}}(s,a)\right)\right] \quad (12)$$

where ε is the clipping range of PPO algorithm, ensuring that the updated policy does not diverge too far from the previous distribution. One thing to be careful in the implementation is that the KL penalty terms are dependent on the policy distribution. PPO algorithm with the KL regularization.

The term $A_\alpha^{\pi_{\text{old}}}(s, a)$ can be computed as follows:

$$V^{\pi_{\text{old}}}(s) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t (r_\theta(s_t, a_t) - \alpha \log \pi_\phi(a_t|s_t)/u) \Big| s_0 = s, \pi_{\text{old}}\right], \tag{13}$$

$$Q^{\pi_{\text{old}}}(s, a) = r_\theta(s, a) + \mathbb{E}\left[\sum_{t=1}^{\infty} \gamma^t (r_\theta(s_t, a_t) - \alpha \log \pi_\phi(a_t|s_t)/u) \Big| s_0 = s, a_0 = a, \pi_{\text{old}}\right], \tag{14}$$

$$A^{\pi_{\text{old}}}(s, a) = Q^{\pi_{\text{old}}}(s, a) - V^{\pi_{\text{old}}}(s), \qquad \text{(Advantage estimate)} \tag{15}$$

$$A_\alpha^{\pi_{\text{old}}}(s, a) = A^{\pi_{\text{old}}}(s, a) - \alpha. \tag{16}$$

We refer the work of Shi et al. (2019) for the detailed derivation of entropy-regularized policy gradient algorithms.

E.2 Network Architectures and Hyperparameters

For all policy and discriminator networks, we use networks with 2-layer MLP with 256-dim layers, and the activation function is ReLU. For input layer, we normalize inputs (state and action vectors) by calculating exponential moving average and variance.

Details for Policy Networks For multi-goal environments, the policy function is represented by a Gaussian mixture with four modes. In contrast, a single diagonal Gaussian function is used for other unimodal tasks. For enforcing action bounds, we apply an invertible squashing function (tanh) to the raw action samples and compute the likelihoods of the bounded actions such as $\texttt{tanh}(\texttt{Normal}(\mu, \sigma))$ (Haarnoja et al., 2018). In our implementation, we separated the distribution network into mean network and standard deviation network. The gradient penalty regularization is applied to the value network.

Details for CAIRL Networks For CAIRL networks, the reward network consists softplus activation at the final output layer while the potential network has linear activation. Gradient penalty is also used in the both networks. We do not explicitly construct the target potential networks, instead we use the same potential network, but the target potential network does not involved any gradient computation. Also, to discard the learning of terminal state values, $h_{\bar{\psi}}$ is outputs as follows:

$$h_{\bar{\psi}}(s) = \begin{cases} 0 & \text{if } s \text{ is a terminal state not caused by time limits,} \\ \texttt{no\_grad}(h_\psi(s)) & \text{otherwise} \end{cases}$$

Table 3 shows the hyperparameters of conducted experiments.

Table 3: Hyperparameters.

(a) Shared parameters

Parameter	Value
Optimizer	Adam$(0, 0.99)$
Learning rate (policy)	$1 \cdot 10^{-4}$
Learning rate (discriminator)	$4 \cdot 10^{-4}$
Discount factor (γ)	0.99
Clipping Range (ε)	0.2
Gradient penalty (η)	10^{-4}
Shaping regularization (λ)	10^{-4}
Batch size per rollout	2048
Policy rollouts	3
Discriminator rollouts	3
Gradient steps per iteration	15

(b) Environment specific parameters

Environment	# of threads	Temp. (α)
Multi-goal (Point)	1	1
Multi-goal (Ant)	16	10^{-2}
Humanoid-v3	8	10^{-3}
Walker2d-v3	3	10^{-3}
Others	1	10^{-2}

F   ADDITIONAL EXPERIMENTAL RESULTS

F.1   ADDITIONAL BASELINE RESULTS

Table 4: The evaluation on imitation learning benchmark control tasks presented over 5 different random seeds with 4 and 100 expert trajectory data.

Method	Environment				
	Hopper-v3	HalfCheetah-v3	Walker2d-v3	Ant-v3	Humanoid-v3
Expert	$3688.9_{\pm358}$	$3580.3_{\pm135}$	$5297.0_{\pm696}$	$4030.8_{\pm839}$	$9049.0_{\pm3114}$
GAIL	$3227.6_{\pm403}$	$\mathbf{3431.9_{\pm251}}$	$2369.8_{\pm507}$	$\mathbf{4090.8_{\pm252}}$	$8816.5_{\pm504}$
AIRL	$\mathbf{3229.8_{\pm341}}$	$3127.6_{\pm296}$	$\mathbf{3326.7_{\pm1231}}$	$3956.5_{\pm302}$	$538.8_{\pm580}$
FAIRL	$374.1_{\pm300}$	$1147.4_{\pm330}$	$281.4_{\pm116}$	$1501.3_{\pm371}$	$351.9_{\pm30}$
CAIRL	$\mathbf{3565.4_{\pm233}}$	$3163.5_{\pm297}$	$5089.6_{\pm339}$	$3990.9_{\pm254}$	$\mathbf{9644.6_{\pm385}}$
GAIL	$\mathbf{3513.1_{\pm273}}$	$\mathbf{3493.9_{\pm279}}$	$4392.4_{\pm391}$	$\mathbf{4093.2_{\pm258}}$	$9199.4_{\pm443}$
AIRL	$3349.0_{\pm318}$	$\mathbf{3482.6_{\pm202}}$	$\mathbf{5165.7_{\pm205}}$	$4027.0_{\pm282}$	$8532.5_{\pm720}$
FAIRL	$236.2_{\pm10}$	$744.2_{\pm249}$	$281.4_{\pm116}$	$2106.0_{\pm372}$	$375.2_{\pm22}$
CAIRL	$\mathbf{3571.6_{\pm309}}$	$3246.4_{\pm244}$	$\mathbf{5268.1_{\pm194}}$	$3979.6_{\pm296}$	$\mathbf{9469.5_{\pm374}}$

F.2   VISUALIZATION OF TRAJECTORIES GENERATED BY IMITATION LEARNING AGENTS

Fig. 7 shows the trajectories from the trained models in the 3D environment with different seeds. Firstly, the result suggest that CAIRL recovers multi-modal policies which is equivalent to the property MaxEnt IRL. At the same time, CAIRL is fundamentally advanced algorithm compared to MaxEnt IRL algorithms because it can be applied various large domain without knowing dynamics by by enlarging number of parameters in neural networks.

Figure 7: Multi-goal Ant trajectories with different random seeds

F.3   ABLATION STUDY ON HYPERPARAMETERS

We provide experiments on ablation study on three controllable hyperparameters in Fig. 8.

Figure 8: Experiments on hyperparameters of CAIRL. (a) If the shaping regularization λ is excessively high, learning of the potential-based shaping is disabled, and the reward function shows unstable behavior. (b) The gradient penalty is applied for ensuring convergence of discriminators. The results suggest that sufficiently low gradient penalty is preferred for achieving desired performance (c) compared to the other hyperparameters, CAIRL is robust with the temperature α.

F.4   VISUALIZATION OF CRIPPLEDANT LOCOMOTION

We provide the visualization of generated samples from a trained agent trained by CAIRL algorithm in Fig. 9. Even though dynamics of the environment is considerably misaligned, the algorithm still can teach agent appropriate algorithm to teach an agent to go desired direction. We believe that this work also provided effective transfer learning algorithm for sequential decision problems.

Figure 9: Visualization of trained agent on CrippledAnt environment. The model maximizes the movement speed toward the right side, without showing biased locomotion such as moving to the forward or to the backward. Also, the orientation of the torso is preserved throughout the episode, implying that the algorithm is capable of imitating experts even under variation in the dynamics.