A Text is Worth Several Tokens:
Text Embedding from LLMs Secretly Aligns Well with The Key Tokens

Abstract

Text embeddings from large language models (LLMs) have achieved excellent results in tasks such as information retrieval, semantic textual similarity, etc. In this work, we show an interesting finding: when feeding a text into the embedding LLMs, the obtained text embedding will be able to be aligned with the key tokens in the input text. We first fully analyze this phenomenon on eight embedding LLMs and show that this phenomenon is universal and is not affected by model architecture, training strategy, and embedding method. With a deeper analysis, we find that the main change in embedding space between the embedding LLMs and their original generative LLMs is in the first principal component. By adjusting the first principal component, we can align text embedding with the key tokens. Finally, we give several examples to demonstrate the vast application potential of this finding: (1) we propose a simple and practical sparse retrieval method based on the aligned tokens, which can achieve 80% of the dense retrieval effect of the same model while reducing the computation significantly; (2) we show that our findings provide a novel perspective to help understand fuzzy concepts (e.g., semantic relatedness vs. semantic similarity) and emerging technologies (e.g., instruction-following embedding) in this field.

1 Introduction

Large language models (LLMs) have recently made rapid progress on various natural language understanding tasks using the generative paradigm (Brown et al., 2020). However, not all tasks lend themselves to the generative paradigm in practice; tasks such as information retrieval, text clustering, and semantic text similarity usually rely on high-quality text embeddings. Thus, more and more attention has been focused on obtaining high-quality textual embeddings from large language models (Jiang et al., 2023b; Springer et al., 2024; BehnamGhader et al., 2024).

Figure 1: Existing paradigms on LLMs for text generation and embedding (left) and the novel findings of this work (right).

As shown on the left half of Figure 1, the LLM for generation takes the texts as input and output. The input text is tokenized and passed through the module f to obtain its hidden states. Then, a decoder layer g is required, which maps the high-dimensional hidden states to the vocabulary-length logits and computes the decoded probability for each token. When LLMs are converted for text embedding, current methods typically incorporate the following changes: (1) g is discarded because there is no need to map to the vocabulary; (2) f is converted into $\hat{f}$ using prompt-engineering (Jiang et al., 2023b; Springer et al., 2024) or contrastive learning (Muennighoff, 2022; BehnamGhader et al., 2024); and (3) a pooling strategy p is used to weighted sum of hidden states and obtain the text embedding.

In this paper, we are not proposing a new text embedding method for LLMs. Instead, our research surrounds a very interesting finding: when the text embedding obtained by $\hat{f}$ passes through the decoder layer g from the same LLM, the tokens with the highest decoding probability are highly related to the input text. In other words, the embedding of

the input text is aligned with some key tokens of that text. As shown in the right half of Figure 1, when the input text is "*What diseases are parrots prone to ?*", we can find the literally-related tokens, such as "disease" and the semantically-related tokens, such as "birds" and "suscept" have the highest decoding probabilities.

Considering the unusual nature of this phenomenon, we first introduce eight LLMs for text embedding to verify the generalizability of this finding (**Section 3**). Interestingly, we observe that the above phenomenon is universal and independent of the LLMs' architecture, the training strategy, and the embedding method. Subsequently, we perform deeper analyses based on these LLMs to understand this finding more intuitively and precisely.

To better explain this phenomenon, we compare the embedding spaces of f and $\hat{f}$ using spectral analysis (**Section 4**). We find that the dominant change in $\hat{f}$ is mainly concentrated in the first principal component. By manually adjusting the first principal component of the embedding space, we can replicate the phenomenon of aligning text embeddings to key tokens.

With a deeper understanding of our findings, we believe that it has a rich potential for application (**Section 5**). For example, we find that the criticism of LLM-generated embedding mainly stems from its high dimensionality (1024~4096), resulting in significant inference and storage overhead (Muennighoff et al., 2024). To address this, we propose a new sparse retrieval method based on our findings. We convert document embeddings into a sparse representation consisting only of aligned tokens and utilize a few aligned tokens from the query embedding for expansion. Despite its simplicity, our method achieves over 80% of the performance of the original LLM's dense retrieval and outperforms strong baselines like BM25 (Robertson et al., 2009) and SPLADE v2 (Formal et al., 2021). At the same time, we show that our work helps to intuitively understand (1) the training-data influence to semantic relevance and semantic similarity tasks and (2) the working mechanism of the instruction-following embedding (Su et al., 2023) in the Appendix.

The contributions of this paper are summarized as follows:

- We find an interesting and unusual phenomenon: the text embeddings obtained in the embedding LLM align with the key tokens;

- We explain why this phenomenon occurs from

the perspective of spectral analysis and find that the current method mainly changes the first principal component of the original embedding space of the LLMs;

- We show a series of example applications, including improvements to the method and interpretability of the model, demonstrating that our findings have large application value.

2 Background

2.1 Basic Paradigm

Given a LLM F, we can divide it into two parts:

$$F = g \circ f \tag{1}$$

where g is the decoder layer, and f is the rest modules of the LLM. In the existing LLM embedding methods, g is discarded, while f can be used as an encoder. Given a text s_i, we convert it to a token sequence using LLM's tokenizer and get $s_i = \{t_{i1}, \cdots, t_{il}\}$, where l is the sequence length; then we can get the hidden state of the last layer:

$$\mathbf{H} = [\mathbf{h}_{i1}^{(t)}, \cdots, \mathbf{h}_{il}^{(t)}] = f(s_i) \tag{2}$$

where $\mathbf{H} \in \mathbb{R}^{d \times l}$ and $\mathbf{h}_{ij}^{(t)} \in \mathbb{R}^{d \times 1}$ is the i-th d-dimensional column vector of $\mathbf{H}$. Subsequently, the pooling strategy $p(.)$ is used to $\mathbf{H}$ for the text embedding $\mathbf{h}_i$, which can be expressed as

$$\mathbf{h}_i = p(f(s_i)) = p(\mathbf{H}) = \sum_{j=1}^{l} \alpha_j \mathbf{h}_{ij}^{(t)} \tag{3}$$

where α_j is the weight of the hidden states and $\sum_{j=1}^{l} \alpha_j = 1$. Specifically, there are three popular pooling strategies in practice: for last pooling, $\alpha_j = 1$ if $j = l$ else is 0; for mean pooling, $\alpha_j = 1/l$ for each j; for weighted mean pooling (Muennighoff, 2022), $\alpha_j = j / \sum_{j=1}^{l} j$.

However, text embeddings obtained directly from the encoder f show poor performance. It is unsurprising since the pre-training task, i.e., the next token prediction, is not designed for embedding, and the unidirectional attention detracts from the expressive power of the hidden states (Springer et al., 2024). In the subsequent subsections, we describe how the existing methods improve the embedding's quality based on the top of f. For simplicity, we indiscriminately refer to the models proposed by the existing methods as $\hat{f}$.

2.2 Embedding via Prompt Engineering

The model $\hat{f}$ based on prompt engineering fills the text into prompt templates to improve the quality of text embedding, which can be expressed as

$$\hat{f}(s_i) = f(t(s_i)) \quad (4)$$

where $t(.)$ represents the operation of filling the text into a fixed prompt template.

PromptEOL (Jiang et al., 2023b) introduces a prompt template: `This sentence:"[text]" means in one word:"`, where `[text]` is a placeholder. In practice, the template where `[text]` is replaced by a specific text is sent into the encoder f, and the last pooling strategy is used to obtain the text embedding. The following works design the better prompt template based on task-oriented (Lei et al., 2024) or chain-of-thought (Zhang et al., 2024) can lead to better performance. Springer et al. (2024) proposes a prompt template: `Rewrite the sentence: [text], rewritten sentence: [text]`, where both `[text]` are the placeholder. In practice, both placeholders are filled with the same text, and the text embedding is obtained by the mean pooling strategy, but it is pooled only within the range of the second occurrence of the text.

The methods based on prompt engineering are simple and training-free, so they do not potentially compromise the generative capabilities of the LLMs. However, they provide limited performance improvement for text embedding tasks.

2.3 Embedding via Contrastive Learning

The methods based on contrastive learning inherited the good experience of the BERT-based encoder era (Gao et al., 2021). In these methods, $\hat{f}$ is fine-tuned f with contrastive learning. Due to the large parameter count of f itself, parameter-efficient fine-tuning methods such as LoRA (Hu et al., 2021) are usually used.

Given a text dataset D, for any text s_i sampled from D, we first obtain its embedding $\mathbf{h}_i$ from f with a specific pooling strategy. Then positive pairs $(\mathbf{h}_i, \mathbf{h}_i^+)$ and negative pairs $\{(\mathbf{h}_i, \mathbf{h}_{ij}^-)\}_{j=1}^N$ are constructed following different settings, where N is the negative example number. In the unsupervised setting, two data-augmented views of a text are considered a positive pair, while the negative samples are randomly sampled from the datasets. In the supervised setting, the positive pair is a labelled text pair, which can be query-document, question-answer or hypothesis-entailment (Li et al., 2023b),

etc., while potential hard negative pairs may be introduced, such as hypothesis-contradiction. Finally, the contrastive loss can be expressed as

$$\mathcal{L}_{\text{cl}} = -\log \frac{e^{d(\mathbf{h}_i, \mathbf{h}_i^+)/\tau}}{e^{d(\mathbf{h}_i, \mathbf{h}_i^+)/\tau} + \sum_{j=1}^N e^{d(\mathbf{h}_i, \mathbf{h}_{ij}^-)/\tau}} \quad (5)$$

where $d(\cdot, \cdot)$ is a distance function, τ is the temperature hyper-parameter. During fine-tuning, the contrastive loss draws positive text pairs close while pushing negative text pairs away.

Additional Tricks There are some effective tricks in the existing works, which include: (1) switching casual attention to bi-directional attention (BehnamGhader et al., 2024); (2) using different instruction prefixes for the datasets from different tasks to minimize inter-task interference (Su et al., 2023); (3) co-training contrastive learning and next word prediction to minimize reductions to generative capability (Muennighoff et al., 2024).

3 Embedding Aligns with Key Tokens

3.1 Motivation

To analyze the pre-trained transformer in the embedding space, Elhage et al. (2021); Geva et al. (2022); Dar et al. (2022) attempt to multiply the attention or feed-forward layer parameters with the token embedding matrix to explain how these parameters work. For example, Geva et al. (2022) finds that multiplying the feed-forward value vector with the token embedding matrix can obtain a distribution over the vocabulary, and the tokens with high probability can explain what the FFN updates to hidden layer representations. Inspired by these works, we try to interpret the text embeddings obtained from LLMs by mapping them into the token space.

3.2 Method

To implement the above idea, we need a text dataset D, and some $(\hat{f}, T, \mathbf{E}_g)$ triplets. $\hat{f}$ is the LLM outputing d-dimensional text embeddings, $T = \{t_1, \cdots, t_L\}$ is the L-sized vocabulary and $\mathbf{E}_g = [\mathbf{e}_{t_1}, \cdots, \mathbf{e}_{t_L}]^\top \in \mathbb{R}^{L \times d}$ is the token embedding matrix from the decoded layer g, where $\mathbf{e}_{t_j} \in \mathbb{R}^{d \times 1}$ is the token embedding of token t_j.

Note that T and $\mathbf{E}_g$ are determined by the original LLM F. $\mathbf{E}_g$ is also the only parameter in g[1],

---

[1]To the best of our knowledge, all popular LLMs follow the original design of the decoder layer from GPT (Radford et al., 2018), i.e., a linear layer without bias, which also can be regarded as a token embedding matrix.

Model	Architecture		Fine-tuning		Embedding	
	Backbone	Attention	Paradigm	Corpus	Pooling	Similarity
SGPT$_{nli}$	GPT-Neo	casual	SCL	NLI	weighted mean	cosine
SGPT$_{msmarco}$	(1.3B)	casual	SCL	MS MARCO	weighted mean	cosine
OPT$_{EOL}$	OPT	casual	PE	-	last token	dot product
OPT$_{EOL+CSE}$	(1.3B)	casual	PE+SCL	NLI	last	dot product
LLaMA$_{EOL}$	LLaMA	casual	PE	-	last token	dot product
LLaMA$_{EOL+CSE}$	(7B)	casual	PE+SCL	NLI	last	dot product
GritLM	Mistral	bi-directional	SCL+NTP	Tulu 2+E5+S2ORC	mean	cosine
LLM2Vec	(7B)	bi-directional	MNTP→SCL	E5	weighted mean	cosine

Table 1: Detailed information on the model used to study the embedding space. The paradigms are shortened as follows: supervised contrastive learning (SCL), unsupervised contrastive learning (UCL), prompt engineering (PE), next token prediction (NTP), and masked next token prediction (MNTP) (BehnamGhader et al., 2024) separately.

therefore, there is no difference between $\mathbf{E}_g \mathbf{h}_i$ and $g(\mathbf{h}_i)$ for any text embedding $\mathbf{h}_i \in \mathbb{R}^{d \times 1}$.

Process 1 Embedding-Token Alignment Analysis

Input: A text dataset D and the $(\hat{f}, T, \mathbf{E}_g)$ triplet.
1: Initialization: $i \leftarrow 0$, $j \leftarrow 0$
2: **while** $i \leq |D|$ **do**
3:     Get the i-th text s_i in D
4:     Deduplicate tokenizer(s_i) to obtain T_{s_i}
5:     Calculate $\mathbf{h}_i \leftarrow$ pooling($\hat{f}(s_i)$)
6:     **while** $j \leq |T|$ **do**
7:         Calculate $p(t_j|s_i) \leftarrow \mathbf{e}_{t_j}^\top \mathbf{h}_i$
8:         Update $j \leftarrow j + 1$
9:     **end while**
10:    Sort T in descending order by $p(t_i|s_i)$ to get $\hat{T}_{s_i}$
11:    Update $i \leftarrow i + 1$
12: **end while**
Output: T_{s_i} and $\hat{T}_{s_i}$

Given a text s_i sampled from D, we need to obtain its literal token set T_{s_i} and aligned token set $\hat{T}_{s_i}$ and capture the potential relation between these two sets. We use Process 1 to analyze the alignment of text embedding with the tokens. For T_{s_i}, we (1) convert s_i into tokens by the tokenizer of f and (2) deduplicate the token sequence to form a token set T_{s_i}. For $\hat{T}_{s_i}$, we (1) follow the pooling strategy of $\hat{f}$ to obtain the text embedding, (2) multiply the text embedding with the token embedding matrix and get the decoding score $p(t_j|s_i)$ for each token t_j, and (3) obtain the ordered token set $\hat{T}_{s_i}$ by sorting in descending order according to the score.

3.3 Experiment

Dataset D We randomly sample 10K of the 1M Wikipedia texts provided by Gao et al. (2021) and report the metric calculated by this dataset. Experiments on other datasets, such as SNLI (Bowman et al., 2015) and MSMARCO (Nguyen et al., 2016), lead to similar conclusions; please refer to

Appendix G for details.

Triplet $(\hat{f}, T, \mathbf{E}_g)$ We selected eight embedding model based on LLMs for analysis, which includes SGPT$_{nli}$ and SGPT$_{msmarco}$ (Muennighoff, 2022); OPT$_{EOL}$, OPT$_{EOL+CSE}$, LLaMA$_{EOL}$ and LLaMA$_{EOL+CSE}$ (Jiang et al., 2023b); GritLM (Muennighoff et al., 2024) and LLM2Vec (BehnamGhader et al., 2024). The key information overview of these models is placed in Table 1. We consider these embedding LLMs as $\hat{f}$ and obtain T and $\mathbf{E}_g$ from their backbone models.

Note that none of the improvement ideas for these models go beyond what we describe in Section 2, and please refer to Appendix A for detailed information on each model. Additionally, to ensure the generalizability of subsequent conclusions, the LLMs selected have the following attributes:

- **Different Architecture:** The backbones of these LLMs include: GPT-Neo (Gao et al., 2020), OPT (Zhang et al., 2022), LLaMA (Touvron et al., 2023) and Mistral (Jiang et al., 2023a). GritLM and LLM2Vec enable bi-directional attention, while the other LLMs keep the casual attention;
- **Different Fine-Tuning Methods:** These LLMs rely on different methods to improve the embedding capability, such as prompt engineering, contrastive learning, or multi-task learning, while the different corpus was used for fine-tuning.
- **Different Embedding Methods:** These LLMs use different pooling strategies to obtain embeddings and calculate the similarity using cosine similarity or dot product [2].

---

[2]Regardless of what the similarity metric is recommended,

Model	Top 10 Aligned Tokens
GPT-Neo	_and , Ċ _in _(. _the _as _on _for
SGPT$_{nli}$	_2003 2003 _03 _3 _March _game _released _three _games 03
SGPT$_{msmarco}$	_Advance _Game _Released _Releases _ADV Game _GAME _release _released _releases
OPT	Ċ _The _It _A _In _This _An _As _Its
OPT$_{EOL}$	released Re Released reve Game re November It in In
OPT$_{EOL+CSE}$	_Game _March _games _Nintendo _game _Microsoft _PlayStation _Games Game _2003
LLaMA	<0x0A> _The _It _A _In _This _Play _An _As
LLaMA$_{EOL}$	Re it re It _Re _it _It in The In
LLaMA$_{EOL+CSE}$	_game _games _Game game Game _Games _March _release _released _November
Mistral	, _and 2 _ 1 _in _(_as - _the
GritLM	_Game _Xbox _Pok _game _cross _revealed _Windows , _ _reveal
LLM2Vec	_release _releases _released _Release _revealed _releasing release _Xbox _game _reveal

Table 2: The top 10 aligned tokens for eight $\hat{f}$ for text embedding and their corresponding f for text generation when the input text is "*Revealed in March 2003, it was released across Game Boy Advance, PlayStation 2, GameCube, Xbox and Microsoft Windows in November 2003*".

3.4 Analysis of Aligned Tokens

Since the ordered set $\hat{T}_{s_i}$ is as large as T, we analyze only the top K tokens in $\hat{T}_{s_i}$. We introduce $\hat{T}_{s_i}^K$ to denote the first K elements in $\hat{T}_{s_i}$. We sample an input text from D and show the top 10 aligned tokens of the text embedding, i.e., $\hat{T}_{s_i}^{10}$, in Table 2. We also show the aligned tokens for the original f, using the same pooling strategy as the corresponding $\hat{f}$ for fair comparison.

We use different colours to indicate the relationship between each token and the surface token set T_{s_i}: Green represents the token is in T_{s_i}; Yellow represents the token and a token in T_{s_i} are same after stemming or lemmatization[3]; Red represents the token and any tokens in T_{s_i} have no literal connection. As shown in Table 2, we find that: (1) the text embeddings from the original f align with some tokens related T_{s_i}, but most of them are meaningless tokens, such as "and" and "the" etc; (2) compared to those aligned from f, the text embeddings from $\hat{f}$ also align with the tokens related to T_{s_i} but more meaningful, such as "game" and "November"; (3) even though some tokens are marked red, this only means that they are literally unrelated to T_{s_i}, but there may be a deeper connection. For example, "Nintendo" is the development company of "Game Boy Advance" in the input text.

Note that the input text is not specially selected, and we provide more cases in Appendix G.

To quantitatively portray the relationship between these aligned tokens and the input text, we designed three metrics and performed a more in-depth quantitative analysis. The analysis results show that text embeddings from f and $\hat{f}$ consistently align certain tokens in the input text, while $\hat{f}$-aligned tokens tend to be more diverse and more meaningful to the input text. Please refer to Appendix B for more details.

In addition, if the aligned token appears in the input text, we can record the words where the aligned tokens are split. We call these words decomposing the aligned tokens as "parent words". and analyze the connection between "parent word" and some traditional linguistic concepts of words, including part of speech, named entity and dependency grammar. Indeed, we find a high probability that "parent words" are nouns (NOUN), adjectives (ADJ) and proper nouns (PROPN), while there is a weaker connection with named entities and dependent grammars. Please refer to Appendix C for more details.

3.5 Discussion

How to understand? The text embedding aligns well with some key tokens in the input text after passing through the decoder layer, which means the text embedding is closer to these tokens than other tokens in high-dimensional space. Note that **the absolute position of the text embedding in**

---

we use a simple matrix multiplication between $\mathbf{E}_g$ and $\mathbf{h}_i$, to ensure consistency with the original decoding process.

[3]We use the tools provided by NLTK (Loper and Bird, 2002): SnowballStemmer for stemming and WordNetLemmatizer for lemmatization.

the whole space is described here, rather than in a subspace, since, as far as we can observe, all LLMs' decoder layer weights, i.e., the token embedding matrixes, are full rank.

How to explain? The explanation for this phenomenon is not straightforward because (1) the decoding layer, whose weights are never seen during the process from f to $\hat{f}$, can precisely decode some tokens related to the input text from the embedding; (2) the optimization objective of contrastive learning by itself does not guarantee it will happen. Therefore, we analyze the singular value spectrum of the embedding space before and after training in Section 4.

How to use? This interesting finding brings extreme interpretability to text embedding. In Section 5, we show the aligning tokens of the text embedding change with different training data and different instructions. Meanwhile, we propose a sparse retrieval method for solving the computational and storage overhead caused by the ultra-high dimensionality of LLM representations.

4 Spectral Analysis of Embedding Space

For a deeper understanding of the phenomenon, we use the same text dataset D in Section 3 and some $(f, \hat{f})$ pairs. We convert all texts in D into embeddings via f and use the SVD decomposition to obtain a set of standard orthogonal bases in d-dimensional space, which can be expressed as

$$\mathbf{U} = [\mathbf{u}_1, \cdots, \mathbf{u}_d] \in \mathbb{R}^{d \times d} \tag{6}$$

where $\mathbf{u}_j \in \mathbb{R}^{d \times 1}$ corresponds to the singular vector of j-th largest singular value.

For any text s_i from D, we denote its embedding obtained from f and $\hat{f}$ as $\mathbf{h}_i$ and $\hat{\mathbf{h}}_i$, separately. Then we metric the variation in each principal component between $\mathbf{h}_i$ and $\hat{\mathbf{h}}_i$ based on $\mathbf{U}$:

$$v_j = \mathop{\mathbb{E}}_{s_i \sim D} \left[\left(\hat{\mathbf{h}}_i - \mathbf{h}_i \right)^\top \mathbf{u}_j \right] \tag{7}$$

where v_j represents the variation in the j-th largest principal component. Due to space limitations, we select four $(f, \hat{f})$ pairs and plot their $\{v_j\}_{j=1}^d$ in Figure 2 and show the variation of the other four embedding LLMs in Appendix F.

Observation 1. *Compared to the original embedding space, the variation of the largest principal component, i.e., v_1, is dominant.*

Compared with the original LLMs, the embedding space corresponding to SGPT$_{\text{nli}}$, OPT$_{\text{EOL+CSE}}$, and LLaMA$_{\text{EOL+CSE}}$ significantly decreases in the first principal component, while only the pair corresponding to GritLM shows a small increase. As with the qualitative analysis, we speculate that this results from co-tuning with contrastive learning and next-token prediction. We further find that the embedding space corresponding to LLM2Vec has a significant decrease in the first principal component, too; please refer to Appendix F for details.

We further analyze the contribution of the first principal component and the other components in aligning tokens. Specifically, we divide the text embedding $\mathbf{h}_i$ into two components:

$$\mathbf{h}_i = \mathbf{h}_i^{\text{1st}} + \mathbf{h}_i^{\text{rest}} \tag{8}$$

where $\mathbf{h}_i^{\text{1st}} = \mathbf{u}_1^\top \mathbf{h}_i \mathbf{u}_1$ and $\mathbf{h}_i^{\text{rest}} = \sum_{j=2}^d \mathbf{u}_j^\top \mathbf{h}_i \mathbf{u}_j$. We then measure the contribution of $\mathbf{h}_i^{\text{1st}}$ and $\mathbf{h}_i^{\text{rest}}$ to aligning tokens. Based on the matrix decomposition, we divide the contribution into two parts:

$$\underbrace{\mathbf{E}_g \mathbf{h}_i}_{C_{s_i}} = \underbrace{\mathbf{E}_g \mathbf{h}_i^{\text{1st}}}_{C_{s_i}^{\text{1st}}} + \underbrace{\mathbf{E}_g \mathbf{h}_i^{\text{rest}}}_{C_{s_i}^{\text{rest}}}. \tag{9}$$

Specifically, we sample a text s_i from D, rank and obtain the top K tokens based on C_{s_i} and see how much $C_{s_i}^{\text{1st}}$ and $C_{s_i}^{\text{text}}$ contribute to the logits. Due In Figure 3a, we provide an example and obtain the following observation:

Observation 2. *The first principal component contributes much more to meaningless tokens than meaningful tokens.*

Combining Observation 1 and 2, we can see: (1) current text embedding LLMs always maximize the perturbation of the first principal component, while (2) the first principal component contributes mainly to meaningless tokens. Therefore, we give the following hypothesis:

Hypothesis 1. *The text embeddings of original LLMs have been aligned with the key tokens but are not reflected due to the affection by the first principal component.*

To verify the hypothesis, we manually adjust the embeddings from f. Specifically, considering that the variation on the other principal components is small compared to the first principal component, we can simplify as follows:

(a) GPT-Neo and SGPT$_{\text{nli}}$ (b) OPT and OPT$_{\text{EOL+CSE}}$ (c) LLaMA and LLaMA$_{\text{EOL+CSE}}$ (d) Mistral and GritLM

Figure 2: The variation in each principal component of the embedding space.

(a) Contribution to the aligned tokens.   (b) Aligned tokens after adjusting $\mathbf{u}_1$.

Figure 3: The situation of the aligned token when f is GPT-Neo, $\hat{f}$ is SGPT$_{\text{nli}}$ and the input text is "*Making a Killing is a 2018 Canadian-American crime-mystery film co-written, co-produced and directed by Devin Hume.*"

$$\underset{s_i \sim D}{\mathbb{E}} \left[\left(\hat{\mathbf{h}}_i - \mathbf{h}_i \right)^\top \mathbf{U} \right] \approx [v_1, 0, \cdots, 0]$$
$$\Rightarrow \underset{s_i \sim D}{\mathbb{E}} \hat{\mathbf{h}}_i \approx \underset{s_i \sim D}{\mathbb{E}} \mathbf{h}_i + v_1 \mathbf{u}_1 \tag{10}$$

Therefore, for each text embedding $\mathbf{h}_i$, we subtracted a certain amount of the first principal component and obtained the adjusted embedding $\mathbf{h}_i^{\text{adj}}$:

$$\mathbf{h}_i^{\text{adj}} = \mathbf{h}_i + \lambda \mathbf{u}_1 \tag{11}$$

where $\lambda \in R$ is a hyper-parameter. In Figure 3b, we report the top 10 tokens aligned by $\mathbf{h}_i^{\text{adj}}$ and their corresponding logits when adjusting λ for $0.95v_1$, v_1 and $1.05v_1$. As shown in Figure 3b, the embedding from f can align with more meaningful tokens of the input text by adjusting only the first principal component, verifying our hypothesis. We show that similar conclusions exist on f of other studies in Appendix F.

5 Potential Application

Sparse Retrieval The LLMs for embedding show superior Information Retrieval (IR) performance over the embedding models based on traditional PLMs (e.g., BERT (Kenton and Toutanova, 2019) and RoBERTa (Liu et al., 2019)). However, the dimensionality of these LLMs' output embeddings (1024~4096) far exceeds the 768 dimensions of traditional PLMs, which will incur exponential computation and storage overhead in practice. To overcome this problem, we propose a new sparse retrieval method to generate high-quality query extensions for queries and sparse representations for documents.

For each document d_i, we obtain its embedding $\hat{\mathbf{h}}_{d_i}$ and aligned token set $\hat{T}_{d_i}$ using the embedding LLM. Then we can maintain a vocabulary-length sparse vector $\tilde{h}_{d_i} = [w_{t_1}, \cdots, w_{t_L}]$, where only those dimensions corresponding to the top K aligned tokens are not zero:

$$w_{t_i} = \begin{cases} \mathbf{e}_{t_i}^\top \hat{\mathbf{h}}_{d_i} & \text{if } t_i \in \hat{T}_{d_i}^K \\ 0 & \text{otherwise} \end{cases} \tag{12}$$

For each query q_i, we get its surface token set T_{q_i} using the tokenizer and its aligned token set $\hat{T}_{q_i}$. It is easy to see that we can extend T_{q_i} using the first M elements in $\hat{T}_{q_i}$, obtaining the expanded token set $\tilde{T}_{q_i} = T_{q_i} \cup \hat{T}_{q_i}^M$.

In ad-hoc retrieval scenarios, all document sparse representations can be computed and cached

in advance while the query is computed and extended on the fly. Therefore, we can calculate the similarity of q_i and d_j as follows:

$$\text{Similarity}(q_i, d_j) = \sum_{t_k \in (\tilde{T}_{q_i} \cap \hat{T}_{d_i}^K)} w_{t_i} \quad (13)$$

We select LLM2Vec and GritLM due to their SOTA performance but up to 4096 embedding dimensions. For evaluation, we select four information retrieval datasets: FiQA (Maia et al., 2018), NFCorpus (Boteva et al., 2016), SciFact (Wadden et al., 2020) and ArguAna (Wachsmuth et al., 2018) and report the nDCG@10. For hyperparameter, we experiment under the settings $K \in \{1000, 2000, 3000\}$ and $M \in \{25, 50, 75, 100\}$ and report the best results in Table 3. We report the detailed results in Appendix E and find that performance is insensitive to K, while increasing with the increase of M in most cases.

Our sparse retrieval approach preserves 80% of the text embeddings' performance, outperforming the strong baselines: BM25 and SPLADEv2. Since the length of sparse representation is fixed, our sparse retrieval method can achieve a retrieval efficiency similar to that of BM25 when ignoring the consumption of the query encoding process. Compared to the original dense retrieval method, our method only needs 13% FLOPs in the inference stage (see Appendix E.4 for calculation details), with plenty of room for further improvement.

More Insights   Due to space constraints, we provide more sights in Appendix D, mainly explaining that different training data and different instructions align embeddings of the same input text to different tokens, achieving better performance for specific downstream tasks.

Model	FiQA	NFCorpus	SciFact	ArguAna
BM25	0.236	0.325	0.665	0.315
SPLADEv2	0.336	0.334	0.693	0.479
LLM2Vec	0.531	0.393	0.789	0.575
to Spar.	0.404	0.326	0.669	0.481
GirtLM	0.600	0.409	0.792	0.632
to Spar.	0.457	0.336	0.703	0.526

Table 3: The performance on four IR datasets. "to Spar." expresses our sparse retrieval method.

6   Related Work

Reconstructing the information of the original text from its embedding (Pan et al., 2020) has been explored primarily as a topic in privacy security. Recently, some works have tried reconstructing the original text from text embeddings by training additional decoders. Li et al. (2023a) is the first to try a single-round reduction method, while Morris et al. (2023) and Chen et al. (2024) use an iterative multi-round method, Vec2Text, to achieve better text reconstruction performance. Unlike these methods, **our findings do not involve any training process but only draw on the pre-trained decoding layers in the LLMs.**

The most related finding is proposed by Ram et al. (2023), which finds that the text embeddings produced by some BERT-based embedders (DPR (Karpukhin et al., 2020), MPNet (Song et al., 2020) and Spider (Ram et al., 2022)) can be aligned with key tokens after passing through the pre-trained MLM head. We would like to elaborate on the differences between the two pieces of work in the following three areas: (1) Ram et al. (2023) present three retrieval models that exhibit this phenomenon, whereas, in our preliminary experiments, many similar models below 1B do not exhibit this phenomenon, including but not limited to SimCSE (Gao et al., 2021), GTE (Li et al., 2023b), Contriever (Izacard et al., 2022), E5 (Wang et al., 2022) (these counter-examples lead to our exclusion of PLMs below 1B as study subjects and the choice of LLM). To our knowledge, this phenomenon is universally present in LLM, and no counter-examples have been found to date; (2) Ram et al. (2023) primarily describe this phenomenon, while this work further analyzes and explains its cause using spectral analysis; (3) Ram et al. (2023) only focuses on dense retrieval applications, while we provide an application example of sparse retrieval and two application examples of interpretability.

7   Conclusion

In this work, we show the alignment of text embeddings obtained from LLMs for embedding with key tokens in the input text. We first perform qualitative and quantitative analyses on eight LLMs to demonstrate the generalizability of our conclusions. Then, We use spectral analysis to understand the phenomenon better and show that text embeddings can be aligned to key tokens by adjusting the first principal component. For application, three examples given on interpretability or information retrieval demonstrate our findings' broad application promise and continued research value.

Limitation

We summarize several limitations of this work as follows:

- For universality, we cannot observe a similar phenomenon in the embedding models based on traditional PLMs except DPR (Karpukhin et al., 2020). We conjecture that the reason comes from two sources: (1) traditional PLMs have a higher degree of embedding space variation than LLMs due to too few parameters; (2) traditional PLMs use a complex MLM head for training, and the text embedding is obtained too far away from the final decoded token embedding matrix, resulting in no dependencies between them.

- For the study targets, we only conducted the empirical study for the LLMs for English embedding. We have not extended the study to a multi-lingual setting due to insufficient LLMs for multi-lingual embedding.

- In Section 4, we have only shown that adjusting the first principal component can achieve alignment with key tokens, but we have not yet been able to explain why the pre-training phase of the LLMs can form such an embedding space, nor can we achieve the same performance as the existing methods by tuning only the first principal component. At the same time, it is conceivable that we cannot achieve a similar embedding quality to contrastive learning by adjusting only the first principal component.

References

Parishad BehnamGhader, Vaibhav Adlakha, Marius Mosbach, Dzmitry Bahdanau, Nicolas Chapados, and Siva Reddy. 2024. Llm2vec: Large language models are secretly powerful text encoders. *arXiv preprint arXiv:2404.05961*.

Vera Boteva, Demian Gholipour, Artem Sokolov, and Stefan Riezler. 2016. A full-text learning to rank dataset for medical information retrieval. In *Advances in Information Retrieval: 38th European Conference on IR Research, ECIR 2016, Padua, Italy, March 20–23, 2016. Proceedings 38*, pages 716–722. Springer.

Samuel Bowman, Gabor Angeli, Christopher Potts, and Christopher D Manning. 2015. A large annotated corpus for learning natural language inference. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 632–642.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Yiyi Chen, Heather Lent, and Johannes Bjerva. 2024. Text embedding inversion security for multilingual language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7808–7827.

Guy Dar, Mor Geva, Ankit Gupta, and Jonathan Berant. 2022. Analyzing transformers in embedding space. *arXiv preprint arXiv:2209.02535*.

Nelson Elhage, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, et al. 2021. A mathematical framework for transformer circuits. *Transformer Circuits Thread*, 1:1.

Thibault Formal, Carlos Lassance, Benjamin Piwowarski, and Stéphane Clinchant. 2021. Splade v2: Sparse lexical and expansion model for information retrieval. *arXiv preprint arXiv:2109.10086*.

Leo Gao, Stella Biderman, Sid Black, Laurence Golding, Travis Hoppe, Charles Foster, Jason Phang, Horace He, Anish Thite, Noa Nabeshima, et al. 2020. The pile: An 800gb dataset of diverse text for language modeling. *arXiv preprint arXiv:2101.00027*.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. 2021. Simcse: Simple contrastive learning of sentence embeddings. *arXiv preprint arXiv:2104.08821*.

Mor Geva, Avi Caciularu, Kevin Ro Wang, and Yoav Goldberg. 2022. Transformer feed-forward layers build predictions by promoting concepts in the vocabulary space. *arXiv preprint arXiv:2203.14680*.

Edward J Hu, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. 2021. Lora: Low-rank adaptation of large language models. In *International Conference on Learning Representations*.

Minyoung Huh, Brian Cheung, Tongzhou Wang, and Phillip Isola. 2024. The platonic representation hypothesis. *arXiv preprint arXiv:2405.07987*.

Gautier Izacard, Mathilde Caron, Lucas Hosseini, Sebastian Riedel, Piotr Bojanowski, Armand Joulin, and Edouard Grave. 2022. Unsupervised dense information retrieval with contrastive learning. *Transactions on Machine Learning Research*.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. 2023a. Mistral 7b. *arXiv preprint arXiv:2310.06825*.

Ting Jiang, Shaohan Huang, Zhongzhi Luan, Deqing Wang, and Fuzhen Zhuang. 2023b. Scaling sentence embeddings with large language models. *arXiv preprint arXiv:2307.16645*.

Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense passage retrieval for open-domain question answering. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6769–6781.

Jacob Devlin Ming-Wei Chang Kenton and Lee Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of naacL-HLT*, volume 1, page 2.

Yibin Lei, Di Wu, Tianyi Zhou, Tao Shen, Yu Cao, Chongyang Tao, and Andrew Yates. 2024. Meta-task prompting elicits embedding from large language models. *arXiv preprint arXiv:2402.18458*.

Haoran Li, Mingshi Xu, and Yangqiu Song. 2023a. Sentence embedding leaks more information than you expect: Generative embedding inversion attack to recover the whole sentence. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 14022–14040.

Zehan Li, Xin Zhang, Yanzhao Zhang, Dingkun Long, Pengjun Xie, and Meishan Zhang. 2023b. Towards general text embeddings with multi-stage contrastive learning. *arXiv preprint arXiv:2308.03281*.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

Edward Loper and Steven Bird. 2002. Nltk: The natural language toolkit. In *Proceedings of the ACL-02 Workshop on Effective Tools and Methodologies for Teaching Natural Language Processing and Computational Linguistics*, pages 63–70.

Macedo Maia, Siegfried Handschuh, André Freitas, Brian Davis, Ross McDermott, Manel Zarrouk, and Alexandra Balahur. 2018. Www'18 open challenge: financial opinion mining and question answering. In *Companion proceedings of the the web conference 2018*, pages 1941–1942.

John Morris, Volodymyr Kuleshov, Vitaly Shmatikov, and Alexander M Rush. 2023. Text embeddings reveal (almost) as much as text. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 12448–12460.

Niklas Muennighoff. 2022. Sgpt: Gpt sentence embeddings for semantic search. *arXiv preprint arXiv:2202.08904*.

Niklas Muennighoff, Hongjin Su, Liang Wang, Nan Yang, Furu Wei, Tao Yu, Amanpreet Singh, and Douwe Kiela. 2024. Generative representational instruction tuning. *arXiv preprint arXiv:2402.09906*.

Tri Nguyen, Mir Rosenberg, Xia Song, Jianfeng Gao, Saurabh Tiwary, Rangan Majumder, and Li Deng. 2016. Ms marco: A human-generated machine reading comprehension dataset.

Xudong Pan, Mi Zhang, Shouling Ji, and Min Yang. 2020. Privacy risks of general-purpose language models. In *2020 IEEE Symposium on Security and Privacy (SP)*, pages 1314–1331. IEEE.

Letian Peng, Yuwei Zhang, Zilong Wang, Jayanth Srinivasa, Gaowen Liu, Zihan Wang, and Jingbo Shang. 2024. Answer is all you need: Instruction-following text embedding via answering the question. *arXiv preprint arXiv:2402.09642*.

Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. 2018. Improving language understanding by generative pre-training.

Ori Ram, Liat Bezalel, Adi Zicher, Yonatan Belinkov, Jonathan Berant, and Amir Globerson. 2023. What are you token about? dense retrieval as distributions over the vocabulary. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2481–2498.

Ori Ram, Gal Shachaf, Omer Levy, Jonathan Berant, and Amir Globerson. 2022. Learning to retrieve passages without supervision. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2687–2700.

Stephen Robertson, Hugo Zaragoza, et al. 2009. The probabilistic relevance framework: Bm25 and beyond. *Foundations and Trends® in Information Retrieval*, 3(4):333–389.

Elvis Saravia, Hsien-Chi Toby Liu, Yen-Hao Huang, Junlin Wu, and Yi-Shin Chen. 2018. Carer: Contextualized affect representations for emotion recognition. In *Proceedings of the 2018 conference on empirical methods in natural language processing*, pages 3687–3697.

Kaitao Song, Xu Tan, Tao Qin, Jianfeng Lu, and Tie-Yan Liu. 2020. Mpnet: Masked and permuted pre-training for language understanding. *Advances in neural information processing systems*, 33:16857–16867.

Jacob Mitchell Springer, Suhas Kotha, Daniel Fried, Graham Neubig, and Aditi Raghunathan. 2024. Repetition improves language model embeddings. *arXiv preprint arXiv:2402.15449*.

Hongjin Su, Weijia Shi, Jungo Kasai, Yizhong Wang, Yushi Hu, Mari Ostendorf, Wen-tau Yih, Noah A Smith, Luke Zettlemoyer, and Tao Yu. 2023. One embedder, any task: Instruction-finetuned text embeddings. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 1102–1121.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

Henning Wachsmuth, Shahbaz Syed, and Benno Stein. 2018. Retrieval of the best counterargument without prior topic knowledge. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 241–251.

David Wadden, Shanchuan Lin, Kyle Lo, Lucy Lu Wang, Madeleine van Zuylen, Arman Cohan, and Hannaneh Hajishirzi. 2020. Fact or fiction: Verifying scientific claims. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7534–7550.

Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. 2022. Text embeddings by weakly-supervised contrastive pre-training. *arXiv preprint arXiv:2212.03533*.

Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. 2023. Improving text embeddings with large language models. *arXiv preprint arXiv:2401.00368*.

Adina Williams, Nikita Nangia, and Samuel R Bowman. 2018. A broad-coverage challenge corpus for sentence understanding through inference. In *Proceedings of NAACL-HLT*, pages 1112–1122.

Bowen Zhang, Kehua Chang, and Chunping Li. 2024. Simple techniques for enhancing sentence embeddings in generative language models. *arXiv preprint arXiv:2404.03921*.

Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. 2022. Opt: Open pre-trained transformer language models. *arXiv preprint arXiv:2205.01068*.

A Detailed Information of Models

This section details the text embedding LLMs used for the study in the main text. Note taht these LLMs are CC BY 4.0 compliant and open source and can be used to obtain text embedding or any of the downstream applications they support.

- **SGPT$_{nli}$** are based on GPT-Neo and fine-tuned with contrastive learning on both SNLI (Bowman et al., 2015) and MNLI (Williams et al., 2018) dataset. SGPT$_{nli}$ includes four versions of 125m, 1.3B, 2.7B and 5.7B variants, and the variant used for this work is `SGPT-1.3B-weightedmean-nli`[4].

- **SGPT$_{msmarco}$** share the same backbone and training paradigm with SGPT$_{nli}$ except the training data. The variant used for this work is `SGPT-1.3B-weightedmean-msmarco-specb-bitfit`[5].

- **OPT$_{EOL}$** are based on OPT and use prompt template `This sentence:"[text]" means in one word:"` to guide OPTs in aggregating the semantics of the whole text into a single location. Due to the training-free nature of OPT$_{EOL}$, it can be easily applied to any variant of OPT, and the variant used for this work is `OPT-1.3B`[6].

- **OPT$_{EOL+CSE}$** are parameter-efficient fine-tuned with contrastive learning on SNLI and MNLI dataset on the top of OPT$_{EOL}$. All LoRA weights of OPT$_{EOL+CSE}$ are open-sourced, and the weight corresponds to OPT-1.3B[7] are used for comparing fairly with OPT$_{EOL}$.

- **LLaMA$_{EOL}$** share the same prompt template with OPT$_{EOL}$ but are based on LLaMA. The variant used for this work is `LLaMA-7B`[8].

- **LLaMA$_{EOL+CSE}$** are parameter-efficient fine-tuned with contrastive learning on SNLI and MNLI dataset on the top of LLaMA$_{EOL}$. The weight corresponds to `LLaMA-7B`[9] are used for comparing fairly with OPT$_{EOL}$.

- **GirtLM** is fine-tuned with instruction-tuning and contrastive learning to achieve a better trade-off between the generation and embedding capabilities. `GritLM-7B`[10], whose backbone is Mistral-7B-Instruct-v0.2, is used in this work.

---

[4] https://huggingface.co/Muennighoff/SGPT-1.3B-weightedmean-nli
[5] https://huggingface.co/Muennighoff/SGPT-1.3B-weightedmean-msmarco-specb-bitfit
[6] https://huggingface.co/facebook/opt-1.3b
[7] https://huggingface.co/royokong/prompteol-opt-1.3b
[8] https://llama.meta.com/llama-downloads/
[9] https://huggingface.co/royokong/prompteol-llama-7b
[10] https://huggingface.co/GritLM/GritLM-7B

(a) The metrics when the dataset D contains 10K documents sampled from the Wiki Corpus.

(b) The metrics when the dataset D contains 10K documents sampled from the SNLI training set.

(c) The metrics when the dataset D contains 10K documents sampled from the MSMARCO document set.

Figure 4: The comparison of evaluation metric when embedding with eight $\hat{f}$ and their corresponding f.

- **LLM2Vec** is a three-step method to adjust LLMs for text embeddings, which includes (1) changing the casual attention to bi-directional attention; (2) fine-tuning the LLM with a new task, masked next token prediction (MNTP), to adapt the LLM to use bi-directional attention; (3) fine-tuning the LLM with supervised contrastive learning to improve the embedding capability. The second-step [11] and third-step [12] LoRA weights corresponding to Mistral-7B-Instruct-v0.2 are used.

B Quantitative Analysis

To quantitatively reflect the connection between $\hat{T}_{s_i}^K$ and T_{s_i}, we propose three evaluation metrics:

Hit@K To measure whether the top K tokens of $\hat{T}_{s_i}$ contains any token in T_{s_i}, we propose the

---

[11] https://huggingface.co/McGill-NLP/LLM2Vec-Mistral-7B-Instruct-v2-mntp

[12] https://huggingface.co/McGill-NLP/LLM2Vec-Mistral-7B-Instruct-v2-mntp-supervised

metric of Hit@K as follows:

$$\text{Hit@K} = \mathbb{E}_{s_i \sim D}\left[\mathbb{I}\left(\left|\hat{T}_{s_i}^K \cap T_{s_i}\right| > 0\right)\right] \quad (14)$$

where $\mathbb{I}(.)$ is the indicator function, $|\cdot|$ represents the element number of the set.

Local Alignment Rate To measure the overlap degree between the tokens in T_{s_i} and the top $|T_{s_i}|$ tokens in $\hat{T}_{s_i}$, we propose the metric of Local Alignment Rate (LAR) as follows:

$$\text{LAR} = \mathbb{E}_{s_i \sim D}\left[\left|\hat{T}_{s_i}^{K_i} \cap T_{s_i}\right| / K_i\right] \quad (15)$$

where K_i is denoted as $|T_{s_i}|$ for simplicity.

Global Alignment Rate LAR can not reflect the global alignment situation. For example, elements in $\hat{T}_{s_i}^{K_i} \cap T_{s_i}$ and $\hat{T}_{s_j}^{K_j} \cap T_{s_j}$ can be either the completely same or completely different, but cannot be reflected in LAR. To measure the overlap degree in the dataset D globally, we propose the metric of

(a) Overlap between parent words and pos-of-speeches.

(b) Overlap between parent words and named entities.

(c) Overlap between parent words and nodes of dependency grammar.

Figure 5: The analysis of parent words with the MSMARCO dataset and LLM2Vec.

Global Alignment Rate (GAR) as follows:

$$\text{GAR} = \left| \cup_{i=1}^{|D|} \left(\hat{T}_{s_i}^{K_i} \cap T_{s_i} \right) \right| / \left| \cup_{i=1}^{|D|} T_{s_i} \right| \quad (16)$$

where $|D|$ represents the text number of D.

We report the Hit@10, LAR, and GAR for the original LLM and their variants used for text embedding in Figure 4. The following findings can be easily concluded: (1) all f and $\hat{f}$ except LLaMA maintain a high Hit@10, which means at least one token in the input text is aligned; (2) all $\hat{f}$ also maintain a low LAR and but higher GAR than that of the corresponding f; (3) compared to OPT$_{\text{EOL}}$ and LLaMA$_{\text{EOL}}$, OPT$_{\text{EOL+CSE}}$ and LLaMA$_{\text{EOL+CSE}}$ lead to a lower LAR and a higher GAR after contrastive learning.

Combined with the qualitative analysis, we conclude that text embeddings from f and $\hat{f}$ consistently align certain tokens in the text and

that $\hat{f}$-aligned tokens tend to be more diverse and more meaningful to the input text.

C "Parent Word" Analysis

In this section, we try to explore which words in the original text decompose these aligned tokens and whether these words are connected to some traditional concepts in linguistics. For space reasons, we only report the results for LLM2Vec here. We found similar results for other models.

Specifically, we constructed the dataset by taking 500 pairs of queries and documents from the MS-MARCO dataset to cover both long and short texts. We pass all data through LLM2Vec and record the aligned token set $\hat{T}_{s_i}^5$ for each input text. Subsequently, we use spaCy [13] to segment the input text and use LLM2Vec's tokenizer to act on each word.

---

[13]https://spacy.io/

If any word's tokenized results hit any token in $\hat{T}_{s_i}^5$, then we consider this word as a "parent word".

Also, using spaCy, we can annotate the part-of-speech types, named entity categories, and dependent grammatical nodes of each word. The overlap between the parent word and these concepts is shown in Figure 5. It can be seen that parent words are concentrated in a few lexemes such as nouns (NOUN), adjectives (ADJ) and proper nouns (PROPN), while they are more dispersed for named entities and dependent grammars.

D More Application Demonstration

D.1 Semantic Relevance v.s. Similarity

Current textual embedding models are often fine-tuned with different datasets depending on their evaluation task. For example, the NLI dataset is often used for training when evaluating the Semantic Text Similarity (STS) task on "semantic similarity". Instead, the MS-MARCO dataset is often used for training when evaluating the information retrieval task on "semantic relevance". Previously, it was difficult to distinguish the embedding spaces obtained from training on different datasets, although both above settings only use contrastive learning to fine-tune. Benefiting from the "token align" phenomenon, we can now understand this phenomenon by mapping the text embeddings to token space.

We select SGPT$_{\text{nli}}$ and SGPT$_{\text{msmarco}}$ to study because there is no difference between them except for the fine-tuning dataset. Considering a toy example of two sentences (S_A, S_B):

S_A: I like apples.
S_B: I dislike apples.

We obtain the embedding of both two sentences with SGPT$_{\text{nli}}$ and SGPT$_{\text{msmarco}}$ and align the embedding to the token space with the decoder layer. As shown in Table 4, most aligned tokens of S_A are related to "apple", while there is some difference in the tokens aligned by S_B. Specifically, when SGPT$_{\text{nli}}$ is used, tokens related to "dislike" are in the majority, whereas when SGPT$_{\text{msmarco}}$ is used, the ratio of tokens related to "dislike" and "apple" is balanced.

We believe that this phenomenon can help to intuitively understand the difference between "semantic similarity" and "semantic relatedness":

- In the semantic similarity setting, S_A and S_B are not considered to have a high degree

Model	Top 5 aligned token of S_A
SGPT$_{\text{nli}}$
SGPT$_{\text{msmarco}}$	_apple _apples _Apple apple Apple
_apple _Apple Apple apple _liking
	Top 5 aligned token of S_B
SGPT$_{\text{nli}}$
SGPT$_{\text{msmarco}}$	_dislike _disliked hate _hates _apple
_dislike _Apple _disliked _apple Apple

Table 4: Comparison of the aligned tokens when using different fine-tuning data.

of similarity because one of them is an affirmative S_A and the other is a negative sentence. SGPT$_{\text{nli}}$ aligns the embedding of S_B to "dislike" to ensure that the embedding of the two sentences is far enough apart. Therefore, the similarity of the two sentences given by SGPT$_{\text{nli}}$ is only `0.419`;

- In the semantic relevance setting, S_A and S_B can be considered highly relevant because they both describe whether "I" like "apples" or not. SGPT$_{\text{msmarco}}$ aligns the embedding of S_B to both "dislike" and "apple" to ensure that the final similarity reflects their relevance. Therefore, the similarity of the two sentences given by SGPT$_{\text{msmarco}}$ is `0.816`;

D.2 Instruction v.s. No-Instruction

Recent works such as Instructor (Su et al., 2023; Peng et al., 2024) use different instruction prefixes to distinguish between different embedding tasks. To explain the validity of the instruction-following embedding, we show that the same text will align to different tokens when prompted by different instructions. Considering a toy example of three sentences: (S_A, S_B, S_C) and one instruction I:

S_A: I really enjoyed the movie last night.
S_B: I didn't enjoy the movie last night at all.
S_C: I had a great time watching the film this afternoon.
I: Classify the emotion expressed in the given Twitter message into one of the six emotions: anger, fear, joy, love, sadness, and surprise.

where I is introduced by (Wang et al., 2023) and used for the EmotionClassification dataset (Saravia et al., 2018). We use LLM2Vec as the studied LLM and observe whether aligned tokens from the same text differ with the instruction and without the instruction.

As shown in Table 5, the tokens aligned by all sentence largely changed when adding I. Specifically, when I is not added, all tokens are aligned to

the non-sentiment tokens first. Interestingly, when I is added, S_A and S_C is mainly aligned to the tokens related to "joy", while S_B is mainly aligned to the token related to "sadness".

Similarly, we believe that this phenomenon can help to understand how the instruction-following embeddings work intuitively:

- When no instruction is added, the LLM can only "randomly" select some key tokens to align. For both S_A and S_B, the LLM happens to both choose topic-related tokens. As a result, similarity(S_A, S_B)=0.821 is higher than similarity(S_A, S_C)=0.718.

- When the instruction for sentiment classification is added, the LLM "adaptively" selects the sentiment tokens to align with. As a result, similarity($I + S_A$, $I + S_B$)=0.814 is lower than similarity($I + S_A$, $I + S_C$)=0.829, .

Setting	Top 5 aligned token of S_A
-wo I	_Movie _movie _cinema _movies _watched
-w I	_Joy _joy _happiness joy _Love
	Top 5 aligned token of S_B
-wo I	_movie _Movie _movies _cinema _Mov
-w I	_sad _Sad _disappointment _disappointed _anger
	Top 5 aligned token of S_C
-wo I	_afternoon _cinema _movie _Movie _movies
-w I	_joy _Joy joy _happiness _delight

Table 5: Comparison of the aligned tokens when using the instruction or not.

Note that a similar phenomenon has also been observed by (Peng et al., 2024) under the special fine-tuning method and the last-pooling strategy. The phenomenon we observed is more general because LLM2Vec does not even seem to have any instructions when fine-tuning and is using a weighted-mean pooling strategy. We similarly emphasize that this interesting phenomenon is present in most embedding LLMs and is easy to verify.

E Details of Sparse Retrieval

E.1 Evaluation Dataset and Metric

We provide the statistics of four evaluation datasets in Table 6 and use the version provided by BEIR[14]. nDCG@10 used for evaluation is the recommended metric for the BEIR Benchmark. The calculation

[14]https://github.com/beir-cellar/beir.

Dataset	Domain	#Query	#Corpus	Relevancy
FiQA	Finance	648	57,638	Binary
NFCorpus	Medical	323	6,633	3-level
SciFact	Science	300	5,183	Binary
ArguAna	Misc.	1,406	8,674	Binary

Table 6: Statistics of the evaluation dataset. Relevancy represents the query-document relation level.

of nDCG@10 can be divided into three main steps: (1) calculating DCG@10:

$$DCG@10 = \sum_{i=1}^{10} \frac{2^{rel_i} - 1}{\log_2(i + 1)} \qquad (17)$$

where rel_i is the relevance score of the i-th item, which is usually a nonnegative integer and $\log_2(i + 1)$ is the positional discount factor, which is used to reduce the weight of lower-ranked items because users are more likely to pay attention to the top-ranked items. (2) calculating $IDCG@10$ (Ideal DCG@10), which is the DCG value when assuming that the retrieved results are ordered optimally. The results are sorted from highest to lowest based on the relevance score. (3) normalizing $DCG@10$ and obtaining nDCG@10:

$$nDCG@10 = \frac{DCG@10}{IDCG@10} \qquad (18)$$

E.2 Implementation Details

We follow the evaluation methods of LLM2Vec and GirtLM by adding different instructions in front of different datasets. The instruction is given in Table 7. We use Python 3.10 and Pytorch 2.3.0 for the implementation, while our experiments are all done on a single NVIDIA A100 40GB with CUDA 12.4.

E.3 Hyper-parameter Experiment

Since no validation set exists for ArguAna and Sci-fact, we report the performance variation on the non-zero number of sparse representation, i.e., K, and the extended token number of query, i.e., M, on the test set of all four datasets. We find that K has little effect on the results, so selecting a lower K is a good choice for low storage scenarios. The situation is more complex for M: (1) the performance on FiQA and NFCorpus peaks at M=75 while the other two datasets show a steady boost ; (2) when the embedding LLM is good enough, such as the case of GritLM, even a large M can lead to a steady boost in retrieval results.

| (a) GPT-Neo and SGPT$_{\text{msmarco}}$ | (b) OPT and OPT$_{\text{EOL}}$ | (c) LLaMA and LLaMA$_{\text{EOL}}$ | (d) Mistral and LLM2Vec |

Figure 6: The variation in each principal component of the embedding space.

(a) Performance of sparse retrieval based on LLM2Vec.

(b) Performance of sparse retrieval based on GritLM.

Figure 7: Performance Variation of sparse retrieval with hyper-parameters.

E.4 Dense Retrieval v.s. Sparse Retrieval on FLOPs

A more precise portrayal of the overhead of our sparse retrieval method would highlight the potential of the application even more. Although it is well known that sparse retrieval has significantly lower overhead compared to dense retrieval, the actual amount of overhead reduction is challenging to compare pretty because they utilize completely different retrieval methods.

We give the formulae for calculating FLOPs for both sparse and dense retrieval methods with the same embedding LLM.

Dense Retrieval For each document and a query vector of dimension d, the dot product with the query vector involves d multiplications and $d-1$ additions. Therefore, the total FLOPs for N documents is: FLOPs$_{\text{dense}} = N \times (d + (d-1)) = N \times (2d-1) \approx 2Nd$

Sparse retrieval The dot product can be computed only for the non-zero entries. The FLOPs for calculating the dot product for each document are proportional to the number of non-zero terms in both the query and the document. Let $\hat{M}$ be the number of non-zero terms in the query, and K be the average number of non-zero terms per document. Therefore, the total FLOPs for N documents is: FLOPs$_{\text{sparse}} = N \times (\hat{M} + K)$

Comparison To compare the two methods, we can analyze the ratio:

$$\text{Ratio} = \frac{\text{FLOPs}_{\text{sparse}}}{\text{FLOPs}_{\text{dense}}} = \frac{\hat{M} + K}{2d} \quad (19)$$

In our implementation, $\hat{M}$ is the size sum of the query token set and the expanded token set, and since the expanded token set's size is much larger than the original query length, so $\hat{M} \approx M = 100$. Meanwhile, since the sparse retrieval effect is not sensitive to K, we choose the lowest value set in the experiment, i.e., $K = 1000$. Recall that

$d = 4096$ for both LLM2Vec and GirtLM. Therefore, Ratio $= \frac{\hat{M}+K}{2d} \approx \frac{100+1000}{2\times 4096} = 7.45$. Note that hyperparameters such as chunk size, number of indexes, etc., will affect the actual retrieval overhead. Therefore, the above quantitative results are for reference only.

F Additional Results on Spectral Analysis

Variation of Principal Components We show the variation principal component for the remaining 4 embedding LLMs in Figure 6. We find that, with the exception of LLaMA$_{\text{EOL}}$, the embedding spaces of the other three $\hat{f}$ decrease significantly on the first principal component. We would like to explain the anomaly of LLaMA$_{\text{EOL}}$ in terms of the recently popular "Platonic Representation Hypothesis"(Huh et al., 2024). LLaMA$_{\text{EOL}}$ is based on prompt engineering and is not considered a powerful embedding model compared to other $\hat{f}$. According to the "Platonic Representation Hypothesis", powerful embedding models always produce convergent embeddings, while weaker embedding models produce embeddings that will be more disparate from them. Thus, we conjecture that the anomalies of LLaMA$_{\text{EOL}}$ indicate precisely that the embedding space generated by it is not good enough. This is corroborated by the fact that LLaMA$_{\text{EOL+CSE}}$ in Figure 2 behaves consistently with other models.

Adjusting First Principal Components In Figure 8, we show the first principal component adjustment corresponding to the 3 additional $(f, \hat{f})$ pairs. It can be observed that although the effects vary, the overall adjusting first principal components all align the embedding to the key tokens, in line with the conclusion of Section 4.

G Additional Qualitative Analysis

In Table 8, we provide three more examples from Wiki1M, SNLI, and MSMARCO to reflect the generalizability of our findings. We observe similar alignment phenomena as in Section 3.4, demonstrating the generalizability of our findings.

Dataset	Instruction
FiQA	Given a financial question, retrieve user replies that best answer the question
NFCorpus	Given a question, retrieve relevant documents that best answer the question
SciFact	Given a scientific claim, retrieve documents that support or refute the claim
ArguAna	Given a claim, find documents that refute the claim

Table 7: Instruction used when obtaining embedding from LLM2Vec and GirtLM.

(a) Contribution to the aligned tokens (OPT).

(b) Aligned tokens after adjusting $\mathbf{u}_1$ guided by OPT$_{\text{EOL+CSE}}$.

(c) Contribution to the aligned tokens (LLaMA).

(d) Aligned tokens after adjusting $\mathbf{u}_1$ guided by LLaMA$_{\text{EOL+CSE}}$.

(e) Contribution to the aligned tokens (Mistral).

(f) Aligned tokens after adjusting $\mathbf{u}_1$ guided by GirtLM.

Figure 8: Situation of the aligned token when the input text is "*Making a Killing is a 2018 Canadian-American crime-mystery film co-written, co-produced and directed by Devin Hume.*". Figure (a)-(b) show the situation when f is OPT, $\hat{f}$ is OPT$_{\text{EOL+CSE}}$; Figure (c)-(d) show the situation when f is LLaMA, $\hat{f}$ is LLaMA$_{\text{EOL+CSE}}$; Figure (e)-(f) show the situation when f is Mistral, $\hat{f}$ is GirtLM.

Dataset	Input Text
Wiki1M	*Chatwood was chosen for the role as Ubisoft wanted music that had Persian elements in it to fit the setting, while not being pure Persian music.*

GPT-Neo	_in	_the	,	_to	_"	_âG	_as	_and	Ċ	_a
SGPT$_{nli}$	_Persian	_music	_MUS	_Music	_musical	_mus	_compos	_Persia	_Pers	_Iranian
SGPT$_{msmarco}$	_Ubisoft	_Music	_music	_MUS	WOOD	_soundtrack	_playlist	Music	_XCOM	_Persian

OPT	Ċ	_	_The	_He	_Chat	_It	_I	_This	_In	_They
OPT$_{EOL}$	pure	not	Music	We	_Persian	Not	U	_The	music	Pure
OPT$_{EOL+CSE}$	_Chat	_chat	_music	_Music	Chat	_Persian	_Ubisoft	chat	_musical	_Persia

LLaMA	_The	_Ch	<0x0A>	_He	_She	_"	_U	_It	_In	_This
LLaMA$_{EOL}$	Ch	Pers	_Pers	_Ch	I	_we	_he	the	The	it
LLaMA$_{EOL+CSE}$	_Ch	_chat	_music	_Pers	chat	_Iran	Ch	_musical	_Music	music

Mistral	,	_"	_in	_to	_for	_as	_and	_the	_a	_
GritLM	_Pers	_chat	_Chat	_wood	_U	_music	Chat	_Wood	_pers	Pers
LLM2Vec	_Chat	_music	_chat	Chat	_U	_Pers	_Music	_wood	_Wood	chat

Dataset	Input Text
NLI	*In 2000, GNP was less than GDP because income receipts from the rest of the world were less than U.S. payments to the rest of the world.*

GPT-Neo	Ċ	_(	.	,	_in	_G	_the	_GDP	_and	_of
SGPT$_{nli}$	_less	_GN	_impover	_income	_GDP	_low	_lesser	_economic	_little	_poverty
SGPT$_{msmarco}$	_GN	_GDP	GN	_Pik	_Krugman	_Gross	Gs	_Gn	_income	G

OPT	_	Ċ	_In	_Now	_GN	_The	_Today	_That	_This	_Since
OPT$_{EOL}$	GN	_GN	G	_less	less	In	The	the	_the	_In
OPT$_{EOL+CSE}$	_GN	_income	_GDP	_payments	_2000	_2001	GN	_Income	_incomes	_Global

LLaMA	\n	_In	_The	_This	_G	_That	_But		_However	_Net
LLaMA$_{EOL}$	def	the	The	_the	_The	In	USA	_U	_trade	G
LLaMA$_{EOL+CSE}$	_income	_rece	_pay	_payment	Rece	pay	_Pay	_G	_exports	_deb

Mistral	_the	,	_in	_(	_of	_for	.	_	_and	-
GritLM	_payments	_G	_income	_world	_rece	_U	_rest	_US	_the	_Pay
LLM2Vec	_G	_income	_payments	_world	_U	_less	_payment	_rece	_World	_pay

Dataset	Input Text
MSMARCO	*Disney's Theme Parks had an operating cost of 571 million dollars divided by their 11 parks and being open 365 days a year, on average their operating cost per day is around $355,000.*

GPT-Neo	_a	\n	_(	.	_in	,	_for	_and	_the	_per
SGPT$_{nli}$	Ĥ¬	_5	_five	_operating	_365	_$	_cost	_55	_operation	_operations
SGPT$_{msmarco}$	_operating	_Operating	_Theme	_theme	_operation	_OPER	_Operation	_Parks	operation	_cost

GPT-Neo	_a	Ċ	_(	.	_in	,	_for	_and	_the	_per
SGPT$_{nli}$	Ĥ¬	_5	_five	_operating	_365	_$	_cost	_55	_operation	_operations
SGPT$_{msmarco}$	_operating	_Operating	_Theme	_theme	_operation	_OPER	_Operation	_Parks	operation	_cost

OPT	_	Ċ	_So	_That	_This	_The	_They	_I	_If	
OPT$_{EOL}$	Disney	_Disney	$	_$	The	_operating	Cost	average	the	_The
OPT$_{EOL+CSE}$	_Disney	Disney	_Disneyland	_parks	_operating	_Walt	_5	_costing	_annual	_park

LLaMA	<0x0A>	0	_This	_That	_The	_If	_Disney	_With	_I	_In
LLaMA$_{EOL}$	Dis	_Disney	The	the	_the	_	_per	aver	Oper	oper
LLaMA$_{EOL+CSE}$	_Disney	_park	Theme	_Park	_theme	park	_cost	_operating	theme	_par

Mistral	,	_	1	_in	.	_(	_and	_per	_a	2
GritLM	_operating	_theme	_Disney	_cost	_Theme	_day	_parks	_park	_costs	_daily
LLM2Vec	_operating	_parks	_park	_Disney	_theme	_Park	_Theme	_Oper	_daily	Theme

Table 8: The top 10 aligned tokens for eight $\hat{f}$ for text embedding and their corresponding f for text generation.