Beyond Freezing the Router: Rank-Aligned Post-Training Quantization for Mixture-of-Experts Models

Abstract

Quantizing Mixture-of-Experts language models remains a challenging problem because quantization noise propagates across layers and distorts downstream expert selection. Although common practice keeps the router in full precision, we show that this strategy is insufficient: quantization-induced errors in expert outputs still shift the logits of the next-layer router, and freezing the router removes the opportunity to compensate for these shifts. Motivated by this finding, we propose **RouteQuant**, a post-training quantization framework that explicitly embraces *router quantization* to correct for expert-level distortion. We analyze how quantization alters router rankings and flippings, and provide a theoretical proof showing that deviations in expert outputs are bounded by both expert-selection and gap-preservation errors. These insights motivate two router-alignment objectives: (i) *Rank-Aware Jaccard Loss*, which aligns the top-k routing sets between full-precision and quantized models, and (ii) *Gap Hinge Loss*, which preserves the margin between consecutive expert logits to suppress rank flipping. In addition to router alignment, we further introduce *Expert-Aware Smoothing Factor*, which assigns separate activation smoothing factors to heterogeneous experts. Across OLMoE, DeepSeek-MoE, and Qwen3-MoE, RouteQuant consistently improves perplexity on C4 and WikiText-2 and enhances zero-shot accuracy under W4A4 and W4A8 across diverse downstream tasks, demonstrating the effectiveness of the proposed framework. Code is available at `https://anonymous.4open.science/r/route-quant`.

1 Introduction

Large language models (LLMs) continue to advance rapidly and reshape modern natural language processing (Achiam et al., 2023; Grattafiori et al., 2024; Guo et al., 2025; Yang et al., 2025). As parameter counts and training corpora grow, Mixture-of-Experts (MoE) architectures emerge as a scalable design that raises effective capacity without proportional compute (Shazeer et al., 2017; Fedus et al., 2022; Dai et al., 2024; Muennighoff et al., 2025). An MoE layer comprises a learned router and a pool of experts; for each input token, the router computes routing scores, activates the top-k experts, and aggregates their outputs. Variants include shared experts that capture common knowledge across tokens, while routed experts specialize. As model size and MoE adoption increase, deployment becomes constrained by memory and latency, so low-precision inference via quantization becomes essential for practical serving.

Quantizing MoE models introduces challenges beyond those observed in dense Transformers, as each layer's output is jointly shaped by the router's expert selection and the experts' transformed activations. Prior studies have highlighted the router's sensitivity, noting that even minor perturbations can lead to misrouting (Ma et al., 2025; Fu et al., 2025). Given that the router accounts for only a tiny fraction of total model parameters (*e.g.*, 0.03%), previous work commonly retains router layers in full precision to avoid degradation and preserve routing accuracy (Kwon et al., 2023; Chen et al., 2025a). However, we revisit this assumption and show that keeping the router in full precision is not necessarily optimal. After quantization, the expert FFNs produce shifted logits due to quantization noise, creating a mismatch between the frozen full-precision router and the altered expert behaviors. We illustrate this mismatch in Figure 1. In this coupled system, a preserved router cannot compensate for expert-side shifts, leading to inconsistent MoE outputs governed by both components. We argue that the router should instead *adapt* to these quantization-induced changes. To

Figure 1: Confusion matrices at **layer 0** comparing FP16 vs. DuQuant (Lin et al., 2024a) top-k indices under W4A4 without quantize router.

Figure 2: Effect of router quantization under W4A4. **w/ router** (●) quantizes the router together with experts, while **w/o router** (×) keeps the router in full precision.

achieve this without retraining, we propose a simple but effective strategy: we quantize the router as well. Allowing the router to undergo the quantization process enables its logits to co-adapt with the quantized experts, implicitly correcting expert-side errors. We empirically observe that router quantization improves MoE PTQ performance, as shown in Figure 2, indicating that aligning the router with quantized experts is sometimes preferable to preserving it in full precision.

However, the improvement is not universal: router quantization helps only when it shifts expert selection in a direction that meaningfully compensates for expert-side quantization errors. Since each MoE layer's output is jointly determined by both router decisions and expert computations, adjusting the router alone cannot fully account for how expert quantization perturbs the final output. To address this coupling, we theoretically analyze how quantization perturbs the MoE output and show that the router-induced error decomposes into two controllable factors: (i) the *selected expert index*, and (ii) the *gap* between adjacent expert logits. These two components determine whether quantization changes the top-k routing decision and how severely the output deviates from full precision. Guided by this insight, we construct two router-alignment objectives that explicitly constrain these factors: *Rank-Aware Jaccard Loss (RAJ)*, which stabilizes the top-k expert indices, and *Gap Hinge Loss (GH)*, which preserves the score margins between consecutive experts. By enforcing both index consistency and margin structure, these losses enable the quantized router to compensate for expert-side quantization errors. In addition, we incorporate an *Expert-Aware Smoothing Factor (ES)* that assigns each expert a channel-wise smoothing factor, preventing heavy-tailed experts from distorting shared quantization ranges and further reducing expert-side noise. Together, these components form a cohesive MoE-aware PTQ strategy.

Our main contributions are as follows:

- We show that keeping the router in full precision is suboptimal because it cannot adapt to expert-side quantization errors. We instead propose a simple strategy: quantizing the router to co-adapt with quantized experts.

- We theoretically link router quantization error to expert output error and identify two key factors, the selected expert index and the inter-expert score gap. Accordingly, we introduce *Rank-Aware Jaccard Loss* and *Gap Hinge Loss* to stabilize both.

- We validate our framework on OLMoE, DeepSeek-MoE, and Qwen3-MoE, achieving lower perplexity on C4 and WikiText-2 and higher accuracy on diverse reasoning tasks.

2 Related Work

2.1 Mixture-of-Experts LLMs

Early studies propose using gating networks to adaptively route each input to specialized sub-networks (Jacobs et al., 1991; Jordan & Jacobs, 1994), and subsequent work extends this idea to a variety of domains (Deisenroth & Ng, 2015; Aljundi et al., 2017). In LLMs, an MoE layer places expert MLPs behind a lightweight gate (linear projection plus softmax) and routes each token to the top-k experts with load-balancing regularization (Shazeer et al., 2017); systems advance scale MoE transformers with automated sharding and parallelism (Lepikhin et al., 2021).

Large-scale instances vary in routing. Switch transformer uses top-1 gating to reduce activation cost (Fedus et al., 2022); GLaM shows that top-2 improves the accuracy, an efficiency trade-off at trillion parameter scale (Du et al., 2022); Mixtral 8×7B activates two experts per token and rivals dense peers at similar cost (Jiang et al., 2024). DeepSeek-MoE increases expert granularity, keeps a few active experts per token, and adds always-on shared experts to capture global knowledge (Dai et al., 2024); DeepSeek-V2/V3 further refine routing, optimization, and systems (Liu et al., 2024a;b).

Unlike dense transformers, which apply all parameters to every token, MoE models rely on a router to decide which subset of experts is activated. This router is therefore central to both efficiency and accuracy: small perturbations in its outputs directly change expert selection and propagate through the entire forward pass. Our work focuses on this router behavior and its interaction with expert heterogeneity, distinguishing MoE-specific challenges from those in dense architectures.

2.2 Post-Training Quantization for LLMs

PTQ is a standard route to deploy LLMs efficiently, reducing memory and bandwidth without retraining. In dense transformers, PTQ minimizes layerwise reconstruction error while preserving numerical structure relevant to generation. GPTQ casts weight-only quantization as a blockwise least-squares problem with Hessian-aware error compensation, delivering strong 4-bit accuracy at negligible calibration cost (Frantar et al., 2022). AWQ accounts for activation statistics during calibration, preserves high-saliency channels, and uses data-aware scaling to control outliers (Lin et al., 2024b). DuQuant redistributes activation outliers via a dual transformation that rebalances ranges in both activation and weight, enabling competitive W4A4 across dense LLMs (Lin et al., 2024a).

In MoE architectures, the router is the critical component as its outputs determine which experts are activated; even small quantization errors can cascade into misrouted tokens and dominate accuracy loss. Existing MoE-specific PTQ methods only partially address this challenge. Although MoEQuant reweights expert calibration by router weights, it does not explicitly correct quantization-induced changes in routing decisions (Chen et al., 2025b). Additionally, EAQuant applies a KL-divergence objective to align router logit distributions (Fu et al., 2025), and QESC adopts a top-k MSE loss that aligns the logits of highly probable experts (Chen et al., 2025a). These methods primarily focus on preserving the original routing behavior, rather than explicitly enabling the router to adapt to expert-side quantization errors. As discussed in Figure 1, quantized experts produce shifted activations that induce a mismatch, motivating us to consider router quantization as a mechanism for co-adaptation between routing decisions and quantized experts.

3 Methodology

3.1 Router–Expert Coupling in MoE Outputs

An MoE layer with E experts and top-k routing computes, for an input x,

$$y(x) = \sum_{j \in \text{top-}k} \pi_j(x)\, \mathcal{E}_j(x), \tag{1}$$

where $\pi_j(x)$ are routing weights derived from router logits $r(x) \in \mathbb{R}^E$, and $\mathcal{E}_j$ denotes the j-th expert. We consider a full-precision router $r^{(\text{fp})}$ and its quantized counterpart $r^{(q)}$. Let:

$$I = (i_1, \ldots, i_k) = \text{top-}k\big(r^{(\text{fp})}(x)\big), \tag{2}$$

$$J = (j_1, \ldots, j_k) = \text{top-}k\big(r^{(q)}(x)\big), \tag{3}$$

be the ordered top-k expert indices for the full-precision and quantized routers, respectively. The corresponding MoE outputs are:

$$y^{(\text{fp})}(x) = \sum_{j \in I} \pi_j^{(\text{fp})}(x)\, \mathcal{E}_j(x), \tag{4}$$

$$y^{(q)}(x) = \sum_{j \in J} \pi_j^{(q)}(x)\, \mathcal{E}_j(x). \tag{5}$$

To characterize how router quantization perturbs the MoE output, we decompose the index sets as:

$$S^* = I \cap J, \quad S^- = I \setminus J, \quad S^+ = J \setminus I. \tag{6}$$

Here, S^* contains experts that both routers select, S^- contains experts dropped by the quantized router, and S^+ contains new experts.

Proposition 1 (Router-induced MoE output error). *Assume that for a given input x, the expert outputs are uniformly bounded, i.e., $\|\mathcal{E}_j(x)\| \le B(x)$, $\forall j$. Then the router-induced output discrepancy obeys:*

$$\big\|y^{(\text{fp})}(x) - y^{(q)}(x)\big\| \le B(x)\Big(\sum_{j \in S^*} \big|\pi_j^{(\text{fp})}(x) - \pi_j^{(q)}(x)\big| + \sum_{j \in S^-} \pi_j^{(\text{fp})}(x) + \sum_{j \in S^+} \pi_j^{(q)}(x) \Big). \tag{7}$$

The first term in Equation (7) measures how much router weights on *shared* experts change; the latter two terms depend on the probability mass assigned to *mismatched* experts, *i.e.*, how much the top-k sets differ. Thus, router-induced error is governed by two key factors: (i) which experts appear in the top-k list, and (ii) how router weights change on the corresponding experts.

Next, we connect index changes to the underlying router logits. Let:

$$r_{(1)}^{(\text{fp})}(x) \ge \cdots \ge r_{(E)}^{(\text{fp})}(x), \tag{8}$$

denote the sorted full-precision logits, and define the consecutive logit gaps:

$$\Delta_r^{(\text{fp})}(x) = r_{(r)}^{(\text{fp})}(x) - r_{(r+1)}^{(\text{fp})}(x). \tag{9}$$

Proposition 2 (Gap condition for top-k stability). *If the quantized consecutive gaps satisfy:*

$$\Delta_r^{(q)} \ge \Delta_r^{(\text{fp})}, \tag{10}$$

for all $r \in \{1, \ldots, k\}$, then the ordered top-k expert indices are preserved.

Proposition 2 provides a sufficient condition for preserving the ordered top-k routing under quantization. Specifically, if the quantized inter-expert logit gaps are no smaller than their full-precision counterparts, rank inversions cannot occur, and the selected experts remain unchanged. Combining Proposition 1 and 2, the router-induced MoE error is dominated by:

1. the *top-k index mismatch* between I and J, and

2. the *logit gaps* $\Delta_r^{(\text{fp})}(x)$ that determine how easily the ranks flip.

The full proof is provided in Appendix A. This analysis motivates a router-alignment objective that explicitly stabilizes both the selected expert identities and the relative score gaps among experts. Based on this insight, we introduce two complementary loss functions that directly target these two sources of routing error. Notably, our quantization is built upon DuQuant (Lin et al., 2024a), and we integrate the proposed losses into the learnable weight clipping (Shao et al., 2024).

3.2 Rank-Aware Jaccard Loss (RAJ)

Proposition 1 shows that index mismatch between I and J directly inflates the router-induced error via the S^- and S^+ terms in Equation (7). Empirically, we also observe that quantization errors in the router are not arbitrary: the quantized router usually selects experts that are close in rank to the full-precision choices, with most mistakes occurring near the top-k boundary (see Figure 1). This suggests that aligning the *set and order* of selected experts, especially at higher ranks, is more important than matching all experts.

To capture this, we design a rank-weighted similarity objective on the top-k expert indices. We first assign geometric weights $w_r = \beta^{r-1}$ with $\beta \in (0, 1]$ so that higher ranks receive larger emphasis. We emphasize higher-ranked experts, as, from the router's perspective, they receive larger routing weights and therefore contribute more strongly to the final MoE output. Errors at these positions have a large impact: if a top-ranked expert is misrouted, the resulting representation can deviate substantially from the full-precision behavior. Using these, we define affinity vectors $A_{\text{fp}}, A_q \in \mathbb{R}^E$:

$$A_{\text{fp(q)}}(e) = \begin{cases} w_r, & \text{if } e = i_r(j_r), \\ 0, & \text{otherwise,} \end{cases} \tag{11}$$

The *Rank-Aware Jaccard (RAJ)* similarity between I and J is:

$$J_W(I, J) = \frac{\sum_{e=1}^{E} \min(A_{\text{fp}}(e), A_q(e))}{\sum_{e=1}^{E} \max(A_{\text{fp}}(e), A_q(e))} \in [0, 1],$$

and the corresponding loss is:

$$\mathcal{L}_{\text{RAJ}} = 1 - J_W(I, J). \tag{12}$$

This design directly measures the agreement between full-precision and quantized top-k experts while prioritizing higher ranks. Unlike logit-based losses, it is invariant to affine transformations of r that preserve ordering, and it decreases whenever near-miss errors (such as swapping rank-k and rank-$(k+1)$ experts) are corrected. By maximizing overlap between I and J, $\mathcal{L}_{\text{RAJ}}$ explicitly reduces the S^- and S^+ contributions in Equation (7), thereby mitigating index-driven routing errors.

3.3 Gap Hinge Loss (GH)

While *RAJ* stabilizes which experts appear in the top-k list, it does not control how close router scores are between adjacent experts, and thus cannot prevent rank flipping, as discussed in Proposition 2. To address this, we explicitly encourage larger gaps between consecutive experts within the full-precision top-k sequence, making the selection more robust to perturbations.

We first extract paired full-precision and quantized scores on the fixed full-precision top-k index set $I = (i_1, \ldots, i_k)$:

$$r_r^{(\text{fp})} = r_{i_r}^{(\text{fp})}, \qquad \tilde{r}_r^{(q)} = r_{i_r}^{(q)}. \tag{13}$$

We then define consecutive gaps as:

$$\Delta_r^{(\text{fp})} = r_r^{(\text{fp})} - r_{r+1}^{(\text{fp})}, \qquad \Delta_r^{(q)} = \tilde{r}_r^{(q)} - \tilde{r}_{r+1}^{(q)},$$

for $r = 1, \ldots, k-1$. The GH loss penalizes quantized gaps that shrink below the full-precision reference (up to a margin $\gamma \geq 0$):

$$\mathcal{L}_{\text{GH}} = \frac{1}{k-1} \sum_{r=1}^{k-1} \left[\Delta_r^{(\text{fp})} - \Delta_r^{(q)} + \gamma \right]_+, \tag{14}$$

where $[x]_+ = \max(0, x)$. Since our target is to preserve the margins, we simply set $\gamma = 0$.

By preserving the logit gaps, $\mathcal{L}_{\text{GH}}$ enforces a condition of Equation (10): when $\Delta_r^{(q)}$ does not shrink too much relative to $\Delta_r^{(\text{fp})}$, rank inversions on the top-k set become less likely under bounded quantization noise. Hence, *GH* reduces the probability of routing changes that would increase the index mismatch terms in Equation (7).

(a) OLMoE   (b) DeepSeek-MoE   (c) Qwen3-MoE

Figure 3: Expert activations in the **last layer** for each model.

Total router-consistency objective. We combine *RAJ* and *GH* into a router-consistency objective:

$$\mathcal{L}_{\text{router}} = \lambda_{\text{RAJ}}\,\mathcal{L}_{\text{RAJ}} + \lambda_{\text{GH}}\,\mathcal{L}_{\text{GH}}, \tag{15}$$

Together, they implement the theoretical insights of Proposition 1 and 2 by jointly controlling top-k indices and inter-expert margins.

3.4 Expert-Aware Smoothing Factor (ES)

The router-consistency objective targets expert *selection*, but MoE output error also comes from quantization noise in the experts themselves. To reduce this expert-side error, we introduce an *Expert-Aware Smoothing Factor (ES)* that assigns each expert its own channel-wise scaling. Existing multi-expert schemes typically compute a per-channel smoothing factor for each expert and then take the maximum across experts, forcing all experts in the layer to share one smoothing factor per channel (Fu et al., 2025). This max-aggregation is dominated by a few heavy-tailed experts and either clips light-tailed experts or wastes quantization levels on most experts. As seen in Figure 3, experts exhibit markedly different activation and weight statistics, motivating an expert-specific design. Additional layers are shown in Figures 10 to 12.

Let an MoE MLP take input $\boldsymbol{x} \in \mathbb{R}^d$, and let expert $i \in \{1, \ldots, E\}$ use weights $W^i \in \mathbb{R}^{m \times d}$ with column $\mathbf{W}_j^i$ for channel j. Following SmoothQuant (Xiao et al., 2023), we introduce a positive diagonal matrix $D_i = \text{diag}(\boldsymbol{s}^i)$, where $\boldsymbol{s}^i = (s_1^i, \ldots, s_d^i)$, and rewrite:

$$W^i \boldsymbol{x} = \left(W^i D_i\right)\left(D_i^{-1}\boldsymbol{x}\right) \triangleq \widetilde{W}^i \widetilde{\boldsymbol{x}}^i, \tag{16}$$

which is algebraically exact in full precision. We then quantize $\widetilde{W}^i$ per channel and $\widetilde{\boldsymbol{x}}^i$ per token.

Let $|x_j|$ denote the magnitude of the j-th input activation on a small calibration set, and $|\mathbf{W}_j^i|$ the absolute values of the corresponding weight column. For $j = 1, \ldots, d$, $i = 1, \ldots, E$, and $\alpha \in [0, 1]$, we define:

$$s_j^i = \frac{\max(|x_j|)^\alpha}{\max(|\mathbf{W}_j^i|)^{1-\alpha}}, \tag{17}$$

for normalization between activations and weights.

Compared with a single shared s_j per channel, *ES* adapts to each expert's statistics, reduces activation clipping, and stabilizes weight quantization. This improves expert outputs that the router aggregates, further lowering MoE output logit error with negligible runtime overhead as shown in Table 7.

Table 1: Reported total parameters, active parameters, and expert configuration for all models.

Model	Total Param.	Act. Param.	top-k E.	Total E.
OLMoE	6.7B	1.3B	8	64
DeepSeek	16.4B	2.8B	6	64
Qwen3	30.5B	3.3B	8	128

Table 2: **Main results under W4A4.** DuQuant serves as the baseline; the comparison includes MoEQuant, EAQuant, QESC, and RouteQuant on OLMoE, DeepSeek-MoE, and Qwen3-MoE.

Model	Method	Perplexity ↓		Accuracy ↑							
		Wiki2	C4	ARC-C	ARC-E	BoolQ	HellaS	OBQA	RTE	Wino.	Average
OLMoE	FP16	6.65	10.86	46.59	77.10	70.09	58.47	32.60	71.12	68.51	60.64
	DuQuant	8.28	12.20	40.96	72.26	63.88	54.99	30.20	60.43	64.72	55.35 (-)
	MoEQuant	8.03	12.02	40.70	73.44	66.30	55.69	29.60	62.09	63.38	55.89 (+0.97%)
	EAQuant	7.75	11.75	41.38	**73.65**	**66.97**	56.05	31.00	62.45	65.43	56.70 (+2.45%)
	QESC	7.76	11.75	41.38	73.53	65.66	55.93	29.60	65.70	**65.75**	56.79 (+2.61%)
	RouteQuant	**7.73**	**11.73**	**43.17**	72.85	65.57	**56.21**	**32.00**	69.31	65.67	**57.83 (+4.48%)**
DeepSeek	FP16	6.51	9.10	45.14	75.88	72.69	58.10	32.40	62.82	70.32	59.62
	DuQuant	7.66	10.52	39.25	71.33	64.89	53.54	25.00	57.04	64.64	53.67 (-)
	MoEQuant	7.55	10.24	39.08	70.83	66.67	53.54	26.60	58.24	64.09	54.15 (+0.89%)
	EAQuant	7.34	10.07	38.40	71.00	68.44	54.68	26.80	57.04	**65.82**	54.60 (+1.73%)
	QESC	7.35	10.10	39.58	70.83	67.22	54.58	28.40	58.24	64.25	54.73 (+1.97%)
	RouteQuant	**7.31**	**10.06**	**40.19**	**72.01**	**68.65**	**55.12**	**28.80**	**59.93**	64.40	**55.59 (+3.57%)**
Qwen3	FP16	8.70	12.31	52.56	79.34	88.75	59.52	34.00	83.03	70.32	66.79
	DuQuant	9.86	13.62	46.33	73.44	**86.67**	56.71	**32.60**	**80.51**	64.25	62.93 (-)
	MoEQuant	9.85	13.58	47.18	73.99	86.64	55.29	31.80	80.14	65.82	62.98 (+0.08%)
	EAQuant	9.59	13.29	49.15	75.29	86.48	**56.72**	30.40	77.62	66.46	63.16 (+0.37%)
	QESC	9.59	13.30	48.29	75.42	86.51	56.63	31.60	79.06	65.67	63.31 (+0.61%)
	RouteQuant	**9.58**	**13.28**	**49.66**	**75.84**	86.64	56.69	32.40	79.78	**66.61**	**63.95 (+1.61%)**

4 Experiments

4.1 Settings

Setup. We conduct all experiments on a single NVIDIA A100 (80 GB) GPU using `PyTorch` and fix the random seed across runs. For post-training calibration, we sample 256 sequences from the C4 corpus with a sequence length of 2048 tokens (Raffel et al., 2020). We use DuQuant (Lin et al., 2024a) as our underlying quantization framework and apply per-token activation quantization and per-channel weight quantization, following Fu et al. (2025). We configure the router to W8A8 in all experiments and ablation studies unless otherwise specified. The hyperparameters are set to $\alpha = 0.6$, $\beta = 0.95$, $\lambda_{\text{RAJ}} = 1$ and $\lambda_{\text{GH}} = 1$. We evaluate our method on state-of-the-art MoE models: OLMoE (Muennighoff et al., 2025), DeepSeek-MoE (Dai et al., 2024), and Qwen3-MoE (Yang et al., 2025). The detailed model configurations are summarized in Table 1.

Dataset. We evaluate perplexity on WikiText-2 (Merity et al., 2017) and C4 (Raffel et al., 2020). For zero-shot accuracy, we use ARC-Challenge, ARC-Easy (Clark et al., 2018), BoolQ (Clark et al., 2019), HellaSwag (Zellers et al., 2019), OpenBookQA (Mihaylov et al., 2018), RTE (Dagan et al., 2005), and WinoGrande (Sakaguchi et al., 2021). We follow the standard zero-shot protocol (no in-context examples) and score multiple-choice options by their average token log-likelihood. In addition, we evaluate our method on math and coding benchmarks, with details provided in Appendix B.

Evaluation Metrics. We evaluate models using token-level perplexity, zero-shot accuracy, and router consistency. Perplexity measures the model's average surprise over the evaluation corpus, where lower values indicate better language modeling; accuracy measures the fraction of correct predictions on downstream tasks, where higher values are better. We compute perplexity with model's native tokenizer and mea-

Table 3: **Main results under W4A8.** DuQuant serves as the baseline; the comparison includes MoEQuant, EAQuant, QESC, and RouteQuant on OLMoE, DeepSeek-MoE, and Qwen3-MoE.

Model	Method	Perplexity ↓		Accuracy ↑							
		Wiki2	C4	ARC-C	ARC-E	BoolQ	HellaS	OBQA	RTE	Wino.	Average
OLMoE	FP16	6.65	10.86	46.59	77.10	70.09	58.47	32.60	71.12	68.51	60.64
	DuQuant	7.30	11.41	43.60	73.53	65.93	56.98	31.20	62.09	66.54	57.12 (-)
	MoEQuant	7.22	11.30	**43.94**	**75.21**	65.47	56.52	31.00	66.45	66.85	57.92 (+1.39%)
	EAQuant	7.27	**11.25**	41.78	73.24	67.22	56.52	**31.80**	67.51	66.92	57.86 (+1.28%)
	QESC	7.21	11.26	42.66	73.53	**67.74**	56.61	30.80	67.23	66.77	57.91 (+1.37%)
	RouteQuant	**7.14**	**11.25**	41.89	72.85	67.68	**57.16**	31.40	**68.59**	**67.09**	**58.09 (+1.70%)**
DeepSeek	FP16	6.51	9.10	45.14	75.88	72.69	58.10	32.40	62.82	70.32	59.62
	DuQuant	7.02	9.70	41.47	73.44	70.37	56.21	**29.20**	60.28	67.32	56.90 (-)
	MoEQuant	6.90	9.58	41.47	73.19	72.08	**56.75**	28.60	59.21	67.96	57.04 (+0.24%)
	EAQuant	6.89	9.58	41.89	74.07	71.38	56.34	**29.20**	60.29	67.96	57.30 (+0.71%)
	QESC	6.89	9.57	41.81	74.24	71.50	56.46	29.00	59.93	67.25	57.15 (+0.48%)
	RouteQuant	**6.88**	**9.56**	**42.83**	**74.28**	**73.12**	56.68	**29.20**	**61.37**	**68.27**	**57.96 (+1.87%)**
Qwen3	FP16	8.70	12.31	52.56	79.34	88.75	59.52	34.00	83.03	70.32	66.79
	DuQuant	9.20	12.69	52.13	**79.42**	86.35	58.07	33.40	79.03	66.98	65.05 (-)
	MoEQuant	9.19	12.67	51.28	77.78	**88.87**	58.17	33.80	80.51	67.88	65.47 (+0.64%)
	EAQuant	9.13	12.62	51.54	78.20	85.85	58.52	35.00	80.87	67.32	65.33 (+0.42%)
	QESC	9.13	12.62	50.85	78.28	86.97	**58.68**	33.80	80.51	67.01	65.16 (+0.16%)
	RouteQuant	**9.01**	**12.61**	**52.99**	78.54	87.95	58.53	**35.40**	**82.67**	**69.14**	**66.46 (+2.16%)**

(a) W4A4   (b) W4A8

Figure 4: Layer-averaged confusion matrices of router top-k indices versus FP16 on OLMoE; RouteQuant shows stronger on-diagonal alignment than DuQuant.

sure accuracy under the standard zero-shot protocol. For zero-shot benchmarks, we use the open-source `lm-evaluation-harness` to standardize prompting and scoring under its default configuration (Gao et al., 2024). Router consistency is quantified by the *Match Score* defined in Appendix C.

4.2 Results

Main Results. Tables 2 and 3 summarize PTQ performance on OLMoE, DeepSeek-MoE, and Qwen3-MoE. Across both bit settings, RouteQuant attains the best average accuracy among PTQ baselines and closes the perplexity gap to full precision. Relative to DuQuant, RouteQuant improves the average zero-shot accuracy at W4A4 by +4.48% on OLMoE, +3.57% on DeepSeek-MoE, and +1.61% on Qwen3-MoE, and at W4A8 by +1.70% on OLMoE, +1.87% on DeepSeek-MoE, and +2.16% on Qwen3-MoE. It also yields the lowest perplexity among quantized methods under W4A4 and W4A8. Overall, RouteQuant consistently strengthens accuracy while preserving perplexity across diverse MoE backbones and bit budgets, supporting our design of expert-specific scaling and router-consistency losses for robust PTQ of MoE. We also provide the W3A8 experiments in Appendix D.

Router Consistency (Match Score). Table 4 reports the agreement between FP16 routing and each PTQ method, while the layer-averaged confusion matrices in Figure 4 visualize the same trend. Across

Table 4: Match Score under W4A4 and W4A8.

Bits	Method	Match Score ↑		
		OLMoE	DeepSeek	Qwen3
	DuQuant	63.71	56.11	51.68
	MoEQuant	64.25	57.38	52.23
W4A4	EAQuant	65.02	58.11	52.45
	QESC	65.10	58.32	52.69
	RouteQuant	**66.95**	**59.24**	**53.97**
	DuQuant	72.87	62.56	66.17
	MoEQuant	73.69	62.88	66.97
W4A8	EAQuant	73.54	63.96	66.86
	QESC	73.67	63.78	66.45
	RouteQuant	**75.25**	**65.00**	**68.13**

Figure 5: Average accuracy with "Perfect Match" routing, where the selections follows the FP16 top-k.

Table 5: Ablation of RouteQuant objectives on OLMoE (W4A4).

ES	RAJ	GH	ARC-C	ARC-E	BoolQ	HellaS	OBQA	RTE	Wino.	Avg. ↑
			40.96	72.26	63.88	54.99	30.20	60.43	64.72	55.35 (-)
✓			41.30	73.36	**65.96**	**56.40**	31.00	64.62	66.06	56.96 (+2.91%)
	✓	✓	42.41	**74.24**	65.78	55.77	29.20	63.54	**67.09**	56.86 (+2.73%)
✓	✓		41.89	72.84	65.38	56.25	31.00	67.51	65.87	57.25 (+3.43%)
✓		✓	43.09	73.32	65.42	56.15	31.60	68.23	65.52	57.62 (+4.10%)
✓	✓	✓	**43.17**	72.85	65.57	56.21	**32.00**	**69.31**	65.67	**57.83** (+4.48%)

OLMoE, DeepSeek-MoE, and Qwen3-MoE, RouteQuant achieves the highest match scores under both W4A4 and W4A8, indicating that its quantized router decisions remain closest to the full-precision baseline. These improvements in routing consistency directly parallel the accuracy gains reported in Tables 2 and 3: methods that better preserve router behavior deliver stronger accuracy at the same level. This reinforces our design principle that stabilizing router rankings is essential for low-bit MoE inference and translates into downstream performance improvements.

4.3 Ablation Study

Perfect-Match Routing. To isolate the effect of routing on downstream accuracy, the quantized model is executed under a *perfect-match* scheme in which the selected top-k experts at every token exactly follow the FP16 router while all experts remain quantized. On OLMoE at W4A4, this scheme boosts average accuracy across all methods, validating that routing mismatches are a principal source of PTQ degradation (see Figure 5). The smaller headroom for RouteQuant is consistent with its higher match score, showing that *RAJ* and *GH* already recover much of the routing fidelity.

Objective-wise Impact. We quantify the contribution of each objective on OLMoE at W4A4 (see Table 5). Starting from the DuQuant baseline, *ES* alone raises the average to 56.96. On top of *ES*, adding *RAJ* improves performance to 57.25, and *GH* further to 57.62. Applying *RAJ+GH* without *ES* also yields improvement, showing that these objectives are effective on their own. Enabling all three delivers the best result, reinforcing the effectiveness of our design objective.

Rank-Decay Sensitivity (β). We study the weighting parameter β in *RAJ* (see Figure 6), which controls how importance decays across expert ranks: $\beta = 1$ assigns a uniform weight to all top-k ranks, while a smaller β applies an exponential decay that emphasizes higher-ranked experts. Sweeping $\beta \in \{0.85, 0.90, 0.95, 1.00\}$, we find that $\beta = 0.95$ consistently yields the best average accuracy under both W4A4 and W4A8. $\beta \leq 0.90$ overemphasize the top-1 and top-2 experts and amplify noise from minor rank flips, whereas $\beta = 1.00$ spreads weight too uniformly and under-penalizes lower-rank mismatches. The peak at $\beta = 0.95$ indicates that a mild

Figure 6: Average accuracy of different β on OLMoE under W4A4 and W4A8.

Figure 7: Effect of λ_{RAJ}:λ_{GH} on OLMoE under W4A4 and W4A8.

Table 6: **W4A8 results with router at W4A8.** DuQuant serves as the baseline; the comparison includes MoEQuant, EAQuant, QESC, and RouteQuant on OLMoE, DeepSeek-MoE, and Qwen3-MoE.

Model	Method	Perplexity ↓		Accuracy ↑							
		Wiki2	C4	ARC-C	ARC-E	BoolQ	HellaS	OBQA	RTE	Wino.	Average
OLMoE	FP16	6.65	10.86	46.59	77.10	70.09	58.47	32.60	71.12	68.51	60.64
	DuQuant	7.43	11.52	**42.75**	**74.24**	65.11	56.05	29.20	62.82	66.22	56.63 (-)
	MoEQuant	7.20	11.32	40.36	72.26	**67.74**	57.20	30.80	66.45	**67.80**	57.52 (+1.57%)
	EAQuant	7.18	11.29	40.19	72.31	**67.74**	57.43	31.00	67.51	67.48	57.67 (+1.83%)
	QESC	7.18	11.30	41.47	72.90	67.22	57.35	30.80	66.15	66.69	57.51 (+1.56%)
	RouteQuant	**7.17**	**11.28**	42.66	73.61	66.88	57.13	**31.20**	**68.95**	66.61	**58.15 (+2.69%)**
DeepSeek	FP16	6.51	9.10	45.14	75.88	72.69	58.10	32.40	62.82	70.32	59.62
	DuQuant	7.03	9.74	41.81	73.27	71.74	**56.63**	26.80	57.76	**68.03**	56.58 (-)
	MoEQuant	6.92	9.61	41.89	73.40	71.77	56.52	27.40	58.84	67.48	56.76 (+0.32%)
	EAQuant	6.91	9.59	41.64	74.45	71.44	56.13	**29.40**	59.57	66.54	57.02 (+0.79%)
	QESC	6.91	9.59	41.47	74.28	71.10	56.28	29.20	**60.29**	66.93	57.08 (+0.89%)
	RouteQuant	**6.90**	**9.58**	**42.83**	**74.79**	**73.06**	56.62	28.80	59.57	67.01	**57.53 (+1.68%)**
Qwen3	FP16	8.70	12.31	52.56	79.34	88.75	59.52	34.00	83.03	70.32	66.79
	DuQuant	9.29	12.83	51.19	**79.88**	87.49	57.61	33.00	79.42	68.03	65.23 (-)
	MoEQuant	9.25	12.70	52.05	77.74	88.26	58.03	34.40	80.87	67.88	65.60 (+0.57%)
	EAQuant	9.31	12.71	51.11	78.54	86.70	**58.36**	33.40	81.59	68.67	65.48 (+0.38%)
	QESC	9.26	12.68	51.54	79.04	86.88	58.14	**34.80**	79.78	68.75	65.56 (+0.51%)
	RouteQuant	**9.04**	**12.65**	**52.99**	79.12	**88.53**	58.32	34.40	**82.67**	**70.48**	**66.64 (+2.17%)**

exponential decay strikes the right balance, prioritizing the top of the FP16 ranking while still regularizing lower ranks, thereby improving router consistency and downstream accuracy.

Balancing Rank and Margin. The router-loss is $\mathcal{L}_{\text{router}}$ (see Figure 7) is controlled by λ_{RAJ} and λ_{GH} to balance between rank and margin preservation. A sweep over ratios {1:4, 1:2, 1:1, 2:1, 4:1} on OLMoE shows that 1:1 attains the highest average accuracy under both W4A4 and W4A8. Skewing the weights toward *RAJ* (e.g., 4:1) over-penalizes benign rank shuffles and dampens margins, while favoring *GH* (e.g., 1:4) prioritizes separation but becomes less sensitive to near ties within the top-k. The symmetric setting aligns the objectives, improving match score and yielding the best downstream accuracy at the same bit budget.

Router-Quantized Robustness. In the main experiments, the router is kept at W8A8 while only the expert modules are quantized. To further validate the robustness of our design, we additionally quantize the router to W4A8, matching the precision used for experts. This setting is substantially more challenging since router logits directly determine expert selection and are highly sensitive to quantization noise. As shown in Table 6, RouteQuant consistently achieves the best average accuracy across OLMoE, DeepSeek-MoE, and Qwen3-MoE. These results further confirm our hypothesis that improving routing stability is crucial

Table 7: Tokens/sec throughput under W4A8. Values are reported as mean±std over 5 runs.

Model	Tokens-per-second ↑		
	OLMoE	DeepSeek	Qwen3
DuQuant	6.52 ± 0.01	23.88 ± 0.05	1.17 ± 0.01
MoEQuant	6.84 ± 0.03	24.56 ± 0.06	1.21 ± 0.02
EAQuant	6.72 ± 0.05	24.14 ± 0.07	1.20 ± 0.01
QESC	6.70 ± 0.03	24.08 ± 0.05	1.19 ± 0.01
RouteQuant	6.49 ± 0.03	23.79 ± 0.06	1.16 ± 0.01

Table 8: Comparison between keeping the router in full precision with *ES* only (*w/o router*) and full RouteQuant with a quantized router (*w/ router*).

Model	Method	Wiki2 ↓	C4 ↓	Avg. ↑
OLMoE	w/o router	7.74	11.74	57.41
	w/ router	7.73	11.73	57.83
DeepSeek	w/o router	7.32	10.06	55.23
	w/ router	7.31	10.06	55.59
Qwen3	w/o router	9.59	13.30	63.52
	w/ router	9.58	13.28	63.95

Table 9: Zero-shot accuracy under W4A16 quantization.

Model	Method	Accuracy ↑							
		ARC-C	ARC-E	BoolQ	HellaS	OBQA	RTE	Wino.	Average
OLMoE	FP16	46.59	77.10	70.09	58.47	32.60	71.12	68.51	60.64
	AWQ	41.55	74.49	66.67	56.69	31.40	**63.90**	65.43	57.16
	GPTQ	42.66	**75.21**	67.34	57.33	31.80	62.82	67.72	57.84
	RouteQuant	**45.22**	**75.21**	**70.00**	**57.66**	**32.60**	62.82	**68.27**	**58.83**
DeepSeek	FP16	45.14	75.88	72.69	58.10	32.40	62.82	70.32	59.62
	AWQ	41.38	72.22	65.66	55.73	28.40	57.04	66.61	55.29
	GPTQ	42.49	73.61	67.55	56.21	29.40	60.43	65.67	56.48
	RouteQuant	**44.45**	**74.37**	**73.82**	**56.62**	**30.00**	**64.62**	**68.75**	**58.95**
Qwen3	FP16	52.56	79.34	88.75	59.52	34.00	83.03	70.32	66.79
	AWQ	45.73	73.53	86.48	56.51	**33.60**	80.51	67.80	63.45
	GPTQ	48.81	76.94	87.95	57.01	32.80	77.98	68.82	64.33
	RouteQuant	**53.07**	**79.25**	**88.69**	**58.66**	32.80	**81.23**	**68.98**	**66.10**

under aggressive precision constraints, making RouteQuant more resilient when both routing and expert computation are quantized.

Runtime Efficiency. We evaluate decoding throughput (Tokens/Sec.) on a single NVIDIA A100 using prompts of 1024 tokens and generating 128 tokens, and we report the mean ± std over five runs. The Table 7 shows that DuQuant, MoEQuant, EAQuant and QESC achieve similar runtimes with small standard deviations, indicating that RouteQuant remains comparable even when incorporating heterogeneous expert scaling. This parity is expected because *ES* introduces only a lightweight per-expert scaling that is applied once during quantization and reduces to a constant multiplication at inference, incurring negligible overhead. Similarly, *RAJ* and *GH* are optimization objectives that are invoked only in the calibration stage to adjust quantization parameters, and thus do not alter the forward pass or add runtime cost. As a result, the inference computation graph and memory traffic remain identical to the baseline, ensuring that RouteQuant preserves runtime efficiency while providing superior accuracy and perplexity.

Full-Precision Router in RouteQuant. We further examine whether keeping the router in full precision is beneficial within the RouteQuant framework. Since *ES* is independent of the router's precision, while *RAJ* and *GH* require a quantized router to regularize routing consistency, we compare an *ES*-only variant with an FP16 router (*w/o router*) against full RouteQuant with *ES+RAJ+GH* and a quantized router (*w/ router*). As shown in Table 8, the FP16-router setting consistently underperforms RouteQuant across all models. This demonstrates that expert scaling alone is insufficient, and that router quantization is essential for fully realizing the benefits of RouteQuant.

Table 10: Results on VLM benchmarks on Qwen3-VL-MoE (W4A4).

Method	Accuracy ↑								
	GQA	ChartQA	ScienceQA	RWQA	K-DTC	OCR	MMMU	ai2d	Average
FP16	64.04	85.28	93.63	66.14	83.33	84.80	52.00	86.08	76.91
DuQuant	59.42	79.52	90.71	63.22	79.21	81.28	48.19	82.36	72.99 (-)
MoEQuant	60.26	80.28	91.93	63.22	80.55	82.31	48.22	**83.97**	73.84 (+1.17%)
EAQuant	61.92	82.44	91.56	63.82	80.73	82.58	49.13	83.16	74.42 (+1.96%)
QESC	61.87	**84.22**	91.44	63.65	80.68	82.47	49.22	83.08	74.58 (+2.18%)
RouteQuant	**62.08**	84.17	**92.17**	**64.08**	**81.19**	**82.98**	**50.90**	83.16	**75.09 (+2.88%)**

Weight-only quantization (W4A16). The main experiments primarily focus on scenarios where both weights and activations are quantized. To assess whether our method remains effective without activation quantization, we further conduct evaluations under the weight-only setting. Compared against strong baselines such as AWQ (Lin et al., 2024b) and GPTQ (Frantar et al., 2022), our method consistently achieves large gains in zero-shot accuracy (see Table 9). This demonstrates that our approach not only addresses activation outliers but also provides robust improvements when only the weight domain is quantized.

5 Extending to Multimodal MoEs

To further demonstrate that our proposed quantization framework generalizes beyond language-only MoE models, we additionally evaluate it on a state-of-the-art multimodal architecture. Specifically, we conduct experiments on the Qwen3-VL-30B-A3B-Instruct model (Yang et al., 2025) to assess whether the same quantization strategies remain effective in vision–language settings.

For post-training calibration, we sample image–text pairs from the Flickr30k dataset (Plummer et al., 2015), following an analogous setup to our experiments. We quantize the model using the same configuration as in prior sections, with per-token activation quantization and per-channel weight quantization, and we evaluate W4A4 variant. Multimodal performance is assessed using `lmms-eval` under its default evaluation protocol. We test across a wide range of benchmarks covering visual reasoning, document understanding, scientific question answering, and real-world perception: GQA (Hudson & Manning, 2019), ChartQA (Masry et al., 2022), ScienceQA (Lu et al., 2022), RealWorldQA (Zhang et al., 2025), K-DTCBench (Ju et al., 2024), OCRBench (Liu et al., 2024c), MMMU (Yue et al., 2023), and AI2D (Kembhavi et al., 2016).

Across all datasets, we observe that the W4A4 version of our method consistently outperforms competing quantization baselines (see Table 10). Notably, the gap is especially clear on multimodal reasoning and knowledge-intensive tasks. These findings validate that the proposed approach is not only effective for large MoE language models but also transfers robustly to more complex multimodal systems, highlighting its versatility and practical utility across diverse architectures.

6 Conclusion and Future Work

This paper studies PTQ of MoE models and establishes that router performance governs low-bit accuracy, with errors concentrating as near-neighbor flips near the top-k experts and arising from small score margins. We present RouteQuant, a training-free, calibration-only framework that combines *ES* with *RAJ* and *GH* objectives to stabilize expert rankings and preserve margins; Empirically, the framework yields lower perplexity on C4 and WikiText-2 and higher zero-shot accuracy on OLMoE, DeepSeek-MoE, and Qwen3-MoE under W4A4 and W4A8. Looking ahead, we plan to extend our framework to multimodal MoE settings, where heterogeneous modalities may amplify router instability under quantization. We also aim to study adaptive precision guided by observed rank gaps and load patterns, to further enhance robustness and generalization across diverse tasks.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023. doi: https://doi.org/10.48550/arXiv.2303.08774.

Rahaf Aljundi, Punarjay Chakravarty, and Tinne Tuytelaars. Expert gate: Lifelong learning with a network of experts. In *Proceedings of the 2017 IEEE conference on computer vision and pattern recognition*, pp. 3366–3375, 2017.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Pondé de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

Yuanteng Chen, Yuantian Shao, Peisong Wang, and Jian Cheng. EAC-MoE: Expert-selection aware compressor for mixture-of-experts large language models. In *Proceedings of the 2025 Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2025a. doi: 10.18653/v1/2025.acl-long.633.

Zhixuan Chen, Xing Hu, Dawei Yang, Zukang Xu, XUCHEN, Zhihang Yuan, Sifan Zhou, and JiangyongYu. MoEQuant: Enhancing quantization for mixture-of-experts large language models via expert-balanced sampling and affinity guidance. In *Proceedings of the 2025 International Conference on Machine Learning*, 2025b.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. BoolQ: Exploring the surprising difficulty of natural yes/no questions. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 2924–2936, 2019. doi: https://doi.org/10.18653/v1/N19-1300.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018. doi: https://doi.org/10.48550/arXiv.1803.05457.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Ido Dagan, Oren Glickman, and Bernardo Magnini. The pascal recognising textual entailment challenge. In *Proceedings of the 2005 Machine learning challenges workshop*, pp. 177–190, 2005.

Damai Dai, Chengqi Deng, Chenggang Zhao, R.x. Xu, Huazuo Gao, Deli Chen, Jiashi Li, Wangding Zeng, Xingkai Yu, Y. Wu, Zhenda Xie, Y.k. Li, Panpan Huang, Fuli Luo, Chong Ruan, Zhifang Sui, and Wenfeng Liang. DeepSeekMoE: Towards ultimate expert specialization in mixture-of-experts language models. In *Proceedings of the 2024 Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2024. doi: https://doi.org/10.18653/v1/2024.acl-long.70.

Marc Deisenroth and Jun Wei Ng. Distributed gaussian processes. In *Proceedings of the 2015 International Conference on Machine Learning*, pp. 1481–1490, 2015.

Nan Du, Yanping Huang, Andrew M Dai, Simon Tong, Dmitry Lepikhin, Yuanzhong Xu, Maxim Krikun, Yanqi Zhou, Adams Wei Yu, Orhan Firat, et al. GLaM: Efficient scaling of language models with mixture-of-experts. In *Proceedings of the 2022 International Conference on Machine Learning*, pp. 5547–5569, 2022.

William Fedus, Barret Zoph, and Noam Shazeer. Switch Transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39, 2022.

Elias Frantar, Saleh Ashkboos, Torsten Hoefler, and Dan Alistarh. GPTQ: Accurate post-training quantization for generative pre-trained transformers. *arXiv preprint arXiv:2210.17323*, 2022. doi: https://doi.org/10.48550/arXiv.2210.17323.

Zhongqian Fu, Ning Ding, Kai Han, Xianzhi Yu, Xiaosong Li, Xinghao Chen, Yehui Tang, and Yunhe Wang. EAQuant: Enhancing post-training quantization for moe models via expert-aware optimization. *arXiv preprint arXiv:2506.13329*, 2025. doi: https://doi.org/10.48550/arXiv.2506.13329.

Leo Gao, Jonathan Tow, Baber Abbasi, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Alain Le Noac'h, Haonan Li, Kyle McDonell, Niklas Muennighoff, Chris Ociepa, Jason Phang, Laria Reynolds, Hailey Schoelkopf, Aviya Skowron, Lintang Sutawika, Eric Tang, Anish Thite, Ben Wang, Kevin Wang, and Andy Zou. The language model evaluation harness, 07 2024.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024. doi: https://doi.org/10.48550/arXiv.2407.21783.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025. doi: https://doi.org/10.48550/arXiv.2501.12948.

Drew A Hudson and Christopher D Manning. GQA: A new dataset for real-world visual reasoning and compositional question answering. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 6700–6709, 2019.

Robert A Jacobs, Michael I Jordan, Steven J Nowlan, and Geoffrey E Hinton. Adaptive mixtures of local experts. *Neural computation*, 3(1):79–87, 1991. doi: https://doi.org/10.1162/neco.1991.3.1.79.

Albert Q Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, et al. Mixtral of experts. *arXiv preprint arXiv:2401.04088*, 2024. doi: https://doi.org/10.48550/arXiv.2401.04088.

Michael I Jordan and Robert A Jacobs. Hierarchical mixtures of experts and the em algorithm. *Neural computation*, 6(2):181–214, 1994. doi: https://doi.org/10.1162/neco.1994.6.2.181.

Jeongho Ju, Daeyoung Kim, SunYoung Park, and Youngjune Kim. VARCO-VISION: Expanding frontiers in korean vision-language models, 2024. URL `https://arxiv.org/abs/2411.19103`.

Aniruddha Kembhavi, Mike Salvato, Eric Kolve, Minjoon Seo, Hannaneh Hajishirzi, and Ali Farhadi. A diagram is worth a dozen images. In *European conference on computer vision*, pp. 235–251. Springer, 2016.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 2023 symposium on operating systems principles*, pp. 611–626, 2023.

Dmitry Lepikhin, HyoukJoong Lee, Yuanzhong Xu, Dehao Chen, Orhan Firat, Yanping Huang, Maxim Krikun, Noam Shazeer, and Zhifeng Chen. GShard: Scaling giant models with conditional computation and automatic sharding. In *Proceedings of the 2021 International Conference on Learning Representations*, 2021.

Haokun Lin, Haobo Xu, Yichen Wu, Jingzhi Cui, Yingtao Zhang, Linzhan Mou, Linqi Song, Zhenan Sun, and Ying Wei. DuQuant: Distributing outliers via dual transformation makes stronger quantized LLMs. In *Proceedings of the 2024 Annual Conference on Neural Information Processing Systems*, 2024a.

Ji Lin, Jiaming Tang, Haotian Tang, Shang Yang, Wei-Ming Chen, Wei-Chen Wang, Guangxuan Xiao, Xingyu Dang, Chuang Gan, and Song Han. AWQ: Activation-aware weight quantization for on-device llm compression and acceleration. *Proceedings of the 2024 machine learning and systems*, 6:87–100, 2024b.

Aixin Liu, Bei Feng, Bin Wang, Bingxuan Wang, Bo Liu, Chenggang Zhao, Chengqi Dengr, Chong Ruan, Damai Dai, Daya Guo, et al. Deepseek-v2: A strong, economical, and efficient mixture-of-experts language model. *arXiv preprint arXiv:2405.04434*, 2024a. doi: https://doi.org/10.48550/arXiv.2405.04434.

Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, et al. Deepseek-v3 technical report. *arXiv preprint arXiv:2412.19437*, 2024b. doi: https://doi.org/10.48550/arXiv.2412.19437.

Yuliang Liu, Zhang Li, Mingxin Huang, Biao Yang, Wenwen Yu, Chunyuan Li, Xu-Cheng Yin, Cheng-Lin Liu, Lianwen Jin, and Xiang Bai. OCRBench: on the hidden mystery of ocr in large multimodal models. *Science China Information Sciences*, 67(12):220102, 2024c.

Pan Lu, Swaroop Mishra, Tony Xia, Liang Qiu, Kai-Wei Chang, Song-Chun Zhu, Oyvind Tafjord, Peter Clark, and Ashwin Kalyan. Learn to explain: Multimodal reasoning via thought chains for science question answering. In *The 36th Conference on Neural Information Processing Systems (NeurIPS)*, 2022.

Wenhan Ma, Hailin Zhang, Liang Zhao, Yifan Song, Yudong Wang, Zhifang Sui, and Fuli Luo. Stabilizing moe reinforcement learning by aligning training and inference routers. *arXiv preprint arXiv:2510.11370*, 2025.

Ahmed Masry, Xuan Long Do, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. ChartQA: A benchmark for question answering about charts with visual and logical reasoning. In *Findings of the association for computational linguistics: ACL 2022*, pp. 2263–2279, 2022.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. In *Proceedings of the 2017 International Conference on Learning Representations*, 2017.

Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. Can a suit of armor conduct electricity? a new dataset for open book question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2381–2391, 2018. doi: https://doi.org/10.18653/v1/D18-1260.

Niklas Muennighoff, Luca Soldaini, Dirk Groeneveld, Kyle Lo, Jacob Morrison, Sewon Min, Weijia Shi, Pete Walsh, Oyvind Tafjord, Nathan Lambert, et al. OLMoE: Open mixture-of-experts language models. In *Proceedings of the 2025 International Conference on Learning Representations*, 2025.

Bryan A Plummer, Liwei Wang, Chris M Cervantes, Juan C Caicedo, Julia Hockenmaier, and Svetlana Lazebnik. Flickr30k entities: Collecting region-to-phrase correspondences for richer image-to-sentence models. In *Proceedings of the IEEE international conference on computer vision*, pp. 2641–2649, 2015.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of machine learning research*, 21(140):1–67, 2020.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. *Communications of the ACM*, 64(9):99–106, 2021. doi: https://doi.org/10.1145/3474381.

Wenqi Shao, Mengzhao Chen, Zhaoyang Zhang, Peng Xu, Lirui Zhao, Zhiqian Li, Kaipeng Zhang, Peng Gao, Yu Qiao, and Ping Luo. OmniQuant: Omnidirectionally calibrated quantization for large language models. In *Proceedings of the 2024 International Conference on Learning Representations*, 2024.

Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc Le, Geoffrey Hinton, and Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. In *Proceedings of the 2017 International Conference on Learning Representations*, 2017.

Guangxuan Xiao, Ji Lin, Mickael Seznec, Hao Wu, Julien Demouth, and Song Han. Smoothquant: Accurate and efficient post-training quantization for large language models. In *Proceedings of the 2023 International Conference on Machine Learning*, pp. 38087–38099, 2023.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025. doi: https://doi.org/10.48550/arXiv.2505.09388.

Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, et al. MMMU: A massive multi-discipline multimodal understanding and reasoning benchmark for expert agi. *arXiv preprint arXiv:2311.16502*, 2023.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. HellaSwag: Can a machine really finish your sentence? In *Proceedings of the 2019 Annual Meeting of the Association for Computational Linguistics*, pp. 4791–4800, 2019. doi: https://doi.org/10.18653/v1/P19-1472.

Kaichen Zhang, Bo Li, Peiyuan Zhang, Fanyi Pu, Joshua Adrian Cahyono, Kairui Hu, Shuai Liu, Yuanhan Zhang, Jingkang Yang, Chunyuan Li, et al. Lmms-eval: Reality check on the evaluation of large multimodal models. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pp. 881–916, 2025.

A   Theoretical Analysis of Router Quantization

In this section we provide proofs for Proposition 1: *Router-induced MoE output error* and Proposition 2: *Gap condition for top-k stability.*

A.1   Proof of Proposition 1

Proof. For a fixed input x, we have:

$$y^{(\text{fp})}(x) = \sum_{j \in I} \pi_j^{(\text{fp})}(x)\,\mathcal{E}_j, \tag{18}$$

$$y^{(q)}(x) = \sum_{j \in J} \pi_j^{(q)}(x)\,\mathcal{E}_j, \tag{19}$$

where we omit x for brevity.

Using the decomposition $I = S^* \cup S^-$ and $J = S^* \cup S^+$, we have:

$$y^{(\text{fp})} - y^{(q)} = \sum_{j \in S^*} \big(\pi_j^{(\text{fp})} - \pi_j^{(q)}\big)\mathcal{E}_j + \sum_{j \in S^-} \pi_j^{(\text{fp})}\mathcal{E}_j - \sum_{j \in S^+} \pi_j^{(q)}\mathcal{E}_j. \tag{20}$$

Taking norms and applying the triangle inequality yields:

$$\big\|y^{(\text{fp})} - y^{(q)}\big\| \leq \sum_{j \in S^*} \big|\pi_j^{(\text{fp})} - \pi_j^{(q)}\big|\,\|\mathcal{E}_j\| + \sum_{j \in S^-} \pi_j^{(\text{fp})}\|\mathcal{E}_j\| + \sum_{j \in S^+} \pi_j^{(q)}\|\mathcal{E}_j\|. \tag{21}$$

Under the assumption that $\|\mathcal{E}_j(x)\| \leq B(x)$ for all j, we obtain:

$$\big\|y^{(\text{fp})}(x) - y^{(q)}(x)\big\| \leq B(x)\Big(\sum_{j \in S^*} \big|\pi_j^{(\text{fp})}(x) - \pi_j^{(q)}(x)\big| + \sum_{j \in S^-} \pi_j^{(\text{fp})}(x) + \sum_{j \in S^+} \pi_j^{(q)}(x)\Big), \tag{22}$$

which is exactly Equation (7). $\qquad\square$

A.2   Proof of Proposition 2

Proof. Let $I = (i_1, \ldots, i_k)$ denote the ordered top-k indices under the full-precision logits $r^{(\text{fp})}$, and let I^c be its complement. Define the consecutive gaps along the FP ordering as

$$\Delta_r^{(\text{fp})} = r_{i_r}^{(\text{fp})} - r_{i_{r+1}}^{(\text{fp})} > \epsilon, \quad r = 1, \ldots, k. \tag{23}$$

Assume that the quantized logits satisfy the gap condition along the same FP order:

$$\Delta_r^{(q)} \triangleq r_{i_r}^{(q)} - r_{i_{r+1}}^{(q)} \geq \Delta_r^{(\text{fp})}, \quad r = 1, \ldots, k. \tag{24}$$

Then, for any $r \in \{1, \ldots, k\}$, summing over consecutive gaps yields

$$r_{i_r}^{(q)} - r_{i_{k+1}}^{(q)} = \sum_{t=r}^{k} \Delta_t^{(q)} \geq \sum_{t=r}^{k} \Delta_t^{(\text{fp})} = r_{i_r}^{(\text{fp})} - r_{i_{k+1}}^{(\text{fp})} > 0, \tag{25}$$

which implies $r_{i_r}^{(q)} > r_{i_{k+1}}^{(q)}$ for all $r \leq k$.

Moreover, since i_{k+1} is the highest-ranked index in I^c under the FP ordering, we have $r_{i_{k+1}}^{(q)} \geq r_j^{(q)}$ for all $j \in I^c$ whenever the FP order is preserved on I^c. Therefore,

$$r_{i_r}^{(q)} > r_j^{(q)}, \quad \forall r \leq k, \ \forall j \in I^c, \tag{26}$$

which shows that no index in I^c can enter the top-k under quantization. Hence, the ordered top-k expert indices are preserved with full precision. $\qquad\square$

Table 11: Performance on math and coding benchmarks.

Method	GSM8K ↑ (8-shot CoT EM)	HumanEval ↑ (0-shot Pass@1)
FP16	87.89	41.70
DuQuant	75.72	32.34
MoEQuant	77.12	35.83
EAQuant	78.25	37.20
QESC	78.33	36.89
RouteQuant	**80.21**	**38.41**

B Math and Coding Evaluation

In addition to the main benchmarks, we further evaluate our method on representative math and coding tasks to assess its robustness on reasoning-intensive workloads. Specifically, we report results on GSM8K (8-shot chain-of-thought exact match) for mathematical reasoning (Cobbe et al., 2021) and HumanEval (0-shot Pass@1) for code generation (Chen et al., 2021). As shown in Table 11, while post-training quantization leads to noticeable performance degradation compared to FP16, RouteQuant consistently outperforms other MoE quantization baselines on both tasks. These results suggest that preserving routing consistency not only benefits language modeling and multiple-choice benchmarks, but also improves robustness on complex reasoning and program synthesis tasks.

C Match Score for Router Consistency

We quantify the agreement between FP16 and quantized routing with a *Match Score* that evaluates whether the quantized router preserves both the membership and the order of the FP16 top-k experts. For each MoE layer $\ell \in \{1, \ldots, L\}$, let:

$$I^{(\ell)} = (i_1^{(\ell)}, \ldots, i_k^{(\ell)}) = \text{top-}k(\mathbf{r}_\ell^{(\text{fp})}, k),$$

$$J^{(\ell)} = (j_1^{(\ell)}, \ldots, j_k^{(\ell)}) = \text{top-}k(\mathbf{r}_\ell^{(\text{q})}, k),$$

denote the ordered top-k expert indices from FP16 and quantized router logits, respectively, where top-$k(\cdot, k)$ returns the indices sorted by descending scores. Define the quantized rank function:

$$\rho_\ell^{(\text{q})}(e) = \begin{cases} s, & \text{if } e = j_s^{(\ell)} \text{ with } s \in \{1, \ldots, k\}, \\ \infty, & \text{if } e \notin J^{(\ell)}, \end{cases}$$

so that an FP16-selected expert missing from the quantized top-k receives infinite rank (and thus zero credit). The layerwise agreement is then averaged over the k FP16-selected experts and over all L layers:

$$S = \frac{1}{kL} \sum_{\ell=1}^{L} \sum_{r=1}^{k} \frac{1}{1 + \left| r - \rho_\ell^{(\text{q})}(i_r^{(\ell)}) \right|}, \tag{27}$$

with the convention $1/(1 + \infty) = 0$. By construction, $S \in [0, 1]$; $S = 1$ if and only if the quantized top-k exactly matches FP16, including ranks in every layer, and S approaches 0 when FP16-selected experts are consistently absent from the quantized top-k or appear only at much lower ranks. We compute $\mathbf{r}_\ell^{(\text{fp})}$ and $\mathbf{r}_\ell^{(\text{q})}$ for each input token and then report the dataset-level Match Score by averaging Equation (27) over tokens in a held-out set. Equivalently, if $S^{(t)}$ denotes Equation (27) evaluated on token t, the reported score is:

$$\bar{S} = \frac{1}{T} \sum_{t=1}^{T} S^{(t)},$$

Table 12: **Results under W3A8.** DuQuant serves as the baseline; the comparison includes MoEQuant, EAQuant, QESC, and RouteQuant on OLMoE, DeepSeek-MoE, and Qwen3-MoE.

Model	Method	Perplexity ↓		Accuracy ↑							
		Wiki2	C4	ARC-C	ARC-E	BoolQ	HellaS	OBQA	RTE	Wino.	Average
OLMoE	FP16	6.65	10.86	46.59	77.10	70.09	58.47	32.60	71.12	68.51	60.64
	DuQuant	10.78	14.33	36.00	66.71	61.74	50.76	27.60	**61.37**	59.12	51.90 (-)
	MoEQuant	8.89	12.74	37.28	68.73	**66.91**	54.35	28.20	57.04	62.98	53.64 (+3.36%)
	EAQuant	8.79	12.66	37.12	68.73	62.08	54.46	28.60	59.57	64.48	53.58 (+3.23%)
	QESC	8.79	12.67	37.03	68.31	61.93	54.42	28.20	59.21	63.93	53.29 (+2.68%)
	RouteQuant	**8.75**	**12.65**	**38.48**	**70.79**	63.85	**54.58**	**30.60**	60.65	**65.75**	**54.96 (+5.89%)**

Table 13: Zero-shot accuracy under W4A4 quantization with **128** calibration samples from **C4**.

Model	Method	Accuracy ↑							
		ARC-C	ARC-E	BoolQ	HellaS	OBQA	RTE	Wino.	Average
OLMoE	FP16	46.59	77.10	70.09	58.47	32.60	71.12	68.51	60.64
	DuQuant	**40.53**	70.24	65.20	55.20	29.80	62.82	63.06	55.26
	MoEQuant	39.85	**71.59**	65.81	54.86	29.60	62.82	**65.43**	55.71
	EAQuant	39.24	71.00	**65.66**	55.01	31.00	63.54	63.93	55.63
	QESC	39.16	70.45	65.81	**56.01**	30.80	64.62	64.33	55.88
	RouteQuant	39.76	71.00	**65.66**	55.81	**31.80**	**66.79**	64.17	**56.43**

where T is the number of evaluated tokens. This metric is sensitive to both rank inversions within the selected set and omissions of FP16-selected experts, which makes it a faithful proxy for router consistency under quantization.

D Additional Experiments

Lower-Precision Robustness. Pushing weights to 3-bit while keeping activations at 8-bit stresses the MoE pipeline, yet RouteQuant remains the most robust. All methods experience a drop in accuracy relative to FP16, yet RouteQuant shows the smallest gap and attains the best average accuracy (see Table 12). The trend aligns with our routing hypothesis: lower weight precision amplifies rank flips and narrows score margins, making router consistency increasingly critical. *ES* stabilizes per-expert activation ranges, and *RAJ/GH* improve the match score by preserving rankings and margin gaps, which in turn sustains downstream accuracy under the more aggressive W3A8 setting.

Varying calibration samples. Throughout the main experiments, the number of calibration samples is fixed at 256. To examine the sensitivity of our method to this choice, we additionally conduct experiments with 128 and 512 calibration samples (see Table 13 and 14). In both cases, our method continues to outperform all baselines by a clear margin. These results suggest that our method is robust across different calibration budgets and does not rely on a carefully chosen sample size to deliver improvements.

Alternative calibration dataset. The primary results in the paper adopt C4 as the calibration dataset. To evaluate whether our method generalizes to other corpora, we also perform calibration on WikiText-2 (see Table 15). Even under this shift in data distribution, our method maintains consistent advantages over all competing approaches. This highlights that our improvements are not tied to a specific calibration corpus and confirms the general applicability of our design.

Table 14: Zero-shot accuracy under W4A4 quantization with **512** calibration samples from **C4**.

Model	Method	Accuracy ↑							
		ARC-C	ARC-E	BoolQ	HellaS	OBQA	RTE	Wino.	Average
OLMoE	FP16	46.59	77.10	70.09	58.47	32.60	71.12	68.51	60.64
	DuQuant	38.74	69.74	65.66	55.20	29.80	63.54	63.85	55.22
	MoEQuant	40.53	72.10	63.67	54.96	28.40	65.70	64.56	55.70
	EAQuant	41.72	72.85	65.90	55.92	30.60	67.51	**66.56**	57.29
	QESC	42.32	72.64	**66.06**	**56.11**	**31.80**	67.15	66.06	57.45
	RouteQuant	**42.66**	**74.62**	65.63	55.91	31.60	**69.31**	66.46	**58.03**

Table 15: Zero-shot accuracy under W4A4 quantization with **256** calibration samples from **WikiText-2**.

Model	Method	Accuracy ↑							
		ARC-C	ARC-E	BoolQ	HellaS	OBQA	RTE	Wino.	Average
OLMoE	FP16	46.59	77.10	70.09	58.47	32.60	71.12	68.51	60.64
	DuQuant	39.16	69.82	64.37	55.01	27.40	62.45	62.19	54.34
	MoEQuant	39.60	72.18	67.80	55.30	28.40	**63.18**	65.75	56.03
	EAQuant	41.72	73.86	65.81	55.93	28.20	62.85	64.17	56.08
	QESC	42.24	**74.58**	65.26	55.83	28.20	62.85	64.96	56.27
	RouteQuant	**42.49**	73.95	**68.01**	**56.02**	**28.60**	**63.18**	**65.90**	**56.88**

E   Additional Visualizations

To complement the analyses in the main text, we provide extended visualizations for both router behavior and expert activations. First, confusion matrices for additional OLMoE layers are shown in Figures 8 and 9. These figures confirm our earlier observation that router errors after quantization are highly localized: most mis-selections occur between neighboring experts, with errors clustering near the diagonal rather than spreading arbitrarily. This further supports the claim that router performance is the dominant factor for MoE quantization.

Second, we present detailed activation distributions across experts at different depths. As shown in Figures 10 to 12, experts within the same layer exhibit markedly heterogeneous activation ranges. This reinforces the motivation behind our *Expert-Aware Smoothing Factor*, which assigns each expert its own scaling factor instead of relying on max-aggregation across experts. These visualizations clearly illustrate why per-expert scaling avoids over-clipping light-tailed experts and prevents wasted quantization levels on the majority of channels.

Figure 8: Confusion matrices at **layer 0-7** comparing FP16 vs. EAQuant top-k indices under W4A4.

Figure 9: Confusion matrices at **layer 8-15** comparing FP16 vs. EAQuant top-k indices under W4A4.

(a) OLMoE   (b) DeepSeek-MoE   (c) Qwen3-MoE

Figure 10: Expert activations in the **2nd layer** for each model.

(a) OLMoE   (b) DeepSeek-MoE   (c) Qwen3-MoE

Figure 11: Expert activations in the **6th layer** for each model.

(a) OLMoE   (b) DeepSeek-MoE   (c) Qwen3-MoE

Figure 12: Expert activations in the **10th layer** for each model.