Counterfactual Neural Temporal Point Process for Misinformation Impact Estimation on Social Media

Abstract

Recent years have witnessed the rise of misinformation campaign which spread specific narratives on social media to manipulate public opinions on different areas, such as politics and healthcare. Consequently, an effective and efficient automatic methodology to estimate the impact of the misinformation on user beliefs and activities is needed. However, existing works on misinformation impact estimation either rely on small-scale psychological experiments or can only discover the correlation between user behaviour and misinformation. To address these issues, in this paper, we build up a causal framework that model the causal effect of misinformation from the perspective of temporal point process. To adapt the large-scale data, we design an efficient yet precise way to estimate the **Individual Treatment Effect** (ITE) via neural temporal point process and gaussian mixture models. Extensive experiments on synthetic dataset and real-world dataset verify the effectiveness and efficiency of our model.

1 Introduction

Recent researches reveals that widespread fake news and misleading information have been exploited by misinformation campaigns to manipulate public opinions in different areas, such as healthcare[23, 25, 12] and politics[13]. To address this crucial challenge, research efforts from different perspectives have been devoted, such as fake news detection and coordination detection[22, 23, 25].

However, an essential associated research question has not been explored sufficiently: how to know a piece of misinformation's causal influence on a user's beliefs and activities on a large-scale social media. Precisely estimating such impact is crucial for delivering the corresponding clarification contents to the users that are most likely to be affected. Nevertheless, most of existing researches in social media analysis focus on understanding correlation between misinformation and user activities, rather than causal effect [25, 12, 28]. As a result, they can not distinguish the effect from personal prior beliefs and engagement with misinformation. Current researches on misinformation's causal influence on people are mainly from psychology field [11, 26]. They are usually based on carefully designed psychological randomised controlled trials on recruited subjects. Thus, it is impossible to extend them onto large-scale social media platforms due to the high cost to recruit enough subjects and ethical risk in conducting such a large-scale psychology experiments.

Since personal beliefs are usually unobservable, researchers usually apply the feature of the tweets generated or retweeted by the users as a proxy [25]. However, the lack of appropriate algorithmic tools to conduct causal analysis on social media posts prevents researchers from understanding causal effect of misinformation. The processes that social media users generate original posts and

engage with existing posts are typical temporal point processes. But existing methodologies for temporal causal effect estimation mostly focus on covariates and outcomes continuously distributed on timeline [4, 3, 2], rather than discrete event points randomly scattered on timeline. Although the essential theory for counterfactual analysis of point process is already established[19], most works are motivated by healthcare and thus focus on the hazard models, e.g. survival analysis [1] or the chance to catch cancer [20], which only consider the single occurrence of the most recent future event. However, on social media, we care more about multiple events happening in a time window. [10] is a rare work studying the causal effect on multiple occurrences in temporal point process. But one of its assumption is that the event marks must be categorized to a finite number of classes, leaving no space for the rich continuous features of social media posts, such as user sentiment and subjectivity scores.

In this work, we propose a framework that models the causal effect of a given piece of information on user beliefs and activities via counterfactual analysis on temporal point process with continuous features. We first define a causal structure model that characterizes the misinformation impact as how the engagement with the misinformation change a user's intensity function of generating original posts. In this model, the engagement with misinformation is considered as the treatment, and the user's future conditional intensity function is considered as the outcome. Then we design a functional that converts the change of two functions to a vector with intuitive physical meaning. To estimate the effect, we design a neural temporal point process model. It disentangles the distribution of event timestamp and post feature (e.g. the text embedding). Then it models the distribution of post features and event timestamp with Gaussian Mixture Model and uni-variate temporal point process respectively. Such design enables it to acquire a closed-form solution of the feature expect without a loss of expressive power, leading to a well balance between precision and inference time complexity.

A critical challenge in training neural networks to recognize causal effect is the hidden bias in the dataset. In social media data, the most crucial bias is from information cocoons [32]: users tend more to engage with the contents that they are interested in, and thus personalized recommendation systems will deliver user more contents that they are interested in to increase user engagement. Such bias leads to a data distribution different from randomised controlled trials and thus make neural networks give biased estimation. To decorrelate time-varying treatment from user's covariates and history in point process, we apply adversarial training to optimize a min-max game. More specifically, the encoder tries to minimize the likelihood of the observed treatments while a treatment predictor tries to maximize it. Our theoretic analysis proves that any balanced solution of the min-max game, rather than the global optimal solution in existing works [4], can help us remove the bias from information cocoons. The extensive experiments on synthetic dataset and real-world datasets also indicate that our framework is able to acquire unbiased and identifiable estimation to the causal effect.

In conclusion, the main contributions of the proposed model are as follows:

- We propose a novel research problem on misinformation impact, which aims to find the causal effect of misinformation on users' belief and activities on social media.

- We propose a causal structure model to quantify the causal effect of misinformation and further design a neural temporal process model to conduct unbiased estimation to the effect.

- We evaluate our model on synthetic datasets to examine its effectiveness and efficiency and ues it to recognize identifiable causal effect of misinformation from real-world data.

2 Related Work

2.1 Influence of Misinformation

Recent researches about misinformation mainly focus on detecting fake news[22, 17, 21], misinformation campaign detection [24, 31] and understanding how fake news attract user engagement[7]. Some researcher attempts to study the relation between misinformation and people's behaviours [11, 26, 25, 12]. However, most of them focus on mining the correlation between misinformation and people behaviours rather than causal effects. Only a limited amount of works, such as [26] try to

understand the causal effect. However, they are usually from psychology field, and mainly rely on carefully designed randomised controlled trials. Extending such trials on large-scale social media platforms brings not only high cost but also potential ethical risk.

2.2 Temporal Point Process

The process that a user retweet or posts tweets can usually be modeled as a temporal point process with event feature [24]. A temporal point process (TPP) with event feature is a stochastic process whose realization is a sequence of discrete events in a continuous timeline: $S = [(\boldsymbol{f}_1, t_1), (\boldsymbol{f}_2, t_2), ...]$, where $\boldsymbol{f}^1$ is the event feature (a scalar or a vector) and t is the timestamp of the event. A TPP is fully characterized by an intensity function $\lambda(\boldsymbol{f}, t|S_h)$ defined in the following integral equation:

$$\mathbb{E}(N(\boldsymbol{F}, T_1, T_2)|S_h) = \int_{\boldsymbol{F}} d\boldsymbol{f} \int_{T_1}^{T_2} \lambda(\boldsymbol{f}, t|S_h) dt \tag{1}$$

where $\boldsymbol{F}$ is an area in the feature space, S_h is the historical sequence of all events happening before time T_1, $N(\boldsymbol{F}, T_1, T_2)$ is the number of events whose feature vectors are in $\boldsymbol{F}$ and timestamps are in the range $[T_1, T_2]$. The meaning of $\lambda(\boldsymbol{f}, t|S_h)$ is the expected instantaneous speed that the user generate posts at point $\boldsymbol{f}$ in the feature space on time t. The process after time t_i is fully described by $\lambda(\cdot, \cdot|S_h)$ [6]. Recent works propose to apply neural networks to model the λ function [8, 15, 30, 33, 16, 6].

2.3 Counterfactual Analysis on Temporal Point Process and Continuous Time Series

A previous work[10] proposes a counterfactual analysis framework to understand the causal influence of event pairs in temporal point process. It defines the individual treatment effect (ITE) of an event toward future process as:

$$ITE = \mu_y^1(t, t+T) - \mu_y^0(t, t+T) = \frac{1}{T} \int_t^{t+T} \lambda_y^1(t) - \lambda_y^0(t) dt \tag{2}$$

where μ_y is the expect of the event number of type y per unit time in time range $[t, t+T]$. μ_y^1 indicate the case that a treatment is applied (exposed to misinformation) and μ_y^0 is in contrary. However, this metric is only suitable in the case that the events can be categorized to finite discrete types. This is not applicable for social media post because most meaningful features of the posts, such as geographical information, sentiment score and subjective score, are naturally continuous. Forcibly discretizing them will lose meaningful information. Besides, for counterfactual analysis of time series, [4] proposes CRN, a neural model that can learn unbiased estimation to counterfactual world and causal effect. [3] proposes to analyze counterfactual estimation using synthetic controls via a novel neural controlled differential equation model. [2] introduces a new causal prior graph to avoid the undesirable explanations that include confounding or noise and use a multivariate Gaussian distribution to model the real continuous values. However, all of them focus on modeling an observable variable existing on a continuous timeline instead of temporal point process. Unless getting heavily revised, such previous work can not be simply transferred to our problem scenario.

3 Proposed Causal Structure Model and Treatment Effect

3.1 Causal Structure Model

In this study, we focus on understanding how a user's engagement with the misinformation post causally influence the characters of the posts generated by the user in a fixed future time window. We formulate the process that a user interact the post shared by others and generate social media posts as two temporal point process where each event carries a continuous outcome vector. We denote the process of engaging the diffusion of a post as P_e and the process generating new posts as P_g. Then

---

[1]We use bold font to emphasize that $\boldsymbol{f}$ is a feature vector rather than a function.

121 the realization of the two temporal point process are respectively two sequences S_e and S_g of discrete
122 events with continuous outcome vector in a continuous time range:

$$S_e = [(\boldsymbol{f}_1^{(e)}, t_1^{(e)}), (\boldsymbol{f}_2^{(e)}, t_2^{(e)}), ...], \quad S_g = [(\boldsymbol{f}_1^{(g)}, t_1^{(g)}), (\boldsymbol{f}_2^{(g)}, t_2^{(g)}), ...] \tag{3}$$

123 where $\boldsymbol{f}$ is the feature vector characterizing
124 the event and t is the time stamp. For S_{in},
125 each event correspond to an interaction (e.g.
126 "like" or comment), and the vector $\boldsymbol{f}^{(e)}$ is the
127 feature of the content (like the text represen-
128 tation, sentiment score and metadata) from
129 others. Similarly, for S_g, the vector $\boldsymbol{f}^{(g)}$ is the
130 feature of the content generated by the user.
131 To examine the causal effect of an interaction
132 event on the posts generated by the user in
133 the future, we construct the following causal

Figure 1: The proposed causal structured model de-
scribing the impact of a piece of information on user.

134 structure model, formulated as $< X, Y, Tr >$, where X is the covariate, Y is the outcome and
135 Tr is the treatment. In this model, given an interaction event $(\boldsymbol{f}_i^{(e)}, t_i^{(e)})$ whose causal effect is
136 to be examined, we consider the this event as the treatment Tr, and all the events, including both
137 engagement events and posting events, that happen before $t_i^{(e)}$ are considered as the covariates. As
138 for the outcome, rather than simply considering the most next generation event after $t_i^{(e)}$, we need
139 a representation that can reflect the change of the whole generating process S_g in a fixed future
140 time window T. Thus we apply the conditional intensity function of the future process, denoted
141 as $\lambda(\boldsymbol{f}, t | Tr \cup X)$, as outcome. As discussed in the related work section, λ function completely
142 describe the future process. The overview of the model is presented in Figure. 1.

143 **3.2 Treatment Effect Evaluation**

144 In traditional counterfactual analysis works, the outcome is usually a scalar or a vector with finite
145 dimensions. Thus, the treatment effect can be trivially computed by comparing the difference of the
146 outcomes from real world and counterfactual world. However, in our framework, it is non-trivial to
147 compute the difference of two functions. To overcome this challenge, we propose to first apply a
148 functional $\mathcal{F}$ to project the λ function to a vector with finite dimensions:

$$\mathcal{F}_T(\lambda, Tr \cup X) = \frac{\phi(t, t+T, \lambda, Tr \cup X)}{\mu(t, t+T, \lambda, Tr \cup X)} \tag{4}$$

149
$$\phi(t, t+T, \lambda, Tr \cup X) = \mathbb{E}_{S \sim P(S|\lambda, Tr \cup X)}[\sum_{(\boldsymbol{f}_i, t_i) \in S_{t:t+T}} \boldsymbol{f}_i] \tag{5}$$

150
$$\mu(t, t+T, \lambda, Tr \cup X) = \mathbb{E}_{S \sim P(S|\lambda, Tr \cup X)}|S_{t:t+T}| = \mathbb{E}(N(\sup(\boldsymbol{f}), t, t+T)|Tr \cup X) \tag{6}$$

151 where $P(S|\lambda, Tr \cup X)$ is the distribution of the event sequence S sampled from the temporal point
152 process described by $\lambda(\cdot, \cdot | Tr \cup X)$, T is the time window that is a hyper-parameter, $\sup(\boldsymbol{f})$ is the
153 support set of $\boldsymbol{f}$ (the area where the probability density is larger than 0), and $S_{t:t+T}$ is a sub-sequence
154 of S. $S_{t:t+T}$ contains every event in S that happens at a time between t and $t+T$. The intuitive
155 meaning of $\mathcal{F}$ is the expected mean feature vector of all posts generated by a user. Thus, by comparing
156 the outputs of $\mathcal{F}$ in real world and counterfactual world, we can see how the engagement with a
157 specific post change the average features, e.g. general sentiment scores or text embedding. With this
158 functional, we can simply compute the individual treatment effect as:

$$ITE = \mathcal{F}_T(\lambda, Tr \cup X) - \mathcal{F}_T(\lambda, \emptyset \cup X) \tag{7}$$

159 where $\emptyset$ is an empty set, $\mathcal{F}_T(\lambda, \emptyset \cup X)$ is the functional from counterfactual world in which we assume
160 that the treatment is not applied (e.g. the misinformation post is not recommended or labeled as
161 misinformation). For brief, we write $\mathcal{F}_T(\lambda, \emptyset \cup X)$ as $\mathcal{F}_T(\lambda, X)$ The overall impact of the treatment
162 can be represented with the average treatment effect:

$$ATE = \mathbb{E}_{(X, Tr) \sim U}[\mathcal{F}_T(\lambda, Tr \cup X) - \mathcal{F}_T(\lambda, X)] \tag{8}$$

163 where U is the set of users who engaged with the treatment post.

3.3 Treatment Effect Calculation

In the above sections, we define the causal structure model and the treatment effect. However, the above formulas are hard to compute. Therefore, in this subsection, we will derive a computable formulation of the treatment effect. We will start from the following theorem:

Theorem 1. *For a user u, if the intensity function $\lambda(\boldsymbol{f}, t | Tr \cup X)$ is known, then we have:*

$$\mu(t, t+T, \lambda_1, Tr \cup X) = \int_{sup(\boldsymbol{f})} d\boldsymbol{f} \int_{t}^{t+T} \lambda(\boldsymbol{f}, t | Tr \cup X) dt \tag{9}$$

$$\phi(t, t+T, \lambda_1, Tr \cup X) = \int_{sup(\boldsymbol{f})} \boldsymbol{f} d\boldsymbol{f} \int_{t}^{t+T} \lambda(\boldsymbol{f}, t | Tr \cup X) dt \tag{10}$$

The first equation can be trivially proved by replacing the $\boldsymbol{F}$ in Equation 1 with the support set. The second one can be proved with the Campbell's Theorem [5]. A detailed proof is provided in the appendix. The above formulas contain double integral, which is inefficient to compute. To transform the double integral to a single integral, based on a previous work in spatial-temporal point process [6], we have:

$$\lambda(\boldsymbol{f}, t | Tr \cup X) = \lambda(t | Tr \cup X) p(\boldsymbol{f} | t, Tr \cup X) \tag{11}$$

Thus, we can disentangle $\lambda(\boldsymbol{f}, t)$ and respectively model $\lambda(t_i)$ and $p(\boldsymbol{f} | t)$. More importantly, we can simply model μ as:

$$\mu(t, t+T, \lambda, Tr \cup X) = \int_{t}^{t+T} \lambda(t | Tr \cup X) dt \int_{sup(\boldsymbol{f})} p(\boldsymbol{f} | t, Tr \cup X) d\boldsymbol{f} = \int_{t}^{t+T} \lambda(t | Tr \cup X) dt \tag{12}$$

And with this formula, we have:

$$
\begin{aligned}
\phi(t, t+T, \lambda, Tr \cup X) &= \int_{sup(\boldsymbol{f})} \int_{t}^{t+T} \boldsymbol{f} \lambda(t | Tr \cup X) p(\boldsymbol{f} | t, Tr \cup X) d\boldsymbol{f} dt \\
&= \int_{t}^{t+T} \lambda(t | Tr \cup X) dt \int_{sup(\boldsymbol{f})} \boldsymbol{f} p(\boldsymbol{f} | t, Tr \cup X) d\boldsymbol{f} \\
&= \int_{t}^{t+T} \lambda(t | Tr \cup X) \mathbb{E}[\boldsymbol{f} | t, Tr \cup X] dt
\end{aligned}
\tag{13}
$$

The above formulas contain only single integrals. Thus, they can be efficiently approximated with summation: $\int_{x_1}^{x_2} f(x) dx \approx \sum_{i=0}^{(x_2 - x_1)/\Delta x} f(x_1 + i\Delta x)\Delta x$

4 Neural Estimation of Treatment Effects

The above section construct a causal framework that can measure the impact of a given social media post based on the change of $\lambda(t | Tr \cup X)$ and $p(\boldsymbol{f} | t, Tr \cup X)$. In this section, as shown in Figure 2 we will further discuss how to estimate the impact with a neural temporal point process model.

4.1 Learning Conditional Intensity Function via Maximum Likelihood Estimation

The log-likelihood of an observed event (f, t) (no matter an engagement event or an generation event) can be written as:

$$\log p(\boldsymbol{f}, t | Tr \cup X) = \log \lambda(t | Tr \cup X) - \int_{t_n}^{t} \lambda(t | Tr \cup X) dt + \log p(\boldsymbol{f} | t, Tr \cup X) \tag{14}$$

where t_n is the timestamp of the last event in the set $Tr \cup X$. The above equation provides us with a way to learn $\lambda(t | Tr \cup X)$ and $p(\boldsymbol{f} | t, Tr \cup X)$ by maximizing the likelihood of each event given the historical information (treatment and covariates). To enable the model to make correct prediction for both $\lambda(\boldsymbol{f}, t | Tr \cup X)$ and $\lambda(\boldsymbol{f}, t | X)$, we construct two kinds of samples to train the functions:

Samples with valid Treatment: If for a generating event $(\boldsymbol{f}^{(g)}, t^{(g)})$, its most recent previous event is an engagement event $(\boldsymbol{f}^{(e)}, t^{(e)})$ (in other words, the user does not have other activity between the engagement event and the generating event), then we can construct a sample $(Y, Tr \cup X)$, where $Y = (\boldsymbol{f}^{(g)}, t^{(g)})$, $Tr = (\boldsymbol{f}^{(e)}, t^{(e)})$, and X is a sequence that contains all engagement events and generation events before Tr.

Samples without Treatment: If for a generating event $(\boldsymbol{f}^{(g)}, t^{(g)})$, its most recent previous event is still a generating event (in other words, the user generate two original posts without engaging with other posts), then we can construct a sample (Y, X), where $Y = (\boldsymbol{f}^{(g)}, t^{(g)})$ and X is a sequence that contains

Figure 2: The proposed neural model to estimate the impact of misinformation.

all engagement events and generation events before Y. In this sample, between the last generation event in X and Y, there is no interruption from treatment. Thus, it helps the model to learn $\lambda(t|X)$ and $p(\boldsymbol{f}|t, X)$

For a sample $(Y, Tr \cup X)$ or (Y, X), we first use a shared encoder $H(\cdot)$ to project $(Tr \cup X)$ (or X) to a representation vector $h = H(Tr \cup X)$ (or $h = H(X)$ for the case where treatment is NULL). Then we model the intensity function and feature distribution as $\lambda(t|h)$ and $p(\boldsymbol{f}|t, h)$. For $\lambda(t|h)$, following FullyNN, we use a multi-layer perceptron $MLP(h, t)$ to model its integral $\int_{t_n}^{t} \lambda(t|h) dt$. The MLP's partial derivative with respect to t is $\lambda(t|h)$.

To model $p(\boldsymbol{f}|t, h)$, a straightforward solution borrowed from generative deep learning is to apply a neural network, i.e. the decoder, to transform a simple distribution, e.g. a Gaussian distribution whose parameters are decided based on h and t, to a complicated distribution. The decoder can be trained via different loss function, like reconstruction error (variational auto encoder) and likelihood (normalizing flow)[2] [27, 6]. However, this method has an important drawback: its conditional expect $\mathbb{E}[\boldsymbol{f}|t, h]$ does not have a closed-form solution. To compute the expect, we can only apply sampling or approximation, e.g. forwarding the expect of the simple distribution into the decoder[3]. To address the above challenge, we propose to explicitly model $p(\boldsymbol{f}|t, h)$ with a mixture of Gaussian distributions:

$$p(\boldsymbol{f}|t, h) = \sum_{j=1}^{m} w_j(t, h) g(\frac{\boldsymbol{f}_i - \boldsymbol{u}_j(t, h)}{\sigma_j(t, h)}) \tag{15}$$

$$w(t, h) = \text{softmax}(MLP_w(h, t)), \sigma(t, h) = \exp(MLP_\sigma(h, t)), \boldsymbol{\mu}_j(t, h) = MLP_{\boldsymbol{\mu}}^{(j)}(h, t) \tag{16}$$

where w_j is the mixture weight, σ_j is a scalar, $\boldsymbol{u}_j$ is a vector with the same dimension as $\boldsymbol{f}$, and $g(\cdot)$ is a standard multivariate gaussian distribution $\mathcal{N}(\boldsymbol{0}, \boldsymbol{I})$ whose covariant matrix is an identical matrix. Although the formula of each component is simple, their mixture has a theoretical guarantee on universal approximation to all distributions [29]. Because the expect of a mixture distribution is the mixture of the expects, we have a closed-form solution for $\mathbb{E}[\boldsymbol{f}|t, h]$:

$$\mathbb{E}_{\boldsymbol{f} \sim p(\boldsymbol{f}|t, h)}[\boldsymbol{f}|t, h] = \sum_{j=1}^{m} w_j(t, h) \boldsymbol{u}_j(t, h) \tag{17}$$

4.2 Adversarial Balanced Neural Temporal Point Process

As discussed in the related work section, by maximizing the likelihood of the posts generated by the users, we can train a neural network that predict $\lambda(t|Tr \cup X)$ and $p(\boldsymbol{f}|t, Tr \cup X)$. However,

---

[2]GAN is not suitable because for fixed h and t we only have one sample, which can be easily memorized.
[3]Because the decoder D is a non-linear function, $\mathbb{E}[D(x)]$ is usually different from $D(\mathbb{E}[x])$

previous works have proved that if we do not balance the bias from the correlation between treatment and covariates, the model will tend to give biased prediction and thus can not give precise estimation of the treatment effect. A crucial bias in social media data is information cocoon: personalized recommendation systems will deliver user the contents that they are interested in. For example, it will deliver more anti-vaccine posts to anti-vaccine users because they are more likely to be interested in those contents. As a result, the anti-vaccine users will engage more with anti-vaccine posts.

To address the above issue, following previous works in neural counterfactual prediction, we apply domain adversarial training to learn a representation h that is invariant to such a bias[4]. More specifically, we hope to learn a encoder H such that for any two users with different history X_1 and X_2, $p(Tr|H(X_1)) = p(Tr|H(X_2))$ for the same Tr. In other words, in the representation space, the probability that the two users interact with the same post at the same time should be same, which is the same as psychology experiments that divide the experimental and controlled groups randomly. To achieve this object, we apply adversarial training to remove the information about future treatment from the representation of covariates. More specifically, we additionally train a treatment predictor $\hat{p}(Tr|H(X))$ by modeling $\lambda_{tr}(t^{(e)}|h)$ and $p_{tr}(\boldsymbol{f}^{(e)}|t, h)$ with the encoding h of the historical covariates X. However, between the treatment predictor and the encoder, we insert a **gradient reversal layer (GRL)**[9, 18, 4] to reverse the sign of the gradient. Thus, when we optimize the treatment predictor to maximize the likelihood of the observed treatment $Tr = (\boldsymbol{f}^{(e)}, t^{(e)})$, the GRL will make the encoder to minimize the likelihood. This process leads to the following min-max game:

$$\min_H \max_{\hat{p}} \mathbb{E}_{Tr, X \sim p(Tr, X)} \log \hat{p}(Tr|H(X)) \tag{18}$$

The following theorem provide theoretic guarantee that the above adversarial training reduce the bias introduced by treatment-covariate correlation (e.g. recommendation system and personal interest):

Theorem 2. *Given the following min-max game:*

$$min_H max_{\hat{p}} \mathbb{E}_{Tr, X \sim p(Tr, X)} \log \hat{p}(Tr|H(X)) \tag{19}$$

the min gamer's Nash balanced solution H^*, ensures for any X_1, X_2, the following equation holds:

$$p(Tr|H^*(X_1)) = p(Tr|H^*(X_2)) \tag{20}$$

where p denote the ground-truth conditional distribution of treatment given encoding.

5 Experiments

On real-world social media platforms, the ground truth causal effects of user engagement with posts, no matter misinformation post or information post, are unknown. To address the unknown ground truth causal effect, previous works of causality analysis evaluate their models on synthetic dataset. In this paper, following previous works, we evaluate the performance of our model and compare it with baselines on synthetic dataset. Then we apply our proposed method to evaluate the impact misinformation on a real-world social media data about COVID-19 vaccine collected from Twitter.

5.1 Experiments on Synthetic Data

Synthetic Data Generation: To simulate the real-world social media, we generate 15000 users and 120 post of news. Each user i is represented with a hidden vector u_i, which correspond to the status of a social media user. Each piece news n has two randomly generated feature vectors: a topic vector $v_{topic}(n)$ and an inherent influence vector $v_{in}(n)$. Each user has two kinds of activities: (1) engaging with one of the 120 news post and (2) posting a post with original contents. The chance that a user engage with a post is decided by $v_{in}(n)$ and u_i, simulating **information cocoons**. Engagement event with news post n will change the hidden status u of the user. The scale and direction of the change are decided by the current user status, the topic vector and the inherent influence vector jointly. For each user, the engagement events and the posting events are modeled through two Hawkes process respectively. Both Hawkes processes are influenced by user status u. Also, the feature of each posting event $\boldsymbol{f}$ is drawn from a distribution $P(\boldsymbol{f}|u, t)$ characterized by a random parameterized multi-layer

Method	Accuracy ↑	RAE ↓	RRSE ↓	Inference Time
FullyNN (CNTPP w/o Adversarial Balance)	73.0%	0.865	0.901	7.23ms
CRN-VAE (Approximation)	85.9%	0.279	0.503	**4.05ms**
CRN-VAE (Sampling)	87.8%	0.237	0.454	29.34ms
CNTPP(Ours)	**88.0%**	**0.234**	**0.448**	7.12ms

Table 1: Estimation Error to the ground-truth ITE

277 perceptron (MLP) taking (u, t) and random noises as input and output $\boldsymbol{f}$. Thus, the engagement with
278 the news post will have causal effects on the two processes. Since we have all parameters of the
279 model, we can calculate the ground-truth ITE defined in Eq. 7 for the synthetic dataset. The details
280 of the data generation algorithm is included in the Appendix.

281 **Baselines:** To the best of our knowledge, the causality effect on temporal user behaviour from
282 misinformation is not explored by previous works. Thus, we lack well-established baselines for this
283 specific task. To address this issue, we select some baselines from previous works on temporal point
284 process and temporal causal inference. We extend them to adapt our setting. The baselines include
285 two kinds:

286 **Non-causal neural temporal point process** that predict the user future behaviours without consid-
287 ering causal effect. We select **FullyNN** [16] as representative of this kind as it has the same neural
288 architecture as our model. It can also be regarded as our model's variant **w/o adversarial balancing**.

289 **Causal neural temporal point process** that aims at discovering causal effect of event pairs in
290 temporal point process. This kind includes **CIP** [10] and **CRN-VAE** [4] (we heavily revise the
291 original model CRN from the paper so that it can adapt our setting). CRN-VAE can also be regarded
292 as ablation variants of our work that uses VAE to model $p(\boldsymbol{f}|t, h)$. Since VAE does not have a closed
293 form solution of feature expect, we report the results applying sampling and approximation separately.

294 In this work, we will evaluate the proposed model in two aspects:

295 **ITE Estimation**: we will evaluate the
296 model by comparing ITE estimated by the
297 model and the ground-truth ITE. We report
298 three metrics: accuracy (the model need
299 to correctly predict whether the engage-
300 ment increase or decrease each dimension
301 of the expected average feature), Relative
302 Absolute Error (RAE) and Relative Root
303 Square Error (RRSE). In addition, we also
304 report the inference time of our model to
305 reflect our model's efficiency.

Method	MatDis↓	LinCor↑
CIP	0.90	0.04
FullyNN	0.93	0.236
CRN-VAE (Approximation)	0.84	0.303
CRN-VAE (Sampling)	**0.76**	0.287
Ours	0.77	**0.310**

Table 2: Causal Effect Inference

306 As shown in Table 1, our model establishes new state-of-the-art on all three quantitative metrics. This
307 means that our model can fully utilize the causal information from the multivariates point process for
308 unbiased treatment effect estimation. In particular, the model with causal analysis outperforms the
309 model with direct neural network prediction (FullyNN), which leads to results that are not causally
310 related. Simultaneously, our model outperforms all baselines in all three metrics of estimation
311 precision. Although CRN-VAE incorporated with sampling method can achieve a performance very
312 close to us, it spends substantially longer inference time.

313 **Causal Effect Inference**: CIP defines the treatment effect in a way different from our model. Thus
314 ITE estimation experiment is not fair for it. For a fair comparison, and also to further prove that our
315 model can achieve unbiased estimation, we use all the models to predict the ATE of each news post.
316 Then we evaluate the correlation between the learnt ATEs and ground-truth average change of the
317 news post to all users' hidden statuses. The more correlated the learnt ATE is, the better it reflect the
318 inherent causal effect of the engagement on users. To evaluate the correlation, we apply the following
319 two metrics: **MatDis** and **LinCor**. Their detailed explanation is included in the Appendix.

From Table 2, the ATE of our model best reflect the ground-truth average change of the news post on the simulated data for both two evaluation metrics. This suggests that our model has the potential to discover the influence of misinformation on social media users' hidden status, e.g. interest and idea.

5.2 Experiments on Real World Data

In this section, we apply our proposed model on the Twitter dataset to estimate misinformation impact on social media scenario. We apply the data set collected in [31, 25], including a total of 16,9008 tweets from 24,192 users over a 5-month period from 2020/12/09 to 2021/04/24. Notably, we focus on understand how the tweets that users retweeted influence their behavior of posting original tweets. For each post, its feature f includes: text representation (extracted with a pre-trained BERT), sentiment score and subjectivity score. We discover the following two phenomenons with our model.

(a) Impact on sentiments and subjectivity.

(b) Impact on text representation.

Figure 3: Analysis on real world social media data

Identifiability between misinformation and information in influencing people's narratives: For the desired outcome, we analyze the distinguishability between "retweeting fake news" and "retweeting true news" events. More specifically, for each retweeting event, we use its ITE estimated with our model as feature (dimension reduced via PCA [14]) and whether the content is information or misinformation as label. As shown on Figure 3(b), we can verify the identifiability of our proposed method as the treatment effect of two types of the news are substantially different. This discovery not only supports that misinformation and information influence people's behaviour in different ways, but also provides us with a new paradigm to detect fake news.

Misinformation is hurting people's subjective emotion related to COVID vaccine: To understand the influence of misinformation in a more intuitive way, we analyze the impact of retweeting events on users' average sentiment score and subjectivity score in the future. The higher subjectivity the content gets, the more personal opinions rather than factual information text contains. Then, we use the proposed model to generate the estimated ITE for each retweeting event and plot the results of fake news and real news. As shown on Figure 3(a) (x-axis for sentiment score and y-axis for subjectivity score), we find that both information and misinformation do not substantially influence the users' subjectivity. However, information tends to make people optimistic about vaccines (true news increases the sentiment score), while fake news tends to make people feel negative about vaccines. This discovery strongly supports the hypothesis that misinformation is hurting people's subjective emotion toward COVID-19 vaccines, and suggests that misinformation could be causally responsible for vaccine hesitancy.

6 Conclusion

In this paper, we propose a framework to describe the causal structure model and causal effect about how misinformation influence online user behaviours. We further design a neural temporal point process model to conduct unbiased estimation on the causal effect in a data-driven approach. Experiments on synthetic dataset verify the effectiveness and efficiency of our model. We further apply our model on real-world dataset from Twitter and recognize identifiable causal effect of misinformation. However, it is also noticeable that our model is a statistical machine learning model. Consequently, all of its estimation can only be regarded as a reference rather than judgement.

References

[1] Odd O Aalen, Mats J Stensrud, Vanessa Didelez, Rhian Daniel, Kjetil Røysland, and Susanne Strohmaier. Time-dependent mediators in survival analysis: Modeling direct and indirect effects with the additive hazards model. *Biometrical Journal*, 62(3):532–549, 2020.

[2] Mohammad Taha Bahadori and David Heckerman. Debiasing concept-based explanations with causal analysis. In *International Conference on Learning Representations*, 2021.

[3] Alexis Bellot and Mihaela van der Schaar. Policy analysis using synthetic controls in continuous-time. In *ICML*, 2021.

[4] Ioana Bica, Ahmed M Alaa, James Jordon, and Mihaela van der Schaar. Estimating counter-factual treatment outcomes over time through adversarially balanced representations. *arXiv preprint arXiv:2002.04083*, 2020.

[5] N. Campbell. The study of discontinuous phenomena. *Proc Cambr. Phil. Soc*, vol. 15:pp. 117–136, 1909.

[6] Ricky TQ Chen, Brandon Amos, and Maximilian Nickel. Neural spatio-temporal point processes. *arXiv preprint arXiv:2011.04583*, 2020.

[7] Lu Cheng, Ruocheng Guo, Kai Shu, and Huan Liu. Causal understanding of fake news dissemination on social media. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*, pages 148–157, 2021.

[8] Nan Du, Hanjun Dai, Rakshit Trivedi, Utkarsh Upadhyay, Manuel Gomez-Rodriguez, and Le Song. Recurrent marked temporal point processes: Embedding event history to vector. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 1555–1564, 2016.

[9] Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *International conference on machine learning*, pages 1180–1189. PMLR, 2015.

[10] Tian Gao, Dharmashankar Subramanian, Debarun Bhattacharjya, Xiao Shou, Nicholas Mattei, and Kristin Bennett. Causal inference for event pairs in multivariate point processes. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

[11] Daniel Jolley and Karen M Douglas. The effects of anti-vaccine conspiracy theories on vaccination intentions. *PloS one*, 9(2):e89177, 2014.

[12] Katherine Kricorian, Rachel Civen, and Ozlem Equils. Covid-19 vaccine hesitancy: Misinformation and perceptions of vaccine safety. *Human Vaccines & Immunotherapeutics*, 18(1):1950504, 2022.

[13] Luca Luceri, Silvia Giordano, and Emilio Ferrara. Detecting troll behavior via inverse reinforcement learning: A case study of russian trolls in the 2016 us election. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 14, pages 417–427, 2020.

[14] Aleix M Martinez and Avinash C Kak. Pca versus lda. *IEEE transactions on pattern analysis and machine intelligence*, 23(2):228–233, 2001.

[15] Hongyuan Mei and Jason M Eisner. The neural hawkes process: A neurally self-modulating multivariate point process. In *Advances in Neural Information Processing Systems*, pages 6754–6764, 2017.

[16] Takahiro Omi, Kazuyuki Aihara, et al. Fully neural network based model for general temporal point processes. *Advances in neural information processing systems*, 32, 2019.

[17] Verónica Pérez-Rosas, Bennett Kleinberg, Alexandra Lefevre, and Rada Mihalcea. Automatic detection of fake news. In *Proceedings of the 27th International Conference on Computational Linguistics*, pages 3391–3401, Santa Fe, New Mexico, USA, August 2018. Association for Computational Linguistics.

[18] Edward Raff and Jared Sylvester. Gradient reversal against discrimination. *arXiv preprint arXiv:1807.00392*, 2018.

[19] Kjetil Røysland. Counterfactual analyses with graphical models based on local independence. *The Annals of Statistics*, 40(4):2162–2194, 2012.

[20] Pål Christie Ryalen, Mats Julius Stensrud, Sophie Fosså, and Kjetil Røysland. Causal inference in continuous time: an example on prostate cancer therapy. *Biostatistics*, 21(1):172–185, 2020.

[21] Fatima K Abu Salem, Roaa Al Feel, Shady Elbassuoni, Mohamad Jaber, and May Farah. Fa-kes: a fake news dataset around the syrian war. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 13, pages 573–582, 2019.

[22] Karishma Sharma, Feng Qian, He Jiang, Natali Ruchansky, Ming Zhang, and Yan Liu. Combating fake news: A survey on identification and mitigation techniques. *ACM Transcations on Intelligent Systems and TEchnology*, 2019.

[23] Karishma Sharma, Sungyong Seo, Chuizheng Meng, Sirisha Rambhatla, Aastha Dua, and Yan Liu. Coronavirus on social media: Analyzing misinformation in twitter conversations. *arXiv preprint arXiv:2003.12309*, 2020.

[24] Karishma Sharma, Yizhou Zhang, Emilio Ferrara, and Yan Liu. Identifying coordinated accounts on social media through hidden influence and group behaviours. *arXiv preprint arXiv:2008.11308*, 2020.

[25] Karishma Sharma, Yizhou Zhang, and Yan Liu. Covid-19 vaccines: characterizing misinformation campaigns and vaccine hesitancy on twitter. *arXiv preprint arXiv:2106.08423*, 2021.

[26] Sander Van der Linden. The conspiracy-effect: Exposure to conspiracy theories (about global warming) decreases pro-social behavior and science acceptance. *Personality and Individual Differences*, 87:171–173, 2015.

[27] Qi Wang, Guangyin Jin, Xia Zhao, Yanghe Feng, and Jincai Huang. Csan: A neural network benchmark model for crime forecasting in spatio-temporal scale. *Knowledge-Based Systems*, 189:105120, 2020.

[28] Steven Lloyd Wilson and Charles Wiysonge. Social media and vaccine hesitancy. *BMJ Global Health*, 5(10):e004206, 2020.

[29] Assaf J. Zeevi and Ronny Meir. Density estimation through convex combinations of densities: Approximation and estimation bounds. *Neural Networks*, 10(1):99–109, 1997.

[30] Qiang Zhang, Aldo Lipani, Omer Kirnap, and Emine Yilmaz. Self-attentive hawkes process. *ICML*, 2020.

[31] Yizhou Zhang, Karishma Sharma, and Yan Liu. Vigdet: Knowledge informed neural temporal point process for coordination detection on social media. *Advances in Neural Information Processing Systems*, 34, 2021.

[32] Frederik Zuiderveen Borgesius, Damian Trilling, Judith Möller, Balázs Bodó, Claes H De Vreese, and Natali Helberger. Should we worry about filter bubbles? *Internet Policy Review. Journal on Internet Regulation*, 5(1), 2016.

[33] Simiao Zuo, Haoming Jiang, Zichong Li, Tuo Zhao, and Hongyuan Zha. Transformer hawkes process. *NeurIPS*, 2020.