Is There a One-Model-Fits-All Approach to Information Extraction? Revisiting Task Definition Biases

Abstract

Definition bias is a negative phenomenon that can mislead models. However, definition bias in information extraction appears not only across datasets from different domains but also within datasets sharing the same domain. We identify two types of definition bias in IE: bias among information extraction datasets and bias between information extraction datasets and instruction tuning datasets. To systematically investigate definition bias, we conduct three probing experiments to quantitatively analyze it and discover the limitations of unified information extraction and large language models in solving definition bias. To mitigate definition bias in information extraction, we propose a multi-stage framework consisting of definition bias measurement, bias-aware fine-tuning, and task-specific bias mitigation. Experimental results demonstrate the effectiveness of our framework in addressing definition bias.

Figure 1: Definition bias among different datasets and LLMs even when they share the same entity type (for NER) or the same relation type (for RE)

1 Introduction

Bias in machine learning refers to systematic errors in predictions in the machine learning process, which consist of annotator bias, measurement bias, etc (Hellström et al., 2020). In the era of large language models (LLMs), this issues are addressed by filtering low-quality corpora (Kojima et al., 2022) and training with human preferences (Ouyang et al., 2022). However, the performance remains subpar in handling information extraction (IE) tasks (Wadhwa et al., 2023), which we believe is due to definition bias.

Definition bias in IE refers to the tendency of an information extraction system to favor certain interpretations of data over others, often due to the way concepts, entities, or relationships are defined within the system. As the fast development of Unified Information Extraction (UIE) and Large Language Models (LLMs) in recent years, two novel definition bias emerge, which are: *Bias among IE datasets* and *Bias between IE and instruction*

tuning (IFT) datasets. Regarding *Bias among IE datasets*, it refers to the definition differences between different data sets under the same annotation schema. As illustrated in Figure 1, different datasets have different annotation to the same input for both Named Entity Recognition (NER) and Relation Extraction (RE) tasks. Regarding *Bias between IE and instruction tuning datasets*, it highlights the mismatch between information extraction task and general task. As depicted in Figure 1, although GPT-4 (OpenAI, 2023) is capable of extracting entities or relational triples in accordance with the specified task description without providing extra examples, its prediction differ from those in the existing datasets.

To systematically investigate definition bias in IE, we devise a series of probing experiments. First, we analyze *whether definition bias exists and how it varies among datasets sharing the same tasks*. By conducting cross-validation experiment among

Figure 2: Three settings for the probing tasks on definition bias across datasets, including (a) fully supervised, (b) source prompt and (c) LLMs zero/few-shot.

various dataset in the NER and RE, we observe a significant decrease in performance, indicating that definition bias negatively impacts the transferability of a fully-supervised model. An intuitive way to alleviate definition bias is unified information extraction, which is trained across multiple IE dataset. Hence, we analyze *in the unified information extraction mode, does definition bias still exist?* By introducing source prompt that apply true or fake source name for the UIE models, we discover the inconsistency of the UIE for extraction, which indicates that UIE suffer from definition bias among IE dataset. The other way to mitigate definition bias is LLM, which is able to understand a wide range of human instructions. Thereupon, we analyze *Can LLMs address the challenge of definition bias?* By conducting experiments on few-shot settings on NER and RE task with in-context learning, we find that it's difficult for LLMs without parameter updates to attain satisfactory performance, which indicates that LLMs still suffer from definition bias between IE and instruction fine-tuning datasets.

According to our probing experiments, it is im-perative to address definition bias when propos-ing a universal solution for IE tasks. However, mitigating definition bias is non-trivial, primarily owing to the following three challenges. 1. Enhanc-ing the capacity of LLMs in general information extraction tasks is vital to reduce the definition bias between information extraction datasets and instruction tuning datasets; 2. It is essential to miti-gate the definition bias during the tuning of LLMs with diverse datasets; 3. Learning from new data over time, adapting to new tasks while ensuring the model remains relevant and less biased, is a significant challenge.

To address these challenges, we propose a frame-work to alleviate definition bias, which consists of definition bias measurement, bias-aware fine-tuning and task-specific bias mitigation. With us-ing Fleiss' Kappa (Fleiss, 1971), we measure the two type of definition bias above. Then we conduct bias-aware fine-tuning with multiple information extraction instructions to enhance the extraction capabilities with less definition bias. Ultimately, we conduct the task-specific bias mitigation, with

low-rank adaptation technique (LoRA) (Hu et al., 2021) for specific information extraction tasks to further align the LLMs with annotations.

Our paper is organized as follows: In Section 2, we present three probing experiments designed to explore the presence of definition bias and assess the ability of existing frameworks to address this issue in IE. Section 3 details the results and analysis of these experiments, concluding that frameworks based on either one-stage processing or parameter-free updates are insufficient for tackling definition bias in IE. Consequently, we propose a novel framework featuring two-stage fine-tuning, specifically developed to mitigate the identified definition bias, as introduced in Section 4. Ultimately, in Section 5, we compare the performance of our framework against state-of-the-art methods in universal information extraction, demonstrating its effectiveness in reducing definition bias.

2 Definition Bias Probing Experiment

We initially propose an experiment employing cross-validation to investigate the presence of definition bias in the IE task. Subsequently, we design two specific detection tasks: source prompt detection and few-shot prompting in LLMs, to examine two categories of definition bias: bias within IE datasets and bias between IE and instruction fine-tuning datasets. These experiments aim to explore the effectiveness of UIE and LLM frameworks in addressing the definition bias issue.

2.1 Whether definition bias exists?

To better illustrate the definition bias among different information extraction tasks, we design a cross-extraction task. As shown in Figure 2(a), we train multiple fully-supervised models with different datasets on the same task (NER and RE) respectively, and test them on other datasets to evaluate whether definition bias exists.

We first introduce two BERT-based extraction frameworks to handle the NER and RE task respectively.

Named Entity Recognition   We adopt Global-Pointer (Su et al., 2022), an efficient span-based approach that models both the beginning and end positions to predict entities using a two-dimensional scoring matrix. By incorporating extended softmax and cross-entropy, GlobalPointer is better equipped to learn from scenarios involving class imbalance.

Relation Extraction   We adopt RERE (Xie et al., 2021) as the basic model for relation extraction. RERE is a pipeline approach that first performs sentence-level relation detection, followed by subject/object extraction. Specifically, the RERE model treats the former as a multi-class classification task and the latter as a span detection task.

During the cross-validation process, we encountered label type biases across different datasets. For instance, the ACE 2004 dataset requires the extraction of the weapon entity, which is not a requirement in the CoNLL 2003 dataset. Consequently, we focus exclusively on the types of labels (such as entity types in NER and relationship types in RE) that are annotated in both the training and testing datasets. An example is the person label, which is common to both ACE 2004 and CoNLL 2003.

To mitigate the impact of text distribution shift on the experimental results, we sample a subset of sentences with similar semantics as a cross-validation set. Specifically, we measure the semantic similarity between two sentences by calculating the cosine similarity of their sentence embeddings. We define the semantic similarity of the sentence $sent_i$ to the dataset $\mathcal{D}$. Finally, we filter out all sentences that fall below the $threshold(\mathcal{D})$.

$$sim(sent_i, \mathcal{D}) = \max_{ref_j \in \mathcal{D}} cosine(V_{sent_i}, V_{ref_j}) \quad (1)$$

$$threshold(\mathcal{D}) = \sigma \cdot \frac{1}{|\mathcal{D}|} \sum_{s_i \in \mathcal{D}} sim(s_i, \mathcal{D} \setminus \{s_i\}) \quad (2)$$

where V_S denotes the embedding vector of a sentence S encoded by a sentence model[1], and σ denotes the hyper-parameters that adjust the threshold, empirically set to 0.7.

2.2 Can UIE address definition bias?

Unified information extraction, which employs a pre-defined structured extraction language to encode different extraction structures, can accurately recognize extraction instructions. Inspired by Li et al. (2022), which introduces a novel prompt-based method in a transferable setting for text generation tasks, we adopt source prompt settings for probing. Briefly, in our experiment setting, a source can be denoted as the name of the dataset (e.g., ACE 2004). By presenting UIE with various sources—indicating which dataset the instance

---

[1] We adopt MPNet (Song et al., 2020) as our sentence embedding encoder, which is commonly used for retrieval

is from—we can guide it to yield different extraction results. This approach allows us to assess whether it can maintain consistent results with different source prompts.

As Figure 2(b) shows, the probing experiment consists of two parts: *source prompt tuning* and *source prompt inference*. Initially, we undertake a source prompt tuning process to enhance the UIE model's ability to recognize different sources. Subsequently, we examine the definition bias within the UIE model by introducing various sources.

Source Prompt Tuning The source prompt process can be regarded as a general multi-task learning framework. First, we define a set of source information extraction tasks $\mathcal{S} = \{\mathcal{S}_1, ..., \mathcal{S}_n\}$, where the k-th task $\mathcal{S}_k = \{(x_i^k, y_i^k)\}_{i=1}^{N_k}$ contains N_k tuples of the input text $x_i^k \in \mathcal{X}_k$ and its corresponding output text $y_i^k \in \mathcal{Y}_k$. For a target information extraction task $\mathcal{T}$, the goal of multi-task learning is to leverage previously learned task-specific knowledge of the source tasks $\mathcal{S}$ to improve prediction of the extraction result. Differing from the traditional multi-task fine-tuning scenario, in source prompt tuning, we learn an independent *source prompt* p_k for each source information extraction task $\mathcal{S}_k$ in source prompt tuning, where x_i^k consists of extraction task source name s_k, information extraction task description t_k, and the sentence $sent_i^k$.

To clearly demonstrate that UIE with instruction tuning can implicitly learn definitions of dataset through source prompt, we assign a nickname p_k' for every dataset and randomly replace p_k with p_k'. For simplicity, we merely reverse the order of the original dataset names, thereby generating a non-natural language nicknames. This procedure is designed to eliminate the influence caused by the differences in learning various source names in the UIE and ensure that the discrepancies in results between true and fake settings are solely due to dataset definition bias.

Specifically, we adopt Llama-v2-13B (Touvron et al., 2023) and FlanT5-11B (Chung et al., 2022) as our backbone models in source prompt tuning settings because of their powerful instruction understanding and instruction-following capabilities. Based on multiple datasets in NER and RE, we add an additional *source prompt* to every extraction instance to indicate the dataset it belongs to. Further details on source prompt tuning are described in the Appendix A.2.

Source Prompt Inference In reference, we provide different source prompts with the same extraction instance to our UIE models that have been fine-tuned on the dataset with source prompts. To probe the definition bias in universal generative information extraction, UIE predicts the extraction result with **True source** (the extraction case with the original source name), **Nickname source** (a nickname of the original source name) and **Fake source** (the extraction case with a fake source name). With different source name, UIE generates different extraction results following different definitions learned from source prompt tuning.

2.3 Can LLMs address definition bias?

Large language models exhibit remarkable instruction understanding capabilities, which help them achieve extraordinary performance on various tasks. However, due to the definition bias between IE datasets and IFT datasets, there is a significant performance gap in LLMs when it comes to the information extraction task (Wadhwa et al., 2023). In-context learning, where LLMs make predictions based solely on contexts augmented with a few examples, is a training-free learning framework that enables models to adapt to new tasks (Dong et al., 2023). It is considered a solution to address the definition bias between IE datasets and instruction tuning datasets.

As shown in Figure 2(c), we conduct the probing experiment with multiple LLMs in both zero-shot and few-shot settings.

Specifically, we utilize open-source LLMs such as Llama-v2-chat-70B (Touvron et al., 2023), and close-source LLMs ChatGPT, GPT4 (OpenAI, 2023) as our backbone models. In zero-shot settings, we prompt LLMs with a task description, which probes the definition bias between IE and IFT datasets. Meanwhile, in few-shot settings, we prompt LLMs with a task description and an additional four cases randomly sampled from the corresponding training set to examine whether in-context learning can address the definition bias. For a fair comparison, we sample 200 cases from each dataset and test them in both zero-shot and few-shot settings, respectively.

3 Empirical Study of Definition Bias

3.1 Whether definition bias exists?

Following the cross validation setting described in Section 2.1, we conduct experiment separately on

	A04[1]	A05[2]	C03[3]	Ont[4]	Wie[5]	TN7[6]	WiN[7]	PoN[8]
A04[1]	85.10	82.19	35.77	28.89	49.89	28.06	30.54	17.64
A05[2]	83.44	84.45	37.80	26.43	46.53	26.94	29.09	18.23
C03[3]	24.10	16.57	92.19	55.82	55.10	78.26	92.08	53.67
Ont[4]	32.53	21.20	60.60	89.69	49.76	34.75	61.23	37.58
Wie[5]	23.09	8.42	67.10	41.14	86.60	61.99	70.96	44.13
TN7[6]	25.60	21.07	76.16	56.15	73.95	63.39	82.70	54.45
WiN[7]	25.48	20.61	80.10	58.69	57.33	63.44	95.21	51.96
PoN[8]	14.58	10.84	44.36	35.28	40.26	32.65	69.66	77.77

[1] ACE 2004   [3] CoNLL 2003   [5] WikiANN en   [7] WikiNeural
[2] ACE 2005   [4] Ontonotes   [6] TweetNER 7   [8] PolyglotNER

Table 1: Definition bias among different NER tasks.

	CoNLL 04	NYT10	NYT11	GIDs	WikiKBP
CoNLL 04	61.12	10.20	12.07	-	26.98
NYT10	14.36	89.68	52.29	14.33	30.32
NYT11	8.78	83.32	56.82	10.70	32.64
GIDs	-	7.77	6.45	65.12	55.65
WikiKBP	0.00	15.05	2.53	26.49	36.57

Table 2: Definition bias among different RE tasks.

Model	Llama-13b			Flan-T5		
Source	*True*	*Nickname*	*Fake*	*True*	*Nickname*	*Fake*
Named Entity Recognition						
ACE 04	84.93	84.89	60.85	77.82	78.41	45.79
ACE 05	84.85	85.16	61.56	79.20	79.59	44.10
CoNLL 03	81.02	80.87	73.34	78.94	78.84	69.23
Ontonotes	91.85	91.81	81.79	91.03	91.04	78.71
WikiANN en	89.54	89.65	81.43	76.26	76.07	66.08
TweetNER 7	68.92	69.11	66.19	68.35	68.45	60.44
WikiNeural	96.03	95.93	83.51	94.03	94.03	74.30
PolyglotNER	80.21	80.41	68.34	74.00	74.03	54.24
avg	-	-	-12.6	-	-	-18.4
Relation Extraction						
CoNLL 04	69.88	69.51	61.73	67.09	67.00	57.34
NYT10	97.80	97.78	94.82	96.20	96.20	90.54
NYT11	76.14	76.24	72.82	76.14	76.41	71.94
GIDs	80.49	80.15	78.69	76.41	76.34	74.26
WikiKBP	64.68	65.67	63.50	63.78	63.94	59.64
avg	-	-	-3.5	-	-	-5.2

Table 3: Different extraction results obtained by prompting the source prompt tuning UIE with *true*, *nickname* and *fake* source name.

Dataset	Llama-chat-70B	ChatGPT	GPT4
ACE04	8.56	30.42	19.68	32.81	13.70	**35.16**
ACE05	17.64	33.48	20.83	34.32	16.13	**45.30**
CoNLL 03	33.89	49.36	39.70	55.90	46.66	**64.99**
Ontonotes	11.86	27.56	22.14	28.83	31.70	**40.57**
WikiANN en	32.87	50.00	50.83	57.90	51.57	**59.03**
TweetNER 7	31.77	35.68	32.98	38.13	36.62	**47.88**
WikiNeural	42.98	57.03	50.00	59.83	65.23	**70.66**
PolyglotNER	21.44	30.91	42.20	44.88	**45.14**	43.23
CoNLL 04	3.36	18.77	9.22	23.86	24.62	**29.86**
NYT10	2.97	13.17	2.13	13.64	16.67	**20.13**
NYT11	2.03	5.33	1.93	6.50	8.00	**12.00**
GIDs	11.36	7.92	7.89	19.45	6.82	**24.54**
WikiKBP	18.55	29.56	17.25	32.41	25.00	**45.85**

Table 4: Performance of Open-source LLM and close-source LLM on various information extraction task in (**zero-shot** | **few-shot**) settings.

NER and RE tasks in general domain. Table 1,2 show the validation result in fully-supervised settings.

Briefly, we define the model trained and tested on the same dataset as the *reference model*. The numbers in the table cells represent the F1 scores when compared to the golden label. Additionally, the depth of color in each cell indicates the relative quality of extraction in comparison to the reference model. In other words, the darker the cell color, the closer the extraction results are to those of the reference model. The rows of the table represent the training dataset, while the columns represent the test dataset.

Intuitively, the deepest red cells are distributed along the diagonal of the entire table, illustrating that definition bias exists among different datasets, even though they share the same types. This is particularly evident in NER tasks, where several datasets focus on common entity types such as person, location, and date. Despite these similarities, definition bias can lead to significant variations in the model's extraction capabilities.

3.2 Can UIE address definition bias?

Following the source prompt setting described in Section 2.2, we tuned Llama-13b and Flan-T5 with source prompt instructions and prompted them with three source settings.

Table 3 displays the extraction results evaluated by F1 scores. Replacing the true source names with fake ones results in a drop in F1 scores across all NER and RE tasks, with an average decrease of 12.6/3.5 and 18.4/5.2, respectively. However, when true source names are replaced with nicknames, the results show virtually no difference. This significant performance gap highlights that UIE is unable to mitigate definition bias during the multi-task learning process. The implicit definition bias permeates the model, leading to inconsistent extraction results, even when the same extraction task instructions are given.

Figure 3: Our two-stage framework for alleviate definition bias. **Left:** we measure two kinds of definition bias with Fleiss' Kappa; **Right:** we first full-parameter fine-tune LLMs with measurement and then fine-tune with LoRA on specific dataset.

3.3 Can LLM address definition bias?

The performance of various models on different tasks is presented in Table 4. Among the evaluated models, GPT-4 stands out by achieving the best performance across almost all datasets in both zero-shot and few-shot settings. Furthermore, the few-shot settings, which incorporate similar cases from the same dataset into the context, enhance performance by an average of 9.82 compared to the zero-shot settings. This improvement underscores the capacity of in-context learning to partially mitigate definition bias.

Despite these advances, it remains challenging for conventional, off-the-shelf methods to reach the performance levels of fully supervised approaches. This discrepancy underscores the presence of a significant definition bias between datasets used for information extraction and those used for instruction fine-tuning. Additionally, applying LLMs to information extraction faces two primary limitations. First, the constraint on context length prevents the inclusion of all annotated cases within the context. Second, the definition bias across different information extraction datasets complicates the creation of comprehensive prompts that accurately describe the extraction tasks.

4 Alleviate Definition Bias

In this section, we explore methods to enhance the information extraction capabilities of LLMs.

Based on the probing experiments and conclusions outlined in Sections 2 and 3, we find that definition bias across different datasets significantly impacts the performance of UIE and LLMs. This indicates that a framework relying solely on a one-stage, parameter-free update is inadequate for addressing definition bias. To tackle this challenge, we introduce a two-stage fine-tuning framework. Moreover, by identifying and explicitly quantifying the two types of definition biases we have discovered, we can integrate these measurements into our fine-tuning framework, effectively reducing the influence of definition bias.

4.1 Definition Bias Measurement

First, we introduce **Fleiss' Kappa**, a statistical measure used to assess the reliability of agreement among multiple raters when they assign categorical ratings to a set of items. This tool is valuable in identifying and mitigating definition bias.

$$\kappa = 1 - \frac{1 - p_0}{1 - p_e} = \frac{p_0 - p_e}{1 - p_e} \qquad (3)$$

where p_o denotes the *Observed Agreement*, the proportion of times that the raters actually agree, and p_e denotes the *Expected Agreement*, which represents the agreement that could be expected purely by chance. Suppose there are N cases for a task, and each data is labeled n times, and k is the number of categories. These can be calculated

using the following formula.

$$p_e = \sum_{j=1}^{k} p_j^2, \quad p_j = \frac{1}{Nn} \sum_{i=1}^{N} n_{ij} \quad (4)$$

$$p_o = \frac{1}{N} \sum_{i=1}^{N} p_i, \quad p_i = \frac{1}{n(n-1)} \sum_{j=1}^{k} n_{ij}(n_{ij} - 1) \quad (5)$$

where n_{ij} denotes the number of annotator that label case i as category j.

Specifically, we focus on the definition bias in information extraction and split the definition bias into two type: *dataset definition bias* and *type definition bias*.

Dataset Definition Bias κ_D Recognized as the agreement between GPT4 and the annotation of dataset, serving as a measure of reliability for transforming information extraction into instruction tuning dataset. It is conducted by calculating the Fleiss' Kappa between the GPT4 extraction results and the golden annotation of the dataset.

Type Definition bias κ_T Considered as the agreement among information extraction datasets with the same type either entity or relationship, and serves as a metric to evaluate the reliability of these types in terms of consistent annotation.

4.2 Bias-Aware Fine-Tuning

We further fine-tuning the LLMs with information extraction dataset through C-RLFT (Wang et al., 2023a), which enables leveraging mixed-quality training data. We define the quality of the training samples as metrics based on κ_D and κ_T. Suppose there are N entity or relation triples in a case, we calculate the coarse-grained rewards of each case $r_c(x_i, y_i)$ by the formula below.

$$r_c(x_i, y_i) = (1 + \kappa_D)\frac{1}{N} \sum_{i=1}^{N} \kappa_{T_i} \quad (6)$$

4.3 Task-Specific Bias Mitigation

To further enhance the performance of LLMs on specific information extraction datasets, we employ Low-Rank Adaptation (LoRA) for additional instruction tuning. We hypothesize that the updates to the weights for a dataset possess a low intrinsic rank. This low intrinsic dimension adaptation can help mitigate the definition bias between a multi-task learning model and the dataset. Specifically,

Dataset	UIE	USM	InstructUIE	Ours
ACE 04	86.89	**87.62**	-	86.68
ACE 05	85.78	**87.14**	86.66	87.05
CoNLL 03	92.99	**93.16**	92.94	92.47
Ontonotes	-	-	90.19	**90.52**
WikiANN en	-	-	85.13	**86.24**
TweetNER 7	-	-	64.97	**65.70**
WikiNeural	-	-	91.36	**94.59**
PolyglotNER	-	-	70.15	**71.34**
CoNLL 04	75.00	**78.84**	78.48	57.46
NYT10	-	-	**90.47**	89.35
NYT11	-	-	56.06	**57.38**
GIDs	-	-	**81.98**	81.83

Table 5: Main result for comparing with other models on NER and RE tasks.

for a pre-trained weight matrix $W_0 \in \mathbb{R}^{d \times k}$, we constrain its update with a low rank decomposition.

$$h = W_0 x + \Delta W x = W_0 x + BAx \quad (7)$$

where $\Delta W x$ denotes the updatable parameters of W_0, and it can be constrained with a low-rank decomposition $\Delta W = BA$, where $B \in \mathbb{R}^{d \times r}, A \in \mathbb{R}^{r \times k}$, and the rank $r \ll min(d, r)$. W_0 is frozen and does not receive gradient updates while A and B contain trainable parameters during training.

In this stage, model updates its parameter through further fine-tuning on specific dataset to align the annotation.

5 Experiments of Two-stage Framework

This section conducts experiments to validate the effectiveness of our two-stage fine-tuning framework. We select 11B FlanT5 (Chung et al., 2022) as our backbone model. The details of experimental setup and comparison methods are described in the following parts.

5.1 Experimental Setup

In bias-aware fine-tuning, we apply a sampling strategy to balance the dataset. In specific, we sample 10,000 cases from each dataset for training. In task-specific bias mitigation, we apply all examples for training. Further details can be found in Appendix B.2.

Our baseline models contain: UIE (Lu et al., 2022), USM (Lou et al., 2023), and InstructUIE (Wang et al., 2023b).

Figure 4: Ablation Study on 12 information extraction dataset (NER and IE)

5.2 Results

Table 5 presents the result on different dataset with baselines. Although our framework was trained on several information extraction datasets in the general domain, which might be considered unfair for comparing with baselines trained on other datasets, it achieves state-of-the-art on many datasets. It is worth noting that in datasets focusing exclusively on `person`, `location`, `organization` (as listed in Table 16), our framework achieves the best performance on WikiANN en, WikiNeural, and PolyglotNER. This demonstrates the effectiveness of our framework in mitigating definition bias across different datasets.

5.3 Experiment with two-stage fine-tuning

To better improve the effectiveness of our two-stage fine-tuning framework, we conduct ablation study comparing with the following baseline: 1. *Fine-tuning*: fine-tuning the model with information extraction; 2. *Bias-aware fine-tuning*: first stage fine-tuning in Section 4.2; 3. *Fine-tuning+LoRA*: data-specific instruction-tuning with LoRA on the weight of baseline 1; 4. *Ours*: our two-stage fine-tuning framework. The results are shown in Figure 4. Overall, our framework nearly achieves the best performance compared to the baseline, demonstrating its effectiveness. By comparing baseline 1 and 2, it is proven that our bias-aware fine-tuning can alleviate definition bias among IE datasets and help models better align with GPT-4. It is also notable that two-stage fine-tuning consistently improves performance on specific datasets, attributed to the task-specific bias mitigation.

6 Related Work

6.1 LLMs for information extraction

Large language models has shown remarkable performance in instruction following (OpenAI, 2023). To better align the natural instruction task from pre-trained and instruction tuning task, Wei et al. (2023); Wadhwa et al. (2023); Zhang et al. (2023) convert structural information extraction task into natural instruction task such as question answering, multi-choice, etc. While Li et al. (2023); Guo et al. (2023) recast the structured output in the form of code to better leverage the LLMs of code to address the complex structure. Although LLMs show impressive performance in various information extraction task by designing fine-grained instruction, they still fail to address definition bias without further tuning.

6.2 Universal Information extraction

Unified Information extraction, proposed by Lu (2022), uniformly encodes various information extraction task with a pre-defined structured extraction language(SEL), and enhance the common IE abilities via a large-scale pre-trained generation model. Lou et al. (2023) further introduce USM to model different IE tasks, while Wang et al. (2023b) unified tasks into natural language instruction. GoLLIE convert IE schema into code-style structural description and add guidelines to improve zero-shot results (Sainz et al., 2023). However, they mainly focus on how to encode different extraction task into a uniform structure but fail to notice and detect the definition bias among various datasets.

7 Conclusion

In the paper, we propose the definition bias problem in information extraction task. We conduct several probing experiments to comprehensively demonstrate that existing methods cannot address definition bias. We then propose a multi-stage tuning framework, which consists of bias-aware fine-tuning and task-specific bias mitigation, to alleviate the definition bias in a specific dataset. Experimental results show that our framework is efficient in mitigating definition bias.

Limitation

We systematically investigate definition bias in IE with devising a series of probing experiments. And we propose a multi-stage framework to mitigate definition bias in IE. However, there are still some limits of our probing experiment and the solution framework.

First, our probing experiment only focus on the the definition bias among NER and RE tasks, which doesn't cover all the task in information extraction, which remains improvement for the future work.

Second, the performance of our solution framework is restricted by two main reason: 1) more diverse dataset can be used for the bias-aware fine-tuning dataset; 2) the choice on backbone model also plays an important role in model performance. More experiments can more effectively validate the effectiveness of the proposed framework.

Ethic statement

We hereby declare that all authors of this article are aware of and adhere to the provided ACL Code of Ethics and honor the code of conduct.

Use of Human Annotations   Human annotations are only utilized in the early stages of methodological research to assess the feasibility of the proposed solution. All annotators have provided consent for the use of their data for research purposes. We guarantee the security of all annotators throughout the annotation process, and they are justly remunerated according to local standards. Human annotations are not employed during the evaluation of our method.

Risks   The datasets used in the paper have been obtained from public sources and anonymized to protect against any offensive information. Though we have taken measures to do so, we cannot guarantee that the datasets do not contain any socially harmful or toxic language.

References

Rami Al-Rfou, Vivek Kulkarni, Bryan Perozzi, and Steven Skiena. 2015. Polyglot-ner: Massive multilingual named entity recognition. In *Proceedings of the 2015 SIAM International Conference on Data Mining*, pages 586–594. SIAM.

Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, et al. 2022. Scaling instruction-finetuned language models. *arXiv preprint arXiv:2210.11416*.

Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Zhiyong Wu, Baobao Chang, Xu Sun, Jingjing Xu, Lei Li, and Zhifang Sui. 2023. A survey on in-context learning.

Joe Ellis, Xuansong Li, Kira Griffitt, Stephanie M Strassel, and Jonathan Wright. 2012. Linguistic resources for 2013 knowledge base population evaluations. In *TAC*.

Joseph L Fleiss. 1971. Measuring nominal scale agreement among many raters. *Psychological bulletin*, 76(5):378.

Yucan Guo, Zixuan Li, Xiaolong Jin, Yantao Liu, Yutao Zeng, Wenxuan Liu, Xiang Li, Pan Yang, Long Bai, Jiafeng Guo, et al. 2023. Retrieval-augmented code generation for universal information extraction. *arXiv preprint arXiv:2311.02962*.

Thomas Hellström, Virginia Dignum, and Suna Bensch. 2020. Bias in machine learning – what is it good for?

Eduard Hovy, Mitch Marcus, Martha Palmer, Lance Ramshaw, and Ralph Weischedel. 2006. Ontonotes: the 90% solution. In *Proceedings of the human language technology conference of the NAACL, Companion Volume: Short Papers*, pages 57–60.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models.

Sharmistha Jat, Siddhesh Khandelwal, and Partha Talukdar. 2018. Improving distantly supervised relation extraction using word and entity based attention. *arXiv preprint arXiv:1804.06987*.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35:22199–22213.

Junyi Li, Tianyi Tang, Jian-Yun Nie, Ji-Rong Wen, and Wayne Xin Zhao. 2022. Learning to transfer prompts for text generation. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3506–3518.

Peng Li, Tianxiang Sun, Qiong Tang, Hang Yan, Yuanbin Wu, Xuanjing Huang, and Xipeng Qiu. 2023. Codeie: Large code generation models are better few-shot information extractors. *arXiv preprint arXiv:2305.05711*.

Jie Lou, Yaojie Lu, Dai Dai, Wei Jia, Hongyu Lin, Xianpei Han, Le Sun, and Hua Wu. 2023. Universal information extraction as unified semantic matching.

Daming Lu. 2022. daminglu123 at SemEval-2022 task 2: Using BERT and LSTM to do text classification. In *Proceedings of the 16th International Workshop on Semantic Evaluation (SemEval-2022)*, pages 186–189, Seattle, United States. Association for Computational Linguistics.

Yaojie Lu, Qing Liu, Dai Dai, Xinyan Xiao, Hongyu Lin, Xianpei Han, Le Sun, and Hua Wu. 2022. Unified structure generation for universal information extraction. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5755–5772, Dublin, Ireland. Association for Computational Linguistics.

OpenAI. 2023. Gpt-4 technical report.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback.

Xiaoman Pan, Boliang Zhang, Jonathan May, Joel Nothman, Kevin Knight, and Heng Ji. 2017. Cross-lingual name tagging and linking for 282 languages. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1946–1958.

Sebastian Riedel, Limin Yao, and Andrew McCallum. 2010. Modeling relations and their mentions without labeled text. In *Machine Learning and Knowledge Discovery in Databases: European Conference, ECML PKDD 2010, Barcelona, Spain, September 20-24, 2010, Proceedings, Part III 21*, pages 148–163. Springer.

Dan Roth and Wen-tau Yih. 2004. A linear programming formulation for global inference in natural language tasks. In *Proceedings of the eighth conference on computational natural language learning (CoNLL-2004) at HLT-NAACL 2004*, pages 1–8.

Oscar Sainz, Iker García-Ferrero, Rodrigo Agerri, Oier Lopez de Lacalle, German Rigau, and Eneko Agirre. 2023. Gollie: Annotation guidelines improve zero-shot information-extraction.

Erik F Sang and Fien De Meulder. 2003. Introduction to the conll-2003 shared task: Language-independent named entity recognition. *arXiv preprint cs/0306050*.

Kaitao Song, Xu Tan, Tao Qin, Jianfeng Lu, and Tie-Yan Liu. 2020. Mpnet: Masked and permuted pre-training for language understanding. *arXiv preprint arXiv:2004.09297*.

Jianlin Su, Ahmed Murtadha, Shengfeng Pan, Jing Hou, Jun Sun, Wanwei Huang, Bo Wen, and Yunfeng Liu. 2022. Global pointer: Novel efficient span-based approach for named entity recognition.

Ryuichi Takanobu, Tianyang Zhang, Jiexi Liu, and Minlie Huang. 2019. A hierarchical framework for relation extraction with reinforcement learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pages 7072–7079.

Simone Tedeschi, Valentino Maiorca, Niccolò Campolungo, Francesco Cecconi, and Roberto Navigli. 2021. WikiNEuRal: Combined neural and knowledge-based silver data creation for multilingual NER. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 2521–2533, Punta Cana, Dominican Republic. Association for Computational Linguistics.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Asahi Ushio, Leonardo Neves, Vitor Silva, Francesco Barbieri, and Jose Camacho-Collados. 2022. Named entity recognition in twitter: A dataset and analysis on short-term temporal shifts. *arXiv preprint arXiv:2210.03797*.

Somin Wadhwa, Silvio Amir, and Byron C Wallace. 2023. Revisiting relation extraction in the era of large language models. *arXiv preprint arXiv:2305.05003*.

C. Walker and Linguistic Data Consortium. 2005. *ACE 2005 Multilingual Training Corpus*. LDC corpora. Linguistic Data Consortium.

Guan Wang, Sijie Cheng, Xianyuan Zhan, Xiangang Li, Sen Song, and Yang Liu. 2023a. Openchat: Advancing open-source language models with mixed-quality data. *arXiv preprint arXiv:2309.11235*.

Xiao Wang, Weikang Zhou, Can Zu, Han Xia, Tianze Chen, Yuansen Zhang, Rui Zheng, Junjie Ye, Qi Zhang, Tao Gui, Jihua Kang, Jingsheng Yang, Siyuan Li, and Chunsai Du. 2023b. Instructuie: Multi-task instruction tuning for unified information extraction.

Xiang Wei, Xingyu Cui, Ning Cheng, Xiaobin Wang, Xin Zhang, Shen Huang, Pengjun Xie, Jinan Xu, Yufeng Chen, Meishan Zhang, et al. 2023. Zero-shot information extraction via chatting with chatgpt. *arXiv preprint arXiv:2302.10205*.

Chenhao Xie, Jiaqing Liang, Jingping Liu, Chengsong Huang, Wenhao Huang, and Yanghua Xiao. 2021. Revisiting the negative data of distantly supervised relation extraction. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 3572–3581, Online. Association for Computational Linguistics.

Kai Zhang, Bernal Jiménez Gutiérrez, and Yu Su. 2023. Aligning instruction tasks unlocks large language models as zero-shot relation extractors. *arXiv preprint arXiv:2305.11159.*

	A04[1]	A05[2]	C03[3]	Ont[4]	Wie[5]	TN7[6]	WiN[7]	PoN[8]
A04[1]		451	1299	3404	1886	121	2104	1260
A05[2]	489		1112	4649	3552	204	1954	1752
C03[3]	71	67		409	2576	22	1128	550
Ont[4]	569	770	1149		4194	180	2880	2504
Wie[5]	248	310	2338	2086		279	7752	6957
TN7[6]	222	328	1486	1736	3016		2397	1648
WiN[7]	387	407	2239	2843	8230	229		7624
PoN[8]	558	669	2795	4918	9597	387	10869	
#Tot	812	1060	3453	8262	10000	576	11597	10000

[1] ACE 2004   [4] Ontonotes   [7] WikiNeural
[2] ACE 2005   [5] WikiANN en   [8] PolyglotNER
[3] CoNLL 2003   [6] TweetNER 7

Table 6: Filter result in NER task.

	CoNLL 04	NYT10	NYT11	GIDs	WikiKBP
CoNLL 04		1935	150	1879	72
NYT10	242		344	3977	160
NYT11	189	4032		3608	150
GIDs	52	887	83		79
WikiKBP	3	71	8	70	
#Tot	288	5000	369	4307	

Table 7: Filter result in NER task.

A Further detail about probing experiments

In this section, we further introduce the detailed on three probing experiments, including experiment settings and additional experiment results.

A.1 Fully supervised settings

The filter result with similar semantic filtering process is shown in Table 6 and Table 7. While the cross-validation result without the semantic similarity filter process is shown in Table 8 and Table 9.

A.2 Source prompt settings

To eliminate the instruction bias that different dataset focus on different types of entity or relation, we employ a task decomposition approach, which involves constructing separate instructions for every entity type or relationship type. It helps decompose a task instruction with many types into atomic task instruction, which can share across different datasets. Such setting compels the UIE model to focus solely on the source name and apply distinct extraction principle for different source prompts. Table 10 show a case of task decomposition on NER.

	A04[1]	A05[2]	C03[3]	Ont[4]	Wie[5]	TN7[6]	WiN[7]	PoN[8]
A04[1]	85.10	81.54	39.36	31.15	41.70	35.65	29.70	21.10
A05[2]	82.87	84.45	40.31	30.05	40.25	34.72	29.18	20.61
C03[3]	25.63	19.53	92.19	61.11	55.06	68.26	88.89	51.48
Ont[4]	35.04	25.89	59.49	89.69	45.16	37.88	62.20	37.42
Wie[5]	19.18	14.11	64.56	39.22	86.60	59.52	64.52	39.28
TN7[6]	24.78	19.10	71.61	46.84	58.62	63.39	74.17	47.04
WiN[7]	24.10	18.77	78.76	58.69	55.41	64.51	95.21	51.36
PoN[8]	14.49	10.17	46.30	38.18	40.26	34.45	69.45	77.77

[1] ACE 2004   [3] CoNLL 2003   [5] WikiANN en   [7] WikiNeural
[2] ACE 2005   [4] Ontonotes   [6] TweetNER 7   [8] PolyglotNER

Table 8: Definition bias between different NER tasks without similar semantic filtering.

	CoNLL 04	NYT10	NYT11	GIDs	WikiKBP
CoNLL 04	61.12	9.17	7.54	-	24.37
NYT10	14.36	89.68	53.16	15.17	30.30
NYT11	8.78	83.13	56.82	12.50	31.40
GIDs	-	7.44	3.17	65.12	51.67
WikiKBP	0.00	7.95	2.53	18.78	36.57

Table 9: Definition bias between different RE tasks without similar semantic filtering.

A.3 Large language model zero/few-shot settings

We use the prompt in Table 11 for probing experiments and multi-stage fine-tuning, which consist of task description, output format, in-context learning cases and input text.

B Further detail about multi-stage instruction fine-tuning

B.1 Fleiss' Kappa

Table 12 and 13 show the κ_T and κ_D that measure the *type definition bias* and *dataset definition bias*.

B.2 Two-stage training settings

The training hyperparameters of our multi-stage framework are listed in Table 14

C Detail statistic on the dataset

We use 13 dataset in named entity recognition and relation extraction. For NER task, the used dataset include ACE04, ACE05(Walker and Consortium, 2005), CoNLL2003(Sang and De Meulder, 2003), Ontonotes(Hovy et al., 2006),PolyglotNER(Al-Rfou et al., 2015), TweetNER(Ushio et al., 2022), WikiNeural(Tedeschi et al., 2021), WikiANN(Pan et al., 2017). For RE task, the used dataset include CoNLL 2004(Roth and Yih,

---

Original Extraction Instruction

Instruction: Please list all entity words in the text that fit the category. Here's the category list:

[person,organization,location]

And then output the result in the format of "'type1: entity1; type2: entity2; ...'"

Input: *[Input text for NER]*

Output:

Decomposed Extraction Instruction

Instruction: Please list all entity words in the text that fit the category. Here's the category list:

[person]

And then output the result in the format of "'type1: entity1; type2: entity2; ...'"

Input: *[Input text for NER]*

Output:

Instruction: Please list all entity words in the text that fit the category. Here's the category list:

[organization]

And then output the result in the format of "'type1: entity1; type2: entity2; ...'"

*/*Input text*/*

Input: *[Input text for NER]*

Output:

Instruction: Please list all entity words in the text that fit the category. Here's the category list:

[location]

And then output the result in the format of "'type1: entity1; type2: entity2; ...'"

Input: *[Input text for NER]*

Output:

Table 10: A case for decomposing NER tasks instruction which focus on the entity type: person, organization and location

2004), GIDS(Jat et al., 2018), NYT10(Riedel et al., 2010), NYT11-HRL(Takanobu et al., 2019), WikiKBP(Ellis et al., 2012).

The statistic of datasets are listed in Table 15.The pre-defined entity or relation types of every dataset is shown in Table 16.

Type	Fleiss' Kappa
Entity Type of Named Entity Recognition	
person	0.414
location	0.428
organization	0.364
facility	0.021
Relation Type of Relation Extraction	
place lived	0.473
place of birth	0.467
place of death	0.408
children	0.333
location contains	0.150
person of company	0.359

Table 12: κ_T measured with dataset annotation

Dataset	Fleiss' Kappa
ACE 2004	-0.648
ACE 2005	-0.546
CoNLL 2003	-0.350
Ontonotes	-0.594
PolyglotNER	-0.567
TweetNER7	-0.521
WikiANN en	-0.409
WikiNeural	-0.293
conll04	-0.701
GIDS	-0.748
NYT10	-0.799
NYT11	-0.879
WikiKBP	-0.541

Table 13: κ_D measured with dataset annotation and GPT-4

Prompt for Named Entity Recognition

*/*Task prompt*/*

Instruction: Please list all entity words in the text that fit the category. Here's the category list:

*/*Entity type List*/*

[List of the entity type]

*/*Output Format*/*

And then output the result in the format of "'type1: entity1; type2: entity2; ...'"

*/*In-context learning cases*/*

*/*Input text*/*

Input: *[Input text for NER]*

Output:

Prompt for Relation Extraction

*/*Task prompt*/*

Instruction: Given a sentence or paragraph, and a given relationship set that describe the relation between entities. Here's the relation set:

*/*Relation type List*/*

[List of the relationship type]

*/*Output Format*/*

Output the result in the format of "'(subject1, relation1, object1), (subject2, relation2, object2), ...'"

*/*In-context learning cases*/*

*/*Input text*/*

Input: *[Input text for RE]*

Output:

Table 11: Prompts for two type of information extraction task: NER and RE.

Hyper parameters	Settings
Bias-aware fine-tuning	
Learning rate	1e-5
Epoch	5
Batch size	384
Dataset-specific Mitigation	
Learning rate	1e-5
LoRA rank	8
LoRA	
Epoch	10/30
Batch size	256

Table 14: Caption

Dataset	#Train	#Valid	#Test
Named Entity Recognition			
ACE 2004	6202	745	812
ACE 2005	7299	971	1060
CoNLL 03	14041	3250	3453
Ontonotes	59924	8528	8262
PolyglotNER	393982	10000	10000
TweetNER 7	7111	886	576
WikiANN en	20000	10000	10000
WikiNeural	92720	11590	11597
Relation Extraction			
CoNLL 04	922	231	288
GIDs	8526	1417	4307
NYT10	56196	5000	5000
NYT11	62648	149	369
WikiKBP			

Table 15: Detailed datasets statistic.

Dataset	Annotation type
Named Entity Recognition	
ACE 2004	geographical social political, organization, person, location, facility, vehicle, weapon
ACE 2005	organization, person, geographical social political, vehicle, location, weapon, facility
CoNLL 03	location, else, organization, person
Ontonotes	date, organization, person, geographical social political, national religious political, facility, cardinal, location, work of art, law, event, product, ordinal, percent, time, quantity, money, language
PolyglotNER	location, person, organization
TweetNER 7	group, creative work, person, event, product, location, corporation
WikiANN en	location, person, organization
WikiNeural	location, person, organization
Relation Extraction	
CoNLL 04	company founded place, location contains, place lived, person of company, kill
GIDs	place of death, place of birth, education degree, education institution
NYT10	ethnicity, place lived, geographic distribution, company industry, country of administrative divisions, administrative division of country, location contains, person of company, profession, ethnicity of people, company shareholder among major shareholders, sports team of location, religion, neighborhood of, company major shareholders, place of death, nationality, children, company founders, company founded place, country of capital, company advisors, sports team location of teams, place of birth
NYT11	nationality, country capital, place of death, children, location contains, place of birt, place lived, administrative division of country, country of administrative divisions, company, neighborhood of, company founders
WikiKBP	parent, children, person of company, place of birth, place of death, place lived, religion

Table 16: The type of entity or relationship in each dataset.