RESPONSE TO REVIEWER COMMENTS

We'd first like to thank the reviewers for all of their feedback. Below, we've included our response to the reviewer feedback and our revised paper. Changes to the paper are shown in pink.

Reviewer 1

I think the paper can help the readers by motivating vertical reconfiguration early on. While the introduction mentions the lack of logs in certain systems, it is too terse and easy to miss. This leaves me wondering about the motivation for vertical reconfiguration while reading the paper. I suggest the authors moving some of nice arguments from Section 6 to the introduction.

Great point. As you suggested, we moved some arguments from Section 6 into the introduction to motivate vertical reconfiguration earlier on in the paper.

In addition, it would be great if the authors can also comment on whether there are downsides with vertical reconfiguration and external matchmakers.

We added some text to Section 6 discussing the disadvantages of Donut MultiPaxos.

I am also wondering if vertical reconfiguration is fundamentally tied to external masters, or is it just the only way we know. It would be helpful to see some discussion on this early on.

Interesting question. It is possible to co-locate the matchmakers with other nodes (e.g., proposers, acceptors). However, this coupling can be disadvantageous. For example, if acceptors are reconfigured much more often than matchmakers, then coupling the two would force the matchmakers to be reconfigured more often than necessary. DPaxos [13] does the equivalent of co-locating matchmakers and acceptors, but as a consequence, the protocol assumes a fixed set of nodes (as discussed in Section 6).

We can't comment, though, on if there is a more sophisticated way to couple matchmakers with other components of the protocol that we don't know how to do yet. That sounds like an interesting direction of future work.

The paper contains fairly complete details for the most part. The only part I find a little lacking is matchmaker reconfiguration. Though the proof seems detailed, I need to see more details for the protocol to evaluate the proof. Running a Paxos instance makes sense intuitively, but how do proposers figure out current situation? For example, if one proposer shuts down the old matchmakers and immediately crashes, what do we do now? Another proposer may contact the old matchmaker and it will not hear back from them. How does it know if the old matchmakers have been shut down or if the messages are simply delayed? What's the criteria for this new proposer to perform a matchmaker reconfiguration? Does it directly install a new matchmaker configuration, or does it wait to hear back from the old matchmakers (which not never come because the old matchmakers have been shut down already)?

Excellent questions. You're right that the matchmaker reconfiguration protocol was underspecified in the paper. We extended Section 5 to elaborate on the matchmaker reconfiguration protocol.

The experiments seem fair and thorough. My main question here is why more clients improve throughput. Is it because you assume each client generates commands at some rate and you need a certain number of them to saturate the system? If that is the case, it is better to directly use the fundamental parameter of input command rate in the figure and I see no reason to use the number of clients as an arbitrary proxy. If it is for some other reason, it should be explained.

As noted in Section 7.1, clients execute in a closed loop. A client repeatedly proposes a state machine command, waits to receive a response, and then immediately proposes another command. So yes, each client does generate commands at some rate, though the rate is not determined by the client, but rather by the throughput of the state machine replication protocol.

We do this for two reasons. First, it is not uncommon in related papers [9,12,17]. Second, it aligns most naturally with the definitions of linearizability [4] where clients are required to have one pending request at a time. We edited Section 7.1 to note this.

Please also explain the meaning of violin plots. I, for one, do not know what they are.

Violin plots are a way to display a distribution of numerical data. Every violin plot includes a box and whisker plot that shows the 0%, 25%, 50%, 75%, and 100% percentiles of the distribution. However, in addition to the box and whisker plot, the violin plot also shows the full probability density of the distribution overlaid on top of the box and whisker plot.

Below are some secondary comments on readability, clarity, and consistency.

Paxos works in a partially synchronous network, not an asynchronous one. As a deterministic protocol, it is subject to the FLP impossibility.

We added a note of this to Section 2.1.

Section 3.4 mentions that premature garbage collection can make a proposer stuck; Section 3.5 instead says premature garbage collection can be unsafe. I think these are two sides of the same coin. It is better to be consistent about its effect. On a related note, I find it more natural to talk about when to garbage collect before how to garbage collect.

They are two slightly different problems. Section 3.4 asks the question "when is it safe to shut down a set of acceptors?", and the answer is "after we have garbage collected them." Section 3.5 asks the question "when is it safe to garbage collect a set of acceptors?", and the answer is "after we have satisfied one of the three garbage collect scenarios."

In other words, Section 3.4 explains that shutting down a set of acceptors before garbage collecting them can lead to a proposer getting stuck. This cannot lead to a safety violation since prematurely shutting down a set of acceptors is equivalent to failing them, and our protocols are always safe regardless of the number of faults.

Section 3.5 operates under the assumption that we will correctly garbage collect a set of acceptors before shutting them down, but then discusses when to execute this garbage collection. Executing this garbage collection at the wrong time can lead to a safety violation because garbage collecting a set of acceptors allows proposers to divert from the normal path of execution and ignore the garbage collection acceptors. This is not equivalent to simply failing the acceptors.

The "Paxos Made Simple" paper introduced three logical roles in Paxos: proposers, acceptors, and learners. The paper adopts the first two but not the third one. In fact, the paper seems to use "replicas" to refer to learners. I do not recommend this convention. To me, replicas refer to physical servers that may play multiple logical roles. To this end, I associate Paxos with $2f + 1$ replicas. Section 4.1 says there are $f + 1$ replicas (learners in my interpretation) is a little confusing. Later the evaluation section says $2f + 1$ replicas, adding to the confusion.

Paxos is a consensus protocol, not a state machine replication protocol. It doesn't replicate a state machine, so it cannot have state machine replicas. Instead, it has nodes which simply learn of a chosen value. This is why they are called learners.

MultiPaxos does replicate a state machine, and we call the replicas of the state machine "replicas". The replicas do more than learn of chosen values. They also store the values, execute them, and reply to the clients.

MultiPaxos, as described in Section 4.1, only requires $f + 1$ replicas. In Section 4.5, we discuss that Donut MultiPaxos requires $2f + 1$ replicas for garbage collection. This is why we deploy Donut MultiPaxos with $2f + 1$ replicas in the evaluation section.

While I agree that configuration selection is an orthogonal issue, I think it is helpful to fix a simple configuration selection mechanism and stick to it throughout the paper. Currently, Section 4.2 states that leader i selects its own configuration for round i but also mentions other alternatives like an external source; the first paragraph of Section 4.3 says that leader i selects the configuration for round $i + 1$; the last paragraph of Section 4.3 reverts back to leader i selecting the configuration for round i.

We added a note to Section 4.2 clarifying the selection of configurations. We also added a note to Section 3.6 clarifying that we assume the (r, id, s) round scheme throughout the paper, though our technique is not tied to this approach. When a proposer performs a reconfiguration from round i to round $i + 1$, it is the leader of both rounds, and it selects the configurations for both rounds. This is why the text has the leader of round i selecting configurations for both rounds i and $i + 1$.

Related to the above point, it is also helpful to fix a leader/proposer schedule. Section 4.2 suggests each round has a (possibly different) leader. But Section 4.4 seems to imply that the same leader is in charge of both round i and round $i + 1$. The Phase 1 bypassing optimization seems to apply only when a single leader is in charge of both rounds. This makes it more important to discuss the leader schedule. If the same leader stays across rounds, then when do you change leaders? If you routinely change leaders, then you may need to discuss when Phase 1 bypassing is applicable, and revisit the claim that "no commands are delayed".

We added a note to Section 3.6 clarifying that we assume the (r, id, s) round scheme throughout the paper. We also added a note to Section 4.3 clarifying that a new leader is elected only after the old leader has failed. This allows us to perform Phase 1 bypassing on any routine reconfiguration. When a leader does fail, you're right that we cannot perform Phase 1 bypassing. This scenario is evaluated in Section 7.2, which shows that the time required to detect the leader failure dwarfs the overheads of executing Phase 1.

The title of section 6 is not the most suitable one. The section made several good insights, and generality is just one of them. Some of the points in the latter part of Section 6 may fit better in the related work section.

We changed the title of Section 6. We also moved the discussion of Cheap Paxos to the related works section.

Reviewer 2

What I find concerning is that the authors claim that reconfiguration takes only one round of communication. While being technically correct it feels misleading. Engineers measure duration of the reconfiguration from the moment it's started to the moment it's safe to shut down a node. Since the usual deployment of the consensus based systems in the industry consist of $2f+1$ nodes with colocated roles (Etcd, Zookeeper, CockroachDB, Redpanda etc.) having the replicas running on the same nodes as acceptors requires to copy its state before turning a node off (to satisfy GC scenario #3). From this position the following statements "reconfiguring to a new set of machines takes one round trip of communication" and "all of our results hold in a co-located deployment as well" contradict each other.

You're 100% right. That statement was misleading. We edited the statement to clarify that shutting down the old machines takes additional time, and we removed the claim that all of our results hold in a co-located deployment.

Our intention was to highlight the fact that new acceptors can become active and participate in the protocol almost instantly, while the old acceptors can be shut down in the background. This is not true for every reconfiguration protocol, like Horizontal MultiPaxos with a large α for example, where new acceptors must wait for at least α commands or noops to be chosen before they are able to participate in the protocol.

Another issue is the underspecified replica reconfiguration protocol and the unclear responsibility of the replica nodes. The sentence "replicas can also be safely added or removed at any time so long as we ensure that commands replicated on f+1 replicas remain replicated on f+1 replicas" isn't aligned with "state machine replicas execute the commands in log order". After reading them it's unclear whether replicas store commands after execution and how long they should do it.

We added some text to Section 4.5 explaining that replicas must store state machine commands (even after execution) and that a separate log compaction protocol is needed to garbage collect log entries. Garbage collecting the log via log compaction, not to be confused with garbage collecting old configurations (avoiding this confusion is one of the reasons we avoided discussing log compaction in the paper), is a complex but largely orthogonal problem. State machine replication protocols like Raft and MultiPaxos have to perform log compaction even if they don't perform reconfiguration.

Next issue is related to determinism of Paxos rounds: "every round is orchestrated by a single predetermined proposer". This sentence creates an impression that given a current round (a ballot number) it's possible to predict the next one but it isn't true for example after $(4, p_1)$ there may be $(4, p_2)$, $(5, p_1)$ or any other ballot number which is lexicographically greater than the current round.

We edited Section 3.6 to clarify that we assume the (r, id, s) round scheme throughout the paper. With this round scheme, if the current round is (r, p_i, s), the next round is always $(r, p_i, s+1)$. We also clarify that when we discuss the "next round", we do not mean the next round in which a leader is elected. Rather, we simply mean the next largest round in the totally ordered space of rounds. For example, if proposer p_0 is currently leader in round $(0, p_0, 0)$ and fails, proposer p_1 may become leader in round $(0, p_1, 0)$. But, we don't say $(0, p_1, 0)$ is the next round after $(0, p_0, 0)$ $((0, p_0, 1)$ is). We added some text to Section 3.6 clarifying what we mean by "next round".

A related thing is using $i+1$ notation for the next round. The next round (ballot number) isn't defined until it happens so defining it as a function from the previous round isn't right. Also operation $+1$ isn't defined on tuples ("let the set of rounds be the set of lexicographically ordered integer pairs (r, id) where r is an integer and id is a unique proposer id"). It might be better to use "next round" instead of $i+1$ or to use subscripts r_i and r_{i+1} instead of i and $i+1$.

With the (r, id, s) round scheme, the next round is always defined. But more to the point, yes, the notation around rounds is confusing. This is partially because the set of rounds can be any unbounded totally ordered set and the exact set we choose depends on the context. In practice, we deploy the (r, id, s) round scheme to allows us to perform Phase 1 bypassing, but this round scheme is confusing (A proposer always owns the next round, but every proposer also owns an infinite number of rounds, huh?!). The (r, id) round scheme is the simplest round scheme you would use if you didn't care about Phase 1 bypassing, and it's the simplest round scheme to understand how to divide the space of rounds between a changing set of acceptors. Using the natural numbers as rounds is not something you'd ever do in practice, but it's the simplest possible round scheme and is good enough for most proofs. We personally like to think of rounds as simple integers almost always to keep things as simple as possible, which is why we prefer the notation of rounds i and $i+1$. It's also consistent with the safety proofs in [7] on which we base our proofs. We added a note to Section 3.6 clarifying the notation.

The last disturbing part is the evaluation section: the experiment is subject to the coordinated omission problem, it's unclear why the median and IQR metrics were chosen and the conclusion is self contradicting.

Clients wait to receive response before issuing the next command. This setup is subjected to the coordinated omission problem, a phenomenon when the measuring system coordinates with the measured system resulting in hiding the long periods of unavailability behind a single outlier which may be ignored even if we look at p99.

The evaluation part lacks a discussion why median and IQR are the important metrics. Even when the experiment is set up to avoid coordinated omission the reconfiguration still may significantly delay the requests without affecting the chosen metrics. For example when reconfiguration happens every second, lasts 250ms (a quarter of a second) and blocks the overlapping requests it doesn't affect IQR (a function from p75) but delays the requests by 850% (from 0.29ms to 250ms).

I recommend to redesign the experiment to avoid the coordinated omission problem by maintaining the constant rate of the requests, come up with meaningful metrics (e.g. to compare statistics like p99 and max latency of the requests overlapping with the reconfiguration and not overlapping) and back up performance benefits of Donut Paxos with numbers.

Figures 9, 10, 13, 14, and 15 show median latency as well as 95% latency. The violin plots in Figures 11 and 12 show the entire distribution. We thought that this data long with the medians, IQRs, and standard deviations painted a complete picture of the distribution. You're 100% right that the experiments are subject to the coordinated omission problem, but with only at most 8 clients and with clients executing a single pending request at a time, if a client were stalled for a prolonged period of time, the throughout measurements would reflect the stall with a noticeable dip.

The following statements from the evaluation section contradict each other:

"we include the comparison to MultiPaxos for the sake of having some baseline against which we can compare Donut MultiPaxos, but the comparison is shallow"

"Donut MultiPaxos does provide performance benefits over MultiPaxos' and Raft's reconfiguration protocols"

While Donut MultiPaxos does provide some performance benefits compared to MultiPaxos, we don't think these benefits are the main contribution of the paper, which is why we call the comparison shallow. We don't view Donut Multi-Paxos as a competitor to Horizontal MultiPaxos. Horizontal MultiPaxos works great, and if you can use it, you probably should. Rather Donut MultiPaxos is an alternative to

Horizontal MultiPaxos that can be applied to the numerous reconfiguration protocols that cannot leverage horizontal reconfiguration. Donut MultiPaxos also brings theoretical insights to a number of other protocols like Vertical Paxos, Fast Paxos, and DPaxos.

Reviewer 3

The paper addresses an interesting problem that is usually poorly discussed in papers proposing consensus protocols. I like the way in which the solution was presented starting from building a reconfigurable consensus protocol (Donut Paxos) and then extending it to build a reconfigurable replicated state machine (Donut MultiPaxos). Also, I commend the authors for having a detailed proof of the safety of the protocol as well as for discussing how other consensus protocols can be extended to implement vertical reconfiguration.

However, I mark this paper as weak reject for several reasons. First, I have some concerns about the novelty of the solution; you can think of the matchmakers as a separate state machine that is used to manage the configurations. That is, rather than having a single state machines for both user commands and configurations, Donut MultiPaxos decouples them and has one for each. Moreover, there are $2f + 1$ matchmakers and a proposer waits for $f + 1$ (typical majority) matchmaker responses to write current set of acceptors and get all previous configurations.

Donut MultiPaxos builds on a large body of previous work, so we'd like to clarify the novelties of the protocol. First, as you mention, there are surprisingly few papers that discuss reconfiguration at all. And the few papers that do discuss reconfiguration often do so at a very cursory level. Even Lamport's description of how to horizontally reconfigure Multi-Paxos [8]—one of the more fleshed out discussions on the topic—omits many non-obvious implementation details, making the protocol very challenging to implement correctly [11]. Donut MultiPaxos is one of only a handful of reconfiguration protocols that is fully described and proven correct.

Second, we significantly extend the practicality of Vertical Paxos. Vertical Paxos is a consensus protocol, not a state machine replication protocol. As we mention in the paper, Vertical Paxos' garbage collection protocol cannot be simply extended to a state machine replication protocol. Without solving this piece of the puzzle, old configurations cannot be garbage collected, and the protocol becomes somewhat useless. Vertical Paxos, in its current form, cannot realistically be used for state machine replication. Even if we ignore this problem, the Vertical Paxos paper does not describe how to implement the master in an efficient way. We could, as you mention, implement the master using another state machine replication protocol like MultiPaxos, but this would be both

slow and overly complex compared to our matchmaker approach. Part of the novelty of Donut MultiPaxos is not just performing a reconfiguration (which can be done with two state machines), but performing reconfiguration simply and efficiently.

Third, Donut Fast Paxos is the first protocol, to our knowledge, that achieves the theoretical lower bound on fast quorum sizes. We think that this is a relatively significant theoretical contribution, as most papers have tacitly assumed that this is unachievable, and many other papers spend a good deal of effort to reduce fast quorum sizes by only one or two nodes, many shy of the theoretical lower bound [2, 12].

Finally, Donut MultiPaxos has novelty in its generality. There is a growing number of non-log based state machine replication protocols that do not have a way to perform reconfiguration, and MultiPaxos' horizontal approach to reconfiguration cannot be used by these protocols. This leaves a huge hole in the reconfiguration space, and while we cannot prove definitively that our techniques are the one true solution, we think they are certainly a very promising option for a problem without many other existing solutions to turn to.

Second, this decoupling between configuration and command processing accelerates configuration changes. However, it increases the probability of unavailability as the availability of the commands' state machine is tightly coupled to the availability of the matchmakers' state machine. That is, if the matchmakers' state machine is not available, a new leader/proposer cannot execute any command even if all acceptors are up and running. The paper does not discuss this issue or evaluate it.

You're right. We added a note to Section 4.3 clarifying that because Donut MultiPaxos deploys more nodes, it will take less time to reach f failures. However, because failed nodes can be replaced as part of a reconfiguration, the increased probability of failure is practically insignificant.

Third, the paper addresses the reconfiguration of the acceptors only and do not discuss the reconfiguration of replicas. That is, the only place in which the paper discusses that is in the following excerpt: "Replicas can also be safely added or removed at any time so long as we ensure that commands replicated on $f + 1$ replicas remain replicated on $f + 1$ replicas." However, I believe that the issue of making sure that commands are always replicated on majority of replicas is very tricky and this is what guarantees the safety of a replicated state machine.

You're 100% right that making sure commands are always replicated on a majority of replicas is very tricky. We did not mean to trivialize this aspect of the protocol, and we edited the text in Section 5 to clarify that this process is not easy. We omit discussion on this aspect of reconfiguration not because we think it is easy, rather because we think it is orthogonal to

the core of our paper. Donut MultiPaxos can adopt existing mechanisms [16].

Fourth, Donut Paxos was not rigorously evaluated. For instance only 8 clients were used which is very small number of clients and not enough to stress the system. Also, the experiments do not highlight any benefits for Donut MultiPaxos over MultiPaxos in terms of throughput and latency. For better evaluation and better presentation of results, I suggest having a throughput-latency graph that compares Donut MultiPaxos and MultiPaxos for different number of clients and different alpha values (i.e., concurrent commands). The following are other minor notes I have about the experiments:

- *The results shown in Figure 9 and 10 are confusing; why Donut MultiPaxos has higher throughput that MultiPaxos in the first 10 seconds (no reconfigurations occur)?*

The throughput differences between Donut MultiPaxos in Figure 9 and Horizontal MultiPaxos in Figure 10 are due to minor implementation differences between the two protocols and are not fundamental. The two protocols can be optimized to achieve equal throughput. We added some text to Section 7.1 clarifying that the absolute throughput numbers of the two protocols are unimportant for our evaluation. The evaluation focuses only on the variance of throughput and latency during a reconfiguration.

- *Figure 14 and its caption does match the text used to describe it in section 7.2.*

Oops, sorry for the mistake. We edited Section 7.2 to fix this.

- *Having Donut MultiPaxos and MultiPaxos results in the same Figure will make it easier to read and compare results.*

Earlier on, we plotted the results for Donut MultiPaxos and MultiPaxos on the same graph, but the 95% latency shaded regions overlapped too much, and the graph was difficult to read. We later experimented with a couple other types of graphs before deciding the version in the paper was the easiest to read, though it's still far from perfect.

Finally, a minor point, I found that the text is not accurate is some places:

- *"Many state machine replication protocol do not have logs and cannot perform horizontal reconfiguration [2, 8, 27, 30, 33]" (Introduction). The citations include EPaxos and Raft and both have logs.*

EPaxos is implemented with log data structures, but logically EPaxos does not replicate a log like MultiPaxos does. Instead, it replicates a directed graph of commands. It may be possible to perform a horizontal reconfiguration across these internal logs, but that remains an open question. It's complicated by the fact that the order of commands in the graph does not always match the order of commands in the logs. The EPaxos paper itself suggests vertical reconfiguration across epochs rather than horizontal reconfiguration across the logs.

We edited the introduction to remove our confusing wording. Raft does have a log, but it cannot use the ideas behind Horizontal MultiPaxos. We mention this is Section 6 of the paper:

> Even some protocols with logs cannot use the ideas behind Horizontal MultiPaxos. For example, Raft cannot safely perform Horizontal MultiPaxos' reconfiguration [15].

It is fully explained in Section 11.4.1 of Diego Ongaro's thesis [15].

- *Sections 2.2 states that Paxos requires $f+1$ proposes, and I think it does not, and it works fine with any number of proposers.*

You're right. The protocol is safe with any number of proposers. We edited Section 2.2 to say "at least $f+1$" proposers. With fewer than $f+1$ proposers, the protocol cannot nicely handle f failures (though it is still safe).

- *In Figure 4, should the number of replicas be $2f+1$?*

We could implement MultiPaxos with $2f+1$ replicas, but $f+1$ is the minimum required that still tolerates f faults. Later, in Section 4.5, we describe that Donut MultiPaxos requires $2f+1$ replicas in order to implement garbage collection.

- *"Raft cannot safely perform horizontal reconfigurations" (Section 6). I believe that Raft reconfiguration is based on the replicated log.*

We re-worded that sentence to say "Raft cannot safely perform Horizontal MultiPaxos' reconfiguration [15]." This is fully explained in Section 11.4.1 of Diego Ongaro's thesis [15].

- *"protocol. However, while none of the protocols have logs" (Section 6). This not accurate.*

None of Generalized Paxos [6], EPaxos [12], Caesar [1], Atlas [2], CASPaxos [18], TAPIR [20], or Meerkat [19] replicate a log. As we mention above, some of these protocols may be implemented with log-like data structures, but their core abstraction is not a replicated log. We re-worded that part of the paper to make this more clear.

Reviewer 4

I got many questions after reading through this paper. The primary concern is that this paper is missing a good motivation. I agree that reconfiguration is an important piece for a consensus protocol to be practical. But in the industry, consensus protocols are mostly used for configuration service, which manages replicas of primary backup replication. Even for the case when Paxos-like consensus protocol is used for main applications, replacing a failed server can be handled by the network layer (e.g., updating DNS to redirect requests to a new server). Or simple horizontal Paxos-like approach may work fine. To motivate Donut Paxos well, there should be some explanation on why it is important to provide reconfiguration service directly within consensus protocols.

Unfortunately, replacing a failed server cannot easily handled by the network layer. For example, updating a DNS entry to perform a reconfiguration would very likely lead to safety violations, as DNS is eventually consistent. Reconfiguring a state machine replication protocols is very nuanced and easy to get wrong. For example, Raft's initial reconfiguration implementation was ultimately found to be unsafe (see the Acknowledgments sections of [15]). Later, Raft adopted a newer "simpler" reconfiguration protocol, but this protocol was also found to be unsafe [14]. As we discuss in Appendix D of our paper, we also found bugs in DPaxos. Ultimately, a well though out and fully proven protocol, like the ones we present in our paper, are required to safely perform reconfiguration.

We also explain in Section 6 that many protocols, including Raft, cannot use Horizontal MultiPaxos' reconfiguration. We hope that ideas from Donut MultiPaxos can be used by these other protocols.

Another problem is Donut Paxos doesn't provide a complete solution to the reconfiguration problem in state machine replication. Donut Paxos only covers how to safely reconfigure Paxos acceptors and ensure that servers can continue to reach an agreement. However, the difficulty of reconfiguration comes with recovering the state machine on a new replica. When Google first implemented MultiPaxos, they struggled a lot with the subtleties with recovering state machines. (Lamport's paper doesn't cover this topic.) On the other hand, Raft could be adopted widely in the industry since it fully specified how to handle the recovery of state machines, including recovery from a snapshot (they are discussed in Diego's PhD thesis). Without disclosing how to recover the state machine safely, Donut Paxos has the same problem as horizontal MultiPaxos, which will prevents the industry's adoption again.

Reconfiguring acceptors is difficult, which is what we focus on in our paper. And we agree that reconfiguring replicas is also difficult. We did not mean to trivialize this aspect of the

protocol, and we edited the text in Section 5 to clarify that this process is not easy. We omit discussion on this aspect of reconfiguration not because we think it is easy, rather because we think it is orthogonal to the core of our paper. Donut MultiPaxos can adopt existing mechanisms, like the ones you mention [16].

Lastly, the current introduction implies that the exiting reconfiguration protocols cause performance degradation and that Donut Paxos has superior performance to them. However, in the evaluation section, Multi-Paxos's performance is the same as Donut Paxos's. It was a surprise when the evaluation section admits that the performance is not the contribution of Donut Paxos. I think this should be made clear earlier.

We edited to the introduction to make this clearer earlier in the paper.

My suggestions are

- *Clarify contribution: I think Donut Paxos can be valuable if it can be applied to any Paxos-based protocols. To show that, I think it should show another example, maybe applying Donut Paxos to EPaxos. It's a bit disappointing to see just the Multi-Paxos example as it already has horizontal reconfiguration.*
- *Extend protocol to the full solution. If you believe that missing reconfiguration was the reason why the industry didn't adopt improved Paxos variants, you should provide the full solution.*

We agree that extending the ideas from Donut Paxos and Donut MultiPaxos to other protocols, like EPaxos, would significantly improve the paper. However, we think this would be a large enough contribution to constitute its own paper and is out of scope for our paper.

- *I would conduct a survey on how industry people use consensus protocols and what problems they are suffering from. Then, Donut Paxos can be motivated more strongly.*

We agree that discussions with industry practitioners could lead to further insights on reconfiguration research, but we also feel that our contributions are well motivated. If a state machine replication protocol does not perform reconfiguration, it will eventually grind to a halt. And many protocols do not have reconfiguration protocols, making them unusable as a long term solution for replication. Our paper addresses this problem.

Miscellaneous comments

- *Page 1. "inefficient reconfiguration protocols [15, 22]" $\implies$ can you evaluate their performance and show Donut Paxos's performance advantage?*

We think the inneficiences in Generalized Paxos [6] and Viewstamped Replication [10] are apparent without evaluation. Both protocols involve a stop-the-world operation in which all command processing is stopped during a reconfiguration. This drops throughput to 0.

- *Page 1. "4% effect on the median of throughput and latency measurements" $\Rightarrow$ what does it mean? Median of the whole experiment with a failure? If that's the case, medians cannot capture the reconfiguration behavior.*

The 4% number is explained fully in the evaluation section. We provide medians, 95%, interquartile ranges, standard deviations, and full distributions in violin plots. But in short, it means that the throughput and latency don't change a significant amount during a reconfiguration.

- *Page 3. "MATCHA" and "MATCHB" are a bit confusing.*

We agree that MATCHA and MATCHB are a little confusing. We think something like MATCHREQUEST and MATHREPLY would be more clear. But ultimately, we decided that MATCHA and MATCHB were most consistent with the existing PHASE1A, PHASE1B, PHASE2A, and PHASE2B messages that are standard in the literature.

- *Page 4. "The proposer then ends the Matchmaking phase" $\implies$ Is there a termination guarantee?*

There is no guarantee that a proposer will ever successfully finish the Matchmaking Phase. We edited Section 2.1 to clarify that because Donut MultiPaxos is a state machine replication protocol, it is subject to the FLP impossibility result [3] and cannot gaurantee liveness.

- *Page 4. "to every acceptor in every configuration in H_i" $\implies$ Isn't it just 1 per round?*

In practice, yes. In section 4.5, we explain that because garbage collection finishes so quickly, H_i very often contains only a single configuration, specifically C_{i-1}. However, in full generality, it is possible for H_i to contain more than one configuration. In this case, the proposer must contact every acceptor in every configuration in H_i, as described in Section 3.2.

- *Page 4. In Algorithm 3, "an arbitrary configuration" $\implies$ is it truly arbitrary?*

Yes, the configuration is truly arbitrary. The protocol is agnostic to the configuration chosen, so long as it is a valid configuration as defined in Section 2.3.

- *Page 4. In Algorithm 3, "Phase 1 quorum from every configuration in H_i" $\implies$ what is the size of quorum?*

The size of the quorum depends on the configuration chosen. For simple majority quorums with $2f + 1$ acceptors, every Phase 1 quorum has $f + 1$ acceptors. But there are other configurations with smaller or larger quorums than this [5].

References

[1] Balaji Arun, Sebastiano Peluso, Roberto Palmieri, Giuliano Losa, and Binoy Ravindran. Speeding up consensus by chasing fast decisions. In *2017 47th Annual IEEE/IFIP International Conference on Dependable Systems and Networks (DSN)*, pages 49–60. IEEE, 2017.

[2] Vitor Enes, Carlos Baquero, Tuanir França Rezende, Alexey Gotsman, Matthieu Perrin, and Pierre Sutra. State-machine replication for planet-scale systems. In *Proceedings of the Fifteenth European Conference on Computer Systems*, pages 1–15, 2020.

[3] Michael J Fischer, Nancy A Lynch, and Michael S Paterson. Impossibility of distributed consensus with one faulty process. *Journal of the ACM (JACM)*, 32(2):374–382, 1985.

[4] Maurice P Herlihy and Jeannette M Wing. Linearizability: A correctness condition for concurrent objects. *ACM Transactions on Programming Languages and Systems (TOPLAS)*, 12(3):463–492, 1990.

[5] Heidi Howard, Dahlia Malkhi, and Alexander Spiegelman. Flexible paxos: Quorum intersection revisited. In *20th International Conference on Principles of Distributed Systems (OPODIS 2016)*. Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, 2017.

[6] Leslie Lamport. Generalized consensus and paxos. *Technical Report MSR-TR-2005-33, Microsoft Research*, 2005.

[7] Leslie Lamport. Fast paxos. *Distributed Computing*, 19(2):79–103, 2006.

[8] Leslie Lamport et al. Paxos made simple. *ACM Sigact News*, 32(4):18–25, 2001.

[9] Jialin Li, Ellis Michael, Naveen Kr Sharma, Adriana Szekeres, and Dan RK Ports. Just say NO to paxos overhead: Replacing consensus with network ordering. In *12th USENIX Symposium on Operating Systems Design and Implementation (OSDI 16)*, pages 467–483, 2016.

[10] Barbara Liskov and James Cowling. Viewstamped replication revisited. *MIT-CSAIL-TR-2012-021*, 2012.

[11] Jacob R Lorch, Atul Adya, William J Bolosky, Ronnie Chaiken, John R Douceur, and Jon Howell. The smart way to migrate replicated stateful services. In *Proceedings of the 1st ACM SIGOPS/EuroSys European Conference on Computer Systems 2006*, pages 103–115, 2006.

[12] Iulian Moraru, David G Andersen, and Michael Kaminsky. There is more consensus in egalitarian parliaments. In *Proceedings of the Twenty-Fourth ACM Symposium on Operating Systems Principles*, pages 358–372, 2013.

[13] Faisal Nawab, Divyakant Agrawal, and Amr El Abbadi. Dpaxos: Managing data closer to users for low-latency and mobile applications. In *Proceedings of the 2018 International Conference on Management of Data*, pages 1221–1236. ACM, 2018.

[14] Diego Ongaro. Bug in single-server membership changes. https://groups.google.com/forum/#!msg/raft-dev/t4xj6dJTP6E/d2D9LrWRza8J. accessed: 2020-03-01.

[15] Diego Ongaro. *Consensus: Bridging theory and practice*. PhD thesis, Stanford University, 2014.

[16] Diego Ongaro and John Ousterhout. In search of an understandable consensus algorithm. In *2014 USENIX Annual Technical Conference (USENIX ATC 14)*, pages 305–319, 2014.

[17] Dan RK Ports, Jialin Li, Vincent Liu, Naveen Kr Sharma, and Arvind Krishnamurthy. Designing distributed systems using approximate synchrony in data center networks. In *12th USENIX Symposium on Networked Systems Design and Implementation (NSDI 15)*, pages 43–57, 2015.

[18] Denis Rystsov. Caspaxos: Replicated state machines without logs. *arXiv preprint arXiv:1802.07000*, 2018.

[19] Adriana Szekeres, Michael Whittaker, Jialin Li, Sharma Naveen, Arvind Krishnamurthy, Dan Ports, and Irene Zhang. Meerkat: Multicore-scalable replicated transactions following the zero-coordination principle. In *Proceedings of the Fourteenth EuroSys Conference 2020*, 2020.

[20] Irene Zhang, Naveen Kr Sharma, Adriana Szekeres, Arvind Krishnamurthy, and Dan RK Ports. Building consistent transactions with inconsistent replication. *ACM Transactions on Computer Systems (TOCS)*, 35(4):1–37, 2018.

[Solution] Donut Paxos: A Reconfigurable Consensus Protocol

Anonymous authors

Abstract

State machine replication protocols, like MultiPaxos and Raft, are at the heart of numerous distributed systems. To tolerate machine failures, these protocols must replace failed machines with new machines, a process known as reconfiguration. Reconfiguration has become increasingly important over time as the need for frequent reconfiguration has grown. Despite this, reconfiguration has largely been neglected in the literature. In this paper, we present Donut Paxos and Donut MultiPaxos, a reconfigurable consensus and state machine replication protocol respectively. Our protocols can perform a reconfiguration with little to no impact on the latency or throughput of command processing; they can perform a reconfiguration in a few milliseconds; and they present a framework that can be generalized to other replication protocols in a way that previous reconfiguration techniques can not. We provide proofs of correctness for the protocols and optimizations, and present empirical results from an open source implementation. We show that reconfiguration has less than a 4% effect on the median of throughput and latency measurements.

1   Introduction

Many distributed systems [4, 6, 7, 14, 16] rely on a state machine replication protocol, like MultiPaxos [17] or Raft [34], to keep multiple replicas of their data in sync. Over time, machines fail, and if too many machines in a state machine replication protocol fail, the protocol grinds to a halt. Thus, state machine replication protocols have to replace failed machines with new machines as the protocol runs, a process known as reconfiguration.

Reconfiguration is an essential component of state machine replication. It is not an optimization or an afterthought. Without a reconfiguration protocol in place, a state machine replication protocol will inevitably stop working; it's just a matter of when. Despite this, reconfiguration has largely been neglected by current academic literature. Researchers have invented dozens of state machine replication protocols, yet many papers either discuss reconfiguration briefly with no evaluation [31, 36–38], propose theoretically safe but inefficient reconfiguration protocols [18, 26], or do not discuss reconfiguration at all [2, 3, 19, 28, 29].

Ignoring reconfiguration has never been ideal, but we have largely been able to get away with it. Historically, state machine replication protocols were deployed on a fixed set of machines, and reconfiguration was used only to replace failed machines with new machines – an infrequent occurrence. This made it easy to leave reconfiguration out of sight, out of mind. Recently however, systems have become increasingly elastic, and the need for frequent reconfiguration has grown. These elastic systems don't just perform reconfigurations *reactively* when machines fail; they reconfigure *proactively*. For example, cloud databases can proactively request more resources to handle workload spikes, and orchestration tools like Kubernetes [15] are making it easier to build these types of elastic systems. Similarly, in environments with short-lived cloud instances—as with serverless computing and spot instances—and in mobile edge and Internet of Things settings, protocols must adapt to a changing set of machines much more frequently. This frequent need for reconfiguration makes it hard to ignore reconfiguration any longer.

In this paper, we present a reconfigurable consensus protocol and a reconfigurable state machine replication protocol: Donut Paxos and Donut MultiPaxos. In a nutshell, our protocols work by leveraging two key design ideas.

- The first is to *decouple reconfiguration* from the standard processing path. Many replication protocols [23, 26, 31, 34] have machines that are responsible for both processing commands and for orchestrating reconfigurations. By contrast, Donut Paxos introduces a set of distinguished matchmaker machines that are solely responsible for managing reconfigurations and operate off of the critical path. These matchmakers act as a source of truth; they always know the current configuration.

- The second design point is to reconfigure across rounds, a technique known as *vertical reconfiguration* [22]. With vertical reconfiguration, every round of consensus can execute using a different configuration.

At the beginning of every round, the Paxos leader queries the matchmakers to discover the older configurations that were used in previous rounds, and it simultaneously sends the matchmakers the configuration it intends to use in the current round. In this way, the matchmakers act as a registry for configurations. Leaders simultaneously query the past and update the present. This matchmaking phase requires a single round trip of communication and happens rarely. We also introduce a number of novel protocol optimizations to perform the matchmaking completely off the critical path to avoid

degrading performance. Moreover, the protocol employs a garbage collection protocol to delete old configurations stored on the matchmakers. Our protocols have the following desirable properties.

Little to No Performance Degradation. Donut Multi-Paxos can perform a reconfiguration without significantly degrading the throughput or latency of processing client commands. For example, we show that reconfiguration has less than a 4% effect on the median of throughput and latency measurements (Section 7). Note that Donut MultiPaxos is not the first protocol to achieve this [27].

Quick Reconfiguration. Donut MultiPaxos can perform a reconfiguration quickly. Reconfiguring to a new set of machines takes one round trip of communication in the normal case (Section 4). Empirically, this requires only a few milliseconds within a single data center (Section 7). It takes slightly longer to shut down the old machines, but empirically this takes only five milliseconds within a data center (Section 7).

Generality Replication protocols based on classical Multi-Paxos assume a totally ordered log of chosen commands and reconfigure across log entries, known as *horizontal reconfiguration*. However, many state machine replication protocols do not replicate a log [2, 18, 31, 38, 39, 41]. These protocols cannot use horizontal reconfiguration. However, while none of these protocols have logs, they all have rounds and can implement vertical reconfiguration. This allows Donut Paxos and Donut MultiPaxos to serve as a foundation on top of which reconfiguration protocols can be built for these other non-log based protocols.

Theoretical Insights. Donut Paxos generalizes Vertical Paxos [22], it is the first protocol to achieve the theoretical lower bound on Fast Paxos [19] quorum sizes, and it corrects errors in DPaxos [33] (Section 6).

Proven Safe. We describe Donut Paxos and Donut Multi-Paxos precisely and prove that both are safe (Sections 3, 4, 5, A, B). Unfortunately, this is not often done for all reconfiguration protocols [30, 36–38].

2 Background

2.1 System Model

Throughout the paper, we assume an asynchronous network model in which messages can be arbitrarily dropped, delayed, and reordered. We assume machines can fail by crashing but do not act maliciously. We assume that machines operate at arbitrary speeds, and we do not assume clock synchronization. We assume a discovery service that nodes can use to find each other, but do not require that this service be strongly consistent. A node can safely communicate with outdated nodes. A system like DNS would suffice. Every protocol discussed in this paper assumes (for liveness) that at most f machines will fail for some configurable f. All the protocols

discussed in this paper are safe, but due to the FLP impossibility result [10], none of the protocols are guaranteed to be fully live (unless the network is synchronous).

2.2 Paxos

A **consensus protocol** is a protocol that selects a single value from a set of proposed values. **Paxos** [17, 20] is one of the oldest and most popular consensus protocols. A Paxos deployment that tolerates f faults consists of an arbitrary number of clients, at least $f + 1$ nodes called **proposers**, and $2f + 1$ nodes called **acceptors**, as illustrated in Figure 1. To reach consensus on a value, an execution of Paxos is divided into a number of rounds, each round having two phases: Phase 1 and Phase 2. Every round is orchestrated by a single pre-determined proposer. The set of rounds can be any unbounded, totally ordered set. It is common to let the set of rounds be the set of lexicographically ordered integer pairs (r, id) where r is an integer and id is a unique proposer id, where a proposer is responsible for executing every round that contains its id.

Figure 1: Paxos communication diagram ($f = 1$).

When a proposer executes a round, say round i, it attempts to get some value x chosen in that round. Paxos is a consensus protocol, so it must only choose a single value. Thus, Paxos must ensure that if a value x is chosen in round i, then no other value besides x can ever be chosen in any round less than i. This is the purpose of Paxos' two phases. In Phase 1 of round i, the proposer contacts the acceptors to (a) learn of any value that may have already been chosen in any round less than i and (b) prevent any new values from being chosen in any round less than i. In Phase 2, the proposer proposes a value to the acceptors, and the acceptors vote on whether or not to choose it. In Phase 2, the proposer will only propose a value x if it ensured through Phase 1 that no other value has been or will be chosen in a previous round.

More concretely, Paxos executes as follows, as illustrated in Figure 1. When a client wants to propose a value x, it sends x to a proposer p. Upon receiving x, p begins executing one round of Paxos, say round i. First, it executes Phase 1. It sends PHASE1A$\langle i \rangle$ messages to the acceptors. An acceptor ignores a PHASE1A$\langle i \rangle$ message if it has already received a message in a larger round. Otherwise, it replies with a PHASE1B$\langle i, vr, vv \rangle$ message containing the largest round vr in which the acceptor

voted and the value it voted for, vv. If the acceptor hasn't voted yet, then $vr = -1$ and $vv = \text{null}$. When the proposer receives PHASE1B messages from a majority of the acceptors, Phase 1 ends and Phase 2 begins.

At the start of Phase 2, the proposer uses the PHASE1B messages that it received in Phase 1 to select a value x such that no value other than x has been or will be chosen in any round less than i. Specifically x is the vote value associated with the largest received vote round, or any value if no acceptor had voted (see [20] for details). Then, the proposer sends PHASE2A$\langle i, x \rangle$ messages to the acceptors. An acceptor ignores a PHASE2A$\langle i, x \rangle$ message if it has already received a message in a larger round. Otherwise, it votes for x and sends back a PHASE2B$\langle i \rangle$ message to the proposer. If a majority of acceptors vote for the value, then the value is chosen, and the proposer informs the client. Proposer and acceptor pseudocode (with modifications for Donut Paxos) are shown in Algorithm 3 and Algorithm 2.

2.3 Flexible Paxos

Paxos deploys a set of $2f + 1$ acceptors, and proposers communicate with at least a *majority* of the acceptors in Phase 1 and in Phase 2. **Flexible Paxos** [13] is a Paxos variant that eschews the notion of a *majority* for that of an arbitrary *quorum*. Specifically, Flexible Paxos introduces the notion of a **configuration** $C = (A; P1; P2)$. A is a set of acceptors. $P1$ and $P2$ are sets of **quorums**, where each quorum is a subset of A. A configuration satisfies the property that every quorum in $P1$ (known as a **Phase 1 quorum**) intersects every quorum in $P2$ (known as a **Phase 2 quorum**). For a configuration to tolerate f failures, there must exist some Phase 1 quorum and some Phase 2 quorum of non-failed machines despite an arbitrary set of f failures.

Flexible Paxos is identical to Paxos with the exception that proposers now communicate with an arbitrary Phase 1 quorum in Phase 1 and an arbitrary Phase 2 quorum in Phase 2. In the remainder of this paper, we assume that all protocols operate using quorums from an arbitrary configuration rather than majorities from a fixed set of $2f + 1$ acceptors.

3 Donut Paxos

We now present Donut Paxos. To ease understanding, we first describe a simplified version of Donut Paxos that is easy to understand but is also naively inefficient. We then upgrade the protocol to the complete, efficient version by way of a number of optimizations.

3.1 Overview and Intuition

Donut Paxos is largely identical to Paxos. Like Paxos, a Donut Paxos deployment includes an arbitrary number of clients, a set of at least $f + 1$ proposers, and some set of acceptors, as

illustrated in Figure 2. Paxos assumes that a *single, fixed* configuration of acceptors is used for every round. The big difference between Paxos and Donut Paxos is that Donut Paxos allows every round to have a *different* configuration of acceptors. Round 0 may use some configuration C_0, while round 1 may use some completely different configuration C_1. This idea was first introduced by Vertical Paxos [22].

Figure 2: Donut Paxos ($f = 1$).

Recall from Section 2 that a Paxos proposer in round i executes Phase 1 in order to (1) learn of any value that may have been chosen in a round less than i and (2) prevent any new values from being chosen in any round less than i. To do so, the proposer contacts the *fixed set* of acceptors. A Donut Paxos proposer must also execute Phase 1 to establish that these two properties hold. The difference is that there is no longer a single fixed configuration of acceptors to contact. Instead, a Donut Paxos proposer has to contact all of the configurations used in rounds less than i.

However, every round can use a different configuration of acceptors, so how does the proposer of round i know which acceptors to contact in Phase 1? To resolve this question, a Donut Paxos deployment also includes a set of $2f + 1$ **matchmakers**. The protocol executes as follows, as illustrated in Figure 2.

(1) A client proposes a value x by sending it to a proposer (p_1 in Figure 2).

(2,3) When a proposer receives a value x, it begins executing the protocol in some round i. It selects a configuration C_i and sends C_i to the matchmakers. The matchmakers reply with the configurations used in previous rounds. We call this the **Matchmaking phase**. In Figure 2, the proposer executes in round 1 and selects configuration C_1

consisting of acceptors b_1, b_2, and b_3. The matchmakers reply with the configuration C_0 consisting of acceptors a_1, a_2, and a_3.

(4,5) The proposer then executes Phase 1 of Paxos with the prior configurations that it received during the Matchmaking Phase. In Figure 2, the proposer executes Phase 1 with configuration C_0.

(6,7) The proposer then executes Phase 2 with the configuration C_i to get the value x chosen. In Figure 2, the proposer executes Phase 2 with configuration C_1.

(8) Finally, the proposer informs the client that x was chosen.

At first, the extra round trip of communication with the matchmakers and the large number of configurations in Phase 1 make Donut Paxos look slow. This is for ease of explanation. Later, we will eliminate these costs (Section 3.4 – Section 3.6).

3.2 Details

Every matchmaker maintains a log L of configurations indexed by round. That is, $L[i]$ stores the configuration of round i. When a proposer receives a request x from a client and begins executing round i, it first selects a configuration C_i to use in round i. It then sends a MATCHA$\langle i, C_i \rangle$ message to all of the matchmakers.

When a matchmaker receives a MATCHA$\langle i, C_i \rangle$ message, it checks to see if it had previously received a MATCHA$\langle j, C_j \rangle$ message for some round $j \geq i$. If so, the matchmaker ignores the MATCHA$\langle i, C_i \rangle$ message. Otherwise, it inserts C_i in log entry i and computes the set H_i of previous configurations in the log: $H_i = \{(j, C_j) \mid j < i, C_j \in L\}$. It then replies to the proposer with a MATCHB$\langle i, H_i \rangle$ message. Matchmaker pseudocode is given in Algorithm 1. An example execution of a matchmaker is illustrated in Figure 3.

Algorithm 1 Matchmaker Pseudocode

State: a log L indexed by round, initially empty

1: **upon** receiving MATCHA$\langle i, C_i \rangle$ from proposer p **do**
2:     **if** $\exists$ a configuration C_j in round $j \geq i$ in L **then**
3:         ignore the MATCHA$\langle i, C_i \rangle$ message
4:     **else**
5:         $H_i \leftarrow \{(j, C_j) \mid C_j \in L\}$
6:         $L[i] \leftarrow C_i$
7:         send MATCHB$\langle i, H_i \rangle$ to p

When the proposer in round i receives MATCHB$\langle i, H_i^1 \rangle$, ..., MATCHB$\langle i, H_i^{f+1} \rangle$ from $f + 1$ matchmakers, it computes $H_i = \cup_{j=1}^{f+1} H_i^j$. For example, with $f = 1$ and $i = 2$, if the proposer in round 2 receives MATCHB$\langle 2, \{(0, C_0)\} \rangle$ and MATCHB$\langle 2, \{(1, C_1)\} \rangle$, it computes $H_2 = \{(0, C_0), (1, C_1)\}$.

Figure 3: A matchmaker's log over time. (a) Initially, the matchmaker's log is empty. (b) Then, the matchmaker receives MATCHA$\langle 0, C_0 \rangle$. It inserts C_0 in log entry 0 and returns MATCHB$\langle 0, \emptyset \rangle$ since the log does not contain any configuration in any round less than 0. (c) The matchmaker then receives MATCHA$\langle 2, C_2 \rangle$. It inserts C_2 in log entry 2 and returns MATCHB$\langle 2, \{(0, C_0)\} \rangle$. (d) It then receives MATCHA$\langle 3, C_3 \rangle$, inserts C_3 in log entry 3, and returns MATCHB$\langle 3, \{(0, C_0), (2, C_2)\} \rangle$. At this point, if the matchmaker were to receive MATCHA$\langle 1, C_1 \rangle$, it would ignore it.

Algorithm 2 Acceptor Pseudocode

State: the largest seen round r, initially -1
State: the largest round vr voted in, initially -1
State: the value vv voted for in round vr, initially null

1: **upon** receiving PHASE1A$\langle i \rangle$ from p with $i > r$ **do**
2:     $r \leftarrow i$
3:     send PHASE1B$\langle i, vr, vv \rangle$ to p
4: **upon** receiving PHASE2A$\langle i, x \rangle$ from p with $i \geq r$ **do**
5:     $r, vr, vv \leftarrow i, i, x$
6:     send PHASE2B$\langle i \rangle$ to p

Note that every round is statically assigned to a single proposer and that a proposer selects a single configuration for a round, so if two matchmakers return configurations for the same round, they are guaranteed to be the same.

The proposer then ends the Matchmaking phase and begins Phase 1. It sends PHASE1A messages to every acceptor in every configuration in H_i and waits to receive PHASE1B messages from a Phase 1 quorum from every configuration. Using the previous example, the proposer sends PHASE1A messages to every acceptor in C_0 and C_1 and waits for PHASE1B messages from a Phase 1 quorum of C_0 and a Phase 1 quorum of C_1. The proposer then runs Phase 2 with C_i.

Acceptor and proposer pseudocode are shown in Algorithm 2 and Algorithm 3 respectively. To keep things simple, we assume that round numbers are integers, but generalizing to an arbitrary totally ordered set is straightforward. A Donut Paxos acceptor is identical to a Paxos acceptor. A Donut Paxos proposer is nearly identical to a Flexible Paxos proposer with the exception of the Matchmaking phase and the configurations used in Phase 1 and Phase 2. For clarity of exposition, we omit straightforward details surrounding re-sending dropped messages and nacking ignored messages.

Algorithm 3 Proposer Pseudocode. Modifications to a Paxos proposer are underlined and shown in blue.

State: a value x, initially null
State: a round i, initially -1
State: the configuration C_i for round i, initially null
State: the prior configurations H_i for round i, initially null

1: **upon** receiving value y from a client **do**
2:     $i \leftarrow$ next largest round owned by this proposer
3:     $x \leftarrow y$
4:     $C_i \leftarrow$ an arbitrary configuration
5:     send MATCHA$\langle i, C_i \rangle$ to all of the matchmakers

6: **upon** receiving MATCHB$\langle i, H_i^1 \rangle, \ldots,$ MATCHB$\langle i, H_i^{f+1} \rangle$ from $f+1$ matchmakers **do**
7:     $H_i \leftarrow \bigcup_{j=1}^{f+1} H_i^j$
8:     send PHASE1A$\langle i \rangle$ to every acceptor in H_i

9: **upon** receiving PHASE1B$\langle i, -, - \rangle$ from a Phase 1 quorum from every configuration in H_i **do**
10:     $k \leftarrow$ the largest vr in any PHASE1B$\langle i, vr, vv \rangle$
11:     **if** $k \neq -1$ **then**
12:        $x \leftarrow$ the corresponding vv in round k
13:     send PHASE2A$\langle i, x \rangle$ to every acceptor in C_i

14: **upon** receiving PHASE2B$\langle i \rangle$ from a Phase 2 quorum **do**
15:     x is chosen, inform the client

3.3 Proof of Safety

We now prove that Donut Paxos is safe; i.e. every execution of Donut Paxos chooses at most one value.

Proof. Our proof is based on the Paxos safety proof in [19]. We prove, for every round i, the statement $P(i)$: "if a proposer proposes a value v in round i (i.e. sends a PHASE2A message for value v in round i), then no value other than v has been or will be chosen in any round less than i." At most one value is ever proposed in a given round, so at most one value is ever chosen in a given round. Thus, $P(i)$ suffices to prove that Donut Paxos is safe for the following reason. Assume for contradiction that Donut Paxos chooses distinct values x and y in rounds j and i with $j < i$. Some proposer must have proposed y in round i, so $P(i)$ ensures us that no value other than y could have been chosen in round j. But, x was chosen, a contradiction.

We prove $P(i)$ by strong induction on i. $P(0)$ is vacuous because there are no rounds less than 0. For the general case $P(i)$, we assume $P(0), \ldots, P(i-1)$. We perform a case analysis on the proposer's pseudocode (Algorithm 3). Either k is -1 or it is not (line 11). First, assume it is not. In this case, the proposer proposes x, the value proposed in round k (line 12). We perform a case analysis on round j to show that no value other than x has been or will be chosen in any round $j < i$. That is, we show $P(i)$.

Case 1: $j > k$. We show that no value has been or will be

chosen in round j. Recall that at the end of the Matchmaking phase, the proposer computed the set H_i of prior configurations using responses from a set M_i of $f+1$ matchmakers. Either H_i contains a configuration C_j in round j or it doesn't.

First, suppose it does. Then, the proposer sent PHASE1A$\langle i \rangle$ messages to all of the acceptors in C_j. A Phase 1 quorum of these acceptors, say Q, all received PHASE1A$\langle i \rangle$ messages and replied with PHASE1B messages. Thus, every acceptor in Q set its round r to i, and in doing so, promised to never vote in any round less than i. Moreover, none of the acceptors in Q had voted in any round greater than k. So, every acceptor in Q has not voted and never will vote in round j. For a value v' to be chosen in round j, it must receive votes from some Phase 2 quorum Q' of round j acceptors. But, Q and Q' necessarily intersect, so this is impossible. Thus, no value has been or will be chosen in round j.

Now suppose that H_i does *not* contain a configuration for round j. H_i is the union of $f+1$ MATCHB messages from the $f+1$ matchmakers in M_i. Thus, if H_i does not contain a configuration for round j, then none of the MATCHB messages did either. This means that for every matchmaker $m \in M_i$, when m received MATCHA$\langle i, C_i \rangle$, it did not contain a configuration for round j in its log. Moreover, by processing the MATCHA$\langle i, C_i \rangle$ request, the matchmaker is guaranteed to never process a MATCHA$\langle j, C_j \rangle$ request in the future. Thus, every matchmaker in M_i has not processed a MATCHA request in round j and never will. For a value to be chosen in round j, the proposer executing round j must first receive replies from $f+1$ matchmakers, say M_j, in round j. But, M_i and M_j necessarily intersect, so this is impossible. Thus, no value has been or will be chosen in round j.

Case 2: $j = k$. In a given round, at most one value is proposed, let alone chosen. x is *the* value proposed in round k, so no other value could be chosen in round k.

Case 3: $j < k$. By induction, $P(k)$ states that no value other than x has been or will be chosen in any round less than k. This includes round j.

Finally, if k is -1, then we are in the same situation as in Case 1. No value has or will be chosen in a round $j < i$. $\square$

3.4 Garbage Collection (How)

We've discussed how a proposer can change its round and introduce a new configuration. Now, we explain how to shut down old configurations. At the beginning of round i, a proposer p executes the Matchmaking phase and computes a set H_i of configurations in rounds less than i. The proposer then executes Phase 1 with the acceptors in these configurations. Assume H_i contains a configuration C_j for a round $j < i$. If we prematurely shut down the acceptors in C_j, then proposer p will get stuck in Phase 1, waiting for PHASE1B messages from a quorum of nodes that have been shut down. Therefore, we cannot shut down the acceptors in a configuration C_j until we are sure that the matchmakers will never again return C_j

during the Matchmaking phase.

Thus, we extend Donut Paxos to allow matchmakers to garbage collect configurations from their logs, ensuring that the garbage collected configurations will not be returned during any future Matchmaking phase. More concretely, a proposer p can now send a GARBAGEA$\langle i \rangle$ command to the matchmakers informing them to garbage collect all configurations in rounds less than i. When a matchmaker receives a GARBAGEA$\langle i \rangle$ message, it deletes log entry $L[j]$ for every round $j < i$. It then updates a garbage collection watermark w to the maximum of w and i and sends back a GARBAGEB$\langle i \rangle$ message to the proposer. See Algorithm 4.

Algorithm 4 Matchmaker Pseudocode (with GC). Changes to Algorithm 1 are underlined and shown in blue.

State: a log L indexed by round, initially empty
State: a garbage collection watermark w, initially 0
1: **upon** receiving GARBAGEA$\langle i \rangle$ from proposer p **do**
2:     delete $L[j]$ for all $j < i$.
3:     $w \leftarrow \max(w, i)$
4:     send GARBAGEB$\langle i \rangle$ to p
5: **upon** receiving MATCHA$\langle i, C_i \rangle$ from proposer p **do**
6:     **if** $i < w$ or $\exists\, C_j$ in round $j \geq i$ in L **then**
7:         ignore the MATCHA$\langle i, C_i \rangle$ message
8:     **else**
9:         $H_i \leftarrow \{(j, C_j) \mid C_j \in L\}$
10:         $L[i] \leftarrow C_i$
11:         send MATCHB$\langle i, w, H_i \rangle$ to p

We also update the Matchmaking phase in three ways. First, a matchmaker ignores a MATCHA$\langle i, C_i \rangle$ message if i has been garbage collected (i.e. if $i < w$). Second, a matchmaker returns its garbage collection watermark w in every MATCHB that it sends. Third, when a proposer receives MATCHB$\langle i, w_1, H_i^1 \rangle$, ..., MATCHB$\langle i, w_{f+1}, H_i^{f+1} \rangle$ from $f + 1$ matchmakers, it again computes $H_i = \cup_{j=1}^{f+1} H_i^j$. It then computes $w = \max_{j=1}^{f+1} w_j$ and prunes every configuration in H_i in a round less than w. In other words, if any of the $f + 1$ matchmakers have garbage collected round j, then the proposer also garbage collects round j.

Once a proposer receives GARBAGEB$\langle i \rangle$ messages from at least $f + 1$ matchmakers M, it is guaranteed that all future Matchmaking phases will not include any configuration in any round less than i. Why? Consider a future Matchmaking phase run with $f + 1$ matchmakers M'. M and M' intersect, so some matchmaker in the intersection has a garbage collection watermark at least as large as i. Thus, once a configuration has been garbage collected by $f + 1$ matchmakers, we can shut down the acceptors in the configuration.

3.5   Garbage Collection (When)

Once a configuration has been garbage collected, it is safe to shut it down, but when is it safe to garbage collect a configuration? It is not always safe. For example, if we prematurely garbage collect configuration C_j in round j, a future proposer in round $i > j$ may not learn about a value v chosen in round j and then erroneously get a value other than v chosen in round i. There are three situations in which it is safe for a proposer p_i in round i to issue a GARBAGEA$\langle i \rangle$ command. We explain the three situations and provide intuition on why they are safe. Later, we'll see that all three scenarios are important for Donut MultiPaxos. See Section A for a safety proof.

Scenario 1. If the proposer p_i gets a value x chosen in round i, then it can safely issue a GARBAGEA$\langle i \rangle$ command. Why? When a proposer p_j in round $j > i$ executes Phase 1, it will learn about the value x and propose x in Phase 2. But first, it must establish that no value other than x has been or will be chosen in any round less than j. This is $P(j)$ from the safety proof in Section 3.3. The proposer p_i already established this fact for all rounds less than i (this is $P(i)$), so any communication with the configurations in these rounds is redundant. Thus, we can garbage collect them.

Scenario 2. If the proposer p_i executes Phase 1 in round i and finds $k = -1$ (see Algorithm 3), then it can safely issue a GARBAGEA$\langle i \rangle$ command. Recall that if $k = -1$, then no value has been or will be chosen in any round less than i. This situation is similar to Scenario 1. Any future proposer p_j in round $j > i$ does not have to redundantly communicate with the configurations in rounds less than i since p_i already established that no value has been chosen in these rounds.

Scenario 3. If the proposer p_i learns that a value x has already been chosen and has been stored on $f + 1$ non-acceptor machines (e.g., $f + 1$ proposers), then the proposer can safely issue a GARBAGEA$\langle i \rangle$ command after it informs a Phase 2 quorum of acceptors in C_i of this fact. Any future proposer p_j in round $j > i$ will contact a Phase 1 quorum of C_i and encounter at least one acceptor that knows the value x has already been chosen. When this acceptor informs p_j that a value x has already been chosen, p_j stops executing the protocol entirely and simply fetches the value x from one of the $f + 1$ machines that store the value. Note that storing the value on $f + 1$ machines ensures that some machine will store the value despite f failures. The decision of exactly which $f + 1$ machines is not important.

Later, we'll extend this garbage collection protocol to Donut MultiPaxos (Section 4) and see empirically that matchmakers usually return just a single configuration (Section 7).

3.6   Optimizations

We now present a couple of protocol optimizations. First, note that a proposer can proactively run the Matchmaking phase in round i *before* it hears from a client. This is similar

to proactively executing Phase 1, a standard optimization [12]. We call this optimization **proactive matchmaking**.

Second, assume that the proposer in round i has executed the Matchmaking phase and Phase 1. Through Phase 1, it finds that $k = -1$ and thus learns that no value has been chosen in any round less than i (see the safety proof above). Assume that before executing Phase 2 in round i, the proposer decides to perform a reconfiguration. To perform the reconfiguration, the proposer stops executing round i and begins executing the next round $i + 1$[1]. Typically to perform the reconfiguration, the proposer would have to execute the Matchmaking phase, Phase 1, and Phase 2 in round $i + 1$. However, in this case, after executing the Matchmaking phase in round $i + 1$, the proposer can skip Phase 1 and proceed directly to Phase 2. Why? The proposer established in round i that no value has been or will be chosen in any round less than i. Moreover, because it did not run Phase 2 in round i, it also knows that no value has been or will be chosen in round i. Together, these imply that no value has been or will be chosen in any round less than $i + 1$. Normally, the proposer would run Phase 1 in round $i + 1$ to establish this fact, but since it has already established it, it can instead proceed directly to Phase 2. We call this optimization **Phase 1 bypassing**.

Phase 1 Bypassing depends on a proposer being the leader of round i *and* the leader of the next round $i + 1$. We can construct a set of rounds such that this is always the case. Let the set of rounds be the set of lexicographically ordered tuples (r, id, s) where r and s are both integers and id is a proposer id. A proposer is responsible for all the rounds that contain its id. With this set of rounds, the proposer p in round (r, p, s) always owns the next round $(r, p, s + 1)$. For example given two proposers a and b, we have the following ordering on rounds:

$$(0, a, 0) < (0, a, 1) < (0, a, 2) < (0, a, 3) < \cdots$$
$$(0, b, 0) < (0, b, 1) < (0, b, 2) < (0, b, 3) < \cdots$$
$$(1, a, 0) < (1, a, 1) < (1, a, 2) < (1, a, 3) < \cdots$$

We assume this round scheme throughout the rest of the paper. In the next section, we'll see that this optimization is essential for implementing Donut MultiPaxos with good performance. Also note that this optimization is not particular to Donut Paxos. Paxos and MultiPaxos can both take advantage of this optimization.

4 Donut MultiPaxos

4.1 MultiPaxos

First, we summarize MultiPaxos. Whereas Paxos is a consensus protocol that agrees on a single value, **MultiPaxos** [17,40]

---

is a **state machine replication protocol** that agrees on a sequence, or "log" of values. MultiPaxos manages multiple **replicas** of a state machine. Clients send state machine commands to MultiPaxos, MultiPaxos places the commands in a totally ordered log, and state machine replicas execute the commands in log order. By beginning in the same initial state and executing the same commands in the same order, all deterministic state machine replicas are kept in sync.

Figure 4: An example execution of MultiPaxos ($f = 1$). The leader is adorned with a crown.

To agree on a log of commands, MultiPaxos implements one instance of Paxos for every log entry. The ith instance of Paxos chooses the command in log entry i. More concretely, a MultiPaxos deployment that tolerates f faults consists of an arbitrary number of clients, at least $f + 1$ proposers, a configuration C of acceptors which can tolerate f failures, and at least $f + 1$ replicas, as illustrated in Figure 4.

One of the proposers is elected leader in some round, say round i. We assume the leader knows that log entries up to and including log entry k_c have already been chosen (e.g., by communicating with the replicas). We call this log entry the **commit index**. The leader then runs Phase 1 of Paxos in round i for *every* log entry. Note that even though there are an infinite number of log entries larger than k_c, the leader can execute Phase 1 using a finite amount of information. In particular, the leader sends a single PHASE1A$\langle i \rangle$ message that acts as the PHASE1A message for every log entry larger than k_c. Also, an acceptor replies with a PHASE1B$\langle i, vr, vv \rangle$ message only for log entries in which the acceptor has voted. The infinitely many log entries in which the acceptor has not yet voted do not yield an explicit PHASE1B message.

Region 1:   Region 2:   Region 3:
(already chosen) (maybe chosen)   (not chosen)

Figure 5: A leader's knowledge of the log after Phase 1.

The leader's knowledge about the log after Phase 1 can be characterized by the commit index k_c and a **pending index**

---

[1]Note that given a round i, we denote the next largest round in the total ordered set of rounds $i + 1$. We call this the "next round".

k_p with $k_c \le k_p$, as shown in Figure 5. The commit index and pending index divide the log into three regions: a prefix of chosen log entries (Region 1), a suffix of unchosen log entries (Region 3), and a middle region of pending log entries (Region 2). More specifically:

- **Region 1** $[0, k_c]$**:** The leader knows that a command has been chosen in every log entry less than or equal to k_c.

- **Region 3** $[k_p + 1, \infty)$**:** The leader knows that no command has been chosen (in any round less than i) in any log entry larger than k_p.

- **Region 2** $[k_c + 1, k_p]$**:** If there is a command that *may* have already been chosen, then it appears between k_c and k_p. Region 2 may also contain some log entries in which the leader knows (from executing a previous round) that a value has already been chosen, and it may contain some log entries in which the leader knows (from counting votes in Phase 1) that no value has been chosen (we call these "holes").

After Phase 1, the leader sends a PHASE2A message for every unchosen log entry in Region 2, proposing a "no-op" command for the holes. Simultaneously, the leader begins accepting client requests. When a client wants to propose a state machine command, it sends the command to the leader. The leader assigns log entries to commands in increasing order, beginning at $k_p + 1$. It then runs Phase 2 of Paxos to get the command chosen in that entry in round i. Once the leader learns that a command has been chosen in a given log entry, it informs the replicas. Replicas insert chosen commands into their logs and execute the logs in prefix order, sending the results of execution back to the clients. This execution is illustrated in Figure 4.

It is critical to note that a leader performs Phase 1 of Paxos only once *per round*, not once *per command*. In other words, Phase 1 is not performed during normal operation. It is performed only when the leader fails and a new leader is elected in a larger round, an uncommon occurrence.

4.2 Donut MultiPaxos

We first extend Donut Paxos to Donut MultiPaxos with proactive matchmaking but without Phase 1 bypassing or garbage collection. We'll see how to incorporate these two momentarily in Section 4.4. The extension from Donut Paxos to Donut MultiPaxos is analogous to the extension of Paxos to MultiPaxos. Donut MultiPaxos reaches consensus on a totally ordered log of state machine commands, one log entry at a time, using one instance of Donut Paxos for every log entry.

More concretely, a Donut MultiPaxos deployment consists of an arbitrary number of clients, at least $f + 1$ proposers, a set of $2f + 1$ matchmakers, a dynamic set of acceptors (one configuration per round which can tolerate f failures), and a set of at least $f + 1$ state machine replicas. We assume, as is

standard, that a leader election algorithm is used to select one of the proposers as a stable leader in some round, say round i. The leader selects a configuration C_i of acceptors that it will use for *every* log entry. The mechanism by which the configuration is chosen is an orthogonal concern. A system administrator, for example, could send the configuration to the leader, or the configuration could be read from an external service. Throughout the paper, we do not depend any specific mechanism by which a configuration is chosen. We assume that proposers use some unspecified abstract process to select configurations.

The leader then executes the Matchmaking phase in the same way as in Donut Paxos (i.e. it sends MATCHA$\langle i, C_i \rangle$ messages to the matchmakers and awaits MATCHB$\langle i, H_i \rangle$ responses). After the Matchmaking phase completes, the leader executes Phase 1 for *every* log entry. This is identical to MultiPaxos, except that the leader uses the configurations returned by the matchmakers rather than assuming a fixed configuration. Note that proactive matchmaking allows the leader to execute the Matchmaking phase and Phase 1 before receiving any client requests.

The leader then enters Phase 2 and operates exactly as it would in MultiPaxos. It executes Phase 2 with C_i for the log entries in Region 2. Moreover, when it receives a state machine command from a client, it assigns the command a log entry in Region 3, runs Phase 2 with the acceptors in C_i, and informs the replicas when the command is chosen. Replicas execute commands in log order and send the results of executing commands back to the clients.

4.3 Discussion

To reconfigure from some old configuration C_{old} in round i to some new configuration C_{new}, the Donut MultiPaxos leader of round i simply advances to round $i + 1$ and selects the new configuration C_{new}. The new configuration is active immediately after the Matchmaking phase, a one round trip delay. Note that the acceptors in the new configuration C_{new} do not have to undergo any sort of warm up or bootstrapping and do not have to contact any other acceptors in any other configuration.

The new configuration is active immediately, but it is not safe to deactivate the acceptors in the old configuration immediately, as we saw in Section 3.5. We extend Donut Paxos's garbage collection to Donut MultiPaxos momentarily.

Also note that Donut MultiPaxos does *not* perform the Matchmaking phase or Phase 1 on the critical path of normal execution. Similar to how MultiPaxos executes Phase 1 only once per leader change (and not once per command), Donut MultiPaxos runs the Matchmaking phase and Phase 1 only when a new leader is elected or when a leader changes its round (e.g., when a leader transitions from round i to round $i + 1$ as part of a reconfiguration). In the normal case (i.e. during Phase 2), Donut MultiPaxos and MultiPaxos are identical,

(a) Matchmaking   (b) Phase 1   (c) Phase 2

Figure 6: An example Donut MultiPaxos reconfiguration without Phase 1 bypassing. The leader p_1 reconfigures from the acceptors a_1, a_2, a_3 to the acceptors b_1, b_2, b_3. Client commands are drawn as gray dashed lines. Note that every subfigure shows one phase of a reconfiguration using solid colored lines, but the dashed lines show the complete execution of a client request that runs concurrently with the reconfiguration. For simplicity, we assume that every proposer also serves as a replica.

and Donut MultiPaxos does not introduce *any* overheads. In the normal case, Donut MultiPaxos deploys a single stable leader that changes rounds only to perform a reconfiguration. Changing from one leader to another only happens after a leader has failed.

Furthermore, configurations do not have to be unique across rounds. The leader in round i is free to re-use a configuration C_j that was used in some round $j < i$.

Finally, because Donut MultiPaxos deploys more nodes than MultiPaxos, the mean time to failure is decreased, and it will take less time to reach f failures. However, this mean time to failure is many orders of magnitude larger than the time required to perform a reconfiguration. As long as failed machines are replaced via reconfiguration in a reasonable amount of time, it is unlikely to experience f or more failures.

4.4 Optimization

Ideally, Donut MultiPaxos' performance would be unaffected by a reconfiguration. The latency of every client request and the protocol's overall throughput would remain constant throughout a reconfiguration. Donut MultiPaxos as we've described it so far, however, does not meet this ideal. During a reconfiguration, a leader must temporarily stop processing client commands and wait for the reconfiguration to finish before resuming normal operation.

This is illustrated in Figure 6. Figure 6 shows a leader p_1 reconfiguring from a configuration of acceptors C_{old} consisting of acceptors a_1, a_2, and a_3 in round i to a new configuration of acceptors C_{new} consisting of acceptors b_1, b_2, and b_3 in round $i + 1$. While the leader performs the reconfiguration, clients continue to send state machine commands to the leader. We consider such a command and perform a case analysis on when the command arrives at the leader to see whether or not

the command has to be stalled.

Case 1: Matchmaking (Figure 6a). If the leader receives a command during the Matchmaking phase, then the leader can process the command as normal in round i using the acceptors in C_{old}. Even though the leader is executing the Matchmaking phase in round $i + 1$ and is communicating with the matchmakers, the acceptors in C_{old} are oblivious to this and can process commands in Phase 2 in round i.

Case 2: Phase 1 (Figure 6b). If the leader receives a command during Phase 1, then the leader cannot process the command. It must delay the processing of the command until Phase 1 finishes. Here's why. Once an acceptor in C_{old} receives a PHASE1A$\langle i + 1 \rangle$ message, it will reject any future commands in rounds less than $i + 1$, so the leader is unable to send the command to C_{old}. The leader also cannot send the command to C_{new} in round $i + 1$ because it has not yet finished executing Phase 1.

Case 3: Phase 2 (Figure 6c). If the leader receives a command during Phase 2, then the leader can send the command to the new acceptors in C_{new} in round $i + 1$. This is the normal case of execution.

In summary, any commands received during Phase 1 of a reconfiguration are delayed. Fortunately, we can eliminate this problem by using Phase 1 bypassing. Consider a leader performing a reconfiguration from C_i in round i to C_{i+1} in round $i + 1$. At the end of the Matchmaking phase and at the beginning of Phase 1 (in round $i + 1$), let k be the largest log entry that the leader has assigned to a command. That is, all log entries after entry k are empty. These log entries satisfy the preconditions of Phase 1 bypassing, so it is safe for the leader to bypass Phase 1 in round $i + 1$ for these log entries in the following way. When a leader receives a command after the Matchmaking phase, it assigns the command a log entry larger than k, skips Phase 1, and executes Phase 2 in round $i + 1$ with C_{new} immediately.

With this optimization and the round scheme described in Section 3.6, no state machine commands are delayed. Commands received during the Matchmaking phase or earlier are chosen in round i by C_{old} in log entries up to and including k. Commands received during Phase 1, Phase 2, or later are chosen in round $i+1$ by C_{new} in log entries $k+1, k+2, k+3$, and so on. With this optimization Donut MultiPaxos can be reconfigured with minimal performance degradation.

4.5   Garbage Collection

Recall that the Donut MultiPaxos leader p_i in round i uses a single configuration C_i for *every* log entry. The leader p_i can safely issue a GARBAGEA$\langle i \rangle$ command to the matchmakers once it ensures that *every* log entry satisfies one of the three scenarios described in Section 3.5. Recall from Figure 5 that at the end of Phase 1 and at the beginning of Phase 2, the log can be divided into three regions. Each of the three garbage collection scenarios applies to one of the regions.

Scenario 2 applies to Region 3. These are the log entries for which $k = -1$. Scenario 1 applies to Region 2, once the leader has successfully chosen commands in all of the log entries in Region 2. Scenario 3 applies to Region 1 if we make the following adjustments. First, we deploy $2f + 1$ replicas instead of $f + 1$. Second, the leader ensures that the prefix of previously chosen log entries is stored on at least $f + 1$ of the $2f + 1$ replicas. Third, the leader informs a Phase 2 quorum of C_i acceptors that these commands have been stored on the replicas. Every replica maintains a copy of the log of state machine commands and cannot discard a command after execution. The log must also be garbage collected over time, for example, by using snapshots [34]. Note that garbage collecting the log is an orthogonal (but also complicated) issue from garbage collecting old configurations. It must be done regardless of reconfigurations and is outside of the scope of this paper.

In summary, the leader p_i of round i executes as follows. It executes the Matchmaking phase to get the prior configurations H_i. It executes Phase 1 with the configurations in H_i. It enters Phase 2 and chooses commands in Region 2. It informs a Phase 2 quorum of C_i acceptors once the commands in Region 1 have been stored on $f + 1$ replicas. It issues a GARBAGEA$\langle i \rangle$ command to the matchmakers and awaits $f + 1$ GARBAGEB$\langle i \rangle$ responses. At this point, all previous configurations can be shut down.

Note that the leader can begin processing state machine commands from clients as soon as it enters Phase 2. It does not have to stall commands during garbage collection. Note also that during normal operation, old configurations are garbage collected very quickly. In Section 7, we show that H_i almost always contains a single configuration (i.e. C_{i-1}).

5   Reconfiguring Matchmakers

We've discussed how Donut MultiPaxos allows us to reconfigure the set of acceptors. In this section, we discuss how to reconfigure proposers, replicas, and matchmakers (themselves).

Reconfiguring proposers and replicas is straightforward. In fact, Donut MultiPaxos reconfigures proposers and replicas in exactly the same way as MultiPaxos [40], so we do not discuss it at length. In short, a proposer can be safely added or removed at any time. Replicas can also be safely added or removed at any time so long as we ensure that commands replicated on $f + 1$ replicas remain replicated on $f + 1$ replicas. This is a difficult, yet orthogonal challenge. Existing approaches can be adopted by Donut MultiPaxos [35]. For performance, a newly introduced proposer should contact an existing proposer or replica to learn about the prefix of already chosen commands, and a newly introduced replica should copy the log from an existing replica.

Reconfiguring matchmakers is a bit more involved, but still relatively straightforward. Recall that proposers perform the Matchmaking phase only during a change in round. Thus, for the vast majority of the time—specifically, when there is a single, stable leader—the matchmakers are completely idle. This means that the way we reconfigure the matchmakers has to be safe, but it doesn't have to be efficient. The matchmakers can be reconfigured at any time between round changes without any impact on the performance.

Thus, we use the simplest approach to reconfiguration: we shut down the old matchmakers and replace them with new ones, making sure that the new matchmakers' initial state is the same as the old matchmakers' final state. More concretely, we reconfigure from a set M_{old} of matchmakers to a new set M_{new} as follows. First, a proposer (or any other node) sends a STOPA$\langle \rangle$ message to the matchmakers in M_{old}. When a matchmaker m_i receives a STOPA$\langle \rangle$ message, it stops processing messages (except for other STOPA$\langle \rangle$ messages) and replies with STOPB$\langle L_i, w_i \rangle$ where L_i is m_i's log and w_i is its garbage collection watermark. When the proposer receives STOPB messages from $f + 1$ matchmakers, it knows that the matchmakers have effectively been shut down. It computes w as the maximum of every returned w_i. It computes L as the union of the returned logs, and removes all entries of L that appear in a round less than w. An example of this log merging is illustrated in Figure 7.

The proposer then sends L and w to all of the matchmakers in M_{new}. Each matchmaker adopts these values as its initial state. At this point, the matchmakers in M_{new} *cannot* begin processing commands yet. Naively, it is possible that two different nodes could simultaneously attempt to reconfigure to two disjoint sets of matchmakers, say M_{new} and M'_{new}.

To avoid this, every matchmaker in M_{old} doubles as a Paxos acceptor. A proposer attempting to reconfigure to M_{new} acts as a Paxos proposer and gets the value M_{new} chosen by the

Figure 7: An example of merging three matchmaker logs (L_0, L_1, and L_2) during a matchmaker reconfiguration. Garbage collected log entries are shown in red.

matchmakers (which are acting as Paxos acceptors). Once M_new is chosen, the proposer notifies the matchmakers in M_new that the reconfiguration is complete and that they are free to start processing commands.

If a proposer contacts a stale set of matchmakers (e.g., M_old), the matchmakers inform the proposer of their successors (e.g., M_new). This newer set of matchmakers may also be stale, so the proposer repeatedly polls stale matchmakers until it finds the active set of matchmakers. In this way, the matchmakers form a chain, with each set of matchmakers pointing to its successor.

Before a set of matchmakers can be shut down, the identity of its successors must be persisted in some name service (e.g., DNS). Ideally for performance, the name service would always point to the active set of matchmakers, but this is not required for safety.

6 Theoretical Insights

MultiPaxos To reconfigure from a set of nodes N to a new set of nodes N', a MultiPaxos leader gets the value N' chosen in the log at some index i. All commands in the log starting at position $i + \alpha$ are chosen using the nodes in N' instead of the nodes in N, where α is some configurable parameter. This protocol is called **Horizontal MultiPaxos**.

Figure 8: A MultiPaxos log during reconfiguration ($\alpha = 4$).

Donut MultiPaxos has the following advantages over Horizontal MultiPaxos. First, the core idea behind Horizontal MultiPaxos seems simple, but the protocol has a number of hidden subtleties [27]. For example, a newly elected Horizontal MultiPaxos leader with a stale log may not know the latest

configuration of nodes. It may not even know which configuration of nodes to contact to learn the latest configuration of nodes. This makes it unclear when it is safe to shut down old configurations because a newly elected Horizontal Multi-Paxos leader can be arbitrarily out of date. These subtleties and the many others described in [27] makes Horizontal MultiPaxos significantly more complicated than it initially seems. Donut Paxos addresses these subtleties directly. The matchmakers can always be used to learn the latest configuration, and our garbage collection protocol details exactly when and how to shut down old configurations safely.

Second, horizontal reconfiguration is not generally applicable. It is fundamentally incompatible with replication protocols that do not replicate a log. Moreover, researchers are finding that avoiding a log can often be advantageous [2, 8, 18, 31, 38, 39, 41]. For example, protocols like Generalized Paxos [18], EPaxos [31], Atlas [8], and Caesar [2] arrange commands in a partially ordered graph instead of a totally ordered log to exploit commutativity between commands. CASPaxos [38] maintains a single value, instead of a log or graph, for simplicity. Databases like TAPIR [41] avoid ordering transactions in a log for improved performance, and databases like Meerkat [39] do the same to improve scalability. Even some protocols with logs cannot use the ideas behind Horizontal MultiPaxos. For example, Raft cannot safely perform Horizontal MultiPaxos' reconfiguration [34].

Because these protocols do not replicate logs, they cannot use MultiPaxos' horizontal reconfiguration protocol. However, while none of the protocols replicate logs, *all* of them have rounds. This means that the protocols can either use Donut Paxos directly, or at least borrow ideas from Donut Paxos for reconfiguration. For example, we are developing a protocol called BPaxos that is an EPaxos [31] variant which partially orders commands into a graph. BPaxos is a modular protocol that uses Paxos as a black box subroutine. Due to this modularity, we can directly replace Paxos with Donut Paxos to support reconfiguration. The same idea can also be applied to EPaxos. CASPaxos [38] is similar to Paxos and can be extended to Matchmaker CASPaxos in the same way we extended Paxos to Donut Paxos. These are two simple examples, and we don't claim that extending Donut Paxos to some of the other more complicated protocols is always easy. But, the universality of rounds makes Donut Paxos an attractive foundation on top of which other non-log based protocols can build their own reconfiguration protocols.

One could argue that these other protocols are not used as much in industry, so it's not that important for them to have reconfiguration protocols, but we think the causation is in the reverse direction! Without reconfiguration, these protocols cannot be used in industry.

Third, optimizing Horizontal MultiPaxos is not easy. A MultiPaxos leader can process at most α unchosen commands at a time. This makes α an important parameter to tune. If we set α too low, then we limit the protocol's pipeline parallelism

and the throughput suffers. Note that a small α reduces the *normal case* throughput of Horizontal MultiPaxos, not just the throughput during reconfiguration. If we set α too high, then we have to wait a long time for a reconfiguration to complete. If we are reconfiguring because of a failed node, then we might have to endure a long reconfiguration with reduced throughput. Donut MultiPaxos has no α parameter to tune. Note that Horizontal MultiPaxos can be implemented with an optimization in which we select a very large α and then get a sequence of α noops in the log to force a quick reconfiguration. This optimization helps avoid the difficulties of finding a good value of α, but the optimization introduces a new set of subtleties into the protocol. For example, the leader cannot process client requests while it is executing Phase 2 for the α noops. The protocol has to implement additional mechanisms to avoid this one round trip stall.

Fourth, Horizontal MultiPaxos requires a Phase 1 and Phase 2 quorum of acceptors from an old configuration in order to perform a reconfiguration after a leader failure, but Donut MultiPaxos only requires a Phase 1 quorum. Some read optimized MultiPaxos variants perform reads against Phase 1 quorums [5]. These protocols benefit from having very small Phase 1 quorums and very large Phase 2 quorums, requiring Horizontal MultiPaxos to contact far more nodes than Donut MultiPaxos during a reconfiguration.

Finally, we clarify that if Horizontal MultiPaxos is implemented with all of its subtleties ironed out, is deployed with a good choice of α, and is run with small Phase 2 quorums, then it can perform a reconfiguration without performance degradation. In this case, Horizontal MultiPaxos and Donut MultiPaxos both reconfigure, in some sense, "optimally".

Horizontal MultiPaxos also has some advantages over Donut MultiPaxos. For example, reconfiguring the set of matchmakers is simple, but it is still another reconfiguration protocol that has to be implemented which adds complexity to the system.

Vertical Paxos Donut MultiPaxos significantly improves the practicality of Vertical Paxos [22] in a number of ways. First, Vertical Paxos is a consensus protocol, not a state machine replication protocol, and it's not easy to extend Vertical Paxos' garbage collection protocol to a state machine replication protocol. Vertical Paxos garbage collects old configurations in situations similar to Scenario 1 and Scenario 2 from Section 3.5. It does not include Scenario 3. Without this, old configurations cannot be garbage collected, which means that it is never safe to shut down old configurations.

Second, Vertical Paxos requires an external master but does not describe how to implement the master in an efficient way. We could implement the master using another state machine replication protocol like MultiPaxos, but this would be both slow and overly complex. Plus, we would have to implement a reconfiguration protocol for the master as well. Our matchmakers are analogous to the external master but

show that such a master does not require a nested invocation of state machine replication.

Third, Vertical Paxos requires that a proposer execute Phase 1 in order to perform a reconfiguration. Thus, Vertical Paxos cannot be extended to MultiPaxos without causing performance degradation during reconfiguration. This is not the case for matchmakers thanks to Phase 1 bypassing.

Fourth, Vertical Paxos does not describe how proposers learn the configurations used in previous rounds and instead assumes that configurations are fixed in advance by an oracle. Donut Paxos shows that this assumption is not necessary, as the matchmakers store every configuration.

Fast Paxos Fast Paxos [19] is a Paxos variant that shaves off one network delay from Paxos in the best case, but can have higher delays if concurrently proposed commands conflict. While Paxos quorums consist of $f+1$ out of $2f+1$ acceptors, Fast Paxos requires larger quorums. Many protocols have reduced Fast Paxos quorum sizes a bit, but to date, Fast Paxos quorum sizes have remained larger than classic Paxos quorum sizes [8, 31]. Using matchmakers, we can implement Fast Paxos with a fixed set of $f+1$ acceptors (and hence with $f+1$-sized quorums). Specifically, we deploy Fast Paxos with $f+1$ acceptors, with a single unanimous Phase 2 quorum, and with singleton Phase 1 quorums. A full description of the protocol and a proof of correctness is given in Section C.

DPaxos DPaxos is a Paxos variant that allows every round to use a different subset of acceptors from some fixed set of acceptors. Donut Paxos obviates the need for a fixed set of nodes. DPaxos' scope is limited to a single instance of consensus, whereas Donut MultiPaxos shows how to efficiently reconfigure across multiple instances of consensus simultaneously. We also discovered that DPaxos' garbage collection algorithm is unsafe. Donut MultiPaxos fixes the bug. See Section D for details.

7 Evaluation

We now evaluate Donut MultiPaxos. Donut MultiPaxos is implemented in Scala using the Netty networking library. We deployed Donut MultiPaxos on m5.xlarge AWS EC2 instances within a single availability zone. We deploy Donut MultiPaxos with $f=1$, $f+1$ proposers, $2f+1$ acceptors, $2f+1$ matchmakers, and $2f+1$ replicas. For simplicity, every node is deployed on its own machine, but in practice, nodes can be physically co-located. In particular, any two logical roles can be placed on the same machine, so long as the two roles are not the same. For example, we can co-locate a leader, an acceptor, a replica, and a matchmaker, but we can't co-locate two acceptors (without reducing the fault tolerance of the system). For simplicity, we deploy Donut MultiPaxos with a trivial no-op state machine in which every

Table 1: Figure 9 median, interquartile range, and standard deviation of latency and throughput.

	Latency (ms)					
	1 Client		4 Clients		8 Clients	
	0s-10s	10s-20s	0s-10s	10s-20s	0s-10s	10s-20s
median	0.292	0.287	0.317	0.321	0.398	0.410
IQR	0.040	0.026	0.029	0.036	0.036	0.039
stdev	0.114	0.085	0.076	0.081	0.089	0.305

	Throughput (commands/second)					
	1 Client		4 Clients		8 Clients	
	0s-10s	10s-20s	0s-10s	10s-20s	0s-10s	10s-20s
median	2,995	3,177	11,874	11,478	19,146	18,446
IQR	152	53	175	145	140	373
stdev	157	111	298	307	358	520

state machine command is a one byte no-op. All of our results generalize to more complex state machines as well (the choice of state machine is orthogonal to reconfiguration).

7.1 Reconfiguration

Experiment Description. We run a benchmark with 1, 4, and 8 clients. Every client executes in a closed loop. It repeatedly proposes a state machine command, waits to receive a response, and then immediately proposes another command. This model is standard for state machine replication protocols [25, 31, 36] and aligns with the definitions surrounding linearizability [11]. Every benchmark runs for 35 seconds. During the first 10 seconds, we perform no reconfigurations. From 10 seconds to 20 seconds, the leader reconfigures the set of acceptors once every second. In practice, we would reconfigure much less often. This is a worst case stress test for Donut MultiPaxos. For each of the ten reconfigurations, the leader selects a random set of $2f + 1$ acceptors from a pool of $2 \times (2f + 1)$ acceptors. At 25 seconds, we fail one of the acceptors. 5 seconds later, the leader performs a reconfiguration to replace the failed acceptor. The delay of 5 seconds is completely arbitrary. The leader can reconfigure sooner if desired.

We also perform this experiment with an implementation of MultiPaxos with horizontal reconfiguration. As with Donut MultiPaxos, we deploy MultiPaxos with $f + 1$ proposers, $2f + 1$ acceptors, and $2f + 1$ replicas. We set α to 8. Because α is equal to the number of clients, MultiPaxos never stalls because of an insufficiently large α. We do not implement the noop optimization.

Results. The latency and throughput of Donut MultiPaxos are shown in Figure 9. Throughput and latency are both computed using sliding one second windows. Median latency is shown using solid lines, while the 95% latency is shown as a shaded region above the median latency. The black vertical

Figure 9: Donut MultiPaxos' latency and throughput ($f = 1$). Median latency is shown using solid lines, while the 95% latency is shown as a shaded region above the median latency. The vertical black lines show reconfigurations. The vertical dashed red line shows an acceptor failure.

lines denote reconfigurations, and the red dashed vertical line denotes the acceptor failure.

The medians, interquartile ranges (IQR), and standard deviations of the latency and throughput (a) during the first 10 seconds and (b) between 10 and 20 seconds are shown in Table 1. Figure 12 includes violin plots of the same data. The white circles show the median values, while the thick black rectangles show the 25th and 75th percentiles. For latency, reconfiguration has little to no impact (roughly 2% changes) on the medians, IQRs, or standard deviations. The one exception is that the 8 client standard deviation is significantly larger. This is due to a small number of outliers. Reconfiguration has little impact on median throughput, with all differences being statistically insignificant. The IQRs and standard deviations sometimes increase and sometimes decrease. The IQR is always less than 1% of the median throughput, and the standard deviation is always less than 4%.

For every reconfiguration, the new acceptors become active within a millisecond. The old acceptors are garbage collected within five milliseconds. This means that only one configuration is ever returned by the matchmakers. We implement Donut MultiPaxos with an optimization called thriftiness [31]—where PHASE2A messages are sent to a randomly selected Phase 2 quorum—so the throughput and latency expectedly degrade after we fail an acceptor. After we replace the failed acceptor, throughput and latency return to normal within two seconds.

The latency and throughput of MultiPaxos is shown in Figure 10. As with Donut MultiPaxos, MultiPaxos can perform a horizontal reconfiguration without any performance degra-

Figure 10: The latency and throughput of MultiPaxos with horizontal reconfiguration ($f = 1$).

dation. The difference in absolute throughput between the two protocols is due to minor implementation differences, but the variance in throughput (rather than the throughput itself) is what is important for this evaluation. We include the comparison to MultiPaxos for the sake of having some baseline against which we can compare Donut MultiPaxos, but the comparison is shallow. For this reason, we do not elaborate on the results much.

While Donut MultiPaxos does provide performance benefits over MultiPaxos' and Raft's reconfiguration protocols, our goal is not to replace these protocols. Rather, there are dozens of other state machine replication protocols (e.g., EPaxos [31], CASPaxos [38], Caesar [2], Atlas [8]) and distributed databases (e.g., TAPIR [41], Janus [32], Ocean Vista [9]) that do not have any reconfiguration protocol and cannot use the existing reconfiguration protocols from Multi-Paxos or Raft. Our hope is that the ideas in Donut MultiPaxos can be used to implement reconfiguration protocols for these other systems. For this reason, it is difficult to compare Donut MultiPaxos against some existing baseline because they simply do not exist.

Summary. This experiment confirms that Donut Multi-Paxos's throughput and latency remain steady even during abnormally frequent reconfiguration. Moreover, it confirms that Donut MultiPaxos can reconfigure to a new set of acceptors and retire the old set of acceptors on the order of milliseconds.

7.2 Leader Failure

Experiment Description. We deploy Donut MultiPaxos exactly as before. Now, each benchmark runs for 20 seconds. During the first 7 seconds, there are no reconfigurations and

Figure 11: Violin plots of Figure 9 latency and throughput during the first 10 seconds and between 10 and 20 seconds.

no failures. At 7 seconds, we fail the leader. 5 seconds later, a new leader is elected and resumes normal operation. The 5 second delay is arbitrary; a new leader could be elected quicker if desired.

Results. The latency and throughput of the benchmarks are shown in Figure 13. During the first 7 seconds, throughput and latency are both stable. When the leader fails, the throughput expectedly drops to zero. The throughput and latency return to normal within two seconds after a new leader is elected. The results for the same experiment, repeated with Horizontal MultiPaxos, are shown in Figure 14.

Summary. This experiment confirms that the extra latency of the Matchmaker phase during a leader change is negligible.

7.3 Matchmaker Reconfiguration

Experiment Description. We deploy Donut MultiPaxos as above. We again run three benchmarks with 1, 4, and 8 clients. Each benchmark runs for 40 seconds. During the first 10 seconds, there are no reconfigurations and no failures. Between 10 and 20 seconds, the leader reconfigures the set of matchmakers once every second. Every reconfiguration randomly selects $2f + 1$ matchmakers from a set of $2 \times (2f + 1)$ matchmakers. At 25 seconds, we fail a matchmaker. At 30 we perform a matchmaker reconfiguration to replace the failed matchmaker. At 35 seconds, we reconfigure the acceptors.

Results. The latency and throughput of Donut MultiPaxos are shown in Figure 15. The latency and throughput of the protocol remain steady through the first ten matchmaker reconfigurations, through the matchmaker failure and recovery, and through the acceptor reconfiguration. This is confirmed

Figure 12: Violin plots of Figure 10 latency and throughput during the first 10 seconds and between 10 and 20 seconds.

Figure 13: Donut MultiPaxos' latency and throughput ($f = 1$). The dashed red line denotes a leader failure.

Table 2: Figure 15 median, interquartile range, and standard deviation of latency and throughput.

	Latency (ms)					
	1 Client		4 Clients		8 Clients	
	0s-10s	10s-20s	0s-10s	10s-20s	0s-10s	10s-20s
median	0.297	0.292	0.314	0.313	0.404	0.398
IQR	0.032	0.024	0.031	0.030	0.035	0.028
stdev	0.077	0.061	0.093	0.098	0.383	0.067

	Throughput (commands/second)					
	1 Client		4 Clients		8 Clients	
	0s-10s	10s-20s	0s-10s	10s-20s	0s-10s	10s-20s
median	3019	3147	11631	11726	18569	19248
IQR	41	51	140	145	391	71
stdev	66	72	250	231	478	159

by the medians, IQRs, and standard deviations of the latency and throughput during the first 10 seconds and between 10 and 20 seconds, which are shown in Table 2.

Summary. This benchmark confirms that matchmakers are off the critical path. The latency and throughput of Donut MultiPaxos remains steady during a matchmaker reconfiguration and matchmaker failure. Moreover, a matchmaker reconfiguration does not affect the performance of subsequent acceptor reconfigurations.

8 Related Work

SMART. SMART [27] is a reconfiguration protocol that resolves many ambiguities in MultiPaxos' horizontal approach (e.g., when it is safe to retire old configurations). Like MultiPaxos' horizontal reconfiguration protocol, SMART can reconfigure a protocol with minimal performance degradation. SMART differs from Donut Paxos in a number of ways. First, like MultiPaxos' horizontal reconfiguration protocol, SMART is fundamentally log based and is therefore incompatible with many sophisticated state machine replication protocols. Second, SMART assumes that acceptors and replicas are always co-located. This prevents us from reconfiguring the acceptors without reconfiguring the replicas. This is not ideal since we can reconfigure an acceptor without copying any state, but must transfer logs from an old replica to a new replica. SMART's garbage collection also has higher latency that Donut Paxos' garbage collection. For Scenario 3, Donut Paxos proposers wait until a prefix of the log is stored on $f + 1$ replicas. SMART waits for the prefix of the log to be executed and snapshotted by $f + 1$ replicas.

Cheap Paxos. Cheap Paxos [24] is a MultiPaxos variant that consists of a fixed set of $f + 1$ main acceptors and f auxiliary acceptors. During failure-free execution (the normal case), only the main acceptors are contacted. The auxiliary acceptors perform MultiPaxos' horizontal reconfiguration protocol to replace failed main acceptors. As with Fast Paxos, we can deploy Donut MultiPaxos with only $f + 1$ acceptors, f fewer than Cheap Paxos. Donut Paxos does require $2f + 1$ matchmakers, but matchmakers do not act as acceptors and have to process only a single message (i.e. a MATCHA message) to perform a reconfiguration.

Raft. Raft [35] uses a reconfiguration protocol called joint consensus. Like MultiPaxos' horizontal reconfiguration, joint consensus is log-based and therefore incompatible with many existing replication protocols. A simpler reconfiguration protocol for Raft was proposed in [34] but requires more rounds

Figure 14: The latency and throughput of Horizontal Multi-Paxos with $f = 1$.

Figure 15: The latency and throughput of Donut MultiPaxos ($f = 1$). The dotted blue, dashed red, and vertical black lines show matchmaker reconfigurations, a matchmaker failure, and an acceptor reconfiguration respectively.

of communication.

Viewstamped Replication (VR). VR [26] uses a stop-the-world approach to reconfiguration. During a reconfiguration, the entire protocol stops processing commands. Thus, while the reconfiguration is quite simple, it is inefficient. Stoppable Paxos [21] is similar to MultiPaxos' horizontal reconfiguration, but also uses a stop-the-world approach. VR's stop-the-world approach to reconfiguration is also adopted by databases built on VR, including TAPIR [41] and Meerkat [39]. We use a similar approach to reconfigure matchmakers, but because matchmakers are off the critical path, the performance overheads are invisible.

Fast Paxos Coordinated Recovery. Fast Paxos has an optimization called coordinated recovery that is similar to Phase 1 Bypassing. The main difference is that in coordinated recovery, a leader uses Phase 2 information in round i to skip Phase 1 in round $i+1$, whereas with Phase 1 Bypassing, the leader instead uses Phase 1 information. Note that coordinated recovery is not useful for Donut MultiPaxos. It is subsumed by Phase 1 Bypassing. Coordinated recovery is only needed for Fast Paxos because the leader may not know which values were proposed in a round it owns. Phase 1 Bypassing cannot be applied to Fast Paxos for pretty much the same reason.

DynaStore. Vertical Paxos assumes its external master is implemented using state machine replication. MultiPaxos' horizontal reconfiguration also depends on consensus. Donut Paxos does not require consensus to implement matchmakers, but we are not the first to notice this. DynaStore [1] showed that reconfiguring atomic storage does not require consensus.

ZooKeeper. ZooKeeper, a distributed coordinated service, which uses ZooKeeper Atomic Broadcast [14] is a protocol similar to MultiPaxos that can also reconfigure quickly after leader failures.

9 Conclusion

We presented Donut Paxos and Donut MultiPaxos to address the lack of research on the increasingly important topic of reconfiguration. Our protocols achieve a number of desirable properties, both theoretical and practical: they can reconfigure without performance degradation, they provide insights into existing protocols, and they generalize better than existing techniques.

References

[1] Marcos K Aguilera, Idit Keidar, Dahlia Malkhi, and Alexander Shraer. Dynamic atomic storage without consensus. *Journal of the ACM (JACM)*, 58(2):1–32, 2011.

[2] Balaji Arun, Sebastiano Peluso, Roberto Palmieri, Giuliano Losa, and Binoy Ravindran. Speeding up consensus by chasing fast decisions. In *2017 47th Annual IEEE/IFIP International Conference on Dependable Systems and Networks (DSN)*, pages 49–60. IEEE, 2017.

[3] Martin Biely, Zarko Milosevic, Nuno Santos, and Andre Schiper. S-paxos: Offloading the leader for high throughput state machine replication. In *2012 IEEE 31st Symposium on Reliable Distributed Systems*, pages 111–120. IEEE, 2012.

[4] Mike Burrows. The chubby lock service for loosely-coupled distributed systems. In *Proceedings of the*

7th Symposium on Operating Systems Design and Implementation, OSDI '06, page 335–350, USA, 2006. USENIX Association.

[5] Aleksey Charapko, Ailidani Ailijiang, and Murat Demirbas. Linearizable quorum reads in paxos. In *11th USENIX Workshop on Hot Topics in Storage and File Systems (HotStorage 19)*, 2019.

[6] Christos Chrysafis, Ben Collins, Scott Dugas, Jay Dunkelberger, Moussa Ehsan, Scott Gray, Alec Grieser, Ori Herrnstadt, Kfir Lev-Ari, Tao Lin, et al. Foundationdb record layer: A multi-tenant structured datastore. In *Proceedings of the 2019 International Conference on Management of Data*, pages 1787–1802, 2019.

[7] James C Corbett, Jeffrey Dean, Michael Epstein, Andrew Fikes, Christopher Frost, Jeffrey John Furman, Sanjay Ghemawat, Andrey Gubarev, Christopher Heiser, Peter Hochschild, et al. Spanner: Google's globally distributed database. *ACM Transactions on Computer Systems (TOCS)*, 31(3):1–22, 2013.

[8] Vitor Enes, Carlos Baquero, Tuanir França Rezende, Alexey Gotsman, Matthieu Perrin, and Pierre Sutra. State-machine replication for planet-scale systems. In *Proceedings of the Fifteenth European Conference on Computer Systems*, pages 1–15, 2020.

[9] Hua Fan and Wojciech Golab. Ocean vista: gossip-based visibility control for speedy geo-distributed transactions. *Proceedings of the VLDB Endowment*, 12(11):1471–1484, 2019.

[10] Michael J Fischer, Nancy A Lynch, and Michael S Paterson. Impossibility of distributed consensus with one faulty process. *Journal of the ACM (JACM)*, 32(2):374–382, 1985.

[11] Maurice P Herlihy and Jeannette M Wing. Linearizability: A correctness condition for concurrent objects. *ACM Transactions on Programming Languages and Systems (TOPLAS)*, 12(3):463–492, 1990.

[12] Heidi Howard. *Distributed consensus revised*. PhD thesis, University of Cambridge, 2019.

[13] Heidi Howard, Dahlia Malkhi, and Alexander Spiegelman. Flexible paxos: Quorum intersection revisited. In *20th International Conference on Principles of Distributed Systems (OPODIS 2016)*. Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, 2017.

[14] Flavio P Junqueira, Benjamin C Reed, and Marco Serafini. Zab: High-performance broadcast for primary-backup systems. In *2011 IEEE/IFIP 41st International Conference on Dependable Systems & Networks (DSN)*, pages 245–256. IEEE, 2011.

[15] Kubernetes. Kubernetes. https://kubernetes.io. accessed: 2020-03-01.

[16] Cockroach Labs. CockroachDB. https://www.cockroachlabs.com/. accessed: 2020-03-01.

[17] Leslie Lamport. The part-time parliament. *ACM Transactions on Computer Systems (TOCS)*, 16(2):133–169, 1998.

[18] Leslie Lamport. Generalized consensus and paxos. *Technical Report MSR-TR-2005-33, Microsoft Research*, 2005.

[19] Leslie Lamport. Fast paxos. *Distributed Computing*, 19(2):79–103, 2006.

[20] Leslie Lamport et al. Paxos made simple. *ACM Sigact News*, 32(4):18–25, 2001.

[21] Leslie Lamport, Dahlia Malkhi, and Lidong Zhou. Stoppable paxos. *TechReport, Microsoft Research*, 2008.

[22] Leslie Lamport, Dahlia Malkhi, and Lidong Zhou. Vertical paxos and primary-backup replication. In *Proceedings of the 28th ACM symposium on Principles of distributed computing*, pages 312–313, 2009.

[23] Leslie Lamport, Dahlia Malkhi, and Lidong Zhou. Reconfiguring a state machine. *SIGACT News*, 41(1):63–73, 2010.

[24] Leslie Lamport and Mike Massa. Cheap paxos. In *International Conference on Dependable Systems and Networks, 2004*, pages 307–314. IEEE, 2004.

[25] Jialin Li, Ellis Michael, Naveen Kr Sharma, Adriana Szekeres, and Dan RK Ports. Just say NO to paxos overhead: Replacing consensus with network ordering. In *12th USENIX Symposium on Operating Systems Design and Implementation (OSDI 16)*, pages 467–483, 2016.

[26] Barbara Liskov and James Cowling. Viewstamped replication revisited. *MIT-CSAIL-TR-2012-021*, 2012.

[27] Jacob R Lorch, Atul Adya, William J Bolosky, Ronnie Chaiken, John R Douceur, and Jon Howell. The smart way to migrate replicated stateful services. In *Proceedings of the 1st ACM SIGOPS/EuroSys European Conference on Computer Systems 2006*, pages 103–115, 2006.

[28] Yanhua Mao, Flavio P. Junqueira, and Keith Marzullo. Mencius: Building efficient replicated state machines for wans. In *Proceedings of the 8th USENIX Conference on Operating Systems Design and Implementation*, OSDI'08, page 369–384, USA, 2008. USENIX Association.

[29] Parisa Jalili Marandi, Marco Primi, Nicolas Schiper, and Fernando Pedone. Ring paxos: A high-throughput atomic broadcast protocol. In *2010 IEEE/IFIP International Conference on Dependable Systems & Networks (DSN)*, pages 527–536. IEEE, 2010.

[30] Iulian Moraru, David G Andersen, and Michael Kaminsky. A proof of correctness for egalitarian paxos. Technical report, Technical report, Parallel Data Laboratory, Carnegie Mellon University, 2013.

[31] Iulian Moraru, David G Andersen, and Michael Kaminsky. There is more consensus in egalitarian parliaments. In *Proceedings of the Twenty-Fourth ACM Symposium on Operating Systems Principles*, pages 358–372, 2013.

[32] Shuai Mu, Lamont Nelson, Wyatt Lloyd, and Jinyang Li. Consolidating concurrency control and consensus for commits under conflicts. In *12th USENIX Symposium on Operating Systems Design and Implementation (OSDI 16)*, pages 517–532, 2016.

[33] Faisal Nawab, Divyakant Agrawal, and Amr El Abbadi. Dpaxos: Managing data closer to users for low-latency and mobile applications. In *Proceedings of the 2018 International Conference on Management of Data*, pages 1221–1236. ACM, 2018.

[34] Diego Ongaro. *Consensus: Bridging theory and practice*. PhD thesis, Stanford University, 2014.

[35] Diego Ongaro and John Ousterhout. In search of an understandable consensus algorithm. In *2014 USENIX Annual Technical Conference (USENIX ATC 14)*, pages 305–319, 2014.

[36] Dan RK Ports, Jialin Li, Vincent Liu, Naveen Kr Sharma, and Arvind Krishnamurthy. Designing distributed systems using approximate synchrony in data center networks. In *12th USENIX Symposium on Networked Systems Design and Implementation (NSDI 15)*, pages 43–57, 2015.

[37] Sajjad Rizvi, Bernard Wong, and Srinivasan Keshav. Canopus: A scalable and massively parallel consensus protocol. In *Proceedings of the 13th International Conference on emerging Networking EXperiments and Technologies*, pages 426–438, 2017.

[38] Denis Rystsov. Caspaxos: Replicated state machines without logs. *arXiv preprint arXiv:1802.07000*, 2018.

[39] Adriana Szekeres, Michael Whittaker, Jialin Li, Sharma Naveen, Arvind Krishnamurthy, Dan Ports, and Irene Zhang. Meerkat: Multicore-scalable replicated transactions following the zero-coordination principle. In *Proceedings of the Fourteenth EuroSys Conference 2020*, 2020.

[40] Robbert Van Renesse and Deniz Altinbuken. Paxos made moderately complex. *ACM Computing Surveys (CSUR)*, 47(3):1–36, 2015.

[41] Irene Zhang, Naveen Kr Sharma, Adriana Szekeres, Arvind Krishnamurthy, and Dan RK Ports. Building consistent transactions with inconsistent replication. *ACM Transactions on Computer Systems (TOCS)*, 35(4):1–37, 2018.

A Garbage Collection Safety

To prove that the three scenarios from Section 3.5 are safe, we repeat the safety proof from Section 3. The new bits are shown in blue.

Proof. We prove, for every round i, the statement $P(i)$: "if a proposer proposes a value v in round i (i.e. sends a PHASE2A message for value v in round i), then no value other than v has been or will be chosen in any round less than i." At most one value is ever proposed in a given round, so at most one value is ever chosen in a given round. Thus, $P(i)$ suffices to prove that Donut Paxos is safe for the following reason. Assume for contradiction that Donut Paxos chooses distinct values x and y in rounds j and i with $j < i$. Some proposer must have proposed y in round i, so $P(i)$ ensures us that no value other than y could have been chosen in round j. But, x was chosen, a contradiction.

We prove $P(i)$ by strong induction on i. $P(0)$ is vacuous because there are no rounds less than 0. For the general case $P(i)$, we assume $P(0), \ldots, P(i-1)$. We perform a case analysis on the proposer's pseudocode (Algorithm 3). Either k is -1 or it is not (line 11). First, assume it is not. In this case, the proposer proposes x, the value proposed in round k (line 12). We perform a case analysis on round j to show that no value other than x has been or will be chosen in any round $j < i$.

Case 1: $j > k$. We show that no value has been or will be chosen in round j. Recall that at the end of the Matchmaking phase, the proposer computed the set H_i of prior configurations using responses from a set M_i of $f + 1$ matchmakers. Either H_i contains a configuration C_j in round j or it doesn't.

First, suppose it does. Then, the proposer sent PHASE1A$\langle i \rangle$ messages to all of the acceptors in C_j. A Phase 1 quorum of these acceptors, say Q, all received PHASE1A$\langle i \rangle$ messages and replied with PHASE1B messages. Thus, every acceptor in Q set its round r to i, and in doing so, promised to never vote in any round less than i. Moreover, none of the acceptors in Q had voted in any round greater than k. So, every acceptor in Q has not voted and never will vote in round j. For a value v' to be chosen in round j, it must receive votes from some Phase 2 quorum Q' of round j acceptors. But, Q and Q' necessarily intersect, so this is impossible. Thus, no value has been or will be chosen in round j.

Now suppose that H_i does *not* contain a configuration for round j. Either a configuration C_j was garbage collected from H_i or it wasn't. First, assume it wasn't. Then, H_i is the union of $f+1$ MATCHB messages from the $f+1$ matchmakers in M_i. Thus, if H_i does not contain a configuration for round j, then none of the MATCHB messages did either. This means that for every matchmaker $m \in M_i$, when m received MATCHA$\langle i, C_i \rangle$, it did not contain a configuration for round j in its log and never did. Moreover, by processing the MATCHA$\langle i, C_i \rangle$ request and inserting C_i in log entry i, the matchmaker is guaranteed to never process a MATCHA$\langle j, C_j \rangle$ request in the future. Thus, every matchmaker in M_i has not processed a MATCHA request in round j and never will. For a value to be chosen in round j, the proposer executing round j must first receive replies from $f+1$ matchmakers, say M_j, in round j. But, M_i and M_j necessarily intersect, so this is impossible. Thus, no value has been or will be chosen in round j.

Otherwise, a configuration C_j was garbage collected from H_i. Note that none of the matchmakers in M_i had received a GARBAGEA$\langle i' \rangle$ command for a round $i' > i$ when they responded with their MATCHB messages. If they had, they would have ignored our MATCHA$\langle i, C_i \rangle$ message. Let i' be the largest round $j < i' < i$ such that a matchmaker in M_i had received a GARBAGEA$\langle i' \rangle$ message before responding to our MATCHA$\langle i, C_i \rangle$ message.

If i' was garbage collected because of Scenario 1, then k would be at least as large as i' since we would have intersected the Phase 2 quorum of $C_{i'}$ used in round i' to get a value chosen. But $k < j < i'$, a contradiction. If i' was garbage collected because of Scenario 2, then we know no value has been or will be chosen in round j. If i' was garbage collected because of Scenario 3, then we would have intersected the Phase 2 quorum of $C_{i'}$ that knows a value was already chosen, and we would have not proposed a value in the first place. But, we proposed x, a contradiction.

Case 2: $j = k$. In a given round, at most one value is proposed, let alone chosen. x is *the* value proposed in round k, so no other value could be chosen in round k.

Case 3: $j < k$. By induction, $P(k)$ states that no value other than x has been or will be chosen in any round less than k. This includes round j.

Finally, if k is -1, then we are in the same situation as in Case 1. No value has or will be chosen in a round $j < i$. $\square$

B Matchmaker Reconfiguration Safety

We repeat the safety proof from Section A. The new bits are shown in blue.

Proof. We prove, for every round i, the statement $P(i)$: "if a proposer proposes a value v in round i (i.e. sends a PHASE2A message for value v in round i), then no value other than v has been or will be chosen in any round less than i." At most one

value is ever proposed in a given round, so at most one value is ever chosen in a given round. Thus, $P(i)$ suffices to prove that Donut Paxos is safe for the following reason. Assume for contradiction that Donut Paxos chooses distinct values x and y in rounds j and i with $j < i$. Some proposer must have proposed y in round i, so $P(i)$ ensures us that no value other than y could have been chosen in round j. But, x was chosen, a contradiction.

We prove $P(i)$ by strong induction on i. $P(0)$ is vacuous because there are no rounds less than 0. For the general case $P(i)$, we assume $P(0), \ldots, P(i-1)$. We perform a case analysis on the proposer's pseudocode (Algorithm 3). Either k is -1 or it is not (line 11). First, assume it is not. In this case, the proposer proposes x, the value proposed in round k (line 12). We perform a case analysis on round j to show that no value other than x has been or will be chosen in any round $j < i$.

Case 1: $j > k$. We show that no value has been or will be chosen in round j. Recall that at the end of the Matchmaking phase, the proposer computed the set H_i of prior configurations using responses from a set M_i of $f+1$ matchmakers. Either H_i contains a configuration C_j in round j or it doesn't.

First, suppose it does. Then, the proposer sent PHASE1A$\langle i \rangle$ messages to all of the acceptors in C_j. A Phase 1 quorum of these acceptors, say Q, all received PHASE1A$\langle i \rangle$ messages and replied with PHASE1B messages. Thus, every acceptor in Q set its round r to i, and in doing so, promised to never vote in any round less than i. Moreover, none of the acceptors in Q had voted in any round greater than k. So, every acceptor in Q has not voted and never will vote in round j. For a value v' to be chosen in round j, it must receive votes from some Phase 2 quorum Q' of round j acceptors. But, Q and Q' necessarily intersect, so this is impossible. Thus, no value has been or will be chosen in round j.

Now suppose that H_i does *not* contain a configuration for round j. Either a configuration C_j was garbage collected from H_i or it wasn't. First, assume it wasn't. Then, H_i is the union of $f+1$ MATCHB messages from the $f+1$ matchmakers in M_i. Thus, if H_i does not contain a configuration for round j, then none of the MATCHB messages did either. This means that for every matchmaker $m \in M_i$, when m received MATCHA$\langle i, C_i \rangle$, it did not contain a configuration for round j in its log and never did. Moreover, no majority in any previous set of matchmakers contained a configuration in round j. If any majority did have a configuration in round j, then all subsequent matchmakers would as well since a set of matchmakers is initialized from a majority of the previous matchmakers. Moreover, by processing the MATCHA$\langle i, C_i \rangle$ request and inserting C_i in log entry i, the matchmaker is guaranteed to never process a MATCHA$\langle j, C_j \rangle$ request in the future. Moreover, no future set of matchmakers will either. A majority of matchmakers have a configuration in entry i, so all subsequent configurations will as well. Therefore, they will all reject a configuration in round j. Thus, every match-

maker in M_i has not processed a MATCHA request in round j and never will. For a value to be chosen in round j, the proposer executing round j must first receive replies from $f + 1$ matchmakers, say M_j, in round j. But, M_i and M_j necessarily intersect, so this is impossible. This argument holds for every set of matchmakers. Thus, no value has been or will be chosen in round j.

Otherwise, a configuration C_j was garbage collected from H_i. Note that none of the matchmakers in M_i had received a GARBAGEA$\langle i' \rangle$ command for a round $i' > i$ when they responded with their MATCHB messages. If they had, they would have ignored our MATCHA$\langle i, C_i \rangle$ message. Similarly, none of the matchmakers in M_i were initialized with a garbage collection watermark $w > i$. Let i' be the largest round $j < i' < i$ that a matchmaker in M_i garbage collected before responding to our MATCHA$\langle i, C_i \rangle$ message.

If i' was garbage collected because of Scenario 1, then k would be at least as large as i' since we would have intersected the Phase 2 quorum of $C_{i'}$ used in round i' to get a value chosen. But $k < j < i'$, a contradiction. If i' was garbage collected because of Scenario 2, then we know no value has been or will be chosen in round j. If i' was garbage collected because of Scenario 3, then we would have intersected the Phase 2 quorum of $C_{i'}$ that knows a value was already chosen, and we would have not proposed a value in the first place. But, we proposed x, a contradiction.

Case 2: $j = k$. In a given round, at most one value is proposed, let alone chosen. x is *the* value proposed in round k, so no other value could be chosen in round k.

Case 3: $j < k$. We can apply the inductive hypothesis to get $P(k)$ which states that no value other than x has been or will be chosen in any round less than k. This includes round j, which is exactly what we're trying to prove.

Finally, if k is -1, then we are in the same situation as in Case 1. $\square$

C Fast Paxos

Fast Paxos proposer pseudocode is given in Algorithm 5. We do not modify the Fast Paxos acceptor or the matchmakers. For simplicity, we assume that we deploy Fast Paxos with $f + 1$ acceptors, with a single unanimous Phase 2 quorum, and with singleton Phase 1 quorums. Generalizing to arbitrary configurations that satisfy Fast Paxos' quorum intersection requirements is straightforward. Note that Fast Paxos cannot leverage Phase 1 Bypassing. Also note while both MultiPaxos and our Fast Paxos variant both have quorums of size $f + 1$, our Fast Paxos variant has a *fixed* set of $f + 1$ acceptors, while MultiPaxos can choose any set of $f + 1$ acceptors from all $2f + 1$ acceptors. This has some disadvantages in terms of tail latency and fault tolerance.

We now prove that our modifications to Fast Paxos are safe. For simplicity, we ignore garbage collection and matchmaker reconfiguration. Introducing those two features and proving

---

Algorithm 5 Fast Paxos Proposer Pseudocode

State: a round i, initially -1
State: the configuration C_i for round i, initially null
State: the prior configurations H_i for round i, initially null

1: $i \leftarrow$ next largest round owned by this proposer
2: $C_i \leftarrow$ an arbitrary configuration
3: send MATCHA$\langle i, C_i \rangle$ to all of the matchmakers
4: **upon** receiving MATCHB$\langle i, H_i^1 \rangle, \dots,$ MATCHB$\langle i, H_i^{f+1} \rangle$ from $f + 1$ matchmakers **do**
5:     $H_i \leftarrow \bigcup_{j=1}^{f+1} H_i^j$
6:     send PHASE1A$\langle i \rangle$ to every acceptor in H_i
7: **upon** receiving PHASE1B$\langle i, -, - \rangle$ from a Phase 1 quorum from every configuration in H_i **do**
8:     $k \leftarrow$ the largest vr in any PHASE1B$\langle i, vr, vv \rangle$
9:     $V \leftarrow$ the corresponding vv's in round k
10:     **if** $k = -1$ **then**
11:         send PHASE2A$\langle i, \mathsf{any} \rangle$ to every acceptor in C_i
12:     **else if** $V = \{v\}$ **then**
13:         send PHASE2A$\langle i, v \rangle$ to every acceptor in C_i
14:     **else**
15:         send PHASE2A$\langle i, \mathsf{any} \rangle$ to every acceptor in C_i

---

them correct is pretty much identical to what we did with Donut Paxos.

Proof. We prove, for every round i, the statement $P(i)$ which states that if an acceptor votes for a value v in round i (i.e. sends a PHASE2B message for value v in round i), then no value other than v has been or will be chosen in any round less than i. $P(i)$ suffices to prove that Donut Paxos is safe. Why? Well, assume for contradiction that Donut Paxos chooses distinct values x and y in rounds i and j with $i < j$. Some acceptor must have voted for y in round j, so $P(j)$ ensures us that no value other than y could have been chosen in round i. But, x was chosen, a contradiction.

We prove $P(i)$ by strong induction on i. $P(0)$ is vacuous because there are no rounds less than 0. For the general case $P(i)$, we assume $P(0), \dots, P(i-1)$. We perform a case analysis on the proposer's pseudocode. Either k is -1 or it is not (line 8). First, assume it is not. We perform a case analysis on rounds $j < i$.

Case 1: $j > k$. Recall that at the end of the Matchmaking phase, the proposer computed the set H_i of prior configurations using responses from a set M of $f + 1$ matchmakers. Either H_i contains a configuration C_j in round j or it doesn't.

First, suppose it does. Then, the proposer sent PHASE1A$\langle i \rangle$ messages to all of the acceptors in C_j. A Phase 1 quorum of these acceptors, say Q, all received PHASE1A$\langle i \rangle$ messages and replied with PHASE1B messages. Thus, every acceptor in Q set its round r to i, and in doing so, promised to never vote in any round less than i. Moreover, none of the acceptors in Q had voted in any round greater than k. So, every acceptor in Q has not voted and never will vote in round

j. For a value v' to be chosen in round j, it must receive votes from some Phase 2 quorum Q' of round j acceptors. But, Q and Q' necessarily intersect, so this is impossible. Thus, no value has been or will be chosen in round j.

Now suppose that H_i does *not* contain a configuration for round j. H_i is the union of $f+1$ MATCHB messages from the $f+1$ matchmakers in M. Thus, if H_i does not contain a configuration for round j, then none of the MATCHB messages did either. This means that for every matchmaker $m \in M$, when m received MATCHA$\langle i, C_i \rangle$, it did not contain a configuration for round j in its log. Moreover, by processing the MATCHA$\langle i, C_i \rangle$ request and inserting C_i in log entry i, the matchmaker is guaranteed to never process a MATCHA$\langle j, C_j \rangle$ request in the future. Thus, every matchmaker in M has not processed a MATCHA request in round j and never will. For a value to be chosen in round j, the proposer executing round j must first receive replies from $f+1$ matchmakers, say M', in round j. But, M and M' necessarily intersect, so this is impossible. Thus, no value has been or will be chosen in round j.

Case 2: $j = k$. If $V = \{v\}$, then the proposer proposes v. We must prove that no value other than v has been or will be chosen in round k. For a value to be chosen in round k, every acceptor must vote for it in round k. Some acceptor voted for v in round k, so it is the only value with the possibility of receiving a unanimous vote.

Otherwise V contains multiple distinct elements, and the proposer proposes any. We must prove that no value has been or will be chosen in round k. This is immediate since no value can receive a unanimous vote in round k, if two different values have received votes in round k.

Case 3: $j < k$. If $V = \{v\}$, then the proposer proposes v, and we must prove that no value other than v has been or will be chosen in any round less than k. This is immediate from $P(k)$. Otherwise, $V = \{v_1, v_2, \ldots\}$, and the proposer proposes any. We must prove that no value has been or will be chosen in any round less than k. $P(k)$ tells us that no value other than v_1 has been or will be chosen in any round less than k. $P(k)$ also tells us that no value other than v_2 has been or will be chosen in any round less than k. Thus, no value has been or will be chosen in any round less than k.

Finally, if k is -1, then we are in the same situation as in Case 1. No value has been or will be chosen in any round less than i. □

D DPaxos Bug

Consider a DPaxos deployment with $f_d = 1$, $f_z = 0$, three zones, three nodes per zone, and delegate quorums. Thus, a replication quorum consists of two nodes in one zone, and a leader election quorum consists of two nodes in two zones. We name the nodes A through I. Beside each node, we display its ballot, vote ballot, vote value, and intents [20].

Zone 1	Zone 2	Zone 3
(A) $-1,-1,\perp,\emptyset$		(G) $-1,-1,\perp,\emptyset$
	(D) $-1,-1,\perp,\emptyset$	
(B) $-1,-1,\perp,\emptyset$		(H) $-1,-1,\perp,\emptyset$
	(E) $-1,-1,\perp,\emptyset$	
(C) $-1,-1,\perp,\emptyset$		(I) $-1,-1,\perp,\emptyset$
	(F) $-1,-1,\perp,\emptyset$	

Proposer 1 initiates the leader election phase in ballot 0 for value x. It selects $\{A,B,D,E\}$ as its leader election quorum and $\{B,C\}$ as its intent. It sends prepare messages to the leader election quorum, and the leader election quorum replies. Proposer 1 doesn't receive any intents, so it does not expand its leader election quorum. It also learns that no value has been chosen yet, so it proposes value x to B and C. Both accept the value.

Zone 1	Zone 2	Zone 3
(A) $0,-1,\perp,\{0:\{B,C\}\}$		(G) $-1,-1,\perp,\emptyset$
	(D) $0,-1,\perp,\{0:\{B,C\}\}$	
(B) $0,0,x,\{0:\{B,C\}\}$		(H) $-1,-1,\perp,\emptyset$
	(E) $0,-1,\perp,\{0:\{B,C\}\}$	
(C) $0,0,x,\emptyset$		(I) $-1,-1,\perp,\emptyset$
	(F) $-1,-1,\perp,\emptyset$	

Next, proposer 2 initiates the leader election phase in ballot 1 for value y. It selects $\{E,F,H,I\}$ as its leader election quorum and $\{G,H\}$ as its intent. It sends prepare messages to the leader election quorum, and the leader election quorum replies. Proposer 2 receives the intent $\{B,C\}$ in ballot 0 from E, so it expands its leader election quorum and sends a prepare message to C. Proposer 2 learns that value x was chosen in ballot 0, so it ditches y and proposes x to G and H. G accepts, but the propose message to H is dropped.

Zone 1	Zone 2	Zone 3
(A) $0,-1,\perp,\{0:\{B,C\}\}$		(G) $1,1,x,\emptyset$
	(D) $0,-1,\perp,\{0:\{B,C\}\}$	
(B) $0,0,x,\{0:\{B,C\}\}$		(H) $1,-1,\perp,\{1:\{G,H\}\}$
	(E) $1,-1,\perp,\{0:\{B,C\},1:\{G,H\}\}$	
(C) $0,0,x,\{1:\{G,H\}\}$		(I) $1,-1,\perp,\{1:\{G,H\}\}$
	(F) $1,-1,\perp,\{1:\{G,H\}\}$	

Next, garbage collection is run. The garbage collector contacts G and sees that it has accepted a value in ballot 1. It informs all the nodes to discard intents in ballots less than 1.

Zone 1   Zone 2   Zone 3

Next, proposer 3 initiates the leader election phase in ballot 2 for value z It selects $\{D,E,H,I\}$ as its leader election quorum and $\{E,F\}$ as its intent. It sends prepare messages to the leader election quorum, and the leader election quorum replies. Proposer 3 receives intent $\{G,H\}$ in ballot 1, but has already included H in its leader election quorum, so it does not send any additional prepares. It learns that no value has been chosen (this is a bug, x was chosen), so it proposes value z to E and G. Both accept the value, and z is chosen. This is a bug since x was already chosen.

Zone 1   Zone 2   Zone 3

(A) $0,-1,\perp,\emptyset$ (G) $1,1,x,\emptyset$

      (D) $2,-1,\perp,\emptyset 2:\{E,F\}$

(B) $0,0,x,\emptyset$ (H) $2,-1,\perp,\{1:\{G,H\},2:\{E,F\}\}$

      (E) $2,2,z,\{1:\{G,H\},2:\{E,F\}\}$

(C) $0,0,x,\{1:\{G,H\}\}$ (I) $2,-1,\perp,\{1:\{G,H\},2:\{E,F\}\}$

      (F) $2,2,z,\{1:\{G,H\}\}$