Sharp Impossibility Results for hypergraph Testing

Abstract

In a broad Degree-Corrected Mixed-Membership (DCMM) setting, we test whether
a non-uniform hypergraph has only one community or has multiple communities.
Since both the null and alternative hypotheses have many unknown parameters, the
challenge is, given an alternative, how to identify the null that is *hardest* to separate
from the alternative. We approach this by proposing a *degree matching strategy*
where the main idea is leveraging the theory for tensor scaling to create a least
favorable pair of hypotheses. We present a result on standard minimax lower bound
theory and a result on *Region of Impossibility* (which is more informative than the
minimax lower bound). We show that our lower bounds are tight by introducing a
new test that attains the lower bound up to a logarithmic factor. We also discuss
the case where the hypergraphs may have mixed-memberships.

1   Introduction

The hypergraph is a useful representation of social relationships beyond pairwise interactions [5, 11].
For example, the co-authorship hypergraph is often used to analyze the co-authorship topology of
authors, and it provides more information than a co-authorship graph (where an m-author paper is
treated as an m-clique). The community detection on a hypergraph [10] is a problem of great interest
(communities in a hypergraph are clusters of nodes that have more hyperedges within than across). It
has many applications in social network analysis [15] and machine learning [1, 17, 18, 21]. We are
interested in the problem of *global testing*, where we test whether the hypergraph has one community
or multiple communities. It has applications in measuring co-authorship and citation diversity [12]
and discovering non-obvious social groups and patterns [4]. It is also useful for understanding other
problems such as community detection and change-point detection in dynamic hypergraphs.

For instructional purpose only, we start with the 3-uniform hypergraphs (i.e., each hyperedge consists
of 3 nodes), but our results cover both higher-order hypergraphs and non-uniform hypergraphs. Let
$\mathcal{A}$ be the adjacency tensor of a uniform and symmetric order-3 hypergraph with n nodes, where

$$\mathcal{A}_{i_1 i_2 i_3} \text{ equals } 1 \text{ if } i_1, i_2, i_3 \text{ share a hyperedge and equals } 0 \text{ otherwise,} \qquad (1.1)$$

for $1 \leq i_1, i_2, i_3$ (distinct) $\leq n$. Since the tensor is symmetric, $\mathcal{A}_{i_1 i_2 i_3} = \mathcal{A}_{j_1 j_2 j_3}$ for two sets of
indices $\{i_1, i_2, i_3\}$ and $\{j_1, j_2, j_3\}$ if one is a permutation of the other. We do not consider self
hyperedges, hence, $\mathcal{A}_{i_1 i_2 i_3} = 0$ whenever i_1, i_2, i_3 are non-distinct.

Real world hypergraphs have several noteworthy features. First, there may be severe degree het-
erogeneity (i.e., the degree of one node is many times higher than that of another). Second, the
overall sparsity levels may vary significantly from one hypergraph to another. Last, a node may
have mixed-memberships across multiple communities (i.e., nonzero weights on more than one
community). To accommodate these features, we adopt the *Degree-Corrected Mixed-Membership*
(tensor-DCMM) model. The notations below are frequently used in tensor analysis.

Definition 1.1. *(matricization, slicing, and slice aggregation). Let $\mathcal{A}$ be a 3-symmetric tensor of n-
dimension. First, we call the $n \times n^2$ matrix A the matricization of $\mathcal{A}$, defined by $A_{i,j+n(k-1)} = \mathcal{A}_{ijk}$,*

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

37   $1 \le i, j, k \le n$. Second, for $1 \le k \le n$, we use $\mathcal{A}_{::k}$ to denote the $n \times n$ matrix whose row-i-and-
38   column-j is $\mathcal{A}_{ijk}$, $1 \le i, j \le n$, and call it the k-th slice of $\mathcal{A}$. Last, for any $n \times 1$ vector x, we use
39   $(\mathcal{A}x)$ to denote the matrix $\sum_{k=1}^{n} x_k \mathcal{A}_{::k}$, which is an aggregation of the slices.

40   Now, suppose the tensor has K perceivable communities. Let $\mathcal{P}$ be a symmetric (3-uniform) tensor of
41   K-dimension that models the community structure, let $\theta = (\theta_1, \theta_2, \ldots, \theta_n)'$ be positive parameters
42   that model the degree heterogeneity of nodes, and $\pi_1, \pi_2, \ldots, \pi_n$ be K-dimensional membership
43   vectors where $\pi_i(k) = $ the weight node i puts on community k, $1 \le k \le K$. We assume for all
44   $1 \le i_1, i_2, i_3 \le n$ that are three distinct indicies, $\mathcal{A}_{i_1 i_2 i_3}$ are independent Bernoulli random variables
45   with $\mathbb{P}(\mathcal{A}_{i_1 i_2 i_3} = 1) = \theta_{i_1} \theta_{i_2} \theta_{i_3} \sum_{k_1, k_2, k_3 = 1}^{K} \mathcal{P}_{k_1, k_2, k_3} \pi_{i_1}(k_1) \pi_{i_2}(k_2) \pi_{i_3}(k_3)$, where by Definition
46   1.1, the right hand side equals to $\theta_{i_1} \theta_{i_2} \theta_{i_3} \pi'_{i_1}(\mathcal{P}\pi_{i_3})\pi_{i_2}$. Introduce a non-stochastic 3-uniform tensor
47   $\mathcal{Q}$ of n-dimension where $\mathcal{Q}_{i_1 i_2 i_3} = \theta_{i_1} \theta_{i_2} \theta_{i_3} \pi'_{i_1}(\mathcal{P}\pi_{i_3})\pi_{i_2}$ for $1 \le i_1, i_2, i_3 \le n$. Let $\mathrm{diag}(\mathcal{Q})$ be
48   the tensor with the same size of $\mathcal{Q}$ where $(\mathrm{diag}(\mathcal{Q}))_{i_1 i_2 i_3} = \mathcal{Q}_{i_1 i_2 i_3}$ if i_1, i_2, i_3 are non-distinct, and
49   $(\mathrm{diag}(\mathcal{Q}))_{i_1 i_2 i_3} = 0$ otherwise. It follows that

$$\mathbb{E}(\mathcal{A}) = \mathcal{Q} - \mathrm{diag}(\mathcal{Q}), \qquad \text{where} \quad \mathcal{Q}_{i_1 i_2 i_3} = \theta_{i_1} \theta_{i_2} \theta_{i_3} \pi'_{i_1}(\mathcal{P}\pi_{i_3})\pi_{i_2}. \tag{1.2}$$

50   For identifiability, let $P \in \mathbb{R}^{K, K^2}$ be the matricization of $\mathcal{P}$ (see Definition 1.1). We assume

$$\mathrm{rank}(P) = K, \quad \text{and} \quad \mathcal{P}_{iii} = 1 \text{ for all } 1 \le i \le K. \tag{1.3}$$

51   **Definition 1.2.** *We call (1.1)-(1.3) the tensor-DCMM model for* 3-*uniform hypergraphs. We call* $\mathcal{Q}$
52   *and* $\mathcal{P}$ *the Bernoulli probability tensor and community structure tensor for DCMM, respectively.*

53   Later in Section 3, we introduce the *non-uniform tensor-DCMM* as a more sophisticated model. In
54   tensor-DCMM, if we require all π_i to be degenerate (i.e., one entry is 1, all other entries are 0), then
55   tensor-DCMM reduces to the *Degree-Corrected Block Model (tensor-DCBM)* [15]. If we further
56   require $\theta_1 = \ldots = \theta_n$ (but the second condition in (1.3) can be removed), then tensor-DCBM further
57   reduces to the *Stochastic Block Model* (tensor-SBM) [9]. For simplicity, we may drop "tensor" in
58   these terms if there is no confusion. The global testing problem above is then to test

$$H_0 : K = 1 \qquad \text{vs.} \qquad H_1 : K > 1. \tag{1.4}$$

59   Our primary goals are (a) to find a sharp information lower bound for 3-uniform DCMM, and
60   especially, to fully characterize the lower bound by *a simple quantity to be discovered*, and (b) extend
61   the results to more sophisticated non-uniform hypergraphse (see Section 3). A good understanding
62   of the problem greatly helps us understand the fundamental limits of many other problems (e.g.,
63   community detection, determining the number of communities K, dynamic hypergraphs). For
64   example, for community detection (e.g., [10]), we either assume K as known or estimate it first. Note
65   that in parameter regions where we can not tell whether $K = 1$ or $K > 1$, we can not estimate K
66   consistently, so we can not have consistent community detection either. Therefore, a lower bound for
67   global testing is always a valid lower bound for estimating K and for community detection.

68   To facilitate the lower bound study, we frequently adopt a *Random Mixed-Membership (RMM)* model.
69   Introduce a subset $V_0 = \{x \in \mathbb{R}^K : x_k \ge 0, \sum_{k=1}^{K} x_k = 1\}$, and let F be a K-variate distribution
70   with support contained in V_0. We assume

$$\pi_i \overset{iid}{\sim} F; \qquad (\text{let } h = \mathbb{E}_F[\pi_i]). \tag{1.5}$$

71   Moreover, let $V_0^* = \{e_1, e_2, \ldots, e_K\} \subset V_0$, where e_k is the k-th basis vector of $\mathbb{R}^K$. Similarly,
72   RMM-DCMM reduces to RMM-DCBM if we require $\mathrm{supp}(F) = V_0^*$, and reduces to RMM-SBM
73   if we further require $\theta_1 = \theta_2 = \ldots = \theta_n$ (but the second condition in (1.3) can be removed). Let
74   $\theta = (\theta_1, \theta_2, \ldots, \theta_n)'$. We allow $(\theta, \mathcal{P}, h, F)$ to vary with n to cover a variety of settings where we
75   allow for severe degree heterogeneity, mixed-memberships, flexible sparsity levels, and weak signals.

76   **Example 1** (*2-parameter SBM [2, 20]*). This model is a special case of DCMM, where $\theta_1 = \ldots =$
77   $\theta_n = \alpha_n$ (no degree heterogeneity), all π_i are degenerate (no mixed membership), and $\mathcal{P}_{ijk} = 1$ if
78   $i = j = k$ and $\mathcal{P}_{ijk} = \rho_n$ otherwise, for two parameters (α_n, ρ_n). Also, Lin et al. [19] studied a
79   3-parameter SBM, which is the same as above except that they assume a different form of $\mathcal{P}$, where
80   $\mathcal{P}_{ijk}$ equals to 1, ρ_n, or τ_n if i, j, k take 1, 2, or 3 distinct values, respectively, for three parameters
81   $(\alpha_n, \rho_n, \tau_n)$. Compared to DCMM, these models are much narrower: they do not accommodate
82   severe degree heterogeneity or mixed-memberships, and $\mathcal{P}$ is parametrized by 2 or 3 different values.

How to derive a sharp lower bound for global testing (and especially, to identify a *simple quantity* that fully characterizes the lower bound) in our setting is a rather challenging problem. Our model is a non-uniform hypergraph model (see Section 3), which consists of hypergraphs of order $2, 3, \ldots, M$, and each layer consists of many unknown parameters $(\theta, \mathcal{P}, h, F)$. Existing works on lower bounds have been focused on uniform hypergraphs, and non-uniform hypergraphs are much less studied. Even for uniform hypergraphs, existing works have been focused on the the special SBM as in Example 1, not the more general DCMM model. For example, Yuan et al. [20] derived the lower bounds for global testing with the 2-parameter SBM, focusing on the extremely sparse case, Ahn et al. [2] provided lower bound results for exactly recovering the communities (see Kim et al. [16] for a related setting) with a similar model. Lin et al. [19] and Chien et al. [7] used the 3-parameter SBM in Example 1 for study of the lower bounds for community detection. While these papers are very interesting, their lower bounds are characterized by only 2 or 3 parameters (i.e., α_n, ρ_n, τ_n) assumed in their models. For the much broader DCMM model considered here, we have many parameters $\theta, \mathcal{P}, h, F$ (θ is an n-vector and $\mathcal{P}$ is a tensor), and how to extend existing results on special SBM to the DCMM setting here is a challenging problem.

Our contributions. The main challenge in lower bound study is that, since each DCMM model (no matter what K is) has a large number of unknown parameters, so given an alternative hypothesis ($K > 1$), it is hard to identify the null hypothesis ($K = 1$) that is *most difficult to distinguish* from the alternative hypothesis. As our main contribution, we approach this by proposing a *degree matching strategy*, where for any given DCMM model with $K > 1$, we pair it with a DCMM model with $K = 1$ in a way so that for *each node*, the expected degree under the null matches with that under the alternative. This way, it is hard to separate the two hypotheses by a naive degree-based statistic. We show (a) the degree matching is always possible by using a tensor scaling technique [3, 8], and (b) the pair of hypotheses we construct this way lead to sharp results on lower bounds. See Section 2.

We have the following results. Consider the 3-uniform hypergraph first. We first present the standard minimax theory. Define a class of RMM-DCMM models with $K > 1$ and $\mu_2^2 \|\theta\|^2 \|\theta\|_1 \to 0$ (μ_2 is the second singular value of P). In this class, we can find an RMM-DCMM model (the alternative), and pair it with a DCMM model with $K = 1$ (the null), such that the χ^2-divergence between the pair converges to 0 as $n \to \infty$. Therefore, in this class, there *exists an alternative model* that is asymptotically inseparable from the null.

The standard minimax theory only claims that *there exists an alternative model* within a specified class that is inseparable from the null. It is desirable to show a much stronger result where *for any alternative in the class*, we can pair it with a null so that the χ^2-divergence of the pair goes to 0 as $n \to \infty$. In detail, we show that in the parameter space $(\theta, \mathcal{P}, h, F)$ of RMM-DCBM, there is a *Region of Impossibility* defined by $\mu_2^2 \|\theta\|^2 \|\theta\|_1 \to 0$; for *any alternative* in Region of Impossibility, we can pair it with a null such that the χ^2-divergence between the pair goes 0 as $n \to \infty$. Compared with existing results on minimax lower bounds, these results are more informative and theoretically more satisfactory. The proof is also different from the proof of minimax lower bounds: we have used the tensor scaling theory [3, 8] and the "degree matching strategy" aforementioned. We also extend such results to the broader RMM-DCMM case (Section 2.3) and discuss some major differences on the Region of Impossibility between DCBM and the more restrictive SBM (Section 2.4).

Next, we generalize the results to higher-order and non-uniform hypergraphs. Fix $M \geq 2$ and consider a non-uniform hypergraph (e.g., see [10]) that consists of m-uniform hypergraphs for all $m = 2, \ldots, M$, each following a DCMM model with individual $(\theta^{(m)}, \mathcal{P}^{(m)})$ but the common $\pi_1, \ldots, \pi_n$. Let $\ell_m = \|\theta^{(m)}\|_1^{m-2} \|\theta^{(m)}\|^2 (\mu_2^{(m)})^2$. We show that (a) for the m-uniform hypergraph case, the Region of Impossibility for the hypothesis testing (1.4) is fully characterized by the condition of $\ell_m \to 0$, and (b) for the non-uniform hypergraph case, the Region of Impossibility for the hypothesis testing (1.4) is fully characterized by the condition of $\max_{2 \leq m \leq M}\{\ell_m\} \to 0$.

Last, we show that our lower bounds are tight. Consider the non-uniform hypergraph above. We propose a new test statistic and show that the sum of Type I and type II errors $\to 0$ if $\max_{2 \leq m \leq M}\{\ell_m\} \geq \log(n)^{1+\delta}$ for a constant $\delta > 0$ (taking $\delta = 0.1$ will work). Therefore, except for a logarithmic factor here, our lower bounds are tight.

In summary, existing results on lower bounds are largely focused on more restrictive settings (e.g., uniform hypergraphs without degree heterogeneity or mixed membership). We provide sharp lower bounds for a much broader setting. Our study is highly non-trivial because we need (i) a novel *degree matching strategy* to construct least favorable hypothesis pairs, (ii) to identify a simple quantity that

139 is able to fully characterize the lower bounds, (iii) delicate analysis of the χ^2-divergence between the
140 null and alternative, (iv) a carefully designed test that leads to tight upper bounds.

2 Sharp Lower Bounds for 3-Uniform Hypergraphs

142 For notational simplicity, we focus on 3-uniform hypergraphs in this section. The study of higher-
143 order and non-uniform hypergraphs is deferred to Section 3. Consider a (3-uniform) DCMM model.
144 Recall that $h = \mathbb{E}_F[\pi_i]$ and that $P \in \mathbb{R}^{K,K^2}$ is the matricization of the tensor $\mathcal{P}$. In this paper, we
145 use $C > 0$ as a generic constant which may vary from occurrence to occurrence. We assume

$$\|P\| \leq C, \; \theta_{\max} \equiv \max\{\theta_1, \ldots, \theta_n\} \leq C, \; \max_{1 \leq k \leq K}\{h_k\} \leq C \min_{1 \leq k \leq K}\{h_k\}, \; \|\theta\|^2 \|\theta\|_1 \to \infty. \quad (2.6)$$

146 The first condition is mild, because the model identifiability already requires that all diagonal entries
147 of $\mathcal{P}$ are 1. The second one is also mild (note that while the largest possible value of $\theta_{\max}$ is $O(1)$,
148 $\theta_{\max}$ is allowed to tend to 0 relatively fast). The third one assumes that the community memberships
149 are balanced, which is also mild. For the last condition, we will see soon that if $\|\theta\|^2 \|\theta\|_1 \to 0$, then
150 the signal is so weak that successful global testing is impossible, so this condition is also mild.

2.1 Standard minimax lower bounds (RMM-DCMM)

152 We start with the least favorable configuration. The goal is to find a pair of models (a null model with
153 $K = 1$, and an alternative model with $K > 1$) which are hard to distinguish from each other. We
154 use the following degree-matching technique: we choose the pair in a way so that for each node, the
155 expected degree under the null matches with that under the alternative, approximately. The idea is, if
156 the degrees are not matching, then we may separate the two hypotheses by a simple degree-based
157 statistic, so we should not expect the χ^2-divergence between the pair to be small.

158 In detail, consider a pair of models, a DCMM model with $K = 1$ and an RMM-DCMM model with
159 $K > 1$, where for all $1 \leq i_1, i_2, i_3 \leq n$, the Bernoulli probability tensors $\mathcal{Q}$ and $\mathcal{Q}^*$ satisfy

$$\mathcal{Q}_{i_1 i_2 i_3} = \theta_{i_1} \theta_{i_2} \theta_{i_3}, \qquad \mathcal{Q}^*_{i_1 i_2 i_3} = \theta^*_{i_1} \theta^*_{i_2} \theta^*_{i_3} \cdot \pi'_{i_1}(\mathcal{P}\pi_{i_3})\pi_{i_2}; \quad (2.7)$$

160 here we recall that $(\mathcal{P}\pi_{i_3})$ is a $K \times K$ matrix (see Definition 1.1). We call the two models *the null*
161 and *the alternative*, respectively. In (2.7), the community structure tensor $\mathcal{P}$ is as in (1.2), and π_i and
162 $h = \mathbb{E}_F[\pi_i]$ are as in (1.5). Recall that $\theta = (\theta_1, \theta_2, \ldots, \theta_n)'$. Similarly, let $\theta^* = (\theta^*_1, \theta^*_2, \ldots, \theta^*_n)'$.
163 Fix $1 \leq i_1 \leq n$. By definitions and elementary statistics, the leading term of the expected degree of
164 node i_1 under the null and alternative are

$$\theta_{i_1}\|\theta\|_1^2 \; \text{and} \; \theta^*_{i_1} \cdot \|\theta^*\|_1^2 \cdot \pi'_{i_1} a, \; \text{respectively, where } a = (\mathcal{P}h)h \in \mathbb{R}^K. \quad (2.8)$$

165 For least favorable construction, we choose $(\mathcal{P}, h)$ in a way so that

$$a = (\mathcal{P}h)h = c_0^3 \mathbf{1}_K, \qquad \text{for a scalar } c_0 > 0. \quad (2.9)$$

166 For broadness, we allow c_0 to depend on n. There are many $(\mathcal{P}, h)$ that satisfy (2.9). For example,
167 in the 2-parameter SBM model as in Example 1 with $h = (1/K, \ldots, 1/K)'$ and $a_k = (1/K^2)[1 +$
168 $(K^2 - 1)\rho_n]$ for $1 \leq k \leq K$, (2.9) is satisfied with $c_0^3 = (1/K^2)[1 + (K^2 - 1)\rho_n]$. Moreover, we
169 choose θ^*_i in the alternative model such that

$$\theta^*_i = (1/c_0)\theta_i, \qquad 1 \leq i \leq n. \quad (2.10)$$

170 Now, by (2.8)-(2.9), for all $1 \leq i_1 \leq n$, $\theta^*_{i_1}\|\theta^*\|_1^2 \cdot \pi'_{i_1} a = \theta^*_{i_1}\|\theta^*\|_1^2 \cdot c_0^3 = \theta_{i_1}\|\theta\|_1^2$. Therefore, for
171 each node, the expected degree under the alternative matches that under the null (at least in the leading
172 term), making it hard to separate the null and alternative by any naive degree-based statistics. Only
173 when such a degree-matching holds, we can hope two models are asymptotically indistinguishable.
174 This is the key for our least favorable configuration. Recall that $P \in \mathbb{R}^{K,K^2}$ is the matricization of
175 the community tensor $\mathcal{P}$ and μ_k is the k-th largest singular value of P.

Theorem 2.1 (Least favorable configuration). *Fix $K > 1$ and consider a pair of models, a null and
177 an alternative with K communities, given in (2.7), where (2.9)-(2.10) hold. Assume (2.6) holds and
178 $\|\theta\|_1 \|\theta\|^2 \mu_2^2 = o(1)$. As $n \to \infty$, the χ^2-divergence [1] between the pair tends to 0. Therefore, the two
179 models are asymptotically indistinguishable: for any test, the sum of Type I and Type II errors is no
180 smaller than $1 + o(1)$.*

---

[1]The χ^2-divergence between two models, $f_0(\mathcal{A})$ and $f_1(\mathcal{A})$, is defined as $\int [(f_0(\mathcal{A}) - f_1(\mathcal{A}))^2 / f_0(\mathcal{A})]d\mathcal{A}$.
In our setting, the alternative model $f_1(\mathcal{A})$ alone involves an integral over the distribution of π_i in (1.5)

The least favorable configuration gives rises to the standard minimax theorem. Fix $K \geq 1$ and consider a DCMM model (where π_i are non-random). Introduce a vector $g \in \mathbb{R}^K$ by $g_k = (1/\|\theta\|_1) \sum_{i=1}^n \theta_i \pi_i(k)$, $1 \leq k \leq K$. For a constant $0 < c_0 < 1$, and two positive sequences $\{\alpha_n\}_{n=1}^\infty$ and $\{\beta_n\}_{n=1}^\infty$, we define a class of DCMM models by

$$\mathcal{M}_n(K, c_0, \alpha_n, \beta_n) = \left\{ \begin{array}{l} (\theta, \Pi, P): \quad \|P\| \leq c_0, \ \theta_{\max} \leq c_0, \ \max_{1 \leq k \leq K} g_k \leq c_0^{-1} \min_{1 \leq k \leq K} g_k, \\ \|\theta\|_1 \|\theta\|^2 \geq 1/\beta_n, \ \|\theta\|_1 \|\theta\|^2 \mu_2^2 \leq \alpha_n \end{array} \right\}.$$

Here, we assume $\max_{1 \leq k \leq K}\{g_k\} \leq C \min_{1 \leq k \leq K}\{g_k\}$, so the tensor is balanced. This is similar to the third condition in (2.6), except that π_i's are random there. For the null case, $K = P = \pi_i = 1$, and the above defines a class of θ, which we write for short by $\mathcal{M}_n(1, c_0, \alpha_n, \beta_n) = \mathcal{M}_n^*(\beta_n)$. The following theorem is proved in the supplement.

Theorem 2.2 (Minimax lower bound). *Fix $K \geq 2$, a constant $c_0 > 0$, and any sequences $\{\alpha_n\}_{n=1}^\infty$ and $\{\beta_n\}_{n=1}^\infty$ where $\alpha_n = o(1)$ and $\beta_n = o(1)$. As $n \to \infty$, $\inf_\psi \{\sup_{\theta \in \mathcal{M}_n^*(\beta_n)} \mathbb{P}(\psi = 1) + \sup_{(\theta, \Pi, P) \in \mathcal{M}_n(K, c_0, \alpha_n, \beta_n)} \mathbb{P}(\psi = 0)\} = 1 - o(1)$, where the infimum is over all possible tests ψ.*

2.2 Region of Impossibility for RMM-DCBM

The standard minimax theorem in Section 2.1 only says that in the class of all alternative models with $\|\theta\|^2 \|\theta\|_1 \mu_2^2 \to 0$, *there exists one* where we can pair it with a null so the pair are asymptotically inseparable. A much more satisfactory result is to show that, for *any alternative* in the same class, we can pair it with a null such that the pair are asymptotically inseparable. In this section, we prove this for the RMM-DCBM case (mixed-memberships are not allowed). The discussion for the RMM-DCMM (mixed-memberships allowed) is in Section 2.3 and the supplement.

Consider again a pair of models, a DCBM null model and an RMM-DCBM model with $K > 1$, where the Bernoulli probability tensors are $\mathcal{Q}$ and $\mathcal{Q}^*$, respectively. We assume for all $1 \leq i_1, i_2, i_3 \leq n$,

$$\mathcal{Q}_{i_1 i_2 i_3} = \theta_{i_1} \theta_{i_2} \theta_{i_3}, \qquad \mathcal{Q}_{i_1 i_2 i_3}^* = \theta_{i_1}^* \theta_{i_2}^* \theta_{i_3}^* \pi_{i_1}'(\mathcal{P} \pi_{i_3}) \pi_{i_2}. \tag{2.11}$$

Here, the community structure tensor $\mathcal{P}$ is as in (1.2), π_i and $h = \mathbb{E}_F[\pi_i]$ are as in (1.5), and $\text{supp}(F) = \{e_1, \ldots, e_K\}$. Similarly, the goal is degree-matching: for any $(\theta, \mathcal{P}, h, F)$, we construct θ^* in a way so that for each node, the expected degrees under the null and the alternative match with each other approximately. Recall that in Section 2.2, in order to have a desired degree matching, it is crucial to pick an alternative model where the $(\mathcal{P}, h)$ satisfies $a \equiv (\mathcal{P}h)h = c_0^3 \mathbf{1}_K$ for some scalar $c_0 > 0$; once this holds, we have the desired degree matching by taking $\theta^* = (1/c_0)\theta$. Unfortunately, for general $(\mathcal{P}, h)$, we don't have $a \equiv (\mathcal{P}h)h \propto \mathbf{1}_K$, so we should not expect to have the desired degree matching by taking $\theta^* \propto \theta$. In short, for our purpose here, the approach in Section 2.1 no longer works, and we must find a new approach to constructing the model pair.

Our proposal is as follows. For any diagonal matrix $D = \text{diag}(d_1, \ldots, d_K)$ with $d_k > 0, 1 \leq k \leq K$, define a K-dimensional vector a^D by $a^D = (\mathcal{P}^D h)h$, where $\mathcal{P}^D$ is a 3-tensor in dimension K with $\mathcal{P}_{k_1 k_2 k_3}^D = d_{k_1} d_{k_2} d_{k_3} \mathcal{P}_{k_1 k_2 k_3}, 1 \leq k_1, k_2, k_3 \leq K$. We now select a matrix D such that $a^D = \mathbf{1}_K$. The following lemma states that such a D always exists and is unique. It leverages classic results on tensor scaling (e.g., [3, 8]) and is proved in the supplement.

Lemma 2.1. *Fix $K > 1$ and let $\mathcal{P}$, h, D, and a^D be as above. Suppose $\min\{h_1, h_2, \ldots, h_K\} \geq C$. There exists a unique diagonal matrix $D = \text{diag}(d_1, d_2, \ldots, d_K)$ such that $a^D = \mathbf{1}_K$.*

Now, given $(\theta, \mathcal{P}, h, F)$ and the two models in (2.11), let $D = \text{diag}(d_1, d_2, \ldots, d_K)$ be as in Lemma 2.1. Moreover, in (2.11), we choose θ_i^* as follows:

$$\theta_i^* = d_k \theta_i, \quad \text{if node } i \text{ belongs to community } k. \tag{2.12}$$

Combining it with (2.11), we have $\mathcal{Q}_{i_1 i_2 i_3}^* = \theta_{i_1}^* \theta_{i_2}^* \theta_{i_3}^* \cdot \pi_{i_1}'(\mathcal{P} \pi_{i_3}) \pi_{i_2} = \theta_{i_1} \theta_{i_2} \theta_{i_3} \cdot \pi_{i_1}'(\mathcal{P}^D \pi_{i_3}) \pi_{i_2}$. By similar calculations as in (2.8), for $1 \leq i \leq n$, in the null and the alternative, the leading terms of the expected degrees of node i are $\theta_i \|\theta\|_1$ and $\theta_i (\pi_i' a^D) \|\theta\|_1^2$, respectively, where $a^D = (\mathcal{P}^D h)h$. By Lemma 2.1, $a^D = \mathbf{1}_K$. Hence, for each node, the expected degrees match under the null and alternative, so it is hard to separate two models by a naive degree-based statistic. Recall that P is the matricization of $\mathcal{P}$ and μ_k is the k-th singular value of P. Theorem 2.3 is proved in the supplement.

Theorem 2.3 (Impossibility for RMM-DCBM). *Fix $K > 1$. For any given $(\theta, \mathcal{P}, h, F)$, consider a pair of models, a null and an alternative with K communities, as in (2.11), where θ_i^* are given*

by (2.12) with the matrix D as in Lemma 2.1. Suppose (2.6) holds and $\|\theta\|_1\|\theta\|^2\mu_2^2 = o(1)$. As $n \to \infty$, the χ^2-divergence between the pair tends to 0. Therefore, the two models are asymptotically indistinguishable: for any test, the sum of Type I and Type II errors is no smaller than $1 + o(1)$.

Region of Possibility, Region of Impossibility, and tightness. In the parameter space $(\theta, \mathcal{P}, h, F)$ for DCBM, we call the region prescribed by $\|\theta\|_1\|\theta\|^2\mu_2^2 \to 0$ the *Region of Impossibility*: by Theorem 2.3, for any model in this region, we can pair it with a null so that the pair are asymptotically inseparable. We call the region prescribed by $\|\theta\|_1\|\theta\|^2\mu_2^2/\log^{1+\delta}(n) \to \infty$ the *Region of Possibility*: for any alternative model in this region, there is a method that can separate it from *any null* with asymptotically full power (this follows from Theorem 3.2 as a special case). Comparing Region of Impossibility and Region of Possibility, except for a $\log(n)$ term, our lower bounds are tight.

2.3 Region of Impossibility for RMM-DCMM

The discussion for RMM-DCMM is similar, so for reasons of space, we leave it to Section A of the supplement. In that section, we present a similar theorem for RMM-DCMM, where the hypergraphs may have mixed-memberships. The proofs are largely similar, where again the key is to construct a pair of null and alternative using the degree matching strategy. Since the model is more complicated than RMM-DCBM, we need an extra (but mild) condition. See details therein.

2.4 Major differences on Region of Impossibility for the more restrictive RMM-SBM

For an alternative RMM-DCBM, we can always pair it with a null using tensor scaling technique: for each node, the expected degrees under the null and the alternative match with each other. For the more restrictive RMM-SBM (where $\theta_1 = \ldots = \theta_n$), such a degree matching is not always possible: A null SBM has only 1 parameter, so we have insufficient flexibility in choosing the null for degree matching. A consequence is that a naive degree-based test may have non-trivial power for SBM.

Consider a pair of models, where the Bernoulli probability tensors $\mathcal{Q}$ and $\mathcal{Q}^*$ under two hypotheses are such that, for $1 \leq i_1, i_2, i_3 \leq n$,

$$\mathcal{Q}_{i_1 i_2 i_3} = \alpha_n, \qquad \mathcal{Q}^*_{i_1 i_2 i_3} = \pi'_{i_1}(\mathcal{P}\pi_{i_3})\pi_{i_2}. \tag{2.13}$$

Same as before, π_i are *iid* generated from a distribution F on $\{e_1, e_2, \ldots, e_K\}$ with $h = \mathbb{E}_F[\pi_i]$. Let $\hat{\alpha}_n = (n(n-1)(n-2))^{-1}\mathbf{1}'_n(\mathcal{A}\mathbf{1}_n)\mathbf{1}_n, \eta = (1/2)(\mathcal{A}\mathbf{1}_n)\mathbf{1}_n$, and $\bar{\eta}$ be the mean of $\eta_1, \eta_2, \ldots, \eta_K$. Consider the centered-$\chi^2$-statistic $\psi_n = (2n)^{-1/2}\sum_{1 \leq i \leq n}[(\eta_i - \bar{\eta})^2/(\binom{n-1}{2}\hat{\alpha}_n(1 - \hat{\alpha}_n)) - 1]$.

Lemma 2.2. *Consider the global testing problem (1.4) under the SBM model (2.13) for H_0 and H_1, respectively. Let $\widetilde{\alpha}_n = \mathbb{E}[\hat{\alpha}_n], h = (1/n)\sum_{i=1}^n \pi_i$ and $\Sigma = \frac{1}{n}\sum_{i=1}^n(\pi_i - h)(\pi_i - h)'$. Let $\lambda_{K-1}(\Sigma)$ be the $(K-1)$-th largest eigenvalue (in magnitude) of Σ. Assume $\alpha_n \leq c_0, \max_{1 \leq i,j,k \leq K}\{\mathcal{P}_{ijk}\} \leq c_0, n^2\alpha_n \to \infty$, and $n^2\widetilde{\alpha}_n \to \infty$. Also, assume $\min\{h_1, h_2, \ldots, h_K\} \geq C$ and $\lambda_{K-1}(\Sigma) \geq C$. Write $\delta_n = \|\widetilde{\alpha}_n^{-1}(I_K - H_K)(\mathcal{P}h)h\|$, where $H_K = (1/K)\mathbf{1}_K\mathbf{1}'_K$ and I_K is the identity matrix of the same size. As $n \to \infty$, $\psi_n \to N(0,1)$ if H_0 holds, and $\psi_n \to \infty$ if H_1 holds and $n^{3/2}\widetilde{\alpha}_n^{1/2}\delta_n^2 \to \infty$*

The power of the χ^2-test hinges on δ_n. Note that $\delta_n = 0$ if and only if $(\mathcal{P}h)h \propto \mathbf{1}_K$. We call the cases of $(\mathcal{P}h)h \propto \mathbf{1}_K$ and $(\mathcal{P}h)h \not\propto \mathbf{1}_K$ the *symmetric* case and the *asymmetric* case, respectively. For symmetric SBM, $\delta_n = 0$, and we do not expect the χ^2-test to have power. However, for asymmetric SBM, the χ^2-test may have non-trivial power, implying a potential shift of the lower bound.

Example 2. Consider an SBM setting where we either have $K = 1$ (null) or $K = 2$ (alternative). Also, when $K = 2$, we assume $h = (a, 1-a)'$ for some $0 < a < 1$, $\mathcal{P}_{ijk}$ is equal to ρ_0 if $i = j = k$ and ρ_1 otherwise. Suppose $n^2\rho_0 \to \infty$ and $\rho_1/\rho_0 \to 1$. This can be viewed as a special DCBM with $\theta_i \equiv \rho_0^{1/3}$ and off-diagonals of $\mathcal{P}$ being ρ_1/ρ_0. In this case, we have $\|\theta\|_1\|\theta\|^2 \asymp n^2\rho_0$, $\tau_n \equiv \|\theta\|_1\|\theta\|^2\mu_2^2 \asymp n^2\rho_0^{-1}(\rho_1 - \rho_0)^2$, and $n^{3/2}\widetilde{\alpha}_n\delta_n^2 \asymp (n\rho_0)^{-1/2}(2a-1)^2\tau_n$. In the symmetric case where $a = 1/2$, the χ^2-test is powerless, and the Region of Impossibility is given by $\tau_n \to 0$ (same as in the DCBM case). In the asymmetric case where $|a - 1/2| \geq c_0$, by direct calculations, we have that even when $\tau_n \to 0$, we may have $n^{3/2}\widetilde{\alpha}_n^{1/2}\delta_n^2 \to \infty$ (so χ^2-test has asymptotically full power). Here, the interesting range of ρ_0 is $(n^{-2}, 1)$, so we may have $(n\rho_0)^{-1/2} \to \infty$. Therefore, for the asymmetric case, the Region of Impossibility is different from that of DCBM.

In most lower bound results for SBM [2, 7, 19, 20], they focused on the symmetric case $(\mathcal{P}h)h \propto \mathbf{1}_K$. Our lower bound restricted to symmetric SBM agrees with those in the literature. The asymmetric

case $(\mathcal{P}h)h \not\propto \mathbf{1}_K$ is less studied. We discover: (i) the Region of Impossibility for symmetric SBM is similar to that of DCBM (see Example 2), and (ii) the Region of Impossibility for asymmetric SBM is quite different from that of DCBM. This is because DCBM is much broader than SBM, where the problem of global testing is much harder, and a naive degree-based test statistic may lose power.

3 Sharp lower bound for non-uniform hypergraphs

Section 2 discusses lower bounds for uniform 3-hypergraph. We now first extend the results to more general non-uniform hypergraphs, and then present a tight upper bound. Note that our results include those for m-uniform hypergraphs as special cases (see the paragraph behind Theorem 3.1). The notation below is useful:

Definition 3.1. *Given an order-m tensor $\mathcal{M}$ in dimension K and vectors $b_1, b_2, \ldots, b_m \in \mathbb{R}^K$, let* $[\mathcal{M}; b_1, \cdots, b_K]$ *denote the summation* $\sum_{1 \le k_1, k_2, \ldots, k_m \le K} [\mathcal{M}_{k_1 k_2 \ldots k_m} b_1(k_1) b_2(k_2) \cdots b_m(k_m)]$.

Fix $M \ge 2$. Consider a general non-uniform hypergraph that consists of m-uniform hypergraphs for all $2 \le m \le M$. Fixing $2 \le m \le M$, let $\mathcal{A}^{(m)}$ be the adjacency tensor of the order-m hypergraph (i.e., $\mathcal{A}^{(m)}_{i_1 i_2 \cdots i_m} = 1$ if $\{i_1, i_2, \ldots, i_m\}$ is a hyper-edge and 0 otherwise). As before, we model $\mathcal{A}^{(m)}$ with the tensor-DCMM model. Let $\mathcal{P}^{(m)}$ be a symmetric order-m tensor in dimension K, and let $\theta^{(m)} = (\theta_1^{(m)}, \theta_2^{(m)}, \ldots, \theta_n^{(m)})'$ be a positive vector of degree parameters. Let $\pi_1, \pi_2, \ldots, \pi_n$ be the K-dimensional membership vectors (which do not depend on m). We assume $\{\mathcal{A}^{(m)}_{i_1 i_2 \cdots i_m}\}_{1 \le i_1 < i_2 < \ldots < i_m \le n}$ are independent Bernoulli variables, where the Bernoulli probabilities are specified by the tensor $\mathcal{Q}^{(m)}$, given by

$$\mathcal{Q}^{(m)}_{i_1 i_2 \ldots i_m} = \theta_{i_1}^{(m)} \ldots \theta_{i_m}^{(m)} \times [\mathcal{P}^{(m)}; \pi_{i_1}, \cdots, \pi_{i_m}], \qquad 1 \le i_1, i_2, \ldots, i_m \le n. \tag{3.14}$$

Similar to (1.2), we have $\mathbb{E}[\mathcal{A}^{(m)}] = \mathcal{Q}^{(m)} - \text{diag}(\mathcal{Q}^{(m)})$. This extends the tensor-DCMM model to m-uniform hypergraphs for a general m. Finally, we denote the non-uniform hypergraph by $\mathcal{A}[M] \equiv \{\mathcal{A}^{(2)}, \mathcal{A}^{(3)}, \ldots, \mathcal{A}^{(M)}\}$.

Definition 3.2. *We say that $\mathcal{A}[M] = \{\mathcal{A}^{(2)}, \ldots, \mathcal{A}^{(M)}\}$ follows a (general non-uniform) tensor-DCMM model if $\{\mathcal{A}^{(m)}\}_{2 \le m \le M}$ are independent of each other and each $\mathcal{A}^{(m)}$ follows an m-uniform tensor-DCMM model as in (3.14), where $\pi_1, \pi_2, \ldots, \pi_n$ are shared by all $2 \le m \le M$.*

A similar model is introduced in [10], but is more restrictive for it assumes $\theta_1^{(m)} = \theta_2^{(m)} = \cdots = \theta_n^{(m)}$ for each $2 \le m \le M$. Note also the focus of [10] is on community detection, while the focus here is on global testing. As argued before, since in parameter regions where we can not tell whether $K = 1$ or $K > 1$, it is impossible to estimate K and community labels consistently. Therefore, our lower bound is also a valid lower bound for estimating K and for community detection.

We present the *Region of Impossibility* for testing H_0: $K = 1$ versus H_1: $K > 1$. Similarly as in Section 2.2, we focus on the special case of tensor-DCBM models (i.e., each π_i is degenerate); the study of tensor-DCMM is similar. Fix $K > 1$. Consider a DCBM null model with probability tensors $\mathcal{Q}[M] = \{\mathcal{Q}^{(2)}, \ldots, \mathcal{Q}^{(M)}\}$ and an RMM-DCBM model with probability tensors $\mathcal{Q}^*[M] = \{\mathcal{Q}^{*(2)}, \ldots, \mathcal{Q}^{*(M)}\}$, where for every $2 \le m \le M$ and $1 \le i_1, i_2, \ldots, i_m \le n$,

$$\mathcal{Q}^{(m)}_{i_1, i_2, \ldots, i_m} = \theta_{i_1}^{(m)} \theta_{i_2}^{(m)} \cdots \theta_{i_m}^{(m)}, \tag{3.15}$$

$$\mathcal{Q}^{*(m)}_{i_1, i_2, \ldots, i_m} = \theta_{i_1}^{*(m)} \cdots \theta_{i_m}^{*(m)} \times [\mathcal{P}^{(m)}; \pi_{i_1}, \ldots, \pi_{i_m}], \qquad \pi_i \overset{iid}{\sim} F. \tag{3.16}$$

The support of F is in $V_0^* = \{e_1, e_2, \ldots, e_K\}$. Let $h = \mathbb{E}_F[\pi_i]$ and suppose $\min\{h_1, \ldots, h_K\} \ge C$. In the supplemental material, we provide a lemma analogous to Lemma 2.1: For each $2 \le m \le M$, there exists a unique diagonal matrix $D^{(m)} = \text{diag}(d_1^{(m)}, d_2^{(m)}, \ldots, d_K^{(m)})$ such that $\sum_{1 \le i_2, \ldots, i_m \le K} d_{i_1}^{(m)} \cdot \mathcal{P}^{(m)}_{i_1 \cdots i_m} \cdot (d_{i_2}^{(m)} h_{i_2}) \cdots (d_{i_m}^{(m)} h_{i_m}) = 1$, for every $1 \le i_1 \le K$. Its proof leverages the Sinkhorn theorems for higher-order tensors [3, 8]. We choose $\theta^{*(m)}$ in (3.16) by

$$\theta_i^{*(m)} = d_k^{(m)} \theta_i^{(m)}, \quad \text{if node } i \text{ belongs to community } k. \tag{3.17}$$

This is analogous to the degree matching strategy in (2.12), and it is conducted for each m separately. Let $P^{(m)} \in \mathbb{R}^{K \times K^{m-1}}$ be the matricization of $\mathcal{P}^{(m)}$ and let $\mu_2^{(m)}$ be the second singular value of $P^{(m)}$. For short, let $\ell_m = \|\theta^{(m)}\|_1^{m-2} \|\theta^{(m)}\|^2 (\mu_2^{(m)})^2$. Theorem 3.1 is proved in the supplement.

Theorem 3.1 (Impossibility for non-uniform RMM-DCBM). *Fix $K > 1$ and $M \geq 2$. For any given (h, F) and $\{(\theta^{(m)}, \mathcal{P}^{(m)})\}_{2 \leq m \leq M}$, consider a pair of models, a null as in (3.16) and an alternative with K communities as in (3.15), where $\{\theta_i^{*(m)}\}_{1 \leq i \leq n, 2 \leq m \leq M}$ are as in (3.17). Suppose $\|P^{(m)}\| \leq C$, $\max_{1 \leq i \leq n} \theta_i^{(m)} \leq C$, and $\min_{1 \leq k \leq K} h_k \geq C$. If $\max_{2 \leq m \leq M}\{\ell_m\} = o(1)$, then as $n \to \infty$, the χ^2-divergence between the pair tends to 0.*

Below in Section 3.1, we show that the lower bounds are tight. Theorem 3.1 includes m-uniform hypergraphs as a special case (e.g., to apply the theorem to an m_0-uniform hypergraph, we set $\theta^{(m)}$ a zero vector for all $m \neq m_0$). For an m-uniform hypergraph, the Region of Impossibility is given by $\ell_m \to 0$, which is the same as that in Theorem 2.3 when $m = 3$. While many lower bound results are available for uniform hypergraphs [2, 7, 19, 20], non-uniform hypergraphs are less studied. Our lower bound in Theorem 3.1 leads to two notable discoveries: (i) the Regions of Possibility/Impossibility for $\mathcal{A}^{(m)}$ are fully characterized by the simple quantity of ℓ_m; (ii) the Regions of Possibility/Impossibility for non-uniform hypergraphs are fully characterized by the simple quantity of $\max_{2 \leq m \leq M}\{\ell_m\}$.

3.1 Tightness of the lower bounds

We propose a test for the global testing problem (1.4) and show that it attains the lower bounds in Theorems 2.3 and Theorem 3.1. For simplicity, we only discuss this for DCBM with moderate degree heterogeneity but the tightness holds in much broader settings (e.g., DCMM). For each $2 \leq m \leq M$, we first compute a vector $\eta^{(m)} \in \mathbb{R}^n$, which serves as an estimate of θ when the null hypothesis is true. Fix m. Given a positive vector $u \in \mathbb{R}^n$, define $L(u) \in \mathbb{R}^n$ by

$$L_i(u) = \frac{\sum_{i_2,\ldots,i_m(\text{distinct})} \mathcal{A}_{i\,i_2\ldots i_m}^{(m)} + \sum_{i_2,\ldots,i_m(\text{non-distinct})} u_i u_{i_2} \cdots u_{i_m}}{\left(\sum_{i_1,\ldots,i_m(\text{distinct})} \mathcal{A}_{i_1 i_2\ldots i_m}^{(m)} + \sum_{i_1,\ldots,i_m(\text{non-distinct})} u_{i_1} \cdots u_{i_m}\right)^{(m-1)/m}}. \tag{3.18}$$

Let $N_m = \lceil \frac{m-1}{2} \rceil$. Initialize at $u^{(0)} = \mathbf{0}_n$, compute $u^{(k)} = L(u^{(k-1)})$ iteratively for $k = 1, \ldots, N_m$, and output $u^{(N_m)}$ as $\eta^{(m)}$. Next, we construct a statistic $Q_n^{(m)}$ to capture the difference between $\mathcal{A}^{(m)}$ and a rank-1 estimate of the Bernoulli probability tensor. Let $\mathcal{A}^{*(m)}$ be a tensor of the same size as $\mathcal{A}^{(m)}$, where $\mathcal{A}_{i_1\ldots i_m}^{*(m)} = \mathcal{A}_{i_1\ldots i_m}^{(m)} - \eta_{i_1}^{(m)} \cdots \eta_{i_m}^{(m)}$ for $1 \leq i_1, \ldots, i_m \leq n$. We say that $S = (S_1, S_2, \ldots, S_{m+1})$ is an $(m+1)$-partition of $\{1, 2, \ldots, n\}$ if $S_1, \ldots, S_{m+1}$ are disjoint and their union is $\{1, 2, \ldots, n\}$. Let B be the set of all $(m+1)$-partitions. For each $S = (S_1, \ldots, S_{m+1}) \in B$ and $1 \leq k_1, \ldots, k_m \leq m + 1$, let $X_{S,k_1\ldots k_m}^{(m)} = \sum_{i_1 \in S_{k_1}, \ldots, i_m \in S_{k_m}(\text{distinct})} \mathcal{A}_{i_1\ldots i_m}^{*(m)}$. Let $Q_n^{(m)} = \max_{S=(S_1,\ldots,S_{m+1}) \in B} \max_{1 \leq k_1,\ldots,k_m \leq m+1}\{|X_{S,k_1\ldots k_m}^{(m)}|\}$. Finally, we combine $Q_n^{(2)}, \ldots, Q_n^{(M)}$. For each m, let $V_n^{(m)} = \binom{n}{m}\hat{\alpha}_n(1 - \hat{\alpha}_n)$, where $\hat{\alpha}_n = [(n-m)!/n!] \sum_{i_1,\ldots,i_m=1}^n \mathcal{A}_{i_1\ldots i_m}^{(m)}$. The test statistic is $\phi_n = \max_{2 \leq m \leq M}\{\phi_n^{(m)}\}$ where $\phi_n^{(m)} = Q_n^{(m)}/[n \log(n)^{1.1} V_n^{(m)}]^{1/2}$.

Recall that by Theorem 3.1, for any alternative with $\max_{2 \leq m \leq M}\{\ell_m\} = o(1)$, we can pair it with a null so that the pair are asymptotically indistinguishable. The next theorem says that the proposed test statistic ϕ_n can successfully separate any alternative satisfying $\max_{2 \leq m \leq M}\{\ell_m\} \gg \log^{1+\delta}(n)$ (for some $\delta > 0$; taking $\delta = 0.1$ is adequate) from the null. Therefore, except for a logarithmic factor, our lower bounds are tight. Recall that $\ell_m = \|\theta^{(m)}\|_1^{m-2}\|\theta^{(m)}\|^2(\mu_2^{(m)})^2$. Let $\theta_{max}^{(m)}$ and $\theta_{min}^{(m)}$ be the maximum and minimum entry of the vector $\theta^{(m)}$, respectively.

Theorem 3.2 (Tightness of lower bounds). *Consider the general tensor-DCBM model with $M \geq 2$. Let $h = \frac{1}{n}\sum_{i=1}^n \pi_i$, and let $P^{(m)} \in \mathbb{R}^{K, K^{m-1}}$ be the matricization of $\mathcal{P}^{(m)}$. Suppose $\|P^{(m)}\| \leq C$, $\max_{1 \leq k \leq K}\{h_k\} \leq C \min_{1 \leq k \leq K}\{h_k\}$, $\theta_{\max}^{(m)} \leq C\theta_{\min}^{(m)}$, $\theta_{\max}^{(m)} \leq c_0$ for a constant $c_0 < 1$, and $\|\theta^{(m)}\|_1^{m-2}\|\theta^{(m)}\|^2/\log(n) \to \infty$, for every $2 \leq m \leq M$. Then, $\phi_n \to 0$ in probability, if H_0 holds, and $\phi_n \to \infty$ in probability, if H_1 holds and $\max_{2 \leq m \leq M}\{\ell_m\}/[\log^{1.1}(n)] \to \infty$.*

To speed up the computation of ϕ_n for large n, we introduce a proxy statistic by replacing the search over B by a specific $\hat{B}$ as follows: conduct SVD on the matricization of $\mathcal{A}^{(m)}$, take the first $(m+1)$ left singular vectors, and apply the spectral algorithm [13] to partition nodes into $(m+1)$ groups. As long as the hypergraph is not too sparse, this proxy works well and is computationally much faster.

4 Numerical study

We use simulated data to validate our theoretical results. Fix $(n, K, m) = (500, 2, 3)$. In **Experiment 1**, we consider the SBM model and verify that the Regions of Impossibility are different for symmetric and asymmetric SBM (see Section 2.4). Let $\theta_i = n^{-1/2}$ for $1 \leq i \leq n$, and $\mathcal{P}_{ijk} = 1$ if $i = j = k$ and $\mathcal{P}_{ijk} = 1/4$ otherwise. We consider a symmetric case where each communities have 250 nodes and an asymmetric case where two communities have 375 and 125 nodes, respectively. For each setting, we randomly generate the hypergraphs, apply the degree-based χ^2-statistic ψ_n in Section 2.4, and repeat for 500 times. The histograms of ψ_n for two cases are on the left panel of the figure below (green: symmetric alternative; red: asymmetric alternative; blue: density of $N(0,1)$). By Lemma 2.2, $\psi_n \approx N(0,1)$ in the null. Hence, the results suggest that ψ_n is unable to distinguish the symmetric alternative from the null but can distinguish the asymmetric alternative from the null.

In **Experiment 2**, we consider DCBM and use the least-favorable configuration in Section 2.2 where the degree matching strategy is employed. We verify that a degree-based test such as ψ_n indeed has no power. Let (n, K, m) be the same as above. In the null, we let θ_i be iid drawn from $\mathrm{Pareto}(0.5, 5)$ and then re-normalize the vector of θ so that $n^{-2}\|\theta\|_1\|\theta\|^2 = c_n$, for $c_n = n^{-1}$; in the alternative, let $(\mathcal{P}^*, h)$ be the same as in the asymmetric case in Experiment 1 and generate θ_i^* as in (2.12) (D is obtained by treating $D(\mathcal{P}(Dh))Dh = 1_K$ as a nonlinear equation and apply the Matlab function `solve`). The histograms of ψ_n under the null (green) and alternative (red) are shown on the middle panel of the figure below. The two histograms are inseparable from each other.

In **Experiment 3**, we study the test statistic ϕ_n proposed in Section 3.1. The simulation setting is the same as that in Experiment 2, except that $c_n = n^{-1/2}$. To save computing time, we use the proxy of ϕ_n by plugging in a $\hat{B}$ from spectral clustering (see Section 3.1). The histograms of the test statistic under the null (green) and alternative (red) are shown on the right panel of the figure above. We see that ϕ_n successfully distinguishes the alternative from the null. This validates our result in Theorem 3.2. The distribution of ϕ_n in the alternative has two modes, due to that the proxy $\hat{B}$ we plug in has two most frequent realizations. However, this does not affect the testing performance.

5 Conclusion

We consider the problem of global testing for non-uniform hypergraphs in a broad DCMM setting. Given an alternative, how to identify *the null that is hardest to separate from the alternative* is a challenging problem. We solve this by proposing a degree matching strategy, and use it to derive a tight lower bound by tensor scaling techniques and delicate analysis of the χ^2-divergence. We discover that for an m-uniform hypergraph, the Regions of Impossibility/Possibility are governed by the simply quantity of $\ell_m = \|\theta^{(m)}\|_1^{m-2}\|\theta^{(m)}\|^2(\mu_2^{(m)})^2$ (and so those for a non-uniform hypergraph are governed by $\max_{2 \leq m \leq M}\{\ell_m\}$). We also propose a new test that attains the lower bounds, so our lower bounds are tight. For future work, we notice that the test in Section 3.1 is computationally expensive. It is desirable to find some fast algorithms that also achieve the lower bounds. The signed-cycle statistics [6, 14] are polynomial-time statistics that have shown appealing performance for network global testing. It is possible that these statistics can be generalized to hypergraphs to provide polynomial-time tests that are also theoretically optimal. We leave it to future study.

References

[1] Sameer Agarwal, Jongwoo Lim, Lihi Zelnik-Manor, Pietro Perona, David Kriegman, and Serge Belongie. Beyond pairwise clustering. In *2005 IEEE Computer Society Conference on*

Computer Vision and Pattern Recognition (CVPR'05), volume 2, pages 838–845. IEEE, 2005.

[2] Kwangjun Ahn, Kangwook Lee, and Changho Suh. Community recovery in hypergraphs. *IEEE Transactions on Information Theory*, 65(10):6561–6579, 2019.

[3] Ravindra Bapat. D1ad2 theorems for multidimensional matrices. *Linear Algebra and its Applications*, 48:437–442, 1982.

[4] Javier Béjar, Sergio Álvarez, Dario García, Ignasi Gómez, Luis Oliva, Arturo Tejeda, and Javier Vázquez-Salceda. Discovery of spatio-temporal patterns from location-based social networks. *J. Exp. Theor. Artif. Intell.*, 28(1-2):313–329, 2016.

[5] Austin R Benson, David F Gleich, and Jure Leskovec. Higher-order organization of complex networks. *Science*, 353(6295):163–166, 2016.

[6] Sébastien Bubeck, Jian Ding, Ronen Eldan, and Miklós Z Rácz. Testing for high-dimensional geometry in random graphs. *Random Struct. Algor.*, 49(3):503–532, 2016.

[7] I Chien, Chung-Yi Lin, and I-Hsiang Wang. Community detection in hypergraphs: Optimal statistical limit and efficient algorithms. In *International Conference on Artificial Intelligence and Statistics*, pages 871–879, 2018.

[8] Shmuel Friedland. Positive diagonal scaling of a nonnegative tensor to one with prescribed slice sums. *Linear algebra and its applications*, 434(7):1615–1619, 2011.

[9] Debarghya Ghoshdastidar and Ambedkar Dukkipati. Consistency of spectral partitioning of uniform hypergraphs under planted partition model. *Advances in Neural Information Processing Systems*, 27:397–405, 2014.

[10] Debarghya Ghoshdastidar and Ambedkar Dukkipati. Consistency of spectral hypergraph partitioning under planted partition model. *The Annals of Statistics*, 45(1):289–315, 2017.

[11] Jacopo Grilli, György Barabás, Matthew J Michalska-Smith, and Stefano Allesina. Higher-order interactions stabilize dynamics in competitive network models. *Nature*, 548(7666):210, 2017.

[12] Pengsheng Ji, Jiashun Jin, Zheng Tracy Ke, and Wanshan Li. The phase ii data for the networks of statisticians. *Manuscript*, 2019.

[13] Jiashun Jin. Fast community detection by SCORE. *The Annals of Statistics*, 43(1):57–89, 2015.

[14] Jiashun Jin, Zheng Tracy Ke, and Shengming Luo. Optimal adaptivity of signed-polygon statistics for network testing. *Manuscript*, 2019.

[15] Zheng Tracy Ke, Feng Shi, and Dong Xia. Community detection for hypergraph networks via regularized tensor power iteration. *arXiv preprint arXiv:1909.06503*, 2019.

[16] Chiheon Kim, Afonso S Bandeira, and Michel X Goemans. Stochastic block model for hypergraphs: Statistical limits and a semidefinite programming approach. *arXiv:1807.02884*, 2018.

[17] Sungwoong Kim, Sebastian Nowozin, Pushmeet Kohli, and Chang Yoo. Higher-order correlation clustering for image segmentation. *Advances in neural information processing systems*, 24:1530–1538, 2011.

[18] Lei Li and Tao Li. News recommendation via hypergraph learning: encapsulation of user behavior and news content. In *Proceedings of the sixth ACM international conference on Web search and data mining*, pages 305–314, 2013.

[19] Chung-Yi Lin, I Eli Chien, and I-Hsiang Wang. On the fundamental statistical limit of community detection in random hypergraphs. In *2017 IEEE International Symposium on Information Theory (ISIT)*, pages 2178–2182. IEEE, 2017.

[20] Mingao Yuan, Ruiqi Liu, Yang Feng, and Zuofeng Shang. Testing community structures for hypergraphs. *arXiv preprint arXiv:1810.04617*, 2018.

[21] Dengyong Zhou, Jiayuan Huang, and Bernhard Schölkopf. Learning with hypergraphs: Clustering, classification, and embedding. *Advances in neural information processing systems*, 19:1601–1608, 2006.