Representation Learning Beyond Linear Prediction Functions

Abstract

Recent papers on the theory of representation learning has shown the importance of
a quantity called diversity when generalizing from a set of source tasks to a target
task. Most of these papers assume that the function mapping shared representations
to predictions is linear, for both source and target tasks. In practice, researchers in
deep learning use different numbers of extra layers following the pretrained model
based on the difficulty of the new task. This motivates us to ask whether diversity
can be achieved when source tasks and the target task use different prediction
function spaces beyond linear functions. We show that diversity holds even if the
target task uses a neural network with multiple layers, as long as source tasks use
linear functions. If source tasks use nonlinear prediction functions, we provide
a negative result by showing that depth-1 neural networks with ReLu activation
function need exponentially many source tasks to achieve diversity. For a general
function class, we find that eluder dimension gives a lower bound on the number
of tasks required for diversity. Our theoretical results imply that simpler tasks
generalize better. Though our theoretical results are shown for the global minimizer
of empirical risks, their qualitative predictions still hold true for gradient-based
optimization algorithms as verified by our simulations on deep neural networks.

1   Introduction

It has become a common practice (Tan et al., 2018) to use a pre-trained network as the representation
for a new task with *small* sample size in various areas including computer vision (Marmanis et al.,
2015), speech recognition (Dahl et al., 2011; Jaitly et al., 2012; Howard and Ruder, 2018) and
machine translation (Weng et al., 2020). Most representation learning is based on the assumption that
the source tasks and the target task share the same low-dimensional representation.

In this paper, we follow the previous work (Tripuraneni et al., 2020) on representation learning by
assuming each task, labeled by t, generates observations noisily from the mean function $f_t^* \circ h^*$, where
h^* is the true representation shared by all the tasks and f_t^* is called the prediction function. We assume
$h^* \in \mathcal{H}$, the representation function space and $f_t \in \mathcal{F}_t$, the prediction function space. Tripuraneni
et al. (2020) proposed a diversity condition which guarantees that the learned representation will
generalize to target tasks with any prediction function. Assume we have T source tasks labeled by
$1, \dots, T$ and $\mathcal{F}_1 = \cdots = \mathcal{F}_T = \mathcal{F}_{so}$. We denote the target task by ta and let $\mathcal{E}_t(f, h) \in \mathbb{R}$ be the
excess error of $f, h \in \mathcal{F}_t \times \mathcal{H}$ for task t. The diversity condition can be stated as follows: there exists
some $\nu > 0$, such that for any $f_{ta}^* \in \mathcal{F}_{ta}$ and any $h \in \mathcal{H}$,

$$\underbrace{\inf_{f_{ta} \in \mathcal{F}_{ta}} \mathcal{E}_{ta}(f_{ta}, h)}_{\text{Excess error given } h \text{ for target task}} \leq \nu \underbrace{\inf_{f_t \in \mathcal{F}_{so}, t=1,\dots,T} \frac{1}{T} \sum_{t=1}^{T} \mathcal{E}_t(f_t, h)}_{\text{Excess error given } h \text{ for source tasks}}.$$

The diversity condition relates the excess error for source tasks and the target task with respect to any fixed representation h. A smaller ν indicates a better transfer from source tasks to the target task. Generally, we say T source tasks achieve diversity over $\mathcal{F}_{ta}$ when ν is finite and relatively small.

The number of source tasks plays an important role here. To see this, assume $\mathcal{F}_{so} = \mathcal{F}_{ta} = \mathcal{F}$ is a discrete function space and each function can be arbitrarily different. In this case, we will need the target task to be the same as at least one source task, which in turn requires $T \geq |\mathcal{F}|$ and $\nu \geq |\mathcal{F}|$. So far, it has only been understood that when *both* source tasks and target task use *linear* prediction functions, it takes at least d source tasks to be diverse, where d is the number of dimension of the linear mappings. This paper answers the following two open questions with a focus on the deep neural network (DNN) models:

How does representation learning work when $\mathcal{F}_{so} \neq \mathcal{F}_{ta}$?
How many source tasks do we need to achieve diversity with nonlinear prediction functions?

There are strong practical motivations to answer the above two questions. In practice, researchers use representation learning despite the difference in difficulty levels of source and target tasks. We use a more complex function class for substantially harder target task, which means $\mathcal{F}_{so} \neq \mathcal{F}_{ta}$. This can be reflected as extra layers when a deep neural network model is used as prediction functions. On the other hand, the source task and target task may have different objectives. Representation pretrained on a classification problem, say ImageNet, may be applied to object detection or instance segmentation problems. For instance, Oquab et al. (2014) trained a DNN on ImageNet and kept all the layers as the representation except for the last linear mapping, while two fully connected layers are used for the target task on object detection.

Another motivation for our work is the mismatch between recently developed theories in representation learning and the common practice in empirical studies. Recent papers on the theory of representation learning all require multiple sources tasks to achieve diversity so as to generalize to any target task in $\mathcal{F}$ (Maurer et al., 2016; Du et al., 2020; Tripuraneni et al., 2020). However, most pretrained networks are only trained on a single task, for example, the ImageNet pretrained network. To this end, we will show that a single multi-class classification problem can be diverse.

Lastly, while it is common to simply use linear mapping as the source prediction function, there is no clear theoretical analysis showing whether or not diversity can be achieved with *nonlinear* prediction function spaces.

Main contributions. We summarize the main contributions made by this paper.

1. We show that diversity over $\mathcal{F}_{so}$ implies diversity over $\mathcal{F}_{ta}$, when both $\mathcal{F}_{so}$ and $\mathcal{F}_{ta}$ are DNNs and $\mathcal{F}_{ta}$ has more layers. More generally, the same statement holds when $\mathcal{F}_{ta}$ is more complicated than $\mathcal{F}_{so}$, in the way that $\mathcal{F}_{ta} = \mathcal{F}'_{ta} \circ (\mathcal{F}_{so}^{\otimes m})$ for some positive integer m[1] and function class $\mathcal{F}'_{ta}$.

2. Turning our attention to the analysis of diversity for non-linear prediction function spaces, we show that for a depth-1 NN, it requires $\Omega(2^d)$ many source tasks to establish diversity with d being the representation dimension. For general $\mathcal{F}_{so}$, we provide a lower bound on the number of source tasks required to achieve diversity using the eluder dimension (Russo and Van Roy, 2013) and provide a upper bound using the generalized rank (Li et al., 2021).

3. We show that a single source tasks with multiple outputs can be equivalent to multiple source tasks. While our theories are built on empirical risk minimization, our simulations on DNNs for a multi-variate regression problem show that the general statement still hold when a stochastic gradient descent is used for optimization.

2 Preliminaries

We first introduce the mathematical setup of the problem studied in this paper along with the two-phase learning method that we will focus on.

---

[1] $\mathcal{F}^{\otimes T}$ is the T times Cartesian product of $\mathcal{F}$.

Problem setup. Let $\mathcal{X}$ denote the input space. We assume the same input distribution P_X for all tasks, as covariate shift is not the focus of this work. In our representation learning setting, there exists a generic feature representation function $h^* \in \mathcal{H} : \mathcal{X} \mapsto \mathcal{Z}$ that is shared across different tasks, where $\mathcal{Z}$ is the feature space and $\mathcal{H}$ is the representation function space. Since we only consider the different prediction functions, each task, indexed by t, is defined by its prediction function $f_t^* \in \mathcal{F}_t : \mathcal{Z} \mapsto \mathcal{Y}_t$, where $\mathcal{F}_t$ is the prediction function space of task t and $\mathcal{Y}_t$ is the corresponding output space. The observations $Y_t = f_t^* \circ h^*(X) + \epsilon$ are generated noisily with mean function $f_t^* \circ h^*$, where $X \sim P_X$ and ϵ is zero-mean noise that is independent of X.

Our representation is learned on source tasks $\boldsymbol{f}_{so}^* := (f_1^*, \ldots, f_T^*) \in \mathcal{F}_1 \times \cdots \times \mathcal{F}_T$ for some positive integer T. We assume that all the prediction function spaces $\mathcal{F}_t = \mathcal{F}_{so}$ are the same over the source tasks. We denote the target task by $f_{ta}^* \in \mathcal{F}_{ta}$, where $\mathcal{F}_{ta}$ is the target prediction function space. Unlike the previous papers (Du et al., 2020; Tripuraneni et al., 2020; Maurer et al., 2016), which all assume that the same prediction function space is used for all tasks, we generally allow for the possibility that $\mathcal{F}_{so} \neq \mathcal{F}_{ta}$.

Learning algorithm. We consider the same two-phase learning method as in Tripuraneni et al. (2020). In the first phase (the training phase), $\boldsymbol{n} = (n_1, \ldots, n_T)$ samples from each task are available to learn a good representation. In the second phase (the test phase), we are presented n_{ta} samples from the target task to learn its prediction function using the pretrained representation learned in the training phase.

We denote a dataset of size n from task f_t by $S_t^n = \{(x_{ti}, y_{ti})\}_{i=1}^n$. We use empirical risk minimization (ERM) for both phase. In the training phase, we minimize average risks over $\{S_t^{n_t}\}_{t=1}^T$:

$$\hat{R}(\boldsymbol{f}, h \mid \boldsymbol{f}_{so}^*) := \frac{1}{\sum_t n_t} \sum_{t=1}^T \sum_{i=1}^{n_t} l_{so}(f_t \circ h(x_{ti}), y_{ti}),$$

where $l_{so} : \mathcal{Y} \times \mathcal{Y} \mapsto \mathbb{R}$ is the loss function for the source tasks and $\boldsymbol{f} = (f_1, \ldots, f_T) \in \mathcal{F}_{so}^{\otimes T}$. The estimates are given by $(\hat{\boldsymbol{f}}_{so}, \hat{h}) \in \arg\min_{\boldsymbol{f}, h} \hat{R}(\boldsymbol{f}, h \mid \boldsymbol{f}_{so}^*)$. In the second phase, we obtain the dataset $\{x_{ta,i}, y_{ta,i}\}_i^{n_{ta}}$ from the target task and our predictor $\hat{f}_{ta}$ is given by

$$\arg\min_{f \in \mathcal{F}_{ta}} \hat{R}(f, \hat{h} \mid f_{ta}^*) := \frac{1}{n_{ta}} \sum_{i=1}^{n_{ta}} l_{ta}(f \circ \hat{h}(x_{ta,i}), y_{ta,i}),$$

for some loss function l_{ta} on the target task. We also use $R(\cdot, \cdot \mid \cdot)$ for the expectation of the above empirical risks. We denote the generalization error of certain estimates f, h by $\mathcal{E}(f, h \mid \cdot) := R(f, h \mid \cdot) - \min_{f' \in \mathcal{F}, h' \in \mathcal{H}} R(f', h' \mid \cdot)$, where $\mathcal{F}$ can be either $\mathcal{F}_{so}^{\otimes T}$ or $\mathcal{F}_{ta}$ depending on the tasks. Our goal is to bound the generalization error of the target task.

For simplicity, our results are presented under square loss functions. However, we show that our results can generalize to different loss functions in Appendix G. We also assume $n_1 = \cdots = n_T = n_{so}$ for some positive integer n_{so}.

2.1 Model complexity

As this paper considers general function classes, our results will be presented in terms of the complexity measures of classes of functions. We follow the previous literature (Maurer et al., 2016; Tripuraneni et al., 2020) which uses Gaussian complexity. Note that we do not use the more common Rademacher complexity as the proofs require a decomposition theorem that only holds for Gaussian complexity.

For a generic vector-valued function class $\mathcal{Q}$ containing functions $q : \mathbb{R}^d \mapsto \mathbb{R}^r$ and N data points, $X_N = (\boldsymbol{x}_1, \ldots, \boldsymbol{x}_N)^T$, the empirical Gaussian complexity is defined[2] as

$$\hat{\mathfrak{G}}_N(\mathcal{Q}) = \mathbb{E}_{\mathbf{g}} \left[\sup_{\mathbf{q} \in \mathcal{Q}} \frac{1}{\sqrt{N}} \sum_{i=1}^N g_i^T q(\boldsymbol{x}_i) \right], \quad g_i \sim \mathcal{N}(0, I_r) \quad i.i.d.$$

---

[2] Note that the standard definition has a $1/N$ factor instead of $1/\sqrt{N}$. We use the variant so that $\hat{\mathfrak{G}}_N$ does not scale with N in most of the cases we consider and only reflects the complexity of the class.

94 The corresponding population Gaussian complexity is defined as $\mathfrak{G}_N(\mathcal{Q}) = \mathbb{E}_{X_N}\left[\hat{\mathfrak{G}}_N(\mathcal{Q})\right]$, where

95 the expectation is taken over the distribution of X_N.

2.2 Diversity

97 Source tasks have to be diverse enough, to guarantee that the representation learned from source tasks
98 can be generalized to any target task in $\mathcal{F}_{ta}$. To measure when transfer can happen, we introduce the
99 following two definitions, namely that of *transferability* and *diversity*.

Definition 1. *For some $\nu, \mu > 0$, we say the source tasks $f_1^*, \ldots, f_T^* \in \mathcal{F}_{so}$ are (ν, μ)-transferable to task f_{ta}^* if*

$$\sup_{h \in \mathcal{H}} \frac{\inf_{f \in \mathcal{F}_{ta}} \mathcal{E}(f, h \mid f_{ta}^*)}{\inf_{\boldsymbol{f} \in \mathcal{F}_{so}^{\otimes T}} \mathcal{E}(\boldsymbol{f}, h \mid \boldsymbol{f}_{so}^*) + \mu/\nu} \leq \nu.$$

Furthermore, we say they are (ν, μ)-diverse over $\mathcal{F}_{ta}$ if above ratio is bounded for any true target prediction functions $f_{ta}^* \in \mathcal{F}_{ta}$, i.e.

$$\sup_{f_{ta}^* \in \mathcal{F}_{ta}} \sup_{h \in \mathcal{H}} \frac{\inf_{f \in \mathcal{F}_{ta}} \mathcal{E}(f, h \mid f_{ta}^*)}{\inf_{\boldsymbol{f} \in \mathcal{F}_{so}^{\otimes T}} \mathcal{E}(\boldsymbol{f}, h \mid \boldsymbol{f}_{so}^*) + \mu/\nu} \leq \nu.$$

100 When it is clear from the context, we denote $\mathcal{E}(f, h \mid f_{ta}^*)$ and $\mathcal{E}(\boldsymbol{f}, h \mid \boldsymbol{f}_{so}^*)$ by $\mathcal{E}_{ta}(f, h)$ and
101 $\mathcal{E}_{so}(\boldsymbol{f}, h)$, respectively. We will call ν the transfer component and μ, the bias introduced by transfer.
102 The definition of transferable links the generalization error between source tasks and the target task
103 as shown in Theorem 1. The proof can be found in Appendix A.

Theorem 1. *If source tasks $f_1^*, \ldots, f_T^*$ are (ν, μ)-diverse over $\mathcal{F}_{ta}$, then for any $f_{ta}^* \in \mathcal{F}_{ta}$, we have*

$$\mathcal{E}_{ta}(\hat{f}_{ta}, \hat{h}) \leq \nu \mathcal{E}_{so}(\hat{\boldsymbol{f}}_{so}, \hat{h}) + \mu + \frac{\sqrt{2\pi}\hat{\mathfrak{G}}_{n_{ta}}\left(\mathcal{F}_{ta} \circ \hat{h}\right)}{\sqrt{n_{ta}}} + \sqrt{\frac{9\ln(2/\delta)}{2n_{ta}}}.$$

104 The first term in Theorem 1 can be upper bounded using the standard excess error bound of Gaussian
105 complexity. The benefit of representation learning is due to the decrease in the third term from
106 $\hat{\mathfrak{G}}_{n_{ta}}(\mathcal{F}_{ta} \circ \mathcal{H})/\sqrt{n_{ta}}$ without representation learning to $\hat{\mathfrak{G}}_{n_{ta}}(\mathcal{F}_{ta} \circ \hat{h})/\sqrt{n_{ta}}$ in our case. For the
107 problem with complicated representations, the former term can be extremely larger than the later one.

108 In the rest of the paper, we discuss when we can bound (ν, μ), for nonlinear and nonidentical $\mathcal{F}_{so}$
109 and $\mathcal{F}_{ta}$.

3 Negative transfer when source tasks are more complex

111 Before introducing the cases that allow transfer, we first look at a case where transfer is impossible.

112 Let the source task use a linear mapping following the shared representation and the target task
113 directly learns the representation. In other words, f_{ta}^* is identical mapping and known to the learner.
114 We further consider $\mathcal{F}_{so} = \{z \mapsto w^T z : w \in \mathbb{R}^p\}$ and $\mathcal{H} = \{x \mapsto Hx : H \in \mathbb{R}^{p \times d}\}$. The interesting
115 case is when $p \ll d$. Let the optimal representation be H^* and the true prediction function for each
116 source task be $w_1^*, \ldots, w_T^*$. In the best scenario, we assume that there is no noise in the source
117 tasks and each source task collects as many samples as possible, such that we will have an accurate
118 estimation on each $w_t^{*T}H^* \in \mathbb{R}^{p \times d}$ which we denote by W_t^*.

However, the hypothesis class given the information from source tasks are

$$\{H \in \mathbb{R}^{p \times d} : \exists w \in \mathbb{R}^p, w^T H = W_t \text{ for all } t = 1, \ldots, T\}.$$

119 As H^* is in the above class, any QH^* for some rotation matrix $Q \in \mathbb{R}^{p \times p}$ is also in the class. In
120 other words, a non-reducible error of learnt representation is $\max_Q \|H^* - QH^*\|_2^2$ in the worst case.

121 More generally, we give a condition for negative transfer. Consider a single source task f_{so}^*. Let
122 $\mathcal{H}_{so}^* := \arg\min_{h \in \mathcal{H}} \min_{f \in \mathcal{F}_{so}} \mathcal{E}_{so}(f, h)$ and $\mathcal{H}_{ta}^* := \arg\min_{h \in \mathcal{H}} \min_{f \in \mathcal{F}_{ta}} \mathcal{E}_{ta}(f, h)$. In fact, if
123 one hopes to get a representation learning benefit with zero bias ($\mu = 0$), we need all $h \in \mathcal{H}_{so}^*$ to
124 satisfy $\inf_{f \in \mathcal{F}_{ta}} \mathcal{E}_{ta}(f, h) = 0$, i.e. any representation that is optimal in the source task is optimal
125 in the target task as well. Equivalently, we will need $\mathcal{H}_{so}^* \subset \mathcal{H}_{ta}^*$. As shown in Proposition 1, the
126 definition of *transferable* captures the case well.

127 **Proposition 1.** *If there exists a $h' \in \mathcal{H}_{so}^*$ such that $h' \notin \mathcal{H}_{ta}^*$, then $\min_{f_{ta}} \mathcal{E}_{ta}(f_{ta}, h') > 0$.*
128 *Furthermore, there is no $\nu < \infty$, such that f_{so}^* is $(\nu, 0)$-transferable to f_{ta}^*.*

129 *Proof.* The first statement is by definition. Plugging g' into the Definition 1, we will have $\nu = \infty$ □

130 The negative transfer happens when the optimal representation for source tasks may not be optimal
131 for the target task. As the case in our linear example, this is a result of more complex $\mathcal{F}_{so}$, which
132 allows more flexibility to reduce errors. This inspires us to consider the opposite case where $\mathcal{F}_{ta}$ is
133 more complex than $\mathcal{F}_{so}$.

4   Source task as a representation

135 Before discussing more general settings, we first consider a single source task, which we refer to
136 so. Assume that the source task itself is a representation of the target task. Equivalently, the source
137 task has a known prediction function $f_{so}^*(x) = x$. This is a commonly-used framework when we
138 decompose a complex task into several simple tasks and use the output of simple tasks as the input of
139 a higher-level task.

140 A widely-used transfer learning method, called offset learning, which assumes $f_{ta}^*(x) = f_{so}^*(x) +$
141 $w_{ta}^*(x)$ for some offset function w_{ta}^*, also applies here. The offset method enjoys its benefits when
142 w_{ta} has low complexity and can be learnt with few samples. It is worth mentioning that our setting
143 covers a more general setting in Du et al. (2017), which assumes $f_{ta}^*(x) = G(f_{so}^*(x), w_{ta}^*(x))$ for
144 some known transformation function G and unknown w_{ta}^*.

145 We show that a simple Lipschitz condition on $\mathcal{F}_{ta}$ gives us a bounded transfer-component.

146 **Assumption 1** (Lipschitz assumption). *Any $f_{ta} \in \mathcal{F}_{ta}$ is L-Lipschitz with respect to L_2 distance.*

Theorem 2. *If Assumption 1 holds, task so is $(L, 0)$-transferable to task ta and we have with a high probability,*

$$\mathcal{E}_{ta}(\hat{f}_{ta}, \hat{h}) = \tilde{\mathcal{O}} \left(\frac{L\hat{\mathfrak{G}}_{n_{so}}(\mathcal{H})}{\sqrt{n_{so}}} + \frac{\hat{\mathfrak{G}}_{n_{ta}}(\mathcal{F}_{ta} \circ \hat{h})}{\sqrt{n_{ta}}} \right).$$

147 Theorem 2 bounds the generalization error of two terms. The first term that scales with $1/\sqrt{n_{so}}$ only
148 depends on the complexity of $\mathcal{H}$. Though the second term scales with $1/\sqrt{n_{ta}}$, it is easy to see that
149 $\hat{\mathfrak{G}}_{n_{ta}}(\mathcal{F}_{ta} \circ \hat{h}) = \hat{\mathfrak{G}}_{n_{ta}}(\mathcal{F}_{ta}) \ll \hat{\mathfrak{G}}_{n_{ta}}(\mathcal{F}_{ta} \circ \mathcal{H})$ with the dataset $\{\hat{h}(x_{ta,i})\}_{i=1}^{n_{ta}}$.

4.1   General case

151 Previously, we assume that a single source task is a representation of the target task. Now we
152 consider a more general case: there exist functions in the source prediction space that can be used
153 as representations of the target task. Formally, we consider $\mathcal{F}_{ta} = \mathcal{F}_{ta}' \circ (\mathcal{F}_{so}^{\otimes m})$ for some $m > 0$
154 and some target-specific function space $\mathcal{F}_{ta}' : \mathcal{Y}_{so}^{\otimes m} \mapsto \mathcal{Y}_{ta}$. Note that $\mathcal{F}_{ta}$ is strictly larger than $\mathcal{F}_{so}$
155 when $m = 1$ and the identical mapping $x \mapsto x \in \mathcal{F}_{ta}'$. In practice, ResNet (Tai et al., 2017) satisfies
156 the above property.

157 **Assumption 2.** *Assume any $f_{ta}' \in \mathcal{F}_{ta}'$ is L'-Lipschitz with respect to L_2 distance.*

Theorem 3. *If Assumption 2 holds and the source tasks are (ν, μ)-diverse over its own space $\mathcal{F}_{so}$, then we have*

$$\mathcal{E}_{ta}\left(\hat{f}_{ta}, \hat{h}\right) = \tilde{\mathcal{O}} \left(L'm \left(\frac{\nu\hat{\mathfrak{G}}_{Tn_{so}}(\mathcal{F}_{so}^{\otimes T} \circ \mathcal{H})}{\sqrt{Tn_{so}}} + \mu \right) + \frac{\hat{\mathfrak{G}}_{n_{ta}}\left(\mathcal{F}_{ta} \circ \hat{h}\right)}{\sqrt{n_{ta}}} \right).$$

158 It is shown in Tripuraneni et al. (2020) that $\hat{\mathfrak{G}}_{\sum_s n_s}(\mathcal{F}_{so}^{\otimes S} \circ \mathcal{H})$ can be bounded by $\tilde{\mathcal{O}}(\hat{\mathfrak{G}}_{Tn_{so}}(\mathcal{H}) +$
159 $\sqrt{T}\hat{\mathfrak{G}}_{n_{so}}(\mathcal{F}_{so}))$. Thus, the first term scales with $\hat{\mathfrak{G}}_{Tn_{so}}(\mathcal{H})/\sqrt{Tn_{so}} + \hat{\mathfrak{G}}_{n_{so}}(\mathcal{F}_{so})/\sqrt{n_{so}}$. Again the
160 common part shared by all the tasks decreases with $\sqrt{Tn_{so}}$, while the task-specific part scales with
161 $\sqrt{n_{so}}$ or $\sqrt{n_{ta}}$.

4.2 Applications to deep neural networks

Theorem 3 has a broad range of applications. In the rest of the section, we discuss its application to deep neural networks, where the source tasks are transferred to a target task with a deeper network.

We first introduce the setting for deep neural network prediction function. We consider the regression problem with $\mathcal{Y}_{so} = \mathcal{Y}_{ta} = \mathbb{R}$ and the representation space $\mathcal{Z} \subset \mathbb{R}^p$. A depth-$K$ vector-valued neural network is denoted by

$$f(\mathbf{x}) = \sigma\left(\mathbf{W}_K\left(\sigma\left(\ldots\sigma\left(\mathbf{W}_1\mathbf{x}\right)\right)\right)\right),$$

where each $\mathbf{W}_k$ is a parametric matrix of layer k and σ is the activation function. For simplicity, we let $\mathbf{W}_k \in \mathbb{R}^{p \times p}$ for $k = 1, \ldots K$. The class of all depth-K neural network is denoted by $\mathcal{M}_K$. We denote the linear class by $\mathcal{L} = \{x \mapsto \alpha^T x + \beta : \forall \alpha \in \mathbb{R}^p, \|\alpha\|_2 \leq M(\alpha)\}$ for some $M(\alpha) > 0$. We also assume

$$\max\{\|W_k\|_\infty, \|W_k\|_2\|\} \leq M(k).$$

where $\|\cdot\|_\infty$ and $\|\cdot\|_2$ are the infinity norm and spectral norm. We assume any $z \in \mathcal{Z}, \|z\|_\infty \leq D_Z$.

Deeper network for the target task. We now consider the source task with prediction function of a depth-K_{so} neural network followed by a linear mapping and target task with depth-K_{ta} neural network. We let $K_{ta} > K_{so}$. Then we have

$$\mathcal{F}_{ta} = \mathcal{L} \circ \mathcal{M}_{K_{ta}-K_{so}} \circ \mathcal{M}_{K_{so}} \text{ and } \mathcal{F}_{so} = \mathcal{L} \circ \mathcal{M}_{K_{so}}.$$

Using the fact that $\mathcal{M}_1 = \sigma(\mathcal{L}^{\otimes p})$, we can write $\mathcal{F}_{ta}$ as $\mathcal{L} \circ \mathcal{M}_{K_{ta}-K_{so}-1} \circ \sigma \circ (\mathcal{F}_{so}^{\otimes p})$. Thus, we can apply Theorem 3 and the standard Gaussian complexity bound for DNN models, which gives us Corollary 1.

Corollary 1. *Let $\mathcal{F}_{so}$ be depth-K_{so} neural network and $\mathcal{F}_{ta}$ be depth-K_{ta} neural network. If source tasks are $(\nu, 0)$-diverse over $\mathcal{F}_{so}$, we have*

$$\mathcal{E}_{ta}\left(\hat{f}_{ta}, \hat{h}\right) =$$

$$\tilde{\mathcal{O}}\left(p\nu M(\alpha)\Pi_{k=1}^{K_{ta}}M(k)\left(\frac{\hat{\mathfrak{S}}_{Tn_{so}}(\mathcal{H})}{\sqrt{Tn_{so}}} + \frac{D_Z\sqrt{K_{so}}}{\sqrt{n_{so}}}\right) + \frac{D_Z\sqrt{K_{ta}} \cdot M(\alpha)\Pi_{k=1}^{K_{ta}}M(k)}{\sqrt{n_{ta}}}\right). \quad (1)$$

Note that the terms that scales with $1/\sqrt{n_{so}}$ and $1/\sqrt{n_{ta}}$ have similar coefficients $M(\alpha)\Pi_{k=1}^{K_{ta}}M(k)$, which do not depends on the complexity of $\mathcal{H}$. The term that depends on $\hat{\mathfrak{S}}_{Tn_{so}}(\mathcal{H})$ scales with $1/\sqrt{Tn_{so}}$ as we expected.

5 Diversity of non-linear function classes

While Corollary 1 considers the nonlinear DNN prediction function space under a diversity condition, it is not clearly understood how diversity can be achieved for nonlinear spaces. In this section, we first discuss a specific non-linear prediction function space and show a fundamental barrier to achieving diversity. Then we extend our result to general function classes by connecting eluder dimension and diversity. We end the section with positive results for achieving diversity under a generalized rank condition.

We consider a subset of depth-1 neural networks with ReLu activation function: $\mathcal{F} = \{x \mapsto [\langle x, w \rangle - (1 - \epsilon/2)]_+ : \|x\|_2 \leq 1, \|w\| \leq 1\}$ for some $\epsilon > 0$. Our lower bound construction is inspired by the similar construction in Theorem 5.1 of Dong et al. (2021).

Theorem 4. *Let $\mathcal{T} = \{f_1, \ldots, f_T\}$ be any set of depth-1 neural networks with ReLu activation in $\mathcal{F}$. For any $\epsilon > 0$, if $T \leq 2^{d \log(1/\epsilon)-1}$, there exists some representation $h^*, h' \in \mathcal{H}$, some distribution P_X and a target function $f_{ta}^* \in \mathcal{F}$, such that*

$$\inf_{\boldsymbol{f} \in \mathcal{F}} \mathcal{E}_{so}(\boldsymbol{f}, h') = 0, \quad \text{while} \quad \inf_{f \in \mathcal{F}} \mathcal{E}_{ta}(f, h') = \epsilon^2/32.$$

Theorem 4 implies that we need at least $\Omega(2^d \log(1/\epsilon))$ source tasks to achieve diversity. Otherwise, we can always find a set of source tasks and a target task such that the generalization error in source tasks are minimized to 0 while that in target task is $\epsilon^2/32$. Though ReLu gives us a more intuitive result, we do show that similar lower bounds can be shown for other popular activation functions, for example, sigmoid function (see Appendix D).

5.1 Lower bound using eluder dimension

We extend our result by considering a general function space $\mathcal{F}$ and build an interesting connection between diversity and eluder dimension (Russo and Van Roy, 2013). We believe we are the first to notice a connection between eluder dimension and transfer learning.

Eluder dimension has been used to measure the sample complexity in the Reinforcement Learning problem. It considers the minimum number of *inputs*, such that any two functions evaluated similarly at these inputs will also be similar at any other input. However, diversity considers the minimum number of functions such that any two representations with similar *outputs* for these functions will also have similar output for any other functions. Thus, there is a kind of duality between eluder dimension and diversity.

We first formally define eluder dimension. Let $\mathcal{F}$ be a function space with support $\mathcal{X}$ and let $\epsilon > 0$.

Definition 2 (($\mathcal{F}, \epsilon$)-dependence and eluder dimension (Osband and Van Roy (2014)))**.** *We say that* $x \in \mathcal{X}$ *is* ($\mathcal{F}, \epsilon$)-*dependent on* $\{x_1, \dots, x_n\} \subset \mathcal{X}$ *iff*

$$\forall f, \tilde{f} \in \mathcal{F}, \quad \sum_{i=1}^{n} \left\| f(x_i) - \tilde{f}(x_i) \right\|_2^2 \leq \epsilon^2 \implies \|f(x) - \tilde{f}(x)\|_2 \leq \epsilon.$$

We say $x \in \mathcal{X}$ *is* ($\mathcal{F}, \epsilon$)-*independent of* $\{x_1, \dots, x_n\}$ *iff it does not satisfy the definition of dependence.*

The eluder dimension $\dim_E(\mathcal{F}, \epsilon)$ *is the length of the longest possible sequence of elements in* $\mathcal{X}$ *such that for some* $\epsilon' \geq \epsilon$ *every element is* ($\mathcal{F}, \epsilon'$)-*independent of its predecessors.*

We slightly change the definition and let $\dim_E^s(\mathcal{F}, \epsilon)$ *be the shortest sequence such that any* $x \in \mathcal{X}$ *is* ($\mathcal{F}, \epsilon$)-*dependent on the sequence.*

Although $dim_E^s(\mathcal{F}, \epsilon) \leq dim_E(\mathcal{F}, \epsilon)$, it can be shown that in many regular cases, say linear case and generalized linear case, $dim_E(\mathcal{F}, \epsilon)$ is only larger then $dim_E^s(\mathcal{F}, \epsilon)$ up to a constant.

Theorem 5. *For any function class* $\mathcal{F} : \mathcal{X} \mapsto \mathbb{R}$, *and some* $\epsilon > 0$, *let* $\mathcal{F}^*$ *be the dual class of* $\mathcal{F}$. *Let* $d_E = \dim_E^s(\mathcal{F}^*, \epsilon)$. *Then for any sequence of tasks* $f_1, \dots, f_t$, $t \leq d_E - 1$, *there exists a task* $f_{t+1} \in \mathcal{F}$ *such that for some data distribution* P_X *and two representations* h, h^*,

$$\frac{\inf_{f'_{t+1} \in \mathcal{F}} \mathbb{E}_X \|f'_{t+1}(h(X)) - f_{t+1}(h^*(X))\|_2^2}{\frac{1}{t} \inf_{f'_1, \dots, f'_t} \sum_{i=1}^{t} \mathbb{E}_X \|f'_i(h(X)) - f_i(h^*(X))\|_2^2} \geq t/2.$$

Theorem 5 formally describes the connections between eluder dimension and diversity. To interpret the theorem, we first discuss what are good source tasks. Any T source tasks that are diverse could transfer well to a target task if the parameter ν could be bounded by some fixed value that is not increasing with T. For instance, in the linear case, $\nu = \mathcal{O}(d)$ no matter how large T is. While for a finite function class, in the worst case, ν will increase with T before T reaches $|\mathcal{F}|$. Theorem 5 states that if the eluder dimension of the dual space is at least d_E, then ν scales with T until T reaches d_E, as if the function space $\mathcal{F}$ is discrete with d_E elements.

Note that this result is consistent with what is shown in Theorem 7 as eluder dimension of the class discussed above is lower bounded by $\Omega(2^d)$ as well Li et al. (2021).

5.2 Upper bound using approximate generalized rank

Though we showed that diversity is hard to achieve in some nonlinear function class, we point out that diversity can be easy to achieve if we restrict the target prediction function such that they can be realized by linear combinations of some known basis. Tripuraneni et al. (2020) has shown that any source tasks $f_1, \dots, f_T \in \mathcal{F}$ are $(1/T, \mu)$-diverse over the space $\{f \in \mathcal{F} : \exists \tilde{f} \in \text{conv}(f_1, \dots, f_T) \text{ such that } \sup_z \|f(z) - \tilde{f}(z)\| \leq \mu\}$, where $\text{conv}(f_1, \dots, f_T)$ is the convex hull of $\{f_1, \dots, f_T\}$. This can be characterized by a complexity measure, called generalized rank. Generalized rank is the smallest dimension required to embed the input space such that all hypotheses in a function class can be realizable as halfspaces. Generalized rank has close connections to eluder dimension. As shown in Li et al. (2021), eluder dimension can be upper bounded by generalized rank.

Definition 3 (Approximate generalized rank with identity activation)**.** *Let* $\mathcal{B}_d(R) := \{x \in \mathbb{R}^d \mid \|x\|_2 \leq R\}$. *The* μ-*approximate* id-rk$(\mathcal{F}, \mathcal{R})$ *of a function class* $\mathcal{F} : \mathcal{X} \mapsto \mathbb{R}$ *at scale* R *is the*

smallest dimension d for which there exists mappings $\phi : \mathcal{X} \mapsto \mathcal{B}_d(1)$ and $w : \mathcal{F} \mapsto \mathcal{B}_d(R)$ such that

$$\text{for all } (x, f) \in \mathcal{X} \times \mathcal{F} : |f(x) - \langle w(f), \phi(x) \rangle| \leq \mu.$$

Proposition 2. *For any $\mathcal{F}$ with μ-approximate id-rank$(\mathcal{F}, R) \leq d_i$ for some $R > 0$, there exists no more than d_i functions, $f_1, \ldots, f_{d_i}$, such that $w(f_1), \ldots w(f_{d_i})$ span $\mathbb{R}^{d_{d_i}}$. Then $f_1, \ldots, f_{d_i}$ are (d_i, μ)-diverse over $\mathcal{F}$.*

Proposition 2 is a direct application of Lemma 7 in Tripuraneni et al. (2020). Upper bounding id-rank is hard for general function class. However, this notation can be useful for those function spaces with a known set of basis functions. For example, any function space $\mathcal{F}$ that is square-integrable has a Fourier basis. Though the basis is an infinite set, we can choose a truncation level d such that the truncation errors of all functions are less than μ. Then the hypothesis space $\mathcal{F}$ has μ-approximate id-rank less than d.

6 Experiments

In this section, we use simulated environments to evaluate the actual performance of representation learning on DNNs trained with gradient-based optimization methods. We also test the impact of various hyperparameters. Our results indicate that even though our theory is shown to hold for ERM estimators, their qualitative theoretical predictions still hold when Adam is applied and the global minima might not be found. Before we introduce our experimental setups, we discuss a difference between our theories and experiments: our experiments use a single regression task with multiple outputs as the source task, while our analyses are built on multiple source tasks.

6.1 Diversity of problems with multiple outputs

Though we have been discussing achieving diversity from multiple source tasks, we may only have access to a single source task in many real applications, for example, ImageNet, which is also the case in our simulations. In fact, we can show that diversity can be achieved by a single multiclass classification or multivariate regression source task. The diversity for the single multivariate regression problem with L2 loss is trivial as the loss function is decomposable. For multiclass classification problems or regression problems with other loss functions, we will need some assumptions on boundedness and continuous. We refer the readers to Appendix H for details.

6.2 Experiments setup

Our four experiments are designed for the following goals. The first two experiments (Figure 1, a and b) target on the actual dependence on n_{so}, n_{ta}, K_{so} and K_{ta} in Equation (1) that upper bounds the errors of DNN prediction functions. Though the importance of diversity has been emphasized by various theories, no one has empirically shown its benefits over random tasks selection, which we explore in our third experiment (Figure 1, c). Our fourth experiment (Figure 1, d) verifies the theoretical negative results of nonlinearity of source prediction functions showed in Theorem 4 and 5.

Though the hyper-parameters vary in different experiments, our main setting can be summarized below. We consider DNN models of different layers for both source and target tasks. The first K layers are the shared representation. The source task is a multi-variate regression problem with output dimension p and K_{so} layers following the representation. The target task is a single-output regression problem with K_{ta} layers following the representation. We used the same number of units for all the layers, which we denote by n_u. A representation is first trained on the source task using n_{so} random samples and is fixed for the target task, trained on n_{ta} random samples. In contrast, the baseline method trains the target task directly on the same n_{ta} samples without the pretrained network. We use Adam with default parameters for all the training. We use MSE (Mean Square Error) to evaluate the performance under different settings.

6.3 Results

Figure 1 summaries our four experiments, with all the Y axes representing the average MSE's of 100 independent runs with an error bar showing the standard deviation. The X axis varies depending on the goal of each experiment. In subfigure (a), we test the effects of the numbers of observations

272 for both source and target tasks, while setting other hyperparameters by default values. The X axis
273 represents n_{so} and the colors represents n_{ta}. In subfigure (b), we test the effects of the number of
274 shared representation layers K. To have comparable MSE's, we keep the sum $K + K_{ta} = 6$ and run
275 $K = 1, \ldots, 5$ reflected in the X axis, while keeping $K_{so} = 1$. In subfigure (c), we test the effects of
276 diversity. The larger p we have, the more diverse the source task is. We keep the actual number of
277 observations $n_{so} \cdot p = 4000$ for a fair comparison. Lastly, in subfigure (d), we test whether diversity
278 is hard to achieve when the source prediction function is nonlinear. The X axis is the number of layers
279 in source prediction function K_{so}. The nonlinearity increases with K_{so}. We run $K_{so} = 1, 2, 3$ and
280 add an activation function right before the output such that the function is nonlinear even if $K_{so} = 1$.

(a) Effects of sample sizes

(b) Effects of K

(c) Effects of diversity

(d) Effects of K_{so}

Figure 1: **(a)** Effects of the numbers of observations for both source (n_{so}) and target tasks (n_{ta}). **(b)** Effects of the number of shared representation layers K. **(c)** Effects of diversity determined by the output dimensions p. We keep the actual number of observations $n_{so} \cdot p = 4000$. **(d)** Effects of nonlinearity of the source prediction function. Higher K_{so} indicates higher nonlinearity.

281 In Figure 1 (a), MSE's decrease with larger numbers of observations in both source and target tasks,
282 while there is no significant difference between $n_{so} = 1000$ and 10000. The baseline method without
283 representation learning performs worst and it performs almost the same when n_{ta} reaches 1000. In
284 (b), there are positive benefits for all different numbers of the shared layers and the MSE is the lowest
285 at 5 shared layers. As shown in Figure 1 (c), the MSE's and their variances are decreasing when
286 the numbers of outputs increase, i.e., higher diversity. Figure 1 (d) shows that there is no significant
287 difference between baseline and $K_{so} = 1, 2, 3$. When $K_{so} = 2, 3$ there is a negative effects.

7 Discussions

289 In this paper, we studied representation learning beyond linear prediction functions. We showed
290 that the learned representation can generalize to tasks with multi-layer neural networks as prediction
291 functions as long as the source tasks use linear prediction functions. We show the hardness of being
292 diverse when the source tasks are using nonlinear prediction functions by giving a lower bound on
293 the number of source tasks in terms of eluder dimension. We further give an upper bound depending
294 on the generalized rank.

295 There are still open problems in this direction. Despite the upper bound depending on the generalized
296 rank, it lacks understanding of this recently proposed complexity measure. Our analyses rely on the
297 ERM, while in practice as well as in our simulations, gradient-based optimization algorithms are
298 used. Further analyses on the benefits of representation learning that align with practice on the choice
299 of optimization method should be studied.

References

Bartlett, P. L. and Mendelson, S. (2002). Rademacher and gaussian complexities: Risk bounds and structural results. *Journal of Machine Learning Research*, 3(Nov):463–482.

Dahl, G. E., Yu, D., Deng, L., and Acero, A. (2011). Context-dependent pre-trained deep neural networks for large-vocabulary speech recognition. *IEEE Transactions on audio, speech, and language processing*, 20(1):30–42.

Dong, K., Yang, J., and Ma, T. (2021). Provable model-based nonlinear bandit and reinforcement learning: Shelve optimism, embrace virtual curvature. *arXiv preprint arXiv:2102.04168*.

Dragomir, S. S. and Gluscevic, V. (2000). Some inequalities for the kullback-leibler and x^2- distances in information theory and applications. *RGMIA research report collection*, 3(2):199–210.

Du, S. S., Hu, W., Kakade, S. M., Lee, J. D., and Lei, Q. (2020). Few-shot learning via learning the representation, provably. *arXiv preprint arXiv:2002.09434*.

Du, S. S., Koushik, J., Singh, A., and Póczos, B. (2017). Hypothesis transfer learning via transformation functions. In *Advances in neural information processing systems*, pages 574–584.

Fazlyab, M., Robey, A., Hassani, H., Morari, M., and Pappas, G. J. (2019). Efficient and accurate estimation of lipschitz constants for deep neural networks. *arXiv preprint arXiv:1906.04893*.

Golowich, N., Rakhlin, A., and Shamir, O. (2018). Size-independent sample complexity of neural networks. In *Conference On Learning Theory*, pages 297–299. PMLR.

Howard, J. and Ruder, S. (2018). Universal language model fine-tuning for text classification. *arXiv preprint arXiv:1801.06146*.

Jaitly, N., Nguyen, P., Senior, A., and Vanhoucke, V. (2012). Application of pretrained deep neural networks to large vocabulary speech recognition.

Jin, C., Netrapalli, P., Ge, R., Kakade, S. M., and Jordan, M. I. (2019). On nonconvex optimization for machine learning: Gradients, stochasticity, and saddle points. *arXiv preprint arXiv:1902.04811*.

Li, G., Kamath, P., Foster, D. J., and Srebro, N. (2021). Eluder dimension and generalized rank. *arXiv preprint arXiv:2104.06970*.

Marmanis, D., Datcu, M., Esch, T., and Stilla, U. (2015). Deep learning earth observation classification using imagenet pretrained networks. *IEEE Geoscience and Remote Sensing Letters*, 13(1):105–109.

Maurer, A., Pontil, M., and Romera-Paredes, B. (2016). The benefit of multitask representation learning. *The Journal of Machine Learning Research*, 17(1):2853–2884.

Oquab, M., Bottou, L., Laptev, I., and Sivic, J. (2014). Learning and transferring mid-level image representations using convolutional neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1717–1724.

Osband, I. and Van Roy, B. (2014). Model-based reinforcement learning and the eluder dimension. *arXiv preprint arXiv:1406.1853*.

Russo, D. and Van Roy, B. (2013). Eluder dimension and the sample complexity of optimistic exploration. In *NIPS*, pages 2256–2264. Citeseer.

Scaman, K. and Virmaux, A. (2018). Lipschitz regularity of deep neural networks: analysis and efficient estimation. *arXiv preprint arXiv:1805.10965*.

Tai, Y., Yang, J., and Liu, X. (2017). Image super-resolution via deep recursive residual network. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3147–3155.

Tan, C., Sun, F., Kong, T., Zhang, W., Yang, C., and Liu, C. (2018). A survey on deep transfer learning. In *International conference on artificial neural networks*, pages 270–279. Springer.

Tripuraneni, N., Jordan, M., and Jin, C. (2020). On the theory of transfer learning: The importance of task diversity. *Advances in Neural Information Processing Systems*, 33.

Weng, R., Yu, H., Huang, S., Cheng, S., and Luo, W. (2020). Acquiring knowledge from pre-trained model to neural machine translation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 9266–9273.