Toward Unified Source-Free Domain Adaptation via Latent Causal Factors Discovery

Abstract

In the pursuit of transferring a source model to a target domain without access to the source training data, Source-Free Domain Adaptation (SFDA) has been extensively explored across various scenarios, including Closed-set, Open-set, Partial-set, Open-partial-set, and Generalized settings. Existing methods, focusing on specific scenarios, not only address a limited subset of challenges but also necessitate prior knowledge of the target domain, significantly limiting their practical utility and deployability. In light of these considerations, we introduce a more practical yet challenging problem, termed *unified SFDA*, which comprehensively incorporates all specific scenarios in a unified manner. In this paper, we propose a novel approach *latent Causal factors discovery for unified SFDA* (CausalDA). In contrast to previous alternatives that emphasize learning the statistical description of reality, we formulate CausalDA from a causality perspective. The objective is to uncover potential causality between latent variables and model decisions, enhancing the reliability and robustness of the learned model against domain shifts. To integrate extensive world knowledge, we leverage a pre-trained vision-language model such as CLIP. This aids in the formation and discovery of latent causal factors in the absence of supervision in the variation of distribution and semantics, coupled with a newly designed information bottleneck with theoretical guarantees. Extensive experiments demonstrate that CausalDA can achieve new state-of-the-art results in distinct SFDA settings, as well as source-free out-of-distribution generalization.

1 Introduction

Due to demands for privacy and information protection in public security and commercial competition, well-annotated training data are recognized as crucial for varying purposes, requiring stringent access control. In practical scenarios, the use of a source model (pre-trained on the source domain) without access to the actual source data, referred to as Source-Free Domain Adaptation (SFDA) (Kim et al., 2021), has become more feasible. This approach involves the challenges posed by strict data access controls and emphasizes adapting a pre-trained model to new domains without relying on the availability of the original source data.

SFDA has been explored across various scenarios, as summarized in Tab. 1. The most constrained scenario, termed *Closed-set*, assumes identical categories of interest in both the source and target domains, aiming to address covariate shift, such as domain-specific appearance distributions (Li et al., 2020b). *Generalized SFDA* extends this by requiring the adapted model to perform well in both the source and target domains without forgetting the source

Table 1: Summary of different SFDA settings. C_s/C_t: The category set of the source/target domain, $C = C_s \cap C_t$; AF is short for Anti-Forgetting.

Setting	Covariate-shift	Semantic-shift	AF	Category
Closed-set	✓	✗	✗	$C_s = C_t$
Generalized	✓	✗	✓	$C_s = C_t$
Open-set	✓	✓	✗	$C_s \subset C_t$
Partial-set	✓	✓	✗	$C_s \supset C_t$
Open-partial-set	✓	✓	✗	$|C|/|C_s \cup C_t| \in (0,1)$
Unified (Ours)	✓	✓	✓	Any

domain (Yang et al., 2021b). Moving beyond the vanilla category identity constraint, *Open-set* SFDA (Panareda Busto & Gall, 2017) considers the target domain with additional categories, while *Partial-set* SFDA

(Cao et al., 2019) takes the opposite direction. Both scenarios require handling the additional challenge of semantic shift. Synthesizing the two orthogonal dimensions leads to *Open-Partial-Set* (Universal) SFDA (Kundu et al., 2020), a generalized setting that explicitly accounts for unknown category relationships.

Typically, prevalent SFDA methods tend to concentrate on particular scenarios, tackling only a subset of challenges. For instance, SFDA-DE(Ding et al., 2022) focuses on Closed-set scenarios, SF-PGL(Luo et al., 2023) on Open-set scenarios, PSAT(Tang et al., 2024b) on Generalized settings, CRS (Zhang et al., 2023) on Partial-set scenarios, and LEAD (Qu et al., 2024) on Open-partial-set scenarios. Nevertheless, this approach significantly restricts their practical utility and deployability, given that we often possess limited prior knowledge about the target domain and minimal control or selection over its conditions.

To address the aforementioned limitation, this study introduces a more realistic yet challenging problem, referred to as *Unified Source-Free Domain Adaptation (Unified SFDA)*, with the goal of comprehensively addressing all the specific scenarios mentioned in a unified manner. To achieve this, we propose a novel approach *latent Causal discovery of salient factors for unified SFDA (CausalDA)*, going beyond conventional statistical association learning of related variables by exploring the underlying causal relationships (Pearl, 2009). The causal mechanism discovered is expected to be more reliable in varying distributions and semantic contexts, providing a unified solution for different scenarios of SFDA.

In the absence of label supervision for both distributional and semantic variations, our CausalDA is specifically formulated using a structural causal model in the logits space. The latent causal factors are disentangled into two complementary parts: (i) *external causal factors* and (ii) *internal causal factors, consider that the information of both domains is not necessarily complete.* For the former, we leverage a pre-trained large Vision-Language (ViL) model with rich knowledge such as CLIP (Radford et al., 2021), which has been exposed to a vast amount of multimodality information sources. The latter is identified under the guidance of discovered external causal factors. The discovery of external and internal causal factors is alternated by designing a self-supervised information bottleneck with theoretical guarantees.

Our **contributions** are summarized as follows:

(i) We introduce a unified SFDA problem that aligns with practical demands of real-world deployment, ranging from focus on unknown category relationships to source-knowledge preservation and out-of-distribution robustness. By eliminating the need for target-domain priors, our design significantly enhances deployability and versatility in unpredictable real-world environments.

(ii) We propose a novel CausalDA approach for unified SFDA. Instead of learning the statistical description of problem reality as conventional methods do, CausalDA is formulated under a causality perspective. It attempts to reveal the potential causality between latent variables and model decisions, providing favorable robustness against both distributional and semantic shifts.

(iii) Extensive experiments demonstrate that CausalDA consistently achieves new state-of-the-art results on varying SFDA scenarios as well as source-free out-of-distribution generalization.

2 Related Work

2.1 Source-free domain adaptation

Most of the prior SFDA methods consider the Closed-set setting where the source and target domains share the same classes, and the focus is on cross-domain distribution alignment. Existing methods exist in two categories. The first converts SFDA to Unsupervised Domain Adaptation (UDA) by constructing a pseudo-source domain (Li et al., 2020a), exploiting source prototype-guided data generation (Tian et al., 2021) or splitting source-like subset from target data (Du et al., 2024). The second follows self-supervised learning (Liang et al., 2020; Chen et al., 2022b), introducing self-guidance. Besides widely used pseudo-labels (Liang et al., 2020; Litrico et al., 2023), geometry information (Yang et al., 2021a; 2023; Tang et al., 2022), contrastive data (Zhang et al., 2023) and historical data (Tang et al., 2024b) have also been exploited.

Recently, more practical settings have been studied. For example, the Generalized setting shifts aim to mitigate forgetting the source domain (Yang et al., 2021b). A representative approach is combining continual

learning techniques with cross-domain adaptation, e.g., the domain attention-based gradient regulation (Yang et al., 2021b) and source guidance constructed by historical information refining (Tang et al., 2024b). There exist works considering Open-set (Luo et al., 2023), Partial-set (Li & Chen, 2023) and Open-partial-set (Kundu et al., 2020) settings. For instance, to control the Open-set risk, a progressive balanced pseudo-labeling strategy (Luo et al., 2023), and Closed-set class prototypes are proposed (Vray et al., 2024). Estimating the target data distribution helps with negative transfer reduction from the partial classes shift (Lee et al., 2022). Feature decomposition adaptively identifies the target-private data (Qu et al., 2024).

Alternatively, some works were proposed to enhance the discriminating ability for out-of-distribution classes (Samadh et al., 2023). There are two main strategies: Expanding inter-class distance to prevent semantic confusion (Tang et al., 2021; Liang et al., 2020), and introducing external semantics, e.g., CLIP, to match out-of-distribution (Shu et al., 2022).

Most recently, multimodal large models such as CLIP and ShareGPT (Chen et al., 2024b) have been introduced to advance SFDA, substantially enhancing adaptation performance by leveraging generic knowledge in these models. Two strategies are adopted: (1) customizing and adapting this knowledge via mutual knowledge distillation (Tang et al., 2024c; Zhang et al., 2025) or multi-teacher guidance (Chen et al., 2024a) or multimodal space alignment (Chen et al., 2025); and (2) further denoising ViL predictions (Tang et al., 2025). Critically, we highlight a couple of key aspects that make CausalDA conceptually distinct from these SFDA methods. First, CausalDA is unique in design philosophy by learning a causal representation, in contrast to the statistical knowledge DIFO (Tang et al., 2024c) and ProDe (Tang et al., 2025) both are designed to learn. As a consequence, the outreach and generalization can be further extended, leading to the first dedicated unified SFDA approach. Instead, DIFO and ProDe predominantly focus on the conventional closed-set setting. Further, this conceptual discrepancy leads to distinct leveraging of ViL knowledge. DIFO and ProDe both employ the generic ViL knowledge directly as supervision, fostering the establishment of statistical relationships, whilst CausalDA utilizes ViL knowledge to uncover the underlying causal factors for capturing the essence of visual recognition.

Existing work targets only specific SFDA settings, limiting its practical applicability and generality. This paper introduce a unified SFDA setting that incorporates all the pre-existing scenarios. With this new setup, we aim to foster more advanced SFDA methods that could generalize to a variety of problem settings without the need for designing and maintaining an array of distinct algorithms.

2.2 Causality methods in transfer learning

Causality methods aim for a robust function relation between random variables, which is insensitive to the extra variation/disturbing (Schölkopf et al., 2021). This property leads to recent popularity of this new paradigm in transfer learning, e.g., UDA (Wu et al., 2024), domain generalization (DG) (Christiansen et al., 2021), and out-of-distribution (OOD) (Byun et al., 2025). These attempts aim to reduce non-causal factors by introducing artificial intervention. For example, the probability distribution change (used to represent the domain shift) and the semantic consistency constraint are jointly employed to implement this intervention. As source labels are available to ensure consistency, these methods emphasize constructing the distribution change in two lines. One explicitly generates augmented data to disturb the distribution, e.g., the non-linear augmentation and spatially-variable blending augmentation (Ouyang et al., 2022), inverse Fourier transformation augmentation (Lv et al., 2022), generative models-based cross-domain image style transformation (Wang et al., 2022a), and causality-adjusted augmentation (Zhu et al., 2025). The other implicitly modifies the distribution by exploiting cross-domain data. For example, MatchDG (Mahajan et al., 2021) developed cross-domain contrastive learning where the input's positive sample was randomly selected from samples with the same class. COR (Wang et al., 2022b) adopted the variational inference encoder to infer unobserved causal factors from historical data, taking the time domain as a natural distribution change.

Compared with the existing works, the following three features distinguish CausalDA from them. (i) CausalDA does not rely on real labels that are indispensable for previous works. (ii) CausalDA discovers the causal factors instead of indirectly removing the non-causal ones. (iii) CausalDA builds the structural causal model at the logits level, whilst previous methods construct on raw data.

3 Methodology

3.1 Unified SFDA problem

SFDA aims to transfer a model pre-trained on the source domain to a different but related target domain without labeling. Formally, let $\mathcal{X}_s = \{\boldsymbol{x}_i^s\}_{i=1}^{n_s}$ and $\mathcal{Y}_s = \{y_i^s\}_{i=1}^{n_s}$ be the source samples and their truth labels. Similarly, the unlabeled samples and the truth target labels are $\mathcal{X} = \{\boldsymbol{x}_i\}_{i=1}^{n}$ and $\mathcal{Y} = \{y_i\}_{i=1}^{n}$, respectively. The unified SFDA task is to learn a target model $f_{\theta_t} : \mathcal{X} \to \mathcal{Y}$ *without any prior knowledge of the target domain not the relationships between the source and target domains (see Tab. 1)*, given (i) the source model f_{θ_s} pre-trained over $\mathcal{X}_s, \mathcal{Y}_s$, and (ii) the unlabeled target data $\mathcal{X}$.

3.2 Causality in transfer learning with source domain

In transfer learning with available source domain, such as DG and UDA, the causality relation hidden in the statistical dependence (between raw image $\boldsymbol{x}$ and available label $\boldsymbol{y}$) can be summarized to a Structural Causal Model (SCM). As depicted in Fig. 1(a), $\boldsymbol{x}$ is generated jointly by non-causal factors U and causal factors S, while label $\boldsymbol{y}$ is determined by S alone. Here, non-causal factors collectively represent the latent variables that generate the category-independent appearance of images, e.g., different domain styles and spurious dependence (Fig. 2); The causal factors present the ones determining the classification, e.g., the object shape.

Figure 1: Differences of Structural Causal Models (SCM). **(a)** SCM for transfer learning with source domain, where S and U represent causal and non-causal factors. Domain shift is generally caused by U, which, together with the generalizable information S, e.g., the shape/structure of a dog (see Fig. 2), form the observation x. **(b)** Our proposed SCM for SFDA in a latent space (e.g., the logit $\boldsymbol{a}$) where the causal factors S are decomposed into the external S_e and internal S_i components.

In a causal view, solving the transfer learning involves eliminating the domain shift by building a robust classification function, i.e., $P(\boldsymbol{y}|S)$. In the view of SCM, we need to disconnect U to $\boldsymbol{x}$. So existing works impose intervention upon $\boldsymbol{x}$, according to the intervention theory (Pearl, 2009). Formally, this scheme can be formulated as the following form.

$$P(\boldsymbol{y}|S) = P(\boldsymbol{y}|do(x), S), \tag{1}$$

where $do(\cdot)$ means the do-operation of imposing intervention upon the input variables.

In practice, the key idea of tackling Eq. (2) is that when we change the probability distribution of non-causal factors (intervention) whilst keeping the category (prediction consistency), the causality can be extracted. Often, domain-related data augmentation is adopted as an intervention, whilst the source labels ensure prediction consistency. However, both conditions are unavailable in SFDA, making it inapplicable.

Figure 2: Illustration of domain shift. Left: **Different appearance styles** of dog; Right: **Spurious dependence of background:** Cow in grass ground vs. on a car.

3.3 Latent causality in unified SFDA

To address the challenges outlined earlier, we propose an approach named *latent Causal factors discovery* (CausalDA), taking into account the following considerations. Instead of extracting causality in the raw input space $\boldsymbol{x}$, we shift our focus to the logit space $\boldsymbol{A}$: $\boldsymbol{a} = f_{\theta_t}(\boldsymbol{x}) \in \boldsymbol{A}$. The choice of this space for causality analysis is crucial for two main reasons: First and foremost, from a causal perspective, using a post-intervened space enhances causality capture by incorporating a probability distribution shift into the data (Mahajan et al., 2021; Wang et al., 2022b; Pearl, 2009). In our case, the logit space is post-intervened due to the inherent distribution shift between the in-training target model (initialized with the pre-trained source domain model)

Approach	Intervention	Consistency
Existing (Chen & Bühlmann, 2021; Christiansen et al., 2021; Wang et al., 2022b)	Data augmentation	Supervised
CausalDA	Using logit	Unsupervised

Table 2: Analogy of causality learning.

and the target domain. Specifically, the target model's logits for the target domain data reflect this domain shift, making them a particular form of post-intervention in this context.

Furthermore, the logit space is both highly semantic and compact, making it more efficient to manipulate. Since logits encode rich semantic information about class relationships, operating in this space allows for better generalization and transferability across domains. Additionally, its compact representation reduces computational complexity, facilitating more efficient learning and adaptation. These properties collectively make the logit space a more effective choice for our approach. Tab. 2 presents an analogy of CausalDA and the existing causal learning approach.

An overview of CausalDA framework is illustrated in Fig. 1(b). It models both non-causal factors U and causal factors S within a latent space A. Notably, the causal component S is further decomposed into internal (S_i) and external (S_e) sub-components to facilitate a more complete and interpretable modeling of causality.

This internal-external causality decomposition is motivated by the recognition that identifying all relevant causal relationships solely from the source and target domains is often infeasible due to limited training data and domain-specific knowledge. To address this, we introduce a pretrained ViL model, such as CLIP, as an external knowledge source to aid in the discovery of causal relationships. This design leads to two types of causality: (i) **Internal causality** referring to causal factors that can be inferred from the source domain model and the target domain data; (ii) **External causality**, additional complements captured from the ViL model with broad, many-domain information. Such a collaborative design enables a more holistic understanding of causal structures, as empirically validated in `Sec.4.2` and `Sec.4.7.2`.

In contrast to conventional intervention-driven learning, we focus on discovering S from the intertwined S and U as

$$P(\boldsymbol{y}|S) = P(\boldsymbol{y}|dis(S|\{U,S\})), \ S = \{S_i, S_e\}, \tag{2}$$

where $dis(S|\{U,S\}))$ means conducting discover operation on $\{U,S\}$ to decompose S. To make this process computationally tractable, we consider

Principle 1 *Independent Causal Mechanisms (ICM) Principle (Peters et al., 2017): The conditional distribution of each variable given its causes (i.e., its mechanism) does not inform or influence the other mechanisms.*

As in `Sec.3.2`, the lack of access to the source domain prevents the use of conventional causal learning methods. Inspired by Principle 1, we assume conditional independence between external and internal causal factors to enable a divide-and-conquer learning approach. Under this perspective, we propose the following factorized approximation as:

$$P(\boldsymbol{y}|S) \approx P(\boldsymbol{y}|dis(S_e|\{U,S_e\})) \cdot P(\boldsymbol{y}|dis(S_i|\{U,S_i\})). \tag{3}$$

3.4 CausalDA design

We present a concrete design to carry out CausalDA, as depicted in Fig. 3. By Eq. (3), we implement the causality discovery in two successive phases: `phase-1` for S_e and `phase-2` for S_i, as detailed below.

3.4.1 External causality discovery

To obtain external causality for a target task, we explore the potential of recent large multimodal ViL models such as CLIP (Radford et al., 2021). This is because they have accumulated a vast amount of knowledge and exhibited strong generalization abilities across a wide range of perception tasks.

Figure 3: Overview of our CausalDA framework: (a) `Phase-1`: Discovering the external causal factors S_e in form of prompt context $\boldsymbol{v}_e$ from a frozen ViL model using our self-supervised information bottleneck algorithm; (b) `Phase-2`: Discovering the internal causal factors S_i where the updated prompt context $\boldsymbol{v}_e$ is used to predict pseudo-labels as the prior information.

Specifically, we accomplish this idea by encoding S_e into the prompt context $\boldsymbol{v}_e$ of a ViL model g_θ efficiently. That is, our learning target is $\boldsymbol{v}_e$, which is the explicit expression of S_e. We start by formulating the S_e discovery as maximizing the correlation between a random variable representing S_e and the prediction of the target model. Then, the original formulation is converted to a self-supervised information bottleneck problem with a theoretical guarantee, followed by the deep learning instantiation.

With the target samples $\mathcal{X}$ and learnable $\boldsymbol{v}_e$, we obtain the prediction of g_θ as $\hat{\mathcal{P}} = \{\hat{\boldsymbol{p}}_i\}_{i=1}^n$. Meanwhile, we obtain the logits of target model f_{θ_t} for the same data as $\mathcal{A} = \{\boldsymbol{a}_i\}_{i=1}^n$. We introduce three *random variables*, V, Y, and Z, following the probability distributions of $\boldsymbol{v}_e$, $\hat{\mathcal{P}}$ and $\mathcal{A}$, respectively. In CausalDA, we further write $Z = \{Z_e, Z_i\}$ where the latent random variables Z_e and Z_i represent the external S_e and the internal S_i causal factors, respectively.

In an information-theoretic view, for causality relationships, we have to ensure the correlation between Z_e and V. This could be considered an approximation with computational ease. Formally, discovering S_e needs maximizing the following mutual information:

$$\max_{\boldsymbol{v}_e} I\left(Z_e, V\right), \tag{4}$$

where $I(\cdot, \cdot)$ is mutual information of two random variables. Note, mutual information is not a prerequisite for causality discovery; instead, it is an effective design choice that enhances the discovery of external causality.

To achieve Eq. (4), we employ prompt learning (Zhou et al., 2022b) to accomplish the optimization. This is because it allows us to leverage CLIP without tuning model parameters. This avoids potential issues such as catastrophic forgetting and unintended distortion of the pretrained knowledge within the ViL model. Moreover, by preserving CLIP's pretrained knowledge, prompt learning facilitates the discovery of external causality, enabling more effective integration of external knowledge into the causal learning process.

Consider that prompt V is specific to the ViL model g_θ, we further transform the above formula of Eq. (4) as

$$\max_{\boldsymbol{v}_e} I\left(Z_e, Y\right), Y = \phi\left(g_\theta\left(V\right)\right), \tag{5}$$

where $\phi(\cdot)$ is softmax function; so that the two variables under correlation maximization reside in similar semantic spaces. Theoretically, we prove that this transformation can constitute a lower bound on the original, ensuring its validity in optimization.

First, we have the following **Lemma 1** (see the proof in `Appendix-A`).

Lemma 1 *Given random variables Z_1, X_1 and Y_1 where X_1, Y_1 satisfy a mapping $f_1 : X_1 \mapsto Y_1$. When f_1 is compressed, i.e., the output's dimension is smaller than the input's,*

$$I\left(Z_1, X_1\right) \geq I\left(Z_1, Y_1\right). \tag{6}$$

Figure 4: Realizing our self-supervised information bottleneck w.r.t. **Theorem** 1. T_1 is estimated by Variational Mutual Information (VMI) with Gaussian distribution assumption $\mathcal{N}(Z, \Sigma_Z)$. T_2 is computed by Probabilistic Mutual Information (PMI) where function f_w integrates min-max optimization, using covariance matrix Σ_Z from T_1 as weighting parameters w.

The ViL model g_θ is indeed compressing, as it maps a high-dimensional image to a low-dimensional category vector. Let $Z_1 = Z_e$, $X_1 = X$, $Y_1 = Y$ and $f_1 = \phi(g_\theta(\cdot))$, we have $I(Z_e, V) \geq I(Z_e, Y)$ according to **Lemma** 1.

Self-supervised information bottleneck. In Eq. (5), Z_e is the hidden part of the observable logits along with non-causal and internal causal factors. To facilitate this learning process of Z_e, we derive a self-supervised information bottleneck algorithm without prior assumption on the distribution (Kawaguchi et al., 2023). In general, information bottleneck conducts min-max optimization to squeeze out the essentials w.r.t. a task. We introduce a random variable Z' (i.e., the bottleneck) for the ViL's logits $\widehat{\mathcal{O}} = \{\hat{o}_i\}_{i=1}^n$ between V and Y, thereby forming a bottleneck style expression as:

$$\min_{\boldsymbol{v}_e} I(Z, Z') - I(Z', Y), \tag{7}$$

where Z is the logit variable of target model f_{θ_t} which is observed. Note, we do not include the item $I(Z', Y)$ in minimization due to lacking supervision signal like ground-truth labels as used in conventional information bottleneck (Tishby et al., 2000), i.e., a self-supervised formulation. However, we theoretically prove that Eq. (7) admits an upper bound, thus optimizationally valid.

Theorem 1 *Suppose that there are five random variables Z, V, Z', Y and Y'. Among them, Z represents the target domain knowledge; V, Z' and Y express the input instances, an intermediate features of the ViL model and predictions, respectively; Y' depicts a pseudo-label that has a functional relationship f_w (w is learnable parameters) with Z'. When f_w is reversible and uncompressed, we have this upper bound:*

$$\min_{\boldsymbol{v}_e} I(Z, Z') - I(Z', Y) \leq \min_{\boldsymbol{v}_e, w} \underbrace{I(Z, Z')}_{T_1} - \underbrace{I(Y', Y), Y' = f_w(Z')}_{T_2}. \tag{8}$$

The proof is given in `Appendix-B`. **Theorem** 1 suggests that the desired latent factors refinement is conditionally equivalent to a self-supervised information bottleneck, when pseudo-label Y' is generated from the intermediate ViL feature Z' without information loss.

We realize the proposed information bottleneck building on variational information maximization (Houthooft et al., 2016). Fig. 4 shows our pipeline. The key is to construct the function f_w with three properties: (i) The output is a probability distribution, e.g., including a softmax operation ϕ. (ii) No information loss, e.g., no zero weights in w for weighting-based functions. (iii) The weighting parameters w are constrained to be relevant to $I(Z', Z)$. The instantiations of T_1 and T_2 are elaborated below.

As exactly computing mutual information of two vector variables is intractable, we maximize the variational lower bound for the term T_1 (see the proof in (Barber & Agakov, 2004)):

$$I(Z, Z') = \mathbb{E}_{Z, Z'}\left[\log \frac{q(Z'|Z)}{p(Z')}\right] + \text{KL}\left(q(Z'|Z) \| p(Z'|Z)\right) \geq H(Z') + \mathbb{E}_{Z, Z'}\left(\log q(Z'|Z)\right), \tag{9}$$

where $q(Z'|Z)$ is variational distribution approximating the real distribution $p(Z'|Z)$, $\text{KL}(\cdot, \cdot)$ is KL-divergence function, and $H(Z')$ is a constant. In practice, we model $q(Z'|Z)$ as a Gaussian distribution $\mathcal{N}(Z, \Sigma_Z)$ with

mean Z and diagonal covariance matrix Σ_Z. For minimizing T_1, we adopt the Variational Mutual Information (VMI) loss (see $\mathbf{T}_1$ in Fig. 4):

$$\mathcal{L}_{\text{VMI}}\left(\mathcal{X}; \boldsymbol{v}_e, \Sigma_Z\right) = -\mathbb{E}_{Z,Z'}\left(||Z'-Z||^2_{\Sigma_Z^{-1}} + \log|\Sigma_Z|\right) = -\frac{1}{n}\sum_{i=1}^{n}\left(\hat{\boldsymbol{o}}_i - \boldsymbol{a}_i\right)^T \Sigma_Z^{-1}\left(\hat{\boldsymbol{o}}_i - \boldsymbol{a}_i\right) + \log|\Sigma_Z^i|. \quad (10)$$

Consider that the ViL's prediction Y and the pseudo-label Y' are probability distributions, we compute the T_2 term by vanilla mutual information (Ji et al., 2019): $I(Z, Z') = p(Z, Z')/[p(Z)p(Z')]$. The corresponding Probabilistic Mutual Information (PMI) loss function is formed as:

$$\mathcal{L}_{\text{PMI}}\left(\mathcal{X}; \boldsymbol{v}_e, \Sigma_Z\right) = \frac{1}{n}\sum_{i=1}^{n} I\left(\hat{\boldsymbol{p}}_i, \boldsymbol{p}'_i\right), \text{ with } \hat{\boldsymbol{p}}_i = \phi(\hat{\boldsymbol{o}}_i), \quad \boldsymbol{p}'_i = f_w(\hat{\boldsymbol{o}}_i), \quad (11)$$

where $\sum_{c=1}^{C} \boldsymbol{p}'_{i,c} = 1$; $f_w(\cdot)$ is a weighting-based function constructed as follows.

From Eq. (10), $I(Z', Z)$ is a Mean-Square Error (MSE) weighted by Σ_Z. That means Σ_Z detects dimension importance duration minimization, with high-weight dimensions to be suppressed, thus corresponding to the non-causal factors U in our formulation. Thus, taking $1/\Sigma_Z$ as the weighting parameters of f_w shifts the focus of predicting to the causal component S_e (see $\mathbf{f}$ in Fig. 4), formally,

$$\boldsymbol{p}'_i = f_{\left[w = \Sigma_Z^i\right]}\left(\hat{\boldsymbol{o}}_i\right) = \phi\left(\phi\left(\frac{1}{\Sigma_Z^i}\right) \odot \phi\left(\hat{\boldsymbol{o}}_i\right)\right), \quad (12)$$

where $\phi(\cdot)$ is softmax function. Combining Eq. (10), (11), and (12) together, our self-supervised objective for external causality discovery is formed as

$$\min_{\boldsymbol{v}_e, \Sigma_Z} \mathcal{L}_{\text{EC}}\left(\mathcal{X}; \boldsymbol{v}_e, \Sigma_Z\right) = \mathcal{L}_{\text{PMI}}\left(\mathcal{X}; \boldsymbol{v}_e, \Sigma_Z\right) - \alpha\mathcal{L}_{\text{VMI}}\left(\mathcal{X}; \boldsymbol{v}_e, \Sigma_Z\right). \quad (13)$$

Remark. Our design differs from the existing information bottleneck in two aspects: While previous information extraction (Li et al., 2022) is confined to a single model, ours is a cross-model design. Our formulation is self-supervised, in contrast to previous supervised designs.

3.4.2 Internal causality discovery

In `phase-2`, we subsequently discover the internal causal factors S_i by updating the target model. That is, we encode S_i in the target model, as it is latent in nature. Similar to capturing the external factors S_e (Eq. (5)), this encoding can be formulated by maximizing the following conditional mutual information:

$$\max_{\theta_t} I\left(Z_i, Z_\theta\right), \quad \text{s.t.} \quad \max_{\theta_t} I\left(Z_e^*, Z_\theta\right) \quad (14)$$

where random variable Z_θ represents target model parameters θ_t, whilst Z_i denotes random variable of internal causal factors S_i; Z_e^* represents the currently discovered external causal factor S_e^*. The primary term, $\max_{\theta_t} I\left(Z_i, Z_\theta\right)$, aims to capture the internal causality S_i. The condition, $\max_{\theta_t} I\left(Z_e^*, Z_\theta\right)$, ensures the target model simultaneously accommodates the discovered external causality S_e^*.

Given ultra-high dimension and complexity of θ_t, combined with the hidden nature of Z_i, directly optimizing or computing Eq. (14) is intractable. To address this, we interpret the interaction between Z_θ and Z_i as the inherent modeling process that transforms an input sample from pixel space into a predictive probability space. This perspective allows us to reformulate the problem as maximizing the mutual information between the target model's input and output, both of which are *observed* and *operational*. Crucially, theoretical proofs demonstrate that mutual information between inputs and outputs is maximized when outputs are both highly confident and exhibit balanced class distributions (Krause et al., 2010). Inspired by this theoretical finding, we maximize this originally non-computable mutual information by minimizing the following objective:

$$\mathcal{L}_{\text{UN}}(\mathcal{P}; \theta_t) = -\sum_{i=1}^{n} \boldsymbol{p}_i \log \boldsymbol{p}_i + \tau \sum_{c=1}^{C} \text{KL}\left(\varrho_c \| \frac{1}{C}\right), \text{ with } \boldsymbol{p}_i \in \mathcal{P} = \phi(f_{\theta_t}(\mathcal{X})). \quad (15)$$

Algorithm 1 Training CausalDA

Input: Unlabelled target data $\mathcal{X}$, pre-trained source model f_{θ_s}, a frozen ViL model g_θ, max training iteration number M, prompt context $\boldsymbol{v}_e$.

    Initialize target model f_{θ_t}(by f_{θ_s}), $\boldsymbol{v}_e$(by fixed template)

    for iter $k = 1$ to M **do**

        Sample a mini-batch $\mathcal{X}_b$ from $\mathcal{X}$.

        Discover external causal factors S_e: update $(\boldsymbol{v}_e, \Sigma_Z)$ by optimizing $\mathcal{L}_{\mathrm{EC}}(\mathcal{X}_b; \boldsymbol{v}_e, \Sigma_Z)$, fixing $\mathcal{L}_{\mathrm{IC}}$.

        Convert updated $\boldsymbol{v}_e$ to target pseudo-labels for this batch $\mathcal{X}_b$, i.e., obtain $\mathcal{Q}_b = \phi(g_\theta(\mathcal{X}_b, \boldsymbol{v}_e))$.

        Discover internal causal factors S_i: update f_{θ_t} by optimizing $\mathcal{L}_{\mathrm{IC}}$, fixing $\mathcal{L}_{\mathrm{EC}}$.

    end for

    return: The adapted model f_{θ_t}.

In this equation, $\mathcal{P}$ represents the predictions of n training samples $\mathcal{X}$ generated by the target model f_{θ_t}. The first term minimizes the information entropy of each prediction $\boldsymbol{p}_i = [p_{i,c}]_{c=1}^C$. The KL divergence term, on the other hand, regulates the predictive balance across all C categories via pulling the empirical distribution $\varrho_c = \frac{1}{n}\sum_{i=1}^n p_{i,c}$ towards a uniform distribution. The trade-off parameter τ balances these two terms.

Similarly, we convert the external causality S_e^* from its prompt format $\boldsymbol{v}_e$ to pseudo-labels by evaluating the ViL model g_θ: $\mathcal{Q} = \phi(g_\theta(\mathcal{X}, \boldsymbol{v}_e))$. This conversion simplifies model optimization, as it enables the use of the conventional softmax cross-entropy loss, $\mathcal{L}_{\mathrm{SCE}}(\mathcal{P}, \mathcal{Q}; \theta_t)$.

Combining these elements, we optimize Eq. (14) using the following objective function:

$$\mathcal{L}_{\mathrm{IC}} = \min_{\theta_t} \mathcal{L}_{\mathrm{UN}}(\mathcal{P}; \theta_t) + \sigma \mathcal{L}_{\mathrm{SCE}}(\mathcal{P}, \mathcal{Q}; \theta_t) \tag{16}$$

where σ serves as another trade-off parameter.

3.5 Model training

We train CausalDA in an alternating manner. In each iteration, we first optimize prompt context $\boldsymbol{v}_e$ with $\mathcal{L}_{\mathrm{EC}}$ whilst the target model is frozen (i.e., `phase-1`), followed by training the target model by $\mathcal{L}_{\mathrm{IC}}$ (i.e., `phase-2`) while the prompt context is frozen. The ViL model is always frozen throughout. More details for training are presented in Alg. 1.

4 Experiments

4.1 Implementation details

Source models. Following (Zhou et al., 2022b), for source-free out-of-distribution generalization (SF-OODG) we adopt the Pytorch built-in ResNet50 model (pre-trained on ImageNet) as the source model, taking ImageNet variations as evaluation datasets. For other settings, the source model is trained on the source domain in a supervised manner, same as (Liang et al., 2020; Tang et al., 2022).

Networks. Our CausalDA involves two parts: the ViL model and the target model. We choose CLIP (Radford et al., 2021) as the ViL model. The target model's structure is the same as the source model. Following (Liang et al., 2020; Yang et al., 2023), a target model consists of a feature extractor and a classifier (an FC layer). We adapt the feature extractor, which is pre-trained on ImageNet. For fair comparison, we use ResNet101 as the backbone for VisDA and ResNet50 for the others.

Training. There are three parameters with CausalDA: α in L_{EC} (Eq. (13)), τ in L_{UN} (Eq. (15)), and σ in L_{IC} (Eq. (16)). For all settings, we adopt the same configuration $(\alpha, \sigma, \tau) = (0.003, 0.4, 1.0)$. Here, since the value of $\mathcal{L}_{\mathrm{VMI}}$ is large, α is set as small as 0.003. For model training, we use a batch size of 64, an SGD optimizer with momentum 0.9, and 15 epochs on all datasets. The learnable prompt template is initialized with 'a photo of a [CLS].' (Radford et al., 2021), where the [CLS] is a specific target class name.

Unification evaluation protocol. In the SFDA context, unification does not necessarily imply that the proposed method must achieve the absolute best performance in every individual adaptation scenario. Instead, the essence of contributing a unified solution lies in its ability to provide stable and competitive performance across a wide range of settings in a unified manner, without the need of resorting to a diversity of scenario specific designs.

To evaluate the unification of methods, we adopt three harmonic metrics: (1) Overall mean H_{all} that averages over all settings, (2) worst-case relative gap H_{wrg} that is largest percentage shortfall of a method from the per-setting best across all settings, and (3) leave-one-setting-out averages H_{loso} omits one setting at a time and averages the scores over the rest. For a specific method m evaluated over a number of settings $\mathcal{S}$, the metrics can be computed by:

$$\mathrm{H}_{all}(m) = \frac{1}{|\mathcal{S}|} \sum_{s \in \mathcal{S}} x_{m,s}; \ \mathrm{H}_{wrg}(m) = \max_{s \in \mathcal{S}} \frac{b_s - x_{m,s}}{b_s}; \ \mathrm{H}_{loso}(m, s') = \frac{1}{|\mathcal{S} - 1|} \sum_{s \in \mathcal{S} \setminus s'} x_{m,s}, \tag{17}$$

where $x_{m,s}$ specifies the score of method m under a setting s; $b_s = \max_{m'} x_{m',s}$ is the per-setting best; s' is a omitted setting.

4.2 Indirect validation of causal factors

Validating the discovery of causal factors is significant yet non-trivial in causality learning, especially with latent causal factors as in this study. To that end, we adopt a general principle that there exists an intimate connection between invariance and causality useful for generalization (Schölkopf et al., 2021; Arjovsky et al., 2019). That being said, if a learned model enables varying environments generalization, it constitutes *indirect evidence* that the model has captured causal predictors (e.g., a causal explanation of an object, such as why it is a computer).

Concretely, we simulate a spectrum of viewing environments by imposing varying levels of Gaussian noise with gradually increased kernel sizes from 8 to 20. We compare the competitors without (SHOT (Liang et al., 2020)) and with (DIFO (Tang et al., 2024c) and ProDe (Tang et al., 2025)) ViL knowledge (the image-encoder in CLIP adopts backbone ViT-B/32 (Han et al., 2022)). As shown in Fig. 5, all competitors degrade clearly as the noise increases, whilst CausalDA levels off. These findings suggest the method captures invariant pre-

Figure 5: Causality validation: Invariance analysis across varying noise settings on the Ar→Cl task of **Office-home**.

dictors that are compatible with causal explanations, though they do not prove causal recovery rigorously. To further examine if external and internal factors both are effective, we further derive a variant of CausalDA, named as CausalDA^{in}, without the external causality discovery. Specifically, in CausalDA^{in}, the pseudo-labels are directly derived from CLIP's zero-shot predictions. This is consistent with external factors contributing to improved invariance, suggesting a possible complementarity with internal counterparts.

The validation above provides indirect yet preliminary evidence for causality capture. In the following, we present further supporting evidence through adaptation results across diverse SFDA settings.

4.3 Closed-set SFDA

Datasets. The evaluation is based on three challenging benchmarks. **Office-Home** (Venkateswara et al., 2017) is a middle-scale dataset. It contains 15k images belonging to 65 categories from working or family environments, being divided into four domains, i.e., **Ar**tistic, **Cl**ip Art, **Pr**oduct, and **R**eal-**w**ord. **VisDA** (Peng et al., 2017) is a large-scale dataset. It includes 12 types of **S**ynthetic to **R**eal transfer recognition tasks. The source domain contains 152k synthetic images, whilst the target domain has 55k real object images

Table 3: Closed-set results (%) on **Office-Home**, **VisDA**. SF and ViL means source-free and ViL model-required, respectively.

Method	Venue	SF	ViL	Office-Home Ar→Cl	Ar→Pr	Ar→Rw	Cl→Ar	Cl→Pr	Cl→Rw	Pr→Ar	Pr→Cl	Pr→Rw	Rw→Ar	Rw→Cl	Rw→Pr	Avg.	VisDA S→R
Source	–	–	–	43.7	67.0	73.9	49.9	60.1	62.5	51.7	40.9	72.6	64.2	46.3	78.1	59.2	49.2
CLIP-RN	ICML21	–	✓	51.9	81.5	82.5	72.5	81.5	82.5	72.5	51.9	82.5	72.5	51.9	81.5	72.1	83.7
CLIP-B32	ICML21	–	✓	64.9	86.6	87.2	78.0	86.6	87.2	78.0	64.9	87.2	78.0	64.9	86.6	79.2	85.2
DAPL-RN	TNNLS23	✗	✓	54.1	84.3	84.8	74.4	83.7	85.0	74.5	54.6	84.8	75.2	54.7	83.8	74.5	86.9
PADCLIP-RN	ICCV23	✗	✓	57.5	84.0	83.8	77.8	85.5	84.7	76.3	59.2	85.4	78.1	60.2	86.7	76.6	88.5
ADCLIP-RN	ICCV23W	✗	✓	55.4	85.2	85.6	76.1	85.8	86.2	76.7	56.1	85.4	76.8	56.1	85.5	75.9	87.7
SHOT	ICML20	✓	✗	55.0	78.7	81.3	69.1	78.9	79.1	68.2	53.6	81.6	73.5	59.4	83.5	71.8	82.9
GKD	IROS21	✓	✗	56.5	78.3	82.2	69.2	80.4	78.7	67.4	55.4	82.6	74.3	60.3	84.2	72.5	83.0
NRC	NeurIPS21	✓	✗	57.2	79.3	81.3	68.9	80.6	80.2	66.6	57.3	82.0	71.0	57.9	84.9	72.3	85.9
AaD	NeurIPS22	✓	✗	59.3	79.3	82.1	68.9	79.8	79.5	67.2	57.4	83.1	72.1	58.5	85.4	72.7	88.0
AdaCon	CVPR22	✓	✗	47.2	75.1	75.5	60.7	73.3	73.2	60.2	45.2	76.6	65.6	43.3	79.1	65.0	86.8
CoWA	ICML22	✓	✗	57.3	79.3	81.0	69.3	77.9	79.6	68.1	56.4	82.6	72.9	61.3	83.7	72.4	86.9
PLUE	CVPR23	✓	✗	49.1	73.5	78.2	62.9	73.5	74.5	62.2	48.3	78.6	68.6	51.8	81.5	66.9	88.3
TPDS	IJCV24	✓	✗	59.3	80.3	82.1	70.6	79.4	80.9	69.8	56.8	82.1	74.5	61.2	85.3	73.5	87.6
SHOT-B32	ICML20	✓	✓	64.7	84.0	86.4	79.4	87.3	85.4	78.1	65.8	87.6	81.6	65.0	88.5	79.5	85.2
GKD-B32	IROS21	✓	✓	67.2	83.2	84.3	77.0	84.8	83.6	75.5	71.1	86.0	81.1	72.4	88.5	79.6	85.3
NRC-B32	NeurIPS21	✓	✓	55.0	83.4	86.7	78.3	86.5	85.1	77.1	69.9	87.2	90.9	65.5	88.4	79.5	88.2
AaD-B32	NeurIPS22	✓	✓	69.4	83.0	84.9	76.4	85.2	84.6	73.3	71.1	86.3	79.0	72.1	88.7	79.5	82.6
TPDS-B32	IJCV24	✓	✓	67.7	82.7	86.1	76.5	85.0	86.3	73.6	69.4	87.1	79.3	70.5	89.7	79.7	78.0
MMGA-B32	PR25	✓	✓	68.5	84.6	86.8	78.8	87.5	86.5	75.9	68.3	86.3	80.4	69.9	88.6	80.2	89.2
CausalDA-C-RN	–	✓	✓	60.1	85.6	86.2	77.2	86.0	86.3	76.6	61.0	86.5	77.5	61.4	86.2	77.6	89.3
CausalDA-C-B32	–	✓	✓	74.2	90.8	90.3	82.3	91.0	89.9	81.0	74.8	90.0	82.5	74.1	90.9	84.3	90.3

from COCO. **DomainNet-126** (Peng et al., 2019) is another large-scale dataset. As a subset of DomainNet containing 600k images of 345 classes from 6 domains of different image styles, this dataset has 145k images from 126 classes, sampled from 4 domains, **C**lipart, **P**ainting, **R**eal, **S**ketch, as (Peng et al., 2019) identifies severe noisy labels in the dataset.

Competitors. To evaluate CausalDA, we select 14 state-of-the-art methods in three groups. *(i) The first* is the source model and CLIP that lay the basis for CausalDA. *(ii) The second* is the UDA method DAPL (Ge et al., 2023), PADCLIP (Lai et al., 2023), ADCLIP (Singha et al., 2023) that introduces prompt learning to boost the cross-domain transfer. *(iii) The third* includes 9 SFDA methods: SHOT (Liang et al., 2020), GKD (Tang et al., 2021), NRC (Yang et al., 2021a), AaD (Yang et al., 2022), AdaCon (Chen et al., 2022a), CoWA (Lee et al., 2022), PLUE (Litrico et al., 2023), TPDS (Tang et al., 2024a), and MMGA (Chen et al., 2025). By idea, SHOT, GKD, CoWA are pseudo-labels-based methods; NRC, AaD, PLUE, AdaCon exploit the data geometry, e.g., the nearest neighbor, neighborhood, prototypes; TPDS predicts the target probability distribution using error control; MMGA aligns the target domain with the multimodal space represented by CLIP.

For comprehensive comparisons, we implement two variants: (i) CausalDA-C-RN (base) and (ii) CausalDA-C-B32 (premium). The key distinction lies in the backbone of the CLIP image encoder. Specifically, for CausalDA-C-RN, ResNet101 is employed on the VisDA dataset, while ResNet50 is used on the Office-Home and DomainNet-126 datasets. On the other hand, CausalDA-C-B32 adopts ViT-B/32 (Han et al., 2022) as the backbone across all datasets. This extends to all other methods using CLIP.

For an SFDA-focused comparison, we integrate the same CLIP model with existing SFDA methods, utilizing the CLIP's visual backbone (ViT B/32) as the feature extractor, followed by the original training algorithm. As such, all compared methods benefit from the CLIP pre-trained knowledge in a design-generic manner. Specifically, we select five updated SFDA methods as comparisons, including SHOT-B32, GKD-B32, NRC-B32, AaD-B32, and TPDS-B32.

Results. As listed in Tab. 3~4, our CausalDA-C-RN and CausalDA-C-B32 perform best on all tasks across the three datasets except for two tasks. Compared with previous best SFDA methods TPDS (on Office-Home), PLUE (on VisDA) and GKD (on DomainNet-126), CausalDA-C-RN improves by **4.1**%, **1.0**% and **9.3**% in average accuracy, respectively. Compared with these UDA methods with both access to labelled source

Table 4: Closed-set results (%) on **DomainNet-126**. SF and ViL means source-free and ViL model-required, respectively.

Method	Venue	SF	ViL	C→P	C→R	C→S	P→C	P→R	P→S	R→C	R→P	R→S	S→C	S→P	S→R	Avg.
Source	–	–	–	44.6	59.8	47.5	53.3	75.3	46.2	55.3	62.7	46.4	55.1	50.7	59.5	54.7
CLIP-RN	ICML21	–	✓	70.2	87.1	65.4	67.9	87.1	65.4	67.9	70.2	65.4	67.9	70.2	87.1	72.7
CLIP-B32	ICML21	–	✓	76.2	89.0	73.6	77.9	89.0	73.6	77.9	76.2	73.6	77.9	76.2	89.0	79.2
DAPL-RN	TNNLS23	✗	✓	72.4	87.6	65.9	72.7	87.6	65.6	73.2	72.4	66.2	73.8	72.9	87.8	74.8
ADCLIP-RN	ICCV23W	✗	✓	71.7	88.1	66.0	73.2	86.9	65.2	73.6	73.0	68.4	72.3	74.2	89.3	75.2
SHOT	ICML20	✓	✗	63.5	78.2	59.5	67.9	81.3	61.7	67.7	67.6	57.8	70.2	64.0	78.0	68.1
GKD	IROS21	✓	✗	61.4	77.4	60.3	69.6	81.4	63.2	68.3	68.4	59.5	71.5	65.2	77.6	68.7
NRC	NeurIPS21	✓	✗	62.6	77.1	58.3	62.9	81.3	60.7	64.7	69.4	58.7	69.4	65.8	78.7	67.5
AdaCon	CVPR22	✓	✗	60.8	74.8	55.9	62.2	78.3	58.2	63.1	68.1	55.6	67.1	66.0	75.4	65.4
CoWA	ICML22	✓	✗	64.6	80.6	60.6	66.2	79.8	60.8	69.0	67.2	60.0	69.0	65.8	79.9	68.6
PLUE	CVPR23	✓	✗	59.8	74.0	56.0	61.6	78.5	57.9	61.6	65.9	53.8	67.5	64.3	76.0	64.7
TPDS	IJCV24	✓	✗	62.9	77.1	59.8	65.6	79.0	61.5	66.4	67.0	58.2	68.6	64.3	75.3	67.1
SHOT-B32	ICML20	✓	✓	72.8	84.5	72.0	75.1	85.2	72.2	78.2	75.5	71.6	75.2	73.6	83.2	76.6
GKD-B32	IROS21	✓	✓	73.7	84.4	73.6	76.1	85.4	73.6	80.4	76.9	73.9	74.9	74.8	82.1	77.5
NRC-B32	NeurIPS21	✓	✓	72.2	83.4	72.5	75.1	84.8	72.6	78.3	76.7	74.0	75.0	73.7	82.6	76.7
AaD-B32	NeurIPS22	✓	✓	72.2	84.2	72.0	75.3	85.3	72.6	78.2	77.4	73.6	74.8	74.7	82.8	76.9
TPDS-B32	IJCV24	✓	✓	72.5	82.8	71.8	77.7	84.7	72.9	**81.9**	76.5	72.8	73.5	74.2	83.0	77.0
MMGA-B32	PR25	✓	✓	75.4	86.5	69.9	74.6	88.3	72.3	75.9	76.1	70.9	76.2	75.6	87.4	77.4
CausalDA-C-RN	–	✓	✓	75.4	88.2	72.0	75.8	88.3	72.1	76.1	75.6	71.2	77.6	75.9	88.2	78.0
CausalDA-C-B32	–	✓	✓	**79.5**	**89.8**	**76.9**	**81.6**	**90.1**	**77.5**	81.7	**80.4**	**76.6**	**82.5**	**80.1**	**89.9**	**82.2**

data and CLIP, CausalDA-C-RN still improves by **1.0**%, **0.8**%, and **2.8**% on top of second-best methods PADCLIP-RN (on Office-Home, VisDA) and ADCLIP-RN (on DomainNet-126). The improvement expands further when we switch focus to the strong version CausalDA-C-B32. Such results are unsurprising since the well-pretrained CLIP is employed to identify the external causal elements.

On the other hand, CausalDA-C-RN defeats CLIP-RN on all tasks, achieving the improvement of **4.5**%, **5.6**%, and **5.3**% on Office-Home, VisDA, and DomainNet-126 on average, respectively. Similarly, compared with CLIP-B32, the corresponding improvement of CausalDA-C-B32 are changed to **5.1**%, **5.1**% and **3.0**%. This indicates the effect of the prompt learning to discover the external causal elements.

Among the "-B32" models, we have two observations. First, CausalDA-C-B32 outperforms all conventional methods across all tasks on the three datasets, confirming the effectiveness of our design. Second, on the VisDA dataset, improvements with the B32 versions are limited, and they are even outperformed by the ResNet version, such as AaD and TPDS. This is because the rendered synthetic data (the source domain in VisDA) lacks visual details, appearing primarily in shades of white and gray light and shadow. When processed in ViT, this results in confused semantics. As for AaD and TPDS, contrastive computation (AaD) and chain-like search (TPDS) amplify the noise in the confused semantics, leading to uncontrolled error propagation.

4.4 Generalized SFDA

Dataset. We evaluate CausalDA on Office-Home, following previous Generalized SFDA works (Yang et al., 2021b; Tang et al., 2024b).

Evaluation protocol. Unlike Closed-set SFDA, the Generalized SFDA problem highlights the anti-forgetting ability on the seen source domain. In terms of evaluation rule, the same as (Yang et al., 2021b), we adopt the harmonic mean accuracy that is computed by $H = (2 * A_s * A_t)/(A_s + A_t)$ where A_s and A_t are the accuracy on the source domain and the target domain, respectively. Note that the A_s is computed based on the source-testing set. The same as (Yang et al., 2021b; Tang et al., 2024b), on the source domain, the ratio of training and testing sets is 9:1.

Competitors. As listed in Tab. 5, two Generalized SFDA comparisons, GDA (Yang et al., 2021b) and PSAT (Tang et al., 2024b), are additionally selected. GDA integrated domain attention with a local clustering-based self-supervised learning method. Essentially, knowledge of old tasks is preserved by constraining

parameters near their original values. Instead, PSAT enforces the adaptation process to remember the source domain by imposing source guidance, building a target domain-centric anti-forgetting mechanism. As CausalDA, we make two PSAT variants with ResNet50 (PSAT-RN) and ViT (PSAT-B32).

One step adapting. Tab. 5 reports the results, including source and target domain accuracies and their average. Among the "-B32" methods, CausalDA-C-B32 (without any anti-forgetting design) defeats the best specially designed model PSAT-B32 (with an anti-forgetting mechanism) with a lead of **0.3**% in harmonic mean accuracy. CausalDA-C-RN outperforms other alternatives with the same backbone. These results verify the competitiveness of our models in one-step adaptation.

Continual adapting results. We conduct continual adaptation testing following (Yang et al., 2021b). In the adaptation sequence Ar→Cl→Pr→Rw, we first train an initial model on domain Ar, which then serves as the source for adaptation to domain Cl. This process repeats iteratively until the final adaptation to domain Rw is achieved, resulting in four distinct models. Each model is evaluated across all domains, with **10**% of the data in each domain randomly selected as the test set.

Tab. 6 presents the results of CausalDA-C-RN and CausalDA-C-B32. We highlight two observations with CausalDA-C-B32: **First**, if a domain has been encountered during continual

Table 5: One step adapting results (%) on **Office-Home** in Generalized SFDA setting. S, T, H are the results on the source and target domains, and harmonic mean accuracy, respectively; the bracket values in red are the gap between S and T; WAD means With Anti-forgetting Design.

Method	Venue	WAD	Avg.		
			S	T	H
Source	–	✗	98.1	59.2	73.1
SHOT	ICML20	✗	84.2	71.8	77.1
GKD	IROS21	✗	86.8	72.5	78.7
NRC	NeurIPS21	✗	91.3	72.3	80.4
AdaCon	CVPR22	✗	88.2	65.0	74.4
CoWA	ICML22	✗	91.8	72.4	80.6
PLUE	CVPR23	✗	96.3	66.9	78.4
TPDS	IJCV24	✗	83.8	73.5	78.0
GDA	ICCV21	✓	80.0	70.2	74.4
PSAT-RN	TMM24	✓	85.3	72.6	78.4
SHOT-B32	ICML20	✗	81.9	79.5	80.7
GKD-B32	IROS21	✗	89.2	79.5	84.1
NRC-B32	NeurIPS21	✗	81.1	78.6	79.8
TPDS-B32	IJCV24	✗	88.9	79.7	84.1
PSAT-B32	TMM24	✓	89.5	80.7	84.9
MMGA-B32	PR25	✗	86.9	80.2	83.4
CausalDA-C-RN	–	✗	85.0	77.6	80.7
CausalDA-C-B32	–	✗	86.1	84.3	**85.2**

adaptation, the adapted model does not degrade significantly on that domain. For example, in the adaptation sequence Cl→Ar→Pr→Rw, when adapting from Cl to Ar, the accuracy on Ar reaches **83.4**%. Subsequent adaptations to Pr and Rw lead to an average performance drop of **3.7**% (see the second column in the second sub-table). **Second**, the adapted model performs well even on unseen domains. For instance, along the adaptation path Ar→Cl→Pr→Rw, the model's accuracy on Rw gradually improves from **71.1**% to **87.7**%

Table 6: Continual adaptation results (%) on **Office-Home** under Generalized SFDA setting, the first column of each sub-table indicates the adaptation sequence. ↓ means the average accuracy drop of a test domain on the adaptation path compared with the performance when the domain is first seen.

CausalDA-C-RN

	Ar	Cl	Pr	Rw			Cl	Ar	Pr	Rw			Pr	Ar	Cl	Rw			Rw	Ar	Cl	Pr
		Test						Test						Test						Test		
Ar	97.8	46.1	68.4	71.1		Cl	97.5	52.5	65.8	61.5		Pr	99.6	52.2	40.8	71.3		Rw	98.1	63.1	46.3	78.5
Cl	80.0	63.5	64.3	66.0		Ar	80.1	77.8	70.7	75.6		Ar	91.2	78.4	50.2	78.3		Ar	93.4	78.4	50.4	75.6
Pr	78.4	61.7	85.0	76.2		Pr	75.4	74.4	86.9	78.1		Cl	81.5	71.9	61.5	69.9		Cl	83.0	74.7	62.1	69.7
Rw	83.1	60.2	83.2	84.4		Rw	67.6	78.4	85.4	85.6		Rw	87.3	76.9	59.2	85.6		Pr	87.3	72.5	61.5	85.2
↓	17.3	2.5	1.8	−		↓	23.1	1.4	1.6	−		↓	13.0	4.1	2.3	−		↓	10.2	4.8	0.6	−

CausalDA-C-B32

	Ar	Cl	Pr	Rw			Cl	Ar	Pr	Rw			Pr	Ar	Cl	Rw			Rw	Ar	Cl	Pr
		Test						Test						Test						Test		
Ar	97.8	46.1	68.4	71.1		Cl	97.5	52.5	65.8	61.5		Pr	99.6	52.2	40.8	71.3		Rw	98.1	63.1	46.3	78.5
Cl	84.1	77.0	69.3	72.5		Ar	80.9	83.4	72.3	77.0		Ar	90.0	82.5	49.4	80.1		Ar	94.0	82.8	51.2	76.8
Pr	82.5	70.9	91.0	81.1		Pr	74.2	78.1	90.4	82.2		Cl	83.6	75.6	76.2	76.2		Cl	85.2	73.8	76.2	72.5
Rw	86.3	67.6	88.3	87.7		Rw	69.5	81.3	88.9	89.1		Rw	89.8	79.1	69.5	87.7		Pr	89.5	76.9	71.5	90.0
↓	13.5	7.7	2.7	−		↓	22.6	3.7	1.5	−		↓	11.8	5.2	6.7	−		↓	8.5	7.5	4.7	−

(see the fifth column in the first sub-table). These results suggest that CausalDA effectively captures causal factors, making it robust to domain shifts.

4.5 Open-set & Partial-set SFDA

Dataset. We adopt Office-Home for evaluation (Liang et al., 2020; Zhang et al., 2023).

Competitors. Except Source, CLIP, SHOT, and CoWA as in the Closed-set setting, we consider two more contrastive learning based SFDA methods, HCL (Huang et al., 2021) and CRS (Zhang et al., 2023).

Comparison results. As reported in Tab. 7, CausalDA-C-B32 achieves the highest average accuracy, outperforming all competing methods by margins of **5.9**% and **10.7**% over AaD-B32 in the Partial-set setting and SHOT-B32 in the Open-set setting, respectively. Similarly, it significantly outperforms SHOT-B32 and AaD-B32 under both Partial-set and Open-set settings, indicating the efficacy of the proposed design. Only CoWA beats CausalDA-C-RN in the Partial-set setting with a tiny lead **0.3**%. The results indicate that CausalDA is competitive for the Partial-set and Open-set settings.

Table 7: Partial-set, Open-set results (%) on **Office-Home**.

	Partial-set SFDA			Open-set SFDA	
Method	Venue	Avg.	Method	Venue	Avg.
Source	–	62.8	Source	–	46.6
SHOT	ICML20	79.3	SHOT	ICML20	72.8
HCL	NeurIPS21	79.6	HCL	NeurIPS21	72.6
CoWA	ICML22	83.2	CoWA	ICML22	73.2
AaD	NeurIPS22	79.7	AaD	NeurIPS22	71.8
CRS	CVPR23	80.6	CRS	CVPR23	73.2
SHOT-B32	ICML20	80.6	SHOT-B32	ICML20	73.3
AaD-B32	NeurIPS22	81.2	AaD-B32	NeurIPS22	72.4
CausalDA-C-RN	–	82.9	**CausalDA**-C-RN	–	79.6
CausalDA-C-B32	–	**87.1**	**CausalDA**-C-B32	–	**84.0**

4.6 Source-free out-of-distribution generalization

Datasets. We evaluate CausalDA in the SF-OODG setting on four challenging **ImageNet Variants**. Specifically, **IN-V2** (i.e., ImageNet-V2) (Recht et al., 2019) is an independent set consisting of natural images, collected from different sources, a total of 10k images of 1000 ImageNet categories. **IN-A** (i.e., ImageNet-A) (Hendrycks et al., 2021b) is a challenging set consisting of these "natural adversarial examples" (misclassified by a vanilla ResNet50 (He et al., 2016)), containing 7.5k images of 200 ImageNet categories. **IN-R** (i.e., ImageNet-R) (Hendrycks et al., 2021a) is an ImageNet sub-set with artistic renditions. It contains 30k images covering 200 ImageNet categories. **IN-K** (i.e., ImageNet-Sketch) (Wang et al., 2019) collects black and white sketches from the ImageNet validation set. This dataset contains 50k images from 1000 ImageNet categories.

Table 8: SF-OODG results (%) on **ImageNet variants**. L, ViL means label-required, ViL model-required, respectively.

Method	Venue	L	ViL	ImageNet→X				
				IN-V2	IN-K	IN-A	IN-R	Avg.
Source	–	–	–	62.7	22.2	0.7	35.1	30.2
CLIP-RN	ICML21	–	✓	51.5	33.3	21.8	56.1	40.7
CLIP-B32	ICML21	–	✓	54.8	40.8	29.5	66.2	47.8
CoOP-RN	IJCV21	✓	✓	55.4	34.7	23.1	56.6	42.4
CoOP-B32	IJCV21	✓	✓	58.2	41.5	31.3	65.8	49.2
CoCoOp-RN	CVPR22	✓	✓	55.7	34.5	23.3	57.7	42.8
CoCoOp-B32	CVPR22	✓	✓	56.6	40.7	30.3	64.1	47.9
TPT-RN	NeurIPS22	✗	✓	54.7	35.1	26.7	59.1	43.9
ProGrad-RN	ICCV24	✓	✓	54.7	34.4	23.1	56.8	42.2
ProGrad-B32	ICCV24	✓	✓	57.4	41.7	**31.9**	66.5	49.4
SHOT	ICML20	✗	✗	62.5	38.4	2.1	42.7	36.4
GKD	IROS21	✗	✗	62.3	38.2	2.1	42.2	36.2
NRC	NeurIPS21	✗	✗	61.5	0.9	1.3	28.9	23.1
AdaCon	CVPR22	✗	✗	50.9	18.5	2.0	38.6	27.5
CoWA	ICML22	✗	✗	62.7	37.8	1.7	46.3	37.1
PLUE	CVPR23	✗	✗	53.0	18.5	2.0	38.6	28.0
TPDS	IJCV24	✗	✗	62.9	35.0	2.9	48.4	37.3
SHOT-B32	ICML20	✗	✓	69.4	43.6	1.6	58.2	43.2
GKD-B32	IROS21	✗	✓	53.5	45.2	1.0	58.3	39.5
NRC-B32	NeurIPS21	✗	✓	66.2	18.6	15.4	38.0	34.6
TPDS-B32	IJCV24	✗	✓	69.0	38.9	0.6	58.7	41.8
CausalDA-C-RN	–	✗	✓	64.4	42.6	22.3	61.5	47.7
CausalDA-C-B32	–	✗	✓	64.7	**48.4**	30.6	**71.0**	**53.7**

Competitors. In addition to the methods compared in the Closed-set SFDA setting, we include four more: CoOP (Zhou et al., 2022b), CoCoOp (Zhou et al., 2022a), TPT (Shu et al., 2022), and ProGrad (Zhu et al., 2023). Among them, CoOP, CoCoOp, and ProGrad employ prompt learning with supervision from a few labeled samples, while TPT introduces self-supervised prompt tuning by minimizing multi-view entropy.

Table 9: Causal vs. statistical SFDA. OH/VDA/DN126: **Office-Home/VisDA/DomainNet-126**. S/T: Source/Target domain; H: Harmonic mean accuracy. H_g: Average over all settings except closed-set.

Method	Venue	Closed-set				Generalized			Open-set	Partial-set	SF-OODG					
		OH	VDA	DN126	*Avg.*	S	T	H	T	T	IN-V2	IN-K	IN-A	IN-R	*Avg.*	H_g
Source	–	59.2	49.2	54.7	54.4	98.1	59.2	73.8	46.6	62.8	62.7	22.2	0.7	35.1	30.2	53.4
DIFO	CVPR24	83.1	90.3	80.0	84.5	78.0	83.1	80.5	75.9	85.6	59.6	37.7	25.2	66.4	47.2	72.3
ProDe	ICLR25	**84.5**	**91.0**	**85.0**	**86.8**	85.1	84.5	84.8	82.6	84.2	62.1	45.8	24.7	69.7	50.6	75.5
CausalDA	–	84.3	90.3	82.2	85.6	86.1	84.3	**85.2**	**84.0**	**87.1**	**64.7**	**48.4**	**30.6**	**71.0**	**53.7**	**77.5**

Table 10: Unification comparison results (%). H_{all}: Average over all settings; H_{wrg}: The largest percentage shortfall of a method from the per-setting best across all settings; H_{loso}: Omit one setting at a time and average the scores over the rest.

Method	$H_{wrg}(\downarrow)$	$H_{loso}(\uparrow)$					$H_{all}(\uparrow)$
		w/o Closed-set	w/o Generalized setting	w/o Open-set	w/o Partial-set	w/o SF-OODG	
DIFO	12.1	72.3	73.3	74.4	72.0	81.6	74.7
ProDe	5.77	75.5	76.0	76.6	76.2	84.6	77.7
CausalDA	**1.38**	**77.5**	**77.6**	**77.9**	**77.1**	**85.5**	**79.1**

Comparison results. Tab. 8 reports the SF-OODG results. In average accuracy, our methods, CausalDA-C-NR and CausalDA-C-B32, outperform previous SFDA methods by a significant margin, achieving at least a **10**% improvement. Even compared to CLIP and other CLIP-based methods, CausalDA maintains a clear advantage. For example, CausalDA-C-NR improves upon CLIP-C-RN by **7.0**% and surpasses the second-best CLIP-based method, TPT-RN, by **3.8**%. Among the "-B32" models, CausalDA-C-B32 excels with a margin of at least **10.5**% over previous methods.

4.7 Further analysis

All experiments use the strong variant CausalDA-C-B32; the suffix "-C-B32" is omitted hereafter.

4.7.1 Causal vs. statistical SFDA

In this strategic evaluation, we contrast CausalDA with two state-of-the-art statistical SFDA methods, DIFO (Tang et al., 2024c) and ProDe (Tang et al., 2025), both of which are equipped with the same ViL model. Our analysis focuses on two critical modeling aspects, examined across various SFDA settings: *Domain fitness*: Evaluated under Closed-set conditions; *Domain generalization*: Assessed across Generalized, Partial-set, Open-set, and SF-OODG settings.

Based on this evaluation, we draw the following key observations: (1) Domain fitness (Closed-set SFDA): As presented in Tab. 9, CausalDA is indeed outperformed by both DIFO and ProDe in the Closed-set setting. This is attributed to the inherent statistical learning nature of these alternatives, which tends to overfit their models towards the specific target domain. (2) Under the Generalized SFDA setting, CausalDA demonstrates superior performance in H-accuracy, also exhibiting the least drop in source domain accuracy (see S-accuracy). This is because the captured causality mitigates the risk of forgetting the source domain. (3) Except for the Closed-set scenario, CausalDA consistently stands out with strong performance on the other four settings. This highlights the superior domain generalization capabilities achieved through our method's causal knowledge discovery. Importantly, our approach provides the best overall solution across all these diverse settings. Collectively, these results validate that our approach strikes the optimal balance between domain fitness and generalization, thereby laying a solid foundation to serve as a unified SFDA solution.

Unification comparison. To underscore CausalDA's advantage over DIFO and ProDe, we perform a unification evaluation using the metrics in Eq. (17). The comparison in Tab. 10 shows that CausalDA attains the highest score in all scenarios. This indicates that CausalDA delivers robust, stable performance across diverse settings. Moreover, it exhibits no apparent weakness in any single scenario (cf. H_{wrg}), and its all-round

superiority is not driven by any individual setting (cf. H_{loso}). Together, this evidence supports our claim of being towards a universally adaptable framework.

4.7.2 Analysis for causal factors discovery

We conduct causality analysis in two aspects: (1) complementarity of internal and external causality, and (2) analysis for the discovery process based on pseudo-label.

Complementarity of internal and external causality. As aforementioned, causal factors originate from both the domain data itself (encoded internal causality) and external knowledge sources (encoded external causality). To illustrate this complementarity, we conduct an intuitive empirical experiment on the target domain. Specifically, we fuse the zero-shot predictions of the source model (Source) and a ViL model like CLIP using a logical OR operation. That is, if either CLIP or Source correctly predicts the true category of an input instance $\boldsymbol{x}$, we consider $\boldsymbol{x}$ correctly classified. As shown in Fig. 6, Fusion-OR significantly outperforms both Source and CLIP individually, reinforcing the plausibility of our internal-external causality partition.

Figure 6: Zero-shot fusion results (Fusion-OR) of CLIP and the source model (Source) under the Closed-set SFDA setting on the **Office-Home**, **VisDA**, and **DomainNet-126** datasets. This fusion method follows the logical OR principle: An input instance is considered correctly classified if either CLIP or the source model predicts its ground truth category.

Pseudo-label-based analysis for discovery process. In CausalDA, the external causal elements S_e are identified and converted into pseudo-labels. Thus, the quality of these pseudo-labels serves as an indicator of the discovery process. To evaluate this, we compare pseudo-label-based methods SHOT, COWA, and GKD, along with CLIP's zero-shot predictions (denoted as CLIP). The results, shown in Fig. 7, demonstrate that CausalDA-PL achieves significantly higher pseudo-label accuracy than prior methods, benefiting from CLIP-assisted S_e discovery. Furthermore, the performance curve of CausalDA remains consistently above that of CausalDA-PL, with a significant gap throughout training. This highlights the effectiveness of capturing internal causal elements S_i, further enhancing model performance.

Figure 7: Dynamics of pseudo-label accuracy on task Ar→Cl in the **Office-home** dataset. The method "X-PL" means the corresponding accuracy of pseudo-label generated in X.

4.7.3 Model analysis

Feature distribution visualization. Feature distribution provides an intuitive way to evaluate classification performance. We compare with Source (source model), CLIP, SHOT, TPDS, and Oracle (trained on domain Cl with real labels). Fig. 8 presents the logit visualization results using a 3D density chart. As we move from Source to CausalDA, the clustering effect progressively improves, with CausalDA exhibiting the most structured distribution, closely resembling Oracle.

Ablation study. In CausalDA, we separately discover the causal factors $S=\{S_e, S_i\}$. To isolate the effect of this strategy, we evaluate four variations: (i) CausalDA-w-S_i: We use only $\mathcal{L}_{\text{UN}}$ from Eq. (16) as the objective for model training, allowing us to assess the impact of capturing S_i. (ii) CausalDA-w-S_e: We apply pseudo-label supervised learning, regulated by $\mathcal{L}_{\text{SCE}}$, where the pseudo-labels are generated from S_e discovery, regulated by L_{EC}. This isolates the effect of capturing S_e. (iii) CausalDA-w-CLIP: We directly use CLIP's

Figure 8: Logit distribution visualization on transfer task Ar→Cl in **Office-Home**. Oracle: Model trained on the real labels of domain Cl. For a clear view, the first ten categories are displayed.

zero-shot results as pseudo-labels to regulate the discovery of S_i. (iv) CausalDA-w-P1: We retain only the phase-1 objective, removing the loss $\mathcal{L}_{\mathrm{IC}}$ from Eq. (16).

Tab. 11 presents the results of these methods across four SFDA settings and SF-OODG. Specifically, both CausalDA-w-S_i and CausalDA-w-S_e outperform the Source model, but fall significantly behind the full CausalDA version. This suggests that capturing either S_e or S_i independently is effective, but both are necessary for optimal performance. The comparison between CausalDA-w-CLIP and CausalDA highlights the importance of L_{EC}-based prompt learning for S_e discovery. Finally, CausalDA-w-P1 performs considerably worse than CausalDA, emphasizing the value of our two-stage design in the causal factor capture pipeline.

Table 11: Ablation study results (%). CS, OS, PS, and GS mean the Closed-set, Open-set, Partial-set, and Generalized SFDA settings, respectively.

| Method | Office-Home | | | | | IN-K |
	CS	OS	PS	GS	Avg.	SF-OODG
Source	59.2	46.6	62.8	73.1	60.4	30.2
CausalDA-w-S_i	71.3	72.1	71.6	76.6	72.9	36.9
CausalDA-w-S_e	82.5	81.4	85.5	84.9	83.6	44.2
CausalDA-w-CLIP	82.0	78.8	85.1	83.3	82.3	44.2
CausalDA-w-P1	80.3	38.1	80.7	78.1	69.3	40.8
CausalDA	**84.3**	**84.0**	**87.1**	**85.2**	**85.1**	**48.4**

Scalability study of IC instantiation. The objective $\mathcal{L}_{\mathrm{IC}}$ in Eq. (16), which regulates S_i discovery, is a component with multiple implementation options. To evaluate its scalability, we present three alternative instantiations for the two regulators in $\mathcal{L}_{\mathrm{IC}}$. For $\mathcal{L}_{\mathrm{UN}}$, we consider the following alternatives: (i) CausalDA+ENT: Entropy regularization without category balance constraints, (ii) CausalDA+NRC: Data local structure-based regularization, (iii) CausalDA+TPDS: Domain shift control-based regularization. For $\mathcal{L}_{\mathrm{SCE}}$, we test three popular methods: 1-Norm ($||\cdot||_1$), 2-Norm ($||\cdot||_2$), and KL Divergence.

As shown in Tab. 12, in the Closed-set setting, CausalDA+TPDS achieves the best results, with other methods lagging by up to **1.9**% (on VisDA). This indicates that these typical regulators do not significantly affect model performance in this setting. In the SF-OODG setting, all methods (except CausalDA+KL) show a slight accuracy drop compared to CausalDA. For CausalDA+ENT, removing the category balance regularization leads to a performance decrease. The performance loss for CausalDA+NRC and CausalDA+TPDS is attributed to the fact that these methods do not specifically address the SF-OODG setting.

Table 12: Scalability study (%) of IC instantiation.

| Loss | Method | Closed-set | | SF-OODG |
		Office-Home	VisDA	IN-K
$\mathcal{L}_{\mathrm{UN}}$	**CausalDA**+ENT	83.5	90.4	46.8
	CausalDA+NRC	83.9	89.0	47.5
	CausalDA+TPDS	**84.6**	**90.9**	45.0
$\mathcal{L}_{\mathrm{SCE}}$	**CausalDA**+$||\cdot||_1$	83.4	89.3	44.9
	CausalDA+$||\cdot||_2$	83.8	89.2	40.3
	CausalDA+KL	84.5	90.0	**49.1**
	CausalDA	84.3	90.3	48.4

For $\mathcal{L}_{\mathrm{SCE}}$, the results show that probability distribution approximation (KL Divergence) outperforms feature-based methods ($||\cdot||_1$ and $||\cdot||_2$) in preserving model performance in the presence of external causality.

Effect of prompt initialization. In CausalDA, we employ prompt learning to encode the external causal factors S_e. Here, we examine four different prompt initialization strategies (Tab. 13): (i) the conventional constant strategy (rows 1–2), (ii) the sentence strategy (rows 3–4), (iii) the uncertainty strategy (rows 5–7), and (iv) an innovative approach of sentence initialization with different phrase (rows 8–9), which considers the lack of precise supervision in SFDA.

Table 13: Prompt initialization study (%).

#	Initialization template	Closed-set		SF-OODG
		Office-Home	**VisDA**	**IN-K**
1	'X [CLASS].' (#X=4)	83.6	90.1	48.4
2	'X [CLASS].' (#X=16)	82.5	89.6	46.1
3	'There is a [CLASS].'	84.6	90.2	48.6
4	'This is a photo of a [CLASS].'	84.7	89.9	**48.8**
5	'This is maybe a photo of a [CLASS].'	83.9	90.2	**48.8**
6	'This is almost a photo of a [CLASS].'	**84.8**	**90.3**	48.4
7	'This is definitely a photo of a [CLASS].'	84.5	90.0	48.1
8	'a picture of a [CLASS].'	84.6	89.8	48.6
9	'a photo of a [CLASS].'	84.3	**90.3**	48.4

Tab. 13 shows the comparison results for these nine templates across both the Closed-set setting and SF-OODG. The results indicate that the different templates do not cause significant performance differences, suggesting that CausalDA is relatively insensitive to prompt selection. However, when comparing the constant strategy to the others, it becomes clear that initializing with semantic information is the more effective option, which aligns with our expectations.

Figure 9: Parameter sensitiveness study (σ, τ) on transfer task Ar→Cl in **Office-Home**.

Parameters sensitiveness. Taking the transfer task Ar→Cl in Office-Home for example, we evaluate the sensitivity of CausalDA by varying the hyper-parameters $0.2 \leq \sigma \leq 1.1$, $0.7 \leq \tau \leq 1.6$ at the step of 0.1. Fig. 9 indicates that both corresponding terms matter, whilst their sensitivity to performance is not high.

5   Conclusion

We introduce a more challenging Unified SFDA problem that comprehensively addresses all specific scenarios within a unified framework. To tackle this, we propose CausalDA, a novel approach grounded in causality, fundamentally differing from previous methods based on statistical dependence. Specifically, we design a self-supervised information bottleneck to capture external causal elements, convert them into pseudo-labels, and use them to guide the discovery of internal causal factors. Building on our theoretical insights, we implement this information bottleneck using a network-based variational mutual information approach. Extensive experiments across various SFDA settings and SF-OODG validate the superiority of CausalDA over existing methods.

References

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *rXiv preprint arXiv:2006.10726*, 2019.

David Barber and Felix Agakov. The im algorithm: a variational approach to information maximization. *Proc. Adv. Neural Inform. Process. Syst.*, 16(320):201, 2004.

Hoyoon Byun, Gyeongdeok Seo, Joonseong Kang, Taero Kim, Jihee Kim, and Kyungwoo Song. CCL: Causal-aware in-context learning for out-of-distribution generalization. 2025. URL https://openreview.net/forum?id=FxV7Fvlm2T.

Zhangjie Cao, Kaichao You, Mingsheng Long, Jianmin Wang, and Qiang Yang. Learning to transfer examples for partial domain adaptation. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 2985–2994, 2019.

Dian Chen, Dequan Wang, Trevor Darrell, and Sayna Ebrahimi. Contrastive test-time adaptation. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 295–305, 2022a.

Dongjie Chen, Kartik Patwari, Zhengfeng Lai, Sen-ching Cheung, and Chen-Nee Chuah. Empowering source-free domain adaptation with mllm-driven curriculum learning. *arXiv preprint arXiv:2405.18376*, 2024a.

Lijuan Chen, Yunxiang Bai, Ying Hu, Qiong Wang, and Xiaozhi Qi. Source-free domain adaptation via multimodal space-guided alignment. *Pattern Recognition*, pp. 112827, 2025.

Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Conghui He, Jiaqi Wang, Feng Zhao, and Dahua Lin. ShareGPT4v: Improving large multi-modal models with better captions. In *Proc. Eur. Conf. Comput. Vis.*, pp. 370–387. Springer, 2024b.

Weijie Chen, Luojun Lin, Shicai Yang, Di Xie, Shiliang Pu, and Yueting Zhuang. Self-supervised noisy label learning for source-free unsupervised domain adaptation. In *Proc. IEEE Int. Intell. Rob. Syst.*, pp. 10185–10192. IEEE, 2022b.

Yuansi Chen and Peter Bühlmann. Domain adaptation under structural causal models. *J. Mach. Learn. Resear.*, 22(1):11856–11935, 2021.

Rune Christiansen, Niklas Pfister, Martin Emil Jakobsen, Nicola Gnecco, and Jonas Peters. A causal framework for distribution generalization. *IEEE Trans. Pattern Anal. Mach. Intell.*, 44(10):6614–6630, 2021.

Ning Ding, Yixing Xu, Yehui Tang, Chao Xu, Yunhe Wang, and Dacheng Tao. Source-free domain adaptation via distribution estimation. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 7212–7222, 2022.

Yuntao Du, Haiyang Yang, Mingcai Chen, Juan Jiang, Hongtao Luo, and Chongjun Wang. Generation, augmentation, and alignment: A pseudo-source domain based method for source-free domain adaptation. *Mach. Learn.*, 113:3611–3631, 2024.

Chunjiang Ge, Rui Huang, Mixue Xie, Zihang Lai, Shiji Song, Shuang Li, and Gao Huang. Domain adaptation via prompt learning. *IEEE Transactions on Neural Networks and Learning Systems*, 2023.

Kai Han, Yunhe Wang, Hanting Chen, Xinghao Chen, Jianyuan Guo, Zhenhua Liu, Yehui Tang, An Xiao, Chunjing Xu, Yixing Xu, et al. A survey on vision transformer. *IEEE Trans. Pattern Anal. Mach. Intell.*, 45(1):87–110, 2022.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 770–778, 2016.

Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, et al. The many faces of robustness: A critical analysis of out-of-distribution generalization. In *Proc. IEEE Int. Conf. Comput. Vis.*, pp. 8340–8349, 2021a.

Dan Hendrycks, Kevin Zhao, Steven Basart, Jacob Steinhardt, and Dawn Song. Natural adversarial examples. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 15262–15271, 2021b.

Rein Houthooft, Xi Chen, Yan Duan, John Schulman, Filip De Turck, and Pieter Abbeel. Vime: Variational information maximizing exploration. *Proc. Adv. Neural Inform. Process. Syst.*, 29, 2016.

Jiaxing Huang, Dayan Guan, Aoran Xiao, and Shijian Lu. Model adaptation: Historical contrastive learning for unsupervised domain adaptation without source data. *Proc. Adv. Neural Inform. Process. Syst.*, 34: 3635–3649, 2021.

Xu Ji, Joao F Henriques, and Andrea Vedaldi. Invariant information clustering for unsupervised image classification and segmentation. In *Proc. IEEE Int. Conf. Comput. Vis.*, pp. 9865–9874, 2019.

Kenji Kawaguchi, Zhun Deng, Xu Ji, and Jiaoyang Huang. How does information bottleneck help deep learning? In *Proc. Int. Conf. Mach. Learn.*, pp. 16049–16096. PMLR, 2023.

Youngeun Kim, Donghyeon Cho, Kyeongtak Han, Priyadarshini Panda, and Sungeun Hong. Domain adaptation without source data. *IEEE Trans. on Artif. Intell.*, 2(6):508–518, 2021.

Andreas Krause, Pietro Perona, and Ryan Gomes. Discriminative clustering by regularized information maximization. *Proc. Adv. Neural Inform. Process. Syst.*, 23, 2010.

Jogendra Nath Kundu, Naveen Venkat, R Venkatesh Babu, et al. Universal source-free domain adaptation. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 4544–4553, 2020.

Zhengfeng Lai, Noranart Vesdapunt, Ning Zhou, Jun Wu, Cong Phuoc Huynh, Xuelu Li, Kah Kuen Fu, and Chen-Nee Chuah. PADCLIP: Pseudo-labeling with adaptive debiasing in clip for unsupervised domain adaptation. In *Proc. IEEE Int. Conf. Comput. Vis.*, pp. 16155–16165, 2023.

Jonghyun Lee, Dahuin Jung, Junho Yim, and Sungroh Yoon. Confidence score for source-free unsupervised domain adaptation. In *Int. Conf. Mach. Learn.*, pp. 12365–12377. PMLR, 2022.

Bo Li, Yifei Shen, Yezhen Wang, Wenzhen Zhu, Dongsheng Li, Kurt Keutzer, and Han Zhao. Invariant information bottleneck for domain generalization. In *Proc. AAAI Conf. Artif. Intell.*, volume 36, pp. 7399–7407, 2022.

Rui Li, Qianfen Jiao, Wenming Cao, Hau-San Wong, and Si Wu. Model adaptation: Unsupervised domain adaptation without source data. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 9638–9647, 2020a.

Rui Li, Qianfen Jiao, Wenming Cao, Hau-San Wong, and Si Wu. Model adaptation: Unsupervised domain adaptation without source data. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 9641–9650, 2020b.

Weikai Li and Songcan Chen. Partial domain adaptation without domain alignment. *IEEE Trans. Pattern Anal. Mach. Intell.*, 45(7):8787–8797, 2023.

Jian Liang, Dapeng Hu, and Jiashi Feng. Do we really need to access the source data? source hypothesis transfer for unsupervised domain adaptation. In *Proceedings of the Int. Conf. Mach. Learn.*, pp. 6028–6039, 2020.

Mattia Litrico, Alessio Del Bue, and Pietro Morerio. Guiding pseudo-labels with uncertainty estimation for test-time adaptation. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, 2023.

Yadan Luo, Zijian Wang, Zhuoxiao Chen, Zi Huang, and Mahsa Baktashmotlagh. Source-free progressive graph learning for open-set domain adaptation. *IEEE Trans. Pattern Anal. Mach. Intell.*, 2023.

Fangrui Lv, Jian Liang, Shuang Li, Bin Zang, Chi Harold Liu, Ziteng Wang, and Di Liu. Causality inspired representation learning for domain generalization. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 8046–8056, 2022.

Divyat Mahajan, Shruti Tople, and Amit Sharma. Domain generalization using causal matching. In *Int. Conf. Mach. Learn.*, pp. 7313–7324. PMLR, 2021.

Cheng Ouyang, Chen Chen, Surui Li, Zeju Li, Chen Qin, Wenjia Bai, and Daniel Rueckert. Causality-inspired single-source domain generalization for medical image segmentation. *IEEE Trans. Med. Imag.*, 42(4): 1095–1106, 2022.

Pau Panareda Busto and Juergen Gall. Open set domain adaptation. In *Proc. IEEE Int. Conf. Comput. Vis.*, pp. 754–763, 2017.

Judea Pearl. *Causality*. Cambridge university press, 2009.

Xingchao Peng, Ben Usman, Neela Kaushik, Judy Hoffman, Dequan Wang, and Kate Saenko. VisDA: The visual domain adaptation challenge. *arXiv:1710.06924*, 2017.

Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *Proc. IEEE Int. Conf. Comput. Vis.*, pp. 1406–1415, 2019.

Jonas Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of causal inference: foundations and learning algorithms.* The MIT Press, 2017.

Sanqing Qu, Tianpei Zou, Lianghua He, Florian Röhrbein, Alois Knoll, Guang Chen, and Changjun Jiang. Lead: Learning decomposition for source-free universal domain adaptation. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 23334–23343, 2024.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *Proc. Int. Conf. Mach. Learn.*, pp. 8748–8763. PmLR, 2021.

Benjamin Recht, Rebecca Roelofs, Ludwig Schmidt, and Vaishaal Shankar. Do imagenet classifiers generalize to imagenet? In *Int. Conf. Mach. Learn.*, pp. 5389–5400. PMLR, 2019.

Jameel Hassan Abdul Samadh, Hanan Gani, Noor Hazim Hussein, Muhammad Uzair Khattak, Muzammal Naseer, Fahad Khan, and Salman Khan. Align your prompts: Test-time prompting with distribution alignment for zero-shot generalization. In *Proc. Adv. Neural Inform. Process. Syst.*, volume 36, pp. 80396–80413, 2023.

Bernhard Schölkopf, Francesco Locatello, Stefan Bauer, Nan Rosemary Ke, Nal Kalchbrenner, Anirudh Goyal, and Yoshua Bengio. Toward causal representation learning. *Proceedings of the IEEE*, 109(5):612–634, 2021.

Manli Shu, Weili Nie, De-An Huang, Zhiding Yu, Tom Goldstein, Anima Anandkumar, and Chaowei Xiao. Test-time prompt tuning for zero-shot generalization in vision-language models. *Proc. Adv. Neural Inform. Process. Syst.*, 35:14274–14289, 2022.

Mainak Singha, Harsh Pal, Ankit Jha, and Biplab Banerjee. Ad-clip: Adapting domains in prompt space using clip. In *Proc. IEEE Int. Conf. Comput. Vis.*, pp. 4355–4364, 2023.

S Tang, Yuji Shi, Zhiyuan Ma, Jian Li, Jianzhi Lyu, Qingdu Li, and Jianwei Zhang. Model adaptation through hypothesis transfer with gradual knowledge distillation. In *Proc. IEEE/RSJ Int. Conf. Intell. Rob. Syst.*, pp. 5679–5685. IEEE, 2021.

Song Tang, Yan Zou, Zihao Song, Jianzhi Lyu, Lijuan Chen, Mao Ye, Shouming Zhong, and Jianwei Zhang. Semantic consistency learning on manifold for source data-free unsupervised domain adaptation. *Neural Networks*, 152:467–478, 2022.

Song Tang, An Chang, Fabian Zhang, Xiatian Zhu, Mao Ye, and Changshui Zhang. Source-free domain adaptation via target prediction distribution searching. *Int. J. Comput. Vis.*, 132(3):654–672, 2024a.

Song Tang, Yuji Shi, Zihao Song, Mao Ye, Changshui Zhang, and Jianwei Zhang. Progressive source-aware transformer for generalized source-free domain adaptation. *IEEE Trans. on Multime.*, 26:4138–4152, 2024b. doi: 10.1109/TMM.2023.3321421.

Song Tang, Wenxin Su, Mao Ye, and Xiatian Zhu. Source-free domain adaptation with frozen multimodal foundation model. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 23711–23720, 2024c.

Song Tang, Wenxin Su, Yan Gan, Mao Ye, Jianwei Zhang, and Xiatian Zhu. Proxy denoising for source-free domain adaptation. In *Int. Conf. Learn. Represent.*, 2025. DOI: https://arxiv.org/abs/2406.01658.

Jiayi Tian, Jing Zhang, Wen Li, and Dong Xu. VDM-DA: Virtual domain modeling for source data-free domain adaptation. *IEEE Trans. Circuits Syst. Video Technol.*, 32(6):3749–3760, 2021.

Naftali Tishby, Fernando C Pereira, and William Bialek. The information bottleneck method. *arXiv preprint physics/0004057*, 2000.

Hemanth Venkateswara, Jose Eusebio, Shayok Chakraborty, and Sethuraman Panchanathan. Deep hashing network for unsupervised domain adaptation. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 5385–5394, 2017.

Guillaume Vray, Devavrat Tomar, Behzad Bozorgtabar, and Jean-Philippe Thiran. Distill-SODA: Distilling self-supervised vision transformer for source-free open-set domain adaptation in computational pathology. *IEEE Trans. Med. Imag.*, 43(5):2021–2032, 2024.

Haohan Wang, Songwei Ge, Zachary Lipton, and Eric P Xing. Learning robust global representations by penalizing local predictive power. *Proc. Adv. Neural Inform. Process. Syst.*, 32, 2019.

Ruoyu Wang, Mingyang Yi, Zhitang Chen, and Shengyu Zhu. Out-of-distribution generalization with causal invariant transformations. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 375–385, 2022a.

Wenjie Wang, Xinyu Lin, Fuli Feng, Xiangnan He, Min Lin, and Tat-Seng Chua. Causal representation learning for out-of-distribution recommendation. In *Proc. ACM Web Conf.*, pp. 3562–3571, 2022b.

Xuetong Wu, Mingming Gong, Jonathan H. Manton, Uwe Aickelin, and Jingge Zhu. On causality in domain adaptation and semi-supervised learning: an information-theoretic analysis for parametric models. *Journal of Machine Learning Research*, 25(261):1–57, 2024. URL http://jmlr.org/papers/v25/22-1024.html.

Shiqi Yang, Joost van de Weijer, Luis Herranz, Shangling Jui, et al. Exploiting the intrinsic neighborhood structure for source-free domain adaptation. *Proc. Adv. Neural Inform. Process. Syst.*, 34:29393–29405, 2021a.

Shiqi Yang, Yaxing Wang, Joost Van De Weijer, Luis Herranz, and Shangling Jui. Generalized source-free domain adaptation. In *Proc. IEEE Int. Conf. Comput. Vis.*, pp. 8978–8987, 2021b.

Shiqi Yang, Shangling Jui, Joost van de Weijer, et al. Attracting and dispersing: A simple approach for source-free domain adaptation. *Proc. Adv. Neural Inform. Process. Syst.*, 35:5802–5815, 2022.

Shiqi Yang, Yaxing Wang, Joost van de Weijer, Luis Herranz, Shangling Jui, and Jian Yang. Trust your good friends: Source-free domain adaptation by reciprocal neighborhood clustering. *IEEE rans. Pattern Anal. Mach. Intell.*, 2023.

Wenyu Zhang, Li Shen, and Chuan-Sheng Foo. Source-free domain adaptation guided by vision and vision-language pre-training. *Int. J. Comput. Vis.*, 133(2):844–866, 2025.

Yixin Zhang, Zilei Wang, and Weinan He. Class relationship embedded learning for source-free unsupervised domain adaptation. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 7619–7629, 2023.

Kaiyang Zhou, Jingkang Yang, Chen Change Loy, and Ziwei Liu. Conditional prompt learning for vision-language models. In *Proc. IEEE Conf. Comput. Vis. Pattern Recog.*, pp. 16816–16825, 2022a.

Kaiyang Zhou, Jingkang Yang, Chen Change Loy, and Ziwei Liu. Learning to prompt for vision-language models. *Int. J. Comput. Vis.*, 130(9):2337–2348, 2022b.

Beier Zhu, Yulei Niu, Yucheng Han, Yue Wu, and Hanwang Zhang. Prompt-aligned gradient for prompt tuning. In *Proc. IEEE Int. Conf. Comput. Vis.*, pp. 15659–15669, 2023.

Zhanshi Zhu, Qing Dong, Gongning Luo, Wei Wang, Suyu Dong, Kuanquan Wang, Ye Tian, Guohua Wang, and Shuo Li. Causality-adjusted data augmentation for domain continual medical image segmentation. *IEEE Journal of Biomedical and Health Informatics*, pp. 1–14, 2025.

A A Proof of Lemma 1

Restatement of Lemma 1 *Given random variables Z_1, X_1, Y_1 where X_1, Y_1 satisfy a mapping $f_1 : X_1 \mapsto Y_1$. When f_1 is compressed, i.e., the output's dimension is smaller than the input's,*

$$I(Z_1, X_1) \geq I(Z_1, Y_1) \tag{18}$$

Proof. Since mapping f_1 is compressed, the entropy of X_1, Y_1 have $H(X_1) \geq H(Y_1)$. As for $I(Z_1, X_1)$, it has

$$
\begin{aligned}
I(Z_1, X_1) &\geq I(Z_1, X_1) - H(Z_1|Y_1) - I(X_1, Y_1) \\
&\geq [H(Z_1) + H(X_1) - H(Z_1, X_1)] - H(Z_1|Y_1) \\
&\quad - [H(X_1) + H(Y_1) - H(X_1, Y_1)] \\
&= H(Z_1) - H(Z_1|Y_1) - H(Y_1) + H(X_1, Y_1) \\
&\geq I(Z_1, Y_1) - H(Y_1) + \max(H(X_1), H(Y_1)) \\
&\geq I(Z_1, Y_1) - H(Y_1) + H(X_1) \\
&\geq I(Z_1, Y_1) - H(Y_1) + H(Y_1) \\
&= I(Z_1, Y_1)
\end{aligned}
\tag{19}
$$

B A Proof of Theorem 1

Restatement of Theorem 1 *Suppose there are five random variables, Z, V, Z', Y and Y'. Among them, Z represents the target domain knowledge; V, Z' and Y express the input instances, predictions and intermediate features of ViL model, respectively; Y' depicts a pseudo-label that has a learnable functional relationship f_w (w is parameters) with Z'. When the function f_w is reversible and uncompressed, we have this upper bound as follows.*

$$
\min_{\boldsymbol{v}_d} I(Z, Z') - I(Z', Y) \leq \min_{\boldsymbol{v}_d, w} \underbrace{I(Z, Z')}_{T_1} - \underbrace{I(Y', Y)}_{T_2}, Y' = f_w(Z').
\tag{20}
$$

Proof. Since the function f_w is reversible and uncompressed, the Z' and Y' satisfy bidirectional one-to-one mapping. In other words, the from Y' to Z', there is not information loss, formally $H(Y') = H(Z')$, termed condition A. Let $L = I(Z, Z') - I(Z', Y)$, we have

$$
L \leq I(Z, Z') - I(Z', Y) + I(Z', Y') \leq I(Z, Z') - \left[H\left(Z'|Y'\right) - H\left(Z'|Y\right)\right].
\tag{21}
$$

The following discusses separately the two components in the second item of Eq. 21 under condition A.

(1) **Proof** $H(Z'|Y') = H(Y')$.

Let $L_1 = H(Z'|Y')$, we have the relation as

$$
L_1 = H\left(Z', Y'\right) - H\left(Y'\right) \leq H\left(Z'\right) + H\left(Y'\right) - H\left(Y'\right) = H\left(Z'\right)
\tag{22}
$$

Also, we know $L_1 \geq H(Z')$. Combing Eq. 22, we obtain $L_1 = H(Z') = H(Y')$ according to Sandwich Theorem and condition A.

(2) **Proof** $H(Z'|Y) = H(Y'|Y)$.

Let $L_2 = H(Z'|Y)$, $L_3 = H(Y'|Y)$, here, we prove $L_2 = L_3$ with condition A. For L_2, it can be expressed as

$$
L_2 = H\left(Z', Y\right) - H(Y),
\tag{23}
$$

then we have

$$
\begin{aligned}
\max\left(H\left(Z'\right), H(Y)\right) - H(Y) &\leq L_2 \leq H\left(Z'\right) \\
H\left(Z'\right) - H(Y) &\leq L_2 \leq H\left(Z'\right).
\end{aligned}
\tag{24}
$$

Similarly, L_3 can be expressed as

$$
H\left(Y'\right) - H(Y) \leq L_3 \leq H\left(Y'\right).
\tag{25}
$$

$$
\text{Thus, } H\left(Z'\right) - H\left(Y'\right) \leq L_2 - L_3 \leq H\left(Z'\right) - H\left(Y'\right).
\tag{26}
$$

Due to Sandwich Theorem and condition A, we have $L_2 - L_3 = 0$, such that

$$
L \leq I\left(Z, Z'\right) - \left[H\left(Y'\right) - H\left(Y'|Y\right)\right] = I\left(Z, Z'\right) - I\left(Y', Y\right).
\tag{27}
$$