LEARNING EFFICIENT ONLINE 3D BIN PACKING ON PACKING CONFIGURATION TREES

ABSTRACT

Online 3D Bin Packing Problem (3D-BPP) has widespread applications in industrial automation and has aroused enthusiastic research interest recently. Existing methods usually solve the problem with limited resolution of spatial discretization, and/or cannot deal with complex practical constraints well. We propose to enhance the practical applicability of online 3D-BPP via learning on a novel hierarchical representation – packing configuration tree (PCT). PCT is a full-fledged description of the state and action space of bin packing which can support packing policy learning based on deep reinforcement learning (DRL). The size of the packing action space is proportional to the number of leaf nodes, making the DRL model easy to train and well-performing even with continuous solution space. During training, PCT expands based on heuristic rules, however, the DRL model learns a much more effective and robust packing policy than heuristic methods. Through extensive evaluation, we demonstrate that our method outperforms all existing online BPP methods and is versatile in terms of incorporating various practical constraints.

1 INTRODUCTION

As one of the most classic combinatorial optimization problems, the 3D bin packing problem usually refers to packing a set of cuboid-shaped items $i \in \mathcal{I}$, with sizes s_i^x, s_i^y, s_i^z along x, y, z axes, respectively, into the minimum number of bins with sizes S^x, S^y, S^z, in an axis-aligned fashion. The traditional 3D-BPP assumes that all the items to be packed are known a priori (Martello et al., 2000), which is also called *offline* BPP. The problem is known to be strongly NP-hard (De Castro Silva et al., 2003). However, in many real-world application scenarios, e.g., logistics or warehousing (Wang & Hauser, 2019a), the upcoming items cannot be fully observed; only the current item to be packed is observable. Packing items without the knowledge of all upcoming items is referred to as *online* BPP (Seiden, 2002).

Due to its obvious practical usefulness, online 3D-BPP has received increasing attention recently. Given the limited knowledge, the problem cannot be solved by usual search-based methods. Different from offline 3D-BPP where the items can be placed in an arbitrary order, the placement of online BPP must follow the coming order of the items, which imposes additional constraints and difficulty. Online 3D-BPP is usually solved with either heuristic methods (Ha et al., 2017) or learning-based ones (Zhao et al., 2021a), with complementary pros and cons. Heuristic methods are generally not limited by the size of action space, but they find difficulties in handling complex practical constraints such as packing stability or specific packing preferences. Learning-based approaches usually perform better than heuristic methods, especially under various complicated constraints. However, the learning is hard to converge with a large action space, which has greatly limited the applicability of learning-based methods due to, e.g., limited resolution of spatial discretization (Zhao et al., 2021a).

We propose to enhance learning-based online 3D-BPP towards practical applicability through learning with a novel hierarchical representation – *packing configuration tree (PCT)*. PCT is a dynamically growing tree where the internal nodes describe the space configurations of packed items and leaf nodes the packable placements of the current item. PCT is a full-fledged description of the state and action space of bin packing which can support packing policy learning based on deep reinforcement learning (DRL). We extract state feature from PCT using graph attention networks (Velickovic et al., 2018) which encodes the spatial relations of all space configuration nodes. The state feature is

input into the critic and actor networks of the DRL model. The actor network, designed as a pointer mechanism, weighs the leaf nodes and outputs the action (the final placement).

During training, PCT grows under the guidance of heuristics such as *Corner Point* (Martello et al., 2000), *Extreme Point* (Crainic et al., 2008), and *Empty Maximal Space* (Ha et al., 2017). Although PCT is expanded with heuristic rules, confining the solution space to what the heuristics could explore, our DRL model learns a discriminant fitness function (the critic network) for candidate solutions, resulting in an effective and robust packing policy exceeding the heuristic methods. Furthermore, the size of the packing action space is proportional to the number of leaf nodes, making the DRL model easy to train and well-performing even with continuous solution space. Through extensive evaluation, we demonstrate that our method outperforms all existing online 3D-BPP methods and is versatile in terms of incorporating various practical constraints such as isle friendliness and load balancing (Gzara et al., 2020). To the best of our knowledge, we are the first ones to deploy the learning-based method on solving online 3D-BPP with continuous solution space successfully.

2 RELATED WORK

Offline 3D-BPP   The early interest of 3D-BPP mainly focused on its offline setting. Offline 3D-BPP assumes that all items are known as a priori and can be placed in an arbitrary order. Martello et al. (2000) first solved this problem with an exact branch-and-bound approach. Limited by exponential worst-case complexity of exact approaches, lots of heuristic and meta-heuristic algorithms are proposed to get an approximate solution quickly, such as guided local search (Faroe et al., 2003), tabu search (Crainic et al., 2009), and hybrid genetic algorithm (Kang et al., 2012). Hu et al. (2017) decompose the offline 3D-BPP into packing order decisions and online placement decisions. The packing order is optimized with an end-to-end DRL agent and the online placement policy is a hand-designed heuristic. This two-step fashion is widely accepted and followed by Duan et al. (2019), Hu et al. (2020), and Zhang et al. (2021).

Heuristics for Online 3D-BPP   Although offline 3D-BPP has been well studied, their search-based approaches cannot be directly transferred to the online setting. Instead, lots of heuristic methods have been proposed to solve this problem. For reasons of simplicity and good performance, the deep-bottom-left (DBL) heuristic (Karabulut & Inceoglu, 2004) has long been a favorite. Ha et al. (2017) sort the empty spaces with this DBL order and place the current item into the first fit one. Wang & Hauser (2019b) propose a Heightmap-Minimization method to minimizes the volume increase of the packed items as observed from the loading direction. Hu et al. (2020) optimize the empty spaces available for the packing future with a Maximize-Accessible-Convex-Space method.

DRL for Online 3D-BPP   The heuristic methods are intuitive to implement and can be easily applied to various scenarios. However, the price of good flexibility is that all these methods perform mediocrely, especially for online 3D-BPP instances with specific constraints. Designing new heuristics for specific classes of 3D-BPP is heavy work since this problem has an NP-hard solution space, many situations need to be premeditated by trial and error. Substantial domain knowledge is also necessary to ensure the safety and reliability of the algorithm. To automatically generate a policy that works well on specified online 3D-BPP instances, Zhao et al. (2021a) have first employed the DRL method on solving this problem, however, their method only works in a small discrete coordinate space. Despite its limitations, this work is soon followed by Hong et al. (2020) and Zhao et al. (2021b) for logistics robot implementation. Zhang et al. (2021) adopt a similar online placement policy for offline needs referring to Hu et al. (2017). All these learning-based methods only work in a limited-scale grid world, which reduces their practical applicability.

Practical Constraints   The majority of literature for 3D-BPP (Martello et al., 2000) only considers the basic non-overlapping constraint 1 and containment constraint 2:

$$p_i^d + s_i^d \leq p_j^d + S^d(1 - e_{ij}^d) \quad i \neq j, i, j \in \mathcal{I}, d \in \{x, y, z\} \tag{1}$$

$$0 \leq p_i^d \leq S^d - s_i^d \quad i \in \mathcal{I}, d \in \{x, y, z\} \tag{2}$$

Where p means the front-left-bottom coordinate of item i and d the coordinate axes, e_{ij} takes value 1 otherwise 0 if item i precedes item j along d. The algorithms for 3D-BPP are of limited practical

Figure 1: PCT expansion, illustrated using a 2D (xoz) example for simplicity (See Appendix B for 3D version). A newly added item introduces a series of empty spaces and new potential placements are generated, e.g., the left-bottom corner of the empty space. This process can be seen as a placement node being replaced by the current item node and new potential placement nodes formed.

applicability if no even basic real-world constraints, e.g., stability (Ramos et al., 2016), are considered. Zhao et al. (2021b) propose a fast stability calculation method for DRL training and test their learned policy with real logistics boxes. The flaw of their work is the heightmap (frontier) state representation like Zhang et al. (2021) is still used, while the underlying interactions that exist in packed items are missed. The unavailability of underlying spatial information makes their problem a Partially Observable Markov Decision Problem (Spaan, 2012) which is not conducive to DRL training and limits the performance on 3D-BPP instances with more complex practical constraints, like isle friendliness and load balancing (Gzara et al., 2020).

3 METHOD

In this section, we first introduce our PCT concept in Section 3.1 for describing the online packing process. The parameterization of both the tree structure and leaf node selection policy is introduced in Section 3.2 and Section 3.3 respectively. In Section 3.4, we formulate online 3D-BPP as Markov Decision Process based on the PCT, followed by the description of the training method.

3.1 PACKING CONFIGURATION TREE

When a rectangular item n_t is added to a given packing with placement (p_n^x, p_n^y, p_n^z) at time step t, it introduces a series of new potential placements where future items can be accommodated, as illustrated in Figure 1. This process can be seen as a placement node being replaced by an item node, and new potential placement nodes are generated as children. As the packing time step t goes on, these nodes are iteratively updated and a dynamic *packing configuration tree* is formed, denoted as $\mathcal{T}$. The internal node set $\mathbf{B}_t \in \mathcal{T}_t$ represents the space configurations of packed items, and the leaf node set $\mathbf{L}_t \in \mathcal{T}_t$ the packable potential placements. When there is no packable leaf node that makes n_t satisfy the constraints of placement, the packing episode ends.

Traditional 3D-BPP literature only cares about the remaining placements for accommodating the current item n_t, their packing policies can be written as $\pi(\mathbf{L}_t | \mathbf{L}_t, n_t)$. If we want to promote this problem for practical demands, 3D-BPP needs to satisfy more complex practical constraints which also act on $\mathbf{B}_t$. Take packing stability for instance, a newly added item has possibly force and torque influence on the whole item set $\mathbf{B}_t$ (Ramos et al., 2016). The addition of n_t should make $\mathbf{B}_t$ a more stable spatial distribution so that more items can be added in the future. Therefore, our packing policy over $\mathbf{L}_t$ is defined as $\pi(\mathbf{L}_t | \mathcal{T}_t, n_t)$, which means selecting a leaf node from current PCT $\mathcal{T}_t$. For online packing, we hope to find the best leaf node selection policy to expand the PCT with more relaxed constraints and allow more future items appended.

Leaf Node Expansion Schemes The performance of online 3D-BPP policies is strongly influenced by the choice of leaf node expansion schemes – which incrementally calculate new potential placements introduced by the just placed item n_t. A good expansion scheme should reduce the number of solutions to be explored while not missing too many feasible packings. Meanwhile, polynomially computability is also expected. Designing such a scheme from scratch is non-trivial.

Fortunately, several placement rules independent from particular packing problems have been proposed, such as *Corner Point* (Martello et al., 2000), *Extreme Point* (Crainic et al., 2008), and *Empty Maximal Space* (Ha et al., 2017). We extend these schemes which have proven to be accurate and efficient to our PCT expansion. The performance of learned policies will be reported in Section 4.1.

3.2 TREE REPRESENTATION

Given the bin configuration $\mathcal{T}_t$ and current item n_t, the packing policy can be parameterized as $\pi(\mathbf{L}_t|\mathcal{T}_t, n_t)$. The tuple $(\mathcal{T}_t, n_t)$ can be treated as a graph and encoded by Graph Neural Networks (GNNs) (Gori et al., 2005). Specifically, the PCT keeps growing with time step t and cannot be embedded by spectral-based approaches, like Bruna et al. (2014), which require a fixed graph structure. We adopt non-spectral Graph Attention Networks (GATs) (Velickovic et al., 2018), which requires no priori on graph structures.

The raw space configuration nodes $\mathbf{B}_t, \mathbf{L}_t, n_t$ are presented by descriptors in different formats. We use three independent node-wise Multi-Layer Perceptron (MLP) blocks to project these heterogeneous descriptors into the homogeneous node features: $\hat{\mathbf{h}} = \{\phi_{\theta_B}(\mathbf{B}_t), \phi_{\theta_L}(\mathbf{L}_t), \phi_{\theta_n}(n_t)\} \in \mathbb{R}^{d_h \times N}$, d_h is the dimension of each node feature and ϕ_θ is an MLP block with its parameters θ. The feature number N should be $|\mathbf{B}_t| + |\mathbf{L}_t| + 1$, which is a dependent variable related to t. The GAT layer is used to transform $\hat{\mathbf{h}}$ into high-level node features. The Scaled Dot-Product Attention (Vaswani et al., 2017) is applied to each node for calculating the relation weight of one node to another. These relation weights are normalized and used to compute the linear combination of features $\hat{\mathbf{h}}$. The feature of node i embedded by the GAT layer can be represented as:

$$\text{GAT}(\hat{h}_i) = W^O \sum_{j=1}^{N} softmax\left(\frac{(W^Q \hat{h}_i)^T W^K \hat{h}_j}{\sqrt{d_k}}\right) W^V \hat{h}_j \tag{3}$$

Where $W^Q \in \mathbb{R}^{d_k \times d_h}$, $W^K \in \mathbb{R}^{d_k \times d_h}$, $W^V \in \mathbb{R}^{d_v \times d_h}$, and $W^O \in \mathbb{R}^{d_h \times d_v}$ are projection matrices, d_k and d_v are dimensions of projected features. The softmax operation normalizes the relation weight between node i and node j. The initial feature $\hat{\mathbf{h}}$ is embedded by a GAT layer and the skip-connection operation (Vaswani et al., 2017) is followed to get the final output features $\mathbf{h}$:

$$\mathbf{h}' = \hat{\mathbf{h}} + \text{GAT}(\hat{\mathbf{h}}) \quad \mathbf{h} = \mathbf{h}' + \phi_{FF}(\mathbf{h}') \tag{4}$$

Where ϕ_{FF} is a node-wise Feed-Forward MLP with output dimension d_h and $\mathbf{h}'$ is an intermediate variable. Equation 4 can be seen as an independent block and be repeated multiple times with different parameters. However, we find additional parameters require more data for our policy approximation and cannot help the final performances, so we only executed Equation 4 once. For the same consideration, we don't extend GAT to employ the multi-head attention mechanism (Vaswani et al., 2017) and we set $d_v = d_k$. More details are provided in Appendix A.

3.3 LEAF NODE SELECTION

Given the node features $\mathbf{h}$, we need to decide the leaf node indices for accommodating the current item n_t. Since the leaf nodes vary as the PCT keeps growing over time step t, we use a pointer mechanism (Vinyals et al., 2015) to select a leaf node from input $\mathbf{L}_t$, which has varying lengths. We still adopt Scaled Dot-Product Attention for calculating the pointers, the global context feature $\bar{h}$ is aggregated by a mean operation on $\mathbf{h}$: $\bar{h} = \frac{1}{N}\sum_{i=1}^{N} h_i$. The global feature $\bar{h}$ is projected to a query q by matrix $W^q \in \mathbb{R}^{d_k \times d_h}$ and the leaf node features $\mathbf{h_L}$ are utilized to calculate a set of keys $k_{\mathbf{L}}$ by $W^k \in \mathbb{R}^{d_k \times d_h}$. The compatibility $\mathbf{u_L}$ of the query with all keys are computed by:

$$q = W^q \bar{h} \quad k_i = W^k h_i \quad u_i = \frac{q^T k_i}{\sqrt{d_k}} \tag{5}$$

Here h_i only comes from $\mathbf{h_L}$. The compatibility vector $\mathbf{u_L} \in \mathbb{R}^{|\mathbf{L}_t|}$ represents the leaf node selection logits. The probability distribution over the PCT leaf node set $\mathbf{L}_t$ is:

$$\pi_\theta(\mathbf{L}_t|\mathcal{T}_t, n_t) = softmax\left(c_{clip} \cdot \tanh(u_{\mathbf{L}})\right) \tag{6}$$

Following Bello et al. (2017), the compatibility logits are clipped with tanh, where the range is controlled by hyperparameter c_{clip}, and finally normalized by a softmax operation.

3.4 Markov Decision Process Formulation

The online 3D-BPP decision depends only upon the tuple $(\mathcal{T}_t, n_t)$ and can be formulated as Markov Decision Process, which is constructed with state $\mathcal{S}$, action $\mathcal{A}$, transition $\mathcal{P}$, and reward R. We solve this MDP with an end-to-end DRL agent. The MDP model is formulated as follows.

State The state s_t at time step t is represented as $s_t = (\mathcal{T}_t, n_t)$, where $\mathcal{T}_t$ consists of the internal node set $\mathbf{B}_t$ and the leaf node set $\mathbf{L}_t$. Each internal node $b \in \mathbf{B}_t$ is a spatial configuration of sizes (s_b^x, s_b^y, s_b^z) and coordinates (p_b^x, p_b^y, p_b^z) corresponding to a packed item. The current item n_t is a size tuple (s_n^x, s_n^y, s_n^z). Extra properties will be appended to b and n_t for specific packing preferences, such as density, item category, etc. The descriptor for leaf node $l \in \mathbf{L}_t$ is a placement vector of sizes (s_o^x, s_o^y, s_o^z) and position coordinates (p^x, p^y, p^z), where (s_o^x, s_o^y, s_o^z) indicates the sizes of n_t along each dimension after an axis-align orientation o. Only the packable leaf nodes which satisfy placement constraints are provided. Without loss of generality, we stipulate a vertical top-down loading direction in our problem and p^z can be saved once (p^x, p^y) is determined.

Action The action $a_t \in \mathcal{A}$ is an eligible index of selected leaf node l, denoted as $a_t = index(l)$. The action space $\mathcal{A}$ has the same size as $\mathbf{L}_t$. A surge of learning-based methods (Zhao et al., 2021a) directly learns their policy on a grid world through discretizing the full coordinate space, where $|\mathcal{A}|$ grows explosively with the accuracy of the discretization. Different from these existing works, our action space solely depends on the choice of leaf node expansion scheme and the packed items $\mathbf{B}_t$, which will not respond to discretization accuracy. Therefore, our method can also be used to solve the online 3D-BPP with continuous solution space. We also find that even if only a intercepted subset $\mathbf{L}_{sub} \in \mathbf{L}_t$ is provided, our method can still maintain a good performance.

Transition The transition $\mathcal{P}(s_{t+1}|s_t)$ is jointly determined by the current policy π and the distribution of items being sampled. Our online sequence is generated on-the-fly from an item set $\mathcal{I}$ in a uniform distribution. The generalization performance of our method on disturbed item sampling distributions is discussed in Section 4.4.

Reward Our reward function R is defined as $r_t = c_r \cdot w_t$ once n_t is inserted into PCT as an internal node successfully, otherwise, $r_t = 0$ and the packing episode ends. Here c_r is a constant and w_t is the weight of n_t. The choice of w_t depends on the customized needs. For simplicity and clarity, unless otherwise noted, we set w_t as the volume occupancy v_t of n_t, where $v_t = s_n^x \cdot s_n^y \cdot s_n^z$.

Training Method A DRL agent seeks for a policy π to maximize the accumulated discounted reward: $J(\pi) = E_{\tau \sim \pi}[\sum_{t=0}^{\infty} \gamma^t R(s_t, a_t)]$. Where $\gamma \in [0, 1]$ is the discount factor, and $\tau = (s_0, a_0, s_1, \ldots)$ is a sampled trajectory. Our DRL agent is trained with Actor Critic using Kronecker-Factored Trust Region (ACKTR) (Wu et al., 2017), which has proven to perform surprisingly well on online packing problems (Zhao et al., 2021a). The actor weighs the leaf nodes $\mathbf{L}_t$ and outputs the policy distribution $\pi_\theta(\mathbf{L}_t|\mathcal{T}_t, n_t)$. The critic maps the global context $\bar{h}$ into a scalar to predict how much accumulated discount reward can agent get from t on, which is a discriminant fitness function for candidate solutions. The action a_t is sampled on $\pi_\theta(\mathbf{L}_t|\mathcal{T}_t, n_t)$ for training while taking its argmax for the test.

ACKTR runs multiple parallel processes for gathering on-policy training samples. The node number N of each sample varies with the time step t and the packing sequences of each process. For batch calculation, we fullfill PCT to a fixed length with dummy nodes, as illustrated by Figure 2 (a). These added nodes are eliminated by *masked attention* (Velickovic et al., 2018) during the feature calculation of GAT. The aggregation of $\mathbf{h}$ only happens on the eligible nodes. For preserving node spatial relations, state s_t is embedded by GAT as a fully connected graph as Figure 2 (b), without any inner mask operation. More implementation details are provided in Appendix A.

Figure 2: Batch calculation for PCT.

4 EXPERIMENTS

In this section, we first explore the performance of our PCT model combined with different leaf node expansion schemes. Then we will demonstrate the benefits of the PCT structure: better node spatial relation representations as well as more flexible action space. Finally, we test the generalization performance of our method on disturbed item sampling distributions and extend it to other online 3D-BPP with complex practical constraints.

Baselines Although there are very few online packing implementations available through public channels, we still do our best to collect or reproduce various online 3D-BPP algorithms, both heuristic and learning-based methods, from potentially relevant literature. We help the heuristic methods to make a pre-judgment of placement constraints, e.g. stability, in case of premature downtime. The learning-based agents are trained until there are no significant performance gains. Although both Zhao et al. (2021b) and Zhao et al. (2021a) are learning-based methods recently proposed, we only compare with the former since it is the upgrade of the latter. We also compare with the reported results of Zhang et al. (2021) under the same setting. All algorithms are implemented in Python and tested on 2000 instances with a desktop computer equipped with an Intel Xeon Gold 5117 CPU and a single Nvidia GeForce TITAN V GPU. The source code of our method along with all gathered baselines will be published after acceptance for domain development.

Datasets Some baselines like Karabulut & Inceoglu (2004) need to traverse the entire coordinate space to find the optimal solution, and the running cost explodes as the spatial discretization accuracy increases. To ensure that all algorithms are runnable within a reasonable period, we use the discrete dataset proposed by Zhao et al. (2021a) without special declaration. The bin sizes S^d are set to 10 with $d \in \{x, y, z\}$ and the item sizes $s^d \in \mathbb{Z}^+$ are not greater than $S^d/2$ to avoid over-simplified scenarios. Our performance on a more complex continuous dataset will be reported in Section 4.3. Considering that there are many variants of 3D-BPP, we set up three most representative instances:

$Setting\ 1$: Following Zhao et al. (2021b), the stability of the $\mathbf{B}_t$ is checked when n_t is placed. Only two horizontal orientations ($|o| = 2$) are permitted for robot manipulation convenience.

$Setting\ 2$: Following Martello et al. (2000), item n_t only needs to satisfy Constraint 1 and 2. Arbitrary orientation ($|o| = 6$) is allowed here. This is the most common setting in 3D-BPP literature.

$Setting\ 3$: Inherited from $Setting\ 1$, each item n_t has an additional density property $\rho \in (0, 1]$. This property information is appended into the descriptors of $\mathbf{B}_t$ and n_t.

4.1 PERFORMANCE OF PCT POLICIES

We first demonstrate the performance of our learned policies combined with different leaf node expansion schemes. Three existing schemes which have proven to be both efficient and effective are adopted here: Corner Point (CP), Extreme Point (EP), and Empty Maximal Space (EMS). These schemes are all related to boundary points of a packed item along d axes. We combine the start/end points of n_t with the boundary points of $b \in \mathbf{B}_t$ to get the superset, namely *Event Points* (EV) (see Appendix B). We extend these schemes to our PCT model. Although the number of leaf nodes generated by these schemes is within a reasonable range, we only randomly intercept a subset $\mathbf{L}_{sub_t}$ from $\mathbf{L}_t$ if $|\mathbf{L}_t|$ exceeds a certain length, for saving computing resources. The interception length is a constant during training and determined by a grid search (GS) during the test. More implementation details are provided in Appendix A. The performance of these designs against the baselines is summarized in Table 1.

Although PCT grows under the guidance of heuristics, the combinations of PCT with EMS and EV schemes still learn effective and robust policies outperforming all baselines by a large margin regarding all settings. Note that the closer the space utilization is to 1, the more difficult the online 3D-BPP is. It is interesting to see that policies learned on EMS and EV even exceeded the performance of the full coordinate space (FC), which demonstrates that a good leaf node expansion scheme makes the DRL agent easy to train. To prove that the interception of $\mathbf{L}_t$ will not harm the final performance, we train an agent with a full leaf node set derived from the EV scheme (EVF) and the test performance are slightly worse than the intercepted case. We guess that the interception keeps the final performance may be caused by two reasons. First, the solution for 3D-BPP is not unique and a sub-optimal solution may exist even in the intercepted leaf node set $\mathbf{L}_{sub}$. In addition, the randomly chosen leaf nodes force the agent to make a new attempt in case that the policy π falls into the local

Table 1: Performance comparison. Uti. and Num. means the average space utilization and the average number of packed items separately. Var. ($\times 10^{-3}$) is the variance of Uti. and Gap is with respect to the best Uti. across all methods. $Random$ policy picks a packable palcement from full spatial space randomly and DBL is a heuristic method proposed by Karabulut & Inceoglu (2004).

	Method	Setting 1				Setting 2				Setting 3			
		Uti.	Var.	Num.	Gap	Uti.	Var.	Num.	Gap	Uti.	Var.	Num.	Gap
Heuristic	*Random*	26.1%	7.0	10.7	65.6%	27.3%	7.0	11.2	68.3%	26.4%	7.5	10.8	65.1%
	DBL	41.5%	9.6	16.4	45.4%	46.4%	8.5	18.2	46.0%	39.3%	9.6	15.9	48.1%
	Ha et al.	52.1%	20.1	20.6	31.4%	59.9%	10.4	23.8	30.3%	51.9%	20.2	20.6	31.4%
	Hu et al. (2017)	52.5%	12.2	20.8	30.9%	65.0%	6.1	25.6	24.4%	52.4%	12.2	20.7	30.8%
	Wang & Hauser	37.9%	10.0	15.1	50.1%	43.2%	9.0	17.1	49.8%	37.9%	10.0	15.1	49.9%
	Zhao et al.	49.0%	10.8	19.6	35.5%	56.7%	6.6	22.6	34.1%	48.9%	10.7	19.5	35.4%
	Hu et al. (2020)	57.7%	10.5	22.6	24.1%	50.8%	8.8	20.1	40.9%	57.7%	10.6	22.6	23.8%
Learning-based	Zhao et al.	70.9%	6.2	27.5	6.7%	70.3%	4.3	27.4	18.3%	59.6%	5.4	23.1	21.3%
	PCT & CP	69.4%	5.4	26.7	8.7%	81.8%	2.0	31.3	4.9%	69.5%	5.4	26.7	8.2%
	PCT & EP	71.9%	6.6	27.8	5.4%	78.1%	3.8	30.3	9.2%	72.2%	5.8	27.9	4.6%
	PCT & FC	72.4%	4.7	28.0	4.7%	76.9%	3.3	29.7	10.6%	69.8%	5.3	27.1	7.8%
	PCT & EMS	75.8%	4.4	29.3	0.3%	**86.0%**	**1.9**	**33.0**	**0.0%**	75.5%	4.7	29.2	0.3%
	PCT & EV	**76.0%**	**4.2**	**29.4**	**0.0%**	85.3%	2.1	32.8	0.8%	**75.7%**	**4.6**	**29.2**	**0.0%**
	PCT & EVF	75.7%	4.8	29.2	0.4%	80.5%	2.9	31.0	6.4%	73.5%	4.6	28.4	2.9%
	PCT & EV/GS	75.8%	4.7	29.2	0.3%	84.8%	2.1	32.6	1.4%	75.5%	4.8	29.1	0.3%

optimum. We remove GS from EV cases to prove its effectiveness. The performance of Zhao et al. (2021b) deteriorates quickly in $setting$ 2 and $setting$ 3 due to the multiplying orientation space and insufficient state representation separately. The visual results can be found in Appendix C.

We also repeat the same experiment as Zhang et al. (2021), which pack items sampled from a pre-defined item set $|\mathcal{I}| = 64$ in $setting$ 2. While Zhang et al. (2021) packs on average 15.6 items and achieves 67.0% space utilization, our method packs 19.7 items with a space utilization of 83.0%.

4.2 BENEFITS OF TREE PRESENTATION

Here we verify that the PCT representation does help the online 3D-BPP tasks. For this, we embed each space configuration node independently like PointNet (Qi et al., 2017) to prove the node spatial relations help the final performance. We also deconstruct the tree structure into node sequences and embed them with Ptr-Net (Vinyals et al., 2015), which selects a member from serialized inputs, for indicating that the graph embedding fashion fits our tasks well. We have verified that an appropriate choice of $\mathbf{L}_t$ makes DRL agent easy to train, then we remove the internal node set $\mathbf{B}_t$ from $\mathcal{T}_t$, along with its spatial relations with other nodes, to prove $\mathbf{B}_t$ is also a necessary part. We choose EV as the leaf node expansion scheme here. The comparison results are summarized in Table 2.

Table 2: A graph embedding for complete PCT helps the final performance.

Method	Setting 1				Setting 2				Setting 3			
	Uti.	Var.	Num.	Gap	Uti.	Var.	Num.	Gap	Uti.	Var.	Num.	Gap
PointNet	69.2%	6.7	26.9	8.9%	78.9%	3.2	30.5	7.5%	71.5%	5.3	27.7	5.5%
Ptr-Net	64.1%	10.0	25.1	15.7%	77.5%	4.1	30.1	9.1%	63.5%	7.9	24.8	16.1%
$\mathcal{T}/\mathbf{B}$	70.9%	5.9	27.5	6.7%	84.1%	2.6	32.3	1.4%	70.6%	5.3	27.4	6.7%
$\mathcal{T}$	**76.0%**	**4.2**	**29.4**	**0.0%**	**85.3%**	**2.1**	**32.8**	**0.0%**	**75.7%**	**4.6**	**29.2**	**0.0%**

If we ignore the spatial relations between the PCT nodes or only treat it as a flattened sequence, the performance of the learned policies will be severely degraded. Missing internal node set $\mathbf{B}_t$ drops the performance on $setting$ 1 and $setting$ 3. This also confirms that PCT representation is essential for online 3D-BPP of practical needs.

4.3 PERFORMANCE ON CONTINUOUS DATASET

The most concerning issue about online 3D-BPP is their solution space limit. Given that most learning-based methods can only work in a limited discrete coordinate space, we directly test our method in a continuous bin with sizes $S^d = 1$ to prove our superiority. Due to the lack of public

datasets for online 3D-BPP issues, we generate item sizes through a uniform distribution $s^d \sim U(a, S^d/2)$, a is set to 0.1 in case that endless items are generated. Specifically, for the 3D-BPP instances where stability is considered, the diversity of item size s^z needs to be controlled. If all subsets of $\mathbf{B}_t$ meet:

$$\sum_{i \in \mathbf{B}_{sub1}} s_i^z \neq \sum_{i \in \mathbf{B}_{sub2}} s_i^z \quad \mathbf{B}_{sub1}, \mathbf{B}_{sub2} \in \mathbf{B}_t \tag{7}$$

This means any packed items cannot form a new surface for providing support in the direction of gravity and the available packing areas shrinks. Excessive diversity of s^z will degenerate 3D-BPP into 1D-BPP as shown on the right. To prevent this degradation from leading to the underutilization of the bins, we sample s^z from a finite set $\{0.1, 0.2, \ldots, 0.5\}$ on $setting\,1$ and $setting\,3$. The test results on these data distributions are summarized in Table 3.

Table 3: Online 3D-BPP with continuous solution space.

	Method	Setting 1				Setting 2				Setting 3			
		Uti.	Var.	Num.	Gap	Uti.	Var.	Num.	Gap	Uti.	Var.	Num.	Gap
Heu.	Zhao et al.	40.9%	7.4	16.1	37.5%	45.3%	5.2	17.8	31.7%	40.9%	7.3	16.1	38.6%
	Ha et al.	43.9%	14.2	17.2	32.9%	46.1%	6.8	18.1	30.5%	43.9%	14.2	17.2	34.1%
	Hu et al.	48.3%	12.1	18.7	26.1%	58.7%	4.6	22.8	11.5%	48.4%	12.2	18.8	27.3%
DRL	GD	5.6%	–	2.2	91.4%	7.5%	–	2.9	88.7%	5.2%	–	2.1	92.2%
	PCT & EMS	65.3%	4.3	24.9	0.2%	**66.3%**	**2.3**	**27.0**	**0.0%**	**66.6%**	3.3	25.3	**0.0%**
	PCT & EV	**65.4%**	**3.3**	**25.0**	**0.0%**	65.0%	2.6	26.4	2.0%	65.8%	3.6	25.0	2.7%

We find that some heuristic methods, like Ha et al. (2017), also have the potential to work in the continuous domain. We have improved these methods as our baselines. Another intuitive approach for solving continuous online 3D-BPP is driving a DRL agent to sample action from a gaussian distribution (GD) and output continuous coordinates directly. As shown in Table 3, our method still performs the best among all candidates. The DRL agent which outputs continuous actions directly cannot even converge and their variance is not considered. To the best of our knowledge, we are the first ones to deploy the learning-based method on solving online 3D-BPP with continuous solution space successfully.

4.4 GENERALIZATION ON DISTURBED DISTRIBUTIONS

The generalization ability of learning-based algorithms has always been a concern. Here we will demonstrate that our algorithm has a good generalization performance on disturbed item sampling distributions. For each item $i \in \mathcal{I}$, we add a random disturbance δ_i on its original sample probability p_i, e.g., $p_i = p_i \cdot (1 \pm \delta)$. We normalize p_i as the final item sampling distribution. We test different ranges of δ_i and the results are summarized in Table 4.

Table 4: Transfer the best-performing policies directly to the disturbed item sampling distributions. Dif. means how much the test performance drops from the undisturbed case ($\delta_i = 0$).

Disturbance	Setting 1				Setting 2				Setting 3			
	Uti.	Var.	Num.	Dif.	Uti.	Var.	Num.	Dif.	Uti.	Var.	Num.	Dif.
$\delta_i = 0$	76.0%	4.2	29.4	0.0%	86.0%	1.9	33.0	0.0%	75.7%	4.6	29.2	0.0%
$\delta_i \in (0, 10\%]$	75.5%	4.5	29.0	0.7%	85.7%	2.2	32.8	0.3%	75.4%	4.9	29.0	0.4%
$\delta_i \in (0, 20\%]$	75.6%	4.6	29.1	0.5%	85.7%	2.1	32.8	0.3%	75.3%	4.5	29.0	0.5%
$\delta_i \in (0, 30\%]$	75.9%	4.0	29.2	0.1%	85.7%	2.0	32.8	0.3%	75.6%	4.2	29.1	0.1%
$\delta_i \in (0, 40\%]$	75.5%	4.5	29.0	0.7%	85.6%	2.1	32.8	0.5%	75.6%	4.8	29.3	0.1%
$\delta_i \in (0, 50\%]$	75.6%	4.5	28.9	0.5%	85.9%	2.1	32.7	0.1%	75.8%	4.3	29.2	−0.1%
$\delta_i \in (0, 60\%]$	75.5%	4.3	28.9	0.7%	85.8%	2.1	32.8	0.2%	75.5%	4.8	28.9	0.3%
$\delta_i \in (0, 70\%]$	75.9%	4.2	29.2	0.1%	85.7%	2.2	32.8	0.3%	75.4%	4.7	28.8	0.4%
$\delta_i \in (0, 80\%]$	75.7%	4.5	29.2	0.4%	85.6%	2.2	32.9	0.5%	75.4%	4.9	29.3	0.4%
$\delta_i \in (0, 90\%]$	75.7%	4.4	29.2	0.4%	85.7%	2.1	32.8	0.3%	75.2%	5.0	29.0	0.7%
$\delta_i \in (0, 100\%]$	75.8%	4.4	29.0	0.3%	85.5%	2.2	32.6	0.6%	75.3%	4.7	29.3	0.5%

Benefits from the efficient guidance of heuristic leaf node expansion schemes, our method maintains its performance under various amplitude disturbances. Our method even behaves well with a strong

disturbance $\delta_i \in (0, 100]$ applied, which means some items may never be sampled by specific distributions. Note that we only consider the generalization on disturbed distributions. If the train-test distributions are totally different, e.g., train on a complete normal distribution and only test on its normalized tail, a more sensible approach for meeting the economic needs is to fine-tune the learned policies based on newly collected real-time data like Shi et al. (2019).

4.5 More Complex Practical Constraints

To further prove that our method fits 3D-BPP with complex constraints well, we give two demonstrations about extending our method to online 3D-BPP with additional practical constraints: isle friendliness and load balancing (Gzara et al., 2020):

3D-BPP with Isle Friendliness Isle friendliness refers to that items belonging to the same category should be packed as closely as possible. The item weight is set as $w_t = max(0, v_t - c \cdot dist(n_t, \mathbf{B}_t))$, c is a constant. The additional object function $dist(n_t, \mathbf{B}_t)$ means the average distance between n_t and the items of the same category in $\mathbf{B}_t$. The additional category information is appended into the descriptors of $\mathbf{B}_t$ and n_t. Four item categories are tested here.

3D-BPP with Load Balancing Load balancing dictates that the packed items should have an even mass distribution within the bin. The item weight is set as $w_t = max(0, v_t - c \cdot var(n_t, \mathbf{B}_t))$. Object $var(n_t, \mathbf{B}_t)$ is the variance of the mass distribution of the packed items on the bottom of the bin.

Table 5: Online 3D-BPP with practical constraints. Obj. means the task-specific objective score, the smaller the better. $Setting\ 2$ involves no mass property and the load balancing is not considered.

	Method	$Setting\ 1$			$Setting\ 2$			$Setting\ 3$		
		Uti.	Num.	Obj.	Uti.	Num.	Obj.	Uti.	Num.	Obj.
Isle Friendliness	Zhao et al.	58.3%	22.5	4.58	64.2%	24.8	4.67	59.0%	22.8	4.60
	Ours	72.1%	29.0	4.44	85.2%	32.8	2.69	74.6%	28.8	4.45
Load balancing	Zhao et al.	60.3%	23.3	88.0		-		61.1%	23.7	30.1
	Ours	73.7%	28.6	40.5		-		74.0%	28.7	20.9

We choose the learning-based method Zhao et al. (2021b) as our baseline since heuristic methods only take space utilization as their objects. The results are summarized in Table 5. Compared with the baseline algorithm, our method better achieves the additional object while taking into account the space utilization as the primary.

5 Discussion

We formulate the online 3D-BPP as a novel hierarchical representation – packing configuration tree. PCT is a full-fledged description of the state and action space of bin packing which makes the DRL agent easy to train and well-performing. We extract state feature from PCT using graph attention networks which encodes the spatial relations of all space configuration nodes. The graph representation of PCT helps the agent with handling online 3D-BPP with complex practical constraints, while the finite leaf nodes prevent the action space from growing explosively. Our method surpasses all the other online 3D-BPP algorithms and is the first learning-based method that solves online 3D-BPP with continuous solution space successfully. Our method performs well even with a strong disturbance applied on the items sampling distributions. We also give demonstrations to prove that our method is versatile in terms of incorporating various practical constraints.

Our method can be treated as a separate decision module and utilized to solve other variants of 3D-BPP issues, such as multi-bin online 3D-BPP, online 3D-BPP with lookahead (Zhao et al., 2021a), online placement decision for offline 3D-BPP (Hu et al., 2017), the logistics robot implementation for online packing (Zhao et al., 2021b), which have been well studied in previous works. For future research, we are extremely interested in applying our method to the more difficult irregular shape packing like Wang & Hauser (2019a), where the sampling costs for training DRL agents are more expensive and the solution space will be far larger. A good strategy for balancing exploration and exploitation for learning agent is eagerly needed in this situation. How to learn an effective leaf node expansion scheme automatically under this setting is also an interesting question.

6 ETHICS STATEMENT

We believe the broader impact of this research is significant. BPP is considered as one of the most needed academic problems due to its wide applicability in our daily lives (Skiena, 1997). Providing a good solution to online 3D-BPP yields direct and profound impacts beyond academia. We note that online packing setups have been already widely deployed in logistics hubs and manufacturing plants. A good online 3D-BPP solution benefits all the downstream operations like package wrapping, transportation, warehousing, and distribution. We also give demonstrations about applying our method to solving online 3D-BPP with various complex practical constraints, the similar idea can also be adopted to meet other customized desires.

7 REPRODUCIBILITY

Our source code is submitted with the supplemental material. All experimental data are well preserved for checking. The source code of our method along with all gathered baselines mentioned above will be published after acceptance for domain development.

REFERENCES

Irwan Bello, Hieu Pham, Quoc V. Le, Mohammad Norouzi, and Samy Bengio. Neural combinatorial optimization with reinforcement learning. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Workshop Track Proceedings*. OpenReview.net, 2017. URL https://openreview.net/forum?id=Bk9mxlSFx.

Joan Bruna, Wojciech Zaremba, Arthur Szlam, and Yann LeCun. Spectral networks and locally connected networks on graphs. In Yoshua Bengio and Yann LeCun (eds.), *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014. URL http://arxiv.org/abs/1312.6203.

Teodor Gabriel Crainic, Guido Perboli, and Roberto Tadei. Extreme point-based heuristics for three-dimensional bin packing. *INFORMS J. Comput.*, 20(3):368–384, 2008. doi: 10.1287/ijoc.1070. 0250. URL https://doi.org/10.1287/ijoc.1070.0250.

Teodor Gabriel Crainic, Guido Perboli, and Roberto Tadei. Ts2pack: A two-level tabu search for the three-dimensional bin packing problem. *Eur. J. Oper. Res.*, 195(3):744–760, 2009. doi: 10. 1016/j.ejor.2007.06.063. URL https://doi.org/10.1016/j.ejor.2007.06.063.

JL De Castro Silva, NY Soma, and N Maculan. A greedy search for the three-dimensional bin packing problem: the packing static stability case. *International Transactions in Operational Research*, 10(2):141–153, 2003.

Lu Duan, Haoyuan Hu, Yu Qian, Yu Gong, Xiaodong Zhang, Jiangwen Wei, and Yinghui Xu. A multi-task selected learning approach for solving 3D flexible bin packing problem. In Edith Elkind, Manuela Veloso, Noa Agmon, and Matthew E. Taylor (eds.), *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems, AAMAS '19, Montreal, QC, Canada, May 13-17, 2019*, pp. 1386–1394. International Foundation for Autonomous Agents and Multiagent Systems, 2019. URL http://dl.acm.org/citation.cfm?id=3331847.

Oluf Faroe, David Pisinger, and Martin Zachariasen. Guided local search for the three-dimensional bin-packing problem. *INFORMS J. Comput.*, 15(3):267–283, 2003. doi: 10.1287/ijoc.15.3.267. 16080. URL https://doi.org/10.1287/ijoc.15.3.267.16080.

M. Gori, G. Monfardini, and F. Scarselli. A new model for learning in graph domains. In *Proceedings. 2005 IEEE International Joint Conference on Neural Networks, 2005.*, volume 2, pp. 729–734 vol. 2, 2005. doi: 10.1109/IJCNN.2005.1555942.

Fatma Gzara, Samir Elhedhli, and Burak C. Yildiz. The pallet loading problem: Three-dimensional bin packing with practical constraints. *Eur. J. Oper. Res.*, 287(3):1062–1074, 2020. doi: 10.1016/ j.ejor.2020.04.053. URL https://doi.org/10.1016/j.ejor.2020.04.053.

Chi Trung Ha, Trung Thanh Nguyen, Lam Thu Bui, and Ran Wang. An online packing heuristic for the three-dimensional container loading problem in dynamic environments and the physical internet. In Giovanni Squillero and Kevin Sim (eds.), *Applications of Evolutionary Computation - 20th European Conference, EvoApplications 2017, Amsterdam, The Netherlands, April 19-21, 2017, Proceedings, Part II*, volume 10200 of *Lecture Notes in Computer Science*, pp. 140–155, 2017. doi: 10.1007/978-3-319-55792-2_10. URL https://doi.org/10.1007/978-3-319-55792-2_10.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1856–1865. PMLR, 2018. URL http://proceedings.mlr.press/v80/haarnoja18b.html.

Young-Dae Hong, Young-Joo Kim, and Ki-Baek Lee. Smart pack: Online autonomous object-packing system using RGB-D sensor data. *Sensors*, 20(16):4448, 2020. doi: 10.3390/s20164448. URL https://doi.org/10.3390/s20164448.

Haoyuan Hu, Xiaodong Zhang, Xiaowei Yan, Longfei Wang, and Yinghui Xu. Solving a new 3D bin packing problem with deep reinforcement learning method. *CoRR*, abs/1708.05930, 2017. URL http://arxiv.org/abs/1708.05930.

Ruizhen Hu, Juzhan Xu, Bin Chen, Minglun Gong, Hao Zhang, and Hui Huang. Tap-net: transport-and-pack using reinforcement learning. *ACM Trans. Graph.*, 39(6):232:1–232:15, 2020. doi: 10.1145/3414685.3417796. URL https://doi.org/10.1145/3414685.3417796.

Kyungdaw Kang, Ilkyeong Moon, and Hongfeng Wang. A hybrid genetic algorithm with a new packing strategy for the three-dimensional bin packing problem. *Appl. Math. Comput.*, 219(3): 1287–1299, 2012. doi: 10.1016/j.amc.2012.07.036. URL https://doi.org/10.1016/j.amc.2012.07.036.

Korhan Karabulut and Mustafa Murat Inceoglu. A hybrid genetic algorithm for packing in 3d with deepest bottom left with fill method. In Tatyana M. Yakhno (ed.), *Advances in Information Systems, Third International Conference, ADVIS 2004, Izmir, Turkey, October 20-22, 2004, Proceedings*, volume 3261 of *Lecture Notes in Computer Science*, pp. 441–450. Springer, 2004. doi: 10.1007/978-3-540-30198-1_45. URL https://doi.org/10.1007/978-3-540-30198-1_45.

Silvano Martello, David Pisinger, and Daniele Vigo. The three-dimensional bin packing problem. *Oper. Res.*, 48(2):256–267, 2000. doi: 10.1287/opre.48.2.256.12386. URL https://doi.org/10.1287/opre.48.2.256.12386.

James Martens and Roger B. Grosse. Optimizing neural networks with kronecker-factored approximate curvature. In Francis R. Bach and David M. Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, volume 37 of *JMLR Workshop and Conference Proceedings*, pp. 2408–2417. JMLR.org, 2015. URL http://proceedings.mlr.press/v37/martens15.html.

Charles Ruizhongtai Qi, Hao Su, Kaichun Mo, and Leonidas J. Guibas. Pointnet: Deep learning on point sets for 3D classification and segmentation. In *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, pp. 77–85. IEEE Computer Society, 2017. doi: 10.1109/CVPR.2017.16. URL https://doi.org/10.1109/CVPR.2017.16.

António Galrão Ramos, José Fernando Oliveira, and Manuel Pereira Lopes. A physical packing sequence algorithm for the container loading problem with static mechanical equilibrium conditions. *Int. Trans. Oper. Res.*, 23(1-2):215–238, 2016. doi: 10.1111/itor.12124. URL https://doi.org/10.1111/itor.12124.

Steven S. Seiden. On the online bin packing problem. *J. ACM*, 49(5):640–671, 2002. doi: 10.1145/585265.585269. URL https://doi.org/10.1145/585265.585269.

Jing-Cheng Shi, Yang Yu, Qing Da, Shi-Yong Chen, and Anxiang Zeng. Virtual-taobao: Virtual-izing real-world online retail environment for reinforcement learning. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*, pp. 4902–4909. AAAI Press, 2019. doi: 10.1609/aaai.v33i01.33014902. URL https://doi.org/10.1609/aaai.v33i01.33014902.

Steven S Skiena. The stony brook algorithm repository. http://www.cs.sunysb.edu/algorith/implement/nauty/implement.shtml, 1997.

Matthijs TJ Spaan. Partially observable markov decision processes. In *Reinforcement Learning*, pp. 387–414. Springer, 2012.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5998–6008, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html.

Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=rJXMpikCZ.

Oriol Vinyals, Meire Fortunato, and Navdeep Jaitly. Pointer networks. In Corinna Cortes, Neil D. Lawrence, Daniel D. Lee, Masashi Sugiyama, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada*, pp. 2692–2700, 2015. URL https://proceedings.neurips.cc/paper/2015/hash/29921001f2f04bd3baee84a12e98098f-Abstract.html.

Fan Wang and Kris Hauser. Robot packing with known items and nondeterministic arrival order. In Antonio Bicchi, Hadas Kress-Gazit, and Seth Hutchinson (eds.), *Robotics: Science and Systems XV, University of Freiburg, Freiburg im Breisgau, Germany, June 22-26, 2019*, 2019a. doi: 10.15607/RSS.2019.XV.035. URL https://doi.org/10.15607/RSS.2019.XV.035.

Fan Wang and Kris Hauser. Stable bin packing of non-convex 3D objects with a robot manipulator. In *International Conference on Robotics and Automation, ICRA 2019, Montreal, QC, Canada, May 20-24, 2019*, pp. 8698–8704. IEEE, 2019b. doi: 10.1109/ICRA.2019.8794049. URL https://doi.org/10.1109/ICRA.2019.8794049.

Yuhuai Wu, Elman Mansimov, Roger B. Grosse, Shun Liao, and Jimmy Ba. Scalable trust-region method for deep reinforcement learning using kronecker-factored approximation. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5279–5288, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/361440528766bbaaaa1901845cf4152b-Abstract.html.

Jingwei Zhang, Bin Zi, and Xiaoyu Ge. Attend2pack: Bin packing through deep reinforcement learning with attention. *CoRR*, abs/2107.04333, 2021. URL https://arxiv.org/abs/2107.04333.

Hang Zhao, Qijin She, Chenyang Zhu, Yin Yang, and Kai Xu. Online 3D bin packing with constrained deep reinforcement learning. In *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Virtual Event, February 2-9, 2021*, pp. 741–749. AAAI Press, 2021a. URL https://ojs.aaai.org/index.php/AAAI/article/view/16155.

Hang Zhao, Chenyang Zhu, Xin Xu, Hui Huang, and Kai Xu. Learning practically feasible policies for online 3D bin packing. *CoRR*, abs/2108.13680, 2021b. URL https://arxiv.org/abs/2108.13680.

A IMPLEMENTATION DETAILS

We report the details of our implementation in this section, and our source code is also submitted with this supplemental material.

Deep Reinforcement Learning We formulate 3D-BPP as Markov Decision Process and solve it with the deep reinforcement learning method. A DRL agent seeks for a policy π to maximize the accumulated discounted reward:

$$J(\pi) = E_{\tau \sim \pi}[\sum_{t=0}^{\infty} \gamma^t R(s_t, a_t)] \tag{8}$$

Where $\gamma \in [0, 1]$ is the discount factor, and $\tau = (s_0, a_0, s_1, \dots)$ is a trajectory sampled based on the policy π. We extract the feature of state $s_t = (\mathcal{T}_t, n_t)$, using graph attention networks (Velickovic et al., 2018) for encoding the spatial relations of all space configuration nodes. The context feature is fed to two key components of our pipeline: an actor network and a critic network. The actor network, designed as a pointer mechanism, weighs the leaf nodes of PCT, which is written as $\pi(a_t|s_t)$. The action a_t is an eligible index of selected leaf node $l \in \mathbf{L}_t$, denoted as $a_t = index(l)$. The critic network maps the context feature in to a state value prediction $V(s_t)$ which helps the training of actor network. The whole network is trained via a composite loss $L = \alpha \cdot L_{actor} + \beta \cdot L_{critic}$ ($\alpha = \beta = 1$ in our implementation), which consists of actor loss L_{actor} and critic loss L_{critic}. These two loss functions are defined as:

$$\begin{cases} L_{actor} & = (r_t + \gamma V(s_{t+1}) - V(s_t)) \log \pi(a_t|s_t) \\ L_{critic} & = (r_t + \gamma V(s_{t+1}) - V(s_t))^2 \end{cases} \tag{9}$$

Where $r_t = c_r \cdot w_t$ is our reward signal and we set γ as 1 since the packing episode is finite. We adopt a step-wise reward $r_t = c_r \cdot w_t$ once n_t is inserted into PCT as an internal node successfully. Otherwise, $r_t = 0$ and the packing episode ends. The choice of item weight w_t depends on the packing preferences. In the general sense, we set w_t as the volume occupancy $v_t = s_n^x \cdot s_n^y \cdot s_n^z$ of n_t, and the constant c_r is $10/(S^x \cdot S^y \cdot S^z)$. For online 3D-BPP with additional packing constraints, this weight can be set as $w_t = max(0, v_t - c \cdot O(s_t, a_t))$. While term v_t ensures that space utilization is still the primary concern, the objective function $O(s_t, a_t)$ guides the agent to satisfy additional constraints like isle friendliness and load balancing. We adopt ACKTR (Wu et al., 2017) method for training our DRL agent, which iteratively updates an actor and a critic using Kronecker-factored approximate curvature (K-FAC) (Martens & Grosse, 2015) with trust region. Zhao et al. (2021a) have demonstrated that this method has a surprising superiority on online packing problems over other model-free DRL algorithms like SAC (Haarnoja et al., 2018).

Feature extraction Specifically, ACKTR runs multiple parallel processes (64 here) to interact with their respective environments and gather samples. The different processes may have different packing time step t and deal with different packing sequences, the space configuration nodes number N also changes. In order to combine these irregularly shaped data into one batch, we fullfill $\mathbf{B}_t$ and $\mathbf{L}_t$ to fixed lengths, 80 and $25 \cdot |o|$ respectively, with dummy nodes. The descriptors for dummy nodes are all-zero vectors and have the same size as the internal nodes and the leaf nodes. The relation weight logits u_{ij} of dummy node i to arbitrary node j is replaced with $-inf$ to eliminate these dummy nodes during the feature calculation of GAT. The global context feature $\bar{h}$ is aggregated only on the eligible nodes $\mathbf{h}$: $\bar{h} = \frac{1}{N} \sum_{i=1}^{N} h_i$. All space configuration nodes are embedded by GAT as a fully connected graph as Figure 2 (b), without any inner mask operation.

We only provide the packable leaf nodes which satisfy placement constraints for DRL agents. For $setting$ 2, we check in advance if a potential placement satisfies Constraint 1 and 2. For $setting$ 1 and $setting$ 3, we will additionally check if one placement meets the constraints of packing stability. Benefits from the fast stability calculation method proposed by Zhao et al. (2021b), this pre-checking process can be completed in a very short time (the DRL agent samples data at a frequency of more than 400 FPS). If there are too many packable leaf nodes to accommodate the current item n_t, we randomly intercept a subset $\mathbf{L}_{sub_t}$ from $\mathbf{L}_t$ if $|\mathbf{L}_t|$ exceeds $25 \cdot |o|$ for training. During the test, this interception length is determined via a grid search which ranges from 50 to 300 with step length 10.

The node-wise MLPs $\phi_{\theta_B}, \phi_{\theta_L}$, and ϕ_{θ_n} used to embed raw space configuration nodes are two-layer linear networks with LeakyReLU activation function. ϕ_{FF} is a two-layer linear structure activated by ReLU. The features dimensions d_h, d_k, and d_v are 64 in our GAT implementation.

Figure 3: Full potential positions generated by different PCT expansion schemes (all in xoy plane). The gray dashed lines are the boundaries of the bin. The red circles in (a), (b) represent corner points and extreme points respectively. The potential positions introduce by different EMSs are rendered with different colors in (c). All intersections of two dashed lines in (d) constitute event points. Note that, these potential positions should be converted to the front-left-bottom coordinates of the item n_t during the packing process.

B LEAF NODE EXPANSION SCHEMES

We introduce the leaf node expansion schemes here, which are used to incrementally calculate new potential placements introduced by the just placed item n_t. The choice of leaf node expansion schemes strongly influences the performance of the DRL agent. A good expansion scheme should reduce the number of solutions to be explored while not missing too many feasible packings. Meanwhile, polynomially computability is also expected. We extend three existing heuristic placement rules which have proven to be accurate and efficient to our PCT expansion, which refers to *Corner Point*, *Extreme Point*, and *Empty Maximal Space*. Since all these schemes are related to boundary points of packed items, we combine the start/end points of n_t with these boundary points as a superset, namely *Event Point*.

Corner Point Martello et al. (2000) first introduce the concept of Corner Point (CP) for their branch-and-bound methods. Given 2D packed items in the xoy plane, the corner points can be found where the envelope of the items in the bin changes from vertical to horizontal, as shown in Figure 3 (a). Extend this 2D situation to 3D cases, the new potential 3D positions introduce by the just placed item n_t are elements of $\{(p_n^x + s_n^x, p_n^y, p_n^z), (p_n^x, p_n^y + s_n^y, p_n^z), (p_n^x, p_n^y, p_n^z + s_n^z)\}$ if the envelope of the corresponding 2D plane, e.g., xoy, yoz, and xoz, is changed by n_t. The time complexity of finding incremental 3D corner points is $O(c)$ with an easy-to-maintained bin height map data structure to detect the change of envelope on each plane.

Extreme Point Crainic et al. (2008) extend the concept of Corner Point to Extreme Point (EP) and claims their method reaches the best performance of that era. Its insight is to provide the means to exploit the free space defined inside a packing by the shapes of the items that already exist. When the current item n_t is added, new EPs are incrementally generated by projecting the coordinates $\{(p_n^x + s_n^x, p_n^y, p_n^z), (p_n^x, p_n^y + s_n^y, p_n^z), (p_n^x, p_n^y, p_n^z + s_n^z)\}$ on the orthogonal axes, e.g. project $(p_n^x + s_n^x, p_n^y, p_n^z)$ in the directions of the y and z axes to find intersections with all items lying between item n_t and the boundary of the bin. The nearest intersection in the respective direction is an extreme point. Since we stipulate a vertical top-down loading direction, the 3D extreme points in the strict sense may exist a large item blocks the loading direction. So we find the 2D extreme points (see Figure 3 (b)) in each xoy plane and repeat this operation on each distinct z value which satisfies $p_n^z \leq z \leq p_n^z + s_n^z$. The time complexity of this method is $O(m \cdot |\mathbf{B}_{2D}|)$, where $\mathbf{B}_{2D}$ is the packed items that exist in the corresponding z plane and m is the number of related z scans.

Empty Maximal Space The Empty Maximal Space (EMS) (Ha et al., 2017) means the largest empty orthogonal spaces that exist in the bin. This is a simple and effective placement rule. When the current item n_t is placed into an EMS e on its front-left-bottom corner, with e presented by its front-left-bottom position (p_e^x, p_e^y, p_e^z) and sizes (s_e^x, s_e^y, s_e^z), this EMS is split into three smaller EMSs with positions $(p_e^x + s_n^x, p_e^y, p_e^z), (p_e^x, p_e^y + s_n^y, p_e^z), (p_e^x, p_e^y, p_e^z + s_n^z)$ and sizes $(s_e^x - s_n^x, s_e^y, s_e^z), (s_e^x, s_e^y - s_n^y, s_e^z), (s_e^x, s_e^y, s_e^z - s_n^z)$, respectively. If the item n_t only partially intersects with e, we can apply a similar volume subtraction to the intersecting part for splitting e. For each ems, we define the left-up, right-up, left-bottom, and right-bottom corners of its vertical

Figure 4: The 3D schematic diagram of PCT expansion. This PCT grows under the guidance of the EMS expansion scheme. For simplicity, we only choose the right-up corners of each ems bottom as potential positions here.

Figure 5: Visual results.

bottom as potential positions, as shown in Figure 3 (c). These positions need to be converted to the front-left-bottom coordinate for the items to be packed. Since all EMSs $e \in \mathbf{E}$ in the bin needs to detect intersection with n_t, the time complexity of finding 3D EMSs incrementally is $O(|\mathbf{E}|)$. A 3D schematic diagram of PCT expansion guided by EMSs is provided in Figure 4.

Event Point It's not difficult to find that all these three schemes mentioned above are related to boundary points of a packed item along $d \in \{x, y\}$ axes (we assume the initial empty bin is also a special packed item here). When the current item n_t is packed, we update the existing PCT leaf nodes by scanning all distinct z values which satisfy $p_n^z \leq z \leq p_n^z + s_n^z$ and combine the start/end points of n_t with the boundary points that exist in this z plane (see Figure 3 (d)) to get the superset, which is called *Event Points*. The time complexity for detecting event points is $O(m \cdot |B_{2D}|^2)$.

C VISUAL RESULTS

We visualized the experimental results of Section 4.1 in Figure 5. Each plot is a randomly generated item sequence which is packed by our best-performing policies (PCT & EV on *setting* 1 and *setting* 3, PCT & EMS on *setting* 2).