MANIFOLD REGULARIZATION FOR LOCALLY STABLE DEEP NEURAL NETWORKS

ABSTRACT

We apply concepts from manifold regularization to develop new regularization techniques for training locally stable deep neural networks. Our regularizers are based on a sparsification of the graph Laplacian which holds with high probability when the data is sparse in high dimensions, as is common in deep learning. Empirically, our networks exhibit stability in a diverse set of perturbation models, including ℓ_2, ℓ_∞, and Wasserstein-based perturbations; in particular, we achieve 40% adversarial accuracy on CIFAR-10 against an adaptive PGD attack using ℓ_∞ perturbations of size $\epsilon = 8/255$, and state-of-the-art verified accuracy of 21% in the same perturbation model. Furthermore, our techniques are efficient, incurring overhead on par with two additional parallel forward passes through the network.

1 INTRODUCTION

Recent results in deep learning highlight the remarkable performance deep neural networks can achieve on tasks using data from the natural world, such as images, video, and audio. Though such data inhabits an input space of high dimensionality, the physical processes which generate the data often manifest significant biases, causing realistic inputs to be sparse in the input space.

One way of capturing this intuition is the manifold assumption, which states that input data is not drawn uniformly from the input space, but rather supported on some smooth submanifold(s) of much lower dimension. Starting with the work of Belkin et al. (2006), this formulation has been studied extensively in the setting of semi-supervised kernel and regression methods, where algorithms exploit the unlabelled data points to learn functions which are smooth on the input manifold (Geng et al., 2012; Goldberg et al., 2008; Niyogi, 2013; Sindhwani et al., 2005; Tsang and Kwok, 2007; Xu et al., 2010). Such techniques have seen less use in the context of deep neural networks, owing in part to the ability of such models to generalize from relatively sparse data (Zhang et al., 2016).

Contributions   We apply concepts from manifold regularization to train locally stable deep neural networks. In light of recent results showing that neural networks suffer widely from adversarial inputs (Szegedy et al., 2013), our goal is to learn a function which does not vary much in the neighborhoods of natural inputs, independently of whether the network classifies correctly. We show that this definition of local stability has a natural interpretation in the context of manifold regularization, and propose an efficient regularizer based on an approximation of the graph Laplacian when data is sparse in high dimensions. Crucially, our regularizer exploits the continuous piecewise linear nature of ReLU networks to learn a function which is smooth over the data manifold in not only its outputs but also its decision boundaries.

We evaluate our approach by training neural networks with our regularizers for the task of image classification on CIFAR-10 (Krizhevsky et al., 2009). Empirically, our networks exhibit robustness against a variety of adversarial models implementing ℓ_2, ℓ_∞, and Wasserstein-based attacks. We also achieve state-of-the-art *verified* robust accuracy under ℓ_∞ of size $\epsilon = 8/255$. Furthermore, our regularizers are cheap: we simply evaluate the network at two additional random points for each training sample, so the total computational cost is on par with three parallel forward passes through the network. Our techniques thus present a novel, regularization-only approach to learning robust neural networks, which achieves performance comparable to existing defenses while also being an order of magnitude more efficient.

2 BACKGROUND

Manifold regularization   The manifold assumption states that input data is not drawn uniformly from the input domain $\mathcal{X}$, also know as the *ambient space*, but rather is supported on a submanifold $\mathcal{M} \subset \mathcal{X}$, called the *intrinsic space*. There is thus a distinction between regularizing on the ambient space, where the learned function is smooth with respect to the entire input domain (e.g., Tikhonov regularization (Phillips, 1962; Tikhonov et al., 2013)), and regularizing over the intrinsic space, which uses the geometry of the input submanifold to determine the regularization norm.

A common form of manifold regularization assumes the gradient of the learned function $\nabla_{\mathcal{M}} f(x)$ should be small where the probability of drawing a sample is large; we call such functions "smooth". Let μ be a probability measure with support $\mathcal{M}$. This leads to the following intrinsic regularizer:

$$||f||_I^2 := \int_{\mathcal{M}} ||\nabla_{\mathcal{M}} f(x)||^2 d\mu(x) \tag{1}$$

In general, we cannot compute this integral because $\mathcal{M}$ is not known, so Belkin et al. (2006) propose the following discrete approximation that converges to the integral as the number of samples grows:

$$||f||_I^2 \approx \frac{1}{N^2} \sum_{i,j=1}^{N} (f(x_i) - f(x_j))^2 L_{i,j} \tag{2}$$

Here, the $x_1, ..., x_N$ are samples drawn, by assumption, from the input manifold $\mathcal{M}$ according to μ, and L is a matrix of weights measuring the similarity between samples. The idea is to approximate the continuous input manifold using a discrete graph, where the vertices are samples, the edge weights are distances between points, and the Laplacian matrix L encodes the structure of this graph. A common choice of weights is an isotropic Gaussian kernel $L_{i,j} := \exp(-||x_i - x_j||^2/s)$. To improve computational costs, weights are often truncated to the k-nearest neighbors or within some ϵ-ball. Note that the Laplacian can also be interpreted as a discrete matrix operator, which converges under certain conditions to the continuous Laplace operator (Belkin and Niyogi, 2008).

ReLU networks   Our development focuses on a standard architecture for deep neural networks: fully-connected feedforward networks with ReLU activations. In general, we can write the function represented by such a network with n layers and parameters $\theta = \{A_i, b_i\}_{i=1,...,n-1}$ as

$$z_0 = x \tag{3}$$
$$\hat{z}_i = A_i \cdot z_{i-1} + b_i \qquad \text{for } i = 1, ..., n-1 \tag{4}$$
$$z_i = \sigma(\hat{z}_i) \qquad \text{for } i = 1, ..., n-2 \tag{5}$$
$$f(x; \theta) = \hat{z}_{n-1} \tag{6}$$

where the A_i are the weight matrices and the b_i are the bias vectors. We call the z_i "hidden activations", or more simply, activations, and the $\hat{z}_i$ "pre-activations".

In this work, we consider networks in which $\sigma(\cdot)$ in (5) is the Rectified Linear Unit (ReLU)

$$z_i = \sigma(\hat{z}_i) := \max(0, \hat{z}_i)$$

It is clear from this description that ReLU networks are a family of continuous piecewise linear functions. We denote the linear function induced by an input x as $f_x(\cdot; \theta)$, i.e., the analytic extension of the local linear component about x over the input domain.

Adversarial robustness   One common measure of robustness for neural networks is against a norm-bounded adversary. In this model, the adversary is given an input budget ϵ over a norm $||\cdot||_{in}$, and asked to produce an output perturbation δ over a norm $|\cdot|_{out}$. A point x' is an ϵ-δ adversarial example for an input pair (x, y) if

$$||x' - x||_{in} \leq \epsilon$$
$$|f(x'; \theta) - y|_{out} \geq \delta$$

When the specific norm is either unimportant or clear from context, we also write the first condition as $x' \in N_\epsilon(x)$, where $N_\epsilon(x)$ refers to the ϵ-ball or neighborhood about x. If such an adversarial

example does not exist, we say that the network is ϵ-δ robust at x. Standard examples of $||\cdot||_{in}$ include the ℓ_2 and ℓ_∞ "norm", defined for vectors as $||x||_\infty := \max_i |x_i|$. For classification tasks, the adversary is successful if it produces an example in the ϵ-neighborhood of x which causes the network to misclassify. In this case, we drop δ and say that the network is ϵ-robust at x. Note that if $f(x; \theta)$ is already incorrect, then x suffices as an adversarial example.

3 RELATED WORK

Manifold regularization was first introduced by Belkin et al. (2006) in the context of semi-supervised learning, where the goal was to leverage unlabeled samples to learn a function which behaves well (e.g., is smooth, or has low complexity) over the data manifold. The use of manifold regularization for deep neural networks has been explored in several contexts (Tomar and Rose, 2014; 2016; Hu et al., 2018; Zhu et al., 2018). In particular, Lee et al. (2015) combine manifold regularization with adversarial training and show improvements in standard test accuracy. Our approach is to use manifold regularization to induce stability separately from accuracy. We note that a similar decomposition between accuracy and stability forms the basis for the TRADES algorithm (Zhang et al., 2019), though the training procedure ultimately relies on adversarial training. Hein and Andriushchenko (2017) propose a conceptually similar regularizer to minimize the difference between logits and show improved ℓ_2 certified robustness. Finally, several prior works explore regularizing for robustness based on other differential forms (Ross and Doshi-Velez, 2017; Jakubovitz and Giryes, 2018), though they only report results using the weaker single-step PGD adversary.

Adversarial examples were introduced by Szegedy et al. (2013), who found that naively trained neural networks suffer almost complete degradation of performance on natural images under slight perturbations which are imperceptible to humans. A standard class of defenses is *adversarial training*, which is characterized by training on adversarially generated input points (Goodfellow et al., 2014). In particular, the Projected Gradient Descent (PGD) attack (Kurakin et al., 2016; Madry et al., 2017) is widely considered to be an empirically sound algorithm for both training and evaluation of robust models. However, such training methods rely on solving an inner optimization via an iterative method, effectively increasing the number of epochs by a multiplicative factor (e.g., an overhead of 5–10x for standard PGD). Achieving robustness against multiple adversarial models has also been explored previously (Schott et al., 2018; Tramer and Boneh, 2019; Maini et al., 2019; Croce and Hein, 2019b), though in most cases these works use weaker variants of the subset of standard adversaries we consider (e.g., a smaller ϵ or the single-step version of PGD).

Another approach is to train models which are *provably robust*. One method is to use an exact verification method, such as an MILP solver, to prove that the network is robust on given inputs (Tjeng et al., 2017). In particular, Xiao et al. (2019) use a similar loss based on ReLU pre-activations to learn stable ReLUs for efficient verification, but rely on a PGD adversary to train a robust model. Certification methods modify models to work directly with neighborhoods instead of points (Dvijotham et al., 2018; Gowal et al., 2018; Mirman et al., 2018; Wong et al., 2018). In practice, the inference algorithms must overapproximate the neighborhoods to preserve soundness while keeping the representation compact as it passes through the network. This strategy can be interpreted as solving a convex relaxation of the exact verification problem. Though certification thus far has produced better lower bounds, verification as a technique is fully general and can be applied to any model (given sufficient time); recent work also suggests that methods using layerwise convex relaxations may face an inherent barrier to tight verification (Salman et al., 2019).

4 SETTING

We reframe the goal of learning functions that are robust using a perspective which decouples stability from accuracy. The key observation is that we would like to train networks that are locally stable around natural inputs, even if the network output is incorrect. This approach contrasts with adversarial training, which attempts to train the network to classify correctly on worst-case adversarial inputs. In particular, recall that a network is ϵ-robust at x if no point in the ϵ-neighborhood of x causes the network to misclassify. We consider the related property of ϵ-stability:

Definition 4.1 *A function f is ϵ-δ* stable *at an input x if for all $x' \in N_\epsilon(x)$, $|f(x) - f'(x)| \le \delta$. A classifier f is ϵ-stable at an input x if for all $x' \in N_\epsilon(x)$, $f(x) = f(x')$.*

As ϵ-stability is independent of the correct label for x, we argue that ϵ-stability is a property of the function with respect to the input manifold and can thus be captured using manifold regularization. For completeness, we state the following connection between robustness and stability:

Proposition 4.1 *A function f is ϵ-δ robust at an input x iff f is ϵ-δ stable at x and $f(x) = y$. A classifier f is ϵ-robust at an input x iff f is ϵ-stable at x and f correctly classifies x.*

5   MANIFOLD REGULARIZATION FOR DEEP NEURAL NETWORKS

First, we motivate our approach to stability using manifold regularization. Assume that we have a function f such that $||\overline{\nabla} f(x')|| \leq \delta/\epsilon$ for $x' \in N_\epsilon(x)$; clearly f is ϵ-δ stable at input x. This suggests that minimizing the gradient of f might also induce ϵ-stability in f. However, rather than minimizing the gradient of f everywhere, note that we only need ϵ-stability around valid input points; thus we arrive at manifold regularization.

Applying the regularization term in Equation 2 yields, in the limit, a function which is smooth on the data manifold. Unfortunately, a straightforward approach does not suffice for our goal of learning ϵ-stable deep neural networks. The first problem is that convergence of the discrete approximation requires that the samples be dense over the input manifold; however, this assumption is almost certainly violated in most practical applications, particularly in the deep learning regime. The second problem is that smoothness on the data manifold does not yield ϵ-stability; indeed, smoothness as defined in Equation 1 is a global characteristic with average-case guarantees, whereas stability is a local property with worst-case behavior. The next two sections are dedicated to these challenges.

5.1   RESAMPLING FOR LOCAL SMOOTHNESS

We write the ϵ-neighborhood of a manifold $\mathcal{M}$ as $\mathcal{M}_\epsilon := \{x : \exists y \in \mathcal{M}, ||x - y|| \leq \epsilon\}$. Since ϵ-stability is defined over the ϵ-neighborhood of every input point, we might want a function which is smooth over $\mathcal{M}_\epsilon$ instead of just $\mathcal{M}$, e.g., by slightly perturbing every input point. This strategy does produce samples from the ϵ-neighborhood of the data manifold, however note that the induced distribution is not uniform but rather the convolution of the choice of noise distribution with the uniform distribution over $\mathcal{M}$. Nevertheless, this procedure exhibits several properties we can exploit. The first is that for sufficiently small ϵ, we get nearly the same operator over $\mathcal{M}_\epsilon$ and $\mathcal{M}$, so that smoothness over $\mathcal{M}_\epsilon$ does not sacrifice smoothness on the original data manifold $\mathcal{M}$. A more subtle property is that we can actually draw as many distinct points as we would like from $\mathcal{M}_\epsilon$. We leverage these extra points to build a regularizer which yields good estimations of the local smoothness. Moreover, taking a discrete approximation of the form in Equation 2 with the resampled points from $\mathcal{M}_\epsilon$ still converges to the original operator. Formally, we can state the following:

Proposition 5.1 *Let $\epsilon, s > 0$ be given. Let $x_1, ..., x_n$ be n samples drawn uniformly at random from a submanifold $\mathcal{M} \subset \mathcal{X}$. For each x_i, pick c new points $x_{i,1}, ..., x_{i,c}$ by sampling iid perturbations $\delta_{i,1}, ..., \delta_{i,c}$ and setting $x_{i,j} = x_i + \delta_{i,j}$, where $\forall i, j, ||\delta_{i,j}|| < \epsilon$. Given a kernel $k_s(x, y) = \exp(-||x - y||^2/s)$, let L and L_c be the Laplacian matrices defined by the n original samples and $n \cdot c$ new samples, respectively. Then if $\epsilon^2 < s$, we have that L and L_c converge to the same operator in the limit as $n \to \infty$.*

A proof is sketched in Appendix A. For our purposes, this result states that the resampled Laplacian enjoys the same behavior in the limit as the original Laplacian.

5.2   SPARSE APPROXIMATION OF RESAMPLED LAPLACIAN

We next analyze the properties of the Laplacian matrix constructed by the proposed resampling procedure. Although the resampled Laplacian converges to the same operator in the limit, we show that it exhibits behavior we can exploit in the low data regime. The main observation is that, due to the curse of dimensionality (whereby data becomes increasingly sparse in high dimensions), the resampled Laplacian will consist of two types of edges: very short edges between points resampled from the same ϵ-neighborhood, and very long edges between points sampled from different ϵ-neighborhoods. For an appropriate choice of the scale factor s, the exponential form of the kernel causes the weights on the long edges to fall off very quickly compared to the short edges; we thus

approximate the Laplacian by dropping long edges and only using weights from short edges. The problem of approximating a graph Laplacian using a subgraph with fewer edges is known as spectral sparsification (Spielman and Teng, 2011). Note that sampling edges proportional to their weights is an unbiased estimator of L', since:

$$x^T L x = \sum x_i L_{ij} x_j = \mathbb{E}\left[\sum x_i L_{ij} x_j\right] = \sum x_i \mathbb{E}[L_{ij}] x_j = x^T L' x$$

By the curse of dimensionality, the approximation becomes increasingly accurate as the number of dimensions grows. As a result of our choice of sparsification, the computation of the Laplacian is localized, i.e., the discrete approximation for the intrinsic regularizer can now be written as

$$||f||_I^2 \approx \frac{1}{c^2 N^2} \sum_{i=1}^{N} \sum_{j,k=1}^{c} (f(x_{i,j}) - f(x_{i,k}))^2 L(x_{i,j}, x_{i,k}) \tag{7}$$

The inner loop of this computation involves far fewer terms than the full regularizer (since generally $c \ll n$), and can be efficiently computed pointwise over the full dataset.

We emphasize that the validity of this approximation ultimately depends on the sparsity of the dataset, as well as the particular choice of ϵ and s. In particular, we do not expect this approach to yield better results than the standard regularizer when the data is dense. We provide some rough calculations for CIFAR-10, the setting of our experiments. Each image has dimension $32 * 32 * 3$, with pixel values between 0 and 1. The standard deviations over the dataset of each channel are $0.2470, 0.2435, 0.2616$. Then even if we assume that each image occupies a ball of radius 0.25, we would need at least $2^{32*32*3}$ images to cover the entire input space; the 50,000 images in the CIFAR-10 training set cannot even cover 16 dimensions. In comparison, we take $\epsilon = 8/255$, which is about 13% of the standard deviation. We conclude that the sparse approximation holds in this setting while the original manifold regularizer without resampling yields very little information.

5.3 HAMMING REGULARIZERS

We additionally leverage the structure of ReLU networks to induce a stronger regularization effect on the data manifold. The central observation is that not just do we want the function computed by the neural network to be constant (i.e., smooth with respect to its outputs) on the manifold, we also want the network to produce its outputs in roughly the same way.

First, we identify every local linear component $f_x(\cdot; \theta)$ with its "activation pattern", i.e., the sequence of branches taken at each ReLU. We will write $f_H(x; \theta)$ for the map that takes inputs x to their activation patterns, which live on the unit hypercube $\{0, 1\}^N$ (where N is the number of ReLUs in the network). If we endow the hypercube with the standard Hamming distance d_H, this induces a pullback (psuedo-)metric in the input space: $d_H^*(x, y) = d_H(f_H(x; \theta), f_H(y; \theta))$. Notice that the metric identification is exactly the set of local linear components $f_x(\cdot; \theta)$.

Recall that the goal of regularization is to reduce the complexity of the learned function f in the ϵ-neighborhood of inputs x. We argue that d_H^* provides a concise measure of this complexity. Specifically, if we consider the number of distinct local linear components in $N_\epsilon(x)$, then since d_H^* is a psuedo-metric, we have that $\forall x' \in N_\epsilon(x), d_H^*(x, x'; \theta) = 0$ if and only if $N_\epsilon(x)$ is a single linear component. Thus, minimizing d_H^* between x and all $x' \in N_\epsilon(x)$ reduces the number of linear components in the neighborhood of x. In fact, by the triangle inequality, the same holds in the interior of any convex polytope defined by a set of points $\{x_i\}_{i \in I}$ where $\forall i, i' \in I, d_H^*(x_i, x_{i'}; \theta) = 0$. This makes minimizing d_H^* very sample efficient.

Treating $f_H(\cdot; \theta)$ as an output of the network, we have the following (sparse) manifold regularizer:

$$||f_H(\cdot; \theta)||_I^2 := \int_{\mathcal{M}_\epsilon} ||\nabla_{\mathcal{M}_\epsilon} f_H(x; \theta)||^2 d\mu(x)$$

$$\approx \frac{1}{c^2 N^2} \sum_{i=1}^{N} \sum_{j,k=1}^{c} d_H^*(x_{i,j}, x_{i,k}; \theta)^2 L(x_{i,j}, x_{i,k})$$

which is just Equations 1 and 7 with the outputs $f(x)$ replaced by the activation pattern map. However, this loss term is not continuous in the inputs, and furthermore, the gradients vanish almost

Figure 1: Surface and contour plots for H_α ($\alpha = 1$).

everywhere, so it does not generate good training signals. We thus use a continuous relaxation:

$$H_\alpha(\hat{z}, \hat{y}; \theta) := \mathrm{abs}(\tanh(\alpha * \hat{z}) - \tanh(\alpha * \hat{y}))$$

This form is differentiable everywhere except when $\hat{z} = \hat{y}$, and recovers the Hamming distance when we take α to infinity (after scaling). Qualitatively, sensitive activations (i.e., small $|\hat{z}|$ and $|\hat{y}|$) are permitted so long as they are precise. Figure 1 presents the surface and contour plots of H_α. Note that this idea can be extended more generally to other activation functions by penalizing differing pre-activations more when the second derivative of the activation function is large (and so the first-order Taylor approximation has larger errors).

5.4 TRAINING WITH SPARSE MANIFOLD REGULARIZATION

For every sample x, we generate a new random maximal perturbation $\rho \in \{\pm \epsilon\}^d$ and produce the pair of perturbed inputs $x^+ := x + p$ and $x^- := x - p$. We compute the standard manifold regularization term as $||f(\cdot, \theta)||_I^2 \propto \sum_i ||f(x_i^+) - f(x_i^-)||_2^2$. For the Hamming regularizer, we use the ℓ_2 norm to combine the Hamming distances between pre-activations within a layer and normalize by twice the number of elements in each layer. We sum over the layers, then normalize by the total number of layers. Note that in both cases, the weights $L(x_i^+, x_i^-)$ can be dropped since the distance between x_i^+ and x_i^- is constant. The final optimization objective is thus

$$\theta^* = \arg\min_\theta \frac{1}{N} \sum_{i=1}^{N} V(f(x_i; \theta), y_i) + \gamma_K ||f(\cdot; \theta)||_K^2 + \gamma_I ||f(\cdot; \theta)||_I^2 + \gamma_H ||f_H(\cdot; \theta)||_I^2$$

where V is the loss function, $||f(\cdot, \theta)||_K^2$ is the ambient regularizer (e.g., ℓ_2 regularization), and the $\gamma_K, \gamma_I, \gamma_H$ are hyperparameters which control the relative contributions of the different regularizers.

5.5 DISCUSSION

Our development has focused on learning deep neural networks which are smooth when samples are sparse over the input manifold $\mathcal{M}$. While this property is related to ϵ-stability, in general the two are not equivalent. Roughly, ϵ-stability is inherently a property about worst case behavior, whereas manifold regularization is aimed at learning a function which is smooth on average. Nonetheless, from a theoretical perspective there are two reasons to expect smoothness to help with stability. The first is that perfect smoothness yields perfect stability (i.e., a constant function on the data manifold); the second is that the two properties converge in the limit as ϵ approaches zero.

Next, we discuss our choice to focus on the sparse setting. The basic idea is two-fold: first, the requirement that the learned function be ϵ-stable significantly alters the geometry of the input manifold; second, when data is sparse, the amount of information one can glean about the overall geometry of the input manifold is limited, as is evidenced by the vanishing weights in the Laplacian. Our main hypothesis is that the combination of these two observations allows one to formulate a version

Table 1: CIFAR-10 robust accuracy against various adversaries and perturbation models.

Defense	Test Accuracy (%)			
	ℓ_2	ℓ_∞	Wasserstein	Clean
	$\epsilon = 0.5$	$\epsilon = 8/255$	$\epsilon = .1$	
Wong et al. (2019)			76	80.69
baseline (ℓ_∞ certified)			61	66.33
Maini et al. (2019)	66.0	49.8[‡]		81.7
baseline (ℓ_∞ PGD, Madry et al. (2017))	<5.0	45.8		87.3
Manifold Regularization	57.53[§]	36.90[§]	66.02	69.95

[§]Computed using the full AutoAttack+ attack (Croce and Hein, 2020), which includes APGD-CE, APGD-DLR (+targeted), FAB (+targeted) (Croce and Hein, 2019a), and Square Attack (Andriushchenko et al., 2019). [‡]With slightly smaller $\epsilon = 0.03 \approx 7.65/255$. [†]Reported in Maini et al. (2019).

of the regularizer built from resampled data, which maintains the same properties in the limit but yields more local information when data is sparse.

Conversely, consider the alternative approach, namely, directly learning a smooth function when it is possible to produce samples, not necessarily labelled, that are dense over the input manifold $\mathcal{M}$. Then given the central thesis behind this work, one would expect stability to improve. In fact, the top four results for robust accuracy reported in Croce and Hein (2020) all exploit an additional dataset of unlabeled images which is orders of magnitude larger than the original training set (Carmon et al., 2019; Hendrycks et al., 2019; Uesato et al., 2019; Wang et al., 2020).

6 EXPERIMENTAL RESULTS

We report results for two models trained on CIFAR-10 image classification using our regularization techniques: a smaller CNN for exact verification, following Xiao et al. (2019); and a PreActRes-Net18 model (He et al., 2016) for benchmarking against a variety of adversarial models. We also include two ablation studies for the larger model using only intrinsic or Hamming regularization to isolate their individual effects on stability. Appendix B reports training details and hyperparameters; full experimental results (including MNIST, which is not discussed here) are in Appendix C.

6.1 STABILITY

The main characteristic that differentiates our approach conceptually from existing methods for adversarial robustness is that we train our models using pure regularization, i.e., without reference to a particular adversary. In comparison, most methods train and test using inputs produced by the same adversary. While this procedure yields good performance against the adversary used during training, performance degrades significantly when evaluated under different perturbation models. In general, the bounds for various adversarial models are set so that maximal perturbations remain somewhat reasonable by human standards; thus, we expect a model that is stable in the general sense to be robust against a variety of adversaries, particularly those not seen during training.

In line with this observation, we test a single model trained to be stable using manifold regularization against three norm-bounded perturbation models. The first two constitute the most common settings for adversarial robustness, namely, CIFAR-10 robustness using ℓ_∞ and ℓ_2 PGD adversaries bounded at $\epsilon = 8/255$ and 0.5, respectively. We also use a Wasserstein-based PGD adversary at $\epsilon = 0.1$, which is a metric for images more closely aligned with human perceptions. Our results indicates that a model trained using our manifold regularizer does in fact learn to be more stable on test images across a variety of different perturbation models (Table 1). We obtained our results after training for 3 hours on one GPU, compared to several days for standard PGD training (Shafahi et al., 2019).

For comparison, we note that standard adversarial training using PGD from Madry et al. (2017) , which forms the basis of every state-of-the-art approach for ℓ_∞ robustness (Croce and Hein, 2020),

Table 2: CIFAR-10 provable and robust accuracies against an ℓ_∞ adversary at $\epsilon = 8/255$.

Mechanism	Defense	Test Accuracy (%)		
		Verified	Robust	Clean
Adversarial Training	PGD (Madry et al. (2017))		**45.8**	87.3
	FGSM (Madry et al. (2017))		0.0	90.3
Verification	Xiao et al. (2019)	20.27	26.78	40.45
	Manifold Regularization (small)	21.04	25.56	36.66
Regularization	Pang et al. (2019)[‡]		24.8	**92.7**
	Manifold Regularization (large)		40.54	69.95
	intrinsic regularization only		20.11	34.74
	Hamming regularization only		24.87	90.24

[†]With slightly smaller $\epsilon = 0.03 \approx 7.65/255$. [§]Computed from 500 / 10000 images in test set. [‡]Results for regularization only; reported robust accuracy is 55.0% when trained with PGD.

achieves negligible performance when evaluated in the ℓ_2 setting. We also report results from Maini et al. (2019), which was the only other approach in the literature to evaluate their models for both ℓ_∞ and ℓ_2 robustness at the full levels of ϵ using a PGD adversary; their models are trained for 50 epochs with 50 steps of PGD against multiple adversaries in parallel (≈ 5000 effective epochs). Finally, we also report results from Wong et al. (2019) for comparison against the Wasserstein adversary. Their results are obtained against a PGD adversary using a 50-step inner optimization (number of training epochs is not reported); their baseline model is trained to be certifiably robust against ℓ_∞ attacks of size $\epsilon = 2/255$, and achieves lower robustness than ours.

6.2 ABLATION STUDIES

We run several ablation studies to better understand the behavior of our methods. The first column of Table 2 reports the *verifiable robustness* of our smaller model, which outperforms the previous state of the art as reported in Xiao et al. (2019). We emphasize that we provide this metric as a baseline for establishing a provable lower bound on the robustness achieved by our defense, compared to empirical robustness which is often a brittle measure of true robustness, particularly for newly proposed defenses (Athalye et al., 2018; Carlini et al., 2019; Tramer et al., 2020).

The second column of Table 2 presents robust accuracy against the standard PGD adversary used in the literature. The results using the intrinsic or Hamming regularizers alone indicate that both terms contribute to our performance. We also report results for other approaches which are not variants of PGD (i.e., do not rely on solving a minimax problem at each training loop). To the best of our knowledge, Pang et al. (2019) is the only other result in the literature which achieves non-trivial robust accuracy using a regularization-only approach. For context, the best result in this setting is reported by Wang et al. (2020) using a PGD variant at 65.04% robust accuracy.

7 CONCLUSION

We design regularizers based on manifold regularization that encourage piecewise linear neural networks to learn locally stable functions. We demonstrate this stability by showing that a single model trained using our regularizers is resilient against ℓ_2, ℓ_∞, and Wasserstein-based attacks. We also achieve state-of-the-art verified robustness of 21% against ℓ_∞-bounded perturbations of size $\epsilon = 8/255$ on CIFAR-10. Critically, computing our regularizers relies only on random sampling, and thus does not require running an inner optimization loop to find strong perturbations at training time. As such, our techniques exhibit strong scaling, since they increase batch sizes rather than epochs during training, allowing us to train an order of magnitude faster than standard adversarial training. This work thus presents the first regularization-only approach to achieve comparable results to standard adversarial training against a variety of perturbation models.

REFERENCES

Maksym Andriushchenko, Francesco Croce, Nicolas Flammarion, and Matthias Hein. Square attack: a query-efficient black-box adversarial attack via random search, 2019.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples, 2018.

Mikhail Belkin and Partha Niyogi. Towards a theoretical foundation for laplacian-based manifold methods. *Journal of Computer and System Sciences*, 74(8):1289 – 1308, 2008. ISSN 0022-0000. doi: https://doi.org/10.1016/j.jcss.2007.08.006. URL http://www.sciencedirect.com/science/article/pii/S0022000007001274. Learning Theory 2005.

Mikhail Belkin, Partha Niyogi, and Vikas Sindhwani. Manifold regularization: A geometric framework for learning from labeled and unlabeled examples. *Journal of machine learning research*, 7(Nov):2399–2434, 2006.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks, 2017.

Nicholas Carlini, Anish Athalye, Nicolas Papernot, Wieland Brendel, Jonas Rauber, Dimitris Tsipras, Ian Goodfellow, Aleksander Madry, and Alexey Kurakin. On evaluating adversarial robustness. *arXiv preprint arXiv:1902.06705*, 2019.

Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, Percy Liang, and John C. Duchi. Unlabeled data improves adversarial robustness, 2019.

Ronald R. Coifman and Stéphane Lafon. Diffusion maps. *Applied and Computational Harmonic Analysis*, 21 (1):5 – 30, 2006. ISSN 1063-5203. doi: https://doi.org/10.1016/j.acha.2006.04.006. URL http://www.sciencedirect.com/science/article/pii/S1063520306000546. Special Issue: Diffusion Maps and Wavelets.

Francesco Croce and Matthias Hein. Minimally distorted adversarial examples with a fast adaptive boundary attack, 2019a.

Francesco Croce and Matthias Hein. Provable robustness against all adversarial l_p-perturbations for $p \geq 1$, 2019b.

Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks, 2020.

Krishnamurthy Dvijotham, Sven Gowal, Robert Stanforth, Relja Arandjelovic, Brendan O'Donoghue, Jonathan Uesato, and Pushmeet Kohli. Training verified learners with learned verifiers, 2018.

Logan Engstrom, Andrew Ilyas, Shibani Santurkar, and Dimitris Tsipras. Robustness (python library), 2019. URL https://github.com/MadryLab/robustness.

Bo Geng, Dacheng Tao, Chao Xu, Linjun Yang, and Xian-Sheng Hua. Ensemble manifold regularization. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 34(6):1227–1233, 2012.

Andrew B Goldberg, Ming Li, and Xiaojin Zhu. Online manifold regularization: A new learning setting and empirical study. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 393–407. Springer, 2008.

Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples, 2014.

Sven Gowal, Krishnamurthy Dvijotham, Robert Stanforth, Rudy Bunel, Chongli Qin, Jonathan Uesato, Relja Arandjelovic, Timothy Mann, and Pushmeet Kohli. On the effectiveness of interval bound propagation for training verifiably robust models, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks, 2016.

Matthias Hein and Maksym Andriushchenko. Formal guarantees on the robustness of a classifier against adversarial manipulation. In *Advances in Neural Information Processing Systems*, pages 2266–2276, 2017.

Matthias Hein, Jean-Yves Audibert, and Ulrike Von Luxburg. From graphs to manifolds–weak and strong pointwise consistency of graph laplacians. In *International Conference on Computational Learning Theory*, pages 470–485. Springer, 2005.

Matthias Hein, Jean-Yves Audibert, and Ulrike von Luxburg. Graph laplacians and their convergence on random neighborhood graphs. *Journal of Machine Learning Research*, 8(Jun):1325–1368, 2007.

Dan Hendrycks, Kimin Lee, and Mantas Mazeika. Using pre-training can improve model robustness and uncertainty, 2019.

Hongwei Hu, Bo Ma, Jianbing Shen, Hanqiu Sun, Ling Shao, and Fatih Porikli. Robust object tracking using manifold regularized convolutional neural networks. *IEEE Transactions on Multimedia*, 21(2):510–521, 2018.

Daniel Jakubovitz and Raja Giryes. Improving dnn robustness to adversarial attacks using jacobian regularization. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 514–529, 2018.

Alex Krizhevsky et al. Learning multiple layers of features from tiny images. 2009.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial examples in the physical world. *arXiv preprint arXiv:1607.02533*, 2016.

Taehoon Lee, Minsuk Choi, and Sungroh Yoon. Manifold regularized deep neural networks using adversarial examples, 2015.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks, 2017.

Pratyush Maini, Eric Wong, and J Zico Kolter. Adversarial robustness against the union of multiple perturbation models. *arXiv preprint arXiv:1909.04068*, 2019.

Matthew Mirman, Timon Gehr, and Martin Vechev. Differentiable abstract interpretation for provably robust neural networks. In *International Conference on Machine Learning*, pages 3578–3586, 2018.

Partha Niyogi. Manifold regularization and semi-supervised learning: Some theoretical analyses. *The Journal of Machine Learning Research*, 14(1):1229–1250, 2013.

Tianyu Pang, Kun Xu, Yinpeng Dong, Chao Du, Ning Chen, and Jun Zhu. Rethinking softmax cross-entropy loss for adversarial robustness, 2019.

David L Phillips. A technique for the numerical solution of certain integral equations of the first kind. *Journal of the ACM (JACM)*, 9(1):84–97, 1962.

Andrew Slavin Ross and Finale Doshi-Velez. Improving the adversarial robustness and interpretability of deep neural networks by regularizing their input gradients. *arXiv preprint arXiv:1711.09404*, 2017.

Hadi Salman, Greg Yang, Huan Zhang, Cho-Jui Hsieh, and Pengchuan Zhang. A convex relaxation barrier to tight robustness verification of neural networks. In *Advances in Neural Information Processing Systems 32*, pages 9835–9846. Curran Associates, Inc., 2019.

Lukas Schott, Jonas Rauber, Matthias Bethge, and Wieland Brendel. Towards the first adversarially robust neural network model on mnist. *arXiv preprint arXiv:1805.09190*, 2018.

Ali Shafahi, Mahyar Najibi, Amin Ghiasi, Zheng Xu, John Dickerson, Christoph Studer, Larry S. Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free!, 2019.

Vikas Sindhwani, Partha Niyogi, Mikhail Belkin, and Sathiya Keerthi. Linear manifold regularization for large scale semi-supervised learning. In *Proc. of the 22nd ICML Workshop on Learning with Partially Classified Training Data*, volume 28, 2005.

Daniel A Spielman and Shang-Hua Teng. Spectral sparsification of graphs. *SIAM Journal on Computing*, 40 (4):981–1025, 2011.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks, 2013.

Andrei Nikolaevich Tikhonov, AV Goncharsky, VV Stepanov, and Anatoly G Yagola. *Numerical methods for the solution of ill-posed problems*, volume 328. Springer Science & Business Media, 2013.

Vincent Tjeng, Kai Xiao, and Russ Tedrake. Evaluating robustness of neural networks with mixed integer programming. *arXiv preprint arXiv:1711.07356*, 2017.

Vikrant Singh Tomar and Richard C Rose. Manifold regularized deep neural networks. In *Fifteenth Annual Conference of the International Speech Communication Association*, 2014.

Vikrant Singh Tomar and Richard C. Rose. Graph based manifold regularized deep neural networks for automatic speech recognition, 2016.

Florian Tramer and Dan Boneh. Adversarial training and robustness for multiple perturbations. In H. Wallach, H. Larochelle, A. Beygelzimer, F. dAlché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 5866–5876. Curran Associates, Inc., 2019. URL `http://papers.nips.cc/paper/8821-adversarial-training-and-robustness-for-multiple-perturbations.pdf`.

Florian Tramer, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On adaptive attacks to adversarial example defenses, 2020.

Ivor W Tsang and James T Kwok. Large-scale sparsified manifold regularization. In *Advances in Neural Information Processing Systems*, pages 1401–1408, 2007.

Jonathan Uesato, Jean-Baptiste Alayrac, Po-Sen Huang, Robert Stanforth, Alhussein Fawzi, and Pushmeet Kohli. Are labels required for improving adversarial robustness?, 2019.

Ulrike Von Luxburg, Mikhail Belkin, and Olivier Bousquet. Consistency of spectral clustering. *The Annals of Statistics*, pages 555–586, 2008.

Yisen Wang, Difan Zou, Jinfeng Yi, James Bailey, Xingjun Ma, and Quanquan Gu. Improving adversarial robustness requires revisiting misclassified examples. In *International Conference on Learning Representations*, 2020.

Eric Wong, Frank R. Schmidt, Jan Hendrik Metzen, and J. Zico Kolter. Scaling provable adversarial defenses, 2018.

Eric Wong, Frank R. Schmidt, and J. Zico Kolter. Wasserstein adversarial examples via projected sinkhorn iterations, 2019.

Kai Xiao, Vincent Tjeng, Nur Muhammad Shafiullah, and Aleksander Madry. Training for faster adversarial robustness verification via inducing relu stability. *ICLR*, 2019.

Zenglin Xu, Irwin King, Michael Rung-Tsong Lyu, and Rong Jin. Discriminative semi-supervised feature selection via manifold regularization. *IEEE Transactions on Neural networks*, 21(7):1033–1047, 2010.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization, 2016.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P. Xing, Laurent El Ghaoui, and Michael I. Jordan. Theoretically principled trade-off between robustness and accuracy, 2019.

Wei Zhu, Qiang Qiu, Jiaji Huang, Robert Calderbank, Guillermo Sapiro, and Ingrid Daubechies. Ldmnet: Low dimensional manifold regularized neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2743–2751, 2018.

A CONVERGENCE RESULTS

We first sketch a proof of Proposition 5.1. Given a kernel $k_s(x, y) = \exp(-||x - y||^2/s)$ and samples $x_1, ..., x_N$, we can define the discrete operator L for an out-of-sample point x as

$$Lf(x) = \frac{1}{N} \sum_{i=1}^{N} k_s(x, x_i) f(x) - \frac{1}{N} \sum_{i=1}^{N} k_s(x, x_i) f(x_i)$$

We will show pointwise convergence of the original Laplacian L and the resampled Laplacian L'_c to the same continuous operator. Our proof has two parts. First, we show that, for $c = 1$, the resampled Laplacian converges to the original Laplacian. This follows almost immediately from Criterion 5 in Coifman and Lafon (2006), who use perturbation theory to show that sampling from a manifold with noise yields the same approximation so long as the size of the perturbation $|\delta|$, which in our case is bounded by ϵ, is smaller than the scale parameter of the kernel $\sqrt{s}$. To see this, note that since our kernel is smooth, we can linearize the effect of the perturbation on the kernel:

$$k_s(x + \delta_x, y + \delta_y) \le k_s(x, y) + \mathcal{O}\left(\frac{\epsilon}{\sqrt{s}}\right)$$

Then we also have that the perturbation on $Lf(x)$ is of the same order, so that the approximation holds so long as $\epsilon < \sqrt{s}$, as desired.

Next we show that equality holds for arbitrary c. This is a simple consequence of the linearity of the operator L. Imagine fixing c independently perturbed manifolds and then taking the approximation L' to be the average of the operators defined on each of the perturbed manifolds. Clearly this still converges to the same operator L, and since this procedure yields an equivalent formulation of the resampled Laplacian L'_c, we are done.

A few additional observations are in order. It turns out that for L to converge to its continuous counterpart in Equation 1 (i.e., the Laplace-Beltrami operator), we actually need to take the scale of the kernel s to zero (see, e.g. the proofs of convergence in Belkin and Niyogi (2008); Hein et al. (2005; 2007)). Then Proposition 5.1 implies that we also need to take ϵ to zero, so that in the limit we are just sampling from the unperturbed manifold. The situation is actually not so bad, as is possible to prove convergence without taking s to zero, however the continuous operator that is recovered no longer refers to the gradient but rather the value of the kernel over the manifold (Von Luxburg et al. (2008) analyze this case). The spectra of these operators are often used in various clustering algorithms; in the context of deep neural networks, these operators yield similar regularizers for "smoothness", though for a different definition than the one used in this work.

B EXPERIMENTAL METHODS AND HYPERPARAMETERS

We use a PreActResNet18 model (He et al., 2016) for the CIFAR-10 robustness experiments. We train using SGD and weight decay γ_K of 5e-4. We follow Maini et al. (2019) for our learning rate schedule, which is piecewise linear and starts at 0 and goes to 0.1 over first 40 epochs; 0.005 over the next 40 epochs; and 0 over the final 20 epochs. We increase epsilon from 2 to 8 over epochs 10 to 35. We start the weight γ_I of the manifold regularization at 0.8 and the weight γ_H of the Hamming regularization at 2,400; these increase linearly up to a factor of 10 from epochs 20 to 80. We set the hyperparameter $\alpha = 8$.

We use a two-layer convolutional neural network for the CIFAR-10 verification experiments, consisting of 2x2 strided convolutions with 16 and 32 filters, then a 128 hidden unit fully connected layer. This is the same model as used in Wong et al. (2018) and Xiao et al. (2019), except those works use a 100 hidden unit fully connected layer. We use the same schedule for the learning rate and ϵ as in the PreActResNet18 model. The weight γ_I starts at 0.4 and the weight γ_H starts at 9000; these increase linearly up to a factor of 10 from epochs 20 to 80. We use the same hyperparameter α as for the PreActResNet18 model.

We use the CNN with four convolutional layers plus three fully-connected layers from Carlini and Wagner (2017) for the MNIST robustness experiments. We use the same schedule for the learning rate, ϵ, γ_I, and γ_H as in the PreActResNet18 model (except that ϵ scales to 0.3). We use the same hyperparameter α as for the PreActResNet18 model.

To set the hyperparameters γ_I and γ_H on the PreActResNet18 model, we ran a grid search for $\gamma_I = 0.2, ..., 1.0$ and $\gamma_H/\gamma_I = 100, 200, ..., 500$ and selected the settings which yielded the best robust accuracy against a 20-step ℓ_∞ PGD adversary with 10 restarts for $\epsilon = 8/255$ on the full training set; the range of γ_H/γ_I was set such that the corresponding losses were roughly equal for a randomly initialized, untrained network. For reporting results, we train five models using the selected hyperparameters and report results using the one with the median performance on the test set against a 20-step ℓ_∞ PGD adversary at $\epsilon = 8/255$ on CIFAR-10 or 0.3 on MNIST. For the PreActResNet18 model, robust accuracy over the 5 runs ranged from 40.1% to 41.5% with median 40.5%; clean accuracy ranged from 66.9% to 72.4% with median 70.0%.

For our stability results, we use the full version of AutoAttack+, an ensemble of attacks proposed by Croce and Hein (2020), for the ℓ_2 and ℓ_∞ perturbations. We choose the attack because it is parameter-free, which reduces the possibility of misconfiguration; empirically it is at least as strong as standard PGD, and has been successful in breaking many proposed defenses. For the Wasserstein adversary, we use an implementation by Wong et al. (2019). For comparing with standard PGD, we use a 20-step PGD adversary with 10 random restarts and a step size of $2.5 \cdot \epsilon/20$ as implemented by Engstrom et al. (2019). For verification, we adopt the setup of Xiao et al. (2019), using the MIP verifier of Tjeng et al. (2017), with solves parallelized over 8 CPU cores and the timeout set to 120 seconds.

C ADDITIONAL EXPERIMENTS

We plot robustness curves for both CIFAR and MNIST against a standard 20-step PGD adversary with 10 restarts using both ℓ_2 and ℓ_∞ bounds in Figure 2. These results show that, compared with models trained using standard PGD against ℓ_∞ perturbations, our methods perform on par (or substantially better, in the case of the ℓ_2 adversary on CIFAR-10) in a variety of settings, despite the disadvantage of not using the adversary during training. We also used a stronger AutoAttack+ adversary for the CIFAR-10 results in Table 1, which we plot for reference as "ours (AA+)".

For the CIFAR-10 results, we use a PreActResNet18 model trained with manifold regularization on CIFAR-10 at $\epsilon = 8/255$. The curves for PGD are taken from Madry et al. (2017). Our findings mirror those in Schott et al. (2018), namely, that a model trained using PGD on CIFAR-10 for ℓ_∞ performs poorly against ℓ_2 attacks. We also ran a 500-step ℓ_∞ PGD adversary with 20 restarts at $\epsilon = 8/255$ against our model, yielding 40.4% robust accuracy, which is plotted as "ours (PGD+)".

For the MNIST results, we use the CNN architecture from Carlini and Wagner (2017), trained with manifold regularization on MNIST at $\epsilon = 0.3$. The curves for PGD are taken from Madry et al. (2017). The difference in performance is much less dramatic in this case, which we attribute to the lower complexity of the task. We note in particular that both methods experience a sharp drop in performance in the ℓ_∞ case for ϵ larger than the one used during training.

(a) Robust accuracy on CIFAR-10 against a 20-step ℓ_∞ PGD adversary with 10 restarts.

(b) Robust accuracy on CIFAR-10 against a 20-step ℓ_2 PGD adversary with 10 restarts.

(c) Robust accuracy on MNIST against a 20-step ℓ_∞ PGD adversary with 10 restarts.

(d) Robust accuracy on MNIST against a 20-step ℓ_2 PGD adversary with 10 restarts.

Figure 2: Robust accuracy as ϵ increases for a 20-step PGD adversary with 10 restarts.