[Re:] Training Binary Neural Networks using the Bayesian Learning Rule

Reproducibility Summary

(1) gives a mathematically principled approach to solve the discrete optimization problem that occurs in the case of Binary Neural Networks and claims to give a similar performance on various classification benchmarks such as MNIST, CIFAR-10 and CIFAR-100 as compared to their full-precision counterparts, as well as other recent algorithms to train BNNs like PMF and BOP. The paper also claims that BayesBiNN method has an application in continual learning domain as it helps in overcoming catastrophic forgetting of the past by using the posterior approximation of the previous task as a prior for the upcoming task. We try to reproduce all the results presented in the original paper by making a separate and independent code base.

Scope of Reproducibility

We try to verify the performance of our re-implementation of the BayesBiNN optimizer on various classification and regression benchmarks. We also implemented the STE optimizer which was the central baseline model used in the paper. Finally, we tried to evaluate the results of BayesBiNN on the continual learning benchmark to get a better insight.

Methodology

We developed our separate code-base, consisting of an end-to-end trainer with a Keras like interface, for the reproduction which includes the implementation of the BayesBiNN and STE optimizer. We did refer to the author's code open-sourced on GitHub to get some insights about the hyperparameters and other doubts emerged during code development.

Results

We reproduced the accuracy of BayesBiNN optimizer within less than 0.5% of the originally reported value, that upholds the conclusion that it performs nearly as well as it's full-precision counterpart in classification tasks. When we tried this in a semantic segmentation context, we found that the results were very underwhelming and in contrast with the seemingly good results by the STE optimizer even with much hyperparameter tuning. We can conclude that, like other Bayesian methods, it is difficult to train BayesBiNN on more complex tasks.

What was easy

After we worked out the mathematics behind BayesBiNN approach, we developed a pseudo-code for the optimization process which along with references from the author's code, helped us a lot in our reproduction study.

What was difficult

Some of the hyperparameters were not mentioned by the authors in their paper so it was difficult to approximate the values of those parameters. The lack of resources was the next big difficulty that we faced.

Communication with original authors

We had very fruitful conversation with the authors, that helped us in a better understanding of the BayesBiNN approach. It also helped us in our extension to the segmentation domain. The detailed pointers are given at the end of the report.

1 Introduction

Deep Learning is moving towards larger and larger parameters day-by-day, which often makes it difficult to run on resource-constraint devices like mobile phones. Binary Neural Networks (BNNs) could act as a saviour in such situations, helping in largely saving storage and computational costs. The problem of optimizing this binary set of weights is clearly a discrete optimization problem. Previous approaches like STE, and BOP tend to ignore this and use gradient based methods, which still worked in practice. The paper presents a mathematically principled approach for training BNNs which also justifies the current approaches.

2 Scope of reproducibility

The paper mentions a bayesian approach to solve the discrete optimization problem in the case of Binary Neural Networks (BNNs). The outcome of this approach was a BayesBiNN optimizer which could be used to train BNNs and achieve similar accuracy as compared to their full-precision counterparts. To verify the claims given in the paper, we target to achieve the following objectives:

- Work out and present the mathematics behind BayesBiNN in a more simpler way and present the pseudo-code to the optimizer.
- Implement the BayesBiNN optimizer and STE optimizer to verify the accuracy on tasks of varying complexities, as reported in the original paper.
- Reproduce the results for other baselines present in the paper such as PMF according to the hyper-parameters given in the paper.
- Evaluating the performance of BayesBiNN optimizer in more complex domains like semantic segmentation.

3 Methodology

We have re-implemented algorithm proposed in the paper from scratch using PyTorch and created an end-to-end model trainer with a Keras like interface. We referred the code given by authors for the baseline model hyperparameters and the source of synthetic datasets. Following is the algorithmic form of what authors have presented in the paper.

Algorithm 1: Bayesian Learning rule for BayesBiNN

Input: Initialize λ

for *number of training epochs* **do**

    for *i = 1,...,number of mini-batch examples* **do**

        Sample $\epsilon \sim \mathcal{U}(0,1)$ and set $\delta = \frac{1}{2}\log\frac{\epsilon}{1-\epsilon}$

        Initialize $w_b = \tanh((\lambda + \delta)/\tau)$

        Compute following using *gumbel-softmax* trick

$$g_i := \frac{1}{M}\nabla_{w_b}l(y_i, f_{w_r}(x_i))$$

$$s_i := \frac{N(1 - w_b^2)}{\tau(1 - \tanh(\lambda)^2)}$$

    end

    Update μ and λ using following equation

$$\mu \leftarrow \tanh(\lambda)$$

$$\lambda \leftarrow (1-\alpha)\lambda - \alpha[\sum_{i=1}^{M}(s_i \odot g_i) - \lambda_0]$$

end

This would make the paper more interpretive in terms of implementation.

Some of mathematical expressions mentioned in the original paper were sourced from different papers. So here we present the step-wise derivation of those expressions.

Bayesian formulation of the discrete optimization problem, in which loss is minimized w.r.t posterior $q(w)$, given prior $p(w)$ can be written as

$$\mathbb{E}_{q(w)}[\sum_{i=1}^{N} l(y_i, f_w(x_i))] + \mathcal{D}_{KL}[q(w)||p(w)]$$

To solve the above optimization problem, Bayesian learning rule given in (6) is applied, assuming solution to be a part of minimal exponential family of distribution, given by

$$q(w) = h(w)exp[\lambda^T \phi(w) - A(\lambda)]$$

where base measure $h(w)$ is assumed to be 1. Following is the update rule used to learn λ

$$\lambda \leftarrow (1-\rho)\lambda - \rho[\nabla_\mu \mathbb{E}_{q(w)}[l(y_i f_w(x_i))] - \lambda_0]$$

where ρ is the learning rate, $\mu = \mathbb{E}_{q(w)}[\phi(w)]$. Bernoulli distribution being a special case of minimal exponential family distribution, we assume prior $p(w) \sim \mathrm{Bern}(p)$ with $p = 0.5$, and posterior $q(w)$ to be mean-field bernoulli distibution

$$q(w) = \prod_{j=1}^{W} p_j^{\frac{1+w_j}{2}} (1 - p_j)^{\frac{1-w_j}{2}}$$

For weight j,

$$q(w_j) = \exp(\frac{1}{2}(1 + w_j) \log p_j + \frac{1}{2}(1 - w_j) \log(1 - p_j))$$

$$= \exp(\underbrace{w_j}_{\phi(w)} \underbrace{\frac{1}{2} \log \frac{p}{1-p}}_{\lambda}) + \frac{1}{2}\log(p(1-p))$$

Comparing above expression with minimal exponential family distribution, we can say

$$\lambda = \frac{1}{2} \log \frac{p}{1-p} \text{ and } \phi(w) = w.$$

We defined $\mu = \mathbb{E}_{q(w)}[\phi(w)]$,

$$\mu = \int wq(w)dw = \mathbb{E}[q(w)] = \sum_{w^i \in \{-1,1\}} w^i q(w^i)$$

$$= \sum_{w^i \in \{-1,1\}} w^i p^{\frac{1+w^i}{2}} (1-p)^{\frac{1-w^i}{2}} = -(1-p) + p$$

$$= 2p - 1$$

From above derivations we can say that, $p = 1/(1 + \exp(-2\lambda)) = \mathrm{Sigmoid}(2\lambda)$ and $q(w) \sim \mathrm{Bern}(p)$.

To implement the update rule, we need to compute the gradient with respect to μ. Original paper uses a reparamaterization trick called Gumbel-softmax trick (7), which is used to relax the discrete random variables of a concrete distribution (for eg, bernoulli distribution). Binary concrete relaxation (7) of Binary concrete random variable $X \in (0,1)$ with distribution $X \sim \mathrm{BinConcrete}(\alpha, \lambda)$ with temperature λ and location α,

$$X = \frac{1}{1 + \exp(-(\log \alpha + L)/\lambda)}$$

where $L \sim \mathrm{Logistic}$. And its density is given by

$$p_{\alpha,\lambda}(x) = \frac{\lambda \alpha x^{-\lambda-1}(1-x)^{-\lambda-1}}{(\alpha x^{-\lambda} + (1-x)^{-\lambda})^2}$$

Using above expressions, for binary weights $w_j \in \{0,1\}$, relaxed variable $w_r^{\epsilon_j, \tau}(p_j) \in (0,1)$ can be used with temperature τ and $\alpha = e^{2\lambda}$ given by

$$w_r^{\epsilon_j, \tau}(p_j) = \frac{1}{1 + \exp(-\frac{2\lambda_j + 2\delta_j}{\tau})},$$

where $\delta_j \sim \mathrm{Logistic}$ and its density is given by

$$p(w_r^{\epsilon_j, \tau}(p_j)) = \frac{\tau e^{2\lambda} w_r^{\epsilon_j, \tau}(p_j)^{-\tau-1}(1 - w_r^{\epsilon_j, \tau}(p_j))^{-\tau-1}}{(e^{2\lambda} w_r^{\epsilon_j, \tau}(p_j)^{-\tau} + (1 - w_r^{\epsilon_j, \tau}(p_j))^{-\tau})^2}$$

4 Experimental setup

4.1 Model descriptions

We kept the model architectures same as mentioned in the original paper to maintain uniformity and implemented them ourselves. For the MNIST classification task, we used the BinaryConnect architecture and for the CIFAR classification task, we use the VGGBinaryConnect architecture. The authors also compared their BayesBiNN method with the LR-Net method in (8). We implemented the same model architecture as in the LR-Net paper. The detailed architectures are mentioned in the supplementary material provided with this report. For the segmentation task, we used the original U-Net architecture, mentioned in (11) with a minor difference that we introduced a BatchNorm layer after every convolution layer.

4.2 Datasets

The datasets used for image classification tasks are MNIST, CIFAR-10 and CIFAR-100. For generating visualizations for the BayesBiNN and STE methods, we used small toy datasets, Snelson dataset (10) for regression problem and Two Moon's dataset (9) for classification problem. For the segmentation part, we used the Brain Tissue segmentation dataset taken from (11), and for the continual learning visualizations, we used the permuted MNIST dataset (12). The pre-processing of inputs has been kept same as mentioned in the original paper and has been detailed below.

Pre-processing: For MNIST dataset we simply normalize the images and do not perform data augmentation. We keep our validation split as 0.1 uniformly across all sets of experiments except the comparison with LR-Net method (8). For the CIFAR datasets also, we perform the normalization of images along with data-augmentation where we generate images by a randomly cropping a 32x32 image from a 40x40 padded image. Finally, for our semantic segmentation task, we had a very small dataset of 30 images, out of which 24 were chosen for training and 6 for obtaining the validatation score. No other pre-processing has been done in this case.

4.3 Hyperparameters

We have used the hyper-parameters given in the original paper. Table 1 contains the list of all the parameters we used for our experiments:

Optimizer	Parameter	MNIST	CIFAR10	CIFAR100	Snelson Dataset	2 Moons Dataset
BayesBiNN	MC steps	1	1	1	1	5
	Initial LR	10^{-4}	3.10^{-4}	3.10^{-4}	10^{-4}	10^{-3}
	Final LR	10^{-16}	10^{-16}	10^{-16}	10^{-5}	10^{-5}
	LR Scheduler	Cosine	Cosine	Cosine	MultiStepLR	MultiStepLR
	Temperature τ	10^{-10}	10^{-10}	10^{-8}	1	1
	Initialization λ	±10	±10	±10	±10	±15
STE	Initial LR	10^{-2}	10^{-2}	10^{-2}	10^{-1}	10^{-1}
	Final LR	10^{-16}	10^{-16}	10^{-16}	10^{-1}	10^{-3}
	LR Scheduler	Cosine	Cosine	Cosine	MultiStepLR	MultiStepLR
Adam (Full Precision)	Initial LR	10^{-5}	10^{-4}	10^{-4}	-	-
	Final LR	Step	Step	Step	-	-
	LR Scheduler	1	100	100	-	-

Table 1: Training setting for different optimizers on MNIST, CIFAR10 and CIFAR100 datasets.

4.4 Computational requirements

All our final experimental results were performed on a machine having 1 NVIDIA Tesla V100 GPU and 1 single core system with 16 GB memory. Training the Binary Network with BayesBiNN optimizer for a single run, takes around 2.5 GPU hour for MNIST, 5.5 GPU hours for CIFAR-10 and around 8.5 GPU hour for CIFAR-100 dataset, in the current experimental setup.

5 Results

In Table 1 we report our results for various classification benchmarks using our implemented BayesBiNN and STE optimizer. We notice that we get a difference of less than 0.1% as compared to that in the original paper. We generated

the results for baseline STE optimizer and full-precision networks by evaluating our implementation of these methods. We also generated the results of PMF, by modifying it's original open-sourced code and using the hyperparameters mentioned in the original paper.

(a) MNIST   (b) CIFAR10   (c) CIFAR100

Figure 1: Training/Validation/Test accuracy using BayesBiNN optimizer

Datasets	Optimizer	Training Accuracy	Validation Accuracy	Test Accuracy
MNIST	BayesBiNN(ours)	99.90 ±0.01%	99.89 ±0.07%	98.87 ±0.06%
	BayesBiNN(orig.)	99.85 ±0.05%	99.02 ±0.13%	98.86 ±0.05%
	STE	99.90 ±0.01%	98.86 ±0.09%	98.89 ±0.05%
	PMF	-	98.73%	-
	Adam (Full Precision)	99.98 ±0.01%	99.02 ±0.04%	99.02 ±0.01%
CIFAR10	BayesBiNN(ours)	99.96 ±0.01%	93.59 ±0.45%	93.54 ±0.26%
	BayesBiNN(orig.)	99.96 ±0.01%	94.23 ±0.41%	93.72 ±0.16%
	STE	99.99 ±0.01%	93.77 ±0.06%	93.54 ±0.08%
	PMF	-	91.98%	-
	Adam (Full Precision)	99.99 ±0.01%	94.27 ±0.15%	94.38 ±0.16%
CIFAR100	BayesBiNN(ours)	98.35 ±0.1%	74.13 ±0.78%	73.56 ±0.06%
	BayesBiNN(orig.)	98.02 ±0.18%	74.76 ±0.41%	73.68 ±0.31%
	STE	99.22 ±0.03%	72.74 ±0.06%	73.25 ±0.26%
	PMF	-	70.82%	-
	Adam (Full Precision)	99.89 ±0.02%	75.04 ±0.71%	74.80 ±0.39%

Table 2: Results of different optimizers trained on MNIST, CIFAR10 and CIFAR100.

5.1 Comparison with LR-Net

Authors compared their BayesBiNN approach to the LR-Net method presented in (8). We tried to reporduce the result for the same setting. In this comparison, the data pre-processing and augmentation methods remain the same as mentioned in section 4.2, but the validation split is made 0. We denote the test accuracies after 190 epochs in case of MNIST and 290 epochs in case of CIFAR-10, as done in the original paper to maintain uniformity. Note that, our accuracy is matching with that of the original authors in case of MNIST but not in the case of CIFAR-10. We suspect that this is due to some difference in Batch-Norm layers used.

Optimizer	MNIST	CIFAR10
BayesBiNN (ours)	**99.52%**	84.49%
BayesBiNN (orig.)	99.50%	**93.97%**
LR-net (8)	99.47%	93.18%

Table 3: Test accuracy of BayesBiNN and LRNet.

5.2 Continual Learning

As mentioned in the original paper, we try to reproduce the author's claims about weight distribution across tasks in a simple continual learning domain tested on Permuted MNIST. As we can see, as we learn across the tasks, the curve

becomes flatter from the middle conveying that the weights become more deterministic. Our result matches with the claims in the original paper.

(a) Prior λ (b) λ after task 1   (c) λ after task 2

Figure 2: Distribution of $p(w = 1)$ across consecutive learning tasks

5.3 Visualization using Synthetic Dataset

In the original paper, authors present visualizations on binary classification (Two moons datasetr(9)) and toy regression (Snelson dataset(10)) using STE and BayesBiNN optimizer. For classification task, author's claimed that STE is more deterministic classifier compared to BayesBiNN. We reproduced this experiment and the results depicted in Figure 3 seems to be consistent with the author's claim. For regression task, we conclude that author's claim about BayesBiNN (mean) giving smoother curve compared to STE is true, which can also be seen in Figure 4.

Figure 3: Classification on Two Moons dataset using STE and BayesBiNN optimizer.

Figure 4: Regression on Snelson dataset using STE and BayesBiNN optimizer.

Temperature	10	1	0.1	10^{-2}	10^{-3}	10^{-4}
MSE Loss	1.313	0.208	2.151	0.443	0.231	0.199
Temperature	10^{-5}	10^{-6}	10^{-7}	10^{-8}	10^{-9}	10^{-10}
MSE Loss	0.156	0.127	0.173	0.122	0.195	0.173

Table 4: Mean square error loss of Snelson dataset for different temperature.

5.4 Extended Results (Semantic Segmentation)

We tried to validate the performance of the BayesBiNN optimizer on more complex tasks like Semantic Semantic. Unfortunately, the results with BayesBiNN were quite underwhelming as compared to STE and it's full-precision counterpart. We tried various parameters to improve it's performance but none seemed to work. We had a brief discussion with the authors regarding this issue and the authors suggested that Bayesian models are intrinsically very difficult to train. For the results shown in Table 5 and Figure 5, we have use the hyperparameters denoted in Table 1.

	BayesBiNN	STE	Adam (Full Precision)
Validation Score	0.4102	0.3108	0.2943

Table 5: (1 - IoU) score for validation set

(a) BayesBiNN   (b) STE   (c) Adam

Figure 5: Some samples of segmented image outputs

6 Discussion

We reproduced almost all the experiments given in the original paper and most of our results match with the original claims. While this BayesBiNN approach is mathematically principled, we tried it to take a step forward, by using that optimizer on a single segmentation task. However, the results were against our intuition and the result of segmentation were a zoomed segmented image of the input with lots of noise. Apart from this, even in the case of comparison with the LR-Net method, our accuracy differ with that of the original authors, which we feel might be due to some difference in architecture chosen. The major contribution of our work is developing a code base library based on PyTorch with a Keras type interface for training BNNs with several different methods in its arsenal. This would reduce the coding efforts while training a BNNs and could help in future research as benchmarking platform.

6.1 What was easy

The original paper contained a very good explanation of the mathematics behind the BayesBiNN approach. After we worked that out the pseudo code as pointed out in Algorithm 1, the basic implementation of the optimizer became easy and easily verifiable by the author's original code. The appendix in the original paper contained a list of various hyper-parameters used for experiments. This helped us a lot while running the experiments and deciding the range of hyper-parameters while doing ablation studies.

6.2 What was difficult

The most difficult part here was running the large number of experiments in lack of much computational resources. This difficulty was increased since we are taking an average of 5 runs while reporting all our results. Apart from this, we also faced some difficulty in taking care of the hyper-parameters, which were not mentioned in the original paper (like momentum coefficient). To cater that, we had to guess some possible values of the hyper-parameters and run small random searches to find a good candidate. Finally, we also faced difficulty while reproducing the results for the baselines PMF and BOP and adapting their experimental settings to match with that used in the original BayesBiNN paper. Since their code was written long time ago and used older technologies, this task took us a lot of time.

6.3 Communication with original authors

We did not understand the intent of authors for choosing temperature as 1 in case of experiments on synthetic datasets. We were also curious about the author's view on segmentation tasks using BayesBiNN. We mailed this, along with the review of their paper, to the authors to ask for some pointers. The gave the following major pointers:

- It is reasonable that at high temperatures the learned distribution will have high variance. The mode mentioned in the paper refers to the $\text{sign}(\hat{(w)})$, where $\hat{(w)}$ denotes the expectation of the learned posterior Bernoulli distribution. It is not appropriate to directly use the continuous $\hat{(w)}$ as the mode. Another way is to use mean, which samples from the learned posterior Bernoulli distribution and then make predictions using ensemble learning.

- STE is more stable and suggested by the authors to act as a baseline, in particular Adam STE first, to make sure binary networks work. As shown in the paper, there is literally very little difference between STE and BayesBiNN but indeed the latter is difficult to train, as most Bayesian optimizer.

Broader Impact

Recent researches like (3) mention that training a single big transformer model could emit around 626,155 lbs CO_2 which is around 5 times of average carbon emission by a car in it's total lifetime. Clearly, Deep Learning takes a huge toll on the environment which is why there has been an increased focus on much more energy efficient "Green AI". BNNs intrinsically have far less computational and space complexity as compared to their full-precision counterparts and as we can see above they can also achieve an accuracy close to the full-precision networks, at least in the classification tasks and also show potential of expanding well to more complex segmentation tasks. This can help us a lot in moving towards cleaner Deep Learning. This class of technology also provides a huge set of opportunities in extending AI to edge devices with much smaller and low-energy systems. We feel that it's potential impact on environment and sustainability is at par with its academic importance, that is why we see it as a much larger thing than just a set of publications.

References

[1] Xiangming Meng, Roman Bachmann & Mohammad Emtiyaz Khan, Training Binary Neural Networks using the Bayesian Learning Rule. In *Proceedings of the 37 th International Conference on Machine Learning*, Online, PMLR 119, 2020.

[2] L. Biewald, "Experiment Tracking with Weights and Biases," Weights & Biases. [Online]. Available: http://wandb.com/.

[3] Emma Strubell, Ananya Ganesh & Andrew McCallum, Energy and Policy Considerations for Deep Learning in NLP. In the *57th Annual Meeting of the Association for Computational Linguistics (ACL)*. Florence, Italy. July 2019

[4] Ajanthan, T., Dokania, P. K., Hartley, R., & Torr, P. H. S, Proximal mean-field for neural network quantization. In *IEEE International Conference on Computer Vision*, pp. 4871–4880, 2019a.

[5] Helwegen, K., Widdicombe, J., Geiger, L., Liu, Z., Cheng, K.-T., & Nusselder, R., Latent weights do not exist: Rethinking binarized neural network optimization. In *NeurIPS*, 2019.

[6] Khan, M. E. and Rue, H., Learning-Algorithms from Bayesian principles 2020. `https://emtiyaz.github.io/papers/learning_from_bayes.pdf`.

[7] Chris J. Maddison, Andriy Mnih, Yee Whye Teh, The Concrete Distribution: A Continuous Relaxation of Discrete Random Variables In *ICLR*, 2017

[8] Shayer, O., Levi, D., and Fetaya, E. Learning discrete weights using the local reparameterization trick. *ICLR*, 2018.

[9] Moons, T. Two moons datasets description. `https://scikit-learn.org/stable/modules/generated/sklearn.datasets.make_moons.html`.

[10] Snelson, E. and Ghahramani, Z. Sparse Gaussian processes using pseudo-inputs. In *Proceedings of the 18th International Conference on Neural Information Processing Systems*, NIPS05, pp. 12571264, Cambridge, MA, USA, 2005. MIT Press.

[11] Ronneberger, Olaf, Philipp Fischer, and Thomas Brox. "U-net: Convolutional networks for biomedical image segmentation." *International Conference on Medical image computing and computer-assisted intervention. Springer, Cham, 2015*.

[12] Goodfellow, I. J., Mirza, M., Xiao, D., Courville, A., and Bengio, Y. An empirical investigation of catastrophic forgetting in gradient-based neural networks. *ICLR*, 2013.

[13] Zenke, F., Poole, B., and Ganguli, S. Continual learning through synaptic intelligence. In Proceedings of the 34th International Conference on Machine Learning-Volume 70, pp. 3987–3995. JMLR. org, 2017.

[14] LeCun, Y. and Cortes, C. MNIST handwritten digit database. 2010. URL `http://yann.lecun.com/exdb/mnist/`.

[15] Kingma, D. P. and Ba, J. Adam: A method for stochastic optimization. *ICLR*, 2015.

[16] Jang, E., Gu, S., and Poole, B. Categorical reparameterization with Gumbel-softmax. *ICLR*, 2017.

[17] Courbariaux, M., Bengio, Y., and David, J.-P. Binaryconnect: Training deep neural networks with binary weights during propagations. In *Advances in neural information processing systems*, pp. 3123–3131, 2015.