MAKING SUBSTITUTE MODELS MORE BAYESIAN CAN ENHANCE TRANSFERABILITY OF ADVERSARIAL EXAMPLES

ABSTRACT

The transferability of adversarial examples across deep neural networks (DNNs) is the crux of many black-box attacks. Many prior efforts have been devoted to improving the transferability via increasing the diversity in inputs of some substitute models. In this paper, by contrast, we opt for the diversity in substitute models and advocate to attack a Bayesian model for achieving desirable transferability. Deriving from the Bayesian formulation, we develop a principled strategy for possible finetuning, which can be combined with many off-the-shelf Gaussian posterior approximations over DNN parameters. Extensive experiments have been conducted to verify the effectiveness of our method, on common benchmark datasets, and the results demonstrate that our method outperforms recent state-of-the-arts by large margins (roughly 16.8% absolute increase in average attack success rate on ImageNet), and, by combining with these recent methods, further performance gain can be obtained. Our code will be publicly available.

1 INTRODUCTION

The adversarial vulnerability of deep neural networks (DNNs) has attracted great attention over the past decade (Szegedy et al., 2014; Goodfellow et al., 2015; Papernot et al., 2016; Carlini & Wagner, 2017; Madry et al., 2018; Athalye et al., 2018). It has been demonstrated that the prediction of state-of-the-art DNNs can be arbitrarily altered by adding designated perturbations, even imperceptible to human eyes, to their inputs. Threat models involving the adversarial examples can be divided into white-box and black-box settings according to the amount of information (of victim models) being exposed to the adversary.

In black-box attacks, where the adversary can hardly get access to the architecture and parameters of the victim model, the transferability of adversarial examples is often relied on, given the fact that adversarial examples crafted on a substitute model can sometimes fool other models as well. However, such methods also suffer from considerable failure rate when the perturbation budge is small. Thus, much recent effort has been devoted to improve the black-box transferability of adversarial examples, and a variety of transfer-based attacks have been proposed.

Assuming that the substitute model was pre-trained and given, most of the recent research focused only on improving the backpropagation process when issuing attacks, yet little attention has been paid to possible training or finetuning of the substitute model. In this paper, we shall focus more on the training process, and for which we advocate to perform in a Bayesian manner, in order to issue more powerful transfer-based attacks. By introducing probability measures to weights and biases of the substitute model, all these parameters are represented under assumptions of some distributions to be learned. In this way, an ensemble of infinitely many DNNs (that are jointly trained in our view) can be obtained from a single run of training. Adversarial examples are then crafted by maximizing average prediction loss over such a distribution of models, which is a referred to as posterior learned in the Bayesian manner. Extensive experiments on attacking a variety of CIFAR-10 (Krizhevsky & Hinton, 2009) and ImageNet (Russakovsky et al., 2015) victim models have been performed, and we show that the proposed method outperforms previous state-of-the-arts considerably. Moreover, our method can be conjugated with existing methods easily and reliably for further improving the attack performance.

2 BACKGROUND AND RELATED WORK

2.1 ADVERSARIAL ATTACKS

Most existing adversarial attacks can be divided into two categories: white-box attack and black-box attack, according to how much information is accessible to the adversary (Papernot et al., 2016).

White-box attacks. Given full knowledge of the architecture and parameters of a victim model, white-box attacks are typically performed via utilizing some loss gradient with respect to the model inputs. For instance, given a normal sample $(\mathbf{x}, y)$ and a source model $f_{\mathbf{w}} : \mathbb{R}^n \to \mathbb{R}^c$ that is trained to classify $\mathbf{x}$ into $y \in R^c$, it is a popular choice to craft the adversarial example $\mathbf{x} + \mathbf{\Delta x}$ within an ℓ_p bounded small region of $\mathbf{x}$, by maximizing the prediction loss, *i.e.*, $\max_{\|\mathbf{\Delta x}\|_p \leq \epsilon} L(\mathbf{x} + \mathbf{\Delta x}, y, \mathbf{w})$, where ϵ is the perturbation budget. FGSM proposed to calculate $\epsilon \cdot \text{sgn}(\nabla_{\mathbf{x}} L(\mathbf{x}, y, \mathbf{w}))$ for $\mathbf{\Delta x}$ in the $p = \infty$ setting (Goodfellow et al., 2015), and the iterative variants of FGSM, *e.g.*, I-FGSM (Kurakin et al., 2017) and PGD (Madry et al., 2018) can be more powerful.

Black-box attacks. Black-box attacks are more challenging compared to the white-box attacks. Many existing methods largely rely on the transferability of adversarial examples, *i.e.*, adversarial examples crafted on one classification model can generally succeed in attacking some other victim models as well. It is normally assumed to be able to query the victim model to annotate training samples, or be possible to collect a pre-trained source model that is trained to accomplish the same task as the victim models. Aiming at enhancing the adversarial transferability, methods have been proposed to modify the backpropagation computation, see for example the skip gradient method (SGM) (Wu et al., 2020), the linear backpropagation (LinBP) method (Guo et al., 2020), the intermediate-level attack (ILA) (Huang et al., 2019), and ILA++ (Li et al., 2020a; Guo et al., 2022). It is also widely adopted to increase the diversity in inputs (Xie et al., 2019; Dong et al., 2019; Lin et al., 2019; Wang et al., 2021). In this paper, we consider the diversity from another perspective, the substitute model(s), and we introduce a Bayesian approximation for achieving this.

Ensemble-based attacks. Our method can be equivalent to utilizing an ensemble of infinitely many substitute models with different parameters for performing attacks. There exists prior work that also took advantage of multiple substitute models. For instance, Liu et al. (2017) proposed to generate adversarial examples on an ensemble of multiple models that differ in their architectures. Li et al. (2020b) proposed ghost network for gaining transferability, using dropout and skip connection erosion to obtain multiple models. Following the spirit of stochastic variance reduced gradient (Johnson & Zhang, 2013), Xiong et al. (2022) proposed stochastic variance reduced ensemble (SVRE) to reduce the variance of gradients of different substitute models. From a geometric perspective, Gubri et al. (2022b) suggested finetuning with a constant and high learning rate for collecting multiple models along the training trajectory, on which the ensemble attack was performed. Another method collected substitute models by using cSGLD (Gubri et al., 2022a), which is more related to our work, but being different in the sense of posterior approximation and sampling strategy. We will provide detailed comparison in Section 4.2.

2.2 BAYESIAN DNNs

If a DNN is viewed as a probabilistic model, then the training of its parameters $\mathbf{w}$ can be regarded as maximum likelihood estimation or maximum a posterior estimation (with regularization). Bayesian deep learning opts for estimating a posterior of the parameter given data at the same time. Prediction of any new input instance is given by taking expectation over such a posterior. Since DNNs normally involves a huge number of parameters, making the optimization of Bayesian model more challenging than in shallow models, a series of studies have been conducted and many scalabble approximations have been developed. Effective methods utilize variational inference (Graves, 2011; Blundell et al., 2015; Kingma et al., 2015; Khan et al., 2018; Zhang et al., 2018; Wu et al., 2018; Osawa et al., 2019; Dusenberry et al., 2020) dropout inference (Gal & Ghahramani, 2016; Kendall & Gal, 2017; Gal et al., 2017), Laplace approximation (Kirkpatrick et al., 2017; Ritter et al., 2018; Li, 2000), or SGD-based approximation (Mandt et al., 2017; Maddox et al., 2019; 2021; Wilson & Izmailov, 2020). Taking SWAG (Maddox et al., 2019) as an example, which is an SGD-based approximation, it approximates the posterior using a Gaussian distribution with the stochastic weight averaging (SWA) solution as its first raw moment and the composition of a low rank matrix and a diagonal matrix as its second central moment. Our method is develop in a Bayesian spirit and we shall discuss SWAG

thoroughly in this paper. Due to the space limit of this paper, we omit detailed introduction of these methods and encourage readers to check references if needed.

3 TRANSFER-BASED ATTACK AND BAYESIAN SUBSTITUTE MODELS

An intuition for improving the transferability of adversarial examples suggests improving the diversity during backpropagation. Prior work has tried increasing input diversity (Xie et al., 2019; Dong et al., 2019; Lin et al., 2019; Wang et al., 2021) and has indeed achieved remarkable improvements. In this paper we consider model diversity. A straightforward idea seems to train a set of models with diverse architecture or from different initialization. If all models (including the victim models) that are trained to accomplish the same classification task follow a common distribution, then training multiple source models seems to perform multiple point estimates with maximum likelihood estimation. The power of performing attacks on the ensemble of these models increases along with the number of source models. However, the time complexity of such a straightforward method is high, and it scales with the number of source models that could be trained. Here we opt for an Bayesian approach to address this issue and the method resembles performing transfer-based attack on an ensemble of infinitely many DNNs.

3.1 ATTACK ON A BAYESIAN MODEL

Bayesian learning aims to discover a distribution of likely models instead of a single one. Given a posterior distribution over parameters $p(\mathbf{w}|\mathcal{D}) \propto p(\mathcal{D}|\mathbf{w})p(\mathbf{w})$, we can predict the label of a new input $\mathbf{x}$ by Bayesian model averaging, *i.e.*,

$$p(y|\mathbf{x}, \mathcal{D}) = \int_{\mathbf{w}} p(y|\mathbf{x}, \mathbf{w})p(\mathbf{w}|\mathcal{D})d\mathbf{w}, \tag{1}$$

where $p(y|\mathbf{x}, \mathbf{w})$ is the predictive distribution for a given parameter $\mathbf{w}$ which is often obtained from the DNN output with the assistance of the softmax function. In order to perform attacks on such a Bayesian model, we need to solve the following optimization problem:

$$\operatorname*{arg\,min}_{\|\mathbf{\Delta x}\|_p \leq \epsilon} p(y|\mathbf{x} + \mathbf{\Delta x}, \mathcal{D}) = \operatorname*{arg\,min}_{\|\mathbf{\Delta x}\|_p \leq \epsilon} \int_{\mathbf{w}} p(y|\mathbf{x} + \mathbf{\Delta x}, \mathbf{w})p(\mathbf{w}|\mathcal{D})d\mathbf{w}. \tag{2}$$

Apparently, it is intractable to perform exact Bayesian inference on DNNs using Eq. (2), as there exist a super large number of parameters. A series of methods aim to address this. We consider a simple Monte Carlo sampling method to approximate the integral, *i.e.*, $p(y|\mathbf{x}, \mathcal{D}) \approx \frac{1}{M} \sum_i p(y|\mathbf{x}, \mathbf{w}_i)$, where a set of M models each of which parameterized by $\mathbf{w}_i$ are sampled from the posterior $p(\mathbf{w}|\mathcal{D})$. One can then solve Eq. (2) by performing attacks on the ensemble of these models,

$$\operatorname*{arg\,min}_{\|\mathbf{\Delta x}\|_p \leq \epsilon} \frac{1}{M} \sum_{i=1}^{M} p(y|\mathbf{x} + \mathbf{\Delta x}, \mathbf{w}_i) = \operatorname*{arg\,max}_{\|\mathbf{\Delta x}\|_p \leq \epsilon} \frac{1}{M} \sum_{i=1}^{M} L(\mathbf{x} + \mathbf{\Delta x}, y, \mathbf{w}_i), \text{s.\,t.}\ \mathbf{w}_i \sim p(\mathbf{w}|\mathcal{D}). \tag{3}$$

With iterative optimization methods, *e.g.*, I-FGSM and PGD, different sets of models can be sampled at different iteration, as if there exist infinitely many substitute models.

3.2 THE BAYESIAN FORMULATION AND POSSIBLE FINETUNING

In this subsection, we discuss the way of obtaining the Bayesian posterior. Following prior work, we consider a threat model in which finetuning a source model is possible on some benchmark datasets collected for the same task as that of the victim models, although it is feasible to approximate the posterior without taking special care of the training process (Gal & Ghahramani, 2016).

To get started, we simply assume that the posterior is an isotropic Gaussian $\mathcal{N}(\hat{\mathbf{w}}, \sigma^2\mathbf{I})$, where $\hat{\mathbf{w}}$ is the parameter to be trained and σ is a positive constant for controlling the diversity of distribution. The optimization for the Bayesian model can be formulated as

$$\max_{\hat{\mathbf{w}}} \frac{1}{N} \sum_{i=1}^{N} \mathbb{E}_{\mathbf{w} \sim \mathcal{N}(\hat{\mathbf{w}}, \sigma^2\mathbf{I}))} p(y|\mathbf{x}_i, \mathbf{w}). \tag{4}$$

(a) FGSM

(b) I-FGSM

Figure 1: How the (a) FGSM transferability, and (b) I-FGSM transferability change with different choices of σ for the isotropic Gaussian posterior on CIFAR-10. The dots in the plots represent the transferability of adversarial examples crafted by a single sample in the posterior. We performed ℓ_∞ attacks under $\epsilon = 4/255$. Best viewed in color.

We can further reformulate Eq. (4) into

$$\min_{\hat{\mathbf{w}}} \frac{1}{MN} \sum_{i=1}^{N} \sum_{j=1}^{M} L(\mathbf{x}_i, y, \hat{\mathbf{w}} + \boldsymbol{\Delta}\mathbf{w}_j), \text{ s.t. } \boldsymbol{\Delta}\mathbf{w}_j \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}). \tag{5}$$

by adopting Monte Carlo sampling. The computational complexity of the objective in Eq. (5) seems still high, thus we focus on the worst-case parameters from the posterior, whose loss in fact bounds the objective from below. The optimization problem then becomes:

$$\min_{\hat{\mathbf{w}}} \max_{\boldsymbol{\Delta}\mathbf{w}} \frac{1}{N} \sum_{i=1}^{N} L(\mathbf{x}_i, y, \hat{\mathbf{w}} + \boldsymbol{\Delta}\mathbf{w}), \text{ s.t. } \boldsymbol{\Delta}\mathbf{w} \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}) \text{ and } p(\boldsymbol{\Delta}\mathbf{w}) \geq \varepsilon, \tag{6}$$

where ε controls the confidence region of the Gaussian posterior. With Taylor's theorem, we further approximate Eq. (6) with

$$\min_{\hat{\mathbf{w}}} \max_{\boldsymbol{\Delta}\mathbf{w}} \frac{1}{N} \sum_{i=1}^{N} L(\mathbf{x}, y, \hat{\mathbf{w}}) + \nabla_{\hat{\mathbf{w}}} L(\mathbf{x}, y, \hat{\mathbf{w}})^T \boldsymbol{\Delta}\mathbf{w}, \text{ s.t. } \boldsymbol{\Delta}\mathbf{w} \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}) \text{ and } p(\boldsymbol{\Delta}\mathbf{w}) \geq \varepsilon. \tag{7}$$

As $\boldsymbol{\Delta}\mathbf{w}$ is sampled from a zero-mean isotropic Gaussian distribution, the inner maximization problem has an analytic solution, which is $\boldsymbol{\Delta}\mathbf{w}^* = \lambda_{\varepsilon,\sigma} \nabla_{\hat{\mathbf{w}}} L(\mathbf{x}, y, \hat{\mathbf{w}}) / \|\nabla_{\hat{\mathbf{w}}} L(\mathbf{x}, y, \hat{\mathbf{w}})\|$. $\lambda_{\varepsilon,\sigma}$ is computed with the probability density of the zero-mean isotropic Gaussian distribution. Thereafter, the outer gradient for solving Eq. (7) is $\nabla_{\hat{\mathbf{w}}} L(\mathbf{x}, y, \hat{\mathbf{w}}) + \mathbf{H} \boldsymbol{\Delta}\mathbf{w}^*$, which involves second-order partial derivatives in the Hessian matrix $\mathbf{H}$ which can be approximately calculated using the finite difference method. More specifically, the gradient is estimated with $\nabla_{\hat{\mathbf{w}}} L(\mathbf{x}, y, \hat{\mathbf{w}}) + (1/\gamma)(\nabla_{\hat{\mathbf{w}}} L(\hat{\mathbf{w}} + \gamma \boldsymbol{\Delta}\mathbf{w}^*) - \nabla_{\hat{\mathbf{w}}} L(\mathbf{w}))$, where γ is a small positive constant.

A quick experiment on CIFAR-10 (Krizhevsky & Hinton, 2009) using ResNet-18 (He et al., 2016) was performed to evaluate the effectiveness of such finetuning. Introduction of victim models and detailed experimental settings are deferred to Section 4.1. In Figure 1, we compare attack transferability using the deterministic ResNet-18 and Bayesian ResNet-18, by applying FGSM and I-FGSM for single-step and multi-step attacks, respectively. We evaluated with different choices of the posterior covariance by varying the value of σ. Notice that the posterior can also be given even without any finetuning, through directly applying the pre-trained parameters to $\hat{\mathbf{w}}$ in $\mathcal{N}(\hat{\mathbf{w}}, \sigma^2 \mathbf{I})$, and attacking such a "Bayesian" model can be equivalent to attacking the deterministic model when $\sigma \to 0$. While with $\sigma > 0$, one can perform attack in a way as described in Section 3.1. It can be seen that significant improvement (over 21% absolute increase in the I-FGSM average success rate) can be achieved by introducing the additional finetuning, though attacking the pre-trained parameters in a Bayesian manner already outperforms the baseline considerably (roughly 14% increase in the average success rate, see the blue curves in Figure 1(b)). Detailed attack success rates on each victim model are reported in Table 1. Conclusions on ImageNet is consistent with that on CIFAR-10, see Appendix A.

(a) FGSM

(b) I-FGSM

Figure 2: How the (a) FGSM transferability, and (b) I-FGSM transferability change with different scales for the covariance of SWAG posterior on CIFAR-10. The dots in the plots represent the transferability of adversarial examples crafted by a single model in the posterior. We perform ℓ_∞ attacks under $\epsilon = 4/255$. Best viewed in color.

The (possible) finetuning mainly improves performance of the worst model that could be sampled. For instance, with $\sigma = 0.009$, the worst performance in 100 model samples from the posterior shows an test-set prediction accuracy of 90.59% while the model at population mean shows an accuracy of 91.68%. After finetuning, both results increase, to 91.91% and 92.65%, respectively, which means finetuning improves the test-set performance of Bayesian samples and this could be beneficial to adversarial transferability.

Table 1: Comparing transferability of FGSM and I-FGSM adversarial examples generated on a deterministic substitute model and the Bayesian substitute model (with and without additional fine-tuning) under the ℓ_∞ constraint with $\epsilon = 4/255$ on CIFAR-10. The architecture of the substitute models is ResNet-18, and "average" was calculated over all six victim models except for ResNet-18. We performed 10 runs of the experiment and report the average performance in the table.

		fine-tune	ResNet-18	VGG-19	WRN	ResNeXt	DenseNet	PyramidNet	GDAS	Average
FGSM	-	✗	84.76%	33.95%	36.10%	36.89%	34.30%	13.21%	28.60%	30.51%
	Isotropic	✗	85.14%	40.41%	43.33%	43.97%	41.17%	14.92%	33.51%	36.22%
		✓	85.92%	54.06%	55.50%	57.40%	53.13%	19.23%	42.69%	47.00%
	+SWAG	✗	85.76%	55.74%	55.94%	56.80%	53.02%	18.74%	41.61%	46.98%
		✓	85.99%	59.01%	59.64%	61.35%	57.67%	21.22%	45.57%	50.74%
I-FGSM	-	✗	100.00%	37.51%	57.01%	57.95%	52.84%	12.70%	40.32%	43.06%
	Isotropic	✗	100.00%	52.30%	73.46%	75.38%	69.55%	19.61%	53.85%	57.36%
		✓	100.00%	78.80%	91.63%	92.98%	90.22%	41.50%	78.76%	78.98%
	+SWAG	✗	100.00%	83.69%	92.31%	92.98%	90.55%	44.33%	78.04%	80.32%
		✓	100.00%	85.10%	94.66%	94.95%	92.75%	48.93%	83.89%	83.38%

3.3 FORMULATION WITH IMPROVED APPROXIMATION

In Section 3.2, we have demonstrated the power of adopting Bayesian substitute models for generating transferable adversarial examples, with a relatively strong assumption on the posterior though. The posterior in Section 3.2 is assumed to be isotropic, with a presumed covariance matrix. Taking one step further, we consider to learn the covariance matrix from data as well in this subsection.

There exist dozens of methods for achieving the goal, here we choose SWAG (Maddox et al., 2019) which is a simple and scalable one. It introduces an improved approximation to the posterior over parameters. Gaussian approximation is still considered, and more specifically, the SWA solution (Izmailov et al., 2018) is adopted as its mean and the covariance is decomposed into a low rank matrix and a diagonal matrix, i.e., $\mathbf{w} \sim \mathcal{N}(\mathbf{w}_{\text{SWA}}, \mathbf{\Sigma}_{\text{SWAG}})$, where $\mathbf{\Sigma}_{\text{SWAG}} = \frac{1}{2}(\mathbf{\Sigma}_{\text{diag}} + \mathbf{\Sigma}_{\text{low-rank}})$.

In SWAG, both the mean and the covariance are calculated using temporary models during training, and the posterior is estimated by many temporary models from the training dynamics. Recall that the

Table 2: Success rates of transfer-based attacks on ImageNet using ResNet-50 as substitute architecture and I-FGSM as the back-end attack, under the ℓ_∞ constraint with $\epsilon = 8/255$ in the untargeted setting. "Average" was calculated over all ten victim models except for ResNet-50. We performed 10 runs and report the average performance for each result in the table.

Method	ResNet-50	VGG-19	ResNet-152	Inception v3	DenseNet	MobileNet
I-FGSM	**100.00%**	39.22%	29.18%	15.60%	35.58%	37.90%
TIM (2019)	**100.00%**	44.88%	35.14%	22.14%	46.12%	42.62%
SIM (2020)	**100.00%**	53.30%	46.80%	27.04%	54.16%	52.54%
LinBP (2020)	**100.00%**	72.00%	58.62%	29.98%	63.70%	64.08%
Aidmix (2021)	**100.00%**	57.90%	45.80%	23.54%	51.96%	55.34%
TAIG (2022)	**100.00%**	54.32%	45.32%	28.52%	53.34%	55.18%
ILA++ (2022)	99.96%	74.94%	69.64%	41.56%	71.28%	71.84%
LGV (2022)	**100.00%**	89.02%	80.38%	45.76%	88.20%	87.18%
Ours	**100.00%**	**97.24%**	**95.48%**	**68.80%**	**97.10%**	**96.84%**

Method	SENet	ResNeXt	WRN	PNASNet	MNASNet	Average
I-FGSM	17.66%	26.18%	27.18%	12.80%	35.58%	27.69%
TIM (2019)	22.42%	32.04%	33.22%	21.04%	39.82%	33.94%
SIM (2020)	27.04%	41.28%	42.66%	21.74%	50.36%	41.69%
LinBP (2020)	41.02%	51.02%	54.16%	29.72%	62.18%	52.65%
Aidmix (2021)	30.20%	41.86%	42.76%	21.82%	52.26%	42.34%
TAIG (2022)	24.82%	38.36%	42.16%	17.20%	54.90%	41.41%
ILA++ (2022)	53.12%	65.92%	65.64%	44.56%	70.40%	62.89%
LGV (2022)	54.82%	71.22%	75.14%	46.50%	84.58%	72.28%
Ours	**81.40%**	**91.64%**	**93.26%**	**74.08%**	**95.66%**	**89.15%**

posterior concerned in the previous section is constructed using only a single model sampling, it can be readily combined with SWAG for further improving the diversity and adversarial transferability. Specifically, since $\mathbf{w}_{\text{SWA}}$ is unknown during training, we still optimize $\mathbf{w}_i$ and the same learning objective as in Section 3.2 can be derived. The dispersion of $\mathbf{w}$ then comes from two independent Gaussian and the variance matrices are added, *i.e.*, $\mathbf{w} \sim \mathcal{N}(\mathbf{w}_{\text{SWA}}, \boldsymbol{\Sigma}_{\text{SWAG}} + \beta\mathbf{I})$, where $\beta = \sigma^2$.

Figure 2 illustrates the attack performance when SWAG is further incorporated for approximating the posterior. It can be observed that our method still works favourably well, and further improvements can be achieved comparing to the results in Figure 1. Detailed attack success rates on each victim model are provided in Table 1. Conclusions on ImageNet are the same, see Appendix A. Therefore, without further clarification, we shall incorporate SWAG into our method in the following experiments considering the superior performance. Note that for SWAG without our possible finetuning, we estimate the mean and covariance in SWAG by finetuning using cross-entropy loss from the pre-trained model.

4 EXPERIMENTS

In this section, we evaluate the effectiveness of our method by comparing it to a bunch of recent state-of-the-arts.

4.1 EXPERIMENTAL SETTINGS

We tested untargeted ℓ_∞ attacks in the black-box setting, just like prior work (Dong & Yang, 2019; Lin et al., 2019; Wang et al., 2021; Guo et al., 2020; 2022). A bunch of methods were considered for comparison on CIFAR-10 (Krizhevsky & Hinton, 2009), and ImageNet (Russakovsky et al., 2015), using I-FGSM as the back-end method. On CIFAR-10, we set the perturbation budget to $\epsilon = 4/255$ and used ResNet-18 (He et al., 2016) as source model. While on ImageNet, the perturbation budget was set to $\epsilon = 8/255$ and used ResNet-50 (He et al., 2016) as the source model. For victim models on CIFAR-10, we chose a ResNet-18 (He et al., 2016), a VGG-19 with batch normalization (Simonyan & Zisserman, 2015), a PyramidNet (Han et al., 2017), GDAS (Dong & Yang, 2019), a WRN-28-10 (Zagoruyko & Komodakis, 2016), a ResNeXt-29 (Xie et al., 2017), and a DenseNet-

Table 3: Success rates of transfer-based attacks on CIFAR-10 using ResNet-18 as substitute architecture and I-FGSM as the back-end attack, under the ℓ_∞ constraint with $\epsilon = 4/255$ in the untargeted setting. "Average" was calculated over all six victim models except for ResNet-18. We performed 10 runs and report the average performance for each result in the table.

Method	ResNet-18	VGG-19	WRN	ResNeXt	DenseNet	PyramidNet	GDAS	Average
I-FGSM	**100.00%**	37.51%	57.01%	57.95%	52.84%	12.70%	40.32%	43.06%
TIM (2019)	**100.00%**	67.64%	84.51%	84.79%	79.07%	27.30%	65.49%	68.13%
SIM (2020)	**100.00%**	47.62%	64.62%	68.41%	62.43%	17.09%	44.46%	50.77%
LinBP (2020)	**100.00%**	58.43%	78.49%	81.10%	76.50%	27.20%	60.91%	63.77%
Aidmix (2021)	**100.00%**	49.17%	69.94%	69.95%	64.65%	16.90%	49.50%	53.35%
TAIG (2022)	**100.00%**	47.20%	59.70%	63.18%	56.83%	15.29%	43.92%	47.69%
ILA++ (2022)	**100.00%**	59.46%	78.03%	78.49%	74.91%	25.60%	59.11%	62.60%
LGV (2022)	**100.00%**	80.62%	92.52%	92.67%	90.44%	41.50%	77.28%	79.17%
Ours	**100.00%**	**85.10%**	**94.66%**	**94.95%**	**92.75%**	**48.93%**	**83.89%**	**83.38%**

BC (Huang et al., 2017) [1], following Guo et al. (2020; 2022)'s work. On ImageNet, ResNet-50 (He et al., 2016), VGG-19 (Simonyan & Zisserman, 2015), ResNet-152 (He et al., 2016), Inception v3 (Szegedy et al., 2016), DenseNet-121 (Huang et al., 2017), MobileNet v2 (Sandler et al., 2018), SENet-154 (Hu et al., 2018), ResNeXt-101 (Xie et al., 2017), WRN-101 (Zagoruyko & Komodakis, 2016), PNASNet (Liu et al., 2018), and MNASNet (Tan et al., 2019) were adopted as victim models [2]. Since these victim models may require different sizes of inputs, we strictly followed their official pre-processing pipeline to obtain inputs of specific sizes. For CIFAR-10 tests, we performed attacks on all test data. For ImageNet, we randomly sampled 5000 test images from a set of the validation data that could be classified correctly by these victim models, and we learned perturbations to these images, following prior work (Huang & Kong, 2022; Guo et al., 2020; 2022). For comparison, we evaluated attack success rates of adversarial examples crafted utilizing different methods on all victim models. Inputs to all models were re-scaled to $[0.0, 1.0]$. Temporary results after each attack iteration were all clipped to this range to guarantee the inputs to DNNs were close to valid images. When establishing a multi-step baseline using I-FGSM we run it for 20 iterations on CIFAR-10 data and 50 iterations on ImageNet data with a step size of $1/255$.

In possible finetuning, we set $\gamma = 0.1/\|\Delta\mathbf{w}^*\|_2$ and a finetuning learning rate of 0.05 if SWAG was incorporated. We set a smaller finetuning learning rate of 0.001 if it was not. On CIFAR-10, finetune without and with SWAG, we set $\lambda_{\varepsilon,\sigma} = 2$ and $\lambda_{\varepsilon,\sigma} = 0.2$, respectively. When performing attacks, we set $\sigma = 0.009$ and $\sigma = 0.002$ for source models finetuned without and with SWAG, respectively. On ImageNet, we always set $\lambda_{\varepsilon,\sigma} = 1$, and $\sigma = 0.005$ and $\sigma = 0.002$ for source models finetuned without and with SWAG, respectively. Since we found little difference in success rate between using diagonal matrix and diagonal matrix plus low rank matrix as the covariance for SWAG posterior, we always use the diagonal matrix for simplicity. For compared competitors, we followed their official implementations and evaluated on the same test images on CIFAR-10 and ImageNet for generating adversarial examples fairly. For TIM (Dong et al., 2019), we adopted the maximal shift of 3×3 and 7×7 on CIFAR-10 and ImageNet, respectively. For SIM (Lin et al., 2019), the number of scale copies is 5. For Aidmix (Wang et al., 2021), we set the number of scale copies and mix copies to 5 and 3, respectively, and let the mix coefficient be 0.2. For LinBP (Guo et al., 2020), the last six building blocks in ResNet-50 and the last four building blocks in Resnet-18 were modified to be more linear during backpropagation. For TAIG (Huang & Kong, 2022), we set 30 as the number of tuning points. For ILA++ (Li et al., 2020a; Guo et al., 2022), we chose the first block of the last meta-block of ResNet-18 and the first block of the third block of ResNet-50. All experiments are performed on an NVIDIA V100 GPU.

4.2 COMPARISON TO STATE-OF-THE-ARTS

We compare our method to recent state-of-the-arts in Table 2 and 3 on attacking 10 victim models on ImageNet and 6 victim models on CIFAR-10. Methods that increase input diversity, *i.e.*, and TIM (Dong et al., 2019), SIM (Lin et al., 2019), Aidmix (Wang et al., 2021), that modify back-propagation, *i.e.*, LinBP (Guo et al., 2020) and ILA++ (Guo et al., 2022), and very recent methods including TAIG (Huang & Kong, 2022) and LGV (Gubri et al., 2022b) are compared. It can be

---
[1] https://github.com/bearpaw/pytorch-classification
[2] https://pytorch.org/docs/stable/torchvision/models.html

observed in the tables that our method outperforms all these methods significantly. Specifically, our method achieves an average success rate of nearly 89.15% on ImageNet, which outperforms the second best by 16.87%. When attacking Inception v3 and PyramidNet, which are the most challenging victim models on ImageNet and CIFAR-10, respectively, out method outperforms the second best by 23.04% and 7.43% while outperforms the I-FGSM baseline by 53.20% and 36.23%.

Comparison to (more) ensemble attacks. From certain perspectives, our method shows a similar spirit to that of ensemble attacks, thus here we compare more such attacks (Liu et al., 2017; Xiong et al., 2022) empirically. Table 4 reports results of all methods under the ℓ_∞ constraint and $\epsilon = 8/255$. Our method taking ResNet-50 as the substitute architecture achieves an average success rate of 90.03% on ImageNet, while the two prior methods taking ResNet-50, Inception v3, MobileNet, and MNASNet altogether as substitute architectures achieve 46.58% and 57.52%. One may also utilize more than one architecture for our method, as a natural combination of our method and prior methods, see also Table 4 for results. We adopt ResNet-50 and MobileNet as substitute architectures when combine with the ensemble methods.

Table 4: Comparison to ensemble attacks on ImageNet under the ℓ_∞ constraint with $\epsilon = 8/255$. "Average" is obtained on all the 7 models. We performed 10 runs and report the average results.

Method	VGG-19	ResNet-152	DenseNet	SENet	ResNeXt	WRN	PNASNet	Average
Ensemble (2017)	63.68%	48.14%	56.42%	35.96%	45.36%	44.06%	32.46%	46.58%
SVRE (2022)	73.12%	60.00%	66.50%	46.44%	57.72%	55.80%	43.08%	57.52%
Ours	97.24%	95.48%	97.10%	81.40%	91.64%	93.26%	74.08%	90.03%
Ours + Ensemble	98.20%	95.58%	97.90%	83.38%	91.70%	93.84%	76.18%	90.97%
Ours + SVRE	**98.22%**	**96.00%**	**98.04%**	**84.38%**	**93.18%**	**94.06%**	**76.88%**	**91.54%**

Comparison to Gubri et al. (2022a)'s method. Gubri et al. (2022a)'s method suggested to collect multiple substitute models along a single run of training using cSGLD (Zhang et al., 2019). It is related to Bayesian learning in the regard that cSGLD is a Bayesian posterior sampling method. The difference between our method and Gubri et al.'s lie in two aspect. First, as have been demonstrated in Section 3.2, our method is capable of achieving superior transferability even without finetuning. Second, when finetuning is possible, our method focuses on learning an appropriate posterior during finetuning, and it starts sampling substitute models only after finetuning accomplishes. Thus, different sets of models can be sampled at different iteration of I-FGSM using our method, as if there exist infinitely many substitute models. Table 5 compares the two methods empirically and shows the superiority of our method. We followed their experimental settings to evaluate the methods and copy their results in the paper. More specifically, the back-end I-FGSM was perform with $\epsilon = 4/255$ and a step size of $\epsilon/10$ for 50 optimization steps in total. Victim models include ResNeXt-50, DenseNet-121, EfficientNet-B0 (Tan & Le, 2019), etc.

Table 5: Comparison to Gubri et al. (2022a)'s on ImageNet under the ℓ_∞ constraint with $\epsilon = 4/255$. We performed 10 runs and report the average performance for all our results.

Method	ResNet-50	ResNeXt-50	DenseNet	MNASNet	EfficientNet
Gubri et al. (2022a)'s	78.71%	65.11%	61.49%	51.81%	31.11%
Ours	**99.36%**	**77.38%**	**71.68%**	**73.00%**	**41.66%**

Attack robust models. It is also of interest to evaluate the transferability of adversarial examples to robust models, thus we further compare the performance of some competitive methods in this setting in Table 6. The victim models here include an Inception v3 and an EfficientNet-B0 collected from the timm (Wightman, 2019) repository and a ResNet-50 and a DeiT-S (Touvron et al., 2021a) provided by Bai et al. (2021). All these models were trained using adversarial training.

Attack vision transformers. The community has witnessed a surge of transformers in computer vision and machine learning applications. Here we also test the transferability of adversarial examples (generated on convolutional substitute architectures) to some vision transformers. Specifically, we tested with a ViT-B (Dosovitskiy et al., 2020), a DeiT-B (Touvron et al., 2021b), a Swin-B (Liu et al., 2021), and a BEiT(Bao et al., 2021). These models were all collected from timm (Wightman, 2019).

Results in Table 6 show that, though it is indeed more challenging to transfer to vision transformers, our method can also gain considerable improvements.

Table 6: Success rates of attacking vision transformers and adversarially trained models on ImageNet using ResNet-50 as the substitute architecture under the ℓ_∞ constraint with $\epsilon = 8/255$. We performed 10 runs and report the average results in the table.

Method	Vision transformers				Robust models			
	ViT-B	DeiT-B	Swin-B	BEiT	Inception v3	EfficientNet	ResNet-50	DeiT-S
I-FGSM	6.42%	6.44%	6.36%	3.50%	13.28%	11.64%	9.26%	10.68%
ILA++ (2022)	10.52%	19.26%	17.90%	10.22%	16.90%	23.96%	10.08%	11.08%
LGV (2022)	12.62%	18.68%	14.96%	10.58%	19.70%	32.78%	10.56%	11.50%
Ours	**19.18%**	**32.88%**	**24.32%**	**22.78%**	**23.20%**	**49.64%**	**11.02%**	**12.02%**

4.3 COMBINATION WITH OTHER METHODS

We would also like to mention that it is also possible to combine our method with some methods in Table 2 to further enhance the transferability, since our method focuses on model diversity and does not consider improvement in input diversity and backpropagation. In Table 7, we report the attack success rate of our method, in combination with Aidmix, LinBP, and ILA++. It can be seen that the transferability to all victim models are further enhanced. The best performance is obtained when combined with ILA++, leading to an average success rate achieve of 92.90% (which is roughly 30% higher than the original performance of ILA++) and a worst success rate of only 81.64% (when attacking PNASNet).

Table 7: Combining our method with recent state-of-the-arts in Table 2 on ImageNet, The experiment was perfomred under the ℓ_∞ constraint with $\epsilon = 8/255$. We performed 10 runs and report the average results in the table.

	Aidmix		LinBP		ILA++	
	-	+ Ours	-	+ Ours	-	+ Ours
ResNet-50	**100.00%**	**100.00%**	**100.00%**	**100.00%**	99.96%	**100.00%**
VGG-19	57.90%	**97.44%**	72.00%	**97.88%**	74.94%	**98.20%**
ResNet-152	45.80%	**96.24%**	58.62%	**95.18%**	69.64%	**96.30%**
Inception v3	23.54%	**73.60%**	29.98%	**77.10%**	41.56%	**84.10%**
DenseNet	51.96%	**97.84%**	63.70%	**97.78%**	71.28%	**98.18%**
MobileNet	55.34%	**97.60%**	64.08%	**97.22%**	71.84%	**98.12%**
SENet	30.20%	**84.26%**	41.02%	**84.12%**	53.12%	**86.20%**
ResNeXt	41.86%	**92.98%**	51.02%	**90.50%**	65.92%	**93.48%**
WRN	42.76%	**94.22%**	54.16%	**93.24%**	65.64%	**95.04%**
PNASNet	21.82%	**75.88%**	29.72%	**74.14%**	44.56%	**81.64%**
MNASNet	52.26%	**97.24%**	62.18%	**96.04%**	70.40%	**97.78%**
Average	42.34%	**90.73%**	52.65%	**90.32%**	62.89%	**92.90%**

5 CONCLUSION

In this paper, we have considered diversity in substitute models for performing transfer-based attacks. Specifically, we have developed a Bayesian formulation for performing attacks and advocated possible finetuning for improving the Bayesian model. By simply assuming the posterior to be an isotropic Gaussian distribution or, one step further, a more general Gaussian distribution, our attack can be equivalently regarded as generating adversarial examples on a set of infinitely many substitute models while the time complexity of possible finetuning is just as normal. Extensive experiments have been conducted to demonstrate the effectiveness of our method on ImageNet and CIFAR-10. It has been shown our method outperforms recent state-of-the-arts by large margins in attacking more than 10 convolutional DNNs and 4 vision transformers. The transferability to robust models has also been evaluated. Moreover, we have also shown that the proposed method can further be combined with prior methods to achieve even more powerful adversarial transferability.

REFERENCES

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *ICML*, 2018.

Yutong Bai, Jieru Mei, Alan Yuille, and Cihang Xie. Are transformers more robust than cnns? In *Thirty-Fifth Conference on Neural Information Processing Systems*, 2021.

Hangbo Bao, Li Dong, Songhao Piao, and Furu Wei. Beit: Bert pre-training of image transformers. In *International Conference on Learning Representations*, 2021.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural network. In *International conference on machine learning*, pp. 1613–1622. PMLR, 2015.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *IEEE Symposium on Security and Privacy (SP)*, 2017.

Xuanyi Dong and Yi Yang. Searching for a robust neural architecture in four gpu hours. In *CVPR*, 2019.

Yinpeng Dong, Tianyu Pang, Hang Su, and Jun Zhu. Evading defenses to transferable adversarial examples by translation-invariant attacks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4312–4321, 2019.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Michael Dusenberry, Ghassen Jerfel, Yeming Wen, Yian Ma, Jasper Snoek, Katherine Heller, Balaji Lakshminarayanan, and Dustin Tran. Efficient and scalable bayesian neural nets with rank-1 factors. In *International conference on machine learning*, pp. 2782–2792. PMLR, 2020.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pp. 1050–1059. PMLR, 2016.

Yarin Gal, Jiri Hron, and Alex Kendall. Concrete dropout. *Advances in neural information processing systems*, 30, 2017.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *ICLR*, 2015.

Alex Graves. Practical variational inference for neural networks. *Advances in neural information processing systems*, 24, 2011.

Martin Gubri, Maxime Cordy, Mike Papadakis, Yves Le Traon, and Koushik Sen. Efficient and transferable adversarial examples from bayesian neural networks. In *Uncertainty in Artificial Intelligence*, pp. 738–748. PMLR, 2022a.

Martin Gubri, Maxime Cordy, Mike Papadakis, Yves Le Traon, and Koushik Sen. Lgv: Boosting adversarial example transferability from large geometric vicinity. *arXiv preprint arXiv:2207.13129*, 2022b.

Yiwen Guo, Qizhang Li, and Hao Chen. Backpropagating linearly improves transferability of adversarial examples. In *NeurIPS*, 2020.

Yiwen Guo, Qizhang Li, Wangmeng Zuo, and Hao Chen. An intermediate-level attack framework on the basis of linear regression. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2022.

Dongyoon Han, Jiwhan Kim, and Junmo Kim. Deep pyramidal residual networks. In *CVPR*, pp. 5927–5935, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *CVPR*, 2018.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *CVPR*, 2017.

Qian Huang, Isay Katsman, Horace He, Zeqi Gu, Serge Belongie, and Ser-Nam Lim. Enhancing adversarial example transferability with an intermediate level attack. In *ICCV*, 2019.

Yi Huang and Adams Wai-Kin Kong. Transferable adversarial attack based on integrated gradients. *arXiv preprint arXiv:2205.13152*, 2022.

Pavel Izmailov, Dmitrii Podoprikhin, Timur Garipov, Dmitry Vetrov, and Andrew Gordon Wilson. Averaging weights leads to wider optima and better generalization. *arXiv preprint arXiv:1803.05407*, 2018.

Rie Johnson and Tong Zhang. Accelerating stochastic gradient descent using predictive variance reduction. *Advances in neural information processing systems*, 26, 2013.

Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? *Advances in neural information processing systems*, 30, 2017.

Mohammad Khan, Didrik Nielsen, Voot Tangkaratt, Wu Lin, Yarin Gal, and Akash Srivastava. Fast and scalable bayesian deep learning by weight-perturbation in adam. In *International Conference on Machine Learning*, pp. 2611–2620. PMLR, 2018.

Durk P Kingma, Tim Salimans, and Max Welling. Variational dropout and the local reparameterization trick. *Advances in neural information processing systems*, 28, 2015.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526, 2017.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial machine learning at scale. In *ICLR*, 2017.

David X Li. On default correlation: A copula function approach. *The Journal of Fixed Income*, 9 (4):43–54, 2000.

Qizhang Li, Yiwen Guo, and Hao Chen. Yet another intermediate-leve attack. In *ECCV*, 2020a.

Yingwei Li, Song Bai, Yuyin Zhou, Cihang Xie, Zhishuai Zhang, and Alan Yuille. Learning transferable adversarial examples via ghost networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 11458–11465, 2020b.

Jiadong Lin, Chuanbiao Song, Kun He, Liwei Wang, and John E Hopcroft. Nesterov accelerated gradient and scale invariance for adversarial attacks. *arXiv preprint arXiv:1908.06281*, 2019.

Chenxi Liu, Barret Zoph, Maxim Neumann, Jonathon Shlens, Wei Hua, Li-Jia Li, Li Fei-Fei, Alan Yuille, Jonathan Huang, and Kevin Murphy. Progressive neural architecture search. In *ECCV*, 2018.

Yanpei Liu, Xinyun Chen, Chang Liu, and Dawn Song. Delving into transferable adversarial examples and black-box attacks. In *ICLR*, 2017.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 10012–10022, 2021.

Wesley Maddox, Shuai Tang, Pablo Moreno, Andrew Gordon Wilson, and Andreas Damianou. Fast adaptation with linearized neural networks. In *International Conference on Artificial Intelligence and Statistics*, pp. 2737–2745. PMLR, 2021.

Wesley J Maddox, Pavel Izmailov, Timur Garipov, Dmitry P Vetrov, and Andrew Gordon Wilson. A simple baseline for bayesian uncertainty in deep learning. *Advances in Neural Information Processing Systems*, 32, 2019.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *ICLR*, 2018.

Stephan Mandt, Matthew D Hoffman, and David M Blei. Stochastic gradient descent as approximate bayesian inference. *arXiv preprint arXiv:1704.04289*, 2017.

Kazuki Osawa, Siddharth Swaroop, Mohammad Emtiyaz E Khan, Anirudh Jain, Runa Eschenhagen, Richard E Turner, and Rio Yokota. Practical deep learning with bayesian principles. *Advances in neural information processing systems*, 32, 2019.

Nicolas Papernot, Patrick McDaniel, and Ian Goodfellow. Transferability in machine learning: from phenomena to black-box attacks using adversarial samples. *arXiv preprint arXiv:1605.07277*, 2016.

Hippolyt Ritter, Aleksandar Botev, and David Barber. A scalable laplace approximation for neural networks. In *6th International Conference on Learning Representations, ICLR 2018-Conference Track Proceedings*, volume 6. International Conference on Representation Learning, 2018.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. Imagenet large scale visual recognition challenge. *IJCV*, 2015.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *CVPR*, 2018.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *ICLR*, 2015.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *ICLR*, 2014.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *CVPR*, 2016.

Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International conference on machine learning*, pp. 6105–6114. PMLR, 2019.

Mingxing Tan, Bo Chen, Ruoming Pang, Vijay Vasudevan, Mark Sandler, Andrew Howard, and Quoc V Le. Mnasnet: Platform-aware neural architecture search for mobile. In *CVPR*, 2019.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, pp. 10347–10357. PMLR, 2021a.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Herve Jegou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, volume 139, pp. 10347–10357, July 2021b.

Xiaosen Wang, Xuanran He, Jingdong Wang, and Kun He. Admix: Enhancing the transferability of adversarial attacks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 16158–16167, 2021.

Ross Wightman. Pytorch image models. `https://github.com/rwightman/pytorch-image-models`, 2019.

Andrew G Wilson and Pavel Izmailov. Bayesian deep learning and a probabilistic perspective of generalization. *Advances in neural information processing systems*, 33:4697–4708, 2020.

Anqi Wu, Sebastian Nowozin, Edward Meeds, Richard E Turner, Jose Miguel Hernandez-Lobato, and Alexander L Gaunt. Deterministic variational inference for robust bayesian neural networks. *arXiv preprint arXiv:1810.03958*, 2018.

Dongxian Wu, Yisen Wang, Shu-Tao Xia, James Bailey, and Xingjun Ma. Rethinking the security of skip connections in resnet-like neural networks. In *ICLR*, 2020.

Cihang Xie, Zhishuai Zhang, Yuyin Zhou, Song Bai, Jianyu Wang, Zhou Ren, and Alan L Yuille. Improving transferability of adversarial examples with input diversity. In *CVPR*, 2019.

Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *CVPR*, 2017.

Yifeng Xiong, Jiadong Lin, Min Zhang, John E Hopcroft, and Kun He. Stochastic variance reduced ensemble adversarial attack for boosting the adversarial transferability. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14983–14992, 2022.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *BMVC*, 2016.

Guodong Zhang, Shengyang Sun, David Duvenaud, and Roger Grosse. Noisy natural gradient as variational inference. In *International Conference on Machine Learning*, pp. 5852–5861. PMLR, 2018.

Ruqi Zhang, Chunyuan Li, Jianyi Zhang, Changyou Chen, and Andrew Gordon Wilson. Cyclical stochastic gradient mcmc for bayesian deep learning. In *International Conference on Learning Representations*, 2019.

A PERFORMANCE OF POSSIBLE FINETUNE ON IMAGENET

Table 8: Comparing transferability of FGSM and I-FGSM adversarial examples generated on a deterministic substitute model and the Bayesian substitute model (with and without additional fine-tuning) under the ℓ_∞ constraint with $\epsilon = 4/255$ on CIFAR-10. The architecture of the substitute models is ResNet-18, and "Average" was calculated over all six victim models except for ResNet-18. We performed 10 runs of the experiment and report the average performance in the table.

		fine-tune	ResNet-50	VGG-19	ResNet-152	Inception v3	DenseNet	MobileNet
FGSM	-	✗	87.68%	34.40%	27.06%	21.46%	34.38%	36.88%
	Isotropic	✗	95.48%	47.70%	39.18%	31.94%	48.52%	49.14%
		✓	98.30%	67.56%	58.40%	47.26%	68.74%	68.42%
	+SWAG	✗	94.38%	72.00%	58.42%	48.48%	71.06%	73.38%
		✓	96.88%	78.14%	65.52%	55.48%	77.90%	79.06%
I-FGSM	-	✗	100.00%	39.22%	29.18%	15.60%	35.58%	37.90%
	Isotropic	✗	100.00%	55.22%	45.42%	22.94%	50.14%	51.42%
		✓	100.00%	87.82%	81.74%	45.14%	86.18%	85.18%
	+SWAG	✗	100.00%	84.92%	76.54%	43.26%	83.84%	82.92%
		✓	100.00%	97.24%	95.48%	68.80%	97.10%	96.84%

		fine-tune	SENet	ResNeXt	WRN	PNASNet	MNASNet	Average
FGSM	-	✗	17.84%	24.46%	24.78%	15.50%	34.40%	27.12%
	Isotropic	✗	27.32%	36.60%	36.88%	24.12%	45.98%	38.74%
		✓	41.52%	52.96%	55.50%	38.24%	65.54%	56.41%
	+SWAG	✗	37.94%	49.58%	53.40%	35.68%	69.74%	56.97%
		✓	45.16%	57.70%	61.12%	42.78%	76.10%	63.90%
I-FGSM	-	✗	17.66%	26.18%	27.18%	12.80%	35.58%	27.69%
	Isotropic	✗	29.12%	39.76%	41.12%	21.16%	48.94%	40.52%
		✓	61.74%	75.48%	78.04%	51.82%	82.94%	73.61%
	+SWAG	✗	50.94%	67.12%	71.92%	40.96%	81.00%	68.34%
		✓	81.40%	91.64%	93.26%	74.08%	95.66%	89.15%