Explainability Via Causal Self-Talk

Abstract

Explaining the behavior of AI systems is an important problem that, in practice, is generally avoided. While the XAI community has been developing an abundance of techniques, most incur a set of costs that the wider deep learning community has been unwilling to pay in most situations. We take a pragmatic view of the issue, and define a set of desiderata that capture both the ambitions of XAI and the practical constraints of deep learning. We describe an effective way to satisfy all the desiderata: train the AI system to build a causal model of itself. We develop an instance of this solution for Deep RL agents: Causal Self-Talk. CST operates by training the agent to communicate with itself across time. We implement this method in a simulated 3D environment, and show how it enables agents to generate faithful and semantically-meaningful explanations of their own behavior. Beyond explanations, we also demonstrate that these learned models provide new ways of building semantic control interfaces to AI systems.

1 Introduction

As modern machine learning systems become more powerful and embedded in our lives, the need to have these systems explain their behavior becomes increasingly urgent. Despite incredible performance in a variety of domains, almost all systems are completely unable to provide a satisfying answer to the simple question, "Why did you do that?".

While there have been innovations in particular explainability methods [e.g. 8, 55, 56, 66], and some attempts to apply techniques to domains that demand it [e.g. 23, 65], the vast majority of deep learning applications do not engage with these techniques. This is in part because there are few general methods, and most incur costs such as reduced performance and scalability; compounding this, existing techniques often fail to deliver a useful or credible account of the systems' behavior.

We believe that the reason for this is that explanation systems tend to fail to satisfy at least one of a number of key desiderata. Two particular failure modes are most common: the addition of an explanation system limits generality or hurts performance (e.g. when it requires explicitly structuring the base system); or the explanations it produces cannot be trusted to be accurate (e.g. with many external or post-hoc methods). An ideal explanation system would avoid both these pitfalls.

In this paper, we propose one such solution. We take a pragmatic viewpoint that providing explanations of a system's behavior is, in essence, a task of building a *model* of that system. We argue that only the AI system itself is capable of supplying a model that fulfills all the key desiderata. We thus train the base system to supply a "self-model" alongside its main representations. Importantly, the base system and self-model are subject to different constraints: we want the base system to be primarily optimized for performance, while we want the self-model to take on a faithful, semantically-interpretable form. The different form allows the self-model to deliver supplementary utility that the base system does not, e.g. providing an interface to external users, and enabling them to understand, predict, and control the base system in convenient ways.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Our contributions are as follows. In Section 2, we articulate five key desiderata for explanation systems. However, there is some tension between these. In Section 3, we describe how common historical XAI techniques resolve these trade-offs by making extreme choices between the desiderata. In Section 4, we demonstrate that a balance can be found between the five desiderata by training AI systems to build self-models. In particular, we introduce a solution concept for Deep RL agents: Casual Self-Talk (CST). In Sections 5-6 we show that CST allows model-free RL agents in an embodied 3D virtual environment to faithfully explain their behavior in terms of semantically-accessible beliefs about the state of the world.

2 Desiderata for explanatory models

Our goal is to build an explanatory model of an AI system, i.e. a mechanism that translates between its internal representations and/or computations, and some other representational form. We set out five key desiderata for such a model:

Grounded. For the model to be useful to external users, it should deploy a representation language that is semantically-grounded. This may require additional data to train.

Flexible. The method should be able to produce models of many different representational forms (e.g. classes, graphs, strings). Ideally it should also be sufficiently general to be agnostic to the base system's input/output modalities, and possibly even its overall architecture.

Minimally-interfering. Training and inference on the model should have as little impact as possible on the training and inference of the base system. Solutions which are disruptive to performance are highly unlikely to be adopted in practice.

Scalable. Once a solution is found, it should be straightforward to apply it to any network.

Faithful. The model should give accurate, factual, and truthful descriptions of the underlying system. The gold standard is that it is a *causal model* of the agent, facilitating validation through interventions [38]. This is possibly the most challenging to achieve.

A number of past works have also articulated desirable properties for explanations [e.g. 28, 35, 36, 38, 49, 53, 69].[1] Our desiderata focus less on the qualities which constitute a good explanation per se, but instead on what is desired of the method itself that generates the explanation.

3 Common historical solutions

We examine whether various existing explanation techniques satisfy each of these desiderata.

Attribution methods. A set of popular techniques attempts to model a neural network's decision-making at the input level, by estimating contributions to its output from input features [e.g. 18, 27, 56], or training examples [e.g. 6, 14, 42, 43, 46, 71], or by finding optimal inputs for a given output [e.g. 55, 73]. Such approaches benefit from being minimally-interfering (they are entirely post-hoc) and scalable (they can be automated). However, some methods have been empirically shown to be unfaithful [2, 7], while methods which explicitly aim for faithfulness such as LIME [13] and Anchors [60] are only local in scope, and are expensive to scale. Most importantly, all such methods sacrifice flexibility: one is constrained to produce explanations of a very particular form, e.g. expressed in terms of the input modality, whose interpretation may be highly subjective.

Explicitly structuring networks. A sub-field of deep learning has emerged wherein the inter-mediate computations are constrained to particular forms, and/or are grounded by external data [e.g. 5, 10, 16, 23, 25, 47, 62, 63, 72]. As explanations of behavior, structured intermediates are attractive as they are both grounded and faithful by design. However, this is achieved at the expense of minimal-interference, as it requires fundamentally altering the base system to explicitly depend on this structure. It is also limited in flexibility and scalability, as the technique can also only be applied

---

[1]Note that some terms, such as 'faithfulness', do not have standard definitions across this literature [35].

when sufficient domain knowledge or data is available, and only in the form dictated by these prior constraints. These issues are exacerbated by the fact that the representations required to optimize performance objectives are often at odds with those that would subserve explainability.

Fine-grained mechanistic interpretability. One common approach is to allow a base system to train and run *au naturel*, and to post-hoc dissect its representations or computations, often using techniques borrowed or inspired from neuroscience [e.g. 17, 21, 26, 57]. Such approaches champion the minimal-interference desideratum. In the best case, they promise to uncover faithful descriptions of the actual causal processes operating within the base system. However, this comes at a huge cost to scalability. Many human hours are typically expended in reverse engineering, often yielding results that are limited to a handful of neurons or circuits seen in a single network. Moreover, by making strong commitments to respect the internal representations of the base system, it is very difficult to ground the models that arise, let alone to flexibly choose the form they take.

Decoders. Decoders can be viewed as trained tools to map from the internal private language of a base system to an interpretable representation space [e.g. 4, 11, 15, 31–33, 44, 52, 58, 74]. This approach has many attractive qualities: it produces semantically-grounded representations of the base system's internal private language; is flexible in the choice of modality; scales well; and is minimally-interfering, insofar as decoders can be separated from the inference path of the main computational graph and gradients can be stopped from propagating to the base system if desired (though are often not to assist representation learning, [e.g. 3, 37, 40, 48, 54]). This is all achieved, however, at the expense of faithfulness, as decoded outputs are off the causal path of the base system [47]. Decoders just report whether information is *present* in the source representation, not whether that information is actually being *used* for behavior [12, 20, 59]. Similar faithfulness issues arise with post-hoc behavioral analyses [e.g. 19, 30, 39, 50, 66, 70].

4 Solution concept

The challenges faced by previous attempts at explainability show that the tensions between the desiderata are considerable. It is nonetheless possible to reason a way forward.

First, we want a description of the base system that is both grounded and flexible. The internals of the base system are neither. While we could explicitly structure the base system to change this, this would violate the minimal interference desideratum. Thus we need *a model* of the base system. Second, the solution must be scalable. This means we cannot rely on human labor to map from the base system's representations to the model's representations. The only scalable approach is to *learn the model*. Third, the solution must be faithful. Our gold standard of faithfulness requires the ability to validate the model by intervening on it. To do this, one must be able to map in the opposite direction: from interventions on the model onto interventions on the base system. Because both the base system and the model are learned, so this mapping must be learned as well. The most direct way of learning this mapping is to *feed the model's outputs as inputs* back into the base system.

A solution to these problems is thus a "self-model" which is intertwined with the base system. It is built *of the base system*, *by the base system*, and *for the base system*.

We develop an instance of this solution in a particular setting: a Deep RL agent, acting in an episodic POMDP, which builds a model of itself in terms of a set of semantically-grounded beliefs about the state of the world. We consider how to expand the scope of this technique in Section 7.

We follow the standard construction of a POMDP. We denote the agent's observation at time t within an episode as x_t, and assume that it maintains an internal state m_t, which we can take to be, for example, a recurrent state (such as from an LSTM), or a variable-length array of embeddings of previous observations $x_{0:t}$ (as used in a Transformer). We denote the agent's state update function as f_θ, with learned parameters, θ, s.t. $m_{t+1} = f_\theta(x_{t+1}, m_t)$. We denote its policy as $\pi_t = h_\theta(m_t)$.

Our construction starts with a decoder, shown in Figure 1a. A decoder maps from the state m_t to an output $z_t \sim q(z_t)$, via a learned function $g_\theta : m_t \to q(z_t)$. This mapping is trained using target data $\hat{z} \in \mathcal{D}_z$ that lives in a semantically-meaningful space. As we previously identified in Section 3, decoders benefit from being grounded, flexible, scalable, and minimally-interfering. However, their weakness is faithfulness. This is because the output z_t merely reflects what information is present in m_t, and not whether that information is actually used in the computation of π_t.

true, online counterfactual

(a) Ordinary decoder. (b) Re-routed decoder. (c) Causal Self-Talk (CST).

Figure 1: **Architectures.** **(a)** Decoders offer a common and simple solution to modeling a base system, albeit one that lacks faithfulness. **(b)** Re-routing the output of a decoder back into the base system is not sufficient to remedy this. **(c) The Causal Self-Talk (CST) architecture.** This objective requires the decoder output (z_t) to efficiently communicate the contents of the current internal state (m_t) to an earlier state in the same episode ($m_{t'}$). Black denotes the true online inputs, states, and outputs; dashed lines indicate that the true message z_t and next observation x_{t+1} are provided to the earlier state of the agent, shown in blue. The red denotes the result of this counterfactual intervention.

134 We now chart a path forward from decoders, with an aim of making them faithful. To do so, we first
135 define two metrics for faithfulness, one weak, one strong:

136   **Correlational faithfulness:** if the decoder reports a value of $z_t = z$, to what degree is the
137   behavior (from the policy π) *consistent* with this value, z?

138   **Causal faithfulness:**[2] if we were to counterfactually *intervene* on z_t, changing it to a value
139   of z', to what degree would this produce behavior consistent with this new value, z', rather
140   than its original value, z?

141 Causal faithfulness is a much stronger property than correlational faithfulness. It's highly desirable
142 because it allows one to validate the agent's commitment to the value of z_t at runtime by making
143 interventions on it. This validation mechanism is especially useful when out of distribution.

144 **Re-routed decoders.** While it is possible for a decoder to have a degree of correlational faithfulness,
145 it is structurally impossible for it to exhibit causal faithfulness. A simple fix is to route the output of
146 the decoder back into the internal representation (Figure 1b), e.g. by concatenating z_t with x_{t+1}. This
147 amounts to incorporating the decoder output in the state update rule, with $m_{t+1} = f_\theta([x_{t+1}, z_t], m_t)$.

148 The difficulty with this simple solution is that there is no guarantee that f_θ will actually "listen" to z_t
149 when producing m_{t+1}. This is because the information in z_t is largely if not completely redundant
150 with m_t. This may be further exacerbated by the presence of any stochastic sampling in the generation
151 of z_t from m_t. Indeed, as shall be described in Section 6, our experiments find that re-routed decoders
152 make no measurable progress beyond ordinary decoders on causal faithfulness.

153 How do we render the function f_θ sensitive to the value of z, when there is redundancy between z_t
154 and m_t? It is useful to frame the problem in terms of communication. The decoder pathway can be
155 viewed as a (externally-grounded) communication channel between the internal state and itself, i.e.
156 a form of "self-talk" or "inner speech" [67]. The problem therein is that the speaker (m_t) and the
157 listener (also m_t) are identical, so there is no useful information in the message z_t for the listener.

158 **Causal self-talk.** To overcome this problem, we need to create an information asymmetry between
159 speaker and listener. We introduce *Causal Self-Talk* (CST): we encourage f_θ to be sensitive to
160 the message z_t by creating an augmented data distribution where the speaker and listener diverge.
161 Fortunately, we have a ready source of alternate listeners: internal states $m_{t'}$ for $t' < t$.

162 We thus provide the decoder output with an additional role: to compactly and effectively communicate
163 information to *earlier versions of the same agent* (from the same episode), via a semantically-
164 grounded communication channel. Formally, this takes the form of an intervention (Figure 1c):
165 the internal state, m_t, is replaced with a counterfactual one, $m_{t'}$, before being integrated with the
166 original message (z_t) and next observation (x_{t+1}), in order to produce a counterfactual internal state,
167 $m_{t+1}^{(t \leftarrow t')} = f_\theta([x_{t+1}, z_t], m_{t'})$. This yields a counterfactual policy, $\pi_{t+1}^{(t \leftarrow t')} = h_\theta(m_{t+1}^{(t \leftarrow t')})$.

---

[2]Our use of this term is distinct from the "causal faithfulness condition" in causal modelling [64].

This alone, however, is insufficient to fully specify a CST algorithm. We must also stipulate the desired outcome from enacting these interventions. We describe three alternative choices:

CST-RL: The messages z_t should allow earlier versions of the same agent to maximize return given the current environment state. To train this, interventions must occur online (according to some schedule), and we must allow the agent to act according to the counterfactual policy following an intervention. We then use the maximization of subsequent discounted reward as the desired outcome from the intervention, via reinforcement learning (RL).

CST-MR: The messages z_t should allow earlier versions of the same agent to reconstruct the next internal state, m_{t+1}. Unlike CST-RL, this can be done entirely in replay, without requiring the agent to ever act according to the counterfactual policy on a live environment. We add a weighted memory reconstruction (MR) term to the overall loss: $\mathcal{L}_{MR} = ||m_{t+1}^{(t \leftarrow t')} - m_{t+1}||^2$.

CST-PD: The messages z_t should allow earlier versions of the same agent to recover the true current (and future) policy. As with CST-MR, interventions can be simulated entirely in replay. We add a weighted policy distillation (PD) term to the overall loss, using discounting function $\gamma(\cdot)$: $\mathcal{L}_{PD} = \sum_{\Delta t > 0} \gamma(\Delta t) \cdot D_{KL}\left(\pi_{t+\Delta t} \,||\, \pi_{t+\Delta t}^{(t \leftarrow t')} \right)$.

CST and the five desiderata. CST offers a different, less extreme tradeoff between the desiderata. Like ordinary decoders, CST can achieve grounding by supervising the representations z against a signal of known semantics. It is also equally flexible. Relative to ordinary decoders, there is some trade-off with minimal-interference, insofar as the decoder output z_t is now an obligate input into the next time step. However, much like ordinary decoders, the effects on training can, in principle, be contained through appropriate gradient flow, e.g. by limiting updates to parameters of the state update function, f_θ. It may also be possible to fine-tune a pre-existing base system.

CST is highly scalable. CST-RL is straightforward to implement; in its simplest incarnation, fixing $t' = 0$ reduces to dropout on the whole internal state, m_t. The use of RL, however, occurs at the expense of additional data as it requires online execution of the counterfactual policy. CST-PD and CST-MR, in contrast, are entirely self-supervised: they make use of the existing trajectories generated during the training of the base system. These methods augment the data in a manner similar to the interchange intervention technique of [25], using self-imitation as the desired outcome of the intervention. Depending on the degree of non-stationarity afforded by the particular environment (and its degree of partial observability), the size of the augmented dataset can scale quadratically with the length of each episode (from choosing both t and t'); in some settings, it may be possible to exceed this by sampling counterfactual previous states $m_{t'}$ from other episodes.

Finally, unlike ordinary decoders, CST is explicitly trained to provide causal faithfulness, by facilitating counterfactual control. We test the efficacy of this in the following section.

5 Experiments

Task. We study variants of CST in a 3D virtual environment built in Unity [1, 68]. This features a fixed-layout indoor space comprising five rooms, each with a different wall color. The agent receives as input a 1st-person visual observation and a text observation. The agent can freely navigate using a 4D continuous action space ($a \in [-1, 1]^4$) consisting of in-plane movements and a 2-DOF rotation.

We developed a simple task in this environment, called **DaxDucks** (Figure 2). We designed DaxDucks to: (1) be easy for an agent to learn a good policy; (2) require an agent to maintain and update beliefs about the latent environment state in order to maximize reward; (3) provide a source of data to ground the self-model; and (4) provide a means to evaluate the faithfulness of the learned self-model.

DaxDucks is an instruction-based, fast-binding search task, where the agent is rewarded for finding a duck that exhibits an instructed tag. Each episode consists of a sequence of trials. At the beginning of each trial, the agent's avatar spawns in the center of the middle room facing a random direction. Four identical ducks spawn at the center of the four outer rooms. Each duck is randomly assigned one of four tags ("`dax`", "`gavagai`", "`kleeg`", or "`plork`"). The agent is instructed to collect (i.e. collide with) the duck with a specified tag via the text observation channel, e.g. "`Collect a gavagai.`" The agent may observe a duck's tag by entering the duck's room and orienting the center of its view

Figure 2: The **DaxDucks** task. Top-down views are for exposition only.

towards the duck. This adds an additional string to the text observation, e.g. "`This is a kleeg.`".
Colliding with *any* duck terminates the current trial, in which case the agent is respawned in the center
of the middle room again and a random new instruction is delivered; a reward is also delivered if the
agent collided with the correct duck. Finally, when a new trial starts, the ducks usually maintain their
tags, but with a small probability ($p_{sh} = 0.1$), the tags are randomly shuffled between the ducks. Thus
the agent can only maximize reward by effectively retaining a belief state over which tag belongs to
which duck. Each episode lasts for 5000 steps regardless of the number of trials completed.

Agent architecture. For the base system, we used a standard model-free agent architecture. We
encode inputs with a ResNet (images) and an LSTM (text); we use an LSTM memory module and
MLPs for the policy and value heads; and we trained with V-trace [22]. All agents achieved a similarly
high return after training. Full details are in Appendix A.

We demonstrate the flexibility of grounding by considering two forms for the self-model:

One-hot. The message z_t takes the form of a set of four one-hot vectors (one per tag),
expressing which room the agent believes each tag to be in.

Language. The message z_t takes the form of a synthetic language string, expressing which
room the agent believes a single chosen tag to be in.

For the one-hot form (Section 6), we parameterize $q(z_t) = \prod_{\tau=1}^{4} q(z_t^\tau)$ as a product of independent
categorical distributions $q(z_t^\tau)$ for the four tags τ, with g_θ (an MLP) outputting the parameters of each
$q(z_t^\tau)$ at time t, and a sample $z \sim q(z_t)$ concatenated with the encoded input at the next time step.
For the language form (Section 6), we use an LSTM for g_θ, sampling z_t directly. Examples from a
single trajectory are shown in Figure 3a (one-hot) and Figure 4a (language). We ground both forms
of self-model by supervising z_t against ground-truth values. For the language form, this amounts to
constructing a target $\hat{z}_t$ of the form: "`The <instructed tag> is in the <color> room.`".

Given the simplicity of the environment, we implement all three CST algorithms using $t' = 0$
throughout. This means that CST aims to drive the decoder to communicate its beliefs to the earlier
version of the agent from the start of the episode. Although this reduces the scale of data augmentation
from quadratic to linear, and requires interventions on z to be accompanied by a reset of the memory
state to m_0, in return it makes it easier to measure the effects of interventions on the agent's behavior.

We used the following schedules for interventions at training time. For CST-RL, interventions
($m_t \leftarrow m_0$) occurred randomly, with probability $p = 0.03$ that an intervention would occur at any
given timestep t. For CST-MR, we simulated interventions in replay at every timestep. For CST-PD,
we simulated interventions in replay: we divided every trajectory into a sequence of blocks of variable
duration, with a $p = 0.03$ probability that a new block would start at any time t; we computed $\mathcal{L}_{PD}$
only up to a horizon of the end of the block, and with a constant discounting function, $\gamma(\Delta t) = 1$.

(a) Example one-hot messages from a CST-RL agent.

(b) Faithfulness results.

Figure 3: **One-hot-based self-talk. (a) Example messages during a trajectory.** Top-down view (left), agent view (middle), and $q(z_t)$ (right) during a trajectory of DaxDucks, showing the updating of $q(z_t)$ after the start of a new trial (second row) and after discovering the tags have been shuffled (third row). At each time point, the message z_t is sampled from $q(z_t)$. **(b) CST renders the decoder causally faithful.** Average values across $5 \le N \le 10$ training runs per method; error bars show 95% confidence intervals. Dashed lines indicate faithfulness expected from random messages.

6 Results

One-hot self-talk. We start by considering the one-hot form for the messages z (Figure 3a). We compare CST against two baselines: the ordinary decoder (**Ord-Dec**; Figure 1a) and the re-routed decoder (**RR-Dec**; Figure 1b). We focus on the metrics of faithfulness previously introduced.

Correlational faithfulness. When no interventions are taking place, is the agent's physical behavior congruent with the output of its self-model? To measure this, we filter to all times in evaluation episodes when the agent's avatar is in the central room. We then determine the degree to which the belief attested in $q(z_t)$ matches the *next-visited* room, r (whether or not the instructed tag is actually in r). For the one-hot message form, this amounts to reading off the value of $q(z_t^\tau = r)$ for the instructed tag τ.

Causal faithfulness. When we intervene on z_t, is the agent's subsequent physical behavior congruent with this new value? To measure this, we run evaluation episodes where, at the start of each trial, we inject a message z' indicating that the instructed tag is in some random room r'. We then measure the probability that the agent actually visits room r' next.

CST maintains comparable levels of correlational faithfulness as the baseline decoders. However, the decoder baselines failed to exhibit a meaningful degree of causal faithfulness. This is indeed impossible for **Ord-Dec** given the lack of any causal pathway from z_t to m_{t+1}. Re-routing z back to the internal state in **RR-Dec** does result in a small increase above chance, but the effect is relatively tiny. In contrast, all CST objectives substantially increase the degree of causal faithfulness (Figure 3b).

Language-based self-talk. Next, we trained agents to model their belief state using messages z in a synthetic language form (e.g. Figure 4a). We repeated the same set of evaluations on the language-form self-models as we did on the one-hot forms. For correlational faithfulness, we obtain analogous values of $q(z_t^\tau = r)$ by computing the likelihoods of generating the four messages "The <instructed tag> is in the <color> room.", and normalizing these to sum to 1.

(a) Example language messages from a CST-RL agent.

(b) Faithfulness results.

Figure 4: **Language-based self-talk.** Results as in Figure 3.

As with the one-hot form, we found that the greatest gain of CST was its ability to imbue the self-model with causal faithfulness. The effect was most profound with CST-RL, and moderate with CST-PD. However, we found it difficult to get any traction with the memory reconstruction version of the algorithm. Unlike all the other variants, CST-MR was often disruptive to learning the base policy, and ineffective at causal faithfulness on the few seeds where it was able to learn.

We note that the faithfulness results with the language form were overall weaker than for the one-hot form. This may be because the language messages encode a room belief about a single tag, while the one-hot messages encode a belief about all four tags.

Semantic control. As a final test, we consider whether CST endows the self-model with sufficient causal power to act as an effective semantic control interface for the agent. To measure this, we determine how effectively the agent can use injected information to obtain reward. We start with two baselines: (1) the return on evaluation episodes where $p_{sh} = 1$, i.e. where the tags are shuffled on every trial; and (2) the return on evaluation episodes where $p_{sh} = 0$, i.e. where the tags are never shuffled. Respectively, these represent the bounds of rewards the agent naturally obtains when it can acquire (1) minimal or (2) maximal information about the location of the instructed tag. We compare these to the reward obtained on evaluation episodes where information about the tag location is

Figure 5: **Efficacy of semantic control via interventions on the self-model.** By injecting messages z' at the start of each trial, we can successfully guide the agent directly to the goal object under task conditions with $p_{sh} = 1$ where it would otherwise be forced to search.

provided through intervening on z. Specifically, we set $p_{sh} = 1$, and inject a message z' at the start of each trial indicating the location of all the tags (for the one-hot message form), or the location of the instructed tag (for the language message form). The results (Figure 5) show that CST not only furnishes an agent with a semantically-grounded model that describes its behavior, but also one which can be used as a mechanism to guide it.

7 Discussion

We articulated five key desiderata of an ideal explanation system for an AI system: grounding, flexibility, minimal-interference, scalability, and faithfulness. Unlike existing approaches, we seek to satisfy all of these by training the base system to serve a causal model of itself. We developed an instance of this solution for Deep RL agents: Causal Self-Talk. In CST, an agent learns to serve a grounded and faithful model of its internal state by learning to communicate with itself across time. We demonstrated its effectiveness under various forms in a simple embodied task in a simulated 3D environment. We also showed that CST enables a new mechanism for effective semantic control.

We presented three variants of the CST algorithm, based on different training objectives. Ultimately, CST-RL yielded the greatest degree of causal faithfulness and efficacy of semantic control. This is achieved by intervening on the agent's internal state at training time, forcing the agent to learn how to use the content of its self-model to maximize its reward. Its success, however, may reflect features of the particular task setting we study: here, there is a close alignment between writing a faithful z and maximizing reward. This may not always be the case.

In contrast, CST-PD offers an attractive alternative for two reasons. First, it trains entirely in replay, and thus potentially interferes less with the base system relative to CST-RL. Second, as it primarily seeks to enable *imitation* of the current behavior, the faithfulness of the self-model is targeted by design. One challenge here is learning to capture the important features of behavior; rather than simple behavioral cloning, as we have attempted, more impressive gains may be possible using richer imitation learning techniques [e.g. 34]. In principle, CST-MR, which tries to reconstruct the entire memory state, offers the greatest potential. However, we had the least success with it. There also may be theoretical obstacles to deploying CST-MR in some settings, e.g. when the dimensionality of the internal state is very large, or is of variable length.

Limitations.   In our experiments, we only implemented a limited form of CST, where we exclusively revert memory states m_t to the state at time $t' = 0$, rather than the more general case of $t' < t$. This imparts two limitations: (1) it requires m_t to be reverted to m_0 in order to effectively intervene on the message z; and (2) it requires z to contain all behaviorally-relevant information. While sufficient for the simple task at hand, this is unrealistic in more complex environments. When z contains only a partial description of m_t, it will be necessary for the agent to be able to re-integrate injected z values with its current memory state. A viable path to achieving this would be the full solution of memory reversion: sampling $t' < t$ rather than fixing $t' = 0$.

Utility requires that the self-model be grounded in a semantically-meaningful form. We have shown how a ready source of data can be used to train the self-model. How this method stands up in more limited data regimes, or in OOD scenarios where the self-model hasn't been supervised, remains an open question. It may be possible in some domains to leverage semi-supervised methods, and/or to impose structure on the self-model as a helpful constraint.

Future opportunities.   We focused here on expressing the agent's beliefs about the current state of the environment in the self-model. A complete answer to the question, "Why did you do that?" might also include an expression of an agent's goals, plans, and model of the world [53]. The schema we have developed here should be sufficiently flexible to extend in this direction, given the right training data. Ultimately, it would be of great value to determine how to apply these techniques beyond RL agents, repurposing them to model the computational processes occurring in generic Deep Learning systems.

Our primary focus in this paper has been on building self-models to yield explanations. However, this is only one of several utilities that a faithful self-model might deliver. For example, we demonstrate that causal self-models provide a semantic control mechanism. This could be useful for guiding agent learning through human interaction [1], metacognitive reporting and control [9, 24, 29], or as an interface for safety-critical applications [41, 45, 51, 61]. By learning to express its internal state through a different representational schema, this may also open up avenues for new exploration or hierarchical reinforcement learning techniques.

Finally, training agents to constantly talk to themselves might prove to be a data-efficient way of enabling agents to talk to others (and us!). Ultimately, this may pave a way for us to invert of the flow of knowledge, allowing agents to not only answer, "Why did you do that?", but also "How?".

References

[1] Josh Abramson, Arun Ahuja, Iain Barr, Arthur Brussee, Federico Carnevale, Mary Cassin, Rachita Chhaparia, Stephen Clark, Bogdan Damoc, Andrew Dudzik, and Others. Imitating interactive intelligence. *arXiv preprint arXiv:2012.05672*, 2020.

[2] Julius Adebayo, Justin Gilmer, Michael Muelly, Ian Goodfellow, Moritz Hardt, and Been Kim. Sanity checks for saliency maps. *Adv. Neural Inf. Process. Syst.*, 31, 2018.

[3] Zeynep Akata, Lisa Anne Hendricks, Stephan Alaniz, and Trevor Darrell. Generating post-hoc rationales of deep visual classification decisions. In *The Springer Series on Challenges in Machine Learning*, pages 135–154. Springer International Publishing, Cham, 2018.

[4] David Alvarez-Melis and Tommi S Jaakkola. Towards robust interpretability with Self-Explaining neural networks. *arXiv preprint arXiv:1806.07538*, June 2018.

[5] Jacob Andreas, Dan Klein, and Sergey Levine. Modular multitask reinforcement learning with policy sketches. *arXiv preprint arXiv:1611.01796*, November 2016.

[6] Rushil Anirudh, P Bremer, Rahul Sridhar, and JJ Thiagarajan. Influential sample selection: A graph signal processing approach. Technical report, Lawrence Livermore National Lab.(LLNL), Livermore, CA (United States), 2017.

[7] Akanksha Atrey, Kaleigh Clary, and David Jensen. Exploratory not explanatory: Counterfactual analysis of saliency maps for deep reinforcement learning. *arXiv preprint arXiv:1912.05743*, 2019.

[8] Sebastian Bach, Alexander Binder, Grégoire Montavon, Frederick Klauschen, Klaus-Robert Müller, and Wojciech Samek. On Pixel-Wise explanations for Non-Linear classifier decisions by Layer-Wise relevance propagation. *PLOS ONE*, 10(7):e0130140, 2015.

[9] Andrea Banino, Jan Balaguer, and Charles Blundell. Pondernet: Learning to ponder. *arXiv preprint arXiv:2107.05407*, 2021.

[10] Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, Caglar Gulcehre, Francis Song, Andrew Ballard, Justin Gilmer, George Dahl, Ashish Vaswani, Kelsey Allen, Charles Nash, Victoria Langston, Chris Dyer, Nicolas Heess, Daan Wierstra, Pushmeet Kohli, Matt Botvinick, Oriol Vinyals, Yujia Li, and Razvan Pascanu. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, June 2018.

[11] David Bau, Bolei Zhou, Aditya Khosla, Aude Oliva, and Antonio Torralba. Network dissection: Quantifying interpretability of deep visual representations. *arXiv preprint arXiv:1704.05796*, April 2017.

[12] Yonatan Belinkov and James Glass. Analysis methods in neural language processing: A survey. *Transactions of the Association for Computational Linguistics*, 7:49–72, 2019.

[13] Przemyslaw Biecek and Tomasz Burzykowski. Local interpretable model-agnostic explanations (LIME). *Explanatory Model Analysis*, pages 107–123, 2021.

[14] Jacob Bien and Robert Tibshirani. Prototype selection for interpretable classification. *The Annals of Applied Statistics*, 5(4):2403–2424, 2011.

[15] Tyler Bonnen, Daniel L K Yamins, and Anthony D Wagner. When the ventral visual stream is not enough: A deep learning account of medial temporal lobe involvement in perception. *Neuron*, 109(17):2755–2766.e6, September 2021.

[16] Christopher P Burgess, Loic Matthey, Nicholas Watters, Rishabh Kabra, Irina Higgins, Matt Botvinick, and Alexander Lerchner. MONet: Unsupervised scene decomposition and representation. *arXiv preprint arXiv:1901.11390*, January 2019.

[17] Nick Cammarata, Gabriel Goh, Shan Carter, Ludwig Schubert, Michael Petrov, and Chris Olah. Curve detectors. *Distill*, 5(6), June 2020.

[18] Hyeoncheol Cho, Eok Kyun Lee, and Insung S Choi. Layer-wise relevance propagation of InteractionNet explains protein–ligand interactions at the atom level. *Scientific Reports*, 10(1), 2020.

[19] Grégoire Déletang, Jordi Grau-Moya, Miljan Martic, Tim Genewein, Tom McGrath, Vladimir Mikulik, Markus Kunesch, Shane Legg, and Pedro A Ortega. Causal analysis of agent behavior for ai safety. *arXiv preprint arXiv:2103.03938*, 2021.

[20] Yanai Elazar, Shauli Ravfogel, Alon Jacovi, and Yoav Goldberg. Amnesic probing: Behavioral explanation with amnesic counterfactuals. *Transactions of the Association for Computational Linguistics*, 9:160–175, 2021.

[21] Nelson Elhage, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Nova DasSarma, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, Dario Amodei, Tom Brown, Jack Clark, Jared Kaplan, Sam McCandlish, and Chris Olah. A mathematical framework for transformer circuits. *Transformer Circuits Thread*, 2021.

[22] Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Vlad Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, and Others. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. In *International Conference on Machine Learning*, pages 1407–1416, 2018.

[23] Jeffrey De Fauw, Jeffrey De Fauw, Joseph R Ledsam, Bernardino Romera-Paredes, Stanislav Nikolov, Nenad Tomasev, Sam Blackwell, Harry Askham, Xavier Glorot, Brendan O'Donoghue, Daniel Visentin, George van den Driessche, Balaji Lakshminarayanan, Clemens Meyer, Faith Mackinder, Simon Bouton, Kareem Ayoub, Reena Chopra, Dominic King, Alan Karthike-salingam, Cían O Hughes, Rosalind Raine, Julian Hughes, Dawn A Sim, Catherine Egan, Adnan Tufail, Hugh Montgomery, Demis Hassabis, Geraint Rees, Trevor Back, Peng T Khaw, Mustafa Suleyman, Julien Cornebise, Pearse A Keane, and Olaf Ronneberger. Clinically applicable deep learning for diagnosis and referral in retinal disease. *Nature Medicine*, 24(9): 1342–1350, 2018.

[24] Damien S Fleur, Bert Bredeweg, and Wouter van den Bos. Metacognition: ideas and insights from neuro- and educational sciences. *NPJ Sci Learn*, 6(1):13, June 2021.

[25] Atticus Geiger, Zhengxuan Wu, Hanson Lu, Josh Rozner, Elisa Kreiss, Thomas Icard, Noah D Goodman, and Christopher Potts. Inducing causal structure for interpretable neural networks. *arXiv preprint arXiv:2112.00826*, 2021.

[26] Gabriel Goh, Nick Cammarata †, Chelsea Voss †, Shan Carter, Michael Petrov, Ludwig Schubert, Alec Radford, and Chris Olah. Multimodal neurons in artificial neural networks. *Distill*, 2021.

[27] Yash Goyal, Ziyan Wu, Jan Ernst, Dhruv Batra, Devi Parikh, and Stefan Lee. Counterfactual visual explanations. In *International Conference on Machine Learning*, pages 2376–2384, 2019.

[28] Riccardo Guidotti, Anna Monreale, Salvatore Ruggieri, Franco Turini, Fosca Giannotti, and Dino Pedreschi. A survey of methods for explaining black box models. *ACM computing surveys (CSUR)*, 51(5):1–42, 2018.

[29] Jessica B Hamrick, Andrew J Ballard, Razvan Pascanu, Oriol Vinyals, Nicolas Heess, and Peter W Battaglia. Metacontrol for adaptive imagination-based optimization. *arXiv preprint arXiv:1705.02670*, 2017.

[30] Bradley Hayes and Julie A Shah. Improving robot controller transparency through autonomous policy explanation. In *Proceedings of the 2017 ACM/IEEE International Conference on Human-Robot Interaction*, New York, NY, USA, March 2017. ACM.

[31] Lisa Anne Hendricks, Zeynep Akata, Marcus Rohrbach, Jeff Donahue, Bernt Schiele, and Trevor Darrell. Generating visual explanations. In *European conference on computer vision*, pages 3–19, 2016.

[32] Lisa Anne Hendricks, Ronghang Hu, Trevor Darrell, and Zeynep Akata. Generating counterfactual explanations with natural language. *arXiv preprint arXiv:1806.09809*, 2018.

[33] Lisa Anne Hendricks, Anna Rohrbach, Bernt Schiele, Trevor Darrell, and Zeynep Akata. Generating visual explanations with natural language. *Applied AI Letters*, 2(4), December 2021.

[34] Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. *Adv. Neural Inf. Process. Syst.*, 29, 2016.

[35] Alon Jacovi and Yoav Goldberg. Towards faithfully interpretable NLP systems: How should we define and evaluate faithfulness? In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4198–4205, Online, July 2020. Association for Computational Linguistics.

[36] Alon Jacovi, Ana Marasović, Tim Miller, and Yoav Goldberg. Formalizing trust in artificial intelligence: Prerequisites, causes and goals of human trust in AI. In *Proceedings of the 2021 ACM conference on fairness, accountability, and transparency*, pages 624–635, 2021.

[37] Max Jaderberg, Volodymyr Mnih, Wojciech Marian Czarnecki, Tom Schaul, Joel Z Leibo, David Silver, and Koray Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017.

[38] Sarthak Jain and Byron C Wallace. Attention is not explanation. *arXiv preprint arXiv:1902.10186*, February 2019.

[39] Zoe Juozapaitis, Anurag Koul, Alan Fern, Martin Erwig, and Finale Doshi-Velez. Explainable reinforcement learning via reward decomposition. In *IJCAI/ECAI Workshop on explainable artificial intelligence*, 2019.

[40] Bilal Kartal, Pablo Hernandez-Leal, and Matthew E Taylor. Terminal prediction as an auxiliary task for deep reinforcement learning. In *Proceedings of the Fifteenth AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment*, AIIDE'19, Atlanta, Georgia, 2019. AAAI Press.

[41] Huda Khayrallah, Sean Trott, and Jerome Feldman. Natural language for human robot interaction. In *International Conference on Human-Robot Interaction (HRI)*, 2015.

[42] Been Kim, Cynthia Rudin, and Julie A Shah. The bayesian case model: A generative approach for case-based reasoning and prototype classification. *Advances in neural information processing systems*, 27, 2014.

[43] Been Kim, Rajiv Khanna, and Oluwasanmi O Koyejo. Examples are not enough, learn to criticize! criticism for interpretability. *Advances in neural information processing systems*, 29, 2016.

[44] Been Kim, Martin Wattenberg, Justin Gilmer, Carrie Cai, James Wexler, Fernanda Viegas, and Rory Sayres. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (TCAV). *arXiv preprint arXiv:1711.11279*, November 2017.

[45] Jinkyu Kim, Suhong Moon, Anna Rohrbach, Trevor Darrell, and John Canny. Advisable learning for self-driving vehicles by internalizing observation-to-action rules. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. IEEE, June 2020.

[46] Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *International conference on machine learning*, pages 1885–1894. PMLR, 2017.

[47] Pang Wei Koh, Thao Nguyen, Yew Siang Tang, Stephen Mussmann, Emma Pierson, Been Kim, and Percy Liang. Concept bottleneck models. *arXiv preprint arXiv:2007.04612*, July 2020.

[48] Guillaume Lample and Devendra Singh Chaplot. Playing FPS games with deep reinforcement learning. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence*, AAAI'17, pages 2140–2146, San Francisco, California, USA, 2017. AAAI Press.

[49] Zachary C Lipton. The mythos of model interpretability: In machine learning, the concept of interpretability is both important and slippery. *Queueing Syst.*, 16(3):31–57, 2018.

[50] Prashan Madumal, Tim Miller, Liz Sonenberg, and Frank Vetere. Explainable reinforcement learning through a causal lens. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pages 2493–2500, 2020.

[51] Cynthia Matuszek, Evan Herbst, Luke Zettlemoyer, and Dieter Fox. Learning to parse natural language commands to a robot control system. In *Experimental robotics*, pages 403–415, 2013.

[52] Thomas McGrath, Andrei Kapishnikov, Nenad Tomašev, Adam Pearce, Demis Hassabis, Been Kim, Ulrich Paquet, and Vladimir Kramnik. Acquisition of chess knowledge in AlphaZero. *arXiv preprint arXiv:2111.09259*, November 2021.

[53] Tim Miller. Explanation in artificial intelligence: Insights from the social sciences. *Artificial intelligence*, 267:1–38, 2019.

[54] Piotr W Mirowski, Razvan Pascanu, Fabio Viola, Hubert Soyer, Andy Ballard, Andrea Banino, Misha Denil, Ross Goroshin, L Sifre, Koray Kavukcuoglu, Dharshan Kumaran, and Raia Hadsell. Learning to navigate in complex environments. *arXiv preprint arXiv:1611.03673*, 2017.

[55] Alexander Mordvintsev, Christopher Olah, and Mike Tyka. Inceptionism: Going deeper into neural networks. *Google Research Blog*, 2015.

[56] Alexander Mott, Daniel Zoran, Mike Chrzanowski, Daan Wierstra, and Danilo Jimenez Rezende. Towards interpretable reinforcement learning using attention augmented agents. *Adv. Neural Inf. Process. Syst.*, 32, 2019.

[57] Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova DasSarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Scott Johnston, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, Dario Amodei, Tom Brown, Jack Clark, Jared Kaplan, Sam McCandlish, and Chris Olah. In-context learning and induction heads. *Transformer Circuits Thread*, March 2022.

[58] Dong Huk Park, Lisa Anne Hendricks, Zeynep Akata, Anna Rohrbach, Bernt Schiele, Trevor Darrell, and Marcus Rohrbach. Multimodal explanations: Justifying decisions and pointing to the evidence. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*. IEEE, June 2018.

[59] Abhilasha Ravichander, Yonatan Belinkov, and Eduard Hovy. Probing the probing paradigm: Does probing accuracy entail task relevance? *arXiv preprint arXiv:2005.00719*, 2020.

[60] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. Anchors: High-precision model-agnostic explanations. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.

[61] Junha Roh, Chris Paxton, Andrzej Pronobis, Ali Farhadi, and Dieter Fox. Conditional driving from natural language instructions. In *Conference on Robot Learning*, pages 540–551, 2020.

[62] Cynthia Rudin. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence*, 1(5):206–215, 2019.

[63] Tianmin Shu, Caiming Xiong, and Richard Socher. Hierarchical and interpretable skill acquisition in multi-task reinforcement learning. *arXiv preprint arXiv:1712.07294*, December 2017.

[64] Peter Spirtes, Clark N Glymour, Richard Scheines, and David Heckerman. *Causation, prediction, and search*. MIT press, 2000.

[65] Ian Tenney, James Wexler, Jasmijn Bastings, Tolga Bolukbasi, Andy Coenen, Sebastian Gehrmann, Ellen Jiang, Mahima Pushkarna, Carey Radebaugh, Emily Reif, and Ann Yuan. The language interpretability tool: Extensible, interactive visualizations and analysis for NLP models. *arXiv preprint arXiv:2008.05122*, August 2020.

[66] Nicholay Topin and Manuela Veloso. Generation of policy-level explanations for reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 2514–2521, 2019.

[67] L S Vygotsky. *Thought and Language*. The MIT Press. MIT Press, London, England, 2012.

[68] Tom Ward, Andrew Bolt, Nik Hemmings, Simon Carter, Manuel Sanchez, Ricardo Barreira, Seb Noury, Keith Anderson, Jay Lemmon, Jonathan Coe, Piotr Trochim, Tom Handley, and Adrian Bolton. Using unity to help solve intelligence. *arXiv preprint arXiv:2011.09294*, November 2020.

[69] Sarah Wiegreffe and Yuval Pinter. Attention is not not explanation. *arXiv preprint arXiv:1908.04626*, August 2019.

[70] Herman Yau, Chris Russell, and Simon Hadfield. What did you think would happen? explaining agent behaviour through intended outcomes. *Adv. Neural Inf. Process. Syst.*, 33:18375–18386, 2020.

[71] Chih-Kuan Yeh, Joon Kim, Ian En-Hsu Yen, and Pradeep K Ravikumar. Representer point selection for explaining deep neural networks. *Advances in neural information processing systems*, 31, 2018.

[72] Vinicius Zambaldi, David Raposo, Adam Santoro, Victor Bapst, Yujia Li, Igor Babuschkin, Karl Tuyls, David Reichert, Timothy Lillicrap, Edward Lockhart, and Others. Deep reinforcement learning with relational inductive biases. In *International conference on learning representations*, 2018.

[73] Matthew D Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In *European conference on computer vision*, pages 818–833, 2014.

[74] Bolei Zhou, Yiyou Sun, David Bau, and Antonio Torralba. Interpretable basis decomposition for visual explanation. In *Proceedings of the European Conference on Computer Vision (ECCV)*, September 2018.