Rank Overspecified Robust Matrix Recovery: Subgradient Method and Exact Recovery

Abstract

We study the robust recovery of a low-rank matrix from grossly corrupted measurements, with no prior knowledge on the intrinsic rank. We consider the robust matrix factorization approach. We employ a robust ℓ_1 loss function and deal with the challenge of the unknown rank by using an overspecified factored representation of the matrix variable. We then solve the associated nonconvex nonsmooth problem using a subgradient method with diminishing step sizes. We show that under a regularity condition on the sensing matrices and corruption, which we call restricted direction preserving property (RDPP), even with rank overspecified, the subgradient method converges to the exact low-rank solution at a sublinear rate. Moreover, our result is more general in the sense that it automatically speeds up to a linear rate once the factor rank matches the unknown rank. On the other hand, we show that the RDPP condition holds under generic settings, such as Gaussian measurements under independent or adversary sparse corruptions, where the result could be of independent interest. Both the exact recovery and the convergence rate of the proposed subgradient method are numerically verified in the overspecified regime. Moreover, our experiment further shows that our particular design of diminishing stepsize effectively prevents overfitting for robust recovery under overparameterized models, such as robust matrix sensing and learning robust deep image prior. This regularization effect is worth further investigation.

1 Introduction

Robust low rank matrix recovery problems are ubiquitous in computer vision [1], signal processing [2], quantum state tomography [3], etc. In the vanilla setting, the task is to recover a rank r positive semidefinite (PSD) matrix $X_\natural \in \mathbb{R}^{d \times d}$ ($r \ll d$) from a few corrupted linear measurements $\{(y_i, A_i)\}_{i=1}^n$ of the form

$$y_i = \langle A_i, X_\natural \rangle + s_i, \quad i = 1, \ldots, m, \tag{1.1}$$

where $\{s_i\}_{i=1}^m$ are the corruptions. This model can be written succinctly as $y = \mathcal{A}(X_\natural) + s$, where $\mathcal{A} : \mathbb{R}^{d \times d} \to \mathbb{R}^m$ is the measurement operator. Recently, tremendous progress has been made on this problem, leveraging advances on convex relaxation [1, 2], nonconvex optimization [4–7], and high dimension probability [8–11]. However, several practical challenges remain:

- **Nonconvex and nonsmooth optimization for sparse corruptions.** For computational efficiency, we often exploit the low-rank structure via the factorization $X = FF^\top$ with $F \in \mathbb{R}^{d \times r}$, and solve the problem with respect to F via nonconvex optimization. However, in many cases the corruptions s_i are *sparse* [1], which naturally result in very challenging nonsmooth nonconvex problems.
- **Unknown rank and overspecification.** Another major challenge in practice is that the *exact* true rank r is usually *unknown* apriori.[1] To deal with this issue, researchers often solve the problem in

---

[1]There are very few exceptions, such as the case of robust phase retrieval with $r = 1$ [12].

35 *rank overspecified regime*, using a factor variable $F \in \mathbb{R}^{d \times k}$ with a larger inner dimension $k > r$.
36 Most existing analysis relies on the k-th eigenvalue of $X_\natural$ being nonzero and is inapplicable in this
37 setting. Recent work studied the problem either in some special case (e.g., rank one) [13] or under
38 unrealistic communitability conditions [14].

39 **Our approach and contributions.** To deal with these challenges, we consider the following
40 nonconvex and nonsmooth formulation with overspecified rank $k \geq r$,

$$\min_{F:\, F \in \mathbb{R}^{d \times k}} f(F) := \frac{1}{2m} \sum_{i=1}^{m} \left| \langle A_i, FF^\top \rangle - y_i \right| = \frac{1}{2m} \left\| \mathcal{A}(FF^\top) - y \right\|_1, \tag{1.2}$$

41 and apply a subgradient method with *adaptive* stepsize. We summarize our contributions below.

- **Exact recovery with rank overspecification**. In Theorem 3.2, we show that with $m = \tilde{\mathcal{O}}(dk^3)$
  samples[2], even with overspecified rank $k > r$, our subgradient method with spectral initialization
  converges to the ground truth $X_\natural$ *exactly*. When $k > r$, the convergence rate is $\mathcal{O}(\frac{1}{t})$ in the operator
  norm error. $\left\| F_t F_t^\top - X_\natural \right\|$. When $k = r$, the convergence rate boosts to linear (geometric) rate.
- **A new regularity condition.** Key to the proof of the above result is a new regularity condition
  termed *restricted direction preserving property* (RDPP); see Definition 2.1. RDPP ensures that the
  direction of the finite-sample subgradient stays close to its population version along the algorithm's
  iteration path. This property allows us to leverage a recent result on rank overspecification under
  smooth formulations [15]. Moreover, we show that RDPP holds with high probability under
  arbitrary sparse corruptions and standard assumptions on the measurement matrices.
- **Adaptive stepsize and implicit regularization** As shown in [13, 14], for overparametrized robust
  matrix recovery problems, subgradient methods with constant stepsizes suffer from overfitting, even
  when initialized near the origin. In contrast, numerical experiments demonstrate that our theory-
  inspired diminishing stepsize rule has an implicit regularization effect that prevents overfitting.
  Our stepsize rule is easy to implement and almost tuning-free, and performs better than other non-
  adaptive stepsize rules (e.g., sublinear or geometric decaying stepsizes). We demonstrate similar
  good performance of our method in image recovery with a robust deep image prior (DIP) [16].

59 **Related work.** The nonconvex, factorized formulation (1.2) is computationally more efficient than
60 convex relaxation approaches [1, 17, 18], as it involves a smaller size optimization variable and does
61 not require singular value decomposition (SVD). In the corruption-free ($s_i \equiv 0$) and exact rank
62 ($k = r$) setting, provably efficient methods have been studied for the *smooth*, least squares version
63 of (1.2) [19–22]; in this case, the loss function has no spurious local minimum and locally strongly
64 convex [23, 24]. For smooth formulations with rank overspecification ($k \geq r$ or even $k = d$), gradient
65 descent initialized near the origin is shown to *approximately* recover the ground truth matrix [25, 26].

66 When the rank r is known and measurement corruption is present, the work [4] considers the smooth
67 formulation and proposes a gradient descent method with a robust gradient estimator using median
68 truncation. The nonsmooth formulation (1.2) is considered in a recent line of work [5–7], again in the
69 known rank setting ($k = r$), where they show that the loss function satisfies certain sharpness [27]
70 properties and hence subgradient methods converge locally at a linear rate. We emphasize that the
71 above results crucially rely on knowing and using the exact true rank. When the rank is unknown, the
72 work [14] considers a doubly over-parameterized formulation but requires a stringent, commutability
73 assumptions on the measurement matrices; moreover, their analysis concerns continuous dynamic
74 of gradient descent and is hard to generalize to discrete case. Our results only impose standard
75 measurement assumptions and apply to the usual discrete dynamic of subgradient methods.

76 Most related is the recent work [13], which
77 studies subgradient methods for the non-
78 smooth formulation (1.2) in the rank-one
79 case ($r = 1$). Even in this special case,
80 only approximate recovery is guaranteed,
81 i.e., finding an F with $\|FF^\top - X_\natural\|_F \lesssim$
82 $\delta \log(\frac{1}{\delta})$ for a fixed $\delta > 0$. We note that the lack of exact recovery is inherent to their choice of
83 stepsizes, and spectral initialization already guarantees $\|FF^\top - X_\natural\|_F \lesssim \delta$ [13, Equation (85)]. In
84 contrast, our result applies beyond rank-1 case and guarantees exact recovery thanks to the proposed
85 adaptive diminishing stepsize rule. We summarize the above comparison in Table 1.

	[4–7]	[13]	Ours
Rank specification	$k = r$	$k \geq r = 1$	$k \geq r$
Exact Recovery	✓	✗	✓

Table 1: **Comparison of results on robust matrix sensing.**

[2]Here $\tilde{O}$ hides the condition number of $X_\natural$ and other log factors.

2 Models, regularity, and identifiability

In this section, we formally describe our model and assumptions. We then introduce the restricted direction preserving property and establish a basic identifiability result under rank overspecification, both key to the convergence analysis of our algorithm given in Section 3 to follow.

2.1 Observation and corruption models

In this work, we study subgradient methods for the robust low-rank matrix recovery problem (1.2) under the observation model (1.1). Throughout this paper, we assume that the sensing matrices $A_i \in \mathbb{R}^{d \times d}, i = 1, \ldots, m$ are generated *i.i.d.* from the Gaussian Orthogonal Ensemble (GOE). That is, each A_i is symmetric, with the diagonal entries being i.i.d. standard Gaussian $N(0, 1)$, and the upper triangular entries are i.i.d. $N(0, \frac{1}{2})$ independent of the diagonal. We consider two models for the corruption $s = (s_1, \ldots, s_m)^\top$: arbitrary corruption (AC) and random corruption (RC).

Model 1 (AC model). *Under the model AC($X_\natural, \mathcal{A}, p, m$), the index set $S \subset \{1, \ldots, m\}$ of nonzero entries of s is uniformly random with size $\lfloor pm \rfloor$, independently of $\mathcal{A}$, and the values of the nonzero entries are arbitrary.*

Model 2 (RC model). *Under the model RC($X_\natural, \mathcal{A}, p, m$), each s_i, $i = 1, \ldots, m$, is a random variable, independent of $\mathcal{A}$ and each other, with probability $p \in (0, 1)$ being nonzero.*

In the AC model, the values of the nonzero entries of s can be chosen in a coordinated and potentially adversarial manner dependent on $\{A_i\}$ and $X_\natural$, whereas their locations are independent. Therefore, this model is more general than those in [1, 28], which assume random signs.[3] The RC model puts no restriction on the random variables $\{s_i\}$ except for independence, and hence is more general than the model in [13]. In particular, the distributions of $\{s_i\}$ can be heavy-tailed, non-identical and have non-zero means (where the means cannot depend on $\{A_i\}$). Under the RC model, we can allow p to be close to $\frac{1}{2}$ and still achieve exact recovery (see Theorem 3.2).

2.2 Restricted direction preserving property (RDPP)

When the true rank r is known, existing work [5, 6] on subgradient methods typically makes use of the so-called ℓ_1/ℓ_2-restricted isometry property (RIP), which ensures that the function $g(X) = \frac{1}{m} \|\mathcal{A}(X) - y\|_1$ concentrates uniformly around its expecation. Note that the facterized objective f in (1.2) is related to g by $f(F) = \frac{1}{2}g(FF^\top)$. With ℓ_1/ℓ_2-RIP, existing work establishes the sharpness of g when $k = r$, i.e., linear growth around the minimum [5, Proposition 2]. In the rank-overspecification setting, however, g is *not* sharp, as it grows more slowly than linear in the direction of superfluous eigenvectors of F. We address this challenge by directly analyzing the subgradient dynamic, detailed in Section 3, and establishing concentration of the *subdifferential* of g rather than g itself.

Recall the regular subdifferential of $g(X)$ [29] is

$$\mathcal{D}(X) := \frac{1}{m} \sum_{i=1}^{m} \overline{\text{sign}}(\langle A_i, X \rangle - s_i) A_i, \quad \text{and} \quad \overline{\text{sign}}(x) := \begin{cases} \{-1\}, & x < 0 \\ [-1, 1], & x = 0 \\ \{1\}, & x > 0 \end{cases}. \quad (2.1)$$

Since our goal is to study the convergence of the subgradient method, which utilizes only one member $D(X)$ and will be illustrated in Section 3.1, it is enough to consider this member $D(X)$ by setting $\text{sign}(x) = \begin{cases} -1, & x < 0 \\ 1, & x \geq 0 \end{cases}$. We are now ready to state the RDPP condition.

Definition 2.1 (RDPP). *The measurements and corruption $\{(A_i, s_i)\}_{i=1}^{m}$ are said to satisfy restricted direction preserving property with parameters (k', δ) and a scaling function $\psi : \mathbb{R}^{d \times d} \to \mathbb{R}$ if for every symmetric matrix $X \in \mathbb{R}^{d \times d}$ with rank no more than k', we have*

$$D(X) := \frac{1}{m} \sum_{i=1}^{m} \text{sign}(\langle A_i, X \rangle - s_i) A_i, \quad \text{and} \quad \left\| D(X) - \psi(X) \frac{X}{\|X\|_\text{F}} \right\| \leq \delta. \quad (2.2)$$

---

[3]Our results can be extended to the even more general setting with adversarial locations [4–7], with an extra poly(k, κ) factor in the requirement of the corruption rate p compared to the one we present in Section 3.

d	$d=50$	$d=100$	$d=200$	$d=300$
RDPP: $\left\lVert D(X_\natural) - \sqrt{\frac{2}{\pi}}\frac{X_\natural}{\lVert X_\natural \rVert_F} \right\rVert$	0.62/0.28	0.62/0.29	0.63/0.28	0.63/0.28
sign-RIP [13]: $\lVert D(X_\natural) - \sqrt{\frac{2}{\pi}}\frac{X_\natural}{\lVert X_\natural \rVert_F} \rVert_F$	2.30/1.00	3.30/1.43	4.43/2.02	5.49/2.45

Table 2: **Comparison of RDPP and sign-RIP** for $d \in \{50, 100, 200, 300\}$ and $r \in \{1, 5\}$. For each entry with two numbers, the left corresponds to $r = 1$ and the right corresponds to $r = 5$. We set $p = 0$ and $m = 5dr$. Note sign-RIP is never satisfied as the above entries for sign-RIP has value larger than or equal to 1.

Here, the scaling function accounts for the fact that the expectation is not exactly $\frac{X}{\lVert X \rVert_F}$, e.g., when no corruption, $\nabla \mathbb{E}(g(X)) = \sqrt{\frac{2}{\pi}}\frac{X}{\lVert X \rVert_F}$. How does RDPP relate to the ℓ_1/ℓ_2-RIP? In the absence of corruption, as shown in Appendix I, RDPP implies ℓ_1/ℓ_2-RIP for $\delta \lesssim \frac{1}{\sqrt{r}}$. Conversely, we know if ℓ_1/ℓ_2-RIP condition holds for all rank d matrices, then RDPP holds if $p = 0$ [13, Proposition 9].

Recent work studied the robust low-rank recovery problem with overspecified rank under a condition called sign-RIP [13], which is similar to ours. However, a *major* difference between our RDPP and sign-RIP defined in [13] is that RDPP is based on operator norm instead of Frobenius norm in sign-RIP. Although Frobenius norm bound provides a stronger condition, if m is on the order dr as we demonstrated in Table 2, it *cannot* be satisfied even for a fixed rank-1 $X_\natural$ as all values of $\lVert D(X_\natural) - \sqrt{\frac{2}{\pi}}\frac{X_\natural}{\lVert X_\natural \rVert_F} \rVert_F$ is larger than 1. In contrast, generic sensing matrices satisfy RDPP for any rank $k' \geq 1$, and it suffices for our analysis. Indeed, we can show the following.

Proposition 2.2. *Let $m \gtrsim \frac{dk'\left(\log(\frac{1}{\delta}) \vee 1\right)}{\delta^4}$. For Model 1, $(k', \delta + 3\sqrt{\frac{dp}{m}} + 3p)$-RDPP holds with a scaling function $\psi(X) = \sqrt{\frac{2}{\pi}}$ with probability at least $1 - \exp(-(pm+d)) - \exp(-c'm\delta^4)$. For Model 2, (k', δ)-RDPP holds with a scaling function $\psi(X) = \frac{1}{m}\sum_{i=1}^{m}\sqrt{\frac{2}{\pi}}\left(1 - p + p\mathbb{E}_{s_i}\left[\exp(-\frac{s_i^2}{2\lVert X \rVert_F^2})\right]\right)$ with probability at least $1 - Ce^{-cm\delta^4}$. Here c, c', C are universal constants.*

The proof can be found in Appendix D. Such operator norm bound (2.2) is enough for our purpose in approximating the population subgradient of f for low rank F.

2.3 Identifiability of the ground truth $X_\natural$

If the exact rank is given ($k = r$), it is known that our objective function (1.2) indeed identifies $X_\natural$, in the sense that any global optimal solution $F_\star$ coincides with $X_\natural = F_\star F_\star^\top$ [5]. When $k > r$, one may suspect that there might be an idenitfiability or overfitting issue due to rank oversepcification and the presence of corruptions, i.e., there might be F has better objective value f than G with $GG^\top = X_\natural$. However, so long as the number of samples are sufficiently large $m = \Omega(dk)$, we show that the identifiability of $X_\natural$ is ensured. We defer the proof to Appendix G.

Theorem 2.3. *Fix any $p < \frac{1}{2}$. Under either Model 1 or Model 2 with corruption rate p, if $m \geq cdk$, then with probability at least $1 - e^{-c_1 m}$, any global optimizer $F_\star$ of (1.2) satisfies $F_\star F_\star^\top = X_\natural$. Here constants $c, c_1 > 0$ depend only on p.*

Here overfitting does not occur since sample size m matches the degree of freedom of our formulation dk, making it possible to guarantee success of the algorithm described in Section 3. On the other hand, if we are in the heavily overparameterized regime with $m = \mathcal{O}(dr) \ll dk$ (e.g., $k = d$),[4] the above identifiability result should not be expected to hold. Perhaps surprisingly, in Section 4 we empirically show that the proposed method works even in this heavy overparametrization regime with $k = d$. This is in contrast to the overfitting behavior of subgradient methods with constant stepsizes observed in [14], and it indicates an implicit regularization effect of our adaptive stepsize rule.

---

[4]A few authors [13,15] refer to the setting with $k > r$ and $m \asymp dk$ as "overparametrization" since k is larger than necessary. Others reserve the term for the setting $m < dk$, i.e., the number of parameters exceeds the sample size. We generally refer to the former setting as "(rank-)overspecifcation" and the latter as "overparametrization".

3 Main results and analysis

In this section, we first introduce the subgradient method with implementation details. We then show our main convergence results, that subgradient method with diminishing stepsizes converge to the exact solutions even under the setting of overspecified rank. Finally, we sketch the high-level ideas and intuitions of our analysis. All the technical details are postponed to the appendices

3.1 Subgradient method with diminishing stepsizes

A natural idea of optimizing the problem (1.2) is to deploy the subgradient method starting from some initialization $F_0 \in \mathbb{R}^{d \times k}$, and iterate[5]

$$F_{t+1} = F_t - \eta_t g_t, \quad g_t = D(FF^\top - X_\natural)F, \quad , t = 0, 1, 2, \ldots. \tag{3.1}$$

with certain stepsize rule $\eta_t \geq 0$. The vector g_t indeed belongs to the regular subdifferential of $\partial f(F_t) = \mathcal{D}(F_t F_t^\top - X_\natural)F_t$ by chain rule (recall $\mathcal{D}$ in (2.1)).

For optimizing a nonconvex and nonsmooth problem with subgradient methods, it should be noted that the choice of initialization and stepsize is critical for algorithmic success. As observed in Section 4.1, a fixed stepsize rule, i.e., stepsize determined before seeing iterates, such as geometric or sublinear decaying stepsize, cannot perform uniformly well in various rank specification settings, e.g., $k = r, r \leq k = \mathcal{O}(r), k = d$. Hence it is important to have an adaptive stepsize rule.

Initialization We initialize F_0 by a spectral method similar to [13] yet we do not require $F_0 F_0^\top$ to be close to $X_\natural$ even in operator norm. We discuss the initialization in more detail in Section 3.4.

Stepsize choice To obtain exact recovery, we deploy a simple and adaptive diminishing stepsize rule for η_t, which is inspired by the analysis and is easy to tune. As we shall see in Theorem 3.1 and its proof intuition in Section 3.3, the main requirement for stepsize is that it scales with $\|FF^\top - X_\natural\|_F$ for an iterate F, and hence diminishing and adaptive as $FF^\top \to X_\natural$. To estimate $\|FF^\top - X_\natural\|_F$ when corruption exists, we define the operator $\tau_{\mathcal{A},y}(F) : \mathbb{R}^{d \times k} \to \mathbb{R}$ and the corresponding stepsize:

$$\tau_{\mathcal{A},y}(F) = \xi_{\frac{1}{2}}\left(\{|\langle A_i, FF^\top \rangle - y_i|\}_{i=1}^m\right), \quad \text{and} \quad \eta_t = C_\eta \tau_{\mathcal{A},y}(F_t), \tag{3.2}$$

where $\xi_{\frac{1}{2}}(\cdot)$ is the median operator, and $C_\eta > 0$ is a free parameter to be chosen. As $\mathbb{E}|\langle A_1, FF^\top \rangle - y_1| = \sqrt{\frac{2}{\pi}}\|FF^\top - X_\natural\|_F$ without corruption, we expect $\tau_{\mathcal{A},y}(F)$ to estimate $\|FF^\top - X_\natural\|_F$ well up to some scalar when corruption exists since median is robust to corruptions.

3.2 Main theoretical guarantees

First, we present our main convergence result, that ensures that the iterate $F_t F_t^\top$ in subgradient method (3.1) converges to the rank r ground-truth $X_\natural$, based on conditions on initialization, stepsize, and RDPP. Let the condition number of $X_\natural$ be $\kappa := \frac{\sigma_1(X_\natural)}{\sigma_r(X_\natural)}$, the result can be stated as follows.

Theorem 3.1. *Suppose the following conditions hold:*

(i) Let $0 < \epsilon < 1$ be a fixed parameter. Suppose F_0 satisfies

$$\|F_0 F_0^\top - c^* X_\natural\| \leq c_0 \sigma_r / \kappa. \tag{3.3}$$

with some constant $c^* \in [\epsilon, \frac{1}{\epsilon}]$ and $c_0 = \tilde{c}_0 \epsilon$ for some sufficiently small $\tilde{c}_0$, which only depends on c_1 below. Moreover, all the constants $c_i, i \geq 3$ in the following depend only on ϵ and c_1.

(ii) The stepsize satisfies $0 < c_1 \frac{\sigma_r}{\sigma_1^2} \leq \frac{\eta_t}{\|F_t F_t^\top - X_\natural\|_F} \leq c_2 \frac{\sigma_r}{\sigma_1^2}$ for some small numerical constants $c_1 < c_2 \leq 0.01$ and all $t \geq 0$.

(iii) $(r+k, \delta)$-RDPP holds for $\{A_i, s_i\}_{i=1}^m$ with $\delta \leq \frac{c_3}{\kappa^3 \sqrt{k}}$ and a scaling function $\psi \in \left[\sqrt{\frac{1}{2\pi}}, \sqrt{\frac{2}{\pi}}\right]$.

Define $\mathcal{T} = c_4 \kappa^2 \log \kappa$. Then, we have a sublinear convergence in the sense that for any $t \geq 0$,

$$\left\|F_{t+\mathcal{T}} F_{t+\mathcal{T}}^\top - X_\natural\right\| \leq c_5 \sigma_1 \frac{\kappa}{\kappa^3 + t}.$$

Moreover, if $k = r$, then under the same set of condition, we have convergence at a linear rate

$$\left\|F_{t+\mathcal{T}} F_{t+\mathcal{T}}^\top - X_\natural\right\| \leq \frac{c_6 \sigma_r}{\kappa}\left(1 - \frac{c_7}{\kappa^2}\right)^t, \quad t \geq 0.$$

---

[5]Recall the definition of the subgradient $D(X) = \frac{1}{m}\sum_{i=1}^m \text{sign}(\langle A_i, X \rangle - s_i)A_i$ in (2.2) for the objective, $g(X) = \frac{1}{2m}\|\mathcal{A}(X) - y\|_1$ in the original space $X \in \mathbb{R}^{d \times d}$.

We sketch the high-level ideas of the proof in Section 3.3, and postpone all the details to Appendix B. In the last, we show that the conditions of Theorem 3.1 can be met with our model assumptions in Section 2, our initialization scheme in Section 3.4, and our stepsize choice (3.2), with sufficient number of samples m and proper sparsity level p of the corruption s. Define θ_ϵ to be the left quantile of the folded normal distribution $|Z|$, $Z \sim N(0,1)$, i.e., $\mathbb{P}(Z \leq \theta_\epsilon) = \epsilon$. The quantile function is used for the stepsize condition. For both RC and AC models, we now state our results as follows.

Theorem 3.2. *Suppose under Model 1, we have $m \geq c_1 dk^3 \kappa^{12} (\log \kappa + \log k) \log d$ and $p \leq \frac{c_2}{\kappa^3 \sqrt{k}}$ for some universal constants c_1, c_2. And under Model 2, we have fixed $p < \frac{1}{2}$ and $m \geq c_3 dk^3 \kappa^{12} (\log \kappa + \log k) \log d$ for some $c_3 > 0$ dependent only on p. Then under both models, with probability at least $1 - c_4 \exp(-c_5 \frac{m}{\kappa^{12} k^2})$ for some universal constants c_4, c_5, our subgradient method (3.1) with the initialization in Algorithm 1, and the adaptive stepsize choice (3.2) with $C_\eta \in [\frac{c_6}{\theta_{1 - \frac{0.5-p}{3}}} \frac{\sigma_r}{\sigma_1^2}, \frac{c_7}{\theta_{1 - \frac{0.5-p}{3}}} \frac{\sigma_r}{\sigma_1^2},]$ with some universal $c_6, c_7 \leq 0.001$, converges as stated in Theorem 3.1.*

The proof follows by verifying the three conditions in Theorem 3.1. The initialization scheme is verified in Proposition 3.3 in Section 3.4. The RDPP is verified in Proposition 2.2. We defer the verification of the validity of our stepsize rule (3.2) to Appendix E.

Note that the initialization condition in Theorem 3.1 is weaker than those in the literature [4, 5], which requires $F_0 F_0^\top$ to be close to $X_\natural$. Instead, we allow a constant multiple c^* in the initialization condition (3.3). This means we only require $F_0 F_0^\top$ to be accurate in the direction of $X_\natural$ and allows a crude estimate of the scale $\|X_\natural\|_F$. This in turn allows us to have p close to $\frac{1}{2}$ in Theorem 3.2 for the RC Model.[6] If we require $p \lesssim \frac{1}{\kappa \sqrt{r}}$ in both models, which is assumed in [4, 5], then the sample complexity can be improved to $O(dk^3 \kappa^4 (\log \kappa + \log k) \log d)$ and the convergence rate can also be improved. See Appendix H for more details.

3.3 A sketch of analysis for Theorem 3.1

In the following, we briefly sketch the high-level ideas of the proof for Theorem 3.1.

Closeness of the subgradient dynamics to its smooth counterpart. To get the main intuition of our analysis, for simplicity let us first consider the noiseless case, i.e., $s_i = 0$ for all i. Now the objective $f(F)$ in (1.2) has expectation $\mathbb{E}f(F) = \frac{1}{2} \mathbb{E} |\langle A_1, FF^\top - X_\natural \rangle| = \sqrt{\frac{1}{2\pi}} \|FF^\top - X_\natural\|_F$. Hence, when minimizing this expected loss, the subgradient update at F_t with $F_t F_t^\top \neq X_\natural$ becomes

$$F_0 \in \mathbb{R}^{d \times k}; \quad F_{t+1} = F_t - \eta_t \nabla \mathbb{E}f(F) \mid_{F=F_t} = F_t - \eta_t \sqrt{\frac{2}{\pi}} \frac{(F_t F_t^\top - X_\natural)}{\|F_t F_t^\top - X_\natural\|_F} F_t, \ t = 0, 1, 2, \ldots.$$

If we always have $\eta_t \sqrt{\frac{2}{\pi}} = \gamma \|F_t F_t^\top - X_\natural\|_F$ for some $\gamma > 0$, then the above iteration scheme becomes the gradient descent for the smooth problem $\min_{F \in \mathbb{R}^{d \times k}} \|FF^\top - X_\natural\|_F^2$:

$$F_0 \in \mathbb{R}^{d \times k}; \quad F_{t+1} = F_t - \gamma (F_t F_t^\top - X_\natural) F_t, \ t = 0, 1, 2, \ldots. \tag{3.4}$$

Recent work [15] showed that when no corruption presents, the gradient decent dynamic (3.4) converges to the exact rank solution in the rank overspecified setting. Thus, under the robustness setting, our major intuition of stepsize design for the subgradient methods is to ensure that subgradient dynamics (3.1) for finite samples mimic the gradient descent dynamic (3.4). To show this, we need $\eta_t g_t$ in (3.1) to approximate $(F_t F_t^\top - X_\natural) F_t$ up to some multiplicative constant γ, which is indeed ensured by the conditions *(ii)* and *(iii)* in Theorem 3.1. Detailed analysis appears in Appendix B.

Three-stage analysis of the subgradient dynamics. However, recall our condition *(i)* in Theorem 3.1 only ensures that the initial $F_0 F_0^\top$ is close to the ground truth $X_\natural$ up to some constant scaling factor. Thus, different from the analysis for matrix sensing with no corruptions [15], here we need to deal with the issue where the initial $\|F_0 F_0^\top - X_\natural\|$ could be quite large. To deal with this issue, we introduce extra technicalities by decomposing the iterate F_t into two parts, and conduct a three-stage

---

[6]The work [13] actually allows for p to be close to 1 under a simpler RC model. The main reason is that they assume the scale information $\|X_\natural\|_F$ is known a priori and their guarantee is only approximate $\|FF^\top - X_\natural\|_F \lesssim \delta \log \delta$ for a rank-1 $X_\natural$. However, estimating $\|X_\natural\|_F$ accurately requires p to be close to 0.

Algorithm 1: Spectral Initialization

Input: the sensing matrix $\{A_i\}_{i=1}^{m}$ and observations $\{y_i\}_{i=1}^{m}$

    Form $D = \frac{1}{m}\sum_{i=1}^{m}\text{sign}(y_i)A_i$, and compute the top-$k$ eigenpairs of D.

    Collect the eigenvectors as $U \in \mathbb{R}^{d\times k}$, and the eigenvalues as the diagonals of $\Sigma \in \mathbb{R}^{k\times k}$.

    Compute $B = U(\Sigma_+)^{\frac{1}{2}}$ where Σ_+ is the nonnegative part of Σ.

    Compute the median $\xi_{\frac{1}{2}}(\{|y_i|\}_{i=1}^{m})$, and set $\gamma = \xi_{\frac{1}{2}}(\{|y_i|\}_{i=1}^{m})/\theta_{\frac{1}{2}}$.

Output: $F_0 = \sqrt{\gamma}B$.

---

analysis of the iterates. More specifically, since $X_\natural$ is rank r and PSD, let its SVD be

$$X_\natural = [U \quad V] \begin{bmatrix} D_S^* & 0 \\ 0 & 0 \end{bmatrix} [U \quad V]^\top, \tag{3.5}$$

where $D_S^* \in \mathbb{R}^{r\times r}$, $U \in \mathbb{R}^{d\times r}$, and $V \in \mathbb{R}^{d\times(d-r)}$. Here U and V are orthonormal matrices and complement to each other, i.e., $U^\top V = 0$. Thus, for any $F_t \in \mathbb{R}^{d\times r}$, we can always decompose it as

$$F_t = US_t + VT_t, \tag{3.6}$$

where $S_t = U^\top F_t \in \mathbb{R}^{r\times k}$ stands for the signal term and $T_t = V^\top F_t \in \mathbb{R}^{(d-r)\times k}$ stands for an error term. Based on this, we show the following (we refer to Appendix B for the details.):

Stage 1. We characterize the evolution of the smallest singular value $\sigma_r(S_t)$, showing that it will increase above a certain threshold, so that $F_tF_t^\top$ is moving closer to the scaling of $X_\natural$.

Stage 2. We show that the quantity $Q_t = \max\{\|S_tS_t^\top - D_S^*\|, \|S_tT_t^\top\|\}$ decrease geometrically. In the analysis, for first two stages, T_t may not decrease, and the first two stages consist of the burn-in phase $\mathcal{T}$.

Stage 3. We control $E_t = \max\{\|S_tS_t^\top - D_S^*\|, \|S_tT_t^\top\|, \|T_tT_t^\top\|\}$, showing that $E_t \to 0$ at a rate $O(1/t)$ due to the slower convergence of $\|T_tT_t^\top\|$. This further implies that $\|F_tF_t^\top - X_\natural\|$ converges to 0 at a sublinear rate $O(1/t)$. For the case $k = r$, the convergence speeds up to linear due to a better control of $\|T_tT_t^\top\|$.

3.4 Initialization schemes

In this section, we introduce a spectral initialization method as presented in Algorithm 1. The main intuition is that the cooked up matrix D in Algorithm 1 has an expectation $\mathbb{E}(D) = \psi(X)\frac{X}{\|X\|_F}$, so that the obtained factor $BB^\top$ from D should be pointed to the same direction as $X_\natural$ up to a scaling. We then multiply B by a suitable quantity to produce an initialization F_0 on the same scale as $X_\natural$. More specifically, given that θ_ϵ is the left quantile of folded normal distribution introduced before Theorem 3.2, we state our result as follows.

Proposition 3.3. *Let F_0 be the output of Algorithm 1. Fix constant $c_0 < 0.1$. For model 1 with $p \leq \frac{\tilde{c}_0}{\kappa^2\sqrt{r}}$ where $\tilde{c}_0$ depends only on c_0, there exist constants c_1, c_2, c_3 depending only on c_0 such that whenever $m \geq c_1 dr\kappa^4(\log\kappa + \log r)\log d$, we have*

$$\|F_0F_0^\top - c^*X_\natural\| \leq c_0\sigma_r/\kappa. \tag{3.7}$$

with probability (w.p.) at least $1 - c_2\exp(-\frac{c_3 m}{\kappa^4 r})$, where $c^* = \theta_{\frac{1}{2}}$. For Model 2 with a fixed $p < 0.5$ and $m \geq c_4 dr\kappa^4(\log\kappa + \log r)\log d$. Then (3.7) also holds for $c^* \in \left[\sqrt{\frac{1}{2\pi}} \cdot \frac{\theta_{\frac{0.5-p}{3}}}{\theta_{\frac{1}{2}}}, \sqrt{\frac{2}{\pi}} \cdot \frac{\theta_{1-\frac{0.5-p}{3}}}{\theta_{\frac{1}{2}}}\right]$ w.p. at least $1 - c_5\exp(-\frac{c_6 m}{\kappa^4 r})$, where the constants c_4, c_5, c_6 depend only on p and c_0.

The details of the proof can be found in Appendix F. It should be noted in (3.7) that our guarantee ensures $F_0F_0^\top$ is close to $X_\natural$ up to a scalar multiple c^*, instead of the usual guarantees on $\|F_0F_0^\top - X_\natural\|$ [4, 5]. If $p \lesssim \frac{1}{\sqrt{r}\kappa}$, we obtain $\|F_0F_0^\top - X_\natural\| \leq c_0\sigma_r$ in Proposition F.2 and the sample complexity m improves to $dr\kappa^2\log d(\log\kappa + \log r)$.

4 Experiments

In this section, we provide numerical evidence to verify our theoretical discoveries on robust matrix recovery in the rank overspecified regime. First, for robust low-rank matrix recovery, Section 4.1

(a) $k = r$	(b) $k = 2r$	(c) $k = d$

Figure 1: **Convergence of the subgradient method** (3.1) **with different stepsize rules** in the regimes of (a) exact-parameterization $k = r$, (b) rank overspecication $k = 2r$, and (c) over-parameterization $k = d$. We use the following stepsizes: constant stepsizes $\eta_t = \eta_0$, geometric diminishing stepsizes $\eta_t = \eta_0 \cdot 0.9^t$, sublinear diminishing stepsizes $\eta_t = \eta_0/t$, the proposed stepsizes (3.2), and the Polyaks's stepsize.

273 shows that the subgradient method with proposed diminishing stepsizes can (i) exactly recover the
274 underlying low-rank matrix from its linear measurements even in the presence of corruptions and
275 the rank is overspecified, and (ii) prevent overfitting and produce high-quality solution even in the
276 highly over-parameterized regime $k = d$. Furthermore, we apply the strategy of diminishing stepsizes
277 for robust image recovery with DIP [14, 16, 30] in Section 4.2, demonstrating its effectiveness in
278 alleviating overfitting. The experiments are conducted with Matlab 2018a and Google Colab [31].

279 ### 4.1 Robust recovery of low-rank matrices

280 **Data generation and experiment setup.** For any given d and r,
281 we generate the ground truth $X_\natural = F_\natural F_\natural^\top$ with entries of $F_\natural \in \mathbb{R}^{d \times r}$
282 *i.i.d.* from standard normal distribution, and then normalize $X_\natural$ such
283 that $\|X_\natural\|_{\mathrm{F}} = 1$. Similarly, we generate the m sensing matrices
284 $A_1, \ldots, A_m$ to be GOE matrices discussed in Section 2.1. For
285 any given corruption ratio p, we generate the corruption vector
286 $s \in \mathbb{R}^m$ according to the AC model, by randomly selecting $\lfloor pm \rfloor$
287 locations to be nonzero and generating those entries from a *i.i.d.* zero-
288 mean Gaussian distribution with variance 100. We then generate
289 the measurement according to (1.1), i.e., $y_i = \langle A_i, X_\natural \rangle + s_i, i =$
290 $1, \ldots, m$, and we set $n = 100$, $p = 0.2$, and $m = 10nr$. We run the
291 subgradient methods for 10^3 iterations using the following different
292 stepsizes: (i) the constant stepsize $\eta_t = 0.1$ for all $t \geq 0$, (ii)
293 sublinear diminishing stepsizes[7] $\eta_t = \eta_0/t$, (iii) geometrically diminishing stepsizes $\eta_t = \eta_0 \cdot 0.9^t$,
294 (iv) the proposed stepsizes (3.2) with $C_\eta = \frac{1}{2}$, and (v) the Polyak stepsize rule [32] which is given
295 by $\eta_t = \frac{f(F) - f^\star}{\|g_t\|_{\mathrm{F}}^2}$, where $f^\star$ is the optimal value of (1.2) and g_t is the subgradient in (3.1). We use
296 the spectral initialization illustrated in Section 3.4 to generate the initialization F_0.

Figure 2: **Comparison of the proposed stepsize in** (3.2) **and the Polyak stepsize** in the regimes of the exact-parameterization $k = r$ and the rank overspecification $k = 2r$.

297 **Observations from the experimental results.** We run the subgradient method with different
298 stepsize rules and different rank $k = r$, $2r$, and d, and compute the reconstruction error $\|F_t F_t^\top -$
299 $X_\natural\|_{\mathrm{F}}$ for the output of the algorithms. From Figure 1 and Figure 2, our observations are the follows.

300 • *Exact rank case $k = r$.* As shown in Figure 1a, we can see that *(i)* the subgradient method with
301   constant stepsizes does not converge to the target matrix, *(ii)* using sublinear diminishing stepsizes
302   results in a sublinear convergence rate, *(iii)* geometrically diminishing or Polyak[8] stepsizes converge
303   at a linear rate, consistent with the observation in [5], and *(iv)* the proposed stepsize rule also leads
304   to convergence to the ground-truth at a linear rate, which is consistent with Theorem 3.1.

305 • *Overspecified rank case $k = 2r$.* As shown in Figure 1b, the subgradient method with any stepsize
306   rule converges at most a sublinear rate, while constant or geometrically diminishing stepsizes result
307   in poor solution accuracy. The proposed stepsize rule achieves on par convergence performance with
308   the sublinear stepsize rule, which also demonstrates our Theorem 3.1 on the sublinear convergence
309   in the rank overspecified setting. As shown in Figure 2, the proposed strategy (3.2) gives stepsizes
310   similar to Polyak's, and thus both resulting in a similar convergence rate (or the Polyak's is slightly
311   better). However, the Polyak stepsize rule requires knowing the optimal value of the objective
312   function, which is usually unknown a prior in practice.

---

[7]For the two diminising stepsizes, we set $\eta_0 = 2$ when $k = r$ or $2r$, and $\eta_0 = 5$ when $k = d$.

[8]As guaranteed by Theorem 2.3, in this case, the optimal value $f^\star$ is achieved at $F_\natural$.

313 • *Overparameterized case $k = d$.* The results are shown in Figure 1c.[9] In this case, inspired
314 by [13, 26], we use an alternative tiny initialization F_0 by drawing its entries from *i.i.d.* zero-mean
315 Gaussian distribution with standard deviation 10^{-7}. We first note that the constant stepsize rule
316 results in overfitting. In contrast, the proposed diminishing stepsizes can prevent overfitting issues
317 and find a very high-quality solution. We conjecture this is due to certain implicit regularization
318 effects [14, 25, 26] and we leave thorough theoretical analysis as future work.

4.2 Robust recovery of natural images with deep image prior

320 Finally, we conduct an exploratory experiment on robust image recovery with DIP [14, 16]. Here,
321 the goal is to recover a natural image $X_\natural$ from its corrupted measurement $y = X_\natural + s$, where s
322 denotes noise corruptions. To achieve this, the DIP fits the observation by a highly overparameterized
323 deep U-Net[10] $\phi(\Theta)$ by solving $\min_\Theta \|y - \phi(\Theta)\|_\square$ [35], where Θ denotes network parameters and
324 the norm $\|\cdot\|_\square$ can be either ℓ_2 or ℓ_1 depending on the type of noises. As shown in [14, 16, 30], by
325 learning the parameters Θ, the network first reveals the underlying clear image and then *overfits* due
326 to overparameterization, so that in many cases *early stopping* is *crucially* needed for its success.

327 In contrast to the constant stepsize rule, here we show a surprising
328 result that, for sparse corruptions, optimizing a robust loss using the
329 subgradient method with a diminishing stepsize rule does not overfit.
330 In particular, we consider a sparse corruption s by impulse salt-and-
331 pepper noise, and solve the robust DIP problem $\min_\Theta \|y - \phi(\Theta)\|_1$
332 using the subgradient method with a diminishing stepsize rule. We
333 test the performance using three images, "F16", "Peppers" and
334 "Lena" from a standard dataset [36], where we contaminate the
335 image with salt-and-pepper noise by randomly replacing 50% pixels
336 with either 1 or 0 (each happens with 50% probability). We compare
337 the subgradient method with constant stepsize 0.01 (or learning rate)
338 and diminishing stepsize (we use an initial stepsize 0.05 which is
339 then scaled by 0.96 for every 50 iterations). As shown in Figure 3,
340 the subgradient method with constant stepsize eventually overfits
341 so that it requires early stopping. In comparison, optimization with

Figure 3: **Learning curves for robust image recovery with DIP** on different test images with 50% salt-and-pepper noise. Here, we compare the constant and diminishing stepsize rules for DIP.

342 diminishing stepsize prevents overfitting in the sense that the performance continues to improve
343 as training proceeds, and it achieves on par performance with that of constant stepsizes when the
344 learning is early stopped at the optimal PSNR. However, early stopping is not easy to implement in
345 practice without knowing the clean image *a priori*.

5 Discussion

347 In this work, we designed and analyzed a subgradient method for the robust matrix recovery problem
348 under the rank overspecified setting, showing that it converges to the exact solution with a sublinear
349 rate. Based on our results, there are several directions worth further investigation.

350 • *Implicit regularization*. As explored and demonstrated in our experiments in Section 4, our stepsize
351 choice combined with random initialization recovers $X_\natural$ with high accuracy, even if $k \geq r$ and the
352 number of samples m is way less than the degree of freedom (i.e., $m = O(dr)$). Theoretically
353 justifying this phenomenon in the overparameterized regime would be of great interest.
354 • *Other sensing matrix*. In this work, we assume A_i to be a GOE matrix. This specific assumption
355 on the measurement matrix still seems to be restrictive. Generalizing our results to more generic
356 sensing matrices would also be an interesting future direction.
357 • *Rectangular matrices*. In this work, we utilize the fact that $X_\natural$ is PSD, and optimize over one factor
358 F. This is consistent with much existing analysis with rank overspecification [13, 15, 26]. For
359 rectangular $X_\natural$, we need to optimize over two factors U, V. How to combine the analysis here with
360 an extra regularization $\|UU^\top - VV^\top\|_F^2$ in the objective is another interesting direction to pursue.

---

[9]We omit the performance of the Polyak stepsizes since in this case the optimal value $f^\star$ is not easy to compute; it may not be achieved at $F_\natural$ due to the overfitting issue. Our experiments indicate that the Polyak stepsizes do not perform well when computed by setting the optimal value as either 0 or the value at $F_\natural$.

[10]Following [16] (license obtained from [33]), we use the same U-shaped architecture with skip connections, each layer containing a convolution, a nonlinear LeakyReLU and a batch normalization units, Kaiming initialization for network parameters, and Adam optimizer [34]. We set the network width as 192 as used in [14].

References

[1] Emmanuel J Candès, Xiaodong Li, Yi Ma, and John Wright. Robust principal component analysis? *Journal of the ACM (JACM)*, 58(3):1–37, 2011.

[2] Yuanxin Li, Yue Sun, and Yuejie Chi. Low-rank positive semidefinite matrix recovery from corrupted rank-one measurements. *IEEE Transactions on Signal Processing*, 65(2):397–408, 2016.

[3] Markus Rambach, Mahdi Qaryan, Michael Kewming, Christopher Ferrie, Andrew G White, and Jacquiline Romero. Robust and efficient high-dimensional quantum state tomography. *Physical Review Letters*, 126(10):100402, 2021.

[4] Yuanxin Li, Yuejie Chi, Huishuai Zhang, and Yingbin Liang. Non-convex low-rank matrix recovery with arbitrary outliers via median-truncated gradient descent. *Information and Inference: A Journal of the IMA*, 9(2):289–325, 2020.

[5] Xiao Li, Zhihui Zhu, Anthony Man-Cho So, and Rene Vidal. Nonconvex robust low-rank matrix recovery. *SIAM Journal on Optimization*, 30(1):660–686, 2020.

[6] Vasileios Charisopoulos, Yudong Chen, Damek Davis, Mateo Díaz, Lijun Ding, and Dmitriy Drusvyatskiy. Low-rank matrix recovery with composite optimization: good conditioning and rapid convergence. *Foundations of Computational Mathematics*, pages 1–89, 2021.

[7] Tian Tong, Cong Ma, and Yuejie Chi. Low-rank matrix recovery with scaled subgradient methods: Fast and robust convergence without the condition number. *IEEE Transactions on Signal Processing*, 2021.

[8] Roman Vershynin. Introduction to the non-asymptotic analysis of random matrices. *arXiv preprint arXiv:1011.3027*, 2010.

[9] Joel A Tropp. User-friendly tail bounds for sums of random matrices. *Foundations of computational mathematics*, 12(4):389–434, 2012.

[10] Roman Vershynin. *High-dimensional probability: An introduction with applications in data science*, volume 47. Cambridge university press, 2018.

[11] Martin J Wainwright. *High-dimensional statistics: A non-asymptotic viewpoint*, volume 48. Cambridge University Press, 2019.

[12] John C Duchi and Feng Ruan. Solving (most) of a set of quadratic equalities: Composite optimization for robust phase retrieval. *Information and Inference: A Journal of the IMA*, 8(3):471–529, 2019.

[13] Jianhao Ma and Salar Fattahi. Implicit regularization of sub-gradient method in robust matrix recovery: Don't be afraid of outliers. *arXiv preprint arXiv:2102.02969*, 2021.

[14] Chong You, Zhihui Zhu, Qing Qu, and Yi Ma. Robust recovery via implicit bias of discrepant learning rates for double over-parameterization. In *Advances in Neural Information Processing Systems*, 2020.

[15] Jiacheng Zhuo, Jeongyeol Kwon, Nhat Ho, and Constantine Caramanis. On the computational and statistical complexity of over-parameterized matrix sensing. *arXiv preprint arXiv:2102.02756*, 2021.

[16] Dmitry Ulyanov, Andrea Vedaldi, and Victor Lempitsky. Deep image prior. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 9446–9454, 2018.

[17] Benjamin Recht, Maryam Fazel, and Pablo A Parrilo. Guaranteed minimum-rank solutions of linear matrix equations via nuclear norm minimization. *SIAM review*, 52(3):471–501, 2010.

[18] Yudong Chen, Ali Jalali, Sujay Sanghavi, and Constantine Caramanis. Low-rank matrix recovery from errors and erasures. *IEEE Transactions on Information Theory*, 59(7):4324–4337, 2013.

[19] Ruoyu Sun and Zhi-Quan Luo. Guaranteed matrix completion via non-convex factorization. *IEEE Transactions on Information Theory*, 62(11):6535–6579, 2016.

[20] Srinadh Bhojanapalli, Behnam Neyshabur, and Nathan Srebro. Global optimality of local search for low rank matrix recovery. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, pages 3880–3888, 2016.

[21] Rong Ge, Chi Jin, and Yi Zheng. No spurious local minima in nonconvex low rank problems: A unified geometric analysis. In *International Conference on Machine Learning*, pages 1233–1242. PMLR, 2017.

[22] Zhihui Zhu, Qiuwei Li, Gongguo Tang, and Michael B Wakin. Global optimality in low-rank matrix optimization. *IEEE Transactions on Signal Processing*, 66(13):3614–3628, 2018.

[23] Yuejie Chi, Yue M Lu, and Yuxin Chen. Nonconvex optimization meets low-rank matrix factorization: An overview. *IEEE Transactions on Signal Processing*, 67(20):5239–5269, 2019.

[24] Yuqian Zhang, Qing Qu, and John Wright. From symmetry to geometry: Tractable nonconvex problems. *arXiv preprint arXiv:2007.06753*, 2020.

[25] Suriya Gunasekar, Blake Woodworth, Srinadh Bhojanapalli, Behnam Neyshabur, and Nathan Srebro. Implicit regularization in matrix factorization. In *2018 Information Theory and Applications Workshop (ITA)*, pages 1–10. IEEE, 2018.

[26] Yuanzhi Li, Tengyu Ma, and Hongyang Zhang. Algorithmic regularization in over-parameterized matrix sensing and neural networks with quadratic activations. In *Conference On Learning Theory*, pages 2–47. PMLR, 2018.

[27] James V Burke and Michael C Ferris. Weak sharp minima in mathematical programming. *SIAM Journal on Control and Optimization*, 31(5):1340–1359, 1993.

[28] Yuxin Chen, Jianqing Fan, Cong Ma, and Yuling Yan. Bridging convex and nonconvex optimization in robust pca: Noise, outliers, and missing data. *arXiv preprint arXiv:2001.05484*, 2020.

[29] Francis H Clarke, Yuri S Ledyaev, Ronald J Stern, and Peter R Wolenski. *Nonsmooth analysis and control theory*, volume 178. Springer Science & Business Media, 2008.

[30] Reinhard Heckel and Mahdi Soltanolkotabi. Denoising and regularization via exploiting the structural bias of convolutional generators. *arXiv preprint arXiv:1910.14634*, 2019.

[31] Ekaba Bisong. Google colaboratory. In *Building Machine Learning and Deep Learning Models on Google Cloud Platform*, pages 59–64. Springer, 2019.

[32] Boris Teodorovich Polyak. Minimization of unsmooth functionals. *USSR Computational Mathematics and Mathematical Physics*, 9(3):14–29, 1969.

[33] `https://github.com/DmitryUlyanov/deep-image-prior/blob/master/LICENSE`.

[34] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[35] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

[36] `http://www.cs.tut.fi/~foi/GCF-BM3D/index.html#ref_results/`.

[37] Emmanuel J Candes and Yaniv Plan. Tight oracle inequalities for low-rank matrix recovery from a minimal number of noisy random measurements. *IEEE Transactions on Information Theory*, 57(4):2342–2359, 2011.