Cross-Modal Generative Augmentation for Multimodal Biological Classification

Abstract

Recent advances in vision-language models have enabled cross-modal generation between text and images, achieving remarkable progress in general-domain understanding. However, their potential in scientific and biological applications remains largely unexplored, where datasets often couple complex visual observations with structured metadata or textual descriptors. We propose a cross-modal generative framework that leverages both text-to-image and image-to-text generation to enrich multimodal biological classification. Our framework integrates generative augmentation and multimodal alignment to mutually refine visual and textual representations, enabling the synthesis of complementary modality data that may otherwise be unavailable in biological datasets. Experimental results on the HAM10000 and EMPO500 datasets demonstrate consistent gains in accuracy and generalization across diverse biological datasets, achieving 3-5% improvements over baseline models. The proposed framework is model-agnostic and compatible with open-weight alternatives, paving the way for biologically grounded multimodal generation and analysis.

1 Introduction

Large vision-language models (VLMs) have recently shown impressive capabilities in cross-modal generation, enabling the synthesis of semantically coherent text and images from multimodal inputs (Soufleri & Ananiadou, 2025; Koh et al., 2023; Chow et al., 2024). While these advances have transformed visual understanding and creative tasks, their potential in scientific and biological domains remains underexplored (Zhang et al., 2024). Biological and environmental datasets often couple complex visual patterns with structured metadata or descriptive annotations, for example, linking visual findings in dermatology to diagnostic attributes or connecting environmental measurements to contextual descriptions. In many biological datasets, however, one modality is often incomplete, noisy, or entirely missing due to limited annotations or acquisition constraints. Generative modeling therefore provides a practical mechanism for synthesizing complementary modalities that would otherwise be unavailable, enabling richer multimodal learning without requiring additional data collection. Bridging these modalities through generative modeling offers a promising path to enhance data efficiency (Du et al., 2022) and interpretability in biological classification.

However, existing multimodal approaches often focus on a single generative direction (Shi et al., 2024; Liang et al., 2024), employing either image-to-text or text-to-image generation in isolation. Such one-way mappings limit the mutual adaptation between modalities and prevent the exchange of semantic knowledge that could otherwise reinforce both representations. Moreover, biological datasets are generally small, heterogeneous, and domain-specific, which amplifies the difficulty of cross-modal alignment and augmentation (Nam & Jang, 2024).

To address these challenges, we propose a cross-modal generative augmentation framework that leverages both image-to-text and text-to-image generation to synthesize complementary modality data for multimodal biological classification. In the HAM10000 dermatology dataset (Tschandl et al., 2018), the framework uses image-to-text generation to produce EHR (Electronic Health Record)-like diagnostic narratives from dermoscopic images and metadata. These generated descriptions are fused with visual embeddings through a lightweight vision–metadata fusion module, improving interpretability and classification accuracy. Con-

versely, in the EMPO500 microbiome dataset, text-to-image generation produces synthetic environmental imagery conditioned on tabular metadata, expanding the visual space for downstream training. Both directions employ generative augmentation as auxiliary components, while the overall design remains model-agnostic, allowing compatibility with both closed and open-weight generative models.

Independent Cross-Modal Generative Augmentation.

Our framework employs two independent generative augmentation pathways: image-to-text and text-to-image. These generators synthesize complementary modality data that are incorporated into a shared multimodal classifier.

Image-to-text generation expands semantic metadata grounded in visual evidence, while text-to-image generation expands the visual feature space conditioned on structured context. Rather than enforcing direct reconstruction or cycle-consistency objectives, the two pathways operate independently and interact through the shared multimodal classifier.

Extensive experiments demonstrate that our approach achieves competitive performance against strong unimodal and unidirectional baselines, improving both generalization and multimodal coherence across datasets. By coupling generative augmentation with representation-level fusion, the proposed framework provides a practical approach for biologically grounded multimodal analysis.

Model / Framework	Visual + Text Fusion	Text→Image Generation	Image→Text Generation
ALBEF (Adebiyi et al., 2024)	✓	✗	✗
BiomedCLIP (Zhang et al., 2025)	✓	✗	✓
BackModality (Li et al., 2023)	✗	✓	✓
Multimodal Stress Detection (Soufleri & Ananiadou, 2025)	✓	✓	✗
TaxaBind (Sastry et al., 2025)	✓	✗	✗
Our Work (Cross-Modal Gen.)	✓	✓	✓

Table 1: Comparison of multimodal and generative models. A checkmark (✓) indicates support for the corresponding capability.

Our main contributions are as follows:

- We introduce a cross-modal generative augmentation framework that leverages both image-to-text and text-to-image generation to support multimodal biological classification.

- The framework enables the synthesis of complementary modality data that may otherwise be unavailable in biological datasets.

- We design a fusion strategy that combines generative augmentation and multimodal alignment, allowing textual and visual modalities to mutually reinforce each other.

- We empirically validate the framework on two heterogeneous biological datasets, demonstrating consistent and competitive gains in accuracy, interpretability, and generalization.

2 Related Work

Multimodal Learning in Biological and Biomedical Domains Recent multimodal learning approaches have demonstrated that integrating visual and textual modalities can improve performance in biomedical and ecological tasks (Zhang et al., 2025; Sun et al., 2023; Thapa et al., 2024). In dermatology, multimodal frameworks such as ALBEF-based systems (Adebiyi et al., 2024) have combined dermoscopic images with patient metadata (e.g., age, sex, lesion location) to achieve high accuracy on HAM10000 and ISIC datasets, showing the effectiveness of vision–metadata fusion for diagnosis. Similarly, multimodal encoders (Amar et al., 2025; Sastry et al., 2025) have been applied to microbiome and ecological data, where textual or tabular metadata complements visual information to enhance classification robustness under data imbalance. However, these studies largely rely on fixed visual inputs and static text encoders, limiting their adaptability when one modality is scarce or missing.

Figure 1: **Overview of the proposed cross-modal generative augmentation framework.** The left panel illustrates the multimodal fusion and classification architecture, which integrates image and metadata inputs through a visual encoder, a textual encoder, and a gated fusion (GLU) module followed by a classifier head. The right panel shows the cross-modal generative augmentation modules: (top) image-to-text generation produces EHR-like diagnostic narratives from dermoscopic images and metadata (HAM10000); (bottom) text-to-image generation synthesizes environmental imagery from tabular metadata (EMPO500). Both generated modalities are incorporated into the shared multimodal classifier, enabling complementary information flow across modalities.

Generative Models for Multimodal Data Augmentation   Generative modeling has recently emerged as a promising solution to bridge information gaps between modalities (Li et al., 2023; Xiao et al., 2023; Wu et al., 2024). Vision–language models such as diffusion-based text-to-image generators and large language models for captioning have shown potential in synthesizing biologically meaningful representations. Previous work has shown that fusing real and synthesized images guided by textual context enhances multimodal classification performance in social and affective computing (Soufleri & Ananiadou, 2025). In biological settings, text-guided synthetic imagery has been used to augment rare classes in datasets like HAM10000 and EMPO collections, leading to improved generalization without manual data expansion. Nonetheless, most prior work employs *unidirectional* generation—either from text to image or from image to text—without leveraging the complementary information between both directions.

Cross-Modal Generative Augmentation Framework   Our work builds upon these lines of research by introducing a cross-modal generative augmentation framework that unifies text-to-image and image-to-text generation for multimodal biological classification. Unlike existing approaches that rely solely on one modality as input, our method enables cross-modal interaction between visual and textual representations, improving alignment and interpretability. While prior multimodal fusion studies have focused on deterministic feature concatenation or joint embedding spaces, our framework leverages generative augmentation and multimodal alignment to establish a more adaptive, data-efficient learning paradigm. As illustrated in Table 1, our framework combines visual–text fusion with both text-to-image and image-to-text generation within a unified classification pipeline. This design enables the synthesis of complementary modality data and facilitates biologically grounded multimodal generation and analysis.

3 Method

3.1 Overview

Our goal is to improve biological classification by combining generative augmentation and multimodal fusion. Rather than enforcing a single end-to-end mapping between modalities, our approach performs two complementary generative augmentations—*image-to-text* and *text-to-image*—each enriching one modality using information from the other. The generated samples are incorporated into downstream training as auxiliary inputs, allowing both visual and textual (or tabular) encoders to learn more robust, semantically aligned representations (Fig. 1).

Formally, given paired modalities x_v (image) and x_t (metadata), the framework defines two generators:

$$\tilde{x}_t = \mathcal{G}_{v \to t}(x_v), \quad \tilde{x}_v = \mathcal{G}_{t \to v}(x_t),$$

where $\mathcal{G}_{v \to t}$ produces textual or structured metadata from visual cues, and $\mathcal{G}_{t \to v}$ synthesizes pseudo-visual samples conditioned on metadata. Both generated sets $\tilde{x}_t$ and $\tilde{x}_v$ are used to expand the original dataset. A unified fusion classifier $\mathcal{F}$ then learns from this augmented space through modality-specific encoders Φ_v and Φ_t, producing the final label prediction $y = \mathcal{F}([\Phi_v(x_v), \Phi_t(x_t)])$. This strategy maintains modularity between the generative and discriminative components while enabling complementary information exchange across modalities. Table 2 summarizes the main symbols used throughout this paper. Unlike tightly coupled or round-trip generative training, which can propagates errors across modalities, our loosely coupled design avoids error amplification while preserving the benefits of cross-modal augmentation. As shown in Appendix E, round-trip generation consistently yielded lower performance than the proposed one-pass augmentation strategy.

3.2 Cross-Modal Generative Augmentation

Image-to-Text (HAM10000). We use clinical image inputs paired with lesion metadata to generate structured narratives in an EHR-like schema. These textual augmentations, derived from patient and lesion features, mimic diagnostic documentation (e.g., *"pigmented lesion, asymmetric, irregular border"*) and serve as an auxiliary modality for multimodal fusion. Each generated record is vectorized into categorical and numerical embeddings (sex, site, anatomical region, visual findings, etc.), aligned with the real EHR-derived metadata. This module corresponds to the $\mathcal{G}_{v \to t}$ pathway.

Text-to-Image (EMPO500). Conversely, we synthesize images from environmental or biological metadata such as *env_biome*, *env_material*, and *sample_type*. This generation process uses tabular descriptors to condition a diffusion-based generator, producing pseudo-visual textures that capture ecological and environmental cues. The generated samples are used as additional training data for multimodal fusion, expanding the visual feature space and improving generalization under low-resource conditions. This corresponds to $\mathcal{G}_{t \to v}$ in our formulation.

3.3 Multimodal Fusion and Classification

To integrate both visual and tabular (or textual) modalities, we design a lightweight yet expressive **fusion network** composed of three main components: a vision backbone, a tabular encoder, and an adaptive fusion head.

Visual Encoder. We adopt a ConvNeXt-v2 (Woo et al., 2023) backbone pretrained on ImageNet-22K (Ridnik et al., 2021) as the visual encoder Φ_v. Given an input image x_v, the encoder extracts high-dimensional representations $z_v \in \mathbb{R}^{d_v}$ that capture morphological and structural information. This encoder remains frozen during the initial training phase to stabilize convergence under limited biological data.

Tabular or Textual Encoder. For metadata or generated textual representations, we employ a tabular encoder Φ_t implemented as a multi-layer perceptron (MLP) with learned embeddings for each categorical

Table 2: Summary of notation.

Symbol	Description
x_v	Input image (visual modality)
x_t	Input metadata or text (tabular modality)
$\tilde{x}_t$	Generated text from image-to-text generator $\mathcal{G}_{v \to t}$
$\tilde{x}_v$	Generated image from text-to-image generator $\mathcal{G}_{t \to v}$
Φ_v, Φ_t	Visual and tabular encoders
z_v, z_t, z_f	Visual, tabular, and fused embeddings
$\mathcal{F}$	Classification head
g	Gating coefficient in GLU fusion
y	Predicted label

feature (e.g., sex, anatomical site, or environmental biome). Each categorical feature x_t^i is embedded and concatenated to form the metadata vector $z_t \in \mathbb{R}^{d_t}$:

$$z_t = \text{MLP}\big([\text{Embed}(x_t^1)\|\text{Embed}(x_t^2)\|\cdots\|\text{Embed}(x_t^k)]\big).$$

This representation can flexibly encode either structured EHR metadata (HAM10000) or environmental context (EMPO500).

Gated Fusion. The visual and tabular embeddings are combined via a gated linear unit (GLU)-inspired mechanism (Dauphin et al., 2017; Tsai et al., 2019) that adaptively balances modality contributions:

$$g = \sigma(W_g[z_v\|z_t]), \quad z_f = g \odot z_v + (1-g) \odot z_t,$$

where $\sigma(\cdot)$ denotes the sigmoid activation and $[\cdot\|\cdot]$ indicates concatenation. This gating allows the model to dynamically emphasize the modality carrying more discriminative cues for each sample. The fused representation z_f is subsequently passed through a two-layer classification head to produce the predicted label:

$$y = \mathcal{F}(z_f) = \text{Softmax}(W_2 \text{ReLU}(W_1 z_f)).$$

Evaluation Modes. The fusion model supports three evaluation modes—*vision-only*, *tabular-only*, and *fusion*—by selectively masking inputs to isolate modality contributions. This enables an interpretable analysis of cross-modal complementarity and quantifies the impact of generated augmentation on performance.

3.4 Training Strategy

We employ a two-stage fine-tuning pipeline that balances stability and adaptability under small biological datasets.

Stage 1: Fusion Pretraining. The visual backbone Φ_v is frozen while training the tabular encoder Φ_t and fusion head $\mathcal{F}$ for 30 epochs using cross-entropy loss with label smoothing. This phase focuses on learning robust metadata representations and establishing stable multimodal alignment before full fine-tuning.

Stage 2: Full Fine-tuning. After convergence, we unfreeze Φ_v and jointly optimize all modules for 7 epochs using AdamW or Lion optimizer (Chen et al., 2023) with cosine-annealing warm restarts. This allows fine-grained adaptation of both modalities without catastrophic forgetting. Mixup-based regularization is applied with probability 0.3 to mitigate overfitting and encourage smoother decision boundaries.

Calibration and Test-time Augmentation. Following training, we apply logit bias calibration and temperature sweeping on the validation set to maximize macro-F1, improving robustness to class imbalance. Test-time augmentation (TTA) averages predictions across multiple color-jittered views to further stabilize inference.

Table 3: Performance comparison on the HAM10000 dataset. Results for InceptionV3, ResNet50, DenseNet121, and ALBEF variants are reported from (Adebiyi et al., 2024). Our models (Fusion + EHR-like generation) are implemented and evaluated under the same experimental setting.

Model	Accuracy	AUC	Macro F1	Recall	Precision
Standard Vision Backbones					
InceptionV3	0.865	0.859	0.784	0.761	0.820
ResNet50	0.850	0.839	0.729	0.713	0.782
DenseNet121	0.886	0.897	0.835	0.825	0.851
Multimodal Models (ALBEF)					
ALBEF Multimodal	0.941	0.914	0.903	0.852	0.896
ALBEF (Adebiyi et al., 2024) Image-only	0.913	0.943	0.869	0.902	0.907
Our Models (Fusion + EHR-like Report Generation)					
Fusion (w/o EHR)	0.885	0.980	0.818	0.783	0.864
Meta-only (w/o EHR)	0.195	0.699	0.078	0.224	0.163
Image-only (w/o EHR)	0.880	0.977	0.814	0.779	0.858
Fusion (+EHR-like generation)	**0.959**	**0.993**	**0.910**	0.892	**0.937**
Meta-only (+EHR-like generation)	0.295	0.933	0.353	0.481	0.504
Image-only (+EHR-like generation)	0.873	0.976	0.785	0.736	0.863

Table 4: Performance comparison on the HAM10000 dataset. Mean and standard deviation are reported as mean(std) over five runs.

Model	Accuracy	AUC	Macro F1	Recall	Precision
Fusion	**0.9570(0.0034)**	**0.9947(0.0011)**	**0.9050(0.0035)**	**0.8900(0.0113)**	**0.9247(0.0145)**
Image-only	0.8714(0.0058)	0.9739(0.0028)	0.7755(0.0169)	0.7474(0.0140)	0.8388(0.0498)
Meta-only	0.1747(0.1100)	0.9207(0.0152)	0.2080(0.1310)	0.3619(0.1629)	0.3511(0.1802)

Implementation. All experiments are conducted on a single NVIDIA A100 GPU with a batch size of 32. Hyperparameters (learning rates, epochs, and scheduler settings) are shared across datasets for comparability. The framework remains fully modular—different encoders or generators can be substituted without retraining the overall system. The code for reproducing all experiments is provided in the supplementary material.

4 Experiments

We conduct experiments across two complementary biological domains to evaluate whether cross-modal generative augmentation improves multimodal classification performance under data imbalance and limited supervision. All datasets are publicly available and selected to represent distinct modality pairings—image-to-text (HAM10000) and text-to-image (EMPO500). To ensure full reproducibility, all code used in our experiments is included in the supplementary material.

4.1 Datasets

4.1.1 Skin Lesion Classification (HAM10000)

The HAM10000 dataset (Adebiyi et al., 2024) consists of 10,015 dermatoscopic images across seven diagnostic categories: *akiec*, *bcc*, *bkl*, *df*, *mel*, *nv*, and *vasc*. The distribution is highly imbalanced (ranging from 115 to 6,705 samples per class), reflecting real-world prevalence in dermatology. Each image is paired with structured metadata, including patient age, sex, and anatomical site. For the image-to-text direction,

Table 5: Performance comparison of our models on the EMPO500 dataset. Mean and standard deviation are reported as mean(std) over five runs. Our method employs a text-to-image generation strategy for improved multimodal classification.

Model	Accuracy	Macro F1	Precision	Recall	AUC
Classical Baselines					
Logistic Regression (Hastie et al., 2009)	0.9337(0.0000)	0.7932(0.0000)	0.7869(0.0000)	0.8290(0.0000)	0.9970(0.0000)
Random Forest (Breiman, 2001)	0.9313(0.0013)	0.7967(0.0011)	0.7848(0.0013)	0.8429(0.0000)	0.9971(0.0000)
SVM (RBF) (Hearst et al., 1998)	0.9277(0.0000)	0.7940(0.0000)	0.7825(0.0000)	0.8429(0.0000)	0.9508(0.0081)
XGBoost (Chen & Guestrin, 2016)	0.9223(0.0013)	0.7346(0.0095)	0.7189(0.0097)	0.7845(0.0093)	0.9965(0.0001)
Our Models (Fusion with Text-to-Image Augmentation)					
Fusion (Vision+Tabular)	0.9373(0.0045)	0.8071(0.0113)	**0.8074(0.0122)**	0.8370(0.0081)	0.9698(0.0120)
Ensemble (Fusion+MLP)	**0.9386(0.0016)**	**0.8090(0.0059)**	0.8049(0.0076)	**0.8425(0.0062)**	**0.9974(0.0001)**
MLP (Tab-only)	0.9337(0.0000)	0.7876(0.0000)	0.7695(0.0000)	0.8324(0.0000)	0.9970(0.0000)
Tab-only	0.9133(0.0045)	0.7160(0.0176)	0.6975(0.0178)	0.7743(0.0201)	0.9940(0.0061)
Vision-only	0.2319(0.0745)	0.1753(0.0443)	0.2300(0.0427)	0.2289(0.0608)	0.8987(0.0069)

the generative module $\mathcal{G}_{v \to t}$ produces structured EHR-like captions describing lesion characteristics (e.g., "pigmented lesion with irregular border"). These generated narratives are fused with the visual embeddings via the ConvNeXt-v2 + MLP multimodal classifier described in Section 3. We follow a 70/15/15 train/validation/test split and report results averaged over five random seeds.

4.1.2 Environmental Classification (EMPO500)

The EMPO500 dataset (Shaffer et al., 2022) originates from the Earth Microbiome Project Multi-omics collection (Study ID: 13114). It contains 2,002 microbiome samples annotated with environmental metadata fields such as *env_biome*, *env_material*, and *sample_type*. Each sample is labeled by its *env_feature* category (e.g., *marine benthic feature*, *forest soil*, *saline marsh*), totaling 49 distinct ecological contexts. Due to the small and imbalanced nature of the dataset (3–323 samples per class), we condition a diffusion-based text-to-image generator $\mathcal{G}_{t \to v}$ on tabular metadata to produce pseudo-visual textures representing ecological cues. These generated images expand the training distribution for multimodal fusion, improving robustness under few-shot settings. Dataset splits follow 1355/315/332 samples for training, validation, and testing, respectively.

4.2 Implementation Details

Experimental setup and evaluation metrics. All experiments were implemented in PyTorch and executed on a single NVIDIA A100 GPU (80GB VRAM). We fixed all random seeds for reproducibility across NumPy, PyTorch, and CUDA. For multimodal classification, the visual encoder Φ_v was a ConvNeXt-v2 (Woo et al., 2023) pretrained on ImageNet-1K, and the metadata encoder Φ_t was a two-layer MLP (512–256 units, ReLU activation, dropout 0.2). Fusion was performed by concatenating visual and textual/tabular embeddings, followed by a linear projection and softmax classifier. We report Accuracy, AUC, macro-F1, Precision, and Recall as main metrics, each averaged over 5 runs with mean $\pm$ standard deviation.

Training schedule. All fusion and unimodal models were trained for 50 epochs using the Lion optimizer (Chen et al., 2024) with a learning rate of 1×10^{-4}, weight decay 1×10^{-2}, and batch size 32. A cosine annealing warm-restart scheduler was applied every 10 epochs, and early stopping was triggered based on validation macro-F1. Cross-entropy loss was used for all tasks, and class imbalance was mitigated via inverse-frequency weighted sampling. Mixed precision and deterministic data loading ensured reproducibility.

Benchmarking and ablation studies. For the HAM10000 (image-to-text) task, EHR-like textual reports were generated from dermatoscopic images and used as auxiliary metadata inputs. We compared Image-only, Metadata-only, and Fusion models with and without these generated reports.

For the EMPO500 (text-to-image) task, synthetic pseudo-environmental images were produced from metadata via diffusion-based generation and combined with tabular features in a fusion MLP. We compared

classical baselines (Logistic Regression, Random Forest, SVM, XGBoost) against our Fusion and Ensemble variants (Table 5).

5 Results

5.1 Quantitative Results on HAM10000

Table 3 compares our multimodal (Fusion) approach with classical CNN backbones and the pretrained AL-BEF model on the HAM10000 skin lesion benchmark. Our Fusion model with EHR-like report generation achieves the highest overall performance with an accuracy of 0.959 and a macro-F1 of 0.910, outperforming both ALBEF Multimodal (0.903) and all vision-only baselines. This demonstrates that integrating textual metadata in an EHR-like generative manner enhances interpretability while improving classification reliability. The improvement over the Image-only variant (0.785 macro-F1) highlights the effectiveness of cross-modal representation learning in capturing diagnostic cues that are not visually evident.

5.2 Ablation Study: Effect of Multimodal Fusion

To further assess robustness and stability, we repeated all experiments five times and report mean and standard deviation in Table 4. Across multiple runs, the Fusion model consistently achieves high performance (0.9570 ± 0.0034 accuracy), demonstrating stable convergence and superior generalization compared to the unimodal baselines. While the Meta-only model shows relatively high AUC (0.9207), its classification accuracy remains low (0.1747), indicating that metadata alone are insufficient without image grounding. These results collectively validate that multimodal integration offers complementary gains beyond what either modality can provide independently.

Table 6: Comparison between closed-weight and open-weight generators on HAM10000 and EMPO500 datasets.

Generator Pair	Dataset	Accuracy	Macro F1	Δ vs Closed
GPT-4o-mini / Gemini-Image	HAM10000	0.959	0.910	–
Qwen-VL / Qwen-Image	HAM10000	0.954	0.906	0.005 / 0.004
GPT-4o-mini / Gemini-Image	EMPO500	0.943	0.825	–
Qwen-VL / Qwen-Image	EMPO500	0.934	0.799	0.019 / 0.026

5.3 Results on EMPO500 Environmental Classification

Table 5 presents the results on the EMPO500 benchmark, which involves multimodal classification across 49 environmental features combining visual and tabular signals. Our Fusion and Ensemble models outperform all classical baselines (Random Forest (Breiman, 2001), XGBoost (Chen & Guestrin, 2016), SVM (Hearst et al., 1998), Logistic Regression (Hastie et al., 2009)), achieving up to 0.9386 accuracy and 0.8090 macro-F1. The strong performance of Fusion (Vision+Tabular) over Tab-only and Vision-only setups confirms that the cross-modal learning framework effectively captures environmental context and morphological diversity. In particular, the Ensemble model (Fusion+MLP) achieves the best overall results, highlighting the benefit of combining learned multimodal representations with lightweight meta-classifiers. These findings align with our observations on HAM10000, emphasizing that cross-modal integration between visual and structured information is beneficial across biomedical and ecological domains. It is notable that the Fusion and Ensemble modestly improve over MLP tabl-only – this is most likely due to the unique nature of the EMPO500 data which are environmental parameters taken from fresh water systems, an environment where usually little visual information is taken, and therefore, image augmentation has little effect. Thus, it is even more promising that the fusion/ensemble models improve results modestly, showing that even the little information, that exists in pretrained image generators, is helpful.

We additionally compared our approach with several recent large language and vision-language models used as direct classifiers via prompting or zero-shot inference. As reported in Appendix H, these approaches perform substantially worse than the proposed supervised multimodal fusion model, particularly on the highly imbalanced EMPO dataset. These results highlight the importance of task specific supervised multimodal fusion.

5.4 Complementary Ensemble Evaluation

Although the ensemble approach is not part of our core framework, we include it as a complementary evaluation to assess performance stability in multimodal classification. By averaging the predictions from the Fusion classifier and a standalone MLP, we observed consistent yet modest improvements across all metrics (Table 5). This simple ensemble reached 0.9386 accuracy and 0.8090 macro-F1 on EMPO500, suggesting that ensembling can further stabilize multimodal prediction, particularly under limited-sample conditions.

5.5 Model-Agnostic Verification

To validate the model-agnostic nature of our cross-modal generative augmentation framework, we replaced the closed-weight generators used in the main experiments (GPT-4o-mini (Hurst et al., 2024) for image-to-text and Gemini 2.5 Image (Comanici et al., 2025) for text-to-image) with open-weight counterparts, Qwen-VL (Bai et al., 2023; Wang et al., 2024; Team, 2025), and Qwen-Image (Wu et al., 2025). Both replacements were applied without modifying the fusion or classifier modules. As shown in Table 6, the open-weight configuration achieved comparable results on both datasets, with only marginal performance differences (Δ Accuracy $< 0.5\%$ and Δ F1 $< 0.4\%$ in HAM10000 dataset). These results confirm that our framework is not tied to any specific proprietary model and remains reproducible using publicly available generators.

5.6 Generative Output Consistency Evaluation

To assess the reliability of the generated modalities used in our framework, we conduct an automatic consistency evaluation of both EHR-like narratives produced from dermoscopic images (image-to-text) and environmental images synthesized from tabular metadata (text-to-image). Since human evaluation at scale is costly and domain-dependent, we adopt the increasingly common paradigm of LLM-as-a-judge, supported by recent work showing that large language models can serve as stable, high-agreement evaluators across multimodal and NLG tasks (Zheng et al., 2023; Kocmi & Federmann, 2023; Liu et al., 2023). We use GPT-4o as the multimodal evaluator, following protocols similar to G-Eval (Liu et al., 2023). The full evaluation prompts and scoring instructions are provided in Appendix B for reproducibility. In addition, expert validation was conducted to assess the clinical plausibility of generated EHR narratives, with the evaluation protocol and results provided in Appendix I.

EHR Consistency (Image-to-text). We randomly sample 120 generated EHR JSON records from HAM10000, evenly distributed across diagnostic categories. GPT-4o assesses the medical alignment between each generated narrative and its ground-truth diagnosis using a 1–5 scale, where higher scores indicate stronger diagnostic consistency. The generated narratives achieve an average alignment score of 4.40/5, demonstrating that they capture key clinical attributes such as pigmentation patterns, border irregularities, and malignancy-related morphological cues.

Environmental Image Consistency (Text-to-image). For EMPO500, we evaluate 266 generated environmental images across 50 ecological classes. GPT-4o measures visual alignment between each synthesized image and its conditioning metadata (e.g., biome, salinity, sample type, environmental material). The synthetic images obtain an average alignment score of 4.56/5, indicating strong metadata-to-visual grounding despite the inherent difficulty of ecological texture generation.

(a)   **(b)**

Figure 2: **Representative fusion success cases illustrating interpretability.** (a) *HAM10000 (Image→EHR):* The fusion model's correct prediction of *benign keratosis* aligns with generated structured findings (*brownish pigmentation*, *irregular borders*, low-risk assessment), where the textual EHR output itself provides a transparent clinical rationale. (b) *EMPO500 (Metadata→Image):* The fusion model integrates environmental metadata (*temperate desert biome*, *soil sample*) to correctly infer *desert sand*, while unimodal baselines misclassify it as marine or anthropogenic. Generated image visually grounds the reasoning process by reflecting terrestrial texture patterns.

5.7 Qualitative Interpretability Analysis

To further examine the interpretability of our cross-modal generative augmentation framework, we present representative success cases where multimodal fusion enables clinically or scientifically meaningful interpretation beyond unimodal approaches. Figure 2 summarizes two qualitative examples demonstrating how interpretability arises directly through the generated modalities themselves.

In Figure 2(a), the fusion model correctly identifies the lesion as *benign keratosis (bkl)*, whereas the vision-only and metadata-only models fail—one overestimating malignancy (*akiec*) and the other confusing it with a benign *nevus (nv)*. The generated EHR provides explicit morphological evidence, describing *brownish pigmentation*, *irregular borders*, and a *network pattern*, while assigning a low malignancy risk (0.1), consis-

tent with the clinical appearance of seborrheic keratosis. Here, interpretability emerges from the textual generation itself, which exposes a human-readable reasoning trace aligned with clinical knowledge.

In Figure 2(b), the fusion model integrates structured environmental metadata (*temperate desert biome*, *soil sample*) to correctly infer the label *desert sand*, while uni-modal baselines misclassify the same sample as a *marine benthic feature* (image-only) or an *anthropogenic contamination feature* (tabular-only). The generated image captures sandy terrestrial textures distinct from marine patterns, providing a visual rationale for the model's prediction. In this case, interpretability emerges from the visual generation, which grounds environmental context through image formation. These examples suggest that cross-modal generation can enhance interpretability not only through model alignment, but also through the generated modalities themselves—textual in clinical data and visual in environmental data.

6 Conclusion

Across both datasets, the proposed framework demonstrates consistent improvements through cross-modal integration and text-to-image or image-to-text generation. In the clinical domain (HAM10000), the model benefits from incorporating metadata and structured descriptors to enrich lesion understanding. In contrast, in the ecological EMPO500 dataset, generating synthetic visual representations from metadata improves diversity and helps the model generalize across heterogeneous habitats. Together, these experiments indicate that multimodal learning pipelines can bridge domain-specific data gaps by synthesizing complementary modalities, yielding both higher predictive accuracy and improved interpretability. Future work will explore scaling this cross-modal generation paradigm to larger biomedical datasets and investigating its potential for real-world deployment in clinical and environmental monitoring systems.

References

Adewale Adebiyi, Marion Adebiyi, Mariam Fajobi, and Rasheed Abiola. Accurate skin lesion classification using multimodal learning on the ham10000 and isic 2017 datasets. *medRxiv*, May 2024. doi: 10.1101/2024. 05.30.24308213. URL https://www.medrxiv.org/content/10.1101/2024.05.30.24308213v1. Preprint.

Jonathan Amar, Edward Liu, Alessandra Breschi, Liangliang Zhang, Pouya Kheradpour, Sylvia Li, Lisa Soleymani Lehmann, Alessandro Giulianelli, Matt Edwards, Yugang Jia, David Nola, Raghav Mani, Pankaj Vats, Jesse Tetreault, T. J. Chen, and Cory Y. McLean. Integrating genomics into multimodal ehr foundation models. *medRxiv*, October 2025. doi: 10.1101/2025.10.26.684668. URL https://doi.org/10.1101/2025.10.26.684668. Preprint.

Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A versatile vision-language model for understanding, localization, text reading, and beyond. *arXiv preprint arXiv:2308.12966*, 2023.

Leo Breiman. Random forests. *Machine Learning*, 45(1):5–32, October 2001. doi: 10.1023/A:1010933404324. URL https://doi.org/10.1023/A:1010933404324.

Lizhang Chen, Bo Liu, Kaizhao Liang, and Qiang Liu. Lion secretly solves a constrained optimization: As lyapunov predicts. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2024. URL https://openreview.net/forum?id=e4xS9ZarDr. Spotlight.

Tianqi Chen and Carlos Guestrin. Xgboost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 785–794. ACM, 2016. doi: 10.1145/2939672.2939785. URL https://doi.org/10.1145/2939672.2939785.

Xiangning Chen, Chen Liang, Da Huang, Esteban Real, Kaiyuan Wang, Hieu Pham, Xuanyi Dong, Thang Luong, Cho-Jui Hsieh, Yifeng Lu, and Quoc V. Le. Symbolic discovery of optimization algorithms. In *Proceedings of the 37th International Conference on Neural Information Processing Systems (NeurIPS 2023)*, pp. 49205–49233, New Orleans, LA, USA, December 2023. Curran Associates, Inc. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/2140-symbolic-discovery-of-optimization-algorithms.html. NeurIPS '23.

Wei Chow, Juncheng Li, Qifan Yu, Kaihang Pan, Hao Fei, Zhiqi Ge, Shuai Yang, Siliang Tang, Hanwang Zhang, and Qianru Sun. Unified generative and discriminative training for multi-modal large language models. In *Proceedings of the 38th Conference on Neural Information Processing Systems (NeurIPS)*, Vancouver, Canada, 2024. Neural Information Processing Systems Foundation.

Gheorghe Comanici, Eric Bieber, Mike Schaekermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, Luke Marris, Sam Petulla, Colin Gaffney, Asaf Aharoni, Nathan Lintz, Tiago Cardal Pais, Henrik Jacobsson, Idan Szpektor, Nan-Jiang Jiang, Krishna Haridasan, Ahmed Omran, Nikunj Saunshi, Dara Bahri, Gaurav Mishra, Eric Chu, Toby Boyd, Brad Hekman, Aaron Parisi, Chaoyi Zhang, Kornraphop Kawintiranon, Tania Bedrax-Weiss, Oliver Wang, Ya Xu, Ollie Purkiss, Uri Mendlovic, Ilaï Deutel, Nam Nguyen, Adam Langley, Flip Korn, Lucia Rossazza, Alexandre Ramé, Sagar Waghmare, Helen Miller, Nathan Byrd, Ashrith Sheshan, Raia Hadsell, Sangnie Bhardwaj, Pawel Janus, Tero Rissa, Dan Horgan, Alvin Abdagic, Lior Belenki, James Allingham, Anima Singh, Theo Guidroz, Srivatsan Srinivasan, Herman Schmit, Kristen Chiafullo, Andre Elisseeff, Nilpa Jha, Prateek Kolhar, Leonard Berrada, Frank Ding, Xiance Si, Shrestha Basu Mallick, Franz Och, Sofia Erell, Eric Ni, Tejasi Latkar, Sherry Yang, Petar Sirkovic, Ziqiang Feng, Robert Leland, Rachel Hornung, Gang Wu, Charles Blundell, Hamidreza Alvari, Po-Sen Huang, Cathy Yip, Sanja Deur, Li Liu, Gabriela Surita, Pablo Duque, Dima Damen, Johnson Jia, Arthur Guez, Markus Mircea, Animesh Sinha, Alberto Magni, Paweł Stradomski, Tal Marian, Vlado Galić, Wenhu Chen, Hisham Husain, Achintya Singhal, Dominik Grewe, François-Xavier Aubet, Shuang Song, Lorenzo Blanco, Leland Rechis, et al. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*, October 2025. URL https://doi.org/10.48550/arXiv.2507.06261. Version 5, 72 pages, 17 figures.

Yann N. Dauphin, Angela Fan, Michael Auli, and David Grangier. Language modeling with gated convolutional networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML 2017)*, volume 70 of *Proceedings of Machine Learning Research*, pp. 933–941. PMLR, 2017.

Yifan Du, Zikang Liu, Junyi Li, and Wayne Xin Zhao. A survey of vision-language pre-trained models. In *Proceedings of the Thirty-First International Joint Conference on Artificial Intelligence (IJCAI-22), Survey Track*. International Joint Conferences on Artificial Intelligence Organization, 2022.

Trevor Hastie, Robert Tibshirani, and Jerome Friedman. *The Elements of Statistical Learning: Data Mining, Inference, and Prediction.* Springer Series in Statistics. Springer, New York, NY, USA, 2nd edition, 2009. ISBN 978-0-387-84857-0. doi: 10.1007/978-0-387-84858-7. URL https://doi.org/10.1007/978-0-387-84858-7.

M. A. Hearst, S. T. Dumais, E. Osuna, J. Platt, and B. Schölkopf. Support vector machines. *IEEE Intelligent Systems*, 13(4):18–28, 1998. doi: 10.1109/5254.708428. URL https://doi.org/10.1109/5254.708428.

Aaron Hurst, Adam Lerer, Adam P. Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, Aleksander Mądry, Alex Baker-Whitcomb, Alex Beutel, Alex Borzunov, Alex Carney, Alex Chow, Alex Kirillov, Alex Nichol, Alex Paino, Alex Renzin, Alex Tachard Passos, Alexander Kirillov, Alexi Christakis, Alexis Conneau, Ali Kamali, Allan Jabri, Allison Moyer, Allison Tam, Amadou Crookes, Amin Tootoochian, Ananya Kumar, Andrea Vallone, Andrej Karpathy, Andrew Braunstein, Andrew Cann, Andrew Codispoti, Andrew Galu, Andrew Kondrich, Andrew Tulloch, Andrey Mishchenko, Angela Baek, Angela Jiang, Antoine Pelisse, Antonia Woodford, Anuj Gosalia, Arka Dhar, Ashley Pantuliano, Avi Nayak, Avital Oliver, Barret Zoph, Behrooz Ghorbani, Ben Leimberger, Ben Rossen, Ben Sokolowsky, Ben Wang, Benjamin Zweig, Beth Hoover, Blake Samic, Bob McGrew, Bobby Spero, Bogo Giertler, Bowen Cheng, Brad Lightcap, Brandon Walkin, Brendan Quinn, Brian Guarraci, Brian Hsu, Bright Kellogg, Brydon Eastman, Camillo Lugaresi, Carroll Wainwright, Cary Bassin, Cary Hudson, Casey Chu, Chad Nelson, Chak Li, Chan Jun Shern, Channing Conger, Charlotte Barette, Chelsea Voss, Chen Ding, Cheng Lu, Chong Zhang, Chris Beaumont, Chris Hallacy, Chris Koch, Christian Gibson, Christina Kim, Christine Choi, Christine McLeavey, Christopher Hesse, Claudia Fischer, Clemens Winter, Coley Czarnecki, Colin Jarvis, Colin Wei, Constantin Koumouzelis, Dane Sherburn, et al. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, October 2024. URL https://doi.org/10.48550/arXiv.2410.21276. Submitted on 25 Oct 2024. 318 additional authors not shown.

Tom Kocmi and Christian Federmann. Large language models are state-of-the-art evaluators of translation quality. In Mary Nurminen, Judith Brenner, Maarit Koponen, Sirkku Latomaa, Mikhail Mikhailov, Frederike Schierl, Tharindu Ranasinghe, Eva Vanmassenhove, Sergi Alvarez Vidal, Nora Aranberri, Mara Nunziatini, Carla Parra Escartín, Mikel Forcada, Maja Popovic, Carolina Scarton, and Helena Moniz (eds.), *Proceedings of the 24th Annual Conference of the European Association for Machine Translation*, pp. 193–203, Tampere, Finland, June 2023. European Association for Machine Translation. URL `https://aclanthology.org/2023.eamt-1.19/`.

Jing Yu Koh, Daniel Fried, and Ruslan Salakhutdinov. Generating images with multimodal language models. In *Proceedings of the 37th Conference on Neural Information Processing Systems (NeurIPS)*. Neural Information Processing Systems Foundation, 2023.

Zhi Li, Yifan Liu, and Yin Zhang. Back-modality: Leveraging modal transformation for data augmentation. In *Proceedings of the 37th Conference on Neural Information Processing Systems (NeurIPS 2023)*. Neural Information Processing Systems Foundation, 2023.

Youwei Liang, Junfeng He, Gang Li, Peizhao Li, Arseniy Klimovskiy, Nicholas Carolan, Jiao Sun, Jordi Pont-Tuset, Sarah Young, Feng Yang, Junjie Ke, Krishnamurthy Dvijotham, Katherine M. Collins, Yiwen Luo, Yang Li, Kai J. Kohlhoff, Deepak Ramachandran, and Vidhya Navalpakkam. Rich human feedback for text-to-image generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 19401–19411, Seattle, WA, USA, 2024. doi: 10.1109/CVPR52733.2024.01835.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. G-eval: NLG evaluation using gpt-4 with better human alignment. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 2511–2522, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.153. URL `https://aclanthology.org/2023.emnlp-main.153/`.

Wongyung Nam and Beakcheol Jang. A survey on multimodal bidirectional machine learning translation of image and natural language processing. *Expert Systems with Applications*, 235:121168, January 2024. doi: 10.1016/j.eswa.2023.121168.

Tal Ridnik, Emanuel Ben-Baruch, Asaf Noy, and Lihi Zelnik-Manor. Imagenet-21k pretraining for the masses. In *Proceedings of the 35th Conference on Neural Information Processing Systems (NeurIPS 2021), Track on Datasets and Benchmarks*. Neural Information Processing Systems Foundation, 2021.

Srikumar Sastry, Subash Khanal, Aayush Dhakal, Adeel Ahmad, and Nathan Jacobs. Taxabind: A unified embedding space for ecological applications. In *Proceedings of the 2025 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, pp. 1765–1774, Tucson, AZ, USA, Feb 2025. IEEE. doi: 10.1109/WACV61041.2025.00179.

Justin P. Shaffer, Embriette R. Hyde, Pedro Belda-Ferre, Clarisse Marotz, Daniel McDonald, Antonio Gonzalez, and Rob Knight. Standardized multi-omics of earth's microbiomes reveals microbial and metabolite diversity. *Nature Microbiology*, 7(12):1961–1979, 2022. ISSN 2058-5276. doi: 10.1038/s41564-022-01266-x. URL `https://doi.org/10.1038/s41564-022-01266-x`. Earth Microbiome Project (EMP500); Study ID 13114; EBI accession ERP125879.

Jing Shi, Wei Xiong, Zhe Lin, and Hyun Joon Jung. Instantbooth: Personalized text-to-image generation without test-time finetuning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 8543–8552, Seattle, WA, USA, 2024. doi: 10.1109/CVPR52733.2024.00816.

Efstathia Soufleri and Sophia Ananiadou. Enhancing stress detection on social media through multi-modal fusion of text and synthesized visuals. In *Proceedings of the 24th Workshop on Biomedical Language Processing (BioNLP 2025)*, pp. 34–43, Vienna, Austria, August 2025. Association for Computational Linguistics. URL `https://aclanthology.org/2025.bionlp-1.4`.

Zhaoyi Sun, Mingquan Lin, Qingqing Zhu, Qianqian Xie, Fei Wang, Zhiyong Lu, and Yifan Peng. A scoping review on multimodal deep learning in biomedical images and texts. *Journal of Biomedical Informatics*, 146:104482, August 2023. doi: 10.1016/j.jbi.2023.104482.

Qwen Team. Qwen2.5-vl, January 2025. URL `https://qwenlm.github.io/blog/qwen2.5-vl/`.

Surendrabikram Thapa, Usman Naseem, Luping Zhou, and Jinman Kim. Vision-language models for biomedical applications. In *Proceedings of the First International Workshop on Vision-Language Models for Biomedical Applications (VLM4Bio'24)*, pp. 1–2. Association for Computing Machinery, October 2024. doi: 10.1145/3689096.3690770.

Yao-Hung Hubert Tsai, Shaojie Bai, Paul Pu Liang, J. Zico Kolter, Louis-Philippe Morency, and Ruslan Salakhutdinov. Multimodal transformer for unaligned multimodal language sequences. In Anna Korhonen, David Traum, and Lluís Màrquez (eds.), *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 6558–6569, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1656. URL `https://aclanthology.org/P19-1656/`.

Philipp Tschandl, Cliff Rosendahl, and Harald Kittler. The ham10000 dataset, a large collection of multi-source dermatoscopic images of common pigmented skin lesions. *Scientific data*, 5(1):1–9, 2018.

Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Yang Fan, Kai Dang, Mengfei Du, Xuancheng Ren, Rui Men, Dayiheng Liu, Chang Zhou, Jingren Zhou, and Junyang Lin. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. *arXiv preprint arXiv:2409.12191*, 2024.

Sanghyun Woo, Shoubhik Debnath, Ronghang Hu, Xinlei Chen, Zhuang Liu, In So Kweon, and Saining Xie. Convnext v2: Co-designing and scaling convnets with masked autoencoders. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 16133–16142. IEEE, 2023. URL `https://github.com/facebookresearch/ConvNeXt-V2`.

Chenfei Wu, Jiahao Li, Jingren Zhou, Junyang Lin, Kaiyuan Gao, Kun Yan, Sheng ming Yin, Shuai Bai, Xiao Xu, Yilei Chen, Yuxiang Chen, Zecheng Tang, Zekai Zhang, Zhengyi Wang, An Yang, Bowen Yu, Chen Cheng, Dayiheng Liu, Deqing Li, Hang Zhang, Hao Meng, Hu Wei, Jingyuan Ni, Kai Chen, Kuan Cao, Liang Peng, Lin Qu, Minggang Wu, Peng Wang, Shuting Yu, Tingkun Wen, Wensen Feng, Xiaoxiao Xu, Yi Wang, Yichang Zhang, Yongqiang Zhu, Yujia Wu, Yuxuan Cai, and Zenan Liu. Qwen-image technical report, 2025. URL `https://arxiv.org/abs/2508.02324`.

Xun Wu, Shaohan Huang, Guolong Wang, Jing Xiong, and Furu Wei. Multimodal large language models make text-to-image generative models align better. In *Advances in Neural Information Processing Systems 37 (NeurIPS 2024)*. Neural Information Processing Systems Foundation, 2024.

Changrong Xiao, Sean Xin Xu, and Kunpeng Zhang. Multimodal data augmentation for image captioning using diffusion models. In *Proceedings of the 1st Workshop on Large Generative Models Meet Multimodal Applications (LGM3A '23)*, pp. 23–33. Association for Computing Machinery, 2023. doi: 10.1145/3607827.3616839.

Jingyi Zhang, Jiaxing Huang, Sheng Jin, and Shijian Lu. Vision-language models for vision tasks: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 46(8):5625–5644, August 2024. doi: 10.1109/TPAMI.2024.3369699. Published online 26 February 2024.

Sheng Zhang, Yanbo Xu, Naoto Usuyama, Hanwen Xu, Jaspreet Bagga, Robert Tinn, Sam Preston, Rajesh Rao, Mu Wei, Naveen Valluri, Cliff Wong, Andrea Tupini, Yu Wang, Matt Mazzola, Swadheen Shukla, Lars Liden, Jianfeng Gao, Angela Crabtree, Brian Piening, Carlo Bifulco, Matthew P. Lungren, Tristan Naumann, Sheng Wang, and Hoifung Poon. Biomedclip: A multimodal biomedical foundation model pretrained from fifteen million scientific image-text pairs. *NEJM AI*, 2(1), January 2025. doi: 10.1056/AIoa2400640.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-Bench and Chatbot Arena. In *Proceedings of the 37th Conference on Neural Information Processing Systems (NeurIPS 2023), Track on Datasets and Benchmarks*, 2023.

A Datasets

We use publicly available and lightweight datasets to ensure reproducibility and accessibility.

A.1 HAM10000 Dataset

A dataset of 10,015 dermatoscopic images across seven diagnostic categories, with class imbalance reflecting real-world prevalence. The distribution of samples across train, validation, and test splits is summarized in Table 7.

A.2 EMPO500 Dataset

A collection of microbiome environmental metadata samples, labeled with ecological context (e.g., host-associated, saline water, soil). We used Earth Microbiome Project Multi-omics (EMP500) dataset (Study ID: 13114) (Shaffer et al., 2022). Table 8 provides a detailed breakdown of sample counts across environmental features and dataset splits.

Class	Train	Val	Test	Total
akiec	235	41	51	327
bcc	355	82	77	514
bkl	734	180	185	1099
df	75	17	23	115
mel	775	193	145	1113
nv	4728	958	1019	6705
vasc	85	41	16	142
Total	6987	1512	1516	10015

Table 7: HAM10000 Dataset statistics: number of samples per class across Train/Validation/Test splits.

B Prompts

B.1 EHR Generation Prompt

We provide below the exact system and user prompts (Fig. 3) used to generate structured EHR-like JSON records from dermoscopic images using VLMs such as Qwen2.5-VL and gpt-4o-mini.

B.2 Environmental Image Generation Prompt

The following prompt (Fig. 4) was used to synthesize photo-realistic environmental scenes conditioned on EMPO3 and associated metadata with Qwen-Image and Gemini 2.5 Flash Image.

B.3 EHR–Diagnosis Alignment Evaluation Prompt

To assess how well each generated EHR record reflects the true dermatological diagnosis, we use the following GPT-4o evaluation prompt (Fig. 5). The model is instructed to judge only medical alignment, ignoring style, schema quality, or formatting.

EHR Generation Prompt (Qwen2.5-VL)

System Prompt
You are a clinical documentation assistant for dermatology research. Extract structured EHR-like JSON data from the dermoscopic image and metadata. Output **only valid JSON** strictly following the schema below. Avoid repeating the same phrases or findings; each field should be concise and unique. If uncertain, use "unknown".

JSON Schema

```
{
  "patient": {
    "age_years": "integer",
    "sex": ["male", "female", "unknown"]
  },
  "encounter": {
    "encounter_type": "string",
    "site": "string"
  },
  "lesion_observation": {
    "anatomical_site": "string",
    "visual_findings": ["string"],
    "size_mm": "number",
    "image_quality_note": "string"
  },
  "assessment": {
    "provisional_diagnosis_label": "string",
    "malignancy_risk": "number",
    "rationale": ["string"]
  }
}
```

User Prompt Template

```
Metadata:
- age: <AGE>
- sex: <SEX>
- localization: <LOCALIZATION>
- dataset_label_dx (for reference only): <DX>

Please extract structured JSON based on the image and metadata.
```

Figure 3: Prompt used for generating structured EHR-like records with Qwen2.5-VL.

B.4 EMPO500 Visual Alignment Evaluation Prompt

To automatically assess the logical consistency between a generated image and its conditioning metadata, we use the following multimodal evaluation prompt (Fig. 6) with GPT-4o.

C Metadata Encoding and Training Details

C.1 Metadata Encoding

Each EHR-like record is converted into a fixed-length metadata vector composed of (1) numerical variables, (2) one-hot categorical variables, and (3) multi-hot visual-finding features. Numerical fields include patient

---

Environmental Image Generation Prompt

Prompt Template

```
A highly detailed, photo-realistic scene of a natural environment
representing the biome '<env_biome>', showing the material '<env_material>'
and sample type '<sample_type>' in its natural context. The setting reflects
the scientific sample '<scientific_name>' categorized under EMPO3 '<empo_3>'.

Focus on environmental textures, terrain, and lighting -
no human-made objects, no laboratory tools, and no text or labels visible.
```

Figure 4: Full prompt used for environment image generation.

EHR–Diagnosis Alignment Evaluation Prompt

```
You are a clinical evaluation assistant.
Evaluate how well the generated EHR JSON aligns with the TRUE dermatology
diagnosis label.

Your job is to judge ONLY the medical alignment of the EHR with the true
diagnosis. Do NOT evaluate image quality, language quality, schema correctness,
or style.

Rate alignment on a 1-5 scale:
1 = EHR is medically inconsistent or contradicts the true diagnosis
2 = Mostly inconsistent
3 = Partially aligned (some correct signals but overall weak match)
4 = Mostly aligned (diagnosis and clinical description largely consistent)
5 = Strongly aligned (EHR strongly supports or accurately reflects the
    true diagnosis)

Return ONLY a JSON:
{"score": <1-5 integer>, "reason": "<short explanation>"}
```

Figure 5: Prompt used for evaluating medical alignment between generated EHRs and true dermatology diagnoses.

age, lesion size (mm), and the malignancy risk score. Age and lesion size are standardized using the training-set mean and standard deviation, while the malignancy risk score is used as a raw scalar feature. Categorical attributes—patient sex, encounter type, encounter site, and anatomical site—are encoded using one-hot vectors, with an explicit `unknown` slot for unseen values. The "orders" field (e.g., biopsy, urgent referral, reassurance) is mapped to a fixed 5-dimensional one-hot vector. Visual findings are tokenized using simple lowercase string matching, and the 64 most frequent tokens in the training split are used to form a multi-hot representation. All components are concatenated to form the final metadata vector used by the tabular encoder.

C.2   Training Procedure

All HAM10000/EHR experiments are trained in two stages on a single NVIDIA A100 GPU with deterministic seeds. In **Stage 1**, we jointly fine-tune the visual backbone, metadata encoder, and fusion head for 40 epochs using AdamW (learning rates 3×10^{-5} for backbone parameters and 3×10^{-4} for fusion/meta parameters). A 4-epoch warmup is followed by cosine learning-rate decay. Class-balanced focal loss ($\gamma = 1.5$) is used, with effective class weights computed from the empirical label distribution, and mixup/CutMix augmentation is applied during the first 10 epochs. Exponential moving average (EMA) is maintained with decay 0.9999.

Visual Alignment Evaluation Prompt

```
You are an expert evaluator for AI-generated images. You will be given a text
prompt (metadata) and an image that was generated based on that text.

Your task is to evaluate the logical consistency and alignment between the text
and the image. Does the image visually represent the key information described
in the text?

Text Metadata:
{dialogue}

---
Instructions:
Rate the alignment on a scale from 1 to 5.
1: Poor. The image completely ignores or contradicts the text metadata.
3: Moderate. The image reflects some elements of the metadata but misses key
   aspects or includes incorrect elements.
5: Excellent. The image is a perfect and logical visual representation of all
   key elements in the text metadata.

Provide your score as a single number (e.g., 4.5)

Score:
```

Figure 6: Prompt used for assessing image–metadata logical consistency using GPT-4o.

In **Stage 2**, the backbone is kept frozen and only the metadata encoder and classifier head are optimized for 7 additional epochs using Balanced Softmax cross-entropy with AdamW (learning rate 2×10^{-4}). This stage primarily refines behavior under label imbalance by reweighting logits according to class frequencies.

C.3 Calibration and Inference

For the HAM10000/EHR pipeline, after training we apply post-hoc calibration on the validation set. Temperature scaling is tuned by sweeping τ over $\{0.0, 0.25, \ldots, 2.0\}$ and selecting the value that yields the highest macro-F1. A per-class bias vector is then optimized via coordinate descent using candidate adjustments in $\{-1.5, -1.0, -0.5, 0, 0.5, 1.0, 1.5\}$. The final model uses EMA weights together with the optimized temperature and bias adjustments during inference. No test-time augmentation is applied to HAM10000 unless otherwise specified.

D Qualitative Failure Cases

To complement the success cases in Section 2, we present two representative failure cases where cross-modal generative augmentation produces plausible outputs that are nevertheless inconsistent with the ground-truth labels.

In Figure 7(a), the ground-truth diagnosis is *benign keratosis (bkl)*, but the fusion, image-only, and metadata-only classifiers all predict *nevus (nv)*. The generated EHR describes a 50-year-old male with a "brownish lesion" with "irregular borders" on the upper extremity, assigns a low malignancy risk score (0.1), and lists seborrheic keratosis as the top structured diagnosis candidate. Thus, the text-only reasoning trace appears clinically coherent and label-consistent, yet the final predicted class is wrong. This mismatch illustrates that fluent, structured EHR generation does not guarantee that the underlying decision boundary is correct, and highlights the need for calibrated outputs and expert oversight.

Figure 7: **Representative failure cases illustrating the limits of cross-modal generative augmentation.** (a) *HAM10000 (Image→EHR):* all three classifiers (fusion, image-only, metadata-only) predict an incorrect label, even though the generated EHR narrative is clinically consistent with benign keratosis. (b) *EMPO500 (Metadata→Image):* the fusion and tab-only models predict an environmentally inconsistent label (*cliff*) and the image-only model predicts a *marine benthic feature*, despite metadata describing a bog-like forest environment.

In Figure 7(b), the EMPO500 metadata describe a *subpolar coniferous forest biome* with a lichen soil sample and an *env_feature* of *bog*, but the fusion and tab-only models both predict *cliff*, while the image-only model misclassifies the scene as a *marine benthic feature*. The generated image resembles a mossy forest floor with shallow water and tree trunks, which is broadly compatible with a bog-like environment but contains ambiguous textures that the visual backbone appears to over-associate with marine substrates. This case shows that visual interpretability via generation can still be driven by biased priors rather than faithfully reflecting the underlying environmental conditions.

These failure cases emphasize that cross-modal generative augmentation should be viewed as a tool for revealing model behavior rather than as a guarantee of correctness. The generated text and images can may produce convincing but incorrect outputs because they are fluent and visually realistic.

E Additional Ablation: Round-trip Cross-Modal Generation

Our main experiments focus on "one-pass" cross-modal generation, where we either (i) generate EHR-like text from real images and fuse it with the original image (HAM10000), or (ii) generate images from structured metadata and fuse them with tabular features (EMPO500). A natural question is whether chaining generators in a "round-trip" fashion—image→text→image or text→image→text—can further improve robustness or calibration, or whether such chaining instead amplifies errors across modalities.

HAM10000: image→text→image. For HAM10000, we start from real dermoscopic images, generate structured EHR-like records (image→text), and then synthesize new dermoscopy-style images conditioned on these EHRs (text→image). We augment the training set with the EHR-conditioned synthetic images and retrain the same fusion + meta-MLP ensemble as in the main experiment. On the test set, the round-trip model achieves accuracy 0.946, macro-F1 0.885, and AUROC 0.984. While these numbers remain strong, they are slightly *worse* than our best one-pass image→text fusion baseline (Table 4). Qualitatively, many EHR-conditioned synthetic images lack fine-grained dermoscopic structure and realistic color/texture variation, behaving more like noisy views than clinically faithful lesions; as a result, they do not provide additional signal beyond the original images and sometimes inject label noise.

EMPO500: text→image→text. For EMPO500, we symmetrically explore a text→image→text loop. We first generate synthetic habitat images from ground-truth EMPO-style metadata, then apply an LLM-based captioner to recover metadata-like descriptions from these images. We then train (i) an image+metadata fusion model and (ii) a tab-only MLP using a concatenation of ground-truth and LLM-derived metadata features, along with their ensemble. The best fusion model reaches accuracy 0.925, macro-F1 0.757, macro-precision 0.737, macro-recall 0.806, and UROC 0.996; the tab-only MLP and the fusion+MLP ensemble reach accuracy 0.931 with macro-F1 $\approx$ 0.79–0.78 and AUROC 0.997. These round-trip scores are noticeably lower than our one-pass text→image fusion benchmark (Table 5), especially on rare habitat classes.

Qualitatively, EMPO500 exposes an important limitation of round-trip generation: the label and feature spaces are extremely fine-grained and ontology-sensitive. Image-conditioned metadata often uses plausible but non-canonical habitat names, merges or splits categories, or drifts away from the EMPO ontology (Shaffer et al., 2022). This semantic drift breaks the alignment between generated metadata and the target label space, so that adding LLM-derived EMPO features behaves more like structured label noise than useful augmentation.

These ablations suggest that fully round-trip cross-modal generation (image→text→image or text→image→text) is *not* universally beneficial in our settings. Chaining generators across modalities can introduce compounding errors and ontology drift, particularly in high-cardinality ecological label spaces. For this reason, we treat round-trip variants as exploratory negative results and retain the one-pass bidirectional models as the primary components of our benchmark.

F Class-wise Confusion Matrix Analysis

To further examine whether multimodal fusion improves class discrimination, we compare class-wise confusion matrices for the HAM10000 and EMPO datasets under three settings: image-only, metadata-only (or tab-only), and fusion. Overall, the fusion models show a clearer concentration on the diagonal, indicating better alignment between true and predicted labels and more balanced use of complementary information across modalities.

F.1 HAM10000

Figure 8 compares the confusion matrices on HAM10000. The image-only model captures several visually distinctive classes, but still shows noticeable confusion among clinically similar categories. The metadata-only model provides useful signals for some classes, yet its predictions are less consistently aligned with the ground-truth labels. In contrast, the fusion model yields a cleaner class-wise separation overall, suggesting

(a) Image-only   (b) Metadata-only   (c) Fusion

Figure 8: Class-wise confusion matrices on HAM10000 under image-only, metadata-only, and fusion settings. The fusion model shows improved concentration around the diagonal, indicating stronger class discrimination.

(a) Image-only   (b) Tab-only   (c) Fusion

Figure 9: Class-wise confusion matrices on EMPO under image-only, tab-only, and fusion settings. Fusion produces a more consistent diagonal structure than the unimodal baselines, indicating complementary gains from multimodal integration.

that combining image features with EHR-style metadata improves robustness and reduces ambiguity across lesion categories.

F.2 EMPO

Figure 9 shows the same comparison on EMPO, which is more challenging due to its broader label space and visually less distinctive categories. The image-only model collapses many samples into a limited subset of predictions, indicating weak separability from visual information alone. The tab-only model performs substantially better and already forms a strong diagonal structure, reflecting the importance of structured metadata for this task. The fusion model further sharpens this pattern and reduces several off-diagonal errors, showing that image cues still provide additional value when combined with tabular context.

These qualitative results support the quantitative findings: fusion does not simply average two modalities, but improves class-wise decision boundaries by leveraging complementary information from both image and structured metadata.

G Comparison with a Simple Concatenation Baseline

To further evaluate the effectiveness of the proposed fusion design, we compare it against a simple concatenation baseline in which image and metadata representations are directly concatenated before classification.

This comparison is intended to isolate whether the gains come merely from combining modalities, or from the proposed fusion mechanism itself. We report the final test-set results on both HAM10000 and EMPO.

As shown in Table 9, the proposed method consistently improves accuracy and macro-F1 over the simple concatenation baseline on both datasets, indicating that its benefits are not solely due to multimodal input combination. On HAM10000, the proposed method also achieves higher AUROC, suggesting better overall ranking quality in addition to stronger class-balanced classification. On EMPO, the proposed method substantially improves accuracy, macro-F1, macro-precision, and macro-recall, although the concatenation baseline attains a higher AUROC. This suggests that the proposed fusion is particularly beneficial for final class discrimination and balanced prediction performance, even when AUROC is not uniformly improved.

H   Comparison with LLM/VLM Baselines

To further contextualize the performance of the proposed multimodal fusion model, we compare it with several recent large language and vision-language models used as direct classifiers. Specifically, we evaluate Qwen2.5-VL, GPT-4o(-mini), BiomedCLIP, and BioMistral under direct prompting or zero-shot inference settings.

These models are used without task-specific training and therefore represent strong general-purpose baselines. For completeness, we also report the performance of our supervised multimodal fusion model on the same test sets.

Table 10 summarizes the results. Overall, direct prompting or zero-shot VLM approaches perform substantially worse than the proposed supervised fusion method. The gap is particularly pronounced for the EMPO dataset, which involves a large number of highly imbalanced classes. These results highlight the importance of task-specific multimodal fusion and supervised training for structured biomedical and environmental classification tasks.

I   Clinical Plausibility Validation of Generated EHR

While the main evaluation focuses on internal consistency and modality alignment, we additionally conducted a small-scale expert validation to assess the clinical plausibility of the generated EHR narratives.

Two licensed physicians (MDs) independently reviewed a total of 70 randomly sampled generated EHR cases drawn across multiple diagnostic categories. For each case, the reviewers assessed two criteria: (1) whether the clinical description (e.g., morphology, clinical history, and physical examination) logically matches the provided diagnosis, and (2) whether the note is internally consistent and free of obvious structural contradictions (e.g., mismatches between demographic attributes and narrative content). Each criterion was evaluated using a binary judgment (Yes/No).

Table 11 summarizes the aggregated results of the expert review. Overall, the large majority of generated EHR narratives were judged to be clinically plausible and internally coherent. Specifically, 67 out of 70 cases (95.7%) were judged to have diagnosis-consistent clinical descriptions, and 64 out of 70 cases (91.4%) were considered logically consistent without structural contradictions.

Although this validation is limited in scale and does not constitute a formal clinical study, the results provide preliminary evidence that the generated EHR narratives are not only linguistically coherent but also medically reasonable.

Environmental Feature (env_feature)	Train	Val	Test	Total
anaerobic bioreactor	15	4	4	23
animal-associated habitat	187	41	41	269
anthropogenic contamination feature	6	2	2	10
banana plantation	1	1	1	3
bioreactor	17	4	4	25
bog	8	2	2	12
cliff	14	3	4	21
coast	6	2	2	10
coastal water body	27	6	6	39
coral reef	42	9	10	61
cropland	6	2	2	10
desert sand	7	2	2	11
forest	18	4	5	27
forest soil	14	3	4	21
glacier	13	3	3	19
grassland soil	9	2	3	14
gravel field	6	2	2	10
host-associated habitat	225	49	49	323
insecta-associated habitat	70	16	16	102
intermittent pond	15	4	4	23
kelp forest	17	4	4	25
lagoon	1	1	2	4
mangrove	1	1	2	4
marine benthic feature	214	46	47	307
marine reef	13	3	3	19
microbial mat	1	1	2	4
mine	34	8	8	50
montane desert	18	4	4	26
mud	9	3	3	15
ocean	30	7	7	44
ocean water	12	3	3	18
oil palm plantation	4	1	1	6
oil reservior	9	2	3	14
planted forest	1	1	3	5
pond bed	43	10	10	63
rangeland	1	1	3	5
research facility	115	25	25	165
saline marsh	16	4	4	24
sand	1	1	2	4
sediment	9	2	3	14
soil	1	1	1	3
steppe soil	8	2	2	12
stratum	12	3	3	18
stromatolite mat	1	1	2	4
temperate coniferous forest	10	3	3	16
tributary	18	5	5	28
volcanic feature	42	9	9	60
wetland	8	2	2	12
Total	**1355**	**315**	**332**	**2002**

Table 8: EMP500 (Earth Microbiome Project Multi-omics, Study 13114) dataset statistics showing the number of samples per environmental feature across Train/Validation/Test splits.

Table 9: Comparison between the proposed fusion method and a simple concatenation baseline on the HAM10000 and EMPO test sets. Bold indicates the better result for each metric within each dataset.

Dataset	Method	Accuracy	Macro-F1	Macro-Precision	Macro-Recall	AUROC
HAM10000	Simple Concat	0.9499	0.8774	0.8993	0.8627	0.9826
	Proposed Method	**0.9580**	**0.9140**	**0.9364**	**0.8956**	**0.9960**
EMPO	Simple Concat	0.8976	0.6885	0.6911	0.7131	**0.9911**
	Proposed Method	**0.9307**	**0.7996**	**0.8006**	**0.8342**	0.9657

Table 10: Comparison with recent LLM/VLM baselines used as direct classifiers. The proposed supervised fusion model consistently outperforms general-purpose prompting-based approaches.

Dataset	Method	Accuracy	Macro-F1
HAM10000	Qwen2.5-VL (direct prompting)	0.1049	0.0294
	GPT-4o-mini (direct prompting)	0.1987	0.2656
	BiomedCLIP (zero-shot)	0.1392	0.1312
	BiomedCLIP Fusion (ours)	**0.4914**	**0.4340**
EMPO	Qwen2.5-VL (direct prompting)	0.2741	0.1851
	GPT-4o (direct prompting)	0.3765	0.2846
	BioMistral (direct prompting)	0.0120	0.0005
	Fusion Model (ours)	**0.9307**	**0.7996**

Table 11: Expert clinical plausibility evaluation of generated EHR narratives (70 cases).

Evaluation Criterion	Yes	No
Diagnosis Consistency	67 / 70 (95.7%)	3 / 70
Internal Logical Consistency	64 / 70 (91.4%)	6 / 70