Goal-Aware Cross-Entropy
for Multi-Target Reinforcement Learning

Abstract

Learning in a multi-target environment without prior knowledge about the targets requires a large amount of samples and makes generalization difficult. To solve this problem, it is important to be able to discriminate targets through semantic understanding. In this paper, we propose goal-aware cross-entropy (GACE) loss, that can be utilized in a self-supervised way using auto-labeled goal states alongside reinforcement learning. Based on the loss, we then devise goal-discriminative attention networks (GDAN) which utilize the goal-relevant information to focus on the given instruction. We evaluate the proposed methods on visual navigation and robot arm manipulation tasks with multi-target environments and show that GDAN outperforms the state-of-the-art methods in terms of task success ratio, sample efficiency, and generalization. Additionally, qualitative analyses demonstrate that our proposed method can help the agent become aware of and focus on the given instruction clearly, promoting goal-directed behavior.

1 Introduction

Reinforcement learning (RL) research has been expanding to various fields including robotics, to solve increasingly complex problems. For instance, RL has been gradually mastering skills such as robot arm/hand manipulation on an object [2, 48, 36, 22] and navigation to a target destination [18, 39]. However, to benefit humans like the R2-D2 robot, RL must extend to realistic settings that require interaction with multiple objects or destinations, which is still challenging for RL.

For this reason, it is important for multi-target tasks to be considered. We use the term *multi-target tasks* to refer to tasks that require the agent to interact with variable goals. In a multi-target task, *targets* are possible goal candidates, which may be objects or key entities that play a decisive role in determining the success or failure of the task execution. The *goals* may be selected among the targets by the current multi-target task, specified with a cue or an instruction such as "Bring me a {*spoon, cup* or *specific object*}" or "Go to the {*kitchen, livingroom* or *specific destination*}". The states in which the agent reaches the goal are called *goal states*.

Reinforcement learning allows learning multi-target or instruction-based tasks in an end-to-end manner. Latest reinforcement learning studies on these tasks mainly focus on prior knowledge about targets [27, 30, 8]. Other studies focus on learning representation on the environment [46] or about the targets only implicitly [44]. These methods lead to insufficient understanding of the goal, and sample-inefficiency and generalization problems arise.

For this matter, we propose a *Goal-Aware Cross-Entropy (GACE)* loss and *Goal-Discriminative Attention Networks (GDAN)* for multi-target tasks in reinforcement learning. These methods, unlike previous studies without prior knowledge, allow semantic understanding of goals including their appearances and other characteristics. The agent automatically labels and collects goal states data

(a) Architecture from Goal-Aware Cross-Entropy and GDAN   (b) Attention in ActorCritic

Figure 1: Overview of our architecture. (a) A goal-aware visual representation learning method by $\mathcal{L}_{GACE}$ from goal-aware cross-entropy loss. The loss updates the feature extractor and the goal-discriminator. (b) In GDAN, the ActorCritic utilizes the information from the goal-discriminator as the query for goal-directed actions. See the details in Section 3.3 and 3.4.

through trial-and-error in a self-supervised manner. Based on these self-collected data, we use GACE loss as an auxiliary loss to train a goal-discriminator that learns goal representations. Lastly, the GDAN extracts the information from the goal-discriminator as goal-relevant query, with which an attention is performed to infer goal-directed actions.

We additionally propose visual navigation and robot arm manipulation tasks as benchmarks for multi-target task experiments. These tasks involve targets which are the multiple types of objects randomly placed within the environments. In the benchmarks, we make these tasks visually complex using randomized background textures, allowing us to evaluate generalization.

In summary, the contributions of this paper are as follows:

- We propose a Goal-Aware Cross-Entropy loss for learning auto-labeled goal states in a self-supervised manner, solving instruction-based multi-target tasks in reinforcement learning.

- We additionally propose Goal-Discriminative attention networks that use the goal-relevant query from the goal-discriminator to focus exclusively on important goal-related information.

- Our method achieves significantly better performances in terms of the success ratio, sample-efficiency and generalization on visual navigation and robot arm manipulation multi-target tasks. In particular, compared with the baseline methods, our method excels in Sample Efficiency Improvement metric by **17 times** in visual navigation task and by **1.8** times in manipulation task.

- We present two instruction-based benchmarks for goal-based multi-target environments, to interact with multiple targets for realistic settings. These benchmarks will be made publicly available, along with the implementation of our proposed method.

2   Related Work

Multi-Target Tasks in Reinforcement Learning   There have been numerous studies that aim to solve multi-target tasks with reinforcement learning. Wu et al. [44] proposes instruction-based indoor environments, as well as attention networks for multi-target learning to respond to the given instruction. Deisenroth and Fox [11] uses model-based policy search method for multiple targets, instead of learning goal-relevant information. The aforementioned methods are for learning dynamics model or learning targets indirectly for multiple target task. In our method, on the other hand, the policy directly learns to distinguish goals without dynamics model.

The terms *targets* and *goals* have been used in diverse manners in the existing literature. There are subgoal generation methods that generate intermediate goals such as imagined goal [31, 14] or random goals [34] to help agents solve the tasks. Multi-goal RL [47, 35, 13, 10] aims to deal with multiple

tasks, learning to reach different goal states for each task. Scene-driven visual navigation tasks [49, 12, 30] specify the goal by an image. However, these tasks require the agent only to search for visually similar location or object, rather than gaining semantic understanding of goals and promoting generalization. Instruction-based tasks [1, 40] focus on learning to follow detailed instructions. These tasks have a different purpose from our tasks, where we focus on having appropriate interactions with multiple targets depending on the instruction.

Representation Learning in Reinforcement Learning   To improve performance in RL, several recent works have used a variety of representation learning methods. Among these methods, many make use of auxiliary tasks taught via unsupervised learning techniques such as VAE [24, 19] for learning dynamics [16, 45, 38] and contrastive learning method [7] for learning representations [26] of a given environment. Nair et al. [32] uses goal states, specified as the last states of the trajectories, to learn the difference between future state and goal state for redistributing model error in model-based reinforcement learning. The aforementioned methods are for learning representations of the environment rather than for learning those of key states for solving the task. In contrast, our method directly learns goal-relevant state representations.

Jaderberg et al. [21] proposes various auxiliary tasks for representation learning in RL. One such method is reward prediction, which learns environment by predicting the reward of the future state from three classes: {positive, 0, negative}. This method focuses on myopic reward prediction, and not on ultimately learning the goal state to solve the task. Consequently, it is not a suitable method to apply to multi-target environments, where the goal can be selected among a diverse range of objects.

Attention Methods in Reinforcement Learning   The attention method was initially introduced for natural language processing [3] but is now being actively studied in various fields such as computer vision [43]. There are also attention-based methods for reinforcement learning which use inputs from different parts of the state [4, 9]. Other methods include the use of encoding information of sequential frames up to the last step [29], as well as the application of self-attention [6]. Unlike these methods, our approach explicitly extracts and focuses solely on goal-related information for solving a task.

3 Method

3.1 Preliminary

Reinforcement learning (RL) from Sutton and Barto [41] aims to maximize cumulative rewards by trial-and-error in a Markov Decision Process (MDP). An MDP is defined by a tuple $(\mathcal{S}, \mathcal{A}, \mathcal{R}, \mathcal{P}, \gamma)$, where $\mathcal{S}$ is the set of states, $\mathcal{A}$ is the set of actions, $\mathcal{R} : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is the reward function, $\mathcal{P} : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ is the transition probability distribution, and $\gamma \in (0,1]$ is the discount factor. At each time step t, the agent observes state $s_t \in \mathcal{S}$, selects an action $a_t \in \mathcal{A}$ according to its policy $\pi : \mathcal{S} \to \mathcal{A}$, and receives a reward r_t and next state s_{t+1}. In finite-horizon MDPs, return $R_t = \Sigma_{k=0}^{T-t} \gamma^k r_{t+k}$ is accumulated discounted rewards, where T is the maximum episode length. State value function $V(s) = \mathbb{E}[R_t | s_t = s]$ is the expected return from state s.

Instruction-Based Multi-Target Reinforcement Learning   Universal value function approximators [37] estimate state value function as $V(s, x)$, for jointly learning the task from embedded state s and goal information x. This is relevant to the notions of multi-target RL that we define as below.

Multi-target environments contain N *targets*, or goal candidates $\mathcal{T} = \{z_1, z_2, ..., z_N\}$. These environments provide an instruction I^z that specifies which target the agent must interact with, or the *goal* $z \in \mathcal{T}$. The instruction is given randomly every episode, in the form such as "Get the *Bonus*" or "Reach the *Green Box*" as in our benchmark tasks, in which cases the goals are *Bonus* and *Green Box* respectively. Hence, the state value function in such task is $V(s, I^z) = \mathbb{E}[R_t | \bar{s}_t = (s, z)]$, where $\bar{s}_t$ is state conditioned on the goal z. The policy π is also conditioned on the instruction I^z as $\pi(a_t | s_t, I^z)$ where a_t is action at time t given state s_t and I^z.

3.2 Auto-Labeled Goal States for Self-Supervised Learning

Prior to describing the main method in Sec. 3.3 and 3.4, this section explains the automatic collection of goal data for self-supervised learning. Suppose that the instruction I^z specifies the target z

as the goal and the episode ends when the goal is reached at time step t'. We refer to the state $s_{t'}$ as a *goal state*, which we assume is highly correlated with the reward or the rewarding state. Throughout training, the reached goal label z and the corresponding goal state $s_{t'}$ are automatically collected as a tuple $(s_{t'}, one\_hot(z))$, called *storage data*. Rather than being manually provided the goal information, the agent actively gathers the data needed to learn the goals, relying only on the instruction I^z given by the environment. This allows the agent to learn in an end-to-end, self-supervised manner. The states for the failed episodes are also stored as a negative case with low probability ϵ_N. We clarify that the storage data does not serve as the prior during the learning and is instead used for training alongside the multi-target reinforcement learning task.

3.3 Goal-Discriminator by Goal-Aware Cross-Entropy

Our proposed method adds an auxiliary task to the main reinforcement learning task as shown in Figure 1a. A general reinforcement learning model consists of a feature extractor $\sigma(\cdot)$, which converts state s_t to an encoding $\mathbf{e}_t$, and an ActorCritic $f(\cdot)$ that outputs a policy π and value V:

$$\mathbf{e}_t = \sigma(s_t) \tag{1}$$
$$\pi(a_t|s_t, I), V(s_t, I) = f(\mathbf{e}_t, I) \tag{2}$$

where I is the instruction. The details of the ActorCritic $f(\cdot)$ and the resulting loss $\mathcal{L}_{RL}$ depend on the specific reinforcement learning algorithm that is chosen. In our visual navigation experiments, we use asynchronous advantage actor-critic (A3C) [28] as the main algorithm, where the loss $\mathcal{L}_{RL}$ is defined as the following

$$\mathcal{L}_p = \nabla \log \pi(a_t|s_t, I)(R_t - V(s_t, I)) + \beta \nabla H(\pi(a_t|s_t, I)) \tag{3}$$
$$\mathcal{L}_v = (R_t - V(s_t, I))^2 \tag{4}$$
$$\mathcal{L}_{RL} := \mathcal{L}_{A3C} = \mathcal{L}_p + 0.5 \cdot \mathcal{L}_v \tag{5}$$

where $\mathcal{L}_p$ and $\mathcal{L}_v$ respectively denote policy and value loss, R_t denotes the sum of decayed rewards from time steps t to T, and H and β denote the entropy term and its coefficient respectively. See Appendix E for algorithm details.

The vanilla base algorithm is not sufficient for gaining direct understanding of goals. Suppose that we have a set of goal states $\mathcal{S}_z \subset \mathcal{S}$ corresponding to each goal z. Intuitively, given an instruction I^z that specifies z, the agent must learn the value function $V(s, I)$ that discriminates the goals, such that $V(s_{goal}^z, I^z) > V(s_{goal}^j, I^z)$ for $s_{goal}^z \in \mathcal{S}_z$ and $s_{goal}^j \in \mathcal{S}_j, \forall z \neq j$.

To achieve this effect, we propose *Goal-Aware Cross-Entropy* (GACE) loss as our contribution, which trains the goal-discriminator that facilitates semantic understanding of goals alongside the policy in Figure 1a. The inference process is as follows. First, the storage data collected in Sec. 3.2 are sampled as a batch of $s_{goal,i}$'s (with i as data index within the batch) and fed into the feature extractor $\sigma(\cdot)$ for state encoding in Eq. 6. Next, the encoded input data $\mathbf{e}_{s_{goal,i}}$ is fed into the goal-discriminator $d(\cdot)$, a multi-layer perceptron (MLP), in Eq. 7. This yields a prediction $\mathbf{g}_{goal,i}$, a vector that contains probability distribution over possible goals that $s_{goal,i}$ belongs to.

$$\mathbf{e}_{s_{goal,i}} = \sigma(s_{goal,i}) \tag{6}$$
$$\mathbf{g}_{goal,i} = d(\mathbf{e}_{s_{goal,i}}) \tag{7}$$

From the output $\mathbf{g}_{goal,i}$, we calculate the Goal-Aware Cross-Entropy loss $\mathcal{L}_{GACE}$ as Eq. 8, where M is the batch size, and z_i is the automatic label corresponding to state $s_{goal,i}$.

$$\mathcal{L}_{GACE} = -\sum_{i=0}^{M-1} one\_hot(z_i) \cdot \log(\mathbf{g}_{goal,i}) \tag{8}$$

We complete the training procedure by optimizing the overall loss $\mathcal{L}_{total}$ as the weighted sum of the two losses in Eq. 9. We focus on improving the policy for performing the main task and assign weight η to $\mathcal{L}_{GACE}$ for performing goal-aware representation learning for the feature extractor $\sigma(\cdot)$. We note that the goal-discriminator $d(\cdot)$ is updated according to $\mathcal{L}_{GACE}$ only during training, not during inference, excluding the ActorCritic.

$$\mathcal{L}_{total} = \mathcal{L}_{RL} + \eta \mathcal{L}_{GACE} \tag{9}$$

(a) Visual Navigation Task in ViZDoom (b) Robot Manipulation Task

Figure 2: Two kinds of multi-target tasks in our experiments. The object positions and background are randomly shuffled in (a) egocentric visual navigation tasks and (b) robot arm manipulation tasks.

The explained procedure forms a visual representation learning method, where the GACE loss makes the goal-discriminator become goal-aware without external supervision. Such goal-awareness is advantageous for sample-efficiency in multi-target environments, as well as generalization, as it makes the agent robust in a noisy environment. Such effects are demonstrated in our quantitative results and qualitative analyses.

3.4 Goal-Discriminative Attention Networks

The goal-discriminator discussed so far can influence the policy inference. However, in order to effectively utilize the discriminator to enhance the performance and efficiency of the agent, we propose Goal-Discriminative Attention Networks (GDAN). Overall, the goal-aware attention described in Figure 1b involves a *goal-relevant query* q_t^z from within the goal-discriminator $d(\cdot)$, and the *key* k_t and *value* v_t from encoded state in the ActorCritic $f(\cdot)$.

During the inference, the state encoding vector $\mathbf{e}_t$ is passed through the first linear layer of the goal-discriminator, which yields the query vector q_t^z that implicitly represents the goal-relevant information. Meanwhile, the vector $\mathbf{e}_t$ is inferenced through a gated-attention [44] with instruction I for grounding. The gated-attention vector is passed through LSTM (Long Short-Term Memory) [20] and splits in half into key k_t and value v_t. Suppose the vectors q_t^z, k_t, and v_t are d_q-, d_k-, and d_v-dimensional, respectively. The query and key are linearly projected to d_v-dimensional space using learnable parameters $\mathbf{W_q}$ of dimensions $d_v \times d_q$ and $\mathbf{W_k}$ of dimensions $d_v \times d_k$, respectively. The activation function ϕ, which is $\tanh$ in our case, is applied to the resulting vectors to yield a goal-aware attention vector u_t^z in Eq. 10. The attention vector u_t^z contains the goal-relevant information in s_t. Lastly, Hadamard product is performed between u_t^z and v_t in Eq. 11, yielding the attention-dependent state representation vector h_t used for calculating the policy and value. The vector h_t is concatenated with gated-attention vector from a state encoding vector $\mathbf{e}_t$ in ActorCritic $f(\cdot)$.

$$u_t^z = \phi(\mathbf{W_q}q_t^z + \mathbf{W_k}k_t) \tag{10}$$
$$h_t = v_t \odot u_t^z \tag{11}$$

We underscore two points about the proposed networks. First, while the goal-discriminative feature extractor $\sigma(\cdot)$ trained by GACE loss may be sufficient, by constructing attention networks, the implicit goal-relevant information from the goal-discriminator directly affects the ActorCritic $f(\cdot)$ that determines the policy and value. Second, the query vectors are from a part of the goal-discriminator, which allows the ActorCritic to actively query the input for goal-relevant information rather than having to filter out large amounts of unnecessary information. These two design choices enable the agent to selectively allocate attention for goal-directed actions (Figure 5c), making full use of the GACE loss method. Details of our architecture are covered in Appendix B.

4 Experiments

Experimental Setup The experiments are conducted to evaluate the success ratio, sample-efficiency, and generalization of our method, as well as compare our work to competitive baseline methods in multi-target environments. We develop and conduct experiments on (1) visual navigation

tasks based on ViZDoom [23, 18], and (2) robot arm manipulation tasks based on MuJoCo [42]. These multi-target tasks involve N targets which are placed at positions $p_1, p_2, \cdots, p_N$, and provide the index of one target as the goal $z \in \{1, 2, \cdots, N\}$. At time step t, the agent receives state s_t normalized to range [0,1]. The agent receives a positive reward $r_{success}$ if it gets sufficiently close to the goal (i.e. $\|x_t - p_z\| \le \epsilon$) where x_t is the agent position at time t. On the other hand, the agent is penalized by $r_{nongoal}$ if it reaches a non-goal object, or $r_{timeout}$ if it times out at $t \ge T$. Lastly, the agent receives time step penalty r_{step}, which is empirically found to accelerate training. Reaching either a goal or non-goal object terminates the episode. All experiments are repeated three times.

Details of Sample Efficiency Metrics   We introduce Sample Requirement Ratio (SRR) and Sample Efficiency Improvement (SEI) metrics to measure the sample efficiency of each algorithm. For the given task, we select a reference algorithm A and its reference success ratio $X\%$. Suppose this algorithm reaches the success ratio $X\%$ within n_A updates. We measure the SRR metric of another algorithm B as $SRR_B = n_B/n_A$, where B reaches $X\%$ within n_B updates. Also, SEI metric of B is measured as $SEI_B = (n_A - n_B)/n_B$. Lower SRR, higher SEI indicate higher sample efficiency.

4.1   Visual Navigation Task with Discrete Action

We conduct experiments on egocentric 3D navigation task based on ViZDoom (Figure 2a). The RGB-D state is provided as an input to the agent, and three different actions (*MoveForward*, *TurnLeft*, *TurnRight*) are allowed. One item from each of the four different classes of objects – each class (e.g. *Bonus*) containing two different items (e.g. *HealthBonus* and *ArmorBonus*) – is placed within the map, with one class randomly selected as the goal by the instruction for each episode like "Get the *Bonus*". Every episode, the agent is initially positioned at the center of the map. The rewards are set as $r_{success} = 10$, $r_{nongoal} = -1$, $r_{timeout} = -0.1$, $r_{step} = -0.01$. Full details of the environment are provided in the Appendix C.

Details of Each Task   To evaluate the performance of our method on tasks of varying difficulties, we set up four configurations. The **V1** setting consists of a closed fixed rectangular room with walls at the map boundaries, and object positions are randomized across the room. **V2** is identical to V1, except that the textures for the background, such as ceiling, walls and floor, are randomly sampled from a pool of textures every episode. 40 textures are used for the *seen* environment, while 10 are used for the *unseen* environment which is not used for training to evaluate generalization. Hence the tasks allow 40^3 and 10^3 different state variations in *seen* and *unseen* environments respectively. **V3** is more complicated, with larger map size, shuffled object positions, and additional walls within the map boundaries to form a maze-like environment. "Shuffled positions" indicates that the object positions are chosen as a random permutation of a predetermined set of positions. Lastly, **V4** is equivalent to V3 with the addition of randomized background textures for the seen and unseen environments. V2 and V4 allow us to evaluate the agent's generalization to visually complex, unseen environment. V1 and V3 can be regarded as the upper bound of performance on V2 and V4 respectively.

Baselines for Comparison   As the base algorithm, we use `A3C`, an on-policy RL algorithm, with the model architecture that uses gated-attention [5, 33] with LSTM. This baseline is proposed in [44][1] for multi-target learning on navigation. Other competitive general RL methods are added onto the base multi-target learning algorithm, due to rarity of appropriate multi-target RL algorithms for comparison. `A3C+VAE` [16, 38] learns VAE features for all time steps, unlike our methods which learn only for goal states. `A3C+RAD` applies augmentation – the random crop method, known to be the most effective in [25] – to input states in order to improve sample efficiency and generalization. `A3C+GACE` and `A3C+GACE&GDAN` are our methods applied to the `A3C` as covered in Sec. 3.3 and 3.4.

Results   Performance is measured as the success ratio of the agent across 500 episodes in all tasks. As shown in Figure 4, most baselines successfully learn the V1 task, albeit at different ratios. In V4, `A3C+VAE` (green) initially shows the steepest curve, probably because it reaches the object located near the initial agent position before the learning commences properly. `A3C+RAD` (blue) shows the steepest learning curve in V1, but fails to learn in visually complex environments such as V2 and V4. In V3, `A3C+GACE` (orange) and `A3C+GACE&GDAN` (red) achieve 52.6% and 78.2% respectively. We attribute such discrepancy to `A3C+GACE&GDAN`'s more direct and efficient usage of goal-related

---

[1]The cited paper also introduces multi-target tasks, but those are unavailable due to license issue.

(a) V1   (b) V2 Seen   (c) V2 Unseen

(d) V3   (e) V4 Seen   (f) V4 Unseen

Figure 3: Visual navigation learning curves. The solid lines show the average success ratio over the repeated experiments, and the shades indicate bounds given as mean ± standard deviation of success ratio. Orange and red lines are our methods, GACE loss and GACE&GDAN, respectively.

information from the goal-discriminator. Especially, `A3C+GACE&GDAN` achieves as high as 86.6% and 54.9% in V2 seen and V4 seen respectively. Furthermore, in V2 unseen and V4 unseen tasks, the agents trained with our methods generalize well to unseen environments. Thus, our methods achieve the state-of-the-art sample-efficiency and performance in all tasks. The full details are covered in the Appendix B.

The SRR and SEI measurements of the models are shown in Table 1. For measuring sample efficiency, we select A3C as the reference algorithm and 56.55% as the reference success ratio. This is the highest performance of A3C within 2M updates. Our methods show the highest sample efficiency compared to the baselines.

4.2 Robot Manipulation Task with Continuous Action

To evaluate our method in the continuous-action domain, we conduct experiments on the UR5 robot arm manipulation tasks with 6 degrees of freedom, based on MuJoCo (Figure 2b). The environment comprises a robot arm and three objects of different colours (red, green, blue). The state is an RGB image provided from the fixed third-person perspective camera view that captures both the robot and the objects in Figure 2b. The rewards are $r_{success} = 1$, $r_{nongoal} = -0.3$, $r_{timeout} = -0.1$, $r_{step} = -0.01$.

Details of Each Task   Our method is evaluated on two different vision-based tasks. In the **R1** task, the object positions are shuffled among three preset positions, and one of the three objects is randomly specified as the goal by the instruction like "Reach the *Green Box*". The robot arm must reach the goal object within the time limit T steps while avoiding other objects. **R2** task complicates the R1 task by randomly sampling the background color from the specified set of 11^3 colors, allowing 11^3 state variations. The agent's performance is measured on the *seen* environment, in which the agent is trained, as well as the *unseen* environment, which uses background colors that are not used in seen environments. The full details of these tasks are outlined in the Appendix B.

Baselines for Comparison   As a baseline method, we use a deterministic variant of Soft Actor-Critic (`Pixel-SAC` [17]), an off-policy algorithm commonly used in robotic control tasks. As a baseline, we evaluate `SAC+AE` [45], which uses β-VAE [19] for encoding and decoding states. Another baseline is `SAC+CURL` which performs data augmentation (cropping) and contrastive learning between the same images. These baseline methods are all competitive methods in the continuous-action

Table 1: Success ratio (SR) and sample efficiency metrics in visual navigation task **V1**.

Algorithm	SR of **V1** (%)	Number of Updates	SRR (%)	SEI (%)
A3C	56.55 ± 13.8	2M	100	-
+VAE	67.89 ± 3.5	810,086	40.50	146.89
+RAD	82.14 ± 2.3	703,574	35.18	184.26
+GACE (ours)	$\mathbf{94.97 \pm 0.7}$	163,602	8.18	1122.48
+GACE & GDAN (ours)	$\mathbf{95.6 \pm 0.64}$	110,930	**5.55**	**1702.94**

Table 2: Success ratio (SR) and sample efficiency metrics in robot arm manipulation tasks.

Algorithm	SR of **R1** (%)	Num of Updates	SRR (%)	SEI (%)	SR of **R2** Seen (%)	SR of **R2** Unseen (%)
SAC	74.0 ± 7.2	316,637	100	-	24.9 ± 10.5	25.1 ± 10.2
+AE	81.1 ± 2.9	199,218	62.92	58.94	56.6 ± 28.1	57.0 ± 31.3
+CURL	86.5 ± 6.9	120,829	38.16	162.05	83.8 ± 10.1	83.0 ± 0.8
+GACE	93.0 ± 0.7	176,042	55.6	79.86	81.3 ± 8.1	74.2 ± 5.7
+GACE&GDAN	$\mathbf{95.5 \pm 1.5}$	111,863	**35.33**	**183.06**	$\mathbf{87.7 \pm 5.2}$	$\mathbf{86.7 \pm 3.5}$

domain. We use SAC as a base algorithm to apply our methods `SAC+GACE` and `SAC+GACE&GDAN`. Note that the ActorCritic is as depicted in Figure 1b, without the LSTM.

Results The results for robot manipulation tasks are shown in Table 2 and Figure 8 (in Appendix B). Performance is measured as the success ratio of the agent for 100 episodes. In R2 task, a visually diverse environment, `SAC` shows difficulty in learning. `SAC+AE` shows very high variance, possibly losing some important information for solving task in the process of encoding and decoding all pixels in the state. `SAC+CURL` consistently achieves competitive performances in all environments. It seems to successfully extract the features based on the latent dynamics of the state. `SAC+GACE` shows strong performance in R1, but could not outperform `SAC+CURL` in R2. This suggests that learning about the latent dynamics of robot manipulation task is also important due to the nature of the task, especially in environments with varying backgrounds. Finally, `SAC+GACE&GDAN` attains state-of-the art performance in all environments including the unseen task for generalization.

The SRR and SEI measurements of these methods are shown in Table 2. We select SAC as the reference algorithm and 74.0% as the reference success ratio. `SAC+GACE&GDAN` shows the state-of-the-art sample efficiency compared to all baseline models.

4.3 Analyses

Effectiveness of Goal-Aware Cross-Entropy Loss Additional experiments are conducted in the V1 task to investigate how our method influences the agent's learning. To vary the extent to which the GACE loss may affect learning, the goal-discriminator weights are frozen after 10K and 20K updates such that the GACE loss $\mathcal{L}_{GACE}$ does not contribute to learning afterwards. We note that in Figure 4a, although the GACE loss (frozen weights) does not further contribute to learning, the discriminator accuracy improves only by updating the policy. This indicates that throughout the training, the agent gradually develops a feature extractor $\sigma(\cdot)$ that can discriminate targets. Our method makes it possible for the feature extractor to directly learn to discriminate.

In addition, the learning curves in Figure 4b corroborate that such development of the feature extractor is accelerated by the GACE loss. Even when the agent is trained with the GACE only temporarily (as with GACE 10K and 20K), the learning curve is steeper than that with vanilla A3C. Furthermore, the unfrozen GACE (red line) shows a steeper learning curve than GACE 20K, which is again steeper than GACE 10K. Consequently, it can be seen that representation learning of feature extractor updated by GACE loss has positive influence on policy performance than learning solely with policy updates.

Analysis using Saliency Maps To ascertain that an agent trained with GACE and GACE&GDAN indeed becomes goal-aware, we use saliency maps [15] to visualize the operation of three agents

(a) Goal discriminator accuracy (b) Learning curve in V1 task

Figure 4: Additional experiments to analyze the effectiveness of GACE loss. The accuracy of the goal-discriminator (a) and learning curve of the agent (b) are measured with the goal-discriminator weights unfrozen (red), frozen at 10K (purple) and 20K (blue) updates.

within the V2 unseen task, as shown in Figure 5. The blue shades indicate the regions that the agent significantly attends to for policy inference, and the red shades indicate those regions for the value estimation. The overlapping blue and red regions appear purple. The three agents are trained with A3C, GACE, and GACE&GDAN, respectively, for 4M updates. For the ease of analysis, we mark non-goal objects with green circles and goal objects with yellow circles.

Figure 5a shows the operation of the A3C agent. It shows overly high sensitivity to edges in the background, approaching the walls rather than searching for the goal. Also, in the rightmost image in (a), although it does attend to the goal object located on the right side, a *TurnLeft* action is performed. This suggests that the agent cannot discern between objects because it lacks understanding of targets. Figure 5b corresponds to the GACE agent, showing high sensitivity to all targets and intermittent edges. As its attention to targets demonstrates, the ability to distinguish the goal is far superior to that of the A3C agent. Finally, Figure 5c shows that the GACE&GDAN agent exhibits high sensitivity to all goals while hardly responding to irrelevant edges. In addition, upon noticing the goal, the agent allocates attention only to the goal, rather than unnecessarily focusing on the non-goals. These results support that our method indeed promotes goal-directed behaviour that is visually explainable.

(a) A3C Results

(b) GACE Results

(c) GACE & GDAN Results

Figure 5: Visualization of saliency maps in V2 unseen (goal and non-goal in yellow and green circles respectively). (a) The agent is overly sensitive to edges in the background. (b) All goals and non-goals are detected successfully. (c) The agent shows sensitive reaction only to goal.

5 Conclusion

We propose GACE loss for learning goal states in a self-supervised manner, as well as GDAN that promotes goal-focused behaviour. Our methods achieve state-of-the-art sample-efficiency and generalization in two multi-target environments compared to previous methods that learn all states. We believe that the disparity between the performance improvements in the two benchmark suites is due to the degree of similarity between the goal states and the others.

Our method can be abused depending on the goal specified by a user, and if applied to a robot, it can cause physical damage. The limitation of our method is that it may not be well-applied in tasks where instructions do not specify a target (e.g. "Walk forward as far as possible") or tasks with little correlation between states and rewards based on success signal. Nonetheless, this paper brings to light the possible methods of prioritizing data for efficient training, especially in multi-target environment.

References

[1] Anderson, P., Wu, Q., Teney, D., Bruce, J., Johnson, M., Sünderhauf, N., Reid, I., Gould, S., and van den Hengel, A. (2018). Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3674–3683.

[2] Andrychowicz, M., Wolski, F., Ray, A., Schneider, J., Fong, R., Welinder, P., McGrew, B., Tobin, J., Abbeel, P., and Zaremba, W. (2017). Hindsight experience replay. *arXiv preprint arXiv:1707.01495*.

[3] Bahdanau, D., Cho, K., and Bengio, Y. (2014). Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*.

[4] Barati, E. and Chen, X. (2019). An actor-critic-attention mechanism for deep reinforcement learning in multi-view environments. In *IJCAI*, pages 2002–2008.

[5] Chaplot, D. S., Sathyendra, K. M., Pasumarthi, R. K., Rajagopal, D., and Salakhutdinov, R. (2018). Gated-attention architectures for task-oriented language grounding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32.

[6] Chen, H., Liu, Y., Zhou, Z., and Zhang, M. (2020a). A2c: Attention-augmented contrastive learning for state representation extraction. *Applied Sciences*, 10(17):5902.

[7] Chen, T., Kornblith, S., Norouzi, M., and Hinton, G. (2020b). A simple framework for contrastive learning of visual representations. *arXiv preprint arXiv:2002.05709*.

[8] Cheng, R., Agarwal, A., and Fragkiadaki, K. (2018). Reinforcement learning of active vision for manipulating objects under occlusions. In *Conference on Robot Learning*, pages 422–431. PMLR.

[9] Choi, J., Lee, B.-J., and Zhang, B.-T. (2017). Multi-focus attention network for efficient deep reinforcement learning. *arXiv preprint arXiv:1712.04603*.

[10] Colas, C., Fournier, P., Chetouani, M., Sigaud, O., and Oudeyer, P.-Y. (2019). Curious: intrinsically motivated modular multi-goal reinforcement learning. In *International conference on machine learning*, pages 1331–1340. PMLR.

[11] Deisenroth, M. P. and Fox, D. (2011). Multiple-target reinforcement learning with a single policy.

[12] Devo, A., Mezzetti, G., Costante, G., Fravolini, M. L., and Valigi, P. (2020). Towards general-ization in target-driven visual navigation by using deep reinforcement learning. *IEEE Transactions on Robotics*, 36(5):1546–1561.

[13] Dhiman, V., Banerjee, S., Siskind, J. M., and Corso, J. J. (2018). Learning goal-conditioned value functions with one-step path rewards rather than goal-rewards. *ICLR*.

[14] Florensa, C., Held, D., Geng, X., and Abbeel, P. (2018). Automatic goal generation for reinforcement learning agents. In *International conference on machine learning*, pages 1515–1528. PMLR.

[15] Greydanus, S., Koul, A., Dodge, J., and Fern, A. (2018). Visualizing and understanding atari agents. In *Proceedings of the 35th International Conference on Machine Learning*, pages 1792–1801.

[16] Ha, D. and Schmidhuber, J. (2018). World models. *arXiv preprint arXiv:1803.10122*.

[17] Haarnoja, T., Zhou, A., Abbeel, P., and Levine, S. (2018). Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pages 1861–1870.

[18] Harries, L., Lee, S., Rzepecki, J., Hofmann, K., and Devlin, S. (2019). Mazeexplorer: A customisable 3d benchmark for assessing generalisation in reinforcement learning. *Proceedings of the IEEE Conference on Games*.

[19] Higgins, I., Matthey, L., Pal, A., Burgess, C., Glorot, X., Botvinick, M., Mohamed, S., and Lerchner, A. (2017). beta-vae: Learning basic visual concepts with a constrained variational framework. *ICLR*.

[20] Hochreiter, S. and Schmidhuber, J. (1997). Long short-term memory. *Neural computation*, 9(8):1735–1780.

[21] Jaderberg, M., Mnih, V., Czarnecki, W. M., Schaul, T., Leibo, J. Z., Silver, D., and Kavukcuoglu, K. (2017). Reinforcement learning with unsupervised auxiliary tasks. *International Conference in Learning Representations*.

[22] Kalashnikov, D., Irpan, A., Pastor, P., Ibarz, J., Herzog, A., Jang, E., Quillen, D., Holly, E., Kalakrishnan, M., Vanhoucke, V., and Levine, S. (2018). Scalable deep reinforcement learning for vision-based robotic manipulation. In Billard, A., Dragan, A., Peters, J., and Morimoto, J., editors, *Proceedings of The 2nd Conference on Robot Learning*, volume 87 of *Proceedings of Machine Learning Research*, pages 651–673. PMLR.

[23] Kempka, M., Wydmuch, M., Runc, G., Toczek, J., and Jaśkowski, W. (2016). Vizdoom: A doom-based ai research platform for visual reinforcement learning. In *IEEE Conference on Computational Intelligence and Games (CIG)*, pages 1–8.

[24] Kingma, D. P. and Welling, M. (2013). Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*.

[25] Laskin, M., Lee, K., Stooke, A., Pinto, L., Abbeel, P., and Srinivas, A. (2020a). Reinforcement learning with augmented data. *arXiv preprint arXiv:2004.14990*.

[26] Laskin, M., Srinivas, A., and Abbeel, P. (2020b). Curl: Contrastive unsupervised representations for reinforcement learning. *Proceedings of the 37th International Conference on Machine Learning*.

[27] Liu, L., Dugas, D., Cesari, G., Siegwart, R., and Dubé, R. (2020). Robot navigation in crowded environments using deep reinforcement learning. pages 5671–5677.

[28] Mnih, V., Badia, A. P., Mirza, M., Graves, A., Lillicrap, T., Harley, T., Silver, D., and Kavukcuoglu, K. (2016). Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pages 1928–1937.

[29] Mott, A., Zoran, D., Chrzanowski, M., Wierstra, D., and Jimenez Rezende, D. (2019). Towards interpretable reinforcement learning using attention augmented agents. *Advances in Neural Information Processing Systems*, 32:12350–12359.

[30] Mousavian, A., Toshev, A., Fišer, M., Košecká, J., Wahid, A., and Davidson, J. (2019). Visual representations for semantic target driven navigation. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 8846–8852. IEEE.

[31] Nair, A. V., Pong, V., Dalal, M., Bahl, S., Lin, S., and Levine, S. (2018). Visual reinforcement learning with imagined goals. In Bengio, S., Wallach, H., Larochelle, H., Grauman, K., Cesa-Bianchi, N., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc.

[32] Nair, S., Savarese, S., and Finn, C. (2020). Goal-aware prediction: Learning to model what matters. In *International Conference on Machine Learning*, pages 7207–7219.

[33] Narasimhan, K., Barzilay, R., and Jaakkola, T. (2018). Grounding language for transfer in deep reinforcement learning. *Journal of Artificial Intelligence Research*, 63:849–874.

[34] Pardo, F., Levdik, V., and Kormushev, P. (2020). Scaling all-goals updates in reinforcement learning using convolutional neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 5355–5362.

[35] Plappert, M., Andrychowicz, M., Ray, A., McGrew, B., Baker, B., Powell, G., Schneider, J., Tobin, J., Chociej, M., Welinder, P., et al. (2018). Multi-goal reinforcement learning: Challenging robotics environments and request for research. *arXiv preprint arXiv:1802.09464*.

[36] Rajeswaran, A., Kumar, V., Gupta, A., Vezzani, G., Schulman, J., Todorov, E., and Levine, S. (2018). Learning complex dexterous manipulation with deep reinforcement learning and demonstrations. In *Proceedings of Robotics: Science and Systems*, Pittsburgh, Pennsylvania.

[37] Schaul, T., Horgan, D., Gregor, K., and Silver, D. (2015). Universal value function approximators. In *International conference on machine learning*, pages 1312–1320. PMLR.

[38] Shelhamer, E., Mahmoudieh, P., Argus, M., and Darrell, T. (2016). Loss is its own reward: Self-supervision for reinforcement learning. *arXiv preprint arXiv:1612.07307*.

[39] Shen, W. B., Xu, D., Zhu, Y., Guibas, L. J., Fei-Fei, L., and Savarese, S. (2019). Situational fusion of visual representation for visual navigation. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2881–2890.

[40] Shridhar, M., Thomason, J., Gordon, D., Bisk, Y., Han, W., Mottaghi, R., Zettlemoyer, L., and Fox, D. (2020). Alfred: A benchmark for interpreting grounded instructions for everyday tasks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10740–10749.

[41] Sutton, R. S. and Barto, A. G. (2018). *Reinforcement learning: An introduction*. MIT press.

[42] Todorov, E., Erez, T., and Tassa, Y. (2012). Mujoco: A physics engine for model-based control. In *IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 5026–5033.

[43] Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. (2017). Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008.

[44] Wu, Y., Wu, Y., Gkioxari, G., and Tian, Y. (2018). Building generalizable agents with a realistic and rich 3d environment. *arXiv preprint arXiv:1801.02209*.

[45] Yarats, D., Zhang, A., Kostrikov, I., Amos, B., Pineau, J., and Fergus, R. (2019). Improving sample efficiency in model-free reinforcement learning from images. *arXiv preprint arXiv:1910.01741*.

[46] Ye, X., Lin, Z., Lee, J.-Y., Zhang, J., Zheng, S., and Yang, Y. (2019). Gaple: Generalizable approaching policy learning for robotic object searching in indoor environment. *IEEE Robotics and Automation Letters*, 4(4):4003–4010.

[47] Zhao, R., Sun, X., and Tresp, V. (2019). Maximum entropy-regularized multi-goal reinforcement learning. In *International Conference on Machine Learning*, pages 7553–7562. PMLR.

[48] Zhu, H., Gupta, A., Rajeswaran, A., Levine, S., and Kumar, V. (2019). Dexterous manipulation with deep reinforcement learning: Efficient, general, and low-cost. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 3651–3657. IEEE.

[49] Zhu, Y., Mottaghi, R., Kolve, E., Lim, J. J., Gupta, A., Fei-Fei, L., and Farhadi, A. (2017). Target-driven visual navigation in indoor scenes using deep reinforcement learning. In *IEEE international conference on robotics and automation*, pages 3357–3364.