Self-Consistent Learning: Cooperation between Generators and Discriminators

Abstract

Using generated data to improve the performance of downstream discriminative models has recently gained popularity due to the great development of pre-trained language models. In most previous studies, generative models and discriminative models are trained separately and thus could not adapt to any changes in each other. As a result, the generated samples can easily deviate from the real data distribution, while the improvement of the discriminative model quickly reaches saturation. Generative adversarial networks (GANs) train generative models via an adversarial process with discriminative models to achieve joint training. However, the training of standard GANs is notoriously unstable and often falls short of convergence. In this paper, to address these issues, we propose a *self-consistent learning* framework, in which a discriminator and a generator are cooperatively trained in a closed-loop form. The discriminator and the generator enhance each other during multiple rounds of alternating training until a scoring consensus is reached. This framework proves to be easy to train and free from instabilities such as mode collapse and non-convergence. Extensive experiments on sentence semantic matching demonstrate the effectiveness of the proposed framework: the discriminator achieves 10+ AP of improvement on the zero-shot setting and new state-of-the-art performance on the full-data setting.

1 Introduction

The advance of Pre-trained Language Models (PLMs) (Brown et al., 2020; Chowdhery et al., 2022) has substantially improved the performance of deep neural networks across a variety of Natural Language Processing (NLP) tasks. Various language models, based on the Transformer (Vaswani et al., 2017) architecture, have been proposed, leading to state-of-the-art (SOTA) performance on the fundamental discrimination tasks. These models are first trained with self-supervised training objectives (e.g., predicting masked tokens according to surrounding tokens) on massive unlabeled text data, then fine-tuned on annotated data to adapt to downstream tasks of interest. However, annotated data is usually limited to a wide range of downstream tasks, which results in overfitting and a lack of generalization to unseen data.

One straightforward way to deal with this data scarcity problem is data augmentation (Xie et al., 2020), and incorporating generative models to perform data augmentation has been widely adopted recently (Carlini et al., 2021; Gangal et al., 2022). Despite its popularity, the generated text can easily deviate from the real data distribution without exploiting any of the signals passed back from the discrimination task. In previous studies, generative data augmentation and discrimination have been well studied as separate problems, but it is less clear how these two can be leveraged in one framework and how their performances can be improved simultaneously.

Generative Adversarial Networks (GANs) (Goodfellow et al., 2014; Gulrajani et al., 2017) are good attempts to couple generative and discriminative models in an adversarial manner, where a two-player minimax game between learners is carefully crafted. GANs have achieved tremendous success in domains such as image generation (Denton et al., 2015), and related studies have also shown their effectiveness in semi-supervised learning (Salimans et al., 2016; Kumar et al., 2017). However, GANs are notoriously difficult to train, most training objectives work well for only one model, either the discriminator or the generator, so rarely both learners can be optimal at the same time (Arjovsky & Bottou, 2017; Wiatrak et al., 2019). This essentially arises from the adversarial nature of GANs,

that during the process, optimizing one learner can easily destroy the learning ability of the other, making GANs fail to converge.

Another limitation of simultaneously optimizing the generator and the discriminator comes from the discrete nature of text in NLP, as no gradient propagation can be done from discriminators to generators. One theoretically sound attempt is to use reinforcement learning (RL), but the sparsity and the high variance of the rewards in NLP make the training particularly unstable (Caccia et al., 2020).

To address these shortcomings, we novelly introduce a self-consistent learning framework based on one generator and one discriminator: the generator and the discriminator are alternately trained by way of cooperation instead of competition, and the samples are used as the medium to pass the feedback signal from the discriminator. Specifically, in each round of training, the samples generated by the generator are synthetically labeled by the discriminator, and then only part of them would be selected based on dynamic thresholds and used for the training of the discriminator and the generator in the next round. Several benefits can be discovered from this cooperative training process. First, a closed-loop form of cooperation can be established so that we can get the optimal generator and discriminator at the same time. Second, this framework helps improve the generation quality while ensuring the domain specificity of generator, which in turn contributes to training. Third, a steady stream of diverse synthetic samples can be added to the training in each round and lead to continuous improvement of the performance of all learners. Finally, we can start the training with only domain-related corpus and obtain strong results, while these data can be easily sampled with little cost or supervision. Also, the performance on labeled datasets can be further boosted based on the SOTA level. As an example to demonstrate the effectiveness of our framework, we examine it on the task of sentence semantic matching. The experiments show that our method significantly improves over standalone state-of-the-art discriminative models on zero-shot and full-data settings.

Our contributions are summarized as follows,

• We propose a self-consistent learning framework that incorporates the generator and the discriminator, in which both achieve remarkable performance gains simultaneously.

• We propose a dynamic selection mechanism such that cooperation between the generator and the discriminator drives the convergence to reach their scoring consensus.

• Experimental results show that our proposed framework significantly outperforms the state-of-the-art methods for the task of sentence semantic matching.

2 RELATED WORKS

To alleviate the lack of annotated data in supervised learning in NLP, semi-supervised learning (SSL) has been a popular line of research (Van Engelen & Hoos, 2020). The sources of the unlabeled data required by SSL are either collected from the domains or generated by generative language models. Then NLU models can learn from the unlabeled data by pseudo-labeling (Arazo et al., 2020; Banitalebi-Dehkordi & Zhang, 2021) and consistent regularization (Jeong et al., 2019; Sohn et al., 2020). However, collecting unlabeled data comes at a cost(though smaller than labeling data), and the total amount is limited. Even with generative models, there is no guarantee of the quality of the generated samples, because the model cannot tune the generating results based on the performance of the downstream tasks. In contrast, our method usually includes a continuously updated generative model, which dynamically adjusts its generation according to the performance of downstream tasks.

In GANs, the generator is adversarially trained with the discriminator. Unlike conventional GANs in continuous domains, language GANs usually employ Gumbel-Softmax differentiation (Jang et al., 2017; Yin et al., 2020), Reinforcement Learning (RL) (Yu et al., 2017; Wu et al., 2021), or modified training objectives (Montahaei et al., 2021) to update the generator, to use the non-differential signals from the discriminator. However, language GANs are often criticized for underperforming Maximum likelihood estimation (MLE) and are very difficult to train, even the single optimality of either the generator or the discriminator cannot be guaranteed (Alvarez-Melis et al., 2022). In comparison, our proposed framework allows us to cooperatively couple the generator and the discriminator, leading to continuous improvement for both learners.

3 METHODOLOGY

3.1 COOPERATIVE OR ADVERSARIAL

Following the principle of self-consistency outlined in Ma et al. (2022), a closed-loop training needs to be built between the generator and the discriminator, either cooperatively or adversarially. GANs are typical examples of adversarial learning, but training GANs remains quite unstable. Let us consider an extreme case to show the possible instability: the discriminator can perfectly distinguish real data and fake data generated by the generator, and the generator can fully reproduce the real data distribution. Then the discriminator has only a 50% probability of selecting all samples that are generated by the generator. Therefore, any further updates to the generator parameters based on the feedback from the discriminator deviate the generator from the optimum. Neither the generator nor the discriminator can likely be optimal (Arjovsky & Bottou, 2017; Lamprier et al., 2022). In practice, a very delicate balance needs to be maintained between the discriminator and the generator to keep the training stable. In terms of cooperatively closed-loop learning, as discussed below, it does not suffer from instability: the generator and the discriminator usually enhance each other.

3.2 SELF-CONSISTENT LEARNING FRAMEWORK

In this section, we introduce our self-consistent learning (**SCL**) framework.

Figure 1: Overview of the flow chart for the SCL framework.

As shown in Figure 1, our framework, similar to the GANs, consists of a generator and a discriminator model. However, contrasting to the GANs, these two parts in our framework work cooperatively to enhance each other. Specifically, for any given class k, the generator $\mathcal{G}$ now become a conditional generator that takes in an input sentence s_k^a and generate an output sentence s_k^b. The discriminator $\mathcal{D}$ is then responsible for discriminating the sentence using a dynamic threshold $\epsilon_{\mathcal{D}}$. The discriminated sentence is used as positive or negative data for that specific class to continue the training process. Once the new discriminator is trained, the sentence is discriminated again by the new discriminator with a different dynamic threshold $\epsilon_{\mathcal{G}}$. This time only the positive data is passed to the generator as the training data for the new round. In this way, a closed loop of cooperation is formed.

In the above closed-loop training, we propose a **selection mechanism** that uses dynamic thresholds to filter samples. This mechanism is empirically shown to play a critical role in closing the gap between the generator and the discriminator, and thus makes this cooperation loop a virtuous circle. Specifically, as shown in Equation 1, the output probability $p_{\mathcal{D}}(y = k|s_k^b)$ that the sentence $\{s_k^b\}$ belongs to class k is calculated from the embedding representation $\mathbf{H}$ of $\{s_k^b\}$,

$$p_{\mathcal{D}}(y = k|s_k^b) = \text{softmax}(\text{MLP}(\mathbf{H})) \tag{1}$$

where y represents the class label. Then, through the *filter* function in Equation 2, we keep samples whose output probability is not less than threshold $\epsilon_{t,k}$, while other generated samples whose confidence is lower than threshold $\epsilon_{t,k}$ are discarded.

$$\text{filter}(y) \triangleq p_{\mathcal{D}}(y = k|s_k^b) \geq \epsilon_{t,k} \tag{2}$$

where $\epsilon_{t,k}$ represents the dynamic threshold for accepting $\{s_k^b\}$ as negative or positive samples in the t-th round. The generalized threshold function for $\epsilon_{t,k}$ is defined as,

$$\epsilon_{t,k} = f(t, \mathcal{L}_{t-1,k}, \epsilon_{t-1,k}) \tag{3}$$

where $\mathcal{L}_{t-1,k}$ and $\epsilon_{t-1,k}$ represent the discriminator loss and threshold for round $t - 1$, respectively. $\mathcal{L}_{0,k}$ is set as 0 and $\epsilon_{0,k} = \lambda$, where λ represents a hyperparameter.

Theorem 1 *At round t, given the previous round discriminator $\mathcal{D}_\phi^{t-1}$, the aim of optimizing the generator $\mathcal{G}_\theta^t$ boils down to:*

$$\min_\theta \mathbb{D}_{KL}(p_{\mathcal{D}_\phi^{t-1}}(\cdot), p_{\mathcal{G}_\theta^t}(\cdot))$$

where $\mathbb{D}_{KL}$ is the standard KL divergence and $p(\cdot)$ is the probability distribution of the model output.

Theorem 1 shows that the generator at round t is encouraged to approximate the probability distribution given by the previous round discriminator. In particular, on the basis of a well-pretrained discriminator, the generated distribution of the generator can be guaranteed to be faithful to the real data distribution. The proof is given in Appendix A.

Why Cooperative, Not Adversarial? (1) the generator is no longer a challenger to the discriminator that only provides negative data points to fool it, but now serves as a data augmenter to provide both positive and negative data points to enhance the discriminator; (2) the generator no longer updates its parameters through the policy gradients guided by the signals from the discriminator, but rather by utilizing the filtered data points to further improve its conditional generation quality. Note that by deliberately choosing the conditional generation paradigm along with the selection mechanism, we not only make the training more stable due to the different training goals, but also bypass the mode collapse problem of GANs (see Section 4.6 for further discussion). Besides, by iterating through the loops, our framework achieves self-consistency by honing the domain specificity of the generator and increasing the domain data exposure of the discriminator.

3.3 SENTENCE SEMANTIC MATCHING

We leverage the sentence semantic matching task (*i.e.* $k = 2$) as an example to demonstrate the effectiveness of our method. First, let us introduce the formal definition of this task. Given two sentences $s^a = \{w_1^a, w_2^a, ..., w_{\ell_a}^a\}$ and $s^b = \{w_1^b, w_2^b, ..., w_{\ell_b}^b\}$, where w_i^a and w_j^b represent the i-th and j-th tokens in the sentences, and ℓ_a and ℓ_b indicate the length of s^a and s^b. The goal of this task is to learn a discriminator $\mathcal{D}$ to precisely predict the label $y = \mathcal{D}(s^a, s^b)$, where $y \in \mathcal{Y} = \{0, 1\}$ indicates whether the two sentences are similar.

In our task, $\mathcal{G}$ is trained to generate a similar sentence s^b from any given sentence s^a and $\mathcal{D}$ is trained to predict label y from any given sentence pair $\{s^a, s^b\}$. As demonstrated in Figure 1, there are mainly two training processes in the entire framework: fix $\mathcal{G}$ to train $\mathcal{D}$ and fix $\mathcal{D}$ to train $\mathcal{G}$. We introduce the two training procedures in detail with the t-th round training.

Training $\mathcal{D}$: We first randomly sample s_t^a from domain-related corpus C, and then input s_t^a to $\mathcal{G}^t$ to generate s_t^b. Next, we feed sentence pair $\{s_t^a, s_t^b\}$ into $\mathcal{D}^{t-1}$ to predict the label y_{t-1}, and filter $\{s_t^a, s_t^b, y_{t-1}\}$ using threshold $\epsilon_{\mathcal{D}}^{t-1}$. Finally, we train $\mathcal{D}^{t-1}$ on the selected data and pre-training data P to get an improved discriminator $\mathcal{D}^t$. Note that the filtered data have both positive and negative samples. The update process of $\mathcal{D}$ seeks to minimize the cross-entropy loss over all instances:

$$\mathcal{L}_{\mathcal{D}}(\boldsymbol{s}, \boldsymbol{y}) = \frac{1}{|\boldsymbol{s}|} \sum_{i=1}^{|\boldsymbol{s}|} -[y_i \cdot \log p_{\mathcal{D}}(y_i = 1|s_i^a, s_i^b) + (1 - y_i) \cdot \log(1 - p_{\mathcal{D}}(y_i = 1|s_i^a, s_i^b))]$$

Training $\mathcal{G}$: We feed the generated sentence pairs $\{s_t^a, s_t^b\}$ into $\mathcal{D}^t$ to predict new labels y_t, and then filter $\{s_t^a, s_t^b, y_t\}$ using threshold $\epsilon_{\mathcal{G}}^t$ and additional rules [1]. Note that the filtered data has only positive samples. For the filtered data, we supplement it with the pre-training data P to update $\mathcal{G}^t$ to $\mathcal{G}^{t+1}$ [2] We also take out s_t^b from the filtered data and add them to the domain-related corpus. The expanded domain corpus are used to sample conditional sentences in the next round of generation. The update procedure of $\mathcal{G}$ employs the negative log-likelihood function over all instances:

$$\mathcal{L}_{\mathcal{G}}(\boldsymbol{s^a}, \boldsymbol{s^b}) = -\frac{1}{|\boldsymbol{s^b}|} \sum_{t=1}^{|\boldsymbol{s^b}|} \log p_{\mathcal{G}}(s_t^b|s_{<t}^b, \boldsymbol{s^a})$$

For the selection mechanism, we adopt the form $\epsilon^t = m * t + \lambda$ after comparing the effects of different functions through experiments according to Equation 3. where m is the increment of the threshold for each round, λ is the initial threshold, and ϵ_t is the threshold for rounds t.

In the process of training $\mathcal{G}$, since the sentences generated in each round are added to the domain-related corpus, the source of domain-specific data is thus monotonically expanding by iterating the self-consistent learning loop. The formalized process is shown in Algorithm 1.

Algorithm 1 Self-consistent Learning (**SCL**)

Require: Generator $\mathcal{G}$; Discriminator $\mathcal{D}$; Domain-Related Corpus C; Pre-training Data P.
 1: Initialize $\mathcal{G}^0$ and $\mathcal{D}^0$ with pre-trained language models;
 2: Warm-up $\mathcal{G}^0$ and $\mathcal{D}^0$ with pre-training data P to get $\mathcal{G}^1$ and $\mathcal{D}^1$;
 3: **for** each round $i \in [1, n]$ **do**
 4:     **if** Two consecutive rounds of discriminator still improve **then**
 5:         Generate similar sentences $s^b \sim p_{\mathcal{G}^i}(\cdot|s^a)$ from sampled sentences s^a from C;
 6:         Predict pseudo-labels $y^i \sim p_{\mathcal{D}^i}(\cdot|s^a, s^b)$;
 7:         Use threshold $\epsilon_{\mathcal{D}}^i$ to select data on $\{s^a, s^b, y^i\}$ to train $\mathcal{D}^{i+1}$;
 8:         Predict pseudo-labels $y^{i+1} \sim p_{\mathcal{D}^{i+1}}(\cdot|s^a, s^b)$;
 9:         Use threshold $\epsilon_{\mathcal{G}}^i$ and additional rules to select data on $\{s^a, s^b, y^{i+1}\}$ to train $\mathcal{G}^{i+1}$;
10:     **end if**
11: **end for**

---

4 EXPERIMENTS

4.1 TASKS DESIGN

In our experiments, the pre-training datasets are used to warm up the discriminator and generator, and the domain-related corpus is a set of independent sentences. To avoid label leakage, none of the training datasets participate in the pre-training of the generator and discriminator. In other words, the datasets in pre-training and self-consistent training are two non-overlapped datasets.

Zero-shot Baseline: We utilize the best-performing Chinese model RoBERTa-wwm-ext-large (Cui et al., 2020; 2021) and English model ALBERT-xxlarge-v2 (Lan et al., 2020) as the base discriminators in our self-consistent learning framework.

---

[1] The additional rules are used to exclude sentences which are too long, too short, or too similar according to the longest common substring algorithm.

[2] Note that the pre-training data P is used to warm up $\mathcal{G}$ and $\mathcal{D}$. Although pre-training data is not mandatory in subsequent training, we empirically found that including it when training $\mathcal{G}$ can prevent language degeneration and improve downstream performances.

Fine-tune Baseline: We compare our model with several state-of-the-art semantic matching models, including the following. Chinese models MacBERT (Cui et al., 2020), StructBERT (Wang et al., 2020), RoFormer (Su et al., 2021; Su et al., 2022), XLNet (Xu et al., 2020), ELECTRA (Cui et al., 2020), ALBERT (Lan et al., 2020), RoBERTa (Cui et al., 2020; 2021) and English models BERT (Devlin et al., 2019b), XLM-RoBERTa (XLM-R) (Conneau et al., 2020), XLNet (Yang et al., 2019b), ELECTRA (Clark et al., 2020), ALBERT (Lan et al., 2020), RoBERTa (Liu et al., 2019). For a fair comparison, we use models that are as close in size as possible.

4.2 EXPERIMENTS SETUP

4.2.1 DATASETS

We conduct experiments on three Chinese semantic matching datasets AFQMC (Xu et al., 2020), CHIP-STS (Zhang et al., 2022a), Chinese-QQP (Wang et al., 2019) and an English semantic matching dataset MRPC (Wang et al., 2019). More details about the datasets are given in Appendix C.

4.2.2 MODEL PRE-TRAINING

We adopt the well-established Transformer-XL (Dai et al., 2019)/OPT (Zhang et al., 2022b) architectures as the Chinese/English generator. To enable the generator to generate similar sentences with better linguistic quality, we pre-train a Transformer-XL model with 5.0 billion parameters and incrementally pre-train an OPT model with 2.7 billion parameters on the corpus consisting of plain texts and similar sentence pairs. Cleaned large-scale Chinese corpus WuDaoCorpora (Yuan et al., 2021) and English corpus WikiText (Merity et al., 2017) are used as plain texts. Similar sentence pairs that do not overlap with downstream datasets are used in the pre-training, and the designed prompts are employed to guide the generation of similar sentences. More details regarding model pre-training can be found in Appendix B.

4.3 ZERO-SHOT RESULTS

Table 1 shows how the F1 score of the discriminator varies with the number of self-consistent learning rounds on different datasets in the zero-shot task. According to Algorithm 1, the training is stopped when the discriminator no longer improves for two consecutive rounds. In addition, these four datasets are collected from different domains to further reflect the generality of our method in different domains. Specific training settings are recorded in Appendix D.

Table 1: Zero-Shot Performance of the Discriminator. (F1 score (%))

Round Num	AFQMC (*Financial*)	CHIP-STS (*Medical*)	Chinese-QQP (*Common*)	MRPC (*News*)
baseline	38.25	58.82	57.88	68.54
1	39.61	62.89	60.08	75.47
2	44.98	67.24	58.57	76.63
3	45.99	71.38	60.30	83.00
4	45.71	71.45	61.31	83.90
5	48.01	74.06	64.47	84.24
6	50.41	74.08	66.44	84.50
7	50.68	76.66	63.88	84.32
8	**51.36**	76.30	65.46	**84.61**
9	-	76.67	68.08	-
10	-	**77.42**	**70.51**	-
	+13.11	**+18.60**	**+12.63**	**+16.07**

The scores in the last line of Table 1 give the improvement of our discriminator in the last round relative to the first round. We can see that the F1 score gradually increases after each training round, eventually reaching a 10+ absolute percentage (AP) improvement. We believe what drives the improvement of the discriminator is the self-consistency, which it acquires with the generator step by step during the loop.

To verify that the generator also improves after self-consistent training, we adopt Perplexity and Bertscore (Zhang et al., 2020) to measure the language fluency and the semantic similarity (i.e. domain specificity) respectively. For different generators in different rounds, we first select s^a in similar sentence pairs from the same test set as the original sentences input, and generate similar sentences s^b with greedy search. The reason for not using other sampling methods is to ensure reproducibility. Given the generated sentences, we introduce an additional GPT2 [3] model to calculate the perplexity of generated similar sentences, and use a third-party library [4] to calculate the bertscore between the original and generated similar sentences. The results are shown in Table 2.

Table 2: Zero-Shot Performance of the Generator.

	AFQMC	CHIP-STS	Chinese-QQP	MRPC
Perplexity -*first round*	10.13	6.86	12.94	28.71
Perplexity -*last round*	8.43	5.97	12.27	17.56
Bertscore -*first round*	0.79	0.84	0.87	0.94
Bertscore -*last round*	0.80	0.85	0.89	0.97

We can see that the perplexity/bertscore of the last round in Table 2 has decreased/improved compared to the first round. Note that a lower perplexity indicates a more fluent sentence, while a higher bertscore indicates a more similar sentence. It suggests that after self-consistent training, the generator is gradually improved in language fluency and semantic similarity (i.e. domain specificity). The reason why the improvement of the generator is not as obvious as that of the discriminator is that the size of the generator is several times that of the discriminator, and the total number of training samples is limited. In Appendix E, the generated samples of the generator in different rounds are given to show the changes in the generation.

4.4 FINE-TUNE RESULTS

Our method not only works well in the zero-shot case, but also achieves good results in the full-data case. For the sake of a fair comparison, we reproduce several state-of-the-art semantic matching models on the four training sets, and their performances on the test sets are shown in Table 3.

Table 3: F1 Score(%) of Different Discriminators on the Test Datasets.

	#Param(zh/en)	AFQMC	CHIP-STS	Chinese-QQP	MRPC	AVG
BERT$_{large}$	-/335M	-	-	-	82.51	-
XLM-R$_{base}$	-/278M	-	-	-	84.27	-
MacBERT$_{large}$	326M/-	61.11	85.94	72.94	-	73.33
StructBERT$_{large}$	326M/-	60.56	85.17	76.33	-	74.02
RoFormer$_{large}$	316M/-	64.19	84.16	76.56	-	74.97
XLNet$_{large}$	360M/360M	50.31	82.97	64.96	79.51	69.44
ELECTRA$_{large}$	324M/334M	54.59	84.97	71.81	89.64	75.25
ALBERT$_{large}$	221M/223M	56.87	86.32	70.52	91.21	76.23
RoBERTa$_{large}$	326M/355M	57.29	86.93	74.58	90.24	77.26
Our Method	-	**66.59**	**88.39**	**78.43**	**92.78**	**81.55**

Our approach uses the best-performing model on a single test set as the base discriminator for self-consistent learning. The bold scores in the last line of Table 3 show that our method outperforms the SOTA results (shaded in gray) by 1 to 2 AP on all four test datasets, indicating the potential of self-consistent learning to further improve the model performance and establish new SOTA.

---

[3] Wenzhong-GPT2-110M (Wang et al., 2022) for Chinese data, and GPT2-base (Radford et al., 2019) for English data.

[4] https://pypi.org/project/bert-score/

4.5 Evaluating Self-consistency

In this section, we evaluate the consistency between the generator and the discriminator as the learning loop unfolds. We follow the same method used in Section 4.3 and use greedy search to generate similar sentences on the same test set. Then we take the confidence of the discriminator $R_\mathcal{D}$ as the score of the discriminator, which is calculated for the original sentences s^a and the generated similar sentences s^b according to Equation 4.

$$R_\mathcal{D} = p_\mathcal{D}(y^+|s^a, s^b) \tag{4}$$

where y^+ represents a positive label.

However, for the generator, to the best of our knowledge, there is no reliable way to measure how similar s^a and s^b are by using the generator itself. Therefore, to quantify this similarity, we introduce a third-party static model SimCSE [5] to get the embedding representation $\mathbf{A}, \mathbf{B}$ of sentences s^a, s^b. The cosine similarity $R_\mathcal{G}$ between $\mathbf{A}$ and $\mathbf{B}$ is then calculated according to Equation 5 to approximate the score of the generator.

$$\mathbf{A}, \mathbf{B} = \text{Encoder}(s^a), \text{Encoder}(s^b)$$
$$R_\mathcal{G} = \frac{\mathbf{A} \cdot \mathbf{B}}{\|\mathbf{A}\|_2 * \|\mathbf{B}\|_2} \tag{5}$$

where $\mathbf{A}$ and $\mathbf{B}$ both represent the embedding representation at the $[CLS]$ position. Note that the original sentence s^a remains unchanged in each round, while the generated sentence s^b changes.

Finally, for the trained discriminator and generator in each round t, we can obtain two score distributions $\mathbf{R}_\mathcal{D}^t$ and $\mathbf{R}_\mathcal{G}^t$ correspondingly. According to Theorem 1, we draw the curves of KL divergence between $\mathbf{R}_\mathcal{D}^t$ and $\mathbf{R}_\mathcal{G}^t$ in each round for the four datasets: AFQMC, CHIP-STS, Chinese-QQP, and MRPC. As illustrated in Figure 2, all the curves show a clear downward trend, indicating that the distance between the two score distributions decreases with the increase in the number of training rounds until a score consensus is reached. Table 4 shows the values of KL divergence in the first and last rounds. Numerically, it is more evident that the distances are significantly reduced on the four datasets.

Figure 2: The KL divergence between the score distributions of the discriminator and the generator.

	KL Divergence -first round	KL Divergence -last round
AFQMC	0.29	0.26
CHIP-STS	0.16	0.08
Chinese-QQP	0.18	0.06
MRPC	0.22	0.02

Table 4: The KL divergence in the first and last rounds.

---

[5]We use SimCSE-BERT-base to calculate scores on Chinese datasets and sup-SimCSE-BERT-base-uncased on English datasets. (Gao et al., 2021)

4.6 EFFECT OF PRE-TRAINING DATA AND SELECTION MECHANISM

We perform ablation experiments on the pre-training data and the selection mechanism in the zero-shot case. As described in Section 4.1, the pre-training data is used to pre-train the generator and discriminator, completely independent of the experimental datasets in self-consistent training.

To explore the influence of pre-training data on self-consistent training, we no longer add it in each round when training the discriminator, and only the generated data is used. But when the generator is trained, pre-training data is still retained to prevent language degeneration and lack of expressive diversity of the generation. The result of removing pre-training data is shown as the green curves in Figure 3. With all other training parameters being the same, after the same number of training rounds, the discriminator is slightly worse compared to the original method (red curves in Figure 3). However, the green curves maintain an upward trend and are very close to the red curves in all datasets except CHIP-STS. This shows that the generated data plays a key role in continuously improving the discriminator, while the pre-training data has a limited role.

Figure 3: Results of ablation experiments on pre-training data and selection mechanism. Results of the proposed method, results without pre-training data, and results without the selection mechanism are given in red, green, and blue, respectively.

In order to explore the effect of the selection mechanism on training the discriminator, we remove the selection mechanism when training the discriminator, while the training of the generator remains unchanged. The blue curves in Figure 3 depict the performance of the discriminator in each round after removing the selection mechanism. Compared to the original method (red curves), the discriminator only improves in the first round after removing the selection mechanism, which demonstrates the importance of the selection mechanism on the discriminator for the convergence of the self-consistent learning framework.

5 CONCLUSION

In this paper, we propose a self-consistent learning framework to enable cooperative training of the generator and the discriminator. During the training process, the generator and the discriminator continuously enhance each other until reaching a score consensus. This framework can utilize both limited labeled data and large-scale unlabeled domain-related corpus. Experimental results on four Chinese/English sentence semantic matching datasets demonstrate that as a form of closed-loop training, our proposed framework can achieve new state-of-the-art results with continuously improved generators and discriminators.

For future work, we will explore the effectiveness of our self-consistent learning framework on more NLP tasks, since the framework is straightforward and has no additional requirements on generators and discriminators.

6 REPRODUCIBILITY STATEMENT

We now discuss the efforts that have been made to ensure the reproducibility of our work. We have packaged the executable code and data into supplementary materials, which can be downloaded and run directly. In addition, we also provide detailed experimental parameters in the appendix to reproduce the experimental results. All datasets and code platforms (Pytorch) we use are public.

REFERENCES

David Alvarez-Melis, Vikas Garg, and Adam Tauman Kalai. Why gans are overkill for nlp. *arXiv preprint arXiv:2205.09838*, 2022. URL https://arxiv.org/abs/2205.09838.

Eric Arazo, Diego Ortego, Paul Albert, Noel E O'Connor, and Kevin McGuinness. Pseudo-labeling and confirmation bias in deep semi-supervised learning. In *2020 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–8. IEEE, 2020.

Martín Arjovsky and Léon Bottou. Towards principled methods for training generative adversarial networks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL https://openreview.net/forum?id=Hk4_qw5xe.

Amin Banitalebi-Dehkordi and Yong Zhang. Repaint: Improving the generalization of downstream visual tasks by generating multiple instances of training examples. In *32nd British Machine Vision Conference 2021, BMVC 2021, Online, November 22-25, 2021*, pp. 122. BMVA Press, 2021. URL https://www.bmvc2021-virtualconference.com/assets/papers/0068.pdf.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/1457c0d6bfcb4967418bfb8ac142f64a-Abstract.html.

Massimo Caccia, Lucas Caccia, William Fedus, Hugo Larochelle, Joelle Pineau, and Laurent Charlin. Language gans falling short. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=BJgza6VtPB.

Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, et al. Extracting training data from large language models. In *30th USENIX Security Symposium (USENIX Security 21)*, pp. 2633–2650, 2021.

Jing Chen, Qingcai Chen, Xin Liu, Haijun Yang, Daohe Lu, and Buzhou Tang. The BQ corpus: A large-scale domain-specific Chinese corpus for sentence semantic equivalence identification. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 4946–4951, Brussels, Belgium, 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1536. URL https://aclanthology.org/D18-1536.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. Palm: Scaling language modeling with pathways. *CoRR*, abs/2204.02311, 2022. doi: 10.48550/arXiv.2204.02311. URL https://doi.org/10.48550/arXiv.2204.02311.

Kevin Clark, Minh-Thang Luong, Quoc V. Le, and Christopher D. Manning. ELECTRA: pre-training text encoders as discriminators rather than generators. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=r1xMH1BtvB`.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 8440–8451, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.747. URL `https://aclanthology.org/2020.acl-main.747`.

Yiming Cui, Wanxiang Che, Ting Liu, Bing Qin, Shijin Wang, and Guoping Hu. Revisiting pre-trained models for Chinese natural language processing. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 657–668, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.findings-emnlp.58. URL `https://aclanthology.org/2020.findings-emnlp.58`.

Yiming Cui, Wanxiang Che, Ting Liu, Bing Qin, and Ziqing Yang. Pre-training with whole word masking for chinese bert. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 29:3504–3514, 2021. doi: 10.1109/TASLP.2021.3124365.

Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc Le, and Ruslan Salakhutdinov. Transformer-XL: Attentive language models beyond a fixed-length context. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2978–2988, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1285. URL `https://aclanthology.org/P19-1285`.

Emily L. Denton, Soumith Chintala, Arthur Szlam, and Rob Fergus. Deep generative image models using a laplacian pyramid of adversarial networks. In Corinna Cortes, Neil D. Lawrence, Daniel D. Lee, Masashi Sugiyama, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada*, pp. 1486–1494, 2015. URL `https://proceedings.neurips.cc/paper/2015/hash/aa169b49b583a2b5af89203c2b78c67c-Abstract.html`.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, 2019a. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL `https://aclanthology.org/N19-1423`.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, 2019b. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL `https://aclanthology.org/N19-1423`.

Varun Gangal, Steven Y Feng, Malihe Alikhani, Teruko Mitamura, and Eduard Hovy. Nareor: The narrative reordering problem. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 10645–10653, 2022.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. Simcse: Simple contrastive learning of sentence embeddings. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 6894–6910, 2021.

Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks, 2014. URL `https://arxiv.org/abs/1406.2661`.

Ishaan Gulrajani, Faruk Ahmed, Martín Arjovsky, Vincent Dumoulin, and Aaron C. Courville. Improved training of wasserstein gans. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5767–5777, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/892c3b1c6dccd52936e27cbd0ff683d6-Abstract.html.

Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. The curious case of neural text degeneration. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=rygGQyrFvH.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparametrization with gumble-softmax. In *International Conference on Learning Representations (ICLR 2017)*. OpenReview. net, 2017.

Jisoo Jeong, Seungeui Lee, Jeesoo Kim, and Nojun Kwak. Consistency-based semi-supervised learning for object detection. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 10758–10767, 2019. URL https://proceedings.neurips.cc/paper/2019/hash/d0f4dae80c3d0277922f8371d5827292-Abstract.html.

Abhishek Kumar, Prasanna Sattigeri, and Tom Fletcher. Semi-supervised learning with gans: Manifold invariance with improved inference. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5534–5544, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/d3d80b656929a5bc0fa34381bf42fbdd-Abstract.html.

Sylvain Lamprier, Thomas Scialom, Antoine Chaffin, Vincent Claveau, Ewa Kijak, Jacopo Staiano, and Benjamin Piwowarski. Generative cooperative networks for natural language generation. *arXiv preprint arXiv:2201.12320*, 2022. URL https://arxiv.org/abs/2201.12320.

Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. ALBERT: A lite BERT for self-supervised learning of language representations. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=H1eA7AEtvS.

Xin Liu, Qingcai Chen, Chong Deng, Huajun Zeng, Jing Chen, Dongfang Li, and Buzhou Tang. LCQMC:a large-scale Chinese question matching corpus. In *Proceedings of the 27th International Conference on Computational Linguistics*, pp. 1952–1962, Santa Fe, New Mexico, USA, 2018. Association for Computational Linguistics. URL https://aclanthology.org/C18-1166.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv e-prints*, pp. arXiv–1907, 2019.

Yi Ma, Doris Tsao, and Heung-Yeung Shum. On the principles of parsimony and self-consistency for the emergence of intelligence. *Frontiers of Information Technology & Electronic Engineering*, pp. 1–26, 2022.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL https://openreview.net/forum?id=Byj72udxe.

Ehsan Montahaei, Danial Alihosseini, and Mahdieh Soleymani Baghshah. Dgsan: discrete generative self-adversarial network. *Neurocomputing*, 448:364–379, 2021.

Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. 2019.

Tim Salimans, Ian J. Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. In Daniel D. Lee, Masashi Sugiyama, Ulrike von Luxburg, Isabelle Guyon, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pp. 2226–2234, 2016. URL https://proceedings.neurips.cc/paper/2016/hash/8a3363abe792db2d8761d6403605aeb7-Abstract.html.

Kihyuk Sohn, David Berthelot, Nicholas Carlini, Zizhao Zhang, Han Zhang, Colin A Raffel, Ekin Dogus Cubuk, Alexey Kurakin, and Chun-Liang Li. Fixmatch: Simplifying semi-supervised learning with consistency and confidence. *Advances in neural information processing systems*, 33:596–608, 2020.

Jianlin Su, Yu Lu, Shengfeng Pan, Ahmed Murtadha, Bo Wen, and Yunfeng Liu. RoFormer: Enhanced Transformer with Rotary Position Embedding. *arXiv e-prints*, art. arXiv:2104.09864, 2021. URL https://arxiv.org/abs/2104.09864.

Jianlin Su, Shengfeng Pan, Bo Wen, and Yunfeng Liu. Roformerv2: A faster and better roformer - zhuiyiai. Technical report, 2022. URL https://github.com/ZhuiyiTechnology/roformer-v2.

Jesper E Van Engelen and Holger H Hoos. A survey on semi-supervised learning. *Machine Learning*, 109(2):373–440, 2020.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5998–6008, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019. URL https://openreview.net/forum?id=rJ4km2R5t7.

Junjie Wang, Yuxiang Zhang, Lin Zhang, Ping Yang, Xinyu Gao, Ziwei Wu, Xiaoqun Dong, Junqing He, Jianheng Zhuo, Qi Yang, Yongfeng Huang, Xiayu Li, Yanghan Wu, Junyu Lu, Xinyu Zhu, Weifeng Chen, Ting Han, Kunhao Pan, Rui Wang, Hao Wang, Xiaojun Wu, Zhongshen Zeng, Chongpei Chen, Ruyi Gan, and Jiaxing Zhang. Fengshenbang 1.0: Being the foundation of chinese cognitive intelligence. *arXiv preprint arXiv:2209.02970*, 2022. URL https://arxiv.org/abs/2209.02970.

Wei Wang, Bin Bi, Ming Yan, Chen Wu, Jiangnan Xia, Zuyi Bao, Liwei Peng, and Luo Si. Structbert: Incorporating language structures into pre-training for deep language understanding. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=BJgQ4lSFPH.

Maciej Wiatrak, Stefano V Albrecht, and Andrew Nystrom. Stabilizing generative adversarial networks: A survey. *arXiv preprint arXiv:1910.00927*, 2019. URL https://arxiv.org/abs/1910.00927.

Qingyang Wu, Lei Li, and Zhou Yu. Textgail: Generative adversarial imitation learning for text generation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 14067–14075, 2021.

Qizhe Xie, Zihang Dai, Eduard Hovy, Thang Luong, and Quoc Le. Unsupervised data augmentation for consistency training. *Advances in Neural Information Processing Systems*, 33:6256–6268, 2020.

Liang Xu, Hai Hu, Xuanwei Zhang, Lu Li, Chenjie Cao, Yudong Li, Yechen Xu, Kai Sun, Dian Yu, Cong Yu, Yin Tian, Qianqian Dong, Weitang Liu, Bo Shi, Yiming Cui, Junyi Li, Jun Zeng, Rongzhao Wang, Weijian Xie, Yanting Li, Yina Patterson, Zuoyu Tian, Yiwen Zhang, He Zhou, Shaoweihua Liu, Zhe Zhao, Qipeng Zhao, Cong Yue, Xinrui Zhang, Zhengliang Yang, Kyle Richardson, and Zhenzhong Lan. CLUE: A Chinese language understanding evaluation benchmark. In *Proceedings of the 28th International Conference on Computational Linguistics*, pp. 4762–4772, Barcelona, Spain (Online), 2020. International Committee on Computational Linguistics. doi: 10.18653/v1/2020.coling-main.419. URL `https://aclanthology.org/2020.coling-main.419`.

Yinfei Yang, Yuan Zhang, Chris Tar, and Jason Baldridge. PAWS-X: A cross-lingual adversarial dataset for paraphrase identification. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3687–3692, Hong Kong, China, 2019a. Association for Computational Linguistics. doi: 10.18653/v1/D19-1382. URL `https://aclanthology.org/D19-1382`.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime G. Carbonell, Ruslan Salakhutdinov, and Quoc V. Le. Xlnet: Generalized autoregressive pretraining for language understanding. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 5754–5764, 2019b. URL `https://proceedings.neurips.cc/paper/2019/hash/dc6a7e655d7e5840e66733e9ee67cc69-Abstract.html`.

Haiyan Yin, Dingcheng Li, Xu Li, and Ping Li. Meta-cotgan: A meta cooperative training paradigm for improving adversarial text generation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 9466–9473, 2020.

Lantao Yu, Weinan Zhang, Jun Wang, and Yong Yu. Seqgan: Sequence generative adversarial nets with policy gradient. In Satinder P. Singh and Shaul Markovitch (eds.), *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence, February 4-9, 2017, San Francisco, California, USA*, pp. 2852–2858. AAAI Press, 2017. URL `http://aaai.org/ocs/index.php/AAAI/AAAI17/paper/view/14344`.

Sha Yuan, Hanyu Zhao, Zhengxiao Du, Ming Ding, Xiao Liu, Yukuo Cen, Xu Zou, Zhilin Yang, and Jie Tang. Wudaocorpora: A super large-scale chinese corpora for pre-training language models. *AI Open*, 2:65–68, 2021. ISSN 2666-6510. doi: https://doi.org/10.1016/j.aiopen.2021.06.001. URL `https://www.sciencedirect.com/science/article/pii/S2666651021000152`.

Ningyu Zhang, Mosha Chen, Zhen Bi, Xiaozhuan Liang, Lei Li, Xin Shang, Kangping Yin, Chuanqi Tan, Jian Xu, Fei Huang, Luo Si, Yuan Ni, Guotong Xie, Zhifang Sui, Baobao Chang, Hui Zong, Zheng Yuan, Linfeng Li, Jun Yan, Hongying Zan, Kunli Zhang, Buzhou Tang, and Qingcai Chen. CBLUE: A Chinese biomedical language understanding evaluation benchmark. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7888–7915, Dublin, Ireland, 2022a. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-long.544. URL `https://aclanthology.org/2022.acl-long.544`.

Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. Opt: Open pre-trained transformer language models. *arXiv preprint arXiv:2205.01068*, 2022b. URL `https://arxiv.org/abs/2205.01068`.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. Bertscore: Evaluating text generation with BERT. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=SkeHuCVFDr`.

A PROOFS

A.1 PROOF OF THEOREM 1

Theorem 1 *At round t, the aim of the optimization of the generator $\mathcal{G}_\theta^t$, given the previous round discriminator $\mathcal{D}_\phi^{t-1}$, boils down to,*

$$\min_\theta \mathbb{D}_{KL}(p_{\mathcal{D}_\phi^{t-1}}(\cdot), p_{\mathcal{G}_\theta^t}(\cdot))$$

where $\mathbb{D}_{KL}$ is the standard KL divergence and $p(\cdot)$ is the probability distribution of the model output.

Proof. The samples generated by the previous round generator $\mathcal{G}_\theta^{t-1}$ and filtered by the previous round discriminator $\mathcal{D}_\phi^{t-1}$ with a threshold ϵ_{t-1} are used for training of the current round generator $\mathcal{G}_\theta^{t-1}$, the goal of which is to maximize the probability that the generated samples pass the discrimination for fixed $\mathcal{D}_\phi^{t-1}$,

$$\max_\theta \mathbb{E}_{x \sim p_{\mathcal{G}_\theta^t}} p_{\mathcal{D}_\phi^{t-1}}(x)$$

A further transformation of the above formula shows that

$$\max_\theta \mathbb{E}_{x \sim p_{\mathcal{G}_\theta^t}} p_{\mathcal{D}_\phi^{t-1}}(x)$$
$$\Rightarrow \max \int \mathrm{d}\boldsymbol{\theta} \nabla_{\boldsymbol{\theta}} \mathbb{E}_{x \sim p_{\mathcal{G}_\theta^t}} p_{\mathcal{D}_\phi^{t-1}}(x)$$
$$\Rightarrow \max_\theta \int \mathrm{d}\boldsymbol{\theta} \mathbb{E}_{x \sim p_{\mathcal{G}_\theta^t}} \nabla_{\boldsymbol{\theta}} \log p_{\mathcal{G}_\theta^t}(x) p_{\mathcal{D}_\phi^{t-1}}(x)$$
$$\Rightarrow \max_\theta \int \mathrm{d}\boldsymbol{\theta} \nabla_{\boldsymbol{\theta}} \frac{1}{K} \sum_{k=1}^{K} \log p_{\mathcal{G}_\theta^t}(x_k) p_{\mathcal{D}_\phi^{t-1}}(x_k) - \log p_{\mathcal{D}_\phi^{t-1}}(x_k) p_{\mathcal{D}_\phi^{t-1}}(x_k)$$
$$\Rightarrow \min_\theta \mathbb{D}_{KL}(p_{\mathcal{D}_\phi^{t-1}}(\cdot), p_{\mathcal{G}_\theta^t}(\cdot))$$

which concludes our proof.

B MODEL DETAILS

The 5.0B Transformer-XL is pre-trained on 32 A100s with 40G memory for 45 days, the batch size is set to 32*8=256. After running 445k steps, the final validation loss reduces to about 2.4. The 2.7B OPT is incrementally trained on the basis of the open-source model.

During the pre-training of the generator model, we utilize the memory-cache mechanism of Transformer-XL and design a special attention mask to concatenate the multiple input sentences into one sample, to reduce the number of the padding token in a batch and therefore increase the number of effective tokens. To make the generation more robust, we add noise to the original sentences by randomly replacing or discarding tokens with a 5% probability. In addition, the prompts that we use for Chinese generation and English generation are as follows,

- Chinese prompt: "s^a"的相似句是"s^b" (en: A similar sentence to "s^a" is "s^b".)
- English prompt: "s^a" is similar to "s^b"

When training the discriminator, following the usage of special tokens in BERT (Devlin et al., 2019a), we use $[SEP]$ to concatenate two sentences and take the embedding at the $[CLS]$ position to represent the whole sentence to predict the label. Moreover, we utilize the mask method in BERT to randomly mask 15% of the input tokens.

C DATASET DETAILS

The statistics of the experimental datasets are reported in Table 5.

Table 5: Statistics of Experimental Datasets

		AFQMC	CHIP-STS	Chinese-QQP	MRPC(en)
Zero-Shot	domain-related corpus	68668	32000	10800	8,152
	test dataset	4316	4000	3600	1725
Fine-Tune	training dataset	34334	16000	5400	4076
	test dataset	4316	4000	3600	1725

Other Chinese datasets (LCQMC (Liu et al., 2018), OPPO, PAWS-X-zh (Yang et al., 2019a), BQ (Chen et al., 2018), CCKS, Chinese-STS-B (Wang et al., 2019)) and English datasets (QQP (Wang et al., 2019), STS-B (Wang et al., 2019), PAWS-X-en (Yang et al., 2019a)) are collected and used as the corpus of similar sentence pairs for pre-training the generator.

The Chinese-QQP dataset contains 9000 pieces of data randomly selected and translated from the English QQP dataset, which is then divided into training set and test set in a ratio of 3:2.

D   PARAMETER SETTINGS

The training parameters of zero-shot are shown in Table 6. The three thresholds are used to select positive and negative examples for training the discriminator and positive examples for training the generator, respectively. We adopt cosine annealing learning rate decay strategy during training.

Table 6: Parameter Settings of Zero-Shot.

	AFQMC	CHIP-STS	Chinese-QQP	MRPC
Maximum Threshold *-negative*	0.8	0.9	0.95	0.95
Minimum Threshold *-negative*	0.6	0.7	0.8	0.8
Maximum Threshold *-positive*	0.8	0.9	0.95	0.95
Minimum Threshold *-positive*	0.6	0.7	0.8	0.8
Maximum Threshold *-generator*	0.6	0.9	0.95	0.95
Minimum Threshold *-generator*	0.6	0.7	0.8	0.8
Threshold Increase	0.07	0.1	0.05	0.05
Sentence Num	6000	6000	3000	4000
Learning Rate	2e-5			
Warm Up Steps	40			
Early Stopping Patience	1			
Generator Batch Size *-training*	2(concatenate 30 samples)			24
Generator Batch Size *-predicting*	512			100
Discriminator Batch Size *-training*	64			32
Discriminator Batch Size *-predicting*	384			96

The training parameters of fine-tuning are shown in Table 7.

Table 7: Parameter Settings of Fine-Tune.

	AFQMC	CHIP-STS	Chinese-QQP	MRPC
Maximum Threshold *-negative*	0.98	0.98	0.84	0.8
Minimum Threshold *-negative*	0.9	0.7	0.6	0.6
Maximum Threshold *-positive*	0.98	0.98	0.98	0.8
Minimum Threshold *-positive*	0.9	0.7	0.9	0.6
Maximum Threshold *-generator*	0.98	0.98	0.98	0.8
Minimum Threshold *-generator*	0.9	0.7	0.9	0.6
Threshold Increase	0.07	0.07	0.07	0.2
Sentence Num	6000	6000	3000	3000
Learning Rate	5e-6			
Warm Up Steps	40			
Early Stopping Patience	1			
Generator Batch Size *-training*	2(concatenate 30 samples)			24
Generator Batch Size *-predicting*	512			100
Discriminator Batch Size *-training*	32	64	32	32
Discriminator Batch Size *-predicting*	256	384	256	96

E   GENERATE SAMPLES

The generators use nucleus sampling (Holtzman et al., 2020) to generate similar sentences. Generated examples in English are shown in Table 8 and in Chinese in Table 9.

Table 8: Generated Samples in English

MRPC(News)
origin: Hong Kong was flat, Australia, Singapore and South Korea lost 0.2-0.4 percent.
first round: the market is flat, the US is flat, Europe is flat, Japan is flat,
... Malaysia is flat, Philippines is flat, Vietnam is flat, Singapore is
last round: Hong Kong was unchanged, Australia, Singapore and South Korea
were down 0.2-0.4 percent.
origin: Ballmer has been vocal in the past warning that Linux is a threat to Microsoft.
first round: Microsoft is a threat to Linux.
last round: Ballmer has been vocal in the past about the threat Linux poses to Microsoft.
origin: Last year, Congress passed similar, though less expensive, buyout
legislation for peanut farmers, ending that Depression-era program.
first round: The government is going to buy out your farm and give you a check
for $1,000,000.00. You can't refuse.
last round: Congress passed a similar bill last year to end a Depression-era
program for peanut farmers, ending that program.
origin: Licensing revenue slid 21 percent, however, to $107.6 million.
first round: The company's net income fell to $1.1 million, or 2 cents per share,
in the quarter ended Sept. 30, from $1.3 million, or 3 cents per share, a year earlier.
last round: Licensing revenue fell 21 percent to $107.6 million
in the third quarter.
origin: SCO says the pricing terms for a license will not
be announced for weeks.
first round: we're not going to tell you how much it costs to buy a car, but
we're going to tell you how much it costs to rent one.
last round: The pricing terms for a license for the SCO software will not
be announced for several weeks.

Table 9: Generated Samples in Chinese.

AFQMC (Financial)	*origin*：可以用自己的支付宝为别人的花呗还款吗
(Can I use my Alipay to repay someone else's Huabei)
first round：花呗的钱可以让其他人代还吗
(Can someone else pay for the money from Huabei)
last round：花呗能不能帮别人还
(Can my Huabei help others repay?)
	origin：花呗怎么还欠费
(How does Huabei pay off the arrears)
first round：花呗怎么还有电费
(Why does Huabei still have electricity bills)
last round：花呗还款怎么还
(How to pay off Huabei)
	origin：我的花呗收款二维码
(QR code for my Huabei payment)
first round：商家花呗的二维码
(Merchant Huabei's QR code)
last round：花呗收款二维码在哪里
(Where is the QR code for Huabei payment)
CHIP-STS (Medical)	*origin*：艾滋病的病因是什么
(What is the cause of AIDS)
first round：艾滋病毒是什么？
(What is HIV?)
last round：艾滋病是什么原因引起的？
(What causes AIDS?)
	origin：高血压总是流口水是怎么回事
(High blood pressure is always drooling what is going on)
first round：高血压怎么回事
(What about high blood pressure)
last round：高血压为什么会流口水？
(Why does high blood pressure cause drooling?)
	origin：得了糖尿病,现在越来越瘦了怎么回事
(Why am I getting thinner and thinner now that I have diabetes)
first round：糖尿病现在怎么回事？
(What's going on with diabetes now?)
last round：糖尿病患者为什么会瘦？
(Why do people with diabetes lose weight?)
Chinese-QQP (Common)	*origin*：如何从此网站删除我的帐户？
(How do I delete my account from this site?)
first round：怎么删除网站
(How to delete a website)
last round：如何才能删除我的帐户？
(How can I delete my account?)
	origin：关于电子产品的一些好书是什么？
(What are some good books on electronics?)
first round：有什么好的电子产品推荐
(Any good electronics recommendations)
last round：有哪些关于电子产品的好书？
(What are some good books about electronics?)
	origin：为什么没有人看到无尽和无限之间的区别？
(Why does no one see the difference between endless and infinite?)
first round：为什么宇宙中没有极限的存在
(Why is there no limit in the universe)
last round：为什么没有人知道无限和有限之间的区别？
(Why does no one know the difference between infinite and finite?)