Typing assumptions improve identification
in causal discovery

Abstract

Causal discovery from observational data is a challenging task that can only be solved up to a set of equivalent solutions, called an equivalence class. Such classes, which are often large in size, encode uncertainties about the orientation of some edges in the causal graph. In this work, we propose a new set of assumptions that constrain possible causal relationships based on the nature of variables, thus circumscribing the equivalence class. Namely, we introduce *typed directed acyclic graphs*, in which variable types are used to determine the validity of causal relationships. We demonstrate, both theoretically and empirically, that the proposed assumptions can result in significant gains in the identification of the causal graph. We also propose causal discovery algorithms that make use of our proposed assumptions and demonstrate their benefits on simulated and pseudo-real data.

1. Introduction

Can the temperature of a city alter its altitude (Peters et al., 2017)? Can a light bulb change the state of a switch? Can the brakes of a car be activated by their indicator light (de Haan et al., 2019)? Chances are, you did not need to think very hard to answer these questions, since you intuitively understand the implausibility of causal relationships between certain *types of entities*. This form of prior knowledge has been shown to play a key role in causal reasoning (Griffiths et al., 2011; Schulz and Gopnik, 2004; Gopnik and Sobel, 2000). In fact, in the absence of evidence (e.g., data), humans tend to reason inductively and use domain knowledge to generalize known causal relationships to new, similar, entities (Kemp et al., 2010).

Nonetheless, the elucidation of causal relationships often goes beyond human intuition. The abundance of large-scale scientific endeavors to understand the causes of diseases (1KGP, 2010) or natural phenomena (Runge et al., 2019) are good examples. In such cases, computational methods for *causal discovery* may help reveal causal relationships based on patterns of association in data (see Heinze-Deml et al. (2018) for a review). The most common setting consists of representing causal relationships as a directed acyclic graph where vertices correspond to variables of interest and edges indicate causal relationships. Additional assumptions, like the *faithfulness* condition, are then made to enable reasoning about graph structures based on conditional independences in the data. While these enable data-driven causal discovery, the underlying causal graph can only be identified up to its *Markov equivalence class* (Peters et al., 2017), which can often be very large (He et al., 2015) thus leaving many edges unoriented.

Inspired by how humans use types to reason about causal relationships, this work explores how prior knowledge about the nature of the variables can help reduce the size of such

equivalence classes. Building on the theoretical foundations of causal discovery in directed acyclic graphs, we propose a new theoretical framework for the case where *variables are labeled by type*. Such types can be attributed based on prior knowledge, e.g., via a domain expert. We then make assumptions on how types can interact with each other, which constrains the space of possible graphs and leads to reduced equivalence classes. We show, both theoretically and empirically, that when such assumptions hold in the data, significant gains in the identification of causal relationships can be made.

Contributions:

- We propose a new theoretical framework for causal discovery where possible causal relationships are constrained based on the type of variables (Section 4).

- We prove theoretical results that guarantee the orientation of all inter-type edges and, in certain conditions, the convergence of the equivalence class to a singleton (identification), when the number of vertices tends to infinity and the number of types is fixed (Section 5).

- We present simple algorithms to incorporate our type-based assumptions in causal discovery, along with theoretical results that guarantee their consistency (Section 6).

- We present an empirical study that illustrates the benefits of our proposed algorithms over a baseline that does not consider variable types (Section 7).

2. Problem formulation

Causal graphical models. In this work, we adopt the framework of causal graphical models (CGM) (Peters et al., 2017). Let $X = (X_1, \ldots, X_d)$ be a random vector with distribution P_X. Let $G = (V, E)$ be a directed acyclic graph (DAG) with vertices $V = \{v_1, \ldots, v_d\}$. Each vertex $v_i \in V$ is associated to variable X_i and a directed edge $(v_i, v_j) \in E$ represents a direct causal relationship from X_i to X_j. We assume that P_X can be factorized according to G, that is,

$$p(x_1, \ldots, x_d) = \prod_{j=1}^{d} p(x_j \mid pa_j^G),$$

where pa_j^G denotes the parents of X_j in G[1]. From this graph, it is possible to estimate quantities of causal nature (e.g., via do-calculus (Pearl, 1995)). However, in many situations, the structure of G is unknown and must be inferred from data.

Causal discovery. The task of causal discovery consists of learning the structure of G based on observations from P_X. Some assumptions are required to make this possible. By adopting the CGM framework, we assume: (i) *causal sufficiency*, which states there is no unobserved variable that causes more than one variable in X and (ii) the *causal Markov property*, which states that $X_i \perp\!\!\!\perp_G X_j \mid Z \implies X_i \perp\!\!\!\perp_{P_X} X_j \mid Z$, where Z is a set composed of variables in X, $X_i \perp\!\!\!\perp_G X_j \mid Z$ indicates that X_i and X_j are d-separated by Z in G, and $X_i \perp\!\!\!\perp_{P_X} X_j \mid Z$ indicates that X_i and X_j are independent conditioned on Z. Additionally,

---

1. This is a slight abuse of language. Here, we mean the parents of vertex v_j in G.

we assume (iii) *faithfulness*, which states that $X_i \perp\!\!\!\perp_{P_X} X_j \mid Z \implies X_i \perp\!\!\!\perp_G X_j \mid Z$. Hence, conditional independences in the data can be used to learn about the structure of G.

Equivalence classes. Even with these assumptions, G can only be recovered up to a *Markov equivalence class* (MEC) (Peters et al., 2017), which is the set of all the DAGs that encode exactly the same conditional independences as G. The MEC is often characterized graphically using an *essential graph* or *Completed Partially Directed Acyclic Graph* (CPDAG), which corresponds to the union of all Markov equivalent DAGs (Andersson et al., 1997). While two DAGs are Markov equivalent if and only if they have the same skeleton and immoralities (Verma and Pearl, 1990), the CPDAG can contain other oriented edges, resulting from constraints such as not creating cycles or additional immoralities[2]. In some cases, e.g., for sparse graphs, the size of the MEC can be huge (He and Yu, 2016; He et al., 2015), significantly limiting inference about the direction of edges in G. Hence, it is a problem of key importance to find new realistic assumptions to shrink the equivalence class.

There have been a wealth of approaches to alleviate this problem. For instance, some have made progress by including data collected under intervention (Hauser and Bühlmann, 2012), making assumptions about the functional form of causal relationships (Peters et al., 2014; Shimizu et al., 2006)) or including background knowledge on the direction of edges Meek (1995). In this work, we propose an alternative approach, based on background knowledge, where types are attributed to variables and the interaction between types is constrained.

3. Related works

The inclusion of background knowledge in causal discovery aims to reduce the size of the solution space by adding or ruling out causal relationships based on expert knowledge. Several forms of background knowledge have been proposed, which place various levels of burden on the expert. Below, we review those most relevant to our work (see Constantinou et al. (2021) for a review).

Hard background knowledge. This type of background knowledge is "hard" in the sense that it *must be respected* in the inferred graph structures. Previous works have considered: sets of forbidden and known edges (Meek, 1995), a known ordering of the variables (Cooper and Herskovits, 1992), partial orderings of the variables (Andrews, 2020; Scheines et al., 1998), and ancestral constraints (Li and Beek, 2018; Chen et al., 2016). Among these, partial orderings (or *tiered background knowledge*) are the most similar to our contribution. In this setting, it is assumed that an expert partitions the variables into sets called *tiers*, and orders the tiers such that variables in a later tier cannot cause variables in an earlier tier. In contrast, while we require the expert to partition variables into sets (by type), we do not assume that an ordering is known *a priori*.

Soft background knowledge. A setting similar to ours, where the type of each variable dictates its possible causal relationships, was presented in Mansinghka et al. (2012). They proposed a Bayesian method to use this prior knowledge in causal discovery. Their work showed the benefits of such priors, but did not investigate this space of graphs and their properties w.r.t. to structure identifiability.

---

2. For our terminology related to graphs, we refer the reader to the Appendix A of Andersson et al. (1997).

a) t-edge orientations   b) Consistent t-DAG   c) Inconsistent t-DAG

Figure 1: **(a)** Representation of t-edges orientations, where colors represent the different types a, b, and c. **(b)** Representation of a t-DAG that is consistent and follows the orientation of the t-edges in (a). **(c)** Representation of a t-DAG that is not consistent: the red edge $c_2 \to b_1$ is not consistent with $b_1 \to c_1$ (Definition 3).

Grouping variables. Parviainen and Kaski (2017) explored a setting similar to ours, where variables representing different "views" on the same entity are aggregated into groups. They addressed the problem of learning causal relationships between groups of variables, which they represented as *group DAGs*. Our work is conceptually different. First, variables of a given type could correspond to different entities that are similar, rather than multiple views on a common entity. Second, our focus is different: their goal is to recover a group DAG, while our goal is to make assumptions that facilitate the identification of the causal graph in the variable space. Note, however, that their *strong group causality* assumption leads to graphs that are a subset of the consistent t-DAGs that we will present.

Interestingly, several recent works applying causal discovery to real-world problems have used expert knowledge that is compatible with our proposed framework. For example, in their work on Alzheimer's disease, Shen et al. (2020) claim that "edges from biomarkers or diagnosis to demographic variables are prohibited" and that "edges among demographic variables are prohibited", clearly reasoning about relationships between types of variables. Similarly, the work of Flores et al. (2011) outlines an application of tiered background knowledge in a medical case study. Converting this setting to ours simply involves considering each tier as a variable type. As such, the typing assumptions that we propose in this work, and the associated theoretical results, constitute a way of incorporating expert knowledge that is applicable in practice.

4. Typed directed acyclic graphs

Our work builds on two fundamental structures: *typed* directed acyclic graphs (t-DAG), which are essentially DAGs with typed vertices; and *t-edges*, which are sets of edges relating vertices of given types. Formal definitions follow.

Definition 1 (t-DAG) *A* t-DAG D_T*, with k types, is a DAG $D := (V, E)$ augmented with a mapping $T : V \to \mathcal{T}$ such that the type of $v_i \in V$ is $T(v_i) = t_j \in \mathcal{T}$, where $|\mathcal{T}| = k$.*

4

Definition 2 (t-edge) *A t-edge $E(t_i, t_j)$ is the set of edges that goes from a node of type t_i to a node of type t_j. More formally, $E(t_i, t_j) = \{(v_k, v_l) \in E \mid T(v_k) = t_i, T(v_l) = t_j\}$ for any pair of types $t_i, t_j \in \mathcal{T}$.*

For example, the graphs illustrated in Fig. 1 (b) and (c) are t-DAGs where colors represent types and the set $E(a, c) = \{(a_1, c_1), (a_1, c_2)\}$ is a t-edge between types a and c.

4.1. Assumptions on type interactions

We now introduce a new assumption: *type consistency*, which constrains the possible causal relationships that may arise between typed variables. Put simply, this assumption states that causal relationships between two types of variables can only arise in one common direction.

Definition 3 (Consistent t-DAG) *A consistent t-DAG is a t-DAG where, for every pair of distinct types t_i, t_j, if t-edge $E(t_i, t_j) \neq \emptyset$ then we have that $E(t_j, t_i) = \emptyset$. We refer to this structural constraint as type consistency. For conciseness, $t_i \xrightarrow{t} t_j$ denotes $E(t_i, t_j) \neq \emptyset$.*

In Fig. 1 (b), we present an example of a consistent t-DAG. In contrast, the t-DAG shown in Fig. 1 (c) is not consistent: the t-edge $E(c, b)$ (purple to white) contains the edge (c_2, b_1), while the reverse t-edge, $E(b, c)$, is not empty since it contains (b_1, c_1). Notice how, the orientation of all t-edges (Fig. 1 (a)), fully determines the orientation of edges between variables of distinct types in a consistent t-DAG.

Note that alternative assumptions could have been considered. For instance, we could have assumed that t-edges form a DAG (i.e., the types have a partial ordering). However, the assumptions considered here are less restrictive and, as we demonstrate later, lead to interesting results.

4.2. Equivalence classes for consistent t-DAGs

We define the equivalence classes MEC and t-MEC as the set of DAGs and the set of consistent t-DAGs that are Markov equivalent, respectively.

Definition 4 (MEC) *The MEC of a t-DAG D_T is $M(D_T) := \{D' \mid D' \sim D_T\}$ where "$\sim$" denotes Markov equivalence.*

Definition 5 (t-MEC) *The t-MEC of a consistent t-DAG D_T is $M_T(D_T) := \{D'_T \mid D'_T \overset{t}{\sim} D_T\}$ where "$\overset{t}{\sim}$" denotes Markov equivalence limited to consistent t-DAGs with the same type mapping as D_T.*

To represent an equivalence class, we can use an *essential graph*, which corresponds to the union of equivalent DAGs. The union over graphs is defined as the union of their vertices and edges: $G_1 \cup G_2 := (V_1 \cup V_2, E_1 \cup E_2)$. Also, if $(v_i, v_j), (v_j, v_i) \in E_1 \cup E_2$, then the edge is considered to be undirected.

Definition 6 (Essential graph) *The essential graph D^* associated to the consistent t-DAG D_T is:*

$$D^* := \bigcup_{D \in M(D_T)} D.$$

Figure 2: **(a)** The two-type fork structure. In this illustration, a_1 and a_2 are of one type (purple) and b_1 is of another type (orange). **(b)** Orientation rule: if this structure is encountered in an essential graph, it must be oriented in the t-essential graph.

Definition 7 (t-Essential graph) *The t-essential graph D_T^* associated to the consistent t-DAG D_T is*

$$D_T^* := \bigcup_{D \in M_T(D_T)} D.$$

4.3. t-Essential graph properties and size of t-MEC

We consider some statements that can directly be made about t-essential graphs and the size of t-MEC with respect to their non-typed counterparts. Proofs for the propositions can be found in Appendix A. First note that for t-DAGs with k types and d vertices, in the limit cases where each variable belongs to its own type ($k = d$) or all variables belong to a single type ($k = 1$), type consistency does not impose structural constraints on t-DAGs, i.e., any t-DAG is type-consistent and the t-essential graph is identical to the essential graph.

However, in general, the t-essential graph is a version of the essential graph with more oriented edges, thanks to the type consistency assumption:

Proposition 8 *Let D_T^* and D^* be, respectively, the t-essential and essential graphs of an arbitrary consistent t-DAG D_T. Then, $D_T \subseteq D_T^* \subseteq D^*$.*

Indeed, type consistency synchronizes the orientation of some edges, resulting in a reduced set of possible orientations. Some structural properties of the graph may also force the orientation of edges in the t-essential graph. Akin to immoralities in essential graphs, *two-type forks* (see Fig. 2) must be oriented in t-essential graphs.

Proposition 9 *If a consistent t-DAG D_T contains vertices a_1, a_2, b_1 with types $T(a_1) = T(a_2) = a$ and $T(b_1) = b$ ($a \neq b$), with edges $a_1 \leftarrow b_1 \rightarrow a_2$ (a_1, a_2 not adjacent), then the t-edge $b \xrightarrow{t} a$ is directed in the t-essential graph, i.e., the direction of causation between types b and a is known.*

To see this, note that, under type consistency, there are only two possible orientations: $a_1 \rightarrow b_1 \leftarrow a_2$ and $a_1 \leftarrow b_1 \rightarrow a_2$. The first is an immorality and, thus, must be oriented in the essential graph. If it is not, there is only one possible alternate orientation. Therefore, such edges are always oriented in the t-essential graph.

Furthermore, we can upper bound the size of the t-MEC based on the number of undirected edges in the t-essential graph, as stated in the following proposition.

Proposition 10 (Upper bound on the size of the t-MEC) *For any consistent t-DAG D_t, we have $|M_T(D_T)| \leq 2^u \prod_{t_i \in \mathcal{T}} 2^{u_{t_i}}$, where u and u_{t_i} are respectively the number of undirected t-edges and the number of undirected edges between variables of type t_i (intra-type edges) in the t-essential graph of D_t.*

From this bound, we can also directly conclude that if the t-essential graph contains no undirected edges, then $|M_T(D_T)| = 1$. In other words, D_T is identified.

5. Identification for random graphs

In this section, we explore the benefits of variable typing in causal graph identification through the study of a class of graphs generated at random based on a process inspired by the Erdős-Rényi random graphs model (Erdős and Rényi, 1959).

Assume we are given a set of k types $t_1, \ldots, t_k$, probabilities $p_1, \ldots, p_k \in (0,1)^k$ of observing each type s.t. $\sum p_i = 1$, and a *type interaction matrix* $A \in [0,1]^{k \times k}$ where each cell (i,j) is the probability p_{ij} that a variable of type t_i is a direct cause of a variable of type t_j. As per Definition 3 (type consistency), we impose that, $\forall i \neq j$, if $p_{ij} > 0$, then $p_{ji} = 0$.

Definition 11 (Random sequence of growing t-DAG) *We define a random sequence of t-DAGs $(D_{T^n}^n)_{n=0}^\infty$ with $D_{T^n}^n = (V^n, E^n)$ and $|V^n| = n$, such that $D_{T^0}^0 = (\emptyset, \emptyset)$. Each new t-DAG $D_{T^n}^n$ in the sequence is obtained from $D_{T^{n-1}}^{n-1}$ as follows: Create a new vertex v_n and sample its type t from a categorical distribution with probabilities $p_1, ..., p_k$. Let $V^n = V^{n-1} \bigcup \{v_n\}$; Let $T^n(v_n) = t$ and $T^n(v_j) = T^{n-1}(v_j), \forall v_j \in V^{n-1}$; To obtain E^n, for every vertex $v_i \in V^{n-1}$, add the edge (v_i, v_n) to E^{n-1} with probability $p_{T(v_i), T(v_n)}$.*

Our main theorem below states that, as we add more vertices to such a growing sequence of random t-DAGs, we eventually discover the orientation of all t-edges. We defer the proof to Appendix B.1.

Theorem 12 *Let $(D_{T^n}^n)_{n=0}^\infty$ be a random sequence of growing t-DAGs as defined in Definition 11, let U be the number of unoriented t-edges, and let $r_{ij} = -\frac{1}{3} \max \left[\ln(1 - p_i), \ln \left(1 - p_j p_{ij}(1 - p_{jj}) \right) \right]$. For $n \geq 3$, $p_i, p_j \in (0,1)$, and $p_{ij}, p_{jj} \in [0,1]$, we have:*

$$P(U > 0) \leq 4 \sum_{i,j \, : \, i \neq j, p_{ij} > 0} e^{-r_{ij} n}.$$

To give an intuition of the proof, recall Proposition 9, which tells us that any two-type fork structure must be oriented in the t-essential graph, thereby orienting the associated t-edge. We thus argue that, as we add more vertices, the probability of observing a two-type fork for arbitrary type pairs converges to 1. This argument relies on the fact that the number k of types remains constant throughout as the random t-DAG grows.

From Theorem 12 we can derive a result for the case where variables of the same type do not interact ($p_{ii} = 0, \forall i$). In this case, the t-MEC collapses to a singleton as the graph grows, resulting in identification of the true t-DAG.

Corollary 13 *Let $(D_{T^n}^n)_{n=0}^\infty$ be a random sequence of growing t-DAGs as defined in Definition [11] and let $r_{ij} = -\frac{1}{3}\max\left[\ln(1-p_i), \ln\left(1 - p_j p_{ij}\right)\right]$. For $n \geq 3$, $p_i, p_j \in (0,1)$, and $p_{ij} \in [0,1]$, then the size of the t-MEC converges to 1 exponentially fast:*

$$P(|M_T(D_{T^n}^n)| > 1) \leq 4 \sum_{i,j \,:\, i\neq j, p_{ij} > 0} e^{-r_{ij}n}.$$

5.1. Empirical validation

We conduct an empirical study to validate these theoretical results and further compare the size of the MEC and t-MEC for the case where $p_{ii} > 0$. As such, we consider t-DAGs of various sizes, randomly generated according to the process described in Definition [11]. Let k be the number of types in the t-DAG. We attribute uniform probability to each type, i.e., $p_i = 1/k$, $\forall i \in \{1, ..., k\}$. The type interaction matrix A is defined as follows. For each pair of types (t_i, t_j), s.t., $i \neq j$, the direction of the t-edge is sampled randomly with uniform probability and we use a fixed probability of interaction p_{inter}. For example, if the direction $t_i \xrightarrow{t} t_j$ is sampled, then $A_{ij} = p_{\text{inter}}$ and $A_{ji} = 0$. Furthermore, for each type t_i, we attribute a fixed probability p_{intra} for the occurrence of edges between variables of type t_i.

Fig. [3] shows results for t-DAGs with $n = \{10..100\}$ vertices, $k = 10$ types, $p_{\text{inter}} = 0.2$, and various values for p_{intra} (see Appendix [B.2] for additional results). In Fig. [3(a)], we clearly see that as, the number of vertices grows, the number of unoriented t-edges tends to zero irrespective of the value of p_{intra}, supporting the statement of Theorem [12]. Furthermore, Fig. [3(b)] clearly shows that for the case where $p_{\text{intra}} = 0$, the size of the t-MEC tends to 1 (identification) as the number of vertices grows, supporting the statement of Corollary [13]. In sharp contrast, the size of the MEC grows with the number of vertices. Finally, Fig. [3(c)] shows that the size of the t-MEC can be much smaller than that of the MEC, even when the t-DAG contains intra-type edges ($p_{\text{intra}} > 0$).

This last result is particularly interesting since it holds even when the t-DAGs are dominated by intra-type edges (e.g., $p_{\text{intra}} = 0.5$), which are not part of oriented t-edges. It remains an open question to formally quantify the size of the t-MEC vs. the MEC when the graphs contain intra-type edges. The results in Fig. [3(c)] suggests that their ratio may be bounded by a quantity that depends on p_{intra}.

6. Causal discovery algorithms for t-essential graphs

Causal discovery algorithms, such as the PC algorithm (Spirtes et al., 2000), are typically consistent w.r.t. the MEC. That is, given infinite samples from the observational distribution entailed by a causal graph, they are guaranteed to recover its essential graph. Given that the t-MEC is often a small subset of the MEC, it is desirable to find algorithms that can consistently recover t-essential graphs. In this section, we present such algorithms.

6.1. From essential to t-essential graph

Given an essential graph, one can recover the t-essential graph by enumerating all t-DAGs that are consistent and taking their union. We propose a slightly more efficient approach that propagates t-edge orientations using the Meek (1995) orientation rules:

Figure 3: (a) Number of unoriented t-edges w.r.t. the number of vertices (b) Size of the MEC and the t-MEC w.r.t. the number of vertices when $p_{\text{intra}} = 0$ (c) Ratio of the size of t-MEC and the size of MEC w.r.t. the number of vertices.

Algorithm 1: t-Propagation(G, T)

1. Enforce type consistency: If there exists an oriented edge between any pair of variables with types $t_1, t_2 \in \mathcal{T}$ in G, assume $t_1 \xrightarrow{t} t_2$ and orient all edges between these types.

2. Apply the Meek (1995) orientation rules R1-R4 (see their Section 2.1.2) to propagate the edge orientations derived in Step (1).

3. Repeat from Step (1) until the graph is unchanged.

4. Enumerate all t-DAGs that can be produced by orienting edges in the resulting graph. Reject any inconsistent t-DAGs and take the union of all remaining t-DAGs to obtain the t-essential graph (see Definition 7).

If G is a graph with the same skeleton, immoralities, and type mapping T as the t-essential graph D_T^*, then Algorithm 1 is guaranteed to recover the corresponding t-essential graph $M_T(D_T)$ (see Appendix C.1). Thus, Algorithm 1 can be used in conjunction with any MEC-consistent causal discovery algorithm to obtain one that is t-MEC-consistent. However, one major caveat is that, for finite sample sizes, the output of the MEC-consistent algorithm may violate type consistency and cause an irrecuperable failure of t-Propagation (impossibility of orienting t-edges consistently).

Another limitation of this algorithm is its non-polynomial time complexity due to the enumeration in Step (4). Without it, the algorithm would be *sound*, i.e., it would not orient edges that are unoriented in the t-essential graph, but not *complete*, i.e. some edges that should be oriented in the t-essential graph would remain unoriented. To see this, consider the *two-type fork* illustrated in Fig. 2(a). The essential graph for this t-DAG would be completely undirected since it contains no immoralities. This would result in a case where none of the Meek (1995) rules are applicable and thus, Step (2) would not orient any edges. The algorithm would therefore stop and return a fully undirected graph. However, according to Proposition 9, the two-type fork should have been oriented.

Nevertheless, even with an additional rule to orient such structures in Step (2) (as illustrated in Fig. 2(b)), the algorithm would not be complete without Step (4). In Appendix C.1.2, we show more complex counterexamples (non-local and involving multiple t-edges). It thus remains an open question whether it is possible to design a polynomial-time algorithm to find the t-essential graph, as Meek (1995) and Andersson et al. (1997) did for essential graphs. Note, however, that the non-polynomial time complexity was found to be non-prohibitive in our experiments.

6.2. Typed variants of the PC algorithm

The previous algorithm suffices to achieve consistency w.r.t. the t-MEC, but it may fail to produce type-consistent outputs when used with finite sample sizes. Here, we show that it is possible to modify the PC algorithm (Spirtes et al., 2000) to obtain a t-MEC-consistent algorithm that always produces type-consistent outputs.

Recall how the PC algorithm works; it proceeds in three phases: 1) infer the graph's skeleton using conditional independence tests[3], 2) orient all immoralities in the skeleton, 3) apply the Meek (1995) rules to orient as many edges as possible given the edges oriented in Phase (2). To ensure type-consistent outputs, it suffices to modify Phases (2) and (3) to ensure that, when applicable, we orient whole t-edges instead of single edges.

For Phase (3), the modification is simple: replace the usual procedure by t-Propagation (Algorithm 1). For Phase (2), one must deal with errors that may arise when applying conditional independence tests to samples of finite size. Indeed, it is possible to observe edges from the same t-edge involved in both immoralities and two-type forks (see Fig. 2), suggesting multiple orientations when only one is possible. We consider two simple strategies for dealing with such ambiguities that we outline below. They lead to two *Typed-PC (TPC)* algorithms that are both t-MEC-consistent, but differ in their empirical performance, as we show in Section 7. Pseudo-codes and proofs of consistency are given in Appendix C.2.

- **TPC-naive**: Use the first encountered structure (immorality or two-type fork) to orient each t-edge. Naturally, this naive strategy is error-prone.

- **TPC-majority:** We know that only one orientation is possible for t-edges. Hence, look at each structure that would trigger an orientation (immoralities and two-type forks) and choose the orientation based on the most frequent type of structure.

7. Experiments

We conduct causal structure learning experiments[4] to compare the performance of our proposed t-MEC-consistent algorithms with that of a baseline which does not make use of variable types. The t-MEC-consistent algorithms are: TPC-naive and TPC-majority (Section 6.2) and PC (Spirtes et al., 2000) augmented with t-Propagation (Section 6.1). The baseline is the classical PC algorithm. The methods are compared in terms of Structural Hamming Distance (SHD) between their output and the ground-truth t-essential graph (see Appendix D.2 for details). We base the comparison on synthetic and pseudo-real datasets.

---

3. The conditional independence test must be chosen based on the nature of the data. We use the FCIT (Chalupka et al., 2018), since it is non-parametric and applies to both continuous and discrete data.

4. Implementations of the algorithms and code for the experiments are available at censored.

Figure 4: Results on simulated data shown as improvement in SHD w.r.t. the PC baseline (lower is better). The title of each subplot indicates the $(p_{\text{inter}}, p_{\text{intra}})$ configuration.

Figure 5: Results on pseudo-real data shown as improvement in SHD w.r.t. the PC baseline (lower is better). The title of each subplot indicates the underlying network.

Synthetic data. We consider graphs randomly generated according to Section 5.1 with 20 nodes and 5 types. The probabilities of connection p_{inter} and p_{intra} vary in $\{(0.2, 0), (0.4, 0), (0.3, 0.1), (0.2, 0.2)\}$ (see Appendix D.3 for more configurations), where the data set $(0.2, 0)$ is sparse and the three others have a similar density while the density of intra-type edges vary. For each type of graph, we explore multiple parametric forms for the causal relationships: linear, nonlinear additive noise model (ANM) (Bühlmann et al., 2014) and nonlinear non-additive model using neural networks (NN) (Kalainathan et al., 2018). Finally, for each type of graph and parametric form, we generate 50 different consistent t-DAGs and draw 10k samples from their observational distribution.

Pseudo-real data. We consider the following Bayesian networks from the Bayesian Network Repository (number of variables in parentheses): `sachs` (11), `child` (20), `insurance` (27), `alarm` (37), `hailfinder` (56), `win95pts` (76). For each network, the conditional probabilities are fitted to real-world data sets, enabling the generation of pseudo-real data. To assign types to variables, we randomly partition their topological ordering into groups of expected size 5 (see Appendix D.1.2). We consider 50 random type assignments and for each, we sample 50k observations from the Bayesian network.

Results. The results reported in Figures 4 and 5 show the improvement in SHD w.r.t. PC. As expected, all t-MEC-consistent algorithms generally outperform this type-agnostic

baseline, achieving lower SHD w.r.t. the t-essential graph. The PC + t-Propagation method sometimes underperforms compared to the TPC algorithms, mainly because it fails to produce a type-consistent output[5] (49% of the time). Finally, as expected, TPC-majority tends to yield better or equal performance compared to TPC-naive, since it is less vulnerable to errors in t-edge orientations that may arise at Phase (2) of the algorithm (see Section 6.2).

8. Discussion

In this work, we addressed an important problem in causal discovery: it is often impossible to identify the causal graph precisely, due to the size of its Markov equivalence class. This is particularly true for sparse graphs, where the size of the MEC grows super-exponentially with the number of vertices (He et al., 2015). Our theoretical and empirical results clearly demonstrate that there exist conditions in which our variable-typing assumptions greatly shrink the size of the equivalence class. Hence, when such assumptions hold in the data, gains in identification are to be expected. We also proposed methods to recover the t-essential graph from data and, using several synthetic and pseudo-real data sets, showed that they perform better than their type-agnostic counterparts.

We note that the new assumptions that we introduce can be used in conjunction with other strategies to shrink the size of the equivalence class, such as considering interventions (Hauser and Bühlmann, 2012), hard background knowledge on the presence/absence of edges (Meek, 1995), or functional-form assumptions (Peters et al., 2014; Shimizu et al., 2006).

We believe that this work may stimulate new advances at the intersection of machine learning and causality (Schölkopf et al., 2021; Schölkopf, 2019). In fact, machine learning algorithms excel at classification, and thus it may be interesting to explore a setting where the variable types are learned based on some features. Type assignments could be learned in parallel with causal discovery using recent methods for differentiable causal discovery (Brouillard et al., 2020; Zheng et al., 2018). This may further reduce the burden on the human expert in cases where types are hard to assign. As an example, consider the task of learning causal models of gene regulatory networks. One could train a model to assign types to genes based on their categorization in the gene ontology (Gene Ontology Consortium, 2004) or on features of their DNA sequence.

Additionally, an interesting future direction would be to use our typing assumptions to perform causal discovery on multiple graphs at once, i.e., *multi-task causal discovery*. In fact, assume that we are given data for multiple groups of variables that correspond to disjoint systems (no interactions across groups), but that share similar types. It would be possible to use type consistency (Definition 3) to propagate t-edge orientations across graphs.

In conclusion, our type consistency assumption can result in significant gains in identification that can readily be leveraged by modified versions of common causal discovery algorithms. We believe that assumptions based on types are truly important since, in addition to facilitating causal discovery, they are likely to be a key component of causal reasoning in intelligent agents.

---

5. In this case, it simply returns the output of PC.

References

1000 Genomes Project Consortium (1KGP) and others. A map of human genome variation from population-scale sequencing. *Nature*, 467(7319):1061, 2010.

Steen A Andersson, David Madigan, Michael D Perlman, et al. A characterization of markov equivalence classes for acyclic digraphs. *Annals of statistics*, 25(2):505–541, 1997.

Bryan Andrews. On the completeness of causal discovery in the presence of latent confounding with tiered background knowledge. In *The 23rd International Conference on Artificial Intelligence and Statistics*, volume 108 of *Proceedings of Machine Learning Research*, pages 4002–4011. PMLR, 2020.

Philippe Brouillard, Sébastien Lachapelle, Alexandre Lacoste, Simon Lacoste-Julien, and Alexandre Drouin. Differentiable causal discovery from interventional data. In *Advances in Neural Information Processing Systems 33*, 2020.

Peter Bühlmann, Jonas Peters, and Jan Ernest. Cam: Causal additive models, high-dimensional order search and penalized regression. *The Annals of Statistics*, 42(6): 2526–2556, 2014.

Krzysztof Chalupka, Pietro Perona, and Frederick Eberhardt. Fast conditional independence test for vector variables with large sample sizes. *arXiv preprint arXiv:1804.02747*, 2018.

Eunice Yuh-Jie Chen, Yujia Shen, Arthur Choi, and Adnan Darwiche. Learning bayesian networks with ancestral constraints. In *Advances in Neural Information Processing Systems 29*, pages 2325–2333, 2016.

Anthony C Constantinou, Zhigao Guo, and Neville K Kitson. Information fusion between knowledge and data in bayesian network structure learning. *arXiv preprint arXiv:2102.00473*, 2021.

Gregory F Cooper and Edward Herskovits. A bayesian method for the induction of probabilistic networks from data. *Machine learning*, 9(4):309–347, 1992.

Pim de Haan, Dinesh Jayaraman, and Sergey Levine. Causal confusion in imitation learning. In *Advances in Neural Information Processing Systems 32*, pages 11693–11704, 2019.

Paul Erdős and Alfred Rényi. On random graphs. *Publicationes Mathematicae Debrecen*, 6: 290–297, 1959.

M Julia Flores, Ann E Nicholson, Andrew Brunskill, Kevin B Korb, and Steven Mascaro. Incorporating expert knowledge when learning bayesian network structure: a medical case study. *Artificial intelligence in medicine*, 53(3):181–204, 2011.

Gene Ontology Consortium. The gene ontology (go) database and informatics resource. *Nucleic acids research*, 32(suppl_1):D258–D261, 2004.

Alison Gopnik and David M Sobel. Detecting blickets: How young children use information about novel causal powers in categorization and induction. *Child development*, 71(5): 1205–1222, 2000.

Thomas L Griffiths, David M Sobel, Joshua B Tenenbaum, and Alison Gopnik. Bayes and blickets: Effects of knowledge on causal induction in children and adults. *Cognitive Science*, 35(8):1407–1455, 2011.

Alain Hauser and Peter Bühlmann. Characterization and greedy learning of interventional markov equivalence classes of directed acyclic graphs. *The Journal of Machine Learning Research*, 13(1):2409–2464, 2012.

Yangbo He and Bin Yu. Formulas for counting the sizes of markov equivalence classes of directed acyclic graphs. *arXiv preprint arXiv:1610.07921*, 2016.

Yangbo He, Jinzhu Jia, and Bin Yu. Counting and exploring sizes of markov equivalence classes of directed acyclic graphs. *The Journal of Machine Learning Research*, 16(1): 2589–2609, 2015.

Christina Heinze-Deml, Marloes H Maathuis, and Nicolai Meinshausen. Causal structure learning. *Annual Review of Statistics and Its Application*, 5:371–391, 2018.

Diviyan Kalainathan, Olivier Goudet, Isabelle Guyon, David Lopez-Paz, and Michèle Sebag. Sam: Structural agnostic model, causal discovery and penalized adversarial learning. *arXiv preprint arXiv:1803.04929*, 2018.

Charles Kemp, Noah D Goodman, and Joshua B Tenenbaum. Learning to learn causal models. *Cognitive Science*, 34(7):1185–1243, 2010.

Andrew Li and Peter Beek. Bayesian network structure learning with side constraints. In *International Conference on Probabilistic Graphical Models*, pages 225–236. PMLR, 2018.

Vikash Mansinghka, Charles Kemp, Thomas Griffiths, and Joshua Tenenbaum. Structured priors for structure learning. *arXiv preprint arXiv:1206.6852*, 2012.

Christopher Meek. Causal inference and causal explanation with background knowledge. *arXiv preprint arXiv:1302.4972*, 1995.

Pekka Parviainen and Samuel Kaski. Learning structures of bayesian networks for variable groups. *International Journal of Approximate Reasoning*, 88:110–127, 2017.

Judea Pearl. Causal diagrams for empirical research. *Biometrika*, 82(4):669–688, 1995.

Jonas Peters, Joris M Mooij, Dominik Janzing, and Bernhard Schölkopf. Causal discovery with continuous additive noise models. *The Journal of Machine Learning Research*, 15(1): 2009–2053, 2014.

Jonas Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of causal inference: foundations and learning algorithms*. The MIT Press, 2017.

Jakob Runge, Sebastian Bathiany, Erik Bollt, Gustau Camps-Valls, Dim Coumou, Ethan Deyle, Clark Glymour, Marlene Kretschmer, Miguel D Mahecha, Jordi Muñoz-Marí, et al. Inferring causation from time series in earth system sciences. *Nature communications*, 10 (1):1–13, 2019.

Richard Scheines, Peter Spirtes, Clark Glymour, Christopher Meek, and Thomas Richardson. The tetrad project: Constraint based aids to causal model specification. *Multivariate Behavioral Research*, 33(1):65–117, 1998.

Bernhard Schölkopf. Causality for machine learning. *arXiv preprint arXiv:1911.10500*, 2019.

Bernhard Schölkopf, Francesco Locatello, Stefan Bauer, Nan Rosemary Ke, Nal Kalchbrenner, Anirudh Goyal, and Yoshua Bengio. Toward causal representation learning. *Proceedings of the IEEE*, 109(5):612–634, 2021.

Laura E Schulz and Alison Gopnik. Causal learning across domains. *Developmental psychology*, 40(2):162, 2004.

Xinpeng Shen, Sisi Ma, Prashanthi Vemuri, and Gyorgy Simon. Challenges and opportunities with causal discovery algorithms: application to alzheimer's pathophysiology. *Scientific reports*, 10(1):1–12, 2020.

Shohei Shimizu, Patrik O Hoyer, Aapo Hyvärinen, and Antti Kerminen. A linear non-gaussian acyclic model for causal discovery. *Journal of Machine Learning Research*, 7 (Oct):2003–2030, 2006.

Peter Spirtes, Clark N Glymour, Richard Scheines, and David Heckerman. *Causation, prediction, and search*. MIT press, 2000.

Ioannis Tsamardinos, Laura E Brown, and Constantin F Aliferis. The max-min hill-climbing bayesian network structure learning algorithm. *Machine learning*, 65(1):31–78, 2006.

Tom S Verma and Judea Pearl. On the equivalence of causal models. *arXiv preprint arXiv:1304.1108*, 1990.

Xun Zheng, Bryon Aragam, Pradeep Ravikumar, and Eric P. Xing. Dags with NO TEARS: continuous optimization for structure learning. In *Advances in Neural Information Processing Systems 31*, pages 9492–9503, 2018.