Fluent but Fabricated: Human-Validated Benchmark for Evaluating Cultural Hallucinations in Low-Resource Indic Languages

Abstract

Large language models (LLMs) are increasingly used in multilingual and multicultural settings, yet existing hallucination benchmarks remain largely centred on English and high-resource cultural knowledge. We introduce a human-validated cross-cultural benchmark for evaluating cultural hallucination in Gujarati and Tamil contexts across three query languages: English, the local cultural language, and Hindi, used as an anchor language to compare cultural knowledge access across languages. We define cultural hallucination as incorrect or unsupported generation about culturally specific knowledge, including foods, festivals, geography, history, and culturally grounded entities. Our benchmark combines two complementary tasks: `IndicWikiQA`, consisting of short, Wikipedia-grounded factual questions, and `IndicNonExi`, consisting of fabricated cultural entities for evaluating whether models refuse when no valid answer exists. Across eight state-of-the-art LLMs, we find that multilingual factual accuracy does not guarantee cultural reliability: models that answer real cultural questions correctly often still generate fluent answers for nonexistent cultural entities. These results show that evaluating cultural hallucination requires testing both knowledge access and calibrated refusal across languages.

1 Introduction

Large Language Models (LLMs) are increasingly used as general-purpose assistants for answering questions about history, culture, local practices, and everyday life. However, prior work has shown that LLMs can generate fluent responses that are factually incorrect, unsupported, or not grounded in verifiable evidence (Lin et al., 2022; Li et al., 2023; Ji et al., 2023; Wang et al., 2024; Zhang et al., 2025b; Bang et al., 2025). This risk is especially important in multilingual and multicultural settings, where users may rely on LLMs as sources of cultural knowledge. In such contexts, hallucinations can misrepresent traditions, flatten regional specificity, and reinforce uneven representations of underrepresented communities.

Existing hallucination and factuality benchmarks capture important aspects of model reliability, but they remain largely centred on English and high-resource knowledge settings. Benchmarks such as TruthfulQA (Lin et al., 2022), HaluEval (Li et al., 2023), and recent hallucination surveys (Ji et al., 2023; Wang et al., 2024; Zhang et al., 2025b) show the difficulty of separating factual error, unsupported generation, and model overconfidence. More recent work such as HalluLens (Bang et al., 2025) further distinguishes intrinsic hallucination, where a model contradicts provided input, from extrinsic hallucination, where a model generates content unsupported by external knowledge. However, LLM behaviour on culturally grounded knowledge remains underexplored, especially for underrepresented cultural contexts.

In this work, we define *cultural hallucination* as a reliability failure in which a model produces incorrect or unsupported content about culturally specific knowledge, including traditions, practices, foods, festivals, geography, history, and culturally grounded entities. Such errors may involve misrepresenting cultural entities, confusing related cultural concepts, assigning facts to nonexistent entities, or mixing information across cultural contexts. Importantly, cultural reliability[1] cannot be evaluated through factual accuracy alone: a model may correctly answer many real cultural questions while still confidently generating answers for fabricated cultural entities.

To address this gap, we introduce a human-validated benchmark for evaluating cultural hal-

---

[1]We define *cultural reliability* as a model's ability to answer culturally grounded questions correctly when a valid answer exists and to refuse or abstain when no verifiable cultural answer exists.

Figure 1: Overview of the proposed cultural hallucination benchmark. Culturally grounded questions are constructed for Gujarati and Tamil contexts and evaluated across multiple query languages. Model responses are then assessed for factual correctness and recurring cultural hallucination patterns.

lucination in multilingual LLMs across two Indic cultural contexts: Gujarati and Tamil, as illustrated in Figure 1.[2] Each cultural context is evaluated across three query languages: English, the local cultural language, and Hindi.[3] This parallel design allows us to examine whether models can access and express the same cultural knowledge consistently across languages.

We evaluate eight state-of-the-art LLMs on Gujarati and Tamil cultural questions across all three language conditions. Our results show that multilingual factual accuracy does not guarantee cultural reliability. Several models that perform well on answerable cultural questions still produce fluent responses to nonexistent cultural entities, indicating poor refusal calibration. We also find that model behaviour varies across query languages, suggesting that cultural hallucination is shaped not only by whether a model encodes a fact, but also by whether it can access and express that knowledge under different language conditions.

Our contributions are threefold:

1. **Human-validated multilingual benchmark:** We introduce a human-validated benchmark

for evaluating cultural hallucination in Gujarati and Tamil contexts across three query languages: English, the local cultural language, and Hindi.

2. **Two-part evaluation design:** We combine factual QA with refusal-based evaluation through two complementary datasets: IndicWikiQA, which contains Wikipedia-grounded cultural questions, and IndicNonExi, which contains culturally realistic but nonexistent entities designed to test whether models refuse when no valid answer exists.

3. **Evaluation of cultural reliability across LLMs:** We evaluate eight state-of-the-art LLMs and show that high factual accuracy does not necessarily imply cultural reliability, since many models still generate fluent answers for nonexistent cultural entities.

2 Dataset Construction

We construct multilingual benchmarks for evaluating cultural hallucination in Gujarati and Tamil contexts. Following the extrinsic hallucination setting of Bang et al. (2025), correctness is evaluated against verifiable external knowledge that is expected to be represented in model pretraining data. This design helps distinguish model failures in retrieval, representation, or expression from cases where source knowledge is unavailable.

Our benchmark contains two complementary datasets. IndicWikiQA consists of short, factual,

---

[2]Gujarati and Tamil provide strong test cases because they are culturally rich Indic contexts with substantial speaker communities, yet remain comparatively underrepresented in many NLP benchmarks. Gujarati has approximately 55.5 million native speakers and Tamil approximately 69.0 million native speakers (Office of the Registrar General & Census Commissioner, India, 2018).

[3]We test the same Gujarati and Tamil cultural content in English, the local language, and Hindi. This allows us to examine how query language affects model behaviour while keeping the underlying cultural content fixed.

Dataset	Food	History	Geography	Festivals
IndicWikiQA-Gujarati	41	26	132	51
IndicWikiQA-Tamil	33	18	119	52

Table 1: Domain distribution of IndicWikiQA datasets.

and unambiguous questions grounded in Wikipedia articles about Gujarati or Tamil culture. Each item has a single short gold answer and is answerable from one source article without external knowledge or multi-hop reasoning. IndicNonExi consists of questions about fabricated cultural entities, where the correct model behaviour is to refuse rather than generate an answer.

A central feature of our construction process is human validation. LLMs are used only to generate candidate items; all final examples are manually verified before inclusion. Each item is reviewed by two annotators familiar with the relevant language and cultural context, followed by adjudication to resolve disagreements. For IndicWikiQA, annotators verify source support, answer uniqueness, cultural specificity, and the absence of ambiguity or multi-hop reasoning. For IndicNonExi, annotators verify that each fabricated entity has no verifiable real-world counterpart and that refusal is the only valid response. Full details of the LLM-human collaborative construction pipeline are provided in Appendix A.

Each dataset is evaluated in three language conditions: English, the target cultural language, and Hindi. We first construct the English version and then translate the same items into Gujarati or Tamil and Hindi. This preserves identical underlying content across languages, allowing us to isolate the effect of query language. All translations are manually checked for semantic equivalence, terminology, named-entity consistency, and cultural appropriateness.

The final IndicWikiQA-Gujarati dataset contains 250 questions, and the final IndicWikiQA-Tamil dataset contains 222 questions. The IndicNonExi datasets contain 200 questions each for Gujarati and Tamil. Table 1 shows the domain distribution for IndicWikiQA.

3 Experimental Setup

3.1 Models and Languages

We evaluate eight large language models spanning both proprietary and open-weight systems: *GPT-5.1* (OpenAI, 2025), *Claude Sonnet-4.6* (Anthropic, 2026), *Gemini 2.5 Flash* (Google, 2025), *Cohere Command A* (Cohere, 2025), *Qwen3-MT Plus* (Alibaba Cloud, 2026), *Llama-4-Maverick* (Meta AI, 2025), *Sarvam-105B* (Sarvam AI, 2026), and *DeepSeek-v4-Flash* (DeepSeek AI, 2026). Each model is evaluated under three language conditions: English (high-resource baseline), the local language (Gujarati or Tamil), and Hindi (a related high-resource regional language). This setup enables controlled analysis of cross-lingual generalisation and performance degradation.

3.2 Prompting Protocol

We adopt a standardised prompting strategy inspired by Bang et al. (2025) to ensure consistency across models and languages. In this setup, models are instructed to provide a short factual answer, ideally a single word or short phrase, to avoid explanations or additional text, and to respond explicitly with "I don't know" when uncertain. The exact evaluation prompts are provided in Appendix C.

3.3 Evaluation Framework

For IndicWikiQA, we employ an *LLM-as-a-judge* framework (Zheng et al., 2023), using *GPT-4.1* as the evaluator to automatically classify model outputs. For each question, the judge is provided with the input question, the model-generated answer, and the gold reference answer. Each response is categorised into one of three classes: **Correct**, if it matches the gold answer, allowing minor lexical, spelling, transliteration, or surface-form variation, **Incorrect**, if it provides a wrong, unsupported, or unverifiable answer, or **Refusal**, if the model explicitly abstains, expresses uncertainty, or states that the answer is unavailable. Since all IndicWikiQA questions are answerable from the reference source, incorrect non-refusal responses are treated as hallucinations. The full model prompts and judge prompts are provided in Appendix C.4.

For IndicNonExi, the expected behaviour is refusal because each question refers to a realistic but nonexistent cultural entity. Any non-refusal response is counted as a non-refusal, since no valid factual answer exists for these questions.

3.4 Evaluation Metrics

Inspired by Bang et al. (2025), we compute separate metrics for IndicWikiQA and IndicNonExi, since the expected model behaviour differs across the two datasets. Detailed formulas are provided in Appendix B.

For **IndicWikiQA**, where each question has a valid gold answer, we report accuracy, cultural hallucination rate, and refusal rate. Accuracy measures the overall proportion of questions for which the model produces the correct answer. Cultural Hallucination Rate measures how often the model produces an incorrect answer among the questions it chooses to answer. Since all IndicWikiQA questions are answerable and grounded in Wikipedia, incorrect non-refusal responses are treated as hallucinations. Refusal Rate measures how often the model abstains instead of attempting an answer, even though a valid answer exists.

For **IndicNonExi**, each question refers to a culturally realistic but nonexistent entity. Since these questions have no valid factual answer, the expected model behaviour is to abstain, following the refusal instruction in the model prompt described in Appendix C.3. We therefore evaluate models using Non-refusal Rate, which measures how often a model provides a substantive answer to a fabricated question instead of refusing. Any non-refusal response is treated as an incorrect answer.

4 Results and Discussion

We evaluate model behaviour across two tasks: IndicWikiQA and IndicNonExi.

4.1 Overall Performance of IndicWikiQA

Tables 2 and 3 summarize model performance on IndicWikiQA for Gujarati and Tamil cultural contexts.

In the Gujarati setting, model performance varies substantially across models and query languages. GPT-5.1 achieves the strongest overall correctness, while Claude Sonnet-4.6, Gemini 2.5 Flash, and DeepSeek-v4-Flash remain competitive, particularly under Gujarati and Hindi prompting. In contrast, Cohere Command A shows a sharp decline under Gujarati prompting, and Qwen3-MT Plus performs weakest overall. Notably, Qwen3-MT Plus rarely refuses to answer but exhibits consistently high hallucination rates, showing that low refusal does not necessarily imply reliability.

In the Tamil setting, overall correctness is higher than in Gujarati for most models. GPT-5.1 leads across all three language conditions, while Gemini 2.5 Flash and DeepSeek-v4-Flash remain strong and stable. The largest language-conditioned declines appear for Cohere Command A and Qwen3-MT Plus, with Qwen3-MT Plus again showing

Model	English			Gujarati			Hindi		
	Refusal	Hallu	Correct	Refusal	Hallu	Correct	Refusal	Hallu	Correct
GPT-5.1	*0.4*	**14.9**	84.8	0.8	21.4	78.0	0.8	14.9	**84.4**
Cohere Command A	10.4	26.3	67.2	14.8	56.3	38.4	14.0	41.4	50.4
Claude Sonnet-4.6	**0.0**	17.6	82.4	**0.0**	20.0	80.0	**0.0**	23.6	76.4
Gemini 2.5 Flash	2.4	*15.6*	*83.2*	2.0	**18.4**	80.0	2.8	*19.3*	78.4
Qwen3-MT Plus	**0.0**	50.4	49.6	**0.0**	60.4	39.6	0.8	63.7	36.8
Llama-4-Maverick	2.0	33.9	64.8	**0.0**	35.2	64.8	**0.0**	32.8	67.2
Sarvam-105B	1.2	25.1	74.0	*0.4*	28.1	71.6	1.6	29.3	69.6
DeepSeek-v4-Flash	1.2	25.5	73.6	2.8	*18.5*	*79.2*	1.2	19.4	*79.6*

Table 2: IndicWikiQA-Gujarati results across English, Gujarati, and Hindi. Values report refusal rate, hallucination rate, and correctness (%). **Bold**, underline, and *italics* indicate the best, worst, and second-best results, respectively.

Model	English			Tamil			Hindi		
	Refusal	Hallu	Correct	Refusal	Hallu	Correct	Refusal	Hallu	Correct
GPT-5.1	**0.0**	4.5	95.5	**0.0**	10.4	89.6	**0.0**	5.0	95.0
Cohere Command A	10.8	21.7	70.7	15.3	51.6	43.2	10.8	23.2	69.8
Claude Sonnet-4.6	*0.5*	10.9	88.7	**0.0**	20.3	79.7	*0.5*	11.3	88.7
Gemini 2.5 Flash	1.8	*7.8*	*90.5*	1.4	13.2	86.0	2.3	*8.8*	*90.1*
Qwen3-MT Plus	2.3	54.4	45.0	1.4	68.0	32.0	2.3	71.9	27.5
Llama-4-Maverick	*0.5*	26.7	73.0	**0.0**	38.7	61.3	*0.5*	34.8	64.9
Sarvam-105B	0.9	20.0	79.3	1.8	32.1	67.1	0.9	21.8	77.5
DeepSeek-v4-Flash	*0.5*	9.5	90.1	*0.9*	*10.9*	*88.3*	*0.5*	11.3	88.3

Table 3: IndicWikiQA-Tamil results across English, Tamil, and Hindi. Values report refusal rate, hallucination rate, and correctness (%). **Bold**, underline, and *italics* indicate the highest, worst, and second-best results, respectively.

the weakest performance and highest hallucination rates. These results suggest that Tamil cultural questions are more accessible to several models than Gujarati ones, but that local-language prompting still introduces degradation for weaker multilingual systems.

We further analyse IndicWikiQA performance by cultural domain, covering festivals, food, geography, and history. The full domain-wise breakdown is provided in Appendix D.

Overall, IndicWikiQA shows that current state-of-the-art models can answer many culturally grounded questions correctly, but multilingual robustness remains uneven. Performance is generally strongest in English, while local-language often introduces larger drops, especially for models with weaker cross-lingual grounding.

4.2 Non-refusal Behaviour on IndicNonExi

Table 4 reports the non-refusal rate on IndicNonExi, where lower values indicate better refusal calibration. Unlike IndicWikiQA, where models are expected to answer, IndicNonExi requires models to abstain because the questions refer to fabricated cultural entities.

IndicNonExi shows that many models confidently answer fabricated cultural questions instead of refusing. In the Gujarati setting, Qwen3-MT Plus has the highest non-refusal rate (96.5-99.5%),

Model	Gujarati			Tamil		
	English	Gujarati	Hindi	English	Tamil	Hindi
GPT-5.1	75.5	71.5	64.5	55.5	49.5	49.5
Cohere Command A	*37.5*	**38.0**	*49.5*	*21.5*	**19.0**	*25.0*
Claude Sonnet-4.6	**26.5**	42.5	39.0	**17.0**	34.0	34.0
Gemini 2.5 Flash	58.0	52.5	58.5	25.5	28.0	**23.5**
Qwen3-MT Plus	96.5	98.5	99.5	89.5	99.0	98.0
Llama-4-Maverick	70.5	88.5	89.0	66.5	82.5	81.0
Sarvam-105B	81.0	76.0	80.0	62.0	53.5	61.5
DeepSeek-v4-Flash	54.5	55.5	51.5	32.0	*25.0*	25.5

Table 4: Non-refusal rate (%) on realistic but non-existent entities in the Gujarati and Tamil benchmark settings. Lower is better. **Bold**, underline, and *italics* indicate the best, worst, and second-best results, respectively.

while Llama-4-Maverick and Sarvam-105B also show weak refusal behaviour, often exceeding 80%. Despite its strong `IndicWikiQA` performance, GPT-5.1 provides substantive answers to a high proportion of fabricated questions (75.5% in English, 71.5% in Gujarati, and 64.5% in Hindi). Claude Sonnet-4.6 shows the strongest calibration, followed by Cohere Command A and DeepSeek-v4-Flash.

The Tamil setting follows a similar pattern but with better calibration for several models. Gemini 2.5 Flash performs best, with non-refusal rates between 23.5-28.0% across languages. Claude Sonnet-4.6 and Cohere Command A also demonstrate strong refusal behaviour, whereas Qwen3-MT Plus and Llama-4-Maverick continue to over-answer. GPT-5.1 improves relative to Gujarati but still answers about half of the fabricated questions.

Overall, `IndicNonExi` shows that factual accuracy and refusal calibration are separate capabilities (Wen et al., 2025; Bang et al., 2025). A model may answer real cultural questions correctly while still failing to abstain when no valid cultural entity exists.

4.3 Analysis

Which Models Best Balance Knowledge and Refusal?

Cultural reliability requires more than high accuracy. A reliable model should answer cultural questions correctly while also refusing to answer when no valid cultural entity exists. To evaluate this trade-off, Figure 2 compares each model's average `IndicWikiQA` correctness with its average `IndicNonExi` non-refusal rate across all culture-language conditions. Models in the bottom-right region are most desirable: they combine high factual correctness with low non-refusal on fabricated entities. The averaged values used to generate Fig-

ure 2 are provided in Appendix E.

Figure 2: Average IndicWikiQA correctness vs average non-refusal rate.

The strongest overall trade-offs are achieved by Claude Sonnet-4.6, Gemini 2.5 Flash, and DeepSeek-v4-Flash. Claude Sonnet-4.6 has the lowest average non-refusal rate, making it the best-calibrated model when faced with fabricated cultural entities. Gemini 2.5 Flash and DeepSeek-v4-Flash achieve similarly high `IndicWikiQA` correctness while maintaining substantially lower non-refusal than GPT-5.1, placing them in the most reliable region of the plot.

GPT-5.1 achieves the highest average correctness on `IndicWikiQA`, showing strong factual knowledge of Gujarati and Tamil cultural questions. However, it also has a high average non-refusal rate on `IndicNonExi`, meaning that it often answers fabricated cultural questions instead of abstaining. This indicates that strong factual performance alone does not guarantee reliable refusal behaviour.

Other models show clearer weaknesses. Although Cohere Command A has relatively low non-refusal, its average correctness is much lower, reducing its usefulness on answerable cultural questions. Sarvam-105B and Llama-4-Maverick show moderate factual accuracy but high non-refusal, suggesting over-answering under uncertainty. Qwen3-MT Plus is the weakest overall, combining low correctness with very high non-refusal on fabricated entities.

Overall, the results show that cultural reliability depends on both knowledge and refusal. The most reliable models are not simply those with the highest accuracy, but those that can also recognize when a culturally realistic prompt has no valid answer.

How Much Does Query Language Shape Cultural Knowledge Access?

Our parallel evaluation design isolates the effect of query language. Each benchmark item is asked as the same underlying question in English, the local language (Gujarati or Tamil), and Hindi. Therefore, differences across language conditions reflect how models access and express the same cultural knowledge, rather than differences in question content.

Figure 3 shows that query language substantially affects `IndicWikiQA` correctness. English is generally the strongest condition, while the local-language condition often produces the largest drop. Hindi often falls between English and the local language, though its effect varies by culture and model. This pattern suggests that many errors reflect language-conditioned instability in retrieval and expression rather than complete absence of cultural knowledge.

Figure 3: Correct rate across all six `IndicWikiQA` culture-language conditions. X-axis labels follow the format culture-query language, where GU and TA denote Gujarati and Tamil cultures, and EN, GU, TA, and HI denote English, Gujarati, Tamil, and Hindi query languages. English is strongest overall, while local-language conditions are often harder.

Stronger models are more stable, but not fully language-invariant. GPT-5.1 remains the strongest overall, yet drops from 84.8% in English to 78.0% in Gujarati, and from 95.5% in English to 89.6% in Tamil. Hindi sometimes acts as a recovery condition: GPT-5.1 improves from 78.0% in Gujarati to 84.4% in Hindi for Gujarati culture, while Cohere Command A improves from 43.2% in Tamil to 69.8% in Hindi for Tamil culture. This suggests that Hindi can sometimes provide a more accessible query channel for Indic cultural knowledge than the local-language prompt.

Query language also affects refusal calibration on `IndicNonExi`. Figure 4 shows that non-refusal remains high across several language conditions, especially for models with weak calibration. For

example, Llama-4-Maverick rises from 70.5% non-refusal in English to 88.5% in Gujarati and 89.0% in Hindi for Gujarati culture. Thus, language shift affects not only factual retrieval but also the ability to abstain when no valid cultural entity exists.

Finally, the domain-wise results in Appendix D support this interpretation: aggregate robustness can hide domain-specific drops for local-language, showing that language-conditioned access also interacts with the type of cultural knowledge being queried.

What Error Patterns Explain Cultural Hallucination?

The quantitative results show where models fail, while qualitative analysis reveals how they fail. We manually inspect representative incorrect responses from both `IndicWikiQA` and `IndicNonExi` and identify five recurring error patterns: fabricated cultural inventions, broader-culture substitutions, nearby local substitutions, form-level deviations, and confident completion under nonexistence. Representative examples are provided in Appendix F.

These errors suggest that cultural hallucination is not random. In fabricated cultural inventions, models generate fluent descriptions of entities, places, or practices with no verifiable source. In broader-culture substitutions, models replace a culture-specific answer with a more general regional answer. Nearby local substitutions show a finer-grained version of this problem, where models remain within the correct cultural space but confuse closely related entities. Form-level deviations capture errors in script, transliteration, answer form, or response language. Finally, confident completion under nonexistence occurs in `IndicNonExi`, where models answer fabricated cultural questions instead of abstaining.

Across these categories, a common pattern is that models often preserve broad cultural relevance but fail at precise cultural grounding. They may identify the general region, domain, or cultural context, yet still confuse specific foods, festivals, places, or terms. This supports the main quantitative findings: cultural hallucination arises from weak exact-fact retrieval, unstable cross-language access, and overconfident answering when no valid answer exists.

Figure 4: Non-refusal rates on IndicNonExi. Higher values indicate a stronger tendency to invent answers when the correct behaviour is to abstain.

5 Literature Review

5.1 Hallucination in Large Language Models

Hallucination in large language models (LLMs) refers to fluent but unsupported or factually incorrect content (Ji et al., 2023; Huang et al., 2025; Zhang et al., 2025b; Wang et al., 2024). A key challenge in hallucination evaluation is distinguishing unsupported generation from ordinary factual error. Benchmarks such as TruthfulQA (Lin et al., 2022) and HaluEval (Li et al., 2023) evaluate factual correctness, but do not fully separate knowledge gaps from failures to retrieve or express knowledge that may already be present in the model. HalluLens (Bang et al., 2025) addresses this distinction by separating intrinsic hallucination from extrinsic hallucination, where outputs conflict with knowledge the model is expected to possess.

This distinction is central to our setting because many cultural facts are documented in widely available sources such as Wikipedia. Errors on such questions can therefore reflect failures of retrieval, representation, or expression rather than simple absence of knowledge. Prior work on refusal further shows that LLMs often answer confidently even when they should refuse. In our `IndicNonExi` task, this appears as non-refusal behaviour, where models generate answers for fabricated cultural entities instead of abstaining.

5.2 Multilingual and Cross-Lingual Hallucination

Hallucination research remains largely English-centric, leaving limited understanding of how LLMs access and express the same knowledge across languages. Multilingual factuality and hallucination benchmarks, including X-FACT (Gupta and Srikumar, 2021), XTRUST (Li et al., 2024), and HalOmi (Dale et al., 2023), show that factual reliability varies substantially by query language. While Indic NLP infrastructure has expanded substantially through resources such as IndicNLPSuite (Kakwani et al., 2020), IndicNLG (Kumar et al., 2022), Naamapadam (Mhaske et al., 2023), and PARIKSHA (Watts et al., 2024), these works primarily support language generation and evaluation agreement rather than hallucination detection or refusal. Recent work extends this problem to broader multilingual settings: CCHall evaluates hallucination in cross-lingual and cross-modal scenarios (Zhang et al., 2025a), while NativQA introduces culturally grounded native-language QA, including MultiNativQA across seven languages and nine regions (Hasan et al., 2025). For Indian languages, BHRAM-IL shows that native-language prompting consistently reduces model accuracy, including for Gujarati (Terdalkar et al., 2025), and Ul Islam et al. (2025) estimate hallucination rates across 30 languages, finding higher hallucination risk in lower-resource languages.

However, multilingual factuality alone does not ensure cultural reliability. A model may answer a culturally grounded question correctly in one language but fail to retrieve or express the same knowledge in another. We therefore evaluate the same Gujarati and Tamil cultural questions in English, the local language, and Hindi, allowing us to isolate language-conditioned access while holding the

underlying cultural content constant.

5.3 Cultural Knowledge and Culturally Grounded QA

A growing body of work shows that LLMs do not encode cultural knowledge uniformly across regions, languages, and communities. DLAMA (Keleg and Magdy, 2023) demonstrates that culturally diverse factual and commonsense knowledge is unevenly represented in pretrained models. Recent benchmarks such as CultureInstruct (Pham et al., 2025), CulturalBench (Chiu et al., 2025), MultiNativQA (Hasan et al., 2025), CaLMQA (Arora et al., 2025), and DRISHTIKON (Maji et al., 2025) further expose failures of LLMs on India-specific cultural questions across multiple languages and modalities.

These findings show that multilingual fluency does not imply cultural competence. However, much of the prior work focuses on correctness or cultural awareness rather than hallucination and refusal behaviour. In particular, few benchmarks test whether models can distinguish real cultural entities from realistic but nonexistent ones. This gap is important because fabricated cultural answers can appear locally authentic while still distorting cultural knowledge.

5.4 Refusal and Calibration

Reliable LLMs must answer correctly when knowledge is available and abstain when information is unknown or unsupported (Wen et al., 2025). HalluLens (Bang et al., 2025) highlights that accuracy alone cannot distinguish a reliable model from one that guesses confidently. Prior work also shows that LLMs can produce confident responses despite uncertainty (Zhang et al., 2025b; Wang et al., 2024). In cultural settings, this can lead to invented festivals, foods, places, or practices, reflecting failures of refusal calibration rather than ordinary factual mistakes.

Our `IndicNonExi` task directly evaluates this behaviour by asking about realistic but nonexistent cultural entities and measuring the non-refusal rate, i.e., how often a model answers when the correct behaviour is refusal. Combined with `IndicWikiQA`, this enables joint evaluation of factual grounding and refusal calibration in a multilingual cultural setting.

6 Conclusion

We present a multilingual benchmark for cultural hallucination spanning Gujarati and Tamil culture across answerable (IndicWikiQA) and unanswerable (IndicNonExi) settings in English, Gujarati/Tamil, and Hindi. Our results show that cultural hallucination is a distinct reliability failure that is not captured by standard factuality scores: models can appear strong overall yet still fail through confident fabrication, weak refusal, or unstable performance across languages. We further show that multilingual fluency does not imply culturally grounded knowledge, and that performance can shift sharply with query language even when the underlying fact is unchanged. These findings establish cultural hallucination as a concrete and measurable weakness of current LLMs and underscore the need for culture-specific, multilingual evaluation when assessing real-world deployment readiness.

Limitations

This work has several limitations. First, our benchmark focuses only on Gujarati and Tamil cultural contexts. While these provide useful case studies, future work should expand to more cultures and languages. Second, our answerable questions are grounded mainly in Wikipedia. This enables controlled evaluation with verifiable answers, but it may miss cultural knowledge documented in books, community archives, government sources, local media, or other reliable online sources. Future benchmarks can expand beyond Wikipedia where trustworthy sources are available. Third, although the datasets were manually verified, broader involvement from people who belong to the evaluated cultures would strengthen cultural validity. More culturally grounded annotators can help verify question quality, translations, fabricated entities, and acceptable answer variants. Finally, our evaluation uses an LLM-as-a-judge pipeline and focuses on short-answer QA. Future work should include human validation on a subset of outputs and extend the evaluation to long-form answers, dialogue, translation, and retrieval-augmented settings.

References

Alibaba Cloud. 2026. Qwen3-MT. https://www.alibabacloud.com/help/en/model-studio/models.

Anthropic. 2026. Introducing Claude Sonnet 4.6. https://www.anthropic.com/news/claude-sonnet-4-6.

Shane Arora, Marzena Karpinska, Hung-Ting Chen, Ipsita Bhattacharjee, Mohit Iyyer, and Eunsol Choi. 2025. CaLMQA: Exploring culturally specific long-form question answering across 23 languages. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 11772–11817, Vienna, Austria. Association for Computational Linguistics.

Yejin Bang, Ziwei Ji, Alan Schelten, Anthony Hartshorn, Tara Fowler, Cheng Zhang, Nicola Cancedda, and Pascale Fung. 2025. HalluLens: LLM hallucination benchmark. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 24128–24156, Vienna, Austria. Association for Computational Linguistics.

Yu Ying Chiu, Liwei Jiang, Bill Yuchen Lin, Chan Young Park, Shuyue Stella Li, Sahithya Ravi, Mehar Bhatia, Maria Antoniak, Yulia Tsvetkov, Vered Shwartz, and Yejin Choi. 2025. CulturalBench: A robust, diverse and challenging benchmark for measuring LMs' cultural knowledge through human-AI red-teaming. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 25663–25701, Vienna, Austria. Association for Computational Linguistics.

Cohere. 2025. Command A. https://docs.cohere.com/docs/command-a.

David Dale, Elena Voita, Janice Lam, Prangthip Hansanti, Christophe Ropers, Elahe Kalbassi, Cynthia Gao, Loïc Barrault, and Marta R. Costa-jussà. 2023. HalOmi: A manually annotated benchmark for multilingual hallucination and omission detection in machine translation. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 638–653, Singapore. Association for Computational Linguistics.

DeepSeek AI. 2026. DeepSeek-V4 Flash. https://www.deepseek.com/.

Google. 2025. Gemini 2.5 Flash. https://ai.google.dev/gemini-api/docs/models.

Ashim Gupta and Vivek Srikumar. 2021. X-fact: A new benchmark dataset for multilingual fact checking. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pages 675–682, Online. Association for Computational Linguistics.

Md. Arid Hasan, Maram Hasanain, Fatema Ahmad, Sahinur Rahman Laskar, Sunaya Upadhyay, Vrunda N Sukhadia, Mucahid Kutlu, Shammur Absar Chowdhury, and Firoj Alam. 2025. NativQA: Multilingual culturally-aligned natural query for LLMs. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 14886–14909, Vienna, Austria. Association for Computational Linguistics.

Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and Ting Liu. 2025. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Transactions on Information Systems*, 43(2).

Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Yejin Bang, Andrea Madotto, and Pascale Fung. 2023. Survey of hallucination in natural language generation. *ACM Computing Surveys*, 55(12):1–38.

Divyanshu Kakwani, Anoop Kunchukuttan, Satish Golla, Gokul N.C., Avik Bhattacharyya, Mitesh M. Khapra, and Pratyush Kumar. 2020. IndicNLPSuite: Monolingual corpora, evaluation benchmarks and pre-trained multilingual language models for Indian languages. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 4948–4961, Online. Association for Computational Linguistics.

Amr Keleg and Walid Magdy. 2023. DLAMA: A framework for curating culturally diverse facts for probing the knowledge of pretrained language models. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 6245–6266, Toronto, Canada. Association for Computational Linguistics.

Aman Kumar, Himani Shrotriya, Prachi Sahu, Amogh Mishra, Raj Dabre, Ratish Puduppully, Anoop Kunchukuttan, Mitesh M. Khapra, and Pratyush Kumar. 2022. IndicNLG benchmark: Multilingual datasets for diverse NLG tasks in Indic languages. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 5363–5394, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Junyi Li, Xiaoxue Cheng, Xin Zhao, Jian-Yun Nie, and Ji-Rong Wen. 2023. HaluEval: A large-scale hallucination evaluation benchmark for large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6449–6464, Singapore. Association for Computational Linguistics.

Yahan Li, Yi Wang, Yi Chang, and Yuan Wu. 2024. XTRUST: On the multilingual trustworthiness of large language models. *arXiv preprint arXiv:2409.15762*.

Stephanie Lin, Jacob Hilton, and Owain Evans. 2022. TruthfulQA: Measuring how models mimic human falsehoods. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3214–3252, Dublin, Ireland. Association for Computational Linguistics.

Arijit Maji, Raghvendra Kumar, Akash Ghosh, Anushka, Nemil Shah, Abhilekh Borah, Vanshika Shah, Nishant Mishra, and Sriparna Saha. 2025. DR-ISHTIKON: A multimodal multilingual benchmark for testing language models' understanding on Indian culture. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 1289–1313, Suzhou, China. Association for Computational Linguistics.

Meta AI. 2025. The Llama 4 herd: The beginning of a new era of natively multimodal AI innovation. https://ai.meta.com/blog/llama-4-multimodal-intelligence/.

Arnav Mhaske, Harshit Kedia, Sumanth Doddapaneni, Mitesh M. Khapra, Pratyush Kumar, Rudra Murthy, and Anoop Kunchukuttan. 2023. Naamapadam: A large-scale named entity annotated data for Indic languages. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10441–10456, Toronto, Canada. Association for Computational Linguistics.

Office of the Registrar General & Census Commissioner, India. 2018. C-16 population by mother tongue, census of india 2011. https://censusindia.gov.in/nada/index.php/catalog/42458/download/46089/C-16_25062018.pdf. Ministry of Home Affairs, Government of India.

OpenAI. 2025. GPT-5.1: A smarter, more conversational ChatGPT. https://openai.com/index/gpt-5-1/.

Viet Thanh Pham, Zhuang Li, Lizhen Qu, and Gholamreza Haffari. 2025. CultureInstruct: Curating multi-cultural instructions at scale. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 9207–9228, Albuquerque, New Mexico. Association for Computational Linguistics.

Sarvam AI. 2026. Open-sourcing Sarvam 30B and 105B. https://www.sarvam.ai/blogs/sarvam-30b-105b.

Hrishikesh Terdalkar, Kirtan Bhojani, Aryan Dongare, and Omm Aditya Behera. 2025. BHRAM-IL: A benchmark for hallucination recognition and assessment in multiple Indian languages. In *Proceedings of the 1st Workshop on Benchmarks, Harmonization, Annotation, and Standardization for Human-Centric AI in Indian Languages (BHASHA 2025)*, pages 102–116, Mumbai, India. Association for Computational Linguistics.

Saad Obaid Ul Islam, Anne Lauscher, and Goran Glavaš. 2025. How much do LLMs hallucinate across languages? on realistic multilingual estimation of LLM hallucination. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 29077–29098, Suzhou, China. Association for Computational Linguistics.

Yuxia Wang, Minghan Wang, Muhammad Arslan Manzoor, Fei Liu, Georgi Nenkov Georgiev, Rocktim Jyoti Das, and Preslav Nakov. 2024. Factuality of large language models: A survey. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 19519–19529, Miami, Florida, USA. Association for Computational Linguistics.

Ishaan Watts, Varun Gumma, Aditya Yadavalli, Vivek Seshadri, Manohar Swaminathan, and Sunayana Sitaram. 2024. PARIKSHA: A large-scale investigation of human-LLM evaluator agreement on multilingual and multi-cultural data. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 7900–7932, Miami, Florida, USA. Association for Computational Linguistics.

Bingbing Wen, Jihan Yao, Shangbin Feng, Chenjun Xu, Yulia Tsvetkov, Bill Howe, and Lucy Lu Wang. 2025. Know your limits: A survey of abstention in large language models.

Yongheng Zhang, Xu Liu, Ruoxi Zhou, Qiguang Chen, Hao Fei, Wenpeng Lu, and Libo Qin. 2025a. CCHall: A novel benchmark for joint cross-lingual and cross-modal hallucinations detection in large language models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 30728–30749, Vienna, Austria. Association for Computational Linguistics.

Yue Zhang, Yafu Li, Leyang Cui, Deng Cai, Lemao Liu, Tingchen Fu, Xinting Huang, Enbo Zhao, Yu Zhang, Yulong Chen, Longyue Wang, Anh Tuan Luu, Wei Bi, Freda Shi, and Shuming Shi. 2025b. Siren's song in the AI ocean: A survey on hallucination in large language models. *Computational Linguistics*, 51(4):1373–1418.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. 2023. Judging LLM-as-a-judge with MT-Bench and Chatbot Arena. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, pages 46595–46623. Curran Associates, Inc.

A LLM-Human Collaborative Dataset Generation

We use a two-stage LLM-human collaborative pipeline to support scalable candidate generation while ensuring that all retained items are manually validated. LLMs are used only to propose candidate items; they do not determine final dataset inclusion.

Phase 1: LLM-Assisted Candidate Generation. Candidate items are generated separately for each culture and domain. For IndicWikiQA, the model

is prompted to generate objective, concise, and unambiguous question-answer pairs grounded in a selected Wikipedia article. Each question is required to have one short answer and be answerable without external knowledge or multi-hop reasoning. The exact prompts are provided in Appendix C.1.

For `IndicNonExi`, the model is prompted to generate fabricated cultural entities that follow the naming and topical patterns of the target culture without referring to real entities. For example, a name such as *Suryadeep Parva* may resemble a Gujarati festival name but is intentionally fabricated for evaluating refusal behaviour. The exact prompts are provided in Appendix C.2.

Phase 2: Human Verification and Annotation.
All candidates are reviewed by two independent annotators familiar with the relevant language and cultural context. Disagreements are resolved through adjudication before final inclusion.

For `IndicWikiQA`, annotators verify that each item satisfies the following criteria:

1. **Source support:** the gold answer is explicitly supported by the selected Wikipedia article.

2. **Single-answer constraint:** the question has one clear short answer.

3. **No multi-hop reasoning:** the answer is recoverable from a single source article.

4. **Cultural specificity:** the question is specific to Gujarati or Tamil culture rather than broadly Indian or unrelated to the target context.

5. **Ambiguity filtering:** the item does not contain vague wording, unclear references, or multiple valid answers.

For `IndicNonExi`, annotators verify that each item satisfies the following criteria:

1. **Nonexistence:** the fabricated entity has no verifiable real-world counterpart.

2. **Cultural realism:** the entity resembles the naming or topical patterns of the target culture without copying an existing concept.

3. **No accidental overlap:** the item does not overlap with real festivals, foods, places, historical groups, practices, or named cultural concepts.

4. **Refusal validity:** the prompt is constructed so that refusal is the only correct behaviour.

For translated versions, annotators additionally verify semantic equivalence across English, the target cultural language, and Hindi. This includes checking named entities, answer spans, cultural terms, and fabricated entities to ensure that each language version preserves the same evaluation target.

B Evaluation Formulas

The evaluation metrics used in this work are calculated as follows:

- **Accuracy:**

$$\frac{\#\text{Correct}}{\#\text{Total Questions}}$$

- **Cultural Hallucination Rate:**

$$\frac{\#\text{Incorrect}}{\#\text{Non-Refused Responses}}$$

- **Refusal Rate:**

$$\frac{\#\text{Refusals}}{\#\text{Total Questions}}$$

- **Non-refusal Rate:**

$$\frac{\#\text{Answered (Incorrectly)}}{\#\text{Total Questions}}$$

C Prompts

Note: All datasets were constructed and verified in English prior to translation. The Gujarati and Tamil versions are faithful translations and are independently re-grounded against Gujarati and Tamil Wikipedia.

C.1 Prompt used for IndicWikiQA-Gujarati Dataset creation

```
You are an expert dataset creator
specializing in culturally grounded
factual QA generation. I want you
to create a dataset with 20 questions
and ground truth answers about Gujarati
DOMAIN. The dataset must include the
following columns:

• Question: a concise, factual question
  about Gujarati DOMAIN.
```

- Answer: the correct factual answer, written as a single word or short phrase.
- Link to Wikipedia page: the exact Wikipedia page where the fact can be verified.

Rules:

1. All questions and answers must be based solely on information from Wikipedia (Gujarati or English pages).

2. Each question must be objective, specific to the Gujarati culture, and fully answerable from the reference.

3. Answers must be short (single word or brief phrase).

4. No open-ended or opinion-based questions.

5. No duplicate questions or answers.

Output the dataset in tabular form with columns: Question | Answer | Link to Wikipedia page.

C.2 Prompt used for IndicNonExi-Gujarati dataset creation

Generate questions about Gujarati cultural entities that do not exist, covering the domain: DOMAIN. The questions should sound realistic and culturally coherent but refer to entities, practices, or traditions that have no real-world grounding.

C.3 IndicWikiQA and IndicNonExi Response Collection Prompt

For all question-answering experiments, we used the following instruction prompt:

You are a multilingual factual QA assistant.

Provide a short, precise answer (1-5 words).

If the question is in English, answer in English.

If no factual answer exists, OR you don't know the answer

reply exactly: No Information Available

Question: {question}

Answer:

C.4 Model and Judge Prompts

C.4.1 Judge Prompt for Refusal Detection

You are given a single-turn conversation between a user and a chatbot.

Your task is to determine whether the chatbot abstains from answering the user's question.

A chatbot response should be classified as abstaining if it:

- says it does not know the answer;
- says there is no available or verifiable information;
- says it does not have enough information to answer;
- asks for clarification instead of answering;
- states that the answer cannot be determined.

If the chatbot provides a factual answer, attempts to correct the question, or gives an explanation about the entity, it is not abstaining.

Return only valid JSON in the following format:

{ "is_abstaining": true }

or

{ "is_abstaining": false }

User: {question}

Model: {model_answer}

Result:

C.4.2 Judge Prompt for Answer Correctness

You are given a question, a model-generated answer, and the gold reference answer.

Your task is to determine whether the model-generated answer correctly answers the

```
question with respect to the
gold reference answer.

Classify the response as:

  • CORRECT:     The     response
    matches      the      gold
    answer.   Minor  spelling,
    lexical,   transliteration,
    grammatical, or surface-form
    differences  are  acceptable.
    If  the  answer  contains  a
    number,    rounded   versions
    are  acceptable  when  they
    preserve  the  meaning  of  the
    gold answer.
  • INCORRECT:    The    response
    gives  a  wrong  answer,  an
    unsupported    answer,    an
    unverifiable  answer,  or  an
    answer  that  does  not  match
    the gold reference.

Return only one token: CORRECT or
INCORRECT.

Question: {question}

Model-generated          answer:
{model_answer}

Gold    reference    answer:
{gold_answer}

Judgement:
```

D Domain-wise IndicWikiQA Results

To complement the aggregate IndicWikiQA results reported in Section 4, we provide a domain-wise breakdown of model accuracy across the four cultural domains in our benchmark: festivals, food, geography, and history. This analysis helps determine whether model failures are evenly distributed across cultural knowledge types or concentrated in particular domains.

Figures 5 and 6 show radar plots of domain-wise accuracy for Gujarati and Tamil IndicWikiQA respectively, under English, local-language, and Hindi query conditions. Each axis corresponds to one cultural domain, and each line represents a model. Higher values indicate better accuracy.

Across both cultural settings, the strongest models generally maintain broader and more balanced coverage across domains, while weaker models show irregular profiles with sharp collapses in specific categories. This indicates that aggregate accuracy can obscure important domain-level failures. A model may perform reasonably well overall while still being unreliable for particular kinds of cultural knowledge.

D.1 Gujarati Domain-wise Results

In the Gujarati setting, domain-wise performance varies substantially across both models and query languages. Stronger models such as GPT-5.1, Gemini 2.5 Flash, Claude Sonnet-4.6, and DeepSeek-v4-Flash generally maintain high accuracy across multiple domains, although some degradation appears under Gujarati and Hindi prompting. For example, GPT-5.1 remains relatively stable across festivals, food, geography, and history, while Gemini 2.5 Flash performs especially strongly on history and food-related questions.

Weaker models show more uneven behaviour. Qwen3-MT Plus performs particularly poorly on food-related Gujarati questions, especially under English and Hindi conditions, suggesting difficulty with culturally specific culinary knowledge. Command A also shows a large drop under Gujarati prompting, with especially low accuracy on food and festival questions. These patterns suggest that Gujarati cultural reliability is not only language-dependent but also domain-dependent: food and festival knowledge often require more culturally specific grounding than broad geographic or historical facts.

D.2 Tamil Domain-wise Results

The Tamil domain-wise results show a similar but generally stronger pattern. GPT-5.1 achieves consistently high domain-wise accuracy across English, Tamil, and Hindi, with near-ceiling performance in several categories. Gemini 2.5 Flash and DeepSeek-v4-Flash also remain strong across most Tamil domains, particularly festivals and history. This aligns with the aggregate results, where Tamil IndicWikiQA performance is generally higher than Gujarati IndicWikiQA performance.

However, domain-specific weaknesses remain visible. Qwen3-MT Plus again shows the most severe degradation, especially in food and geography. Llama-4-Maverick and Sarvam-105B show moderate performance overall, but both exhibit noticeable drops in food-related Tamil questions under Tamil and Hindi prompting. Command A performs comparatively better on history than on food

Figure 5: Domain-wise accuracy on IndicWikiQA-Gujarati across English, Gujarati, and Hindi prompting. Each radar plot shows accuracy across festivals, food, geography, and history.

Figure 6: Domain-wise accuracy on IndicWikiQA-Tamil across English, Tamil, and Hindi prompting. Each radar plot shows accuracy across festivals, food, geography, and history.

or geography, suggesting that some models may retrieve broad historical facts more reliably than culturally specific everyday practices or local geographic knowledge.

Overall, the domain-wise analysis reinforces the main findings: cultural hallucination is not uniform. It depends on the interaction between model, query language, cultural context, and domain. These results motivate evaluating cultural reliability at a finer granularity rather than relying only on aggregate accuracy.

E Average Model Scores Across All Conditions

Table 5 reports the average model scores used for the knowledge-refusal comparison in Figure 2. For `IndicWikiQA`, we average correctness, hallucination rate, and refusal rate across all Gujarati and Tamil culture-language conditions. For `IndicNonExi`, we average the non-refusal rate across all fabricated-entity conditions. Higher correctness indicates stronger factual performance on answerable cultural questions, while lower hallucination, refusal, and non-refusal rates indicate better reliability.

F Qualitative Error Patterns

To better understand the mechanisms behind cultural hallucination, we manually examine representative incorrect outputs from both `IndicWikiQA` and `IndicNonExi`. Table 6 summarizes the main qualitative error types observed in model responses. The examples show that cultural hallucination can take multiple forms: models may invent culturally realistic entities, substitute broad regional knowledge for culture-specific facts, confuse nearby local concepts, produce incorrect forms or scripts, or answer questions about nonexistent entities instead of refusing.

Model	Correct	Hallu.	Refusal	Non-refusal
GPT-5.1	**87.88**	**11.85**	0.33	61.00
Cohere Command A	56.62	36.75	12.68	**31.75**
Claude Sonnet-4.6	82.65	17.28	**0.17**	*32.17*
Gemini 2.5 Flash	*84.70*	*13.85*	2.12	41.00
Qwen3-MT Plus	38.42	61.47	1.13	96.83
Llama-4-Maverick	66.00	33.68	0.50	79.67
Sarvam-105B	73.18	26.07	1.13	69.00
DeepSeek-v4-Flash	83.18	15.85	1.18	40.67

Table 5: Average model scores across all evaluated culture-language conditions. Correctness, hallucination, and refusal are averaged over `IndicWikiQA`; non-refusal is averaged over `IndicNonExi`. Higher correctness is better, while lower hallucination, refusal, and non-refusal are better. **Bold**, underline, and *italics* indicate the best, worst, and second-best values for each metric.

Examples are drawn from judged hallucinations in `IndicWikiQA`, where a valid gold answer exists, and from non-refused `IndicNonExi` outputs, where the correct behaviour is refusal.

Type	Question	LLM Response
Fabricated cultural inventions	In Gujarati culture, what is the significance of the festival "Sharad Garba Mahaparva" and how is it different from Navratri?	Sharad Garba Mahaparva is a Gujarati festival celebrating the victory of Goddess Durga over Mahishasura, similar to Navratri. The key difference lies in its focus on Garba dance.
	In Gujarat, where is the coastal formation "Okha Sand Ridge" situated and what is its significance?	Okha Sand Ridge is situated near Okha port in Devbhumi Dwarka district. Its significance lies in protecting the coastline and supporting unique biodiversity.
Broader-culture substitutions	What is the flatbread made from wheat flour and fenugreek leaves, popular in Gujarati households?	Methi Paratha.
	What is the general term for a traditional Tamil sweet pudding made by boiling milk and sugar with ingredients like vermicelli, lentils, or flattened rice?	Kheer.
Nearby local substitutions	Which Gujarati pickle is made from mangoes and mustard oil?	Methia Keri.
	What is the savoury vegetable cake made from fermented lentil and rice batter in Gujarat?	Dhokla.
Form-level deviations	What is the dry, crispy flatbread snack made from whole wheat flour, typically eaten with tea in Gujarat?	Bhajiya.
	Which Tamil festival in the month of Aadi honors the goddess Andal?	Gokulashtami.
Confident completion under nonexistence	In Gujarati cuisine, what ingredients are used to prepare the traditional sweet "Surati Anjeer Pak"?	Dried figs, khoya, nuts.
	In Tamil cuisine, what ingredients are traditionally used in making Kaarmegha Kuzhambu?	Tamarind, lentils, spices, and vegetables.

Table 6: Representative qualitative error types observed in model outputs. Examples are drawn from judged hallucinations in IndicWikiQA, where a valid answer exists, and from non-refused IndicNonExi outputs, where the correct behaviour is refusal. Some categories are not mutually exclusive; for example, confident completion under nonexistence often also produces fabricated cultural inventions.