VisualLeakBench: Reproducible Action-Boundary Propagation Failures in Vision-Language Agents

Youting Wang[1] Yuan Tang[2] Yitian Qian[3] Chen Zhao[4]

Abstract

Vision-language agents increasingly consume screenshots, documents, and user interfaces before writing to memory, sending messages, or invoking external tools. We study a concrete failure mode in this setting: action-boundary propagation, where sensitive or unsafe visible text is copied from an image into downstream tool arguments. We present VisualLeakBench, a diversified 500-image benchmark spanning UI, chat, document, form, and dashboard scenes, and evaluate a stratified 100-image agent subset with four production VLM systems under two workflows: note capture and external handoff. At baseline, target strings are propagated into tool arguments in 78.8% of PII cases and 85.5% of rendered unsafe-text cases. Under a defensive system prompt, rendered unsafe-text propagation remains high at 52.6%, while PII tool propagation falls to 2.0%, largely by suppressing tool use rather than preserving utility. Rates are tool-surface dependent: search-like tools suppress PII propagation, but rendered unsafe text still crosses tool boundaries. We measure visual-to-tool propagation rather than downstream instruction execution. We additionally provide a labeled-target oracle upper-bound diagnostic that localizes most failures at the tool boundary while leaving response-side leakage as residual risk.

1. Introduction

Vision-language models are no longer only conversational systems. They are increasingly embedded in agentic workflows that read screenshots, summarize documents, save notes, forward emails, query search engines, and call application APIs. In these settings, a safety failure is not limited to what the model says to a user. A model can extract sensitive visible content and place it into a downstream action, where it may persist in memory, leave the local context, or become input to another system.

This paper studies one such failure mode: action-boundary propagation failure. A vision-language agent receives an image containing sensitive or unsafe visible text, then emits a tool call whose arguments include the target string. For example, a screenshot containing an API key may be saved into long-term notes, or a harmful request rendered in a dashboard may be forwarded to an operations inbox. The failure is trace-level: it may be invisible if evaluation looks only for refusal text or final-task success.

To study this failure mode, we present VisualLeakBench, a visual benchmark for privacy leakage and rendered unsafe-text propagation in agentic inputs. The benchmark is designed around ordinary-looking visual contexts, labeled target strings, and trace-level diagnostics. Rather than treating visual safety as only a response-level chat problem, we evaluate whether visible text propagates into tool arguments under plausible automated workflows, whether this behavior generalizes across visual trigger families, and which mitigations reduce propagation. We deliberately isolate a single action boundary for attribution and reproducibility: this setting should be read as a controlled failure primitive, not as a claim that all deployed long-horizon agents lack memory filters, human checkpoints, or tool validators.

Our prior benchmark studied response-level OCR and PII leakage in non-agentic LVLM settings (Wang et al., 2026). In contrast, this work shifts the unit of analysis to agent tool-use traces and action-boundary propaga-

[1]Northeastern University [2]Carnegie Mellon University [3]Boston University [4]New York University. Correspondence to: Youting Wang <wang.yout@northeastern.edu>.

Published at ICML 2026 Workshop on Failure Modes in Agentic AI, Seoul, South Korea. PMLR 306, 2026. Copyright 2026 by the author(s).

Figure 1. Trace diagnostic. A visual target may be absent from the visible response yet present in tool arguments, so classification and guard diagnostics inspect the action boundary.

tion, with per-trace diagnostics and mitigation residuals across multiple tool surfaces.

Contributions. First, we define action-boundary propagation as a single-step agent failure mode with explicit trigger, action, diagnostic, and harm boundaries. Second, we present a diversified 500-image, five-family visual benchmark and evaluate four production VLM systems on a stratified 100-image agent subset under structured tool-use workflows. Third, we provide trace diagnostics separating direct response leakage, safe tool calls, tool-only propagation, and response-plus-tool leakage. Fourth, we evaluate defensive prompting and show that mitigation can be sharply asymmetric across PII and rendered unsafe text. Finally, we provide a reproducible analysis script that regenerates aggregate, per-cell, error-accounting, minimal-case, and guard-diagnostic tables from per-trace logs.

2. Failure Definition

We define an action-boundary propagation failure as a trace in which: (1) the input image contains a target sensitive or unsafe string; (2) the model emits a downstream tool call; and (3) the normalized target string appears in one or more tool-call arguments. This is stricter than merely calling a tool and different from response-only leakage. Privacy propagation is one important instance of this broader failure family; rendered unsafe-text propagation is another.

In this benchmark, target strings are labeled non-propagatable: PII should be redacted or omitted, and unsafe visible requests should not be stored, forwarded, or searched verbatim unless explicitly sandboxed.

For the rendered unsafe-text track, propagation should not be read as proof that the agent followed the rendered instruction or completed a downstream harm. In a note-capture workflow, the immediate event may be transcription-as-content. Our claim is narrower: unsafe visible text has crossed from a visual input into

an operational argument that may be stored, routed, searched, or consumed by another system. The later harm depends on the tool semantics and downstream consumer, so we treat rendered unsafe-text propagation as a prerequisite failure primitive rather than as task execution.

Table 1. Operational failure components used in our agent evaluation.

Component	Definition
Trigger	Image containing PII or harmful visible text
Agent action	Structured tool call such as save_note or send_email
Primary diagnostic	Target string appears in any tool argument
Secondary diagnostics	Direct response leakage, tool-call rate, any unsafe trace
Mitigation target	Prevent unsafe target strings from reaching downstream tools

Why tool arguments matter. Response-level safety can miss operational harm. A model might say a cautious sentence while still saving the exact sensitive string into a note. Conversely, a model might avoid direct disclosure to the user but pass the content to an external workflow. As shown in Figure 1, we therefore evaluate traces at the boundary where agent output becomes system action.

3. Evaluation Setting

Visual triggers. We construct the diversified VisualLeakBench benchmark, exp_500, with five visual families: UI, chat, document, form, and dashboard. The benchmark has two tracks. The PII track covers eight synthetic PII types: SSNs, credit cards, dates of birth, emails, passwords, phone numbers, PINs, and API keys. The rendered unsafe-text track renders synthetic unsafe requests in ordinary visual contexts; compact tables label this track as Unsafe text, and artifact filenames may abbreviate it as OCR. Some targets resemble visual prompt-injection attempts, but the measured event is propagation into tool arguments rather than instruction execution. Its 50-image subset spans four coarse groups: physical/illicit procedural (9), cyber/phishing/online abuse (13), fraud/evasion/property abuse (15), and intrusion/sabotage/coercion (13). These labels describe trigger coverage rather than a complete harm taxonomy. The synthetic design is intended for controlled, reproducible trigger analysis and trace diagnosis rather than for estimating the full distribution of real enterprise screenshots.

Models. We evaluate four production VLM systems: GPT-5.4, Claude Opus 4.7, Gemini 3.1 Flash Lite, and Grok 4.20. All runs were conducted in April 2026 and use deterministic decoding where supported. Results should be interpreted as snapshots of model behavior under the tested versions.

Agent workflows. We evaluate two single-step tool-use scenarios. In note_capture, the model can call save_note(content) to preserve useful screenshot details for later automation. In external_handoff, the model can call send_email(to, body) to forward actionable content to a fixed operations inbox. Each model must return a JSON object containing a visible response, a tool name, and tool arguments. We evaluate a deterministic stratified 100-image subset: 10 examples per visual family per category, selected with seed 42 and saved as a manifest.

Metrics. Our primary metric is tool propagation rate: the fraction of non-error traces where the normalized target string appears in emitted tool arguments. We also report direct leakage rate, tool-call rate, and any-unsafe rate. Matching is normalized for whitespace, punctuation, hyphens, quotes, and case. This exact-match metric targets a high-precision lower-bound event: exact labeled-target propagation into tool arguments. It does not count partial, paraphrased, inferred, or semantic leakage. Retries are resolved by last-record-wins deduplication over filename, scenario, model, category, and mitigation condition.

Mitigation and guard diagnostic. We test a single defensive system prompt instructing models not to transcribe PII and to refuse social-engineering requests. This is intentionally lightweight: the goal is not to exhaust the defense space, but to identify which failure classes are easy or hard to suppress with a common deployment control. We also run an offline labeled-target oracle diagnostic that blocks a tool call whenever the known synthetic target string appears in tool arguments. This is an upper-bound diagnostic rather than a deployable detector, but it isolates the value of controlling the tool boundary without making additional model calls.

Reproducibility artifact. The supplementary artifact contains baseline and mitigated per-trace CSV logs, a regeneration script, prompts and schemas, normalization rules, deduplication keys, and generated summaries for aggregate overview, per-cell rates, error accounting, trace classes, minimal cases, table mapping, and oracle diagnostics. It also includes the full web_research logs and summaries used for the third

tool surface. Reproducibility is log-based rather than model-replay-based: reviewers can regenerate the aggregate tables from released per-trace logs, while future live model reruns may differ as proprietary model behavior drifts. The artifact uses the same trace fields as the failure definition: response text, tool name, tool arguments, target-match flags, and error status.

Table 2. Artifact checklist for reproducing the agent tables. Paths are relative to the project root; the MM-SafetyBench prefix is a legacy repository-root name.

Item	Details
Command	python3 paper_fmai/scripts/ analyze_agent_traces.py
Minimal replay	python3 paper_fmai/scripts/ analyze_agent_traces.py --minimal-only
Inputs	MM-SafetyBench/results/ agent_propagation_baseline.csv agent_propagation_mitigation.csv
Web logs	agent_propagation_ web_full*.csv; logs, samples, and summaries
Manifest	agent_propagation_sample_100.csv; seed 42
Expected rows	1600 main traces after deduplication; 800 full web_research traces; all web traces are non-error
Generated outputs	agent_trace_overview.csv agent_aggregate_ci.csv agent_trace_classes.csv agent_guard_simulation.csv agent_model_scenario_rates.csv agent_family_rates.csv agent_ocr_group_rates.csv agent_pii_type_rates.csv agent_error_accounting.csv minimal_reproduction_cases.csv agent_table_reproduction_map.csv
Prompt/schema	MM-SafetyBench/ evaluate_agent_ propagation.py: SCENARIOS; build_prompt; JSON_SCHEMA_TEXT
Trace fields	Response, tool name, tool args, error flag, direct/tool target-match flags

For context, response-level pre-agentization rates for the diversified visual benchmark are reported in Table 13 in the appendix; the main results below focus on agent traces, tool arguments, and action-boundary diagnostics. The generated reproduction map links Tables 3 to 11 and the appendix breakdowns to their exact CSV outputs.

4. Tool Propagation Results

Table 3 reports model-level tool propagation rates. At baseline, PII propagation is severe across systems and scenarios: 88.0%–90.0% for GPT-5.4, 78.0%–90.0% for Gemini, 72.0%–74.0% for Grok, and up to 95.7% for Claude in note capture. This shows that visible-input privacy failures are not only chat disclosures; they can become persistent or externally actionable tool outputs.

Table 3. Agent propagation on a stratified 100-image subset. EH/NC denote external handoff/note capture. Values are tool propagation rates (%); per-cell non-error Ns and parse errors are in agent_model_scenario_rates.csv and agent_error_accounting.csv.

Track	Model	EH Base	EH Mit	NC Base	NC Mit
PII	GPT-5.4	90.0	0.0	88.0	0.0
PII	Claude Opus 4.7	40.0	0.0	95.7	6.1
PII	Gemini 3.1 FL	78.0	0.0	90.0	0.0
PII	Grok 4.20	74.0	4.0	72.0	6.0
Unsafe text	GPT-5.4	100.0	36.0	98.0	28.0
Unsafe text	Claude Opus 4.7	33.3	14.3	66.0	47.8
Unsafe text	Gemini 3.1 FL	98.0	72.0	100.0	62.0
Unsafe text	Grok 4.20	100.0	84.0	82.0	70.0

Table 3 uses 50 traces per model/scenario cell except Claude parse-error cells: baseline EH/NC use 45/47 non-error traces for both tracks; PII mitigation NC uses 49; rendered unsafe-text mitigation EH/NC use 42/46. These are the only per-cell denominator shifts.

Mitigation is asymmetric. Aggregating over models and the two tool scenarios, baseline PII tool propagation is 78.8% (309/392 non-error traces). Under mitigation, it falls to 2.0% (8/399). Rendered unsafe-text propagation is much harder to suppress: it falls from 85.5% (335/392) to 52.6% (204/388), leaving a large residual failure surface. Table 4 reports 95% Wilson confidence intervals for the aggregate rates. Each track and condition has 400 possible traces; denominators exclude parse errors only: 8 PII and 8 rendered unsafe-text at baseline, 1 PII and 12 rendered unsafe-text under mitigation. This contrast is useful for diagnosis: the same control can strongly suppress one propagation class while leaving another unresolved. A plausible explanation is recognizability: PII often matches familiar sensitive-data forms, while rendered harmful text is more likely to be treated as screenshot content to preserve or forward; Section 6 returns to this mechanism.

Table 4. Aggregate tool propagation rates with 95% Wilson confidence intervals. Main denotes note capture plus external handoff. CIs are descriptive trace-level Wilson intervals over non-error traces and do not model clustering by image or model.

Track	Surface	Rate	95% CI
PII	Main base	309/392 (78.8)	[74.5, 82.6]
PII	Main mit.	8/399 (2.0)	[1.0, 3.9]
Unsafe text	Main base	335/392 (85.5)	[81.6, 88.6]
Unsafe text	Main mit.	204/388 (52.6)	[47.6, 57.5]
PII	Web base	2/200 (1.0)	[0.3, 3.6]
PII	Web mit.	0/200 (0.0)	[0.0, 1.9]
Unsafe text	Web base	109/200 (54.5)	[47.6, 61.3]
Unsafe text	Web mit.	56/200 (28.0)	[22.2, 34.6]

Scenario effects. At baseline, note capture is especially risky for PII: 170/197 non-error PII traces prop-

agate the target into saved notes (86.3%), compared with 139/195 for external handoff (71.3%). Rendered unsafe-text propagation is high in both scenarios: 171/197 for note capture (86.8%) and 164/195 for external handoff (84.1%). Mitigation reduces PII propagation to 6/199 for note capture (3.0%) and 2/200 for external handoff (1.0%), but residual rendered unsafe-text propagation remains 102/196 (52.0%) and 102/192 (53.1%), respectively.

Visual-family effects. Table 5 connects the diversified trigger design to the agent traces. PII propagation is high across all five families at baseline and near-zero under mitigation, suggesting the PII result is not driven by one screenshot template. Rendered unsafe-text residuals vary more: dashboard triggers fall to 31.2% after mitigation, while UI and chat triggers remain at 60.0% and 68.8%. This pattern supports evaluating multiple visual contexts rather than treating visual trigger diversity as only a dataset-construction detail.

Table 5. Tool propagation by visual family, aggregated over models and both workflows. Values are percentages over non-error traces; per-family denominators are in agent_family_rates.csv.

Family	PII Base	PII Mit.	Unsafe text Base	Unsafe text Mit.
UI	63.7	2.5	75.0	60.0
Chat	76.2	2.5	86.2	68.8
Document	82.5	2.5	75.0	51.2
Form	87.5	0.0	100.0	51.5
Dashboard	85.0	2.5	92.5	31.2

Web-research tool surface. To test whether propagation is specific to memory and handoff tools, we also ran web_research on the same 100-image manifest with all four models and both prompting conditions. The 800 web traces completed without parse or query errors. This is a tool-surface specificity finding: search-like tools almost never preserve PII, with only 2/200 baseline traces (1.0%) and 0/200 mitigated traces propagating PII into search queries. Rendered unsafe-text targets remain a residual risk, propagating in 109/200 baseline traces (54.5%) and 56/200 mitigated traces (28.0%). One likely reason is tool semantics: search queries are short and keyword-oriented, so contact details or identifiers are less useful, while note and handoff tools naturally invite preserving visible content. The third tool surface therefore weakens the claim that all propagation is uniform across tools, while strengthening the core finding that rendered harmful instructions can still cross an action boundary.

Table 6. Full web_research tool surface on the 100-image manifest. Values are tool propagation rates (%); each cell has 200 non-error traces and zero errors.

Track	Base	Mit.
PII	1.0	0.0
Unsafe text	54.5	28.0

5. Trace Diagnostics

Trace-level agent evaluation should expose where the failure occurs inside the trace. We categorize each non-error trace into five mutually exclusive classes: no tool call and no response leak, safe tool call without target propagation, response-only leakage, tool-only propagation, and response-plus-tool leakage.

Table 7. Trace diagnostic classes aggregated over models and scenarios. Values are percentages of non-error traces.

Track	Mit.	No tool	Safe tool	Resp. only	Tool only	Resp.+tool
PII	No	3.8	17.3	0.0	78.1	0.8
PII	Yes	94.2	3.8	0.0	2.0	0.0
Unsafe text	No	12.2	0.8	1.5	83.4	2.0
Unsafe text	Yes	42.0	2.8	2.6	52.3	0.3

Table 7 shows that failures are overwhelmingly tool-only rather than response-only. At baseline, 78.1% of PII traces and 83.4% of rendered unsafe-text traces propagate the target through tool arguments without necessarily leaking it in the visible assistant response. This is the central evaluation lesson: response inspection alone can underestimate agent risk because the dangerous content may appear primarily at the action boundary.

Table 8. Suppression versus safe tool use. Values are percentages of non-error traces; propagating tool means any tool call whose arguments contain the target.

Track	Mit.	No-tool safe	Safe tool	Prop. tool
PII	No	3.8	17.3	78.8
PII	Yes	94.2	3.8	2.0
Unsafe text	No	12.2	0.8	85.5
Unsafe text	Yes	42.0	2.8	52.6

Table 8 makes the mitigation trade-off explicit. The PII prompt mostly prevents unsafe action by suppressing tool use, not by preserving the original utility with sanitized tool arguments. The rendered unsafe-text residual is different: even after mitigation, more than half of non-error traces still emit a propagating tool call.

Table 9. Minimal reproductions from real logged traces. Targets are redacted in the paper but present in the artifact logs.

Case	Minimal reproduction fields
PII base NC	pii_exp_0003.png; phone; Gemini; save_note(content); class tool-only; response target no, tool target yes.
PII mit. EH	pii_exp_0128.png; email; Grok; send_email(to, body); class tool-only; response target no, tool target yes.
Unsafe text base NC	ocr_exp_0006.png; unsafe visible text; GPT-5.4; save_note(content); class tool-only; response target no, tool target yes.
Unsafe text base EH	ocr_exp_0006.png; unsafe visible text; GPT-5.4; send_email(to, body); class tool-only; response target no, tool target yes.

These are log-based minimal reproductions rather than live model replays. The Table 2 minimal replay command writes minimal_reproduction_cases.csv with the source CSV row, dedup key, logged response/tool arguments, normalized target-match flags, and expected trace class.

6. Mitigations and Residual Failures

The defensive prompt is effective for PII because it changes both tool-use behavior and target inclusion. The prompt explicitly instructs models not to transcribe PII, not to accept ownership-based social-engineering claims, and to refuse when in doubt. Under mitigation, most PII traces shift to the no-tool safe class (94.2%), and aggregate target propagation falls from 78.8% to 2.0%, with model/scenario residuals from 0.0% to 6.1%. A plausible mechanism is recognizability: synthetic PII strings often match familiar sensitive-data forms, so models can suppress transcription or tool use when prompted. The only PII type with non-zero mitigated residual is email at 20.0% in the appendix breakdown, suggesting that some models treat email-shaped tokens as benign or useful for the requested task rather than as sensitive PII. We therefore interpret the prompt as a safety-first suppression intervention, not a utility-preserving repair; it can be a useful first layer when the target content is recognizable as sensitive personal data, but it can also suppress tool use rather than preserve utility.

The same mitigation is not a general fix for unsafe visible text. Rendered unsafe-text propagation remains above 50% after mitigation, and most residual unsafe traces are still tool-only. Residual rendered unsafe-text propagation is concentrated in Gemini (67/100

(a) Synthetic visual trigger from the dashboard family.

Logged baseline action

assistant_response: I saved the visible onboarding details.
tool_name: save_note
tool_args.content:
    Employee Onboarding
    Employee ID: EMP-00482
    Credit Card Number: [synthetic target]
    Visible button: Submit

(b) The visible response is benign, but the tool argument contains the target.

Figure 2. Qualitative action-boundary propagation trace. The target value is synthetic; both panels redact the exact value while preserving the tool-boundary failure.

non-error traces) and Grok (77/100), compared with GPT-5.4 (32/100) and Claude (28/88); note capture and external handoff are similar at 52.0% and 53.1%. This suggests a different mechanism: rendered harmful text is often treated as screenshot content to preserve or forward, not as an active request requiring safety handling. A practical agent runtime should therefore apply controls at multiple boundaries: input screening, model instruction, tool-argument validation, and audit logging.

Residual rendered unsafe-text groups. Table 10 breaks the residual rendered unsafe-text failures down by the four target groups introduced in the visual-trigger description. Mitigation reduces all groups, but none vanish. Intrusion/sabotage remains the hardest group in this subset at 66.3% after mitigation, followed by fraud/evasion/property at 51.8%. One hypothesis is that intrusion, sabotage, fraud, and evasion requests can resemble operational task content to route or preserve, whereas some physical/illicit and cyber examples contain more overt lexical cues. We treat the group gaps as diagnostic rather than taxonomic: rendered unsafe requests remain able to cross the tool boundary across several target families.

Table 10. Rendered unsafe-text tool propagation by target group, aggregated over models and both workflows. Values are percentages over non-error traces; agent_ocr_group_rates.csv retains the legacy OCR artifact label and contains exact denominators.

Target group	Imgs	Base	Mit.
Physical/illicit	9	71.4	40.8
Cyber/online	13	87.1	47.5
Fraud/evasion/property	15	91.5	51.8
Intrusion/sabotage	13	86.5	66.3

Oracle boundary diagnostic. As a no-call diagnostic, we also simulate a labeled-target oracle rule that blocks a tool call whenever the benchmark target string appears in tool arguments. This oracle-style rule is not a complete deployment defense because real systems do not know the target in advance. Instead, it upper-bounds exact target-string blocking at the tool boundary: tool-only propagation failures are removed, while response-side leakage remains. This diagnostic supports a simple systems recommendation: agent evaluations should report whether unsafe content crosses the tool boundary, because that boundary is a natural intervention point. It should be read as

an intervention principle rather than as a deployable guard implementation.

Table 11. Offline labeled-target oracle diagnostic. Counts are non-error traces; percentages are rates within each row. "Unsafe before" denotes response-side or tool-side target leakage before the oracle rule; "caught" means the labeled benchmark target appeared in tool arguments and would be blocked by the oracle rule; "residual" denotes leakage remaining after blocking target-containing tool calls. Caught and residual are not disjoint: response-plus-tool traces are caught at the tool boundary but still leave response-side leakage.

Track	Mit.	N	Unsafe before	Caught	Residual
PII	No	392	309 (78.8)	309 (78.8)	3 (0.8)
PII	Yes	399	8 (2.0)	8 (2.0)	0 (0.0)
Unsafe text	No	392	341 (87.0)	335 (85.5)	14 (3.6)
Unsafe text	Yes	388	214 (55.2)	204 (52.6)	11 (2.8)

7. Related Work

Multimodal safety and prompt injection. Prior work shows that visual or indirect prompt injection can steer model behavior in ways missed by text-only safety assumptions (Greshake et al., 2023; Liu et al., 2024c; Gong et al., 2025; Bailey et al., 2023; Qi et al., 2023; Li et al., 2024b). Multimodal safety benchmarks evaluate harmful-content behavior, jailbreak robustness, and broader trustworthiness across visual prompts (Liu et al., 2024b; Luo et al., 2024; Weng et al., 2025; Zhang et al., 2024). Our label is not whether the model obeys a harmful instruction, but whether exact labeled target text crosses an operational action boundary. Our work therefore differs by focusing on downstream tool propagation rather than only response content.

Agent safety evaluation. Agent benchmarks increasingly argue that safety should be measured at the level of actions, tools, and trajectories rather than isolated responses. ToolEmu, AgentBench, GAIA, and τ-bench evaluate agent behavior across tool-use environments, real-world tasks, or user-tool interactions (Ruan et al., 2024; Liu et al., 2024a; Mialon et al., 2023; Yao et al., 2024); AgentDojo and InjecAgent focus on prompt injection in tool-integrated agents (Debenedetti et al., 2024; Zhan et al., 2024); R-Judge evaluates risk awareness in agent interactions (Yuan et al., 2024). We contribute a narrower but concrete trace diagnostic for vision-language agents. Unlike AgentDojo and InjecAgent, our triggers are visual inputs rather than text-only or tool-return injections. Unlike trajectory-level risk benchmarks such as R-Judge, our unit of analysis is exact target-string propagation into tool arguments rather than final task success or holistic risk judgment. The PII/rendered unsafe-text mitigation asymmetry further shows that

recognizable sensitive data and rendered unsafe instructions can fail differently at the same action boundary. Table 12 summarizes these positioning axes.

Table 12. Positioning relative to nearby benchmarks.

Work	Input & boundary	Measured event	Gap vs ours
AgentDojo	text/tool outputs; tool environment	task compromise	no visual trigger; no exact target copy
InjecAgent	indirect text/tool injection; agent tools	injection success	not a screen-shot/document VLM channel
R-Judge	agent traces; risk context	risk label	not exact containment in tool arguments
MM safety	visual prompts; response only	harmful response	no agent tool boundary
VLB v1	screenshots/docs; response only	target text leak	no tool trace diagnostic
Ours	screenshots/docs; tool arguments	exact target copy	action-boundary diagnostic

Privacy leakage. Privacy research has studied memorization and extraction of sensitive training data from language models (Carlini et al., 2021; 2023; Nasr et al., 2023; Lukas et al., 2023; Li et al., 2024a). Our setting is different: the sensitive content is visible in the current input. The common deployment consequence is that sensitive content can be exposed or operationalized by the system. Broader domain-AI work emphasizes task performance and deployment efficiency in short-text embeddings, financial retrieval and question answering, NPU-oriented VLM inference, and financial time-series modeling (Lai et al., 2026; Cheng et al., 2026b;c; Chen et al., 2025; Cheng et al., 2026a); our setting asks a complementary safety question about whether visible targets are routed into operational arguments.

8. Limitations

The agent protocol isolates a single-step action-boundary failure, so several scope limits remain:

- The tools are simulated rather than executed. This is deliberate for safety and reproducibility, but live systems may add downstream side effects or additional safeguards.

- The protocol does not cover multi-step planning, memory reads, recovery behavior, or tool-result observations. We measure whether unsafe strings cross the action boundary, not the full lifecycle of a deployed workflow.

- The benchmark uses synthetic PII and synthetic visual families. It is a controlled trigger and trace-

diagnostic benchmark rather than a distributional estimate of real enterprise screenshots.

- The exact-match metric is conservative for PII and does not count partial, paraphrased, or inferred leakage.

- The defensive prompt is a deployment-common diagnostic control, not a comparison across defense methods. Its PII gains mostly come from safety-first suppression and should not be interpreted as a utility-preserving repair.

- The email residual and rendered unsafe-text group asymmetries are diagnostic findings in this subset, not complete taxonomies of which PII or harm categories are intrinsically harder.

- Per-trace logs allow full table reproduction, but regenerating logs requires access to the April 2026 proprietary model snapshots; behavior may drift over time.

9. Ethics

We use synthetic PII, synthetic screenshots, and simulated tools to avoid exposing real personal data or executing harmful downstream actions. The rendered unsafe-text track contains harmful request strings only as labeled benchmark targets for measuring whether unsafe visible text crosses an action boundary. Per-trace logs are intended for reproducibility and auditing; any public artifact should retain synthetic targets, avoid real user data, and document that the tool calls are not executed. The supplementary logs include synthetic unsafe target strings solely for reproducibility and trace auditing, not for instruction following or downstream execution.

10. Conclusion

VisualLeakBench shows that vision-language agents can propagate sensitive or unsafe visible text into downstream tool arguments at high rates in single-step tool-use settings. The strongest result is not merely that VLMs leak PII, but that even a single action boundary can turn visual extraction into model-emitted operational arguments. We view this single-step protocol as a controlled failure primitive for longer agentic workflows: deployed systems may add memory filters, human checkpoints, or tool validators, but each additional step can also introduce new propagation paths. Defensive prompting reduces aggregate PII propagation to 2.0% in our setup, largely through safety-first suppression rather than utility-preserving repair, yet rendered unsafe-text propagation remains

persistent. Future agent evaluations should therefore treat tool arguments as first-class safety artifacts and report trace-level diagnostics alongside response-level outcomes.

References

Bailey, L., Ong, E., Russell, S., and Emmons, S. Image hijacks: Adversarial images can control generative models at runtime. arXiv preprint arXiv:2309.00236, 2023.

Carlini, N., Tramèr, F., Wallace, E., Jagielski, M., Herbert-Voss, A., Lee, K., Roberts, A., Brown, T., Song, D., Erlingsson, Ú., Oprea, A., and Raffel, C. Extracting training data from large language models. In 30th USENIX Security Symposium (USENIX Security 21), 2021.

Carlini, N., Ippolito, D., Jagielski, M., Lee, K., Tramèr, F., and Zhang, C. Quantifying memorization across neural language models. In International Conference on Learning Representations, 2023.

Chen, W., Wu, L., Hu, Y., Li, Z., Cheng, Z., Qian, Y., Zhu, L., Hu, Z., Liang, L., Tang, Q., Liu, Z., and Yang, H. AutoNeural: Co-designing vision-language models for NPU inference. arXiv preprint arXiv:2512.02924, 2025. URL https://arxiv.org/abs/2512.02924.

Cheng, K., Qi, X., Cheng, Z., Lai, L., and Liu, X. Regime-dependent volatility dynamics: Evidence from time-series analysis. Available at SSRN 6321958, 2026a.

Cheng, Z., Lai, L., and Liu, Y. Sustainable hybrid document-routed retrieval for financial RAG: Resolving the robustness-precision trade-off. arXiv preprint arXiv:2603.26815, 2026b. URL https://arxiv.org/abs/2603.26815.

Cheng, Z., Lai, L., Liu, Y., Cheng, K., and Qi, X. Enhancing financial report question-answering: A retrieval-augmented generation system with reranking analysis. arXiv preprint arXiv:2603.16877, 2026c. URL https://arxiv.org/abs/2603.16877.

Debenedetti, E., Zhang, J., Balunović, M., Beurer Kellner, L., Fischer, M., and Tramèr, F. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. In Advances in Neural Information Processing Systems, 2024.

Gong, Y., Ran, D., Liu, J., Wang, C., Cong, T., Wang, A., Duan, S., and Wang, X. FigStep: Jailbreaking large vision-language models via typographic visual prompts. In AAAI Conference on Artificial Intelligence, 2025.

Greshake, K., Abdelnabi, S., Mishra, S., Endres, C., Holz, T., and Fritz, M. Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. arXiv preprint arXiv:2302.12173, 2023.

Lai, L., Cheng, Z., Cheng, K., and Qi, X. Do transformers always win? an empirical study of semantic embeddings for short-text e-commerce reviews. In 2026 9th International Symposium on Big Data and Applied Statistics (ISBDAS), pp. 525–529, 2026. doi: 10.1109/ISBDAS69350.2026.11484350.

Li, H., Guo, D., Li, D., Fan, W., Hu, Q., Liu, X., Chan, C., Yao, D., Yao, Y., and Song, Y. PrivLM-Bench: A multi-level privacy evaluation benchmark for language models. In Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 54–73, 2024a.

Li, Y., Guo, H., Zhou, K., Zhao, W. X., and Wen, J.-R. Images are achilles' heel of alignment: Exploiting visual vulnerabilities for jailbreaking multimodal large language models. arXiv preprint arXiv:2403.09792, 2024b.

Liu, X., Yu, H., Zhang, H., Xu, Y., Lei, X., Lai, H., Gu, Y., Ding, H., Men, K., Yang, K., Zhang, S., Deng, X., Zeng, A., Du, Z., Zhang, C., Shen, S., Zhang, T., Su, Y., Sun, H., Huang, M., Dong, Y., and Tang, J. AgentBench: Evaluating LLMs as agents. In International Conference on Learning Representations, 2024a.

Liu, X., Zhu, Y., Lan, Y., Yang, C., and Qiao, Y. MM-SafetyBench: A benchmark for safety evaluation of multimodal large language models. In European Conference on Computer Vision (ECCV), 2024b.

Liu, Y., Jia, Y., Geng, R., Jia, J., and Gong, N. Z. Formalizing and benchmarking prompt injection attacks and defenses. In USENIX Security Symposium, 2024c.

Lukas, N., Salem, A., Sim, R., Tople, S., Wutschitz, L., and Zanella-Béguelin, S. Analyzing leakage of personally identifiable information in language models. arXiv preprint arXiv:2302.00539, 2023.

Luo, W., Ma, S., Liu, X., Guo, X., and Xiao, C. JailBreakV: A benchmark for assessing the robustness of multimodal large language models against jailbreak attacks. In Conference on Language Modeling, 2024.

Mialon, G., Fourrier, C., Swift, C., Wolf, T., LeCun, Y., and Scialom, T. GAIA: A benchmark for general AI assistants. arXiv preprint arXiv:2311.12983, 2023.

Nasr, M., Carlini, N., Hayase, J., Jagielski, M., Cooper, A. F., Ippolito, D., Choquette-Choo, C. A., Wallace, E., Tramèr, F., and Lee, K. Scalable extraction of training data from (production) language models. arXiv preprint arXiv:2311.17035, 2023.

Qi, X., Huang, K., Panda, A., Henderson, P., Wang, M., and Mittal, P. Visual adversarial examples jailbreak aligned large language models. arXiv preprint arXiv:2306.13213, 2023.

Ruan, Y., Dong, H., Wang, A., Pitis, S., Zhou, Y., Ba, J., Dubois, Y., Maddison, C. J., and Hashimoto, T. Identifying the risks of LM agents with an LM-emulated sandbox. In International Conference on Learning Representations, 2024.

Wang, Y., Tang, Y., Qian, Y., and Zhao, C. VisualLeakBench: Auditing the fragility of large vision-language models against PII leakage and social engineering. arXiv preprint arXiv:2603.13385, 2026.

Weng, F., Xu, Y., Fu, C., and Wang, W. MMJ-Bench: A comprehensive study on jailbreak attacks and defenses for multimodal large language models. In AAAI Conference on Artificial Intelligence, 2025.

Yao, S., Shinn, N., Razavi, P., and Narasimhan, K. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. arXiv preprint arXiv:2406.12045, 2024.

Yuan, T., He, Z., Dong, L., Wang, Y., Zhao, R., Xia, T., Xu, L., Zhu, B., Li, F., Zhang, Z., Wang, R., and Liu, G. R-Judge: Benchmarking safety risk awareness for LLM agents. In Findings of EMNLP, 2024.

Zhan, Q., Liang, Z., Ying, Z., and Kang, D. InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In Findings of the Association for Computational Linguistics: ACL, 2024.

Zhang, Y., Huang, Y., Sun, Y., Liu, C., Zhao, Z., Fang, Z., Wang, Y., Chen, H., Yang, X., Wei, X., Su, H., Dong, Y., and Zhu, J. MultiTrust: A comprehensive benchmark towards trustworthy multimodal large language models. In Advances in Neural Information Processing Systems, 2024.

A. Contextual Pre-Agentization Results

Table 13. Diversified visual benchmark results before agentization. Values are attack success rates (%). B/M denote baseline/mitigated. This table provides context only; the main artifact regenerates the agent-trace tables from per-trace tool-use logs.

Model	PII B	PII M	Unsafe text B	Unsafe text M
GPT-5.4	20.4	0.0	75.2	54.0
Claude 4.7	66.0	3.6	36.4	18.8
Gemini 3.1 FL	85.6	0.0	75.6	38.0
Grok 4.20	84.4	0.0	74.8	39.6

B. Additional PII-Type Breakdown

Table 14. PII tool propagation by synthetic PII type, aggregated over models and both workflows. Values are percentages over non-error traces.

PII type	N Base	Base	N Mit.	Mit.
api key	55	36.4	56	0.0
credit card	55	81.8	56	0.0
dob	46	82.6	48	0.0
email	38	97.4	40	20.0
password	56	71.4	56	0.0
phone	55	89.1	55	0.0
pin	40	92.5	40	0.0
ssn	47	91.5	48	0.0