Roto-translated Local Coordinate Frames For Interacting Dynamical Systems

Abstract

Modelling interactions is critical in learning complex dynamical systems, namely systems of interacting objects with highly non-linear and time-dependent behaviour. A large class of such systems can be formalized as *geometric graphs*, *i.e.*, graphs with nodes positioned in the Euclidean space given an *arbitrarily* chosen global coordinate system, for instance vehicles in a traffic scene. Notwithstanding the arbitrary global coordinate system, the governing dynamics of the respective dynamical systems are invariant to rotations and translations, also known as *Galilean invariance*. As ignoring these invariances leads to worse generalization, in this work we propose local coordinate frames per node-object to induce roto-translation invariance to the geometric graph of the interacting dynamical system. Further, the local coordinate frames allow for a natural definition of anisotropic filtering in graph neural networks. Experiments in traffic scenes, 3D motion capture, and colliding particles demonstrate that the proposed approach comfortably outperforms the recent state-of-the-art.

1 Introduction

Modelling interacting dynamical systems –systems of interacting objects with highly non-linear and time-dependent behaviour– with neural networks is attracting a significant amount of interest [25, 3, 20] for its potential to learn long-term behaviours directly from observations. A large class of these systems consists of objects in the physical space, for instance pedestrians in a traffic scene [30, 36] or colliding subatomic particles [5]. These systems can be formalized as *geometric graphs*, in which the nodes describe the physical coordinates of the objects among other features. Kipf et al. [25] introduced Neural Relational Inference (NRI) to learn geometric graph dynamical systems using the variational autoencoding framework [24, 37]. Following [25], dynamic NRI [20] advocated sequential latent variable models to encode time-transient behaviours. Both approaches and the majority of learning algorithms for dynamical systems assume an *arbitrary global coordinate system* to encode time-transient interactions and model complex behaviours. In this work we posit that taking into account the relative nature of dynamics is key to accurate modelling of interacting dynamical systems.

Represented by geometric graphs, learning algorithms of dynamical systems subscribe themselves to the Newtonian space. The absolute notion of Newtonian space and mechanics, however, determines that there exist infinite inertial frames that connect with each other by a rotation and translation. Each of these inertial frames is equivalent in that they can all serve as global coordinate frames and, thus, an arbitrary choice is made. Notwithstanding this arbitrariness, the dynamics of the system are invariant to the choice of a global coordinate frame up to a rotation and translation, in what is also known as *Galilean invariance*. Put otherwise, geometric graphs of interacting dynamical systems often exhibit symmetries that if left to their own devices lead models to subpar learning.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Inspired by the notion of Galilean invariance, we focus on inducing roto-translation invariance in interacting dynamical systems and their geometric graphs to sustain the effects of underlying pathological symmetries. Symmetries, invariances and equivariances have attracted an increased interest with learning algorithms in the late years [11, 12, 52, 53, 45, 18]. The reason is that with the increasing complexity of new tasks and data, exploiting the symmetries improves sample efficiency [18, 40] by requiring fewer data points and gradient updates. To date the majority of works on exploiting symmetries or data augmentations are with static data [11, 43, 53]. We argue and show that invariance in representations of dynamic data is just as important, if not more, as it is critical in accounting for the inevitable increased pattern complexity and non-stationarity.

We induce roto-translation invariant representations in graphs by local coordinate frames. Each local coordinate frame is centered at a node-object in the geometric graph and rotated to match its angular position –yaw, pitch, and roll. Since all intermediate operations are performed on the local coordinate frames, the graph neural network is roto-translation invariant and the final transformed output is roto-translation equivariant. We obtain equivariance to global roto-translations by an inverse rotation that transforms the predictions back to the global coordinates.

We make the following three contributions. First, we introduce canonicalized roto-translated local coordinate frames for interacting dynamical systems formalized in geometric graphs. Second, by operating solely on these coordinate frames, we enable roto-translation invariant edge prediction and roto-translation equivariant trajectory forecasting. Third, we present a novel methodology for natural anisotropic continuous filters based on relative linear and angular positions of neighboring objects in the canonicalized local coordinate frames. We continue with a brief introduction of relevant background and then the description of our method. We present related work and finish with experiments and ablation studies on a number of settings, including modelling pedestrians in 2D traffic scenes, 3D particles colliding, and 3D human motion capture systems.

2 Background

2.1 Interacting dynamical systems and geometric graphs

An interacting dynamical system consists of $i = 1, \ldots, N_t$ objects, whose position $\mathbf{p} = (p_x, p_y, p_z)^\top$ and velocity $\mathbf{u} = \frac{d\mathbf{p}}{dt} = (u_x, u_y, u_z)^\top$ in the Euclidean space are recorded over time t. The state of the i-th object at timestep t is described by $\mathbf{x}_i^t = [\mathbf{p}_i^t, \mathbf{u}_i^t]$, adopting for clarity a column vector notation and using $[\cdot, \cdot]$ to denote vector concatenation.

Over the past few years, a natural way that has emerged for organizing interacting dynamical systems is by geometric graphs [3, 25, 20] through space and time, $\mathcal{G} = \{\mathcal{G}^t\}_{t=1}^T$, where $\mathcal{G}^t = (\mathcal{V}^t, \mathcal{E}^t)$ is the snapshot of the graph at timestep t. The nodes $\mathcal{V}^t = \{v_1^t, \ldots, v_{N_t}^t\}$ of the graph correspond to the objects in the dynamical system, with v_i^t corresponding to the state of the i-th object, $\mathbf{x}_i^t$. The edges $\mathcal{E}^t \subseteq \{e_{j,i}^t = (v_j^t, v_i^t) \mid (v_j^t, v_i^t) \in \mathcal{V}^t \times \mathcal{V}^t\}$ of the graph, correspond to the interactions from node-object j to node-object i. We use $\mathcal{N}(i)$ to denote the graph neighbours of node v_i. In the absence of domain knowledge about how objects connect, for instance the links between atoms in molecules, the graph is fully connected. Explicit inference of the graph structure can be achieved by using latent edges $\mathbf{z}_{j,i}^t$ corresponding to the edges $e_{j,i}^t$.

Graph neural networks [41, 31, 19] exchange messages between neighbors and update the vertex and edge embeddings per layer, commonly referred to as message passing

$$\mathbf{h}_{j,i}^{(l)} = f_e^{(l)}\left(\left[\mathbf{h}_i^{(l-1)}, \mathbf{h}_{j,i}^{(l-1)}, \mathbf{h}_j^{(l-1)}\right]\right) \tag{1}$$

$$\mathbf{h}_i^{(l)} = f_v^{(l)}\left(\mathbf{h}_i^{(l-1)}, \underset{j \in \mathcal{N}(i)}{\square} \mathbf{h}_{j,i}^{(l)}\right), \tag{2}$$

where $\mathbf{h}_i^{(l)}$ is the embedding of node v_i at layer l and $\mathbf{h}_{j,i}^{(l)}$ is the embedding of edge $e_{j,i}$ at layer l. f_e, f_v denote differentiable functions such as MLPs and $\square$ denotes a permutation invariant function, commonly a summation or an average. Many graph neural networks rely on isotropic filters [26], although various ways [46, 35] to circumvent this constraint have also been explored.

Figure 1: In (a), objects positioned in the global 2D coordinate frame; arrows represent orientations. In (b)-(e), objects in the canonicalized local coordinate frames, translated to match the target object's position and rotated to match its orientation

2.2 Neural relational inference

Kipf et al. [25] proposed neural relational inference (NRI), a variational autoencoding inference model [24, 37] that explicitly infers the graph structure over a discrete latent graph and simultaneously learns the dynamical system. Given the input trajectories the encoder learns to infer interactions as latent edges $\mathbf{z}_{j,i} \in [0,1]^K$, sampled from a concrete distribution [33, 23] with K edge types. The decoder receives the inferred interactions and the past trajectories, and learns the dynamical system, $p_\theta(\mathbf{x}|\mathbf{z}) = \prod_{t=1}^{T} p_\theta(\mathbf{x}^{t+1}|\mathbf{x}^{1:t}, \mathbf{z})$. The encoder is a regular graph neural network without explicitly taking time into account and learns to infer latent interactions by maximizing the evidence lower bound for the next time step. The decoder is another graph neural network that either assumes Markovian dynamics $p_\theta(\mathbf{x}^{t+1}|\mathbf{x}^{1:t}, \mathbf{z}) = p_\theta(\mathbf{x}^{t+1}|\mathbf{x}^t, \mathbf{z})$ or is recurrent through time. As the prior and encoder in NRI assume static interactions (*e.g.* whether forces between charged particles are attractive or repulsive), dynamic NRI [20] replaces them with a sequential relation prior based on past states, $p_\phi(\mathbf{z}|\mathbf{x}) = \prod_{t=1}^{T} p_\phi(\mathbf{z}^t|\mathbf{x}^{1:t}, \mathbf{z}^{1:t-1})$, and an approximate relation posterior based on both the past and future states. The decoder is also reformulated as $p_\theta(\mathbf{x}|\mathbf{z}) = \prod_{t=1}^{T} p_\theta(\mathbf{x}^{t+1}|\mathbf{x}^{1:t}, \mathbf{z}^{1:t})$, taking into account the dynamic nature of interactions.

2.3 Invariance and equivariance

Last, we give a very brief introduction to invariance and equivariance. A function $f : \mathcal{X} \to \mathcal{Y}$ is equivariant [53] under a group of transformations if every transformation $\pi \in \Pi$ of the input $\mathbf{x} \in \mathcal{X}$ can be associated with a transformation $\psi \in \Psi$ of the output, $\psi[f(\mathbf{x})] = f(\pi[\mathbf{x}])$. A special case is invariance, where $\Psi = \{\mathbb{I}\}$, the identity transformation, $f(\mathbf{x}) = f(\pi[\mathbf{x}])$.

In this work, we are interested in translation, *i.e.*, $f(\mathbf{x}) + \boldsymbol{\tau} = f(\mathbf{x} + \boldsymbol{\tau})$ with the translation vector $\boldsymbol{\tau}$, and rotation invariance/equivariance, *i.e.*, $\mathbf{Q}f(\mathbf{x}) = f(\mathbf{Q}\mathbf{x})$ using the rotation matrix $\mathbf{Q}$.

3 Roto-translation invariance with local coordinate frames

In this section we present our method, termed LoCS (**Lo**cal **C**oordinate frame**S**). We start with the derivation of roto-translated local coordinate frames and continue with the formulation of graph networks and continuous anisotropic filters operating in these frames.

3.1 Local coordinate frames

Starting from the spatio-temporal graph $\mathcal{G}$, we focus for clarity on pairs of node-objects in the same time step, $\mathbf{x}_i^t, \mathbf{x}_j^t$. In the real world objects are not point particles and have a spatial extension. Central to our method is the use of the angular positions $\boldsymbol{\omega} = (\theta, \phi, \psi)^\top$, otherwise known as yaw, pitch and roll, that describe the orientation of a rigid body with respect to the axes of the coordinate system. We, thus, augment the states $\mathbf{x}_i^t$ with the angular positions, using $\mathbf{v}_i^t = [\mathbf{p}_i^t, \boldsymbol{\omega}_i^t, \mathbf{u}_i^t]$ to denote the augmented state that captures the angular position as well as the linear position and velocity.

Our method draws inspiration from Galilean invariance and inertial frames of reference that capture the relative locations and motions of all the objects in a system. We introduce N_t local coordinate frames, one per object in the system. For the i-th object a local coordinate frame is one in which both the linear and the angular position lie on the origin. By the adoption of the local coordinates with respect to object-centric frames the behaviors between objects will not depend on the arbitrary positions of objects in the absolute Newtonian space. In other words, the local coordinates offer invariance to global translations and rotations and do not bias the learning algorithm. Our goal, thereby, is to compute the relative local coordinates of all objects $j = 1, \ldots, N_t$, while iterating over the i-th reference object.

The transformation from global to local coordinate systems is in two steps. Per target node, we first translate the origin to match its linear position by a translation transformation. Since velocities and angular positions are translation invariant, we only need to perform the translation to the linear positions. This gives us the relative positions $\mathbf{r}_{j,i}^t = \left[\mathbf{p}_j^t - \mathbf{p}_i^t \right]$. Then, we canonicalize the local coordinate frame to match the target object's orientation by a rotation transformation, described by the rotation matrix $\mathbf{Q}(\boldsymbol{\omega}_i)$. The coordinates of all other objects are analogously transformed given the i-th local coordinate frame. The rotations are performed independently and equivalently to the state components of the j-th object, namely the relative –due to the translation transformation performed first– linear positions, the angular positions and the velocities. Using tensor operations, we compactly write down the transformed state as:

$$\tilde{\mathbf{R}}(\boldsymbol{\omega}) = \mathbf{Q}(\boldsymbol{\omega}) \oplus \mathbf{Q}(\boldsymbol{\omega}) \oplus \mathbf{Q}(\boldsymbol{\omega}) \tag{3}$$

$$\mathbf{v}_{j|i}^t = \tilde{\mathbf{R}}_i^{t\top} \left[\mathbf{r}_{j,i}^t, \boldsymbol{\omega}_j^t, \mathbf{u}_j^t \right] \tag{4}$$

where $\oplus$ denotes the direct sum operator that concatenates two matrices along the diagonal resulting in a block diagonal matrix and $\tilde{\mathbf{R}}_i^{t\top} = \tilde{\mathbf{R}}^\top(\boldsymbol{\omega}_i^t)$ to reduce notation clutter. The rotation matrix in eq. (3) has three entries. Each $\mathbf{Q}(\boldsymbol{\omega})$ independently transforms the relative linear positions, the angular positions and the velocities. Following the notation introduced above, we also define the matrix $\mathbf{R}_i = \mathbf{R}(\boldsymbol{\omega}_i) = \mathbf{Q}(\boldsymbol{\omega}_i) \oplus \mathbf{Q}(\boldsymbol{\omega}_i)$ that will be used later to rotate the non-augmented states $\mathbf{x}_i^t$.

Local coordinate frames in 2D We start with the simpler case where the dynamical system resides in the 2D Euclidean space, for instance pedestrians in a traffic scene. In 2 dimensions, the angular position is a scalar value, namely the yaw angle θ. Thus, the rotation matrix for a target node v_i is:

$$\mathbf{Q}(\boldsymbol{\omega}_i) = \mathbf{Q}(\theta_i) = \begin{pmatrix} \cos\theta_i & -\sin\theta_i \\ \sin\theta_i & \cos\theta_i \end{pmatrix} \tag{5}$$

Local coordinate frames in 3D When in the 3D Newtonian space the chain of transformations is the same; first, we translate the origin to match each target node's linear position, and then we rotate the local coordinate frames to match each object's orientation. The translation transformation is identical to the 2D case. However, the rotation transformation is more involved. For the 3D case, we must decompose $\mathbf{Q}(\boldsymbol{\omega})$ into 3 chained elemental rotations, described by the matrices $\mathbf{Q}_z(\theta)$, $\mathbf{Q}_y(\phi)$ and $\mathbf{Q}_x(\psi)$. $\mathbf{Q}_z(\theta)$ describes a rotation around the z-axis by an angle θ, $\mathbf{Q}_y(\phi)$ describes a rotation around the y-axis by an angle ϕ and $\mathbf{Q}_x(\psi)$ describes a rotation around the x-axis by an angle ψ. We use the following convention that dictates the order of rotations, $\mathbf{Q}(\boldsymbol{\omega}) = \mathbf{Q}_z(\theta)\mathbf{Q}_y(\phi)\mathbf{Q}_x(\psi)$. Each elemental rotation matrix has similar structure to eq. (5). We provide the complete description of all rotation matrices in appendix A.2. After the computation of the rotation matrix, the states are transformed identically to eq. (4).

The local coordinate frames are invariant with respect to global translations and rotations, either in 2 or 3 dimensions. We provide the detailed derivations of $\mathbf{Q}(\boldsymbol{\omega})$ for the 2D and 3D case in appendices A.1 and A.2, respectively, and a detailed proof in appendix A.3.

3.2 Approximate angular positions

In practice, we do not always have perfect information about the object states, such as the angular positions. In this case, we can approximate them using the angles of the velocity vector as a proxy. Specifically, in 2 dimensions, the angular position is a scalar value and is approximated using the azimuth angle of the polar representation of the velocity vector, $\theta = \tan^{-1}(u_y/u_x)$. In 3 dimensions, we transform velocities to spherical coordinates $(u_\rho, u_\theta, u_\phi)$ and use these angles to rotate the local

coordinate frame and approximate 2 out of the 3 angles. The angle θ is computed as above and $\phi = \cos^{-1}(u_z/\|\mathbf{u}\|_2)$. In this case, we retain invariance for the coordinates for which we have perfect knowledge, while we will have an invariance leakage for the approximate ones. That said, experiments show there is little to no consequences and accurate predictions are still attained.

3.3 Local coordinate frame graph neural networks

Having canonicalized the object states in the interacting system, we obtain representations that are invariant to global translations and rotations. Following [20], we formulate the core of the network as a variational autoencoder [24, 37] with latent edge types that change dynamically over time. The network receives the canonicalized representations as input and operates solely on the local coordinate systems. We infer the graph structure over a discrete latent graph and simultaneously learn the dynamical system. Learning the graph structure is a roto-translation invariant task; we want to predict the same edge distribution for each pair of vertices regardless of the global rotation of translation. In contrast, trajectory forecasting is a roto-translation equivariant task; a global translation and rotation to the input trajectories should affect the output trajectories equivalently. Following [20], we maximize the evidence lower bound, $\mathcal{L}(\phi, \theta) = \mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log p_\theta(\mathbf{x}|\mathbf{z})] - \text{KL}[q_\phi(\mathbf{z}|\mathbf{x})||p_\phi(\mathbf{z}|\mathbf{x})]$. We provide the exact form of the loss components in appendix B.1.

Encoder and prior Our encoder and prior closely follow [20], described in section 2.2. First, we compute the local coordinate frame representations $\mathbf{v}_{j|i}^t$ per pair j, i (including self-loops) and per timestep t according to eq. (4). We then perform a number of message passing steps and obtain a feature vector per object pair. Omitting time indices for clarity, we have

$$\mathbf{h}_{j,i}^{(1)} = f_e^{(1)}\left(\left[\mathbf{v}_{j|i}, \mathbf{v}_{i|i}\right]\right) \tag{6}$$

$$\mathbf{h}_i^{(1)} = f_v^{(1)}\left(g_v^{(1)}\left(\mathbf{v}_{i|i}\right) + \frac{1}{|\mathcal{N}(i)|}\sum_{j \in \mathcal{N}(i)}\mathbf{h}_{j,i}^{(1)}\right) \tag{7}$$

$$\mathbf{h}_{j,i}^{(2)} = f_e^{(2)}\left(\left[\mathbf{h}_i^{(1)}, \mathbf{h}_{j,i}^{(1)}, \mathbf{h}_j^{(1)}\right]\right) \tag{8}$$

The functions $f_e^{(1)}, f_v^{(1)}, f_e^{(2)}$ are MLPs and $g_v^{(1)}$ is a linear layer. We feed the embeddings $\mathbf{h}_{j,i}^{(2)}$ into 2 LSTMs: one forward in time that computes the prior and one backwards in time for the encoder. The hidden state from the forward LSTM is used to compute the prior distribution, while the hidden states from both the forward and the backward LSTM are concatenated to compute the encoder distribution. The formulation is identical to [20]; the exact details can be found in appendix B.1.

During training, we sample interactions $\mathbf{z}_{j,i}^t$ from $q_\phi\left(\mathbf{z}_{j,i}^t|\mathbf{x}\right)$ using Gumbel-Softmax [33, 23]. We perform teacher-forcing during the whole training, and task the model to predict the trajectories only for one step ahead. During inference, we sample interactions from the prior distribution.

Decoder As mentioned in section 2.2, the decoder $p_\theta(\mathbf{x}|\mathbf{z}) = \prod_{t=1}^{T} p_\theta(\mathbf{x}^{t+1}|\mathbf{x}^{1:t}, \mathbf{z}^{1:t})$ is tasked with predicting future trajectories given past and present trajectories as well as the predicted relations. As proposed by [20, 25] we can have either a Markovian or a recurrent decoder, depending on the governing dynamics. In many settings, like colliding elementary particles in physics, the governing dynamics satisfy the Markov property, $p_\theta(\mathbf{x}^{t+1}|\mathbf{x}^{1:t}, \mathbf{z}^{1:t}) = p_\theta(\mathbf{x}^{t+1}|\mathbf{x}^t, \mathbf{z}^t)$. In this case, the decoder is implemented with a graph neural network similar to [20]. In many real-world applications, however, the Markovian assumption does not hold. In that case, the graph neural network also features a GRU unit that learns a recurrent hidden state during the message passing.

We can use local coordinates frames with both types of decoders, as defined in [20, 25], with the difference that the message passing is performed with the local coordinate frame representations $\mathbf{v}_{j|i}^t$, so that we attain roto-translation invariance,

$$\mathbf{m}_{j,i}^t = \sum_k z_{(j,i),k}^t f^k\left(\left[\mathbf{v}_{j|i}^t, \mathbf{v}_{i|i}^t\right]\right) \tag{9}$$

$$\mathbf{m}_i^t = f_v^{(3)}\left(g_v^{(3)}\left(\mathbf{v}_{i|i}^t\right) + \frac{1}{|\mathcal{N}(i)|}\sum_{j \in \mathcal{N}(i)}\mathbf{m}_{j,i}^t\right). \tag{10}$$

The output of the model per time step comprises the position and velocity predictions for the next time step. As common in the literature [20], we predict the difference in position and velocity from the previous time step, which equals the velocity and acceleration respectively, and numerically integrate to make predictions. While the computations up to the output layer are roto-translation invariant, the output prediction must be roto-translation equivariant, so that global roto-translation to the inputs affect the outputs equivalently. To transform predictions back to the global coordinate frame and achieve roto-translation equivariance, we do an inverse rotation, and then integrate numerically, *i.e.*, $\mathbf{x}_i^{t+1} = \mathbf{x}_i^t + \mathbf{R}_i^t \cdot \boldsymbol{\Delta}\mathbf{x}_i^{t+1}$. We provide the definitions for both decoders in appendix B.1 and a detailed proof on equivariance to global rotations and translations in appendix A.3.

3.4 Anisotropic filtering

One of the main reasons why filters in graph neural networks are isotropic is the inherent absence of an invariant coordinate frame. In a geometric graph dynamical system, object positions can serve this role. We, thus, use the local roto-translation invariant coordinate frames for anisotropic filtering, using weights that depend on the relative linear positions and angular positions of objects given the central i-th object. Similar to [44], our filter generating network, implemented by an MLP, is a matrix field that maps relative positions and orientation tuples to graph network filters, *i.e.* weight matrices, $\mathbf{W}_{\mathcal{F}} : \mathbb{R}^D \times \mathcal{S}^{|\boldsymbol{\omega}|} \to \mathbb{R}^{D_{\mathrm{out}} \times D_{\mathrm{in}}}$. The anisotropic filters replace the isotropic ones in updating the latent edge representations, weighing neighbors according to their positions,

$$\mathbf{h}_{j,i}^t = \mathbf{W}_{\mathcal{F}}\big(\big[\mathbf{r}_{j,i}^t, \boldsymbol{\omega}_j^t\big]\big) \cdot \Big[\mathbf{v}_{j|i}^t, \mathbf{v}_{i|i}^t\Big].$$

3.5 Data normalization

While the graph neural networks are roto-translation invariant and equivariant in the intermediate and the output layers respectively, we must also make sure that the pre- and post-processing of data are appropriate. The common practices of min-max normalization or z-score normalization are unsuitable because they anisotropically scale and translate the input and output position and velocities. That is, these transformations change the directions of the velocity vectors non-equivalently. We instead opt for a much simpler data normalization scheme that is suitable for roto-translation invariance with local coordinate frames. We scale the inputs, both positions and velocities, by the maximum speed (velocity norm) in the training set, $s_{\mathrm{max}} = \max_i \|\mathbf{u}_i\|$, that is $\mathbf{x}' = \mathbf{S}^{-1}\mathbf{x}$, where $\mathbf{S} = \mathrm{diag}(s_{\mathrm{max}} \cdot \mathbf{1})$. During post-processing, we can convert our predictions to actual units, *e.g.* m and m/s, by applying the inverse transformation, $\mathbf{x} = \mathbf{S}\mathbf{x}'$. We term this operation *speed normalization*.

4 Related work

Learning dynamical systems & trajectory forecasting In the late years, and alongside NRI [25] and dNRI [20], many have studied learning dynamical systems [3, 39]. Further, many works have focused on the problems of pedestrian motion prediction and traffic scene trajectory forecasting [1, 27, 22, 34, 38]. A number of works [1, 38] uses distance-based heuristics to create the graph adjacency and estimate interactions. Kosaraju et al. [27] use self-attention to predict the influence of neighbouring nodes. Both approaches are different from our work, since we explicitly predict the latent graph structure and perform inference on it.

Equivariant deep learning Equivariant neural networks [11, 12, 52, 53, 45] have risen in popularity over the past few years, demonstrating high effectiveness and parameter efficiency. Schütt et al. [43] use radial basis functions on pair-wise node distances to generate continuous filters and perform message passing using depth-wise separable convolutions. Fuchs et al. [18] introduce SE(3)-transformers by incorporating spherical harmonics in a transformer network, resulting in a 3D roto-translation equivariant attention network. de Haan et al. [14] propose anisotropic gauge equivariant kernels for graph networks on meshes based on neighbouring vertex angles and parallel transport. Walters et al. [49] propose rotationally equivariant continuous convolutions for 2D trajectory prediction. Closer to our work is the work of Satorras et al. [40]. They propose a graph network that leverages the rotation equivariant relative position and roto-translation invariant euclidean distance between node pairs in a novel message passing scheme that updates node features as well as node coordinate embeddings. Different from our work, they do not capitalize on orientations and velocities

Figure 2: Results on synthetic dataset

of neighboring objects. Our work leverages these impactful quantities expressed in local coordinate frames to make more reliable predictions.

Anisotropic filtering Graph neural networks [41, 31, 19] have been used extensively for modeling dynamical systems [54, 34, 25, 20, 3]. Several works [34] incorporate isotropic graph filters [26, 21] as part of the graph network. However, these isotropic filters have a global weight sharing scheme, *i.e.* they use a single weight matrix for all neighbours, which amounts to a linear transformation over the aggregated neighbour information. Veličković et al. [46] use self-attention [2] and [35] use Gaussian Mixture Models (GMMs) based on relative neighbour positions.

Other works address this issue by proposing continuous filters on graphs and point clouds [13, 50, 44, 49, 43, 17]. Highly related to our work is the work of Simonovsky and Komodakis [44]. They generalize convolution to arbitrary graphs and introduce dynamically generated filters based on edge attributes to perform continuous anisotropic convolutions on graph signals and point clouds. Differently, though, they do not operate under roto-translated local coordinate systems. This results in diminished parameter efficiency and weight sharing that they compensate for with data augmentation.

5 Experiments

We evaluate the proposed method, LoCS, on 2D and 3D geometric graph dynamical systems from the literature. In 2D, we evaluate on a synthetic physics simulation dataset proposed by dNRI [20] and on traffic trajectory forecasting [4]. In 3D, we evaluate on an 3D-extended version of the charged particles [25] and on a motion capture dataset [10]. We compare with NRI [25], dNRI [20], and the very recent EGNN [40]. For all methods we use publicly available code from [20, 40]. For EGNN, we autoregressively feed the output as the input to the next timestep. The full implementations details are in appendix B.3. We will share all code, data, and models upon publication.

Our architecture closely follows dNRI[26, 20]. Unless otherwise specified, all common layers have the same structure, and we use the same number of latent edge types. Following [26, 20], we report the mean squared error of positions and velocities over time. We compute errors in the original unnormalized data space for a fair comparison across different data normalization techniques and scales, $E(t) = \frac{1}{ND} \sum_{n=1}^{N} \|\mathbf{x}_n^t - \hat{\mathbf{x}}_n^t\|_2^2$. We also report the L_2 norm errors for positions (displacement errors), $E_p(t) = \frac{1}{N} \sum_{n=1}^{N} \|\mathbf{p}_n^t - \hat{\mathbf{p}}_n^t\|_2$, and velocities, $E_u(t) = \frac{1}{N} \sum_{n=1}^{N} \|\mathbf{u}_n^t - \hat{\mathbf{u}}_n^t\|_2$, separately to gain insights. L_2 norm errors are in the same scale with the respective variables (position and velocity) and, thus, more interpretable than MSE. We always ran experiments using 5 different random initialization seeds and report the mean and the standard deviation. Here we report the main results and visualizations and provide much more extensive examples in the appendix.

5.1 Synthetic dataset

On the synthetic 2D physics simulation we use the same experimental settings as in [20]. The dataset comprises scenes with three particles. Two of the particles move with a constant, randomly initialized velocity and the third particle is initialized with random velocity

(a)   (b)   (c)

Figure 3: LoCS predictions on (a) synthetic dataset, (b) charged particles and (c) inD.

but pushed away when close to one of the others. Scenes last for 50 timesteps. For evaluation, we use the first 25 timesteps as input and the models are tasked with predicting the following 25 timesteps. We report the results in fig. 2 and plot qualitative examples fig. 3a, more in appendix C.1. We also report the average F1 score for relation prediction in table 1. In all visualizations, each color denotes a different object.

Table 1: Relation prediction F1 score on synthetic dataset

Method	NRI	dNRI	LoCS
F1	26.5	60.8	88.9

Semi-transparent trajectories indicate the groundtruth future trajectories. Present timesteps are denoted by small black circles. Markers denote the timesteps, increasing in size as trajectories evolve through time. We observe that our method can reliably model interactions and outperforms competing methods in predicting future trajectories.

5.2 Charged particles

In the charged particles datasets the particles interact with one another via electrostatic forces. We extend the dataset by [25] from 2 to 3 dimensions and, following a similar approach to [18, 40], we remove the virtual boxes that confine the particle trajectories. We generate 30,000 scenes for training, 5,000 for validation and 5,000 for testing. Each scene comprises trajectories of 5 particles that carry either a positive or a negative charge. The forces are either attractive or repulsive according to physical laws. Following [25], training and validation scenes last for 49 timesteps. For evaluation, test scenes last for 20 additional timesteps (50 for visualization). We plot the MSE in fig. 4a and L_2 errors in Figure 6. LoCS has consistently lower errors, in total as well as individually for positions and velocities. We, further, provide qualitative results for 50 future time steps in fig. 3b, see more in appendix C.2.

5.3 Traffic trajectory forecasting

The inD dataset [4] is a real-world 2D traffic trajectory forecasting dataset of pedestrians, vehicles, and cyclists, recorded at 4 different German traffic intersections. Traffic scenes contain a varying number of participants also changing over time. We follow the exact same setting as in dNRI. The dataset contains 36 recordings; we split them in 19/7/10 for training, validation and testing. We divide each scene into 50-step sequences. We use the first 5 timesteps as input and the model has to predict the remaining 45 time steps. We plot the MSE in fig. 4b and L_2 errors in Figure 7 and as before, LoCS outperforms competing methods consistently.

5.4 Motion capture

Last, we experiment with the CMU motion capture database [10] with 3D data, following the exact same setting as [25, 20] and studying the motion of subject #35. We train the models using sequences of 50 timesteps as input and evaluate on sequences of 99 time steps. We plot the MSE in fig. 4c and L_2 errors in fig. 8 and observe that LoCS is attaining consistently lower errors.

5.5 Ablation experiments

High-intensity interactions We assess LoCS in fig. 5a in highly interactive scenarios by creating a subset of the charged particles test set (819 scenes – 16.38% of the original test set) in which a simple constant velocity model performs poorly (L_2 error > 1.5). With more and stronger interactions the proposed local coordinate frames performs even better relatively to competitors.

(a)   (b)   (c)

Figure 4: Total error curves in: (a) charged particles, (b) inD, (c) motion #35

(a)   (b)   (c)

Figure 5: Total error curves in ablation experiments: (a) on highly interactive charged particles, (b) on the impact of speed normalization, (c) on the impact of isotropic filters.

Speed normalization impact We evaluate on the synthetic dataset the impact of the new speed normalization on dNRI instead of min-max normalization in fig. 5b. Speed normalization is important for local coordinate frames to make sure equivariance is maintained after un-normalization, but methods that are not equivariant like dNRI do not benefit from it.

Impact of anisotropic filtering We compare anisotropic and isotropic filtering on inD in fig. 5c. Be it with isotropic or anisotropic filters, the local coordinate frames outperform the competitors. That said, anisotropic filters give a clear advantage over isotropic ones.

6 Conclusion

In this work we introduced LoCS, a method that introduces canonicalized roto-translated local coordinate frames for all objects in interacting dynamical systems formalized in geometric graphs. These coordinate frames grant us global invariance to roto-translations and naturally allow for anisotropic continuous filtering. We demonstrate the effectiveness of our method in a range of 2D and 3D settings, outperforming recent state-of-the-art works.

Limitations Many dynamical systems in nature are not formalized as geometric graphs (*e.g.* social networks), or are not intrinsically described by angular positions (*e.g.* elementary particles). The notions of linear and angular positions are central to local coordinate frames, and thus, our method is only applicable when these quantities are defined, or when they can be approximated. Furthermore, although we approximate angular positions using velocities, our method guarantees full invariance/equivariance to global roto-translations only in the 2D case, while in 3 dimensions we have an equivariance leakage.

References

[1] Alexandre Alahi, Kratarth Goel, Vignesh Ramanathan, Alexandre Robicquet, Li Fei-Fei, and Silvio Savarese. Social LSTM: Human trajectory prediction in crowded spaces. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 961–971, 2016.

[2] Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*, 2014.

[3] Peter W Battaglia, Razvan Pascanu, Matthew Lai, Danilo Rezende, and Koray Kavukcuoglu. Interaction networks for learning about objects, relations and physics. *arXiv preprint arXiv:1612.00222*, 2016.

[4] Julian Bock, Robert Krajewski, Tobias Moers, Steffen Runde, Lennart Vater, and Lutz Eckstein. The inD dataset: A drone dataset of naturalistic road user trajectories at german intersections. In *2020 IEEE Intelligent Vehicles Symposium (IV)*, pages 1929–1934. IEEE, 2019.

[5] Polo Calafiura, Steven Farrell, Heather Gray, Jean-Roch Vlimant, Vincenzo Innocente, Andreas Salzburger, Sabrina Amrouche, Tobias Golling, Moritz Kiehn, Victor Estrade, et al. Trackml: A high energy physics particle tracking challenge. In *2018 IEEE 14th International Conference on e-Science (e-Science)*, pages 344–344. IEEE, 2018.

[6] Ming-Fang Chang, John Lambert, Patsorn Sangkloy, Jagjeet Singh, Slawomir Bak, Andrew Hartnett, De Wang, Peter Carr, Simon Lucey, Deva Ramanan, et al. Argoverse: 3d tracking and forecasting with rich maps. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8748–8757, 2019.

[7] Kyunghyun Cho, Bart Van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*, 2014.

[8] Junyoung Chung, Kyle Kastner, Laurent Dinh, Kratarth Goel, Aaron Courville, and Yoshua Bengio. A recurrent latent variable model for sequential data. *arXiv preprint arXiv:1506.02216*, 2015.

[9] Djork-Arné Clevert, Thomas Unterthiner, and Sepp Hochreiter. Fast and accurate deep network learning by exponential linear units (elus). *arXiv preprint arXiv:1511.07289*, 2015.

[10] CMU. Carnegie-Mellon Motion Capture Database, 2003. URL http://mocap.cs.cmu.edu.

[11] Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pages 2990–2999. PMLR, 2016.

[12] Taco S Cohen and Max Welling. Steerable cnns. *arXiv preprint arXiv:1612.08498*, 2016.

[13] Bert De Brabandere, Xu Jia, Tinne Tuytelaars, and Luc Van Gool. Dynamic filter networks. *arXiv preprint arXiv:1605.09673*, 2016.

[14] Pim de Haan, Maurice Weiler, Taco Cohen, and Max Welling. Gauge equivariant mesh cnns: Anisotropic convolutions on geometric graphs. *arXiv preprint arXiv:2003.05425*, 2020.

[15] Haowen Deng, Tolga Birdal, and Slobodan Ilic. Ppf-foldnet: Unsupervised learning of rotation invariant 3d local descriptors. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 602–618, 2018.

[16] Vijay Prakash Dwivedi, Chaitanya K Joshi, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Benchmarking graph neural networks. *arXiv preprint arXiv:2003.00982*, 2020.

[17] Matthias Fey, Jan Eric Lenssen, Frank Weichert, and Heinrich Müller. Splinecnn: Fast geometric deep learning with continuous b-spline kernels. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 869–877, 2018.

[18] Fabian B Fuchs, Daniel E Worrall, Volker Fischer, and Max Welling. Se (3)-transformers: 3d roto-translation equivariant attention networks. *arXiv preprint arXiv:2006.10503*, 2020.

[19] Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International Conference on Machine Learning*, pages 1263–1272. PMLR, 2017.

[20] Colin Graber and Alexander G Schwing. Dynamic neural relational inference. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8513–8522, 2020.

[21] William L Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs. *arXiv preprint arXiv:1706.02216*, 2017.

[22] Dirk Helbing and Peter Molnar. Social force model for pedestrian dynamics. *Physical review E*, 51(5): 4282, 1995.

[23] Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. *arXiv preprint arXiv:1611.01144*, 2016.

[24] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[25] Thomas Kipf, Ethan Fetaya, Kuan-Chieh Wang, Max Welling, and Richard Zemel. Neural relational inference for interacting systems. In *International Conference on Machine Learning*, pages 2688–2697. PMLR, 2018.

[26] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

[27] Vineet Kosaraju, Amir Sadeghian, Roberto Martín-Martín, Ian Reid, S Hamid Rezatofighi, and Silvio Savarese. Social-bigat: Multimodal trajectory forecasting using bicycle-gan and graph attention networks. *arXiv preprint arXiv:1907.03395*, 2019.

[28] Parth Kothari, Sven Kreiss, and Alexandre Alahi. Human trajectory forecasting in crowds: A deep learning perspective. *arXiv preprint arXiv:2007.03639*, 2020.

[29] Rahul G Krishnan, Uri Shalit, and David Sontag. Deep kalman filters. *arXiv preprint arXiv:1511.05121*, 2015.

[30] Alon Lerner, Yiorgos Chrysanthou, and Dani Lischinski. Crowds by example. In *Computer graphics forum*, volume 26, pages 655–664. Wiley Online Library, 2007.

[31] Yujia Li, Daniel Tarlow, Marc Brockschmidt, and Richard Zemel. Gated graph sequence neural networks. *arXiv preprint arXiv:1511.05493*, 2015.

[32] Yuexin Ma, Xinge Zhu, Sibo Zhang, Ruigang Yang, Wenping Wang, and Dinesh Manocha. Trafficpredict: Trajectory prediction for heterogeneous traffic-agents. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 6120–6127, 2019.

[33] Chris J Maddison, Andriy Mnih, and Yee Whye Teh. The concrete distribution: A continuous relaxation of discrete random variables. *arXiv preprint arXiv:1611.00712*, 2016.

[34] Abduallah Mohamed, Kun Qian, Mohamed Elhoseiny, and Christian Claudel. Social-STGCNN: A social spatio-temporal graph convolutional neural network for human trajectory prediction. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14424–14432, 2020.

[35] Federico Monti, Davide Boscaini, Jonathan Masci, Emanuele Rodola, Jan Svoboda, and Michael M Bronstein. Geometric deep learning on graphs and manifolds using mixture model cnns. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 5115–5124, 2017.

[36] Stefano Pellegrini, Andreas Ess, Konrad Schindler, and Luc Van Gool. You'll never walk alone: Modeling social behavior for multi-target tracking. In *2009 IEEE 12th International Conference on Computer Vision*, pages 261–268. IEEE, 2009.

[37] Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *International conference on machine learning*, pages 1278–1286. PMLR, 2014.

[38] Tim Salzmann, Boris Ivanovic, Punarjay Chakravarty, and Marco Pavone. Trajectron++: Dynamically-feasible trajectory forecasting with heterogeneous data. *arXiv preprint arXiv:2001.03093*, 2020.

[39] Alvaro Sanchez-Gonzalez, Jonathan Godwin, Tobias Pfaff, Rex Ying, Jure Leskovec, and Peter Battaglia. Learning to simulate complex physics with graph networks. In *International Conference on Machine Learning*, pages 8459–8468. PMLR, 2020.

[40] Victor Garcia Satorras, Emiel Hoogeboom, and Max Welling. E (n) equivariant graph neural networks. *arXiv preprint arXiv:2102.09844*, 2021.

[41] Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE transactions on neural networks*, 20(1):61–80, 2008.

[42] Christoph Schöller, Vincent Aravantinos, Florian Lay, and Alois Knoll. What the constant velocity model can teach us about pedestrian motion prediction. *IEEE Robotics and Automation Letters*, 5(2):1696–1703, 2020.

[43] Kristof T Schütt, Pieter-Jan Kindermans, Huziel E Sauceda, Stefan Chmiela, Alexandre Tkatchenko, and Klaus-Robert Müller. Schnet: A continuous-filter convolutional neural network for modeling quantum interactions. *arXiv preprint arXiv:1706.08566*, 2017.

[44] Martin Simonovsky and Nikos Komodakis. Dynamic edge-conditioned filters in convolutional neural networks on graphs. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3693–3702, 2017.

[45] Nathaniel Thomas, Tess Smidt, Steven Kearnes, Lusann Yang, Li Li, Kai Kohlhoff, and Patrick Riley. Tensor field networks: Rotation-and translation-equivariant neural networks for 3d point clouds. *arXiv preprint arXiv:1802.08219*, 2018.

[46] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

[47] Anirudh Vemula, Katharina Muelling, and Jean Oh. Social attention: Modeling attention in human crowds. In *2018 IEEE international Conference on Robotics and Automation (ICRA)*, pages 4601–4607. IEEE, 2018.

[48] Clement Vignac, Andreas Loukas, and Pascal Frossard. Building powerful and equivariant graph neural networks with message-passing. *arXiv preprint arXiv:2006.15107*, 2020.

[49] Robin Walters, Jinxi Li, and Rose Yu. Trajectory prediction using equivariant continuous convolution. *arXiv preprint arXiv:2010.11344*, 2020.

[50] Shenlong Wang, Simon Suo, Wei-Chiu Ma, Andrei Pokrovsky, and Raquel Urtasun. Deep parametric continuous convolutional neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2589–2597, 2018.

[51] Yue Wang, Yongbin Sun, Ziwei Liu, Sanjay E Sarma, Michael M Bronstein, and Justin M Solomon. Dynamic graph cnn for learning on point clouds. *Acm Transactions On Graphics (tog)*, 38(5):1–12, 2019.

[52] Maurice Weiler and Gabriele Cesa. General $e(2)$-equivariant steerable cnns. *arXiv preprint arXiv:1911.08251*, 2019.

[53] Daniel E Worrall, Stephan J Garbin, Daniyar Turmukhambetov, and Gabriel J Brostow. Harmonic networks: Deep translation and rotation equivariance. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5028–5037, 2017.

[54] Sijie Yan, Yuanjun Xiong, and Dahua Lin. Spatial temporal graph convolutional networks for skeleton-based action recognition. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.

[55] Yisong Yue, Patrick Lucey, Peter Carr, Alina Bialkowski, and Iain Matthews. Learning fine-grained spatial models for dynamic sports play prediction. In *2014 IEEE international conference on data mining*, pages 670–679. IEEE, 2014.