Metropolis-Hastings Data Augmentation for Graph Neural Networks

Abstract

Graph Neural Networks (GNNs) often suffer from weak-generalization due to sparsely labeled data despite their promising results on various graph-based tasks. Data augmentation is a prevalent remedy to improve the generalization ability of models in many domains. However, due to the non-Euclidean nature of data space and the dependencies between samples, designing effective augmentation on graphs is challenging. In this paper, we propose a novel framework Metropolis-Hastings Data Augmentation (MH-Aug) that draws augmented graphs from an explicit target distribution for semi-supervised learning. MH-Aug produces a sequence of augmented graphs from the target distribution enables flexible control of the strength and diversity of augmentation. Since the direct sampling from the complex target distribution is challenging, we adopt the Metropolis-Hastings algorithm to obtain the augmented samples. We also propose a simple and effective semi-supervised learning strategy with generated samples from MH-Aug. Our extensive experiments demonstrate that MH-Aug can generate a sequence of samples according to the target distribution to significantly improve the performance of GNNs.

1 Introduction

Graph Neural Networks (GNNs) [1] have been widely used for representation learning on graph-structured data due to their superior performance in various applications such as node classification [2–4], link prediction [5–7] and graph classification [8, 9]. They have been proven effective by achieving impressive performance for diverse datasets such as social networks [10], citation networks [4], physics [11], molecules [12], and knowledge graphs [10]. However, GNNs often suffer from weak-generalization due to their small and sparsely labeled graph datasets. One prevalent remedy to address the problem is data augmentation. Data augmentation increases the diversity of data and improves the generalization power of machine learning models trained on randomly augmented samples. It is widely used to enhance the generalization ability of models in many domains. For instance, in image recognition, advanced methods like [13–15] as well as simple transformations such as random cropping, cutout, Gaussian noise, or blurring have been used to achieve competitive performance.

However, unlike image recognition, designing effective and label-preserving data augmentation for individual samples on graphs is challenging due to their non-Euclidean nature and the dependencies between data samples. In image recognition, it is straightforward to identify operations that preserve labels. For instance, human can verify that rotation, translation, and small color jittering do not change the labels in image classification. In contrast, graphs are less interpretable and it is non-trivial for even human to check whether the augmented samples belong to the original class or not. In addition, due to the dependencies between nodes and edges in a graph, it is hard to control the degree of augmentation for individual samples. For instance, a simple operation on a graph, *e.g.*, dropping a node, may result in a completely different degree of augmentation depending on the graph

structure. If a hub node is removed, the single perturbation affects a substantial amount of other nodes, which are data samples in node classification. To address these challenges, learning-based data augmentation methods for graphs have been proposed. AdaEdge [16] optimizes the graph topology based on the model prediction. [17] proposes GAug-M and GAug-O that generate augmented graphs via a differentiable edge predictor. GraphMix [18] presents interpolation-based regularization by jointly train a fully connected network and graph neural networks. However, they require additional models for augmentation and more importantly do not *explicitly* guarantee that augmentation has a proper strength and diversity.

In this paper, we proposed a novel framework called Metropolis-Hastings Data Augmentation (MH-Aug) that draws augmented graphs from an '*explicit*' target distribution with the desired strength and diversity for semi-supervised learning. Since the direct sampling from the complex distribution is challenging, we adopt the Metropolis-Hastings algorithm to obtain the augmented samples. Recently, the importance of leveraging unlabeled data as well as adopting advanced augmentation has emerged [19, 20]. Inspired by that, we also adopt the consistency training by utilizing the regularizers for unlabeled data. Our extensive experiments demonstrate that MH-Aug can generate a sequence of samples according to the desired distribution and be combined with the consistency training and it significantly improves the performance of graph neural networks.

Our **contributions** are summarized as follows:

- We proposed a novel framework Metropolis-Hastings Data Augmentation that draws augmented samples from an 'explicit' target distribution. To the best of our knowledge, this is the first work that studies data augmentation for graph-structured data from a perspective of a Markov chain Monte Carlo sampling.

- We *theoretically* and *experimentally* prove that our MH-Aug generates the augmented samples according to the desired distribution with respect to the strength and diversity.

- We propose a target distribution that flexibly controls the strength and diversity of augmentation. This includes an efficient way to measure the strength of augmentation reflecting the structural changes of ego-graphs (or samples in node classification).

- Lastly, we propose a simple and effective semi-supervised learning strategy leveraging sequentially generated samples from our method.

2 Related Works

Semi-Supervised Learning on Graphs. GNNs have been widely adopted in representation learning on graphs. For instance, GCN [4] has developed spectral into spatial approaches by localizing the first-order approximation of graph convolutions. GraphSAGE [2] learns to generate embeddings by sampling and aggregating features from the neighborhood of nodes. [3] proposed GAT which employs masked self-attentional layers. However, existing works only utilize a small subset of nodes. To fully utilize a large amount of unlabeled data, recent studies for semi-supervised learning have emerged inspired by semi-supervised frameworks in other domains [19, 20]. GraphMix [18] is a regularization method based on semi-supervised learning by linear interpolation between two data on graphs, and SSL [21] proposes two types of self-supervised learning strategies to exploit available information from graph structure. BVAT [22] promotes the smoothness of GNNs by generating virtual adversarial perturbations. Likewise, we follow semi-supervised strategy to leverage unlabeled data while considering sequentially generated samples from our augmentation.

Data Augmentation on Graphs. Data augmentation is an effective technique to improve generalization by increasing the diversity of training data. It is becoming the *de facto* necessity for model training to employ simple data augmentation (e.g., image rotation, cropping, flipping, translation, and so on). Despite the effectiveness of data augmentation, few approaches have been explored in graph domain due to its non-Euclidean nature and dependencies between data samples. Simple approaches exist such as DropEdge [23] to randomly remove a certain number of edges and AdaEdge [16] to adaptively control the inter-class/intra-class edges. Similarly, a method to propagate the perturbed node features by randomly dropping on a node-based was proposed in [24]. GAug [17] proposes the neural edge predictors as an augmentation module. Unlike existing methods employing simple perturbation [23] or extra augmentor model [17, 25], we propose the sampling-based augmentation, where a sequence of augmented samples are drawn from the *explicitly* designed target distribution for augmentation.

 # 3   Method

 We present a novel data augmentation framework for graph-structured data via Metropolis-Hastings
 algorithm. MH-Aug is a sampling-based augmentation, where a sequence of augmented samples
 are drawn from the explicit target distribution that enables flexible control of strength and diversity
 of augmentation. In this section, we first summarize the basics for our framework and delineate
 the components of MH-Aug. Then, we outline the training procedure with proposed consistency
 regularizers for semi-supervised learning. Lastly, we theoretically prove the distribution of augmented
 samples by MH-Aug converges to the desired target distribution.

3.1   Preliminaries

 A graph is denoted as $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, where $\mathcal{V}$ and $\mathcal{E}$ are the sets of nodes and edges. A k-**hop ego-graph**
 $\mathcal{G}_i$ [26] is a subgraph of $\mathcal{G}$ centered at node $v_i \in \mathcal{V}$, consisting of neighbors within k hops from node
 v_i and all edges between the neighbors including v_i. In other words, the k-hop ego-graph of a node v_i
 is defined as $\mathcal{G}_i = (\mathcal{V}_i, \mathcal{E}_i)$, $\mathcal{V}_i = \{u | S(u, v_i) \leq k, u \in \mathcal{V}\}$, $\mathcal{E}_i = \{(u, v) | (u, v) \in \mathcal{E}$ and $u, v \in \mathcal{V}_i\}$,
 where $S(u, v)$ is the length of the shortest path between nodes u and v. In this paper, we do not
 explicitly specify k for ego-graphs since 2-hop ego-graphs are used in all experiments. $\Delta\mathcal{G}'$ denotes
 the **change ratio of graph** $\mathcal{G}$ to $\mathcal{G}' = (\mathcal{V}', \mathcal{E}')$ measured by the number of added/deleted edges (or
 nodes) divided by the number of original edges (or nodes), *i.e.*, $\Delta\mathcal{G}'_\mathcal{E} = (|\mathcal{E}' - \mathcal{E}| + |\mathcal{E} - \mathcal{E}'|)/|\mathcal{E}|$ and
 $\Delta\mathcal{G}'_\mathcal{V} = (|\mathcal{V}' - \mathcal{V}| + |\mathcal{V} - \mathcal{V}'|)/|\mathcal{V}|$. Since, in this work, we consider only subgraphs of the original
 input graph as augmented samples, which is similar to DropEdge [23] and DropNode [24], the change
 ratio can be equivalently written as $\Delta\mathcal{G}'_\mathcal{E} = 1 - |\mathcal{E}'|/|\mathcal{E}|$ and $\Delta\mathcal{G}'_\mathcal{V} = 1 - |\mathcal{V}'|/|\mathcal{V}|$. Thereby $\Delta\mathcal{G}'_\mathcal{E}$ and
 $\Delta\mathcal{G}'_\mathcal{V}$ are always ranged in $[0, 1]$.

 Metropolis-Hastings (MH) algorithm is a Markov chain Monte Carlo method to draw random
 samples from a target distribution when direct sampling is difficult [27]. The MH algorithm iteratively
 draws samples from the target distribution P being only dependent on the current sample. The MH
 algorithm uses a proposal distribution Q to draw a candidate sample and evaluates the acceptance
 ratio $\mathcal{A}$ to decide whether to accept or reject the candidate sample. The accepted samples by the MH
 algorithm follow the target distribution P.

3.2   Metropolis-Hastings Data Augmentation

 Our objective is to sample the augmented graph $\mathcal{G}'$ from the target distribution P given the original
 graph $\mathcal{G}$ and can be written as

$$\mathcal{G}' \sim P(\mathcal{G}'; \mathcal{G}). \tag{1}$$

 Since direct sampling from the target distribution P is challenging, we propose a novel data augmen-
 tation method based on Metropolis-Hastings algorithm.

 Target Distribution. We design the target distribution P to control the strength and diversity of
 augmentation for effective learning. The strength and diversity can be discussed from two perspectives:
 a full graph and ego-graphs. In our framework, the strength of augmentation is measured by the
 change ratio of augmented ego-graphs, *i.e.*, $\Delta\mathcal{G}'_i$, since most existing GNNs with k-layers learn node
 representations based on their k-hop ego-graphs. On the other hand, the diversity of augmentation
 is controlled by $\Delta\mathcal{G}'$ and $\Delta\mathcal{G}'_i$ from both full graph and ego-graph perspectives. The diversity of
 augmentation is adaptively adjusted for each ego-graph by the standard deviation $\sigma(\epsilon_i)$ that is a
 simple linear function of the entropy ϵ_i of the prediction at node v_i. Given the expected strength
 $\mu_\mathcal{E} \in \mathbb{R}$ and ego-graph level diversity $\sigma(\epsilon_i) \in \mathbb{R}$, the target distribution P w.r.t. edges is given as
 follows:

$$P_\mathcal{E}(\mathcal{G}') \propto \left[\prod_i^{|\mathcal{V}|} \exp\left(-\frac{(\Delta\mathcal{G}'_{i,(\mathcal{E})} - \mu_\mathcal{E}(\epsilon_i))^2}{2\{\sigma_\mathcal{E}(\epsilon_i)\}^2} \right) \right]^{\lambda_1} \cdot \left[\frac{1}{\binom{|\mathcal{E}|}{|\mathcal{E}| \cdot \Delta\mathcal{G}'_\mathcal{E}}} \right]^{\lambda_2}, \tag{2}$$

 where $\Delta\mathcal{G}'_{i,(\mathcal{E})}$ is the change ratio of $\mathcal{G}'_i$ w.r.t. $\mathcal{E}$ and λs are hyperparamters for controlling the influence
 of the two components. To have various full graph change ratios $\Delta\mathcal{G}'_\mathcal{E}$, the normalization by the
 number of possible augmented graphs corresponding to the same change ratio, $\binom{|\mathcal{E}|}{|\mathcal{E}| \cdot \Delta\mathcal{G}'_\mathcal{E}}$, is necessary.
 As the size of graph increases, without the normalization, it becomes extremely difficult to generate

Figure 1: **Sampling process of MH-Aug.** MH-Aug produces augmented samples in two steps. First, it draws a candidate graph $\mathcal{G}'$ from a proposal distribution Q (green). Then, it decides whether to accept or reject the candidate by acceptance ratio $\mathcal{A}$ calculated by P (blue) and Q. The left box shows the details of sampling a candidate graph $\mathcal{G}'$ from the proposal distribution $Q(\mathcal{G}'|\mathcal{G}^{(t)})$ given a current sample $\mathcal{G}^{(t)}$: (1) **Change Ratio Sampling** draws the change ratios $\Delta\mathcal{G}'_\mathcal{E}$ and $\Delta\mathcal{G}'_\mathcal{V}$ of a candidate graph w.r.t. edges and nodes from Gaussian distributions, (2) **Graph Modification** generates $\mathcal{G}'_\mathcal{E}$ and $\mathcal{G}'_\mathcal{V}$ by applying the change ratio to the original graph $\mathcal{G}$, and (3) **Candidate** augmented graph G' is constructed by merging two augmented graphs $\mathcal{G}'_\mathcal{E}$ and $\mathcal{G}'_\mathcal{V}$.

augmented samples with a low (or high) full graph change ratio. For more details, see Section 4.2. Similarly, P with respect to nodes can be written as follows:

$$P_\mathcal{V}(\mathcal{G}') \propto \left[\prod_i^{|\mathcal{V}|} \exp\left(-\frac{(\Delta\mathcal{G}'_{i,(\mathcal{V})} - \mu_\mathcal{V}(\epsilon_i))^2}{2\{\sigma_\mathcal{V}(\epsilon_i)\}^2}\right)\right]^{\lambda_3} \cdot \left[\frac{1}{\binom{|\mathcal{V}|}{|\mathcal{V}|\cdot\Delta\mathcal{G}'_\mathcal{V}}}\right]^{\lambda_4}. \tag{3}$$

With combining the two distributions, the overall target distribution is defined as:

$$P(\mathcal{G}') = P_\mathcal{E}(\mathcal{G}') \cdot P_\mathcal{V}(\mathcal{G}'). \tag{4}$$

In our experiment, unlike the change ratio of the full graph $\Delta\mathcal{G}'_\mathcal{E} = 1 - |\mathcal{E}'|/|\mathcal{E}|$, we define the *ego-graph change ratio* $\Delta\mathcal{G}'_{i,(\mathcal{E})}$ (and $\Delta\mathcal{G}'_{i,(\mathcal{V})}$) with the change of the number of received messages from k-hop ego-graphs. Figure 2 illustrates the calculation of $\Delta\mathcal{G}'_{i,(\mathcal{E})}$ regarding two different cases: (b) dropping distant (2-hop) edges and (c) dropping near (1-hop) edges. In this definition, even if the number of dropped edges is the same, dropping edges connecting nodes closer to the center node v_i leads to a larger $\Delta\mathcal{G}'_{i,(\mathcal{E})}$ than the case of distant nodes ($0.6 > 0.13$), which can be regarded as a much stronger augmentation. It indicates that the amount of received messages depends on not only the number of removed edges but also which edges are dropped. This reflects the *structure* of ego-graphs. In practice, this definition allows time and memory efficient implementation using matrix multiplications as

$$\Delta\mathcal{G}'_{i,(\mathcal{E})} = 1 - \frac{(\tilde{A}'^k\mathbb{1})_i}{(\tilde{A}^k\mathbb{1})_i}, \text{ and } \Delta\mathcal{G}'_{i,(\mathcal{V})} = 1 - \frac{(\tilde{A}^k\mathbf{m})_i}{(\tilde{A}^k\mathbb{1})_i}, \tag{5}$$

where $\tilde{A}$ and $\tilde{A}'$ are adjacency matrices of the original graph $\mathcal{G}$ and the current graph $\mathcal{G}'$, where both graphs include a self-connection for every node, $\mathbb{1} \in \mathbb{R}^{|\mathcal{V}|}$ is a vector of ones, and $\mathbf{m} \in \mathbb{R}^{|\mathcal{V}|}$ is a mask vector for DropNode.

Proposal Distribution. For efficient sampling and a theoretical guarantee of convergence to the target distribution, a proposal distribution is crucial. A proposal distribution $Q(\mathcal{G}'|\mathcal{G}^{(t)})$ suggests a candidate augmented sample $\mathcal{G}'$, given the current sample $\mathcal{G}^{(t)}$. To draw diversely augmented graphs with various edge/node change ratios $\Delta\mathcal{G}'_\mathcal{E}$ and $\Delta\mathcal{G}'_\mathcal{V}$, as presented in Figure 1, a candidate augmented sample is generated by three steps: 1) change ratio sampling, 2) graph modification and 3) merging.

We first independently *sample change ratios* $\Delta\mathcal{G}'_{(\cdot)}$ for edges and nodes from a truncated Gaussian distributions ranged in $[0, 1]$ with mean $\Delta\mathcal{G}^{(t)}_{(\cdot)}$ and standard deviation $\sigma_{\Delta,(\cdot)}$. Then, we *modify the original graph* $\mathcal{G}$ to generate augmented samples $\mathcal{G}'_\mathcal{E}$ and $\mathcal{G}'_\mathcal{V}$, which can be viewed as a uniform

(a) Message Propagation of v_i on $\mathcal{G}_i$ (b) $\Delta\mathcal{G}'_{i,(E)} = 1 - \frac{13}{15}$ (c) $\Delta\mathcal{G}'_{i,(E)} = 1 - \frac{6}{15}$

Figure 2: **Calculation of $\Delta\mathcal{G}'_{i,(\mathcal{E})}$.** (a) displays the message propagation of v_i on ego-graph $\mathcal{G}_i$ in order. The received message of v_i is 15 in the original 2-hop $\mathcal{G}_i$. In case of dropping distant (2-hop) edges (b), the received message of v_i is 13 and $\Delta\mathcal{G}'_{i,(\mathcal{E})}$ becomes 0.13. In case of dropping same number of near (1-hop) edges (c), the received message of v_i is 6 and $\Delta\mathcal{G}'_{i,(\mathcal{E})}$ becomes 0.6. It can be calculated in the same way for DropNode.

161 sampling from all possible augmented graphs with $\Delta\mathcal{G}'_{\mathcal{E}}$ and $\Delta\mathcal{G}'_{\mathcal{V}}$ respectively. Finally, the two
162 graphs $\mathcal{G}'_{\mathcal{E}}$ and $\mathcal{G}'_{\mathcal{V}}$ are *merged* to construct the candidate augmented sample $\mathcal{G}'$. Formally, the proposal
163 distribution is given by:

$$Q(\mathcal{G}'|\mathcal{G}^{(t)}) \propto \frac{\phi(\xi'_{\mathcal{E}})}{\Phi(\beta_{\mathcal{E}}) - \Phi(\alpha_{\mathcal{E}})} \cdot \frac{\phi(\xi'_{\mathcal{V}})}{\Phi(\beta_{\mathcal{V}}) - \Phi(\alpha_{\mathcal{V}})} \cdot \frac{1}{\binom{|\mathcal{E}|}{|\mathcal{E}| \cdot \Delta\mathcal{G}'_{\mathcal{E}}}} \cdot \frac{1}{\binom{|\mathcal{V}|}{|\mathcal{V}| \cdot \Delta\mathcal{G}'_{\mathcal{V}}}}, \qquad (6)$$

164 where $\alpha_{(\cdot)} = \frac{a - \Delta\mathcal{G}^{(t)}_{(\cdot)}}{\sigma_\Delta}$, $\beta_{(\cdot)} = \frac{b - \Delta\mathcal{G}^{(t)}_{(\cdot)}}{\sigma_\Delta}$, $\xi'_{(\cdot)} = \frac{\Delta\mathcal{G}'_{(\cdot)} - \Delta\mathcal{G}^{(t)}_{(\cdot)}}{\sigma_\Delta}$, $\phi(x) = \frac{1}{\sqrt{2\pi}} \exp(-\frac{1}{2}x^2)$ as the
165 probability density function of the standard normal distribution and $\Phi(x) = \frac{1}{2}(1 + erf(\frac{x}{\sqrt{2}}))$ as its
166 cumulative distribution function. In (6), the first and second terms denote the likelihood of the change
167 ratios $\Delta\mathcal{G}'_{\mathcal{E}}$ and $\Delta\mathcal{G}'_{\mathcal{V}}$ given $\Delta\mathcal{G}^{(t)}$. The third and fourth terms are for the probability of a sample with
168 $\Delta\mathcal{G}'_{\mathcal{E}}$ and $\Delta\mathcal{G}'_{\mathcal{V}}$.

169 **Acceptance Ratio.** Starting with the original graph $\mathcal{G}$, MH-Aug draws the candidate graph $\mathcal{G}'$ from
170 the proposal distribution Q. Then, with an acceptance ratio $\mathcal{A}$, MH-Aug decides whether to accept or
171 reject the candidate $\mathcal{G}'$. $\mathcal{A}$ is given as:

$$\mathcal{A} = \min\left\{1, \frac{P(\mathcal{G}')Q(\mathcal{G}^{(t)}|\mathcal{G}')}{P(\mathcal{G}^{(t)})Q(\mathcal{G}'|\mathcal{G}^{(t)})}\right\}. \qquad (7)$$

172 The computation of $\mathcal{A}$ with target distribution in (4) and proposal distribution in (6) is described in
173 the supplement. MH-Aug generates a sequence of augmented graphs $\{\mathcal{G}^{(t)}\}_{0 \le t \le T}$, where T is the
174 number of accepted samples. The overall sampling process of MH-Aug is described in Figure 1.

3.3 Consistency Training with MH-Aug

176 Inspired by recent works [19, 28, 20] that show the importance of advanced augmentation methods
177 in leveraging unlabeled data, we demonstrate the effectiveness of our augmentation method in both
178 supervised and semi-supervised settings. Similar to consistency regularization [20], we propose a
179 simple training strategy with the following regularizers:

$$\mathcal{L}_u = \frac{1}{|\mathcal{V}|} \sum_i^{|\mathcal{V}|} D_{KL}\left[f(\mathcal{G}_i^{(t)}; \theta) \,||\, f(\mathcal{G}_i^{(t+1)}; \theta)\right], \text{ and } \mathcal{L}_h = \frac{1}{|\mathcal{V}|} \sum_i^{|\mathcal{V}|} \left[-f(\mathcal{G}_i; \theta) \log(f(\mathcal{G}_i; \theta))\right], \qquad (8)$$

180 where $D_{KL}(\cdot \,||\, \cdot)$ is the Kullback–Leibler divergence, $f(\cdot)$ is the GNNs parameterized by θ and $\mathcal{G}_i$
181 is the k-hop ego-graph for node i. $\mathcal{L}_u$ encourages the consistency of predictions on two consecutive
182 augmented samples $\mathcal{G}_i^{(t)}$, and $\mathcal{G}_i^{(t+1)}$. $\mathcal{L}_h$ penalizes unconfident predictions and sharpens predictions.

183 The two regularizers can be applied to both labeled and unlabeled nodes in the node classification
184 task. With the two regularizers and the standard cross-entropy loss $\mathcal{L}_s$ for supervised samples, the
185 overall loss for semi-supervised learning is given as

$$\mathcal{L} = \mathcal{L}_s + \gamma_1 \mathcal{L}_u + \gamma_2 \mathcal{L}_h. \qquad (9)$$

Algorithm 1 Metropolis-Hastings Data Augmentation (MH-Aug) Framework

---

Input: target distribution P, proposal distribution Q
Output: network parameter θ

 1: **Initialize** $t \leftarrow 0, \mathcal{G}^{(0)} \leftarrow \mathcal{G}$
 2: **while** not convergence **do**
 3:     Draw $\mathcal{G}'$ from $Q(\mathcal{G}'|\mathcal{G}^{(t)})$ ▷ Q in Eq.(6)
 4:     Draw u from $Uniform(0, 1)$
 5:     **if** $u \leq \mathcal{A}$ **then**   ▷ $\mathcal{A}$ in Eq.(7)
 6:         $\mathcal{G}^{(t+1)} \leftarrow \mathcal{G}'$
 7:         Update θ with $\mathcal{L}(\mathcal{G}, \mathcal{G}^{(t)}, \mathcal{G}^{(t+1)}; \theta)$ ▷ $\mathcal{L}$ in Eq.(9)
 8:         $t \leftarrow t + 1$
 9:     **end if**
10: **end while**

Our framework is outlined in Algorithm 1. Starting from original graph $\mathcal{G}$ with 0 change $\Delta G'$, MH-Aug generates new augmented graph data $\mathcal{G}'$ with the change of $\Delta \mathcal{G}'$. It decides whether to accept or reject the candidate $\mathcal{G}'$ with acceptance score $\mathcal{A}$. GNN models are trained with the accepted augmented data with our loss in (9). Then, the process is repeated until the model converges.

3.4 Theoretical Analysis

The goal of the Metropolis-Hastings algorithm is to generate a sequence of samples according to a desired target distribution P. To accomplish this, the Metropolis-Hastings algorithm uses a Markov process, which asymptotically reaches a unique stationary distribution $\pi(x)$ such that $\pi(x) = P(x)$ [29]. Here, we show that Markov chain of MH-Aug, which has a sequence of augmented graph as states, converges to the unique and stationary target distribution $P(\mathcal{G}')$ defined in (4).

Lemma 3.1. *Let the sequence of augmented graphs $\{\mathcal{G}^{(t)}\}_{0 \leq t \leq T}$ be the Markov chain produced by MH-Aug. If we define the acceptance ratio $\mathcal{A}$ with target distribution P in* (4) *and proposal distribution Q in* (6)*, the sequence converges to a unique stationary target distribution P.*

This can be drawn from the Convergence theorem of Markov chain [30]. The proof is in the supplement. By Lemma 3.1, we theoretically show augmented samples of MH-Aug converges to our desired target distribution. Our toy examples show a sequence of augmented graphs actually converges well to the target distribution (see Section 4.2 for details).

4 Experiments

In this section, we demonstrate the effectiveness of MH-Aug on various benchmark datasets. We start with describing datasets, baselines, and implementation details for the experiments. Next, we evaluate our framework for node classification in Section 4.1 and we offer qualitative analyses in Section 4.2 on three parts: effectiveness of ego-graph perspective for desired target distribution P, necessity of normalization term in P, and whether generated samples from MH-Aug converge to P.

Datasets. We evaluate our method on five benchmark datasets in three categories: (1) Citation networks: CORA and CITESEER [31], (2) Amazon product networks: Computers and Photo [32], and (3) Coauthor Networks: CS [32]. We follow the standard data split protocol in the transductive settings for node classification, *e.g.*, [4] for CORA and CITESEER and [32] for the rest.

Baselines. As backbone models to validate MH-Aug, we adopt three standard graph neural networks: GCN [4], GraphSAGE [1], and GAT [3]. We compare our method with vanilla models (without augmentation), augmentation-based supervised learning (DropEdge [23], AdaEdge [16]), and semi-supervised learning framework (GAug [17], SSL [21], BVAT [22], UDA* [19], GraphMix [18]). In the case of DropEdge [23] and AdaEdge [16], they use only cross-entropy loss (supervised setting) while the rest of models employs extra loss functions for regularization (semi-supervised setting). Note that, UDA* [19], a generic semi-supervised framework, has not yet been studied for the graph domain. Herein we extended it to the graph domain and denote it with an asterisk '*'.

Table 1: Node classification results. Mean accuracy and standard deviation from 10 repetitions are reported. We compare our methods with baselines of two categories: 1) supervised learning with augmentation (*e.g.*, DropEdge and AdaEdge), which are comparable to our MH-Aug (w/o Reg) and 2) semi-supervised learning (*e.g.*, GAug, SSL, BVAT, UDA* and GraphMix) that are comparable to our MH-Aug (w/ Reg). For each dataset and baseGNN the highest score is marked in **bold**.

BaseGNNs	Method	DATASET				
		CORA	**CITESEER**	**Compu.**	**Photo**	**CS**
GCN	Vanilla	$81.54_{\pm0.76}$	$71.64_{\pm0.31}$	$79.68_{\pm2.16}$	$89.02_{\pm1.49}$	$91.45_{\pm0.28}$
	DropEdge [23]	$82.21_{\pm0.71}$	$71.93_{\pm0.31}$	$80.59_{\pm1.75}$	$89.33_{\pm1.58}$	$91.69_{\pm0.43}$
	AdaEdge [16]	$82.30_{\pm0.80}^{\dagger}$	$69.70_{\pm0.90}^{\dagger}$	$80.66_{\pm1.22}$	$\mathbf{89.94_{\pm0.84}}$	$90.30_{\pm0.40}^{\dagger}$
	MH-Aug (w/o Reg)	$\mathbf{83.55_{\pm0.34}}$	$\mathbf{72.96_{\pm0.48}}$	$80.95_{\pm2.03}$	$89.65_{\pm1.67}$	$\mathbf{91.81_{\pm0.33}}$
	GAug-M [17]	$83.50_{\pm0.40}^{\dagger}$	$72.30_{\pm0.40}^{\dagger}$	$78.90_{\pm1.76}$	$88.46_{\pm1.24}$	OOM
	GAug-O [17]	$83.60_{\pm0.50}^{\dagger}$	$73.30_{\pm1.10}^{\dagger}$	OOM	$89.04_{\pm1.18}$	OOM
	SSL [21]	$83.80_{\pm0.73}^{\dagger}$	$72.95_{\pm0.62}^{\dagger}$	-	-	-
	BVAT [22]	$83.60_{\pm0.50}^{\dagger}$	$74.00_{\pm0.60}^{\dagger}$	$80.07_{\pm2.41}$	$88.46_{\pm2.25}$	$92.21_{\pm0.37}$
	UDA*[19]	$83.59_{\pm0.61}$	$73.56_{\pm0.41}$	$81.68_{\pm2.95}$	$89.95_{\pm1.73}$	$92.26_{\pm0.37}$
	GraphMix [18]	$83.90_{\pm0.57}^{\dagger}$	$74.70_{\pm0.59}^{\dagger}$	$80.72_{\pm1.16}$	$89.05_{\pm1.01}$	$91.83_{\pm0.51}^{\dagger}$
	MH-Aug (w/ Reg)	$\mathbf{85.16_{\pm0.35}}$	$\mathbf{75.49_{\pm0.29}}$	$\mathbf{82.80_{\pm2.08}}$	$\mathbf{90.87_{\pm1.49}}$	$\mathbf{92.60_{\pm0.43}}$
GraphSAGE	Vanilla	$79.78_{\pm0.74}$	$71.09_{\pm0.59}$	$79.59_{\pm1.84}$	$89.10_{\pm1.60}$	$91.35_{\pm1.00}$
	DropEdge [23]	$80.36_{\pm0.80}$	$71.46_{\pm0.57}$	$79.87_{\pm1.87}$	$89.86_{\pm1.78}$	$91.84_{\pm0.76}$
	AdaEdge [16]	$80.20_{\pm1.20}^{\dagger}$	$69.40_{\pm0.80}^{\dagger}$	$80.43_{\pm1.30}$	$\mathbf{90.57_{\pm0.70}}$	$90.30_{\pm0.40}^{\dagger}$
	MH-Aug (w/o Reg)	$\mathbf{82.61_{\pm0.66}}$	$\mathbf{72.12_{\pm0.99}}$	$81.74_{\pm2.52}$	$90.37_{\pm1.50}$	$\mathbf{92.27_{\pm0.49}}$
	GAug-M [17]	$83.20_{\pm0.40}^{\dagger}$	$71.20_{\pm0.40}^{\dagger}$	$79.84_{\pm1.99}$	$88.72_{\pm0.97}$	OOM
	GAug-O [17]	$82.00_{\pm0.50}^{\dagger}$	$72.70_{\pm0.70}^{\dagger}$	OOM	$88.16_{\pm2.70}$	OOM
	BVAT [22]	$83.12_{\pm0.64}$	$72.23_{\pm0.46}$	$78.72_{\pm2.73}$	$89.40_{\pm1.79}$	$92.63_{\pm0.48}$
	UDA*[19]	$83.37_{\pm0.29}$	$75.16_{\pm0.16}$	$82.16_{\pm2.00}$	$90.61_{\pm2.00}$	$92.83_{\pm0.39}$
	GraphMix [18]	$82.28_{\pm0.55}$	$69.62_{\pm0.36}$	$81.33_{\pm1.46}$	$88.46_{\pm1.36}$	$89.29_{\pm0.45}$
	MH-Aug (w/ Reg)	$\mathbf{84.70_{\pm0.39}}$	$\mathbf{75.55_{\pm0.44}}$	$\mathbf{83.62_{\pm2.60}}$	$\mathbf{92.19_{\pm1.37}}$	$\mathbf{93.61_{\pm0.58}}$
GAT	Vanilla	$82.23_{\pm0.46}$	$71.37_{\pm0.93}$	$78.47_{\pm1.86}$	$87.80_{\pm1.36}$	$90.90_{\pm0.31}$
	DropEdge [23]	$83.04_{\pm0.37}$	$72.16_{\pm0.91}$	$81.04_{\pm1.86}$	$88.73_{\pm1.54}$	$91.10_{\pm0.37}$
	AdaEdge [16]	$77.90_{\pm2.00}^{\dagger}$	$69.10_{\pm0.80}^{\dagger}$	$77.52_{\pm1.72}$	$88.92_{\pm0.87}$	$86.60_{\pm0.16}^{\dagger}$
	MH-Aug (w/o Reg)	$\mathbf{83.49_{\pm0.69}}$	$\mathbf{72.81_{\pm0.98}}$	$81.72_{\pm1.66}$	$90.23_{\pm0.97}$	$\mathbf{91.40_{\pm0.39}}$
	GAug-M [17]	$82.10_{\pm1.00}^{\dagger}$	$71.50_{\pm0.50}^{\dagger}$	$77.70_{\pm2.10}$	$87.08_{\pm1.00}$	OOM
	GAug-O [17]	$82.20_{\pm0.80}^{\dagger}$	$71.60_{\pm1.10}^{\dagger}$	OOM	$86.45_{\pm1.52}$	OOM
	SSL [21]	$83.70_{\pm0.61}^{\dagger}$	$72.73_{\pm0.72}^{\dagger}$	-	-	-
	UDA*[19]	$83.71_{\pm0.48}$	$73.24_{\pm0.48}$	$82.42_{\pm2.95}$	$89.79_{\pm1.36}$	$91.78_{\pm0.23}$
	GraphMix [18]	$83.32_{\pm0.18}^{\dagger}$	$73.08_{\pm0.23}^{\dagger}$	-	-	-
	MH-Aug (w/ Reg)	$\mathbf{84.95_{\pm0.40}}$	$\mathbf{75.53_{\pm0.32}}$	$\mathbf{83.25_{\pm1.88}}$	$\mathbf{90.61_{\pm1.34}}$	$\mathbf{92.08_{\pm0.58}}$

UDA* denotes our extension of UDA in the graph domain. $\dagger$ denotes the results reported in the original paper.

Implementation Details. For implementations of ours and baseline models, we train models for 2,000 epochs using the Adam optimizer [33] for training. We mainly follow the original papers and released code when reproducing baselines with minimum of modification. For fair comparison, we report final accuracy and standard deviation over 10 fixed random splits for all datasets. More details of experiment settings including hyperparameters such as learning rate, weight decay, and MH-Aug hyperparameters are in the supplement.

4.1 Results on Node Classification

Table 1 shows the experimental results on node classification with five datasets compared to baseline models. We implemented all the baselines and conducted experiments for fair comparison except for the case where the performance (marked with $\dagger$) is available in the original papers [16, 17, 21, 22, 18]. Also, we denote out-of-memory as OOM. Our full framework MH-Aug (w/ Reg), which is trained in the semi-supervised setting, consistently achieves the best performance in all datasets and the

Figure 3: **Diverse $\mathcal{G}'$ sampled by MH-Aug**. The first cell is the original graph G extracted from CORA. With the fixed full graph change ratio $\Delta\mathcal{G}'_{\mathcal{E}}$, augmented graphs with different $\mu_{\mathcal{E}}$ and $\sigma_{\mathcal{E}}$ are generated by MH-Aug. All graphs above are 3-hop ego-graphs with a center node marked as yellow. Nodes and edges which are not in the ego-graph after augmentation are blurred. Mini-maps at the upper right corner is the drop-edge probability, where blue means higher probability and red means low probability to drop the edge. By explicitly controlling the strength and diversity from an ego-graph perspective, MH-Aug generates diverse augmentations.

(a) With Normalization, $\lambda_2 = 1$ (b) Without Normalization, $\lambda_2 = 0$

Figure 4: **The effect of normalization term**. The two plots above show the distribution of augmented graphs w.r.t $\mathrm{E}(\Delta\mathcal{G}'_i)$. We conduct the toy example with the target distribution (a) with normalization (blue) and (b) without normalization (red).

improvement against the vanilla models is 3.16% on average. In particular, we observe that MH-Aug improves the performance by 4.92% compared to the vanilla GraphSAGE on CORA. In addition, MH-Aug provides an 4.16% gain on CITESEER on average over all models (*i.e.*, vanilla GCN, GraphSAGE and GAT).

As an ablation study, we conduct experiments with MH-Aug (w/o Reg), our framework trained in the supervised setting. Table 1 shows that MH-Aug (w/o Reg) achieves 1.47% improvement on average compared to vanilla models. MH-Aug (w/o Reg) provides considerable gain over all dataset and model. More specifically, it provides 3.25% performance improvement compared to the vanilla GAT model on Computers. In addition, MH-Aug (w/o Reg) beats DropEdge for all settings and mostly beats AdaEdge that optimizes the graph topology based on the model predictions. It is worth noting that even though MH-Aug (w/o Reg) does not explicitly utilize unlabeled data during training, MH-Aug (w/o Reg) achieves competitive performance compared to other semi-supervised methods, especially in the following cases: GCN on CORA (83.55%); GraphSAGE on CITESEER (72.12%); and GAT on CORA (83.49%), and Photo (90.23%). This demonstrates the effectiveness of our sampling-based augmentation. More discussion on ablation study is in the supplement.

4.2 Analysis

Effectiveness of Ego-graph Perspective. To validate the effectiveness of ego-graph perspective augmentation, we qualitatively analyze augmented samples by MH-Aug on real data with various settings as shown in Figure 3. An original sample (first column) is a 3-hop ego-graph from CORA. Augmented samples are generated from $\mathcal{G}$ in three settings: $(\mu_{\mathcal{E}}, \sigma_{\mathcal{E}}) = (0,0.05)$, $(\mu_{\mathcal{E}}, \sigma_{\mathcal{E}}) = (1,0.05)$

(a) Drop probability of each edges

(b) Visualization of drop probability on grid graphs

Figure 5: **Convergence to the target distribution**. To verify the convergence of MH-Aug, we simulate the sampling procedure of MH-Aug on a grid graph. (a) is the result of target distribution P given $\mu_{\mathcal{E}} = 0$. We highlight the edges according to drop probability. (b) shows that the samples drawn from MH-Aug (blue) follow the target distribution P (red) that we calculate with (2).

and $(\mu_{\mathcal{E}}, \sigma_{\mathcal{E}}) = (0, 1000)$. The mini maps at the upper right corner shows the edge-drop probability, calculated from $\prod_i^{|\mathcal{V}|} \exp\left(-\frac{(\Delta \mathcal{G}'_{i,(\mathcal{E})} - \mu_{\mathcal{E}})^2}{2\{\sigma_{\mathcal{E}}\}^2}\right)$ of (2). To evaluate the effect of μ_E and σ_E w.r.t. ego-graph, we fix the full-graph change ratio $\Delta G'_{\mathcal{E}}$. Thus, the number of dropped edges is identical for all the augmented graphs in Figure 3. It demonstrates that even if the number of dropped edges is the same, one can generate diverse samples by controlling $\mu_{\mathcal{E}}$ and $\sigma_{\mathcal{E}}$. When $\mu_{\mathcal{E}}$, which controls the expected augmentation strength, is large, *e.g.*, $\mu_{\mathcal{E}} = 1, \sigma_{\mathcal{E}} = 0.05$, more edges near to the center node tend to be dropped. This observation exactly matches to our design in Section 3.2, which considers dropping edges near to the center as a strong augmentation. In addition, the mini map in the fourth cell of Figure 3 indicates if $\sigma_{\mathcal{E}}$ increases, the edge-drop probability of the all edges becomes uniform, *i.e.* MH-Aug subsumes DropEdge as a special case. In sum, the ego-graph perspective enables the explicit control of augmentation strength and diversity to make an advanced augmentation.

Necessity of Normalization Term. As mentioned in Section 3.2, the normalization in the target distribution P by the number of possible augmented graphs corresponding to the same change ratio, $\binom{|\mathcal{E}|}{|\mathcal{E}| \cdot \Delta \mathcal{G}'_{\mathcal{E}}}$, is crucial to generating ego-graphs with the desired ego-graph change ratio $\mu_{\mathcal{E}}$ when the number of edges is huge. We demonstrate it with a small but *fully connected* graph to apply MH-Aug. Figure 4 displays the distribution of the empirical mean of $\Delta \mathcal{G}'_{i,(\mathcal{E})}$ from the augmented graph sampled from P with two different $\mu_{\mathcal{E}} = 0.1$ and $\mu_{\mathcal{E}} = 0.9$. With normalization (Figure 4(a)), the sample mean of $\Delta \mathcal{G}'_i$ of both sampling results are near to the $\mu_{\mathcal{E}}$ values. However, without normalization (Figure 4(b)), the empirical mean of $\Delta \mathcal{G}'_{i,(\mathcal{E})}$ remains the same due to overwhelmingly many possible subgraphs with a certain full graph change ratio $\Delta \mathcal{G}'_{\mathcal{E}}$, *e.g.*, $\binom{100 \times 100}{5000}$ for a fully connected graph with 100 nodes. But this does *not* mean that our MH-Aug fails to converges to the target distribution. It merely converges to the undesirable target distribution. More details are in the supplement.

Convergence to Target Distribution. In Section. 3.4, we theoretically show that the distribution of samples generated by MH-Aug converges to our desired target distribution P. Now, we conduct the experiment to examine whether a sequence of augmented graphs experimentally follows the target distribution. For simplicity, we only consider the change of edges and the target distribution $P_{\mathcal{E}}$ in (2). In 5(a), red line denotes the probability of each edge obtained by calculating P with (2). Blue bars represent the distribution of augmented graphs generated by MH-Aug. It shows MH-Aug generates augmented graphs following the target distribution. In 5(b), we visualize drop probability on graph. Since we set $\mu_{\mathcal{E}}$ small, drop probability of center edges is higher than others.

5   Conclusion

We present a novel semi-supervised strategy with Metropolis-Hastings algorithm based augmentation method. This is the first work to impose data augmentation on graph-structured data from a perspective of a Markov chain Monte Carlo sampling. We theoretically and experimentally show the convergence of augmented samples to target distribution and demonstrate its consistent performance improvement over baselines across five benchmark datasets.

References

[1] William L Hamilton, Rex Ying, and Jure Leskovec. Representation learning on graphs: Methods and applications. *IEEE Data Eng. Bull.*, 2017.

[2] William L. Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *NeurIPS*, 2017.

[3] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. In *ICLR*, 2017.

[4] Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *ICLR*, 2017.

[5] Muhan Zhang and Yixin Chen. Link prediction based on graph neural networks. In *NeurIPS*, 2018.

[6] Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne Van Den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. In *ESWC*. Springer, 2018.

[7] Thomas N Kipf and Max Welling. Variational graph auto-encoders. In *NeurIPS W*, 2016.

[8] Rex Ying, Jiaxuan You, Christopher Morris, Xiang Ren, William L. Hamilton, and Jure Leskovec. Hierarchical graph representation learning with differentiable pooling. In *NeurIPS*, 2018.

[9] David Duvenaud, Dougal Maclaurin, Jorge Aguilera-Iparraguirre, Rafael Gómez-Bombarelli, Timothy Hirzel, Alán Aspuru-Guzik, and Ryan P. Adams. Convolutional networks on graphs for learning molecular fingerprints. In *NeurIPS*, 2015.

[10] Daixin Wang, Peng Cui, and Wenwu Zhu. Structural deep network embedding. In *KDD*, pages 1225–1234, 2016.

[11] Peter Battaglia, Razvan Pascanu, Matthew Lai, Danilo Jimenez Rezende, and Koray kavukcuoglu. Interaction networks for learning about objects, relations and physics. In *NeurIPS*, 2016.

[12] Zhenqin Wu, Bharath Ramsundar, Evan N Feinberg, Joseph Gomes, Caleb Geniesse, Aneesh S Pappu, Karl Leswing, and Vijay Pande. Moleculenet: a benchmark for molecular machine learning. *Chemical science*, 2018.

[13] Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *ICCV*, 2019.

[14] Ekin D Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V Le. Autoaugment: Learning augmentation strategies from data. In *CVPR*, 2019.

[15] Ekin D Cubuk, Barret Zoph, Jonathon Shlens, and Quoc V Le. Randaugment: Practical automated data augmentation with a reduced search space. In *CVPR W*, 2020.

[16] Deli Chen, Yankai Lin, Wei Li, Peng Li, Jie Zhou, and Xu Sun. Measuring and relieving the over-smoothing problem for graph neural networks from the topological view. In *AAAI*, pages 3438–3445, 2020.

[17] Tong Zhao, Yozen Liu, Leonardo Neves, Oliver Woodford, Meng Jiang, and Neil Shah. Data augmentation for graph neural networks. In *AAAI*, 2021.

[18] Vikas Verma, Meng Qu, Kenji Kawaguchi, Alex Lamb, Yoshua Bengio, Juho Kannala, and Jian Tang. Graphmix: Improved training of gnns for semi-supervised learning. In *AAAI*, 2021.

[19] Qizhe Xie, Zihang Dai, Eduard Hovy, Thang Luong, and Quoc Le. Unsupervised data augmentation for consistency training. In *NeurIPS*, volume 33, 2020.

[20] Kihyuk Sohn, David Berthelot, Nicholas Carlini, Zizhao Zhang, Han Zhang, Colin A Raffel, Ekin Dogus Cubuk, Alexey Kurakin, and Chun-Liang Li. Fixmatch: Simplifying semi-supervised learning with consistency and confidence. In *NeurIPS*, volume 33, 2020.

[21] Qikui Zhu, Bo Du, and Pingkun Yan. Self-supervised training of graph convolutional networks. *Arxiv*, 2020.

[22] Zhijie Deng, Yinpeng Dong, and Jun Zhu. Batch virtual adversarial training for graph convolutional networks. In *ICML W*, 2019.

[23] Yu Rong, Wenbing Huang, Tingyang Xu, and Junzhou Huang. Dropedge: Towards deep graph convolutional networks on node classification. In *ICLR*, 2020.

[24] Wenzheng Feng, Jie Zhang, Yuxiao Dong, Yu Han, Huanbo Luan, Qian Xu, Qiang Yang, Evgeny Kharlamov, and Jie Tang. Graph random neural networks for semi-supervised learning on graphs. In *NeurIPS*, volume 33, 2020.

[25] Cheng Zheng, Bo Zong, Wei Cheng, Dongjin Song, Jingchao Ni, Wenchao Yu, Haifeng Chen, and Wei Wang. Robust graph representation learning via neural sparsification. In *ICML*, pages 11458–11468. PMLR, 2020.

[26] Qi Zhu, Yidan Xu, Haonan Wang, Chao Zhang, Jiawei Han, and Carl Yang. Transfer learning of graph neural networks with ego-graph information maximization. *Arxiv*, 2020.

[27] W Keith Hastings. Monte carlo sampling methods using markov chains and their applications. 1970.

[28] Jihoon Tack, Sangwoo Mo, Jongheon Jeong, and Jinwoo Shin. Csi: Novelty detection via contrastive learning on distributionally shifted instances. In *NeurIPS*, 2020.

[29] Christian Robert and George Casella. *Monte Carlo statistical methods*. Springer Science & Business Media, 2013.

[30] Ari Freedman. Convergence theorem for finite markov chains. *Proc. REU*, 2017.

[31] Zhilin Yang, William Cohen, and Ruslan Salakhudinov. Revisiting semi-supervised learning with graph embeddings. In *ICML*, pages 40–48. PMLR, 2016.

[32] Oleksandr Shchur, Maximilian Mumme, Aleksandar Bojchevski, and Stephan Günnemann. Pitfalls of graph neural network evaluation. *Arxiv*, 2018.

[33] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.