WHEN DEBATE FAILS:
BIAS REINFORCEMENT IN LARGE LANGUAGE MODELS

Jihwan Oh,[*] **Minchan Jeong,**[*] **Jongwoo Ko & Se-Young Yun** [†]
Graduate School of AI, KAIST
{ericoh929, mcjeong, jongwoo.ko, yunseyoung}@kaist.ac.kr

ABSTRACT

Large Language Models (LLMs) solve complex problems using training-free methods like prompt engineering and in-context learning, yet ensuring reasoning correctness remains challenging. While self-correction methods such as self-consistency and self-refinement aim to improve reliability, they often reinforce biases due to the lack of effective feedback mechanisms. Multi-Agent Debate (MAD) has emerged as an alternative, but we identify two key limitations: bias reinforcement, where debate amplifies model biases instead of correcting them, and lack of perspective diversity, as all agents share the same model and reasoning patterns, limiting true debate effectiveness. To systematically evaluate these issues, we introduce *MetaNIM Arena*, a benchmark designed to assess LLMs in adversarial strategic decision-making, where dynamic interactions influence optimal decisions. To overcome MAD's limitations, we propose **DReaMAD** (**D**iverse **Rea**soning via **M**ulti-**A**gent **D**ebate with Refined Prompt), a novel framework that (1) refines LLMs' strategic prior knowledge to improve reasoning quality and (2) promotes diverse viewpoints within a single model by systematically modifying prompts, reducing bias. Empirical results show that **DReaMAD** significantly improves decision accuracy, reasoning diversity, and bias mitigation across multiple strategic tasks, establishing it as a more effective approach for LLM-based decision-making.

1 INTRODUCTION

Large Language Models (LLMs) have demonstrated remarkable problem-solving capabilities across a wide range of tasks by leveraging knowledge acquired from vast datasets (Achiam et al., 2023; The; Team et al., 2023; Dubey et al., 2024). These models can address complex decision-making problems using training-free methods such as *prompt engineering* (White et al., 2023; Chen et al., 2023a; Schulhoff et al., 2024b) and *in-context learning* (Brown et al., 2020; Dong et al., 2022; Wei et al., 2022; Mavromatis et al., 2023; Pan, 2023), which provide guidance for effective reasoning. However, these approaches do not explicitly guarantee the correctness of the generated responses.

To address this, recent research has explored self-correction mechanisms that allow LLMs to refine their own outputs without external feedback. Self-consistency (Wang et al., 2022; Chen et al., 2023c) enhances reliability by ensembling multiple responses. Self-refinement (Wan et al., 2023; Shinn et al., 2023; Madaan et al., 2024) enables LLMs to iteratively critique and revise their outputs. However, self-consistency lacks a critical feedback mechanism, meaning it does not iteratively refine responses but merely reduces the model's inherent randomness by converging on the most frequently generated answer. Further recent studies (Huang et al., 2024) suggest that self-refinement can degrade performance, as models often struggle to assess the correctness of their own reasoning.

Recently, inspired by the *Society of Mind* philosophy, Multi-Agent Debate (MAD; Chan et al. 2023; Du et al. 2023; Liang et al. 2023) has emerged as a promising alternative. However, its success has been limited to static problem-solving and lacks assessments for adversarial strategic reasoning (Cobbe et al., 2021; Edwards, 1994; He et al., 2020). Additionally, current evaluations do not account for dynamic decision-making in interactive environments, where an agent's choices

---

[*]Equal contribution.
[†]Correcponding author.

Table 1: Feature comparison between self-correction methods. In contrast to Multi-Agent Debate, **DReaMAD** encourages diverse viewpoints by varying prompts and enhancing debate robustness through automated knowledge structuring.

Methods	Single Model Usage	Multiple Instances	Rethinking Process	Self-Feedback	Diversity in reasoning	Perspective Shifts
Self-Consistency	✓	✓	✗	✗	△	✗
Self-Refinement	✓	✗	✓	✓	✗	✗
Multi-Agent Debate	✓	✓	✓	✗	△	✗
DReaMAD (Ours)	✓	✓	✓	✗	✓	✓

△: means diversity from LLM's randomness, controlled by *temperature* hyperparameter.

influence and adapt to an opponent's actions. This limitation hinders LLMs from retrieving and applying strategic knowledge beyond the given context.

To overcome the above limitation, we introduce *MetaNIM Arena*, a framework for evaluating LLMs in adversarial strategic decision-making. It allows us to assess their ability to adapt dynamically and ensures robust reasoning under mathematically rigorous conditions. Through *MetaNIM Arena*, we systematically analyze two fundamental limitations of MAD:

(1) Bias Reinforcement: In strategic reasoning tasks, LLMs tend to rely on immediate context rather than retrieving broader strategic knowledge, leading to distorted reasoning instead of correct inference. Debate-based frameworks further amplify this issue by reinforcing the model's inherent biases rather than mitigating them (§4.1-4.2).

(2) Lack of Perspective Diversity: Although MAD uses a debate structure, it relies on multiple instances of the same model. This limits the diversity of perspectives introduced in the reasoning process, reducing its ability to challenge inherent biases (§4.3).

Rooted in the *Learning from Multiple Approaches* framework (Council et al., 2005; Cleaves, 2008), research shows that engaging with multiple problem-solving representations enhances comprehension and mitigates biases. Building on this insight, we propose **DReaMAD** (**D**iverse **Rea**soning via **M**ulti-**A**gent **D**ebate with Refined Prompt). **DReaMAD** addresses the limitations of MAD by (1) refining LLMs' domain-specific knowledge to guide more accurate strategic reasoning, and (2) systematically modifying prompts to foster diverse perspectives. A detailed comparison with existing self-correction methods is presented in Table 1. Our key contributions are as follows:

• We introduce **MetaNIM Arena**, a benchmark designed to evaluate LLMs in adversarial strategic decision-making, where mathematical rigor enables precise assessment of reasoning quality and strategic adaptability.

• We identify the **bias reinforcement problem** in Multi-Agent Debate, showing that MAD strengthens both correct and incorrect reasoning rather than inherently improving it.

• We propose **DReaMAD**, a novel framework that refines strategic prior knowledge and enhances reasoning diversity through structured self-prompt refinement and perspective diversification, achieving a +12.0% accuracy gain over standard prompting on *MetaNIM Arena* dataset and a +20.8% higher win rate than MAD in the simulator.

2 PRELIMINARY

2.1 BIAS IN LLMs

Large Language Models (LLMs) can exhibit biases that lead to unfair or skewed outcomes, arising from training data, model architectures, learning objectives, or deployment conditions (Guo et al., 2024). Such biases manifest both *intrinsically*, for instance in word embeddings (Bolukbasi et al., 2016), and *extrinsically*, reflecting real-world disparities (Goldfarb-Tarrant et al., 2021). Moreover, biases can emerge dynamically during interactive reasoning, where current reinforcement mechanisms—like self-consistency and self-refinement—often fail to mitigate them (Huang et al., 2024; Shin et al., 2024). Indeed, recent research shows that iterative interactions can reinforce existing biases instead of diversifying reasoning (Ganguli et al., 2023).

2.2 PROMPT ENGINEERING AND SELF-CORRECTION IN LLMs

Prompt engineering shapes model outputs without retraining, potentially improving generalization and reducing bias (Brown et al., 2020; Reynolds & McDonell, 2021; Zhao et al., 2024; Schulhoff et al., 2024a; Shin et al., 2024). However, fully eliminating biases in complex reasoning remains challenging (Jiang et al., 2022; Lu et al., 2022).

Meanwhile, self-correction mechanisms in LLMs refine responses without external supervision (Ganguli et al., 2023; Liu et al., 2024; Kamoi et al., 2024). Self-consistency, for instance, ensembles multiple outputs but converges on frequent rather than correct answers (Wang et al., 2022; Chen et al., 2023c), and self-refinement can reinforce rather than fix biases (Wan et al., 2023; Shinn et al., 2023; Madaan et al., 2024; Huang et al., 2024). Feedback-loop methods such as STaR (Zelikman et al., 2022), Reflexion (Shinn et al., 2023), and SCoRe (Kumar et al., 2024) also struggle to reliably correct biases or foster diverse reasoning (Guo et al., 2024).

2.3 MULTI-AGENT DEBATE IN LLMS

Multi-Agent Debate (MAD) enables LLM agents to critique each other, enhancing reasoning on complex tasks (Liang et al., 2023; Du et al., 2023). ChatEval (Chan et al., 2023), a multi-agent evaluation system, simulates human judgment to assess model output quality. Optimizations include task-specific strategies for improving debate effectiveness (Smit et al., 2024) and ACC-Debate, an actor-critic framework that trains models to specialize in debates, achieving benchmark gains (Estornell et al., 2024). While these enhancements improve performance, studies reveal a key limitation: static evaluations focus on assessing predefined problems, whereas real-world decision-making often involves dynamic, interactive environments where biases can evolve. Understanding how biases shift in these settings is crucial for developing robust strategies that extend beyond conventional static benchmarks.

3 METANIM ARENA

3.1 OVERVIEW

We introduce *MetaNIM Arena*, illustrated in Figure 8. It features four impartial combinatorial games, meaning both players share identical moves at each state, all information is fully observable, and each game terminates in a finite number of moves. By merging *combinatorial game theory* with adversarial play, *MetaNIM Arena* serves as a benchmark for debate-based strategic reasoning in LLMs.

Dataset and Simulator. Key game situations are systematically collected into a *dataset*, each accompanied by an optimal action, enabling LLMs to be tested for decision-making accuracy. These results appear in Table 3, with details in Appendix A.5. Separately, *MetaNIM Arena* can function as a *simulator*: the model encounters an adaptive opponent, so each trajectory depends on both the agent's and the opponent's actions. Here, binary win/loss outcomes allows evaluation by *win rate*. We demonstrate this approach in Table 4, with further explanation in Appendix A.6. We refer the Appendix B for details of opponent modelling.

3.2 WHY METANIM ARENA?

MetaNIM Arena provides a rigorous environment for *adversarial strategic reasoning* in LLMs. Rather than isolated problem-solving or factual recall, our framework uses impartial combinatorial games, where each position's Grundy number defines the provably correct move. We will discuss further theoretical details in the following Section 3.4. This design offers:

1. Adversarial Strategic Reasoning: Each scenario includes an opponent whose actions shape outcomes. Models must *anticipate* adversarial moves across multiple turns, going beyond static QA or single-step predictions. This approach tests *latent strategic knowledge* in an interactive, step-by-step context.

2. Clear Optimality Criterion: By the Sprague-Grundy Theorem, these games admit an optimal strategy. *MetaNIM Arena* thus measures how closely a model's reasoning aligns with that strategy, instead of relying on approximate metrics like BLEU or perplexity.

We also assert that *MetaNIM Arena* naturally supports Reinforcement Learning framework. By providing a binary win/loss signal and structuring gameplay as a Markov Decision Process (MDP), it enables iterative strategy refinement—an advantage often absent in static benchmarks.

3.3 GAME VARIANTS

Here, we introduce four settings of *MetaNIM Arena*Detailed explanation and theoretically determined winning strategies for these games are provided in Appendix A.

- **NIM:** Agents take turns removing 1 to N (typically 3) objects from a set of heaps where the player who takes the last object wins. Success requires maintaining specific heap configurations to control the game's outcome.
- **Fibonacci:** A variation of NIM where an agent's maximum removal is constrained by the opponent's previous move. Each turn, an agent may remove between 1 and $2\times$ the opponent's last action. This rule introduces dynamic strategy adjustments, balancing immediate gains with long-term positioning.
- **Kayles:** Played with a or two row(s) of pins, where agents take turns knocking down one or two adjacent pins. The player unable to make a move loses. The challenge lies in evaluating pin configurations and predicting the opponent's responses to optimize each turn.
- **Chomp:** Played on a quadrangle grid, agents take turns consuming a "block" of chocolate along with all blocks below and to the right. The player forced to eat the top-right (or top-left) "poisoned" block loses.

3.4 COMBINATORIAL GAMES: THEORY AND STRATEGY

All *MetaNIM Arena* games are impartial combinatorial games, forming a Directed Acyclic Graph (DAG) where vertices represent game states and edges denote valid moves. By the Sprague-Grundy theorem, each state admits a mathematically provable optimal move, enabling an LLM's decisions to be evaluated against the *theoretical optimal strategy*—a key advantage for unbiased assessment.

Theorem 3.1 (Sprague-Grundy)**.** *For a finite impartial combinatorial game under normal play (where the last player to make a valid move wins), the* Grundy number *(or* Nimber*)* $G(S)$ *is recursively defined as follows. If S is a* terminal state *with no valid moves, set $G(S) = 0$. Otherwise,*

$$G(S) \;=\; \mathrm{mex}\{\, G(S') \mid S' \text{ is reachable from } S \},$$

where $\mathrm{mex}(X)$ *is the smallest nonnegative integer not in X. This is well-defined since the game's state space forms a DAG. A position S satisfies $G(S) = 0$ if and only if it is a* losing position*, whereas $G(S) \neq 0$ indicates a* winning position*. Furthermore, if S decomposes into independent subpositions $S_1, \ldots, S_k$, then*

$$G(S)_{(2)} \;=\; G(S_1)_{(2)} \,\oplus\, G(S_2)_{(2)} \,\oplus\, \cdots \,\oplus\, G(S_k)_{(2)},$$

where $\oplus$ denotes bitwise XOR between binary representations.

Optimal Strategy. If $G(S) \neq 0$, there is at least one move to a state S' with $G(S') = 0$, forcing the opponent into a losing position. Because the game's state space forms a DAG, repeatedly applying this strategy guarantees a path to victory when both sides play optimally. Even against suboptimal moves, consistently reducing $G(S)$ to 0 ensures no deterioration of one's own position; however, an immediate shortcut to victory may arise if the opponent makes a severe error.

Misère Variant. *Misère* play reverses the normal condition: taking the last object loses rather than wins. Although standard Sprague-Grundy analysis still applies to most states, a special exception arises when all heaps (or subpositions) are size 1, such as in *misère* Nim. In that endgame scenario, the usual strategy must switch to avoid forcing the final move, ensuring the player leaves the opponent to pick the last object.

4 UNDERSTANDING BIAS REINFORCEMENT IN DEBATE PROCESS

To quantitatively analyze bias in the debate process, we define *strong consistency* and *bias reinforcement* as below.

Definition 4.1 (**Strong Consistency**)**.** *Strong consistency* is a model's tendency to consistently produce the same output with high probability when given identical inputs. If a response's probability exceeds a threshold (set at 0.5) across multiple trials, we label the behavior as strongly consistent.

This phenomenon naturally emerges in strategic decision-making contexts. As shown in Figure 2, when presented with a specific game state, the model repeatedly generates the same reasoning pattern, highlighted in orange. Rather than effectively utilizing strategic prior knowledge, the model fixates on a single line of reasoning, limiting adaptability and decision quality.

Definition 4.2 (**Bias Reinforcement**)**.** *Bias reinforcement* in the context of large language models refers to the phenomenon where iterative reasoning processes—such as multi-agent debates—amplify

Table 2: Bias reinforcement across models: showing that even after the debate concludes, strongly consistent actions continue to exhibit strong consistency, reinforcing biased action distributions in the Fibonacci game. A wrong bias occurs when the model's biased response deviates from the optimal action, while a good bias refers to cases where the biased response aligns with the optimal action. (a, b) indicate the state where the remaining items are a, and player can take the items maximum to b.

(a) GPT-4o	Wrong Bias			Good Bias		
	(20, 19)	(12, 4)	(7, 4)	(15, 10)	(16, 8)	(7, 7)
Standard	0.700	0.675	0.600	0.525	0.725	0.850
+ After MAD	**0.900**	**0.750**	**0.700**	**0.750**	**0.750**	**0.900**

(b) GPT-4o-mini	Wrong Bias			Good Bias		
	(18, 4)	(12, 6)	(10, 4)	(15, 10)	(7, 2)	(15, 2)
Standard	0.700	0.875	0.600	0.975	0.950	0.975
+ After MAD	**0.850**	**0.950**	**0.750**	**1.000**	0.950	**1.000**

(c) GEMINI-1.5-pro	Wrong Bias			Good Bias		
	(20, 19)	(12, 4)	(4, 4)	(15, 10)	(10, 4)	(16, 8)
Standard	0.650	0.600	0.600	0.800	0.625	0.675
+ After MAD	**0.700**	**0.650**	**0.800**	0.800	**0.800**	**0.700**

(d) GEMINI-1.5-flash	Wrong Bias			Good Bias		
	(12, 6)	(12, 4)	(7, 4)	(15, 4)	(20, 19)	(7, 7)
Standard	0.800	0.700	0.525	0.750	0.500	0.750
+ After MAD	**0.850**	**1.000**	**0.750**	0.750	**0.650**	**1.000**

pre-existing model biases instead of mitigating them. Rather than converging toward a more accurate or optimal reasoning outcome, the debate process reinforces strongly consistent, yet potentially suboptimal or distorted, reasoning patterns.

In the rest of this section, we analyze bias reinforcement and lack of diversity in the debate process, using GPT-4o-mini and GEMINI-1.5-pro for the NIM game, and extending the evaluation to Fibonacci with four models: GPT-4o, GPT-4o-mini, GEMINI-1.5-pro, and GEMINI-1.5-flash.

4.1 BIAS REINFORCEMENT IN MAD

In NIM: (Figure 1) We observed that instead of refining reasoning towards optimal strategies, MAD reinforces a model's inherent biases, leading the debate process to align with strongly consistent incorrect responses. To systematically analyze this effect, we identified states where each model exhibits *strong consistency*. We then conducted multi-agent debates using two identical agents initialized with the same model.

In our setup, we collected 40 trials per state, with each agent generating 20 responses at a fixed sampling temperature of 0.7. The same temperature was maintained during the MAD process to ensure consistent evaluation. Initial action distributions are shown in light red, while blue bars represent distributions after three rounds of debate. Ideally, if MAD functioned as an effective self-correction mechanism, the distribution would shift toward optimal actions.

However, we found the opposite: regardless of whether the initial reasoning was correct, the debate process consistently amplifies pre-existing biases rather than mitigating them. For instance, in the top-left graph of Figure 1, the GPT-4o-mini model initially selects a strongly consistent but suboptimal action (Action 3) 82.5% of the time, while only 15.0% of responses align with the optimal strategy. After multiple rounds of debate, instead of converging towards the correct decision, the model further entrenches its bias, increasing the frequency of the incorrect action to 90.0%. Notably, the proportion of optimal responses decreased even further, reinforcing the idea that MAD serves as an amplifier of existing biases rather than a corrective mechanism.

Figure 1: Bias reinforcement in NIM game by MAD. We compared initial action distribution and action distribution after 3 rounds of debates. MAD amplifies a model's biases, making debates favor consistent but potentially incorrect responses.

This phenomenon is not unique to GPT models but is also evident in the GEMINI series (bottom row of Figure 1). Despite architectural differences, GEMINI exhibited the same tendency. Furthermore, we observed that this reinforcement occurs regardless of whether the bias is "wrong" (leading to suboptimal moves) or "good" (aligning with optimal play). As illustrated, even in states

Figure 2: An example demonstrating how the debate process converges to a biased outcome. We observed that bias reinforcement occurs in the first debate. Blue text indicates the correct reasoning and orange text indicates the strong consistent (biased) reasoning. We skipped the second debate process because it follows a process nearly identical to those of the first and third debates. We utilize `GPT-4o-mini` as the debate agent.

where self-consistency initially aligns with optimal actions (good bias cases), the debate process did not introduce additional strategic insights but simply reinforces what is already dominant. In Figure 2, we illustrate in detail how two LLMs, after receiving the current state, produce initial responses and then proceed through a debate process. Notably, they converged on a strongly consistent line of reasoning, which may not necessarily be correct. We observed that only after the first round of debate do the two LLMs reach a consensus.

In Fibonacci: (Table 2) Following our analysis in the NIM game, we extended our investigation to the Fibonacci game, a more complex setting where move constraints and dynamic interactions shape strategic decision-making. We identified states where models exhibit *strong consistency* (threshold: 0.5) and examined whether debate reinforces or mitigates initial biases. As in NIM, we categorize states into those where strong consistency aligns with optimal strategies and those where it leads to suboptimal choices. The MAD framework is then applied to analyze how action distributions evolve post-debate (Table 2 (a), (b) for GPT models and (c), (d) for GEMINI models).

Our results confirm a consistent bias reinforcement effect: rather than converging toward optimal strategies, MAD causes models to reinforce their most self-consistent responses, regardless of correctness. As shown in Table 2, the proportion of responses adhering to the initially strong-consistent action increases after debate, indicating further entrenchment of bias. Our analysis shows that after the debate process, response reinforcement increases by 9.17% in GPT models and 12.29% in GEMINI models, indicating a notable shift towards initially dominant responses across both model families.

4.2 OPTIMAL INPUTS DO NOT REDUCE BIAS IN MAD

To analyze the extent of bias reinforcement in MAD, we conducted an additional experiment using `GPT-4o-mini` in the NIM game, as shown in Figure 3. We first collected 20 responses demonstrating strong consistency, where the model repeatedly selects the same biased action (`Action 2`) with high probability. Additionally, we curated another set of 20 responses exhibiting optimal strategic reasoning, where 80% of actions align with the game-theoretically optimal move (`Action 1`). We then introduced these responses into a multi-agent debate setting using only `GPT-4o-mini`, pairing each strongly consistent response with an optimal response, and observed how the model's reasoning evolves over multiple rounds of debate (denoted the situation in detail in §Appendix E).

Figure 3: Decline in optimal actions over debate rounds, demonstrating the convergence toward consistently biased reasoning. This observation underscores the difficulty of addressing inherent biases in LLMs through MAD.

Our findings reveal that rather than converging toward more optimal decision-making, the debate systematically reinforces the model's pre-existing biases. Initially, the curated dataset contained 80% optimal responses, yet after a single round of debate, the model predominantly aligned with the

Figure 4: **DReaMAD** framework in MAD method. **DReaMAD** improves LLM reasoning by combining **Strategic Prior Knowledge Elicitation** and **Perspective Diversification**. In the first stage, the model reinterprets the problem and formulates high-level strategies to reduce bias. In the second stage, multiple agents adopt distinct viewpoints, engage in structured debate, and refine their conclusions to enhance decision-making.

biased responses, reducing the proportion of optimal decisions. As the debate progressed, this effect intensified, with strong-consistency actions increasingly dominating. That is, even when explicitly injecting high-quality optimized responses, the debate process does not steer the model toward better reasoning. Instead, it systematically aligns with its pre-existing consistency patterns, reinforcing suboptimal but frequent choices.

This limitation in MAD highlights its tendency to amplify biases rather than correct them when strong self-consistency is present. However, applying **DReaMAD** with curated optimal responses significantly improved the preservation of correct reasoning, mitigating bias reinforcement. This underscores the need for mechanisms that introduce diverse perspectives beyond internal debate, which we further discuss in §5.

4.3 LACK OF REASONING DIVERSITY IN MAD

While MAD is designed to refine reasoning by allowing multiple agents to engage in discussion, its effectiveness is fundamentally limited by a lack of true diversity (§2.3). To address this limitation, Chen et al. (2023b) propose a multi-model debate framework that leverages multiple different models to generate diverse reasoning paths. However, our research focuses on self-correction methods that utilize a single model. We observe that even within the same model, slight variations in the prompts can lead to significantly different outputs (demonstrated in Appendix D). For instance, simply including or omitting the word *Fibonacci* in the prompt results in distinct reasoning trajectories. This suggests that diversity in reasoning can be enhanced by strategically modifying prompts within the same model, providing a practical alternative to multi-model debate frameworks.

5 **DReaMAD**: DIVERSE REASONING VIA MULTI-AGENT DEBATE

To address the limitations of Multi-Agent Debate (MAD) and improve strategic decision-making in Large Language Models (LLMs), we introduce **DReaMAD** (**D**iverse **Rea**soning via **M**ulti-**A**gent **D**ebate with Refined Prompt). Our framework refines prior knowledge and ensures diverse perspectives by extending MAD in two main stages:

1. **Strategic Prior Knowledge Elicitation:** The model redefines the problem, extracts key strategic insights, and formulates a high-level strategy before reasoning.

2. **Perspective Diversification:** Multiple agents are instantiated with self-generated distinct viewpoints to engage in dialectical reasoning.

After these stages, the agents conduct a structured multi-agent debate. A final post-debate refinement step then revisits their conclusions to improve reasoning quality. The complete workflow is illustrated in Figure 4 and the detailed prompt formulation used in these two modules is well documented in the Appendix C.

5.1 STRATEGIC PRIOR KNOWLEDGE ELICITATION

To address strong consistent bias, **DReaMAD** integrates a structured module that ensures systematic extraction and refinement of the LLM's internal strategic knowledge before the debate. First, the model is prompted to reinterpret the problem, leading to a more organized understanding of the

Figure 5: In this example, we illustrate how the debate process converges to an optimal outcome using `DReaMAD`. We begin with the same *current state* shown in Figure 2, employing self-generated prompts for each LLM agent.

strategic context (**Game Situation Reinterpretation**). Next, it formulates a set of high-level strategies that can be applied to the scenario at hand (**General Strategy Formulation**), preventing the model from settling too early on potentially flawed reasoning. As shown in Table 3, this module enhances the model's performance in tasks that require strategic prior knowledge (Figure 4-1). We set the *temperature* hyperparameter to be `0.1` for strategic consistency.

5.2 PERSPECTIVE DIVERSIFICATION

Building on MAD, `DReaMAD` mitigates argument homogenization by ensuring each agent adopts a distinct viewpoint prior to the debate. This approach is inspired by the *Learning from Multiple Approaches* concept in education theory (Council et al., 2005; Cleaves, 2008), which suggests that individuals improve their problem-solving skills by exploring multiple representations of the same problem. Analogously, this module ensures that each agent is given differentiated initial prompts that guide reasoning along distinct strategic trajectories. By self-customizing initial prompts for each model instance, `DReaMAD` encourages unique strategic perspectives and reduces the risk of bias reinforcement (Figure 4-2) as demonstrated in Figure 6. We set *temperature* hyperparameter to be `0.7` for diversity.

6 EXPERIMENTS

We utilized the new benchmark *MetaNIM Arena* as both our dataset and simulator. This environment is designed to evaluate the strategic reasoning capabilities of LLMs under adversarial conditions. Our investigation focuses on three key questions: (1) Does our approach improve reasoning quality compared to existing prompting techniques? (2) Does our approach prove its strategic reasoning

Table 3: Effect of Strategic Prior Knowledge Elicitation module. **DReaMAD**$^{(-)}$ indicates our method except multi-agent debate process. We can fully evaluate reasoning ability between different prompting methods. The metric accuracy of selecting optimal action is used. The best results are highlighted in **bold**.

LLM Models	Prompting Methods	NIM	Fibonacci	Chomp	Kayles	Average
GPT-4o	Standard-Prompting	0.95 ± 0.04	0.33 ± 0.04	0.18 ± 0.07	0.19 ± 0.08	0.41
	+ CoT-Prompting	0.96 ± 0.04	0.43 ± 0.11	$\mathbf{0.28} \pm 0.09$	0.20 ± 0.10	0.47
	DReaMAD$^{(-)}$	$\mathbf{0.98} \pm 0.04$	$\mathbf{0.44} \pm 0.09$	0.23 ± 0.10	0.23 ± 0.12	0.47
GPT-4o-mini	Standard-Prompting	0.75 ± 0.05	0.33 ± 0.04	0.40 ± 0.07	0.12 ± 0.06	0.40
	+ CoT-Prompting	0.84 ± 0.08	0.36 ± 0.06	0.61 ± 0.05	0.02 ± 0.03	0.46
	DReaMAD$^{(-)}$	$\mathbf{1.00} \pm 0.00$	$\mathbf{0.49} \pm 0.17$	$\mathbf{0.62} \pm 0.10$	$\mathbf{0.18} \pm 0.11$	$\mathbf{0.57}$
GEMINI-1.5-pro	Standard-Prompting	0.82 ± 0.06	0.42 ± 0.04	0.19 ± 0.08	0.57 ± 0.04	0.50
	+ CoT-Prompting	0.88 ± 0.05	0.47 ± 0.11	0.22 ± 0.11	0.59 ± 0.04	0.54
	DReaMAD$^{(-)}$	$\mathbf{0.97} \pm 0.04$	$\mathbf{0.53} \pm 0.07$	$\mathbf{0.24} \pm 0.05$	$\mathbf{0.72} \pm 0.12$	$\mathbf{0.62}$
GEMINI-1.5-flash	Standard-Prompting	0.94 ± 0.02	0.35 ± 0.04	0.05 ± 0.03	0.01 ± 0.02	0.34
	+ CoT-Prompting	0.93 ± 0.02	0.33 ± 0.07	$\mathbf{0.09} \pm 0.04$	0.0 ± 0.00	0.34
	DReaMAD$^{(-)}$	$\mathbf{0.97} \pm 0.04$	$\mathbf{0.45} \pm 0.06$	0.05 ± 0.00	$\mathbf{0.42} \pm 0.06$	$\mathbf{0.46}$
Average	Standard-Prompting	0.87	0.36	0.21	0.22	-
	+ CoT-Prompting	0.90	0.40	**0.30**	0.20	-
	DReaMAD$^{(-)}$	**0.98**	**0.48**	0.29	**0.39**	-

quality under adversarial decision-making environments? (3) Does generating diverse prompts contribute to better decision-making within the debate framework?

To address these questions, we compared **DReaMAD** against standard prompting methods, Chain-of-Thought (CoT), self-refinement (Madaan et al., 2024), and Multi-Agent Debate (MAD; Du et al. (2023) (standard and CoT prompts is explained in Appendix B). Our algorithm is built upon the work of Du et al. (2023), extending MAD to incorporate structured self-prompt refinement and perspective diversification. For self-refinement, we follow the methodology of Madaan et al. (2024), applying three iterative refinement steps. Similarly, for MAD, we conducted up to three rounds of debate, following Du et al. (2023), with the process terminating early if a consensus is reached before the final round. Additionally, we analyzed whether different LLM architectures, including GPT and GEMINI models, exhibit similar performance improvement through **DReaMAD**.

6.1 DOES **DReaMAD** IMPROVE REASONING QUALITY?

This experiment isolates the effect of strategic prior knowledge elicitation (§5.1), allowing us to assess whether our method enhances decision-making without relying on debate dynamics.

Setup. To evaluate the effectiveness of our approach in improving reasoning capabilities, we compare **DReaMAD** without the debate process against standard prompting and zero-shot CoT prompting across multiple models in the *MetaNIM Arena* dataset (§A.5). For showing versatility of **DReaMAD**, we conduct experiments on four variants of LLMs as shown in Table 3.

Results. Table 3 demonstrates that **DReaMAD** consistently outperforms both standard and CoT prompting across all

Figure 6: Effect of Perspective Diversification with two different prompts. (+)MAD vs **DReaMAD**. We run LLMs total 50 runs for each simulator and report average win-rate.

models and tasks. These results highlight the impact of our method in reinforcing structured strategic reasoning, even without the iterative correction process of debate. Notably, our approach leads to substantial improvements in NIM, Fibonacci, and Kayles, which are environments where long-term strategic planning plays a crucial role. Since defining a general winning strategy in Chomp is non-trivial, applying prior knowledge is challenging and results in less effectiveness compared to other games. Furthermore, we observe that models with inherently weaker reasoning abilities benefit the most from strategic prior knowledge elicitation (*e.g.,* GPT-4o-mini with +17%p, GEMINI-1.5-flash with +12%p on average).

6.2 **DReaMAD** IN ADVERSARIAL STRATEGIC DECISION-MAKING

Setup. We applied **DReaMAD** to GPT-4o-mini and GEMINI-1.5-flash and compared it with self-correction methods, including standard-prompt, self-refinement, and MAD. To demonstrate its effectiveness, we used GPT-4o as the opponent model due to its superior performance. In this

Table 4: Winning rate comparison across different models and different self-correction methods. This is an result based on *MetaNIM Arena* simulator. The best results are highlighted in **bold**.

Method	NIM		Fibonacci		Kayles		Chomp	
	Normal	Misère	Normal	Misère	Single	2 Rows	Rectangular	Square
GEMINI-1.5-flash	0.32	0.54	0.16	0.10	0.54	0.56	**0.78**	0.18
+ ReAct	0.10	0.68	0.16	0.76	0.50	0.30	0.42	0.12
+ Self-Refinement	0.14	0.66	0.18	0.36	0.50	0.46	0.46	0.16
+ Self-Consistency	0.04	0.28	**0.28**	0.86	-	-	-	-
+ MAD	0.06	0.30	0.12	0.78	0.54	0.20	0.74	0.14
+ DReaMAD	**0.38**	**0.84**	0.16	**0.94**	**0.58**	**0.62**	0.60	**0.22**
GPT-4o-mini	0.38	0.54	0.22	0.28	0.46	0.48	0.46	0.38
+ ReAct	0.22	0.68	0.20	0.34	0.40	0.26	0.58	0.34
+ Self-Refinement	0.22	0.70	0.18	0.50	0.46	0.52	0.52	0.44
+ Self-Consistency	0.14	0.52	0.34	0.46	-	-	-	-
+ MAD	0.28	0.62	0.22	0.82	0.42	0.28	0.52	**0.56**
+ DReaMAD	**0.98**	**0.74**	**0.54**	**0.94**	**0.68**	**0.84**	**0.64**	0.22

experiments, we utilized *MetaNIM Arena* simulator (§A.6) to maximize the effect of generating diverse prompts. We aimed to validate our hypothesis in a simulator that requires strategic decision-making within complex dynamics. We ran 50 independent episodes and average the win-rate.

Results. As shown in Table 4, **DReaMAD** consistently outperforms other self-correction methods across various strategic environments, demonstrating a significant improvement in winning rates. This result suggests that our approach enables LLM agents to effectively adapt to complex dynamics, particularly in adversarial decision-making scenarios where strategic reasoning is crucial. However, we observe that **DReaMAD** struggles in the Chomp game, which aligns with our hypothesis that Chomp lacks a well-defined generalized winning strategy. Unlike other tested environments, Chomp requires more exploratory play rather than direct reasoning from prior knowledge, highlighting a limitation of our method in environments where strategic heuristics are less structured.

6.3 DOES GENERATING DIVERSE PROMPTS IMPROVE PERFORMANCE?

We found that providing diverse prompts to multiple instances of the same model improves decision-making. To evaluate this, we generated identical prompts using the Strategic Prior Knowledge Elicitation module for two instances of the same model, denoted as (+)MAD, and distinct prompts for each instance, representing our proposed approach, as shown in Figure 6. We conducted experiments on four variants of *MetaNIM Arena* (NIM-Normal, NIM-Misère, Fibonacci-Normal, and Fibonacci-Misère) simulator (§A.6) total 50 episodes. Our results show that incorporating diverse prompts within the MAD framework significantly enhances performance, validating the effectiveness of our Perspective Diversification module.

Figure 7: Effect of Perspective Diversification by temperature. The Fibonacci dataset is evaluated 15 times with GPT-4o, averaged with a 95% confidence interval. Higher temperatures improve optimal action accuracy, showing that greater prompt diversity enhances reasoning performance.

Further, we examined the effect of varying *temperature* within the **DReaMAD** framework on the *MetaNIM Arena* Fibonacci dataset, adjusting it to 0.0, 0.2, 0.4, 0.6, 0.8, and 1.0 in the *Strategic Prior Knowledge Elicitation* and *Perspective Diversification* modules to assess its impact on prompt diversity. As shown in Figure 7, higher temperature (further diversity) correlates with increased optimal action accuracy, indicating that greater diversity in generated prompts contributes to improved reasoning performance.

7 CONCLUSIONS

Our study shows that Multi-Agent Debate (MAD) often reinforces biases instead of reducing them, leading to suboptimal reasoning. Through our experiments with the *MetaNIM Arena*, we have observed that models persist in biased reasoning even when presented with superior alternatives. While our current strategy focuses on strategic games, the principles of structured self-refinement and diversified reasoning could be valuable for a wider range of NLP tasks. These include complex activities such as multi-step reasoning in question answering, legal analysis, and scientific inference. Future work will explore how these techniques enhance decision-making beyond structured games.

ACKNOWLEDGMENTS

This work was supported by Center for Applied Research in Artificial Intelligence (CARAI) grant funded by DefenseAcquisition Program Administration (DAPA) and Agency for Defense Development (ADD) (UD230017TD).

REFERENCES

The claude 3 model family: Opus, sonnet, haiku.

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

Tolga Bolukbasi, Kai-Wei Chang, James Zou, Venkatesh Saligrama, and Adam Kalai. Man is to computer programmer as woman is to homemaker? debiasing word embeddings. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, NIPS'16, pp. 4356–4364, Red Hook, NY, USA, 2016. Curran Associates Inc. ISBN 9781510838819.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu, Wei Xue, Shanghang Zhang, Jie Fu, and Zhiyuan Liu. Chateval: Towards better llm-based evaluators through multi-agent debate. *arXiv preprint arXiv:2308.07201*, 2023.

Banghao Chen, Zhaofeng Zhang, Nicolas Langrené, and Shengxin Zhu. Unleashing the potential of prompt engineering in large language models: A comprehensive review. *arXiv preprint arXiv:2310.14735*, 2023a.

Justin Chih-Yao Chen, Swarnadeep Saha, and Mohit Bansal. Reconcile: Round-table conference improves reasoning via consensus among diverse llms. *arXiv preprint arXiv:2309.13007*, 2023b.

Xinyun Chen, Renat Aksitov, Uri Alon, Jie Ren, Kefan Xiao, Pengcheng Yin, Sushant Prakash, Charles Sutton, Xuezhi Wang, and Denny Zhou. Universal self-consistency for large language model generation. *arXiv preprint arXiv:2311.17311*, 2023c.

Wendy Pelletier Cleaves. Promoting mathematics accessibility through multiple representations jigsaws. *Mathematics Teaching in the Middle School*, 13(8):446–452, 2008.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

National Research Council, Suzanne Donovan, John Bransford, et al. *How students learn*. National Academies Press Washington, DC, 2005.

Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Jingyuan Ma, Rui Li, Heming Xia, Jingjing Xu, Zhiyong Wu, Tianyu Liu, et al. A survey on in-context learning. *arXiv preprint arXiv:2301.00234*, 2022.

Yilun Du, Shuang Li, Antonio Torralba, Joshua B Tenenbaum, and Igor Mordatch. Improving factuality and reasoning in language models through multiagent debate. *arXiv preprint arXiv:2305.14325*, 2023.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Steven J Edwards. Portable game notation specification and implementation guide. *Retrieved April*, 4:2011, 1994.

Andrew Estornell, Jean-Francois Ton, Yuanshun Yao, and Yang Liu. Acc-debate: An actor-critic approach to multi-agent debate, 2024.

Deep Ganguli, Amanda Askell, Nicholas Schiefer, Thomas I. Liao, Kamilė Lukošiūtė, Anna Chen, Anna Goldie, Azalia Mirhoseini, Catherine Olsson, Danny Hernandez, Dawn Drain, Dustin Li, Eli Tran-Johnson, Ethan Perez, Jackson Kernion, Jamie Kerr, Jared Mueller, Joshua Landau, Kamal Ndousse, Karina Nguyen, Liane Lovitt, Michael Sellitto, Nelson Elhage, Noemi Mercado, Nova DasSarma, Oliver Rausch, Robert Lasenby, Robin Larson, Sam Ringer, Sandipan Kundu, Saurav Kadavath, Scott Johnston, Shauna Kravec, Sheer El Showk, Tamera Lanham, Timothy Telleen-Lawton, Tom Henighan, Tristan Hume, Yuntao Bai, Zac Hatfield-Dodds, Ben Mann, Dario Amodei, Nicholas Joseph, Sam McCandlish, Tom Brown, Christopher Olah, Jack Clark, Samuel R. Bowman, and Jared Kaplan. The capacity for moral self-correction in large language models, 2023.

Seraphina Goldfarb-Tarrant, Rebecca Marchant, Ricardo Muñoz Sánchez, Mugdha Pandya, and Adam Lopez. Intrinsic bias metrics do not correlate with application bias. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 1926–1940, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.150.

Yufei Guo, Muzhe Guo, Juntao Su, Zhou Yang, Mengqiu Zhu, Hongfei Li, Mengyang Qiu, and Shuo Shuo Liu. Bias in large language models: Origin, evaluation, and mitigation, 2024.

Jie He, Tao Wang, Deyi Xiong, and Qun Liu. The box is in the pen: Evaluating commonsense reasoning in neural machine translation. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 3662–3672, 2020.

Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. Large language models cannot self-correct reasoning yet. In *The Twelfth International Conference on Learning Representations*, 2024.

Liwei Jiang, Jena D. Hwang, Chandra Bhagavatula, Ronan Le Bras, Jenny Liang, Jesse Dodge, Keisuke Sakaguchi, Maxwell Forbes, Jon Borchardt, Saadia Gabriel, Yulia Tsvetkov, Oren Etzioni, Maarten Sap, Regina Rini, and Yejin Choi. Can machines learn morality? the delphi experiment, 2022.

Ryo Kamoi, Yusen Zhang, Nan Zhang, Jiawei Han, and Rui Zhang. When can LLMs actually correct their own mistakes? a critical survey of self-correction of LLMs. *Transactions of the Association for Computational Linguistics*, 12:1417–1440, 2024. doi: 10.1162/tacl_a_00713.

Aviral Kumar, Vincent Zhuang, Rishabh Agarwal, Yi Su, John D Co-Reyes, Avi Singh, Kate Baumli, Shariq Iqbal, Colton Bishop, Rebecca Roelofs, Lei M Zhang, Kay McKinney, Disha Shrivastava, Cosmin Paduraru, George Tucker, Doina Precup, Feryal Behbahani, and Aleksandra Faust. Training language models to self-correct via reinforcement learning, 2024.

Tian Liang, Zhiwei He, Wenxiang Jiao, Xing Wang, Yan Wang, Rui Wang, Yujiu Yang, Shuming Shi, and Zhaopeng Tu. Encouraging divergent thinking in large language models through multi-agent debate. *arXiv preprint arXiv:2305.19118*, 2023.

Guangliang Liu, Haitao Mao, Bochuan Cao, Zhiyu Xue, Xitong Zhang, Rongrong Wang, Jiliang Tang, and Kristen Johnson. On the intrinsic self-correction capability of llms: Uncertainty and latent concept, 2024.

Yao Lu, Max Bartolo, Alastair Moore, Sebastian Riedel, and Pontus Stenetorp. Fantastically ordered prompts and where to find them: Overcoming few-shot prompt order sensitivity. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 8086–8098, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-long.556.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, et al. Self-refine: Iterative refinement with self-feedback. *Advances in Neural Information Processing Systems*, 36, 2024.

Costas Mavromatis, Balasubramaniam Srinivasan, Zhengyuan Shen, Jiani Zhang, Huzefa Rangwala, Christos Faloutsos, and George Karypis. Which examples to annotate for in-context learning? towards effective and efficient selection. *arXiv preprint arXiv:2310.20046*, 2023.

Jane Pan. What in-context learning "learns" in-context: Disentangling task recognition and task learning. Master's thesis, Princeton University, 2023.

Laria Reynolds and Kyle McDonell. Prompt programming for large language models: Beyond the few-shot paradigm. In *Extended Abstracts of the 2021 CHI Conference on Human Factors in Computing Systems*, CHI EA '21, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450380959. doi: 10.1145/3411763.3451760.

Sander Schulhoff, Michael Ilie, Nishant Balepur, Konstantine Kahadze, Amanda Liu, Chenglei Si, Yinheng Li, Aayush Gupta, HyoJung Han, Sevien Schulhoff, Pranav Sandeep Dulepet, Saurav Vidyadhara, Dayeon Ki, Sweta Agrawal, Chau Pham, Gerson Kroiz, Feileen Li, Hudson Tao, Ashay Srivastava, Hevander Da Costa, Saloni Gupta, Megan L. Rogers, Inna Goncearenco, Giuseppe Sarli, Igor Galynker, Denis Peskoff, Marine Carpuat, Jules White, Shyamal Anadkat, Alexander Hoyle, and Philip Resnik. The prompt report: A systematic survey of prompting techniques, 2024a.

Sander Schulhoff, Michael Ilie, Nishant Balepur, Konstantine Kahadze, Amanda Liu, Chenglei Si, Yinheng Li, Aayush Gupta, HyoJung Han, Sevien Schulhoff, et al. The prompt report: A systematic survey of prompting techniques. *arXiv preprint arXiv:2406.06608*, 2024b.

Philip Wootaek Shin, Jihyun Janice Ahn, Wenpeng Yin, Jack Sampson, and Vijaykrishnan Narayanan. Can prompt modifiers control bias? a comparative analysis of text-to-image generative models, 2024.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *arXiv preprint arXiv:2303.11366*, 2023.

Andries Smit, Nathan Grinsztajn, Paul Duckworth, Thomas D. Barrett, and Arnu Pretorius. Should we be going mad? a look at multi-agent debate strategies for llms. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org, 2024.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.

Yuxuan Wan et al. Self-polish: Enhance reasoning in large language models via problem refinement. *arXiv preprint arXiv:2305.14497*, 2023.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*, 2022.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Jules White, Quchen Fu, Sam Hays, Michael Sandborn, Carlos Olea, Henry Gilbert, Ashraf Elnashar, Jesse Spencer-Smith, and Douglas C Schmidt. A prompt pattern catalog to enhance prompt engineering with chatgpt. *arXiv preprint arXiv:2302.11382*, 2023.

Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah Goodman. STar: Bootstrapping reasoning with reasoning. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022.

Xufeng Zhao, Mengdi Li, Wenhao Lu, Cornelius Weber, Jae Hee Lee, Kun Chu, and Stefan Wermter. Enhancing zero-shot chain-of-thought reasoning in large language models through logic. In Nicoletta Calzolari, Min-Yen Kan, Veronique Hoste, Alessandro Lenci, Sakriani Sakti, and Nianwen Xue (eds.), *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pp. 6144–6166, Torino, Italia, May 2024. ELRA and ICCL.

A MetaNIM Arena

(fixed) action space: 1 - N   (fluid) action space: 1 - F   (fixed) action space: 1 - 2 (adjacent)   action space: x, y coordinate

NIM   Fibonacci   Kayles   Chomp

Figure 8: The concept illustration of MetaNIM Arena. A detailed explanation of each game can be found in Appendix A.

Algorithm 1 MetaNIM Arena: Turn-Based Opponent Task with Two Agents

---

Require: Initial State S_0, Goal Condition G, Agents A_1 and A_2
Ensure: Final State S_f and Outcome
1: $t \leftarrow 0$ *Initialize turn counter*
2: $S \leftarrow S_0$ *Set initial state*
3: **while** $S \notin G$ **and** game is not terminated **do**
4:     **if** $t \bmod 2 = 0$ **then**
5:        $a_t \leftarrow A_1(S)$ *Agent 1's turn, selects action a_t*
6:     **else**
7:        $a_t \leftarrow A_2(S)$ *Agent 2's turn, selects action a_t*
8:     **end if**
9:     $S \leftarrow \text{UpdateState}(S, a_t)$ *Apply the action and update state*
10:    $t \leftarrow t + 1$ *Increment turn counter*
11:    **if** $S \in G$ **then**
12:       **Success**: Goal Achieved
13:    **end if**
14: **end while**

A.1 NIM

Nim is a mathematical strategy game where two players alternate turns removing objects from distinct heaps/piles. The classic version follows these rules:

- **Heaps**: The game starts with k heaps containing $n_1, n_2, \ldots, n_k$ objects respectively

- **Moves**: On their turn, a player must remove at least 1 to previously fixed number of objects from exactly one heap

- **Objective**: The player who takes the last remaining object wins (normal play convention)

Mathematical Strategy The game can be analyzed using binary representations through the concept of **Nimbers** (Grundy numbers). For any position, the key is to calculate the binary XOR (exclusive OR) sum of all heap sizes:

$$\text{Nim-sum} = n_1 \oplus n_2 \oplus \cdots \oplus n_k$$

A position is **losing** if the Nim-sum equals 0. The winning strategy consists of always moving to a position with Nim-sum 0. For the single-heap variant (as in our current game), this simplifies to maintaining modular arithmetic conditions.

Example Consider a game with heaps [3, 4, 5]:

$$3 = 011_2$$
$$4 = 100_2$$
$$5 = 101_2$$
$$\text{Nim-sum} = 011_2 \oplus 100_2 \oplus 101_2 = 010_2 = 2 \neq 0$$

The first player can win by removing 2 objects from the 5-object heap to make the new Nim-sum 0.

Variants Several Nim variants exist, including:

- Single-heap Nim (as in our current game)
- Misère Nim (player taking last object *loses*)
- Multi-heap Nim with different removal constraints

The fundamental mathematical principles of combinatorial game theory apply to all variants.

A.2   FIBONACCI

The Fibonacci Game, also known as **Fibonacci Nim**, is a combinatorial number game where players alternate removing items from a pile, with move constraints based on the Fibonacci sequence. The rules are:

- **Initial Move**: First player takes $1 \leq k < n$ items from a pile of n items
- **Subsequent Moves**: Each player must take between 1 and *twice* the number of items taken by their opponent in the previous move
- **Objective**: The player who takes the last item wins

Mathematical Strategy The game is governed by Fibonacci numbers ($F_1 = 1, F_2 = 2, F_n = F_{n-1} + F_{n-2}$) and **Zeckendorf's Theorem**, which states that every positive integer can be uniquely expressed as a sum of non-consecutive Fibonacci numbers.

- **Losing Positions**: Pile sizes equal to Fibonacci numbers (F_n)
- **Winning Strategy**: Reduce the pile to the largest Fibonacci number smaller than the current size

For a pile of size m, its Zeckendorf representation is:

$$m = F_{k_1} + F_{k_2} + \cdots + F_{k_r} \quad (|k_i - k_j| \geq 2)$$

The optimal first move is to remove the *smallest* Fibonacci number in this decomposition.

Example For a starting pile of $m = 20$:

$$\text{Zeckendorf: } 20 = 13 + 5 + 2 \quad (F_7 = 13, F_5 = 5, F_3 = 2)$$
$$\text{First move} = \text{Remove smallest term 2}$$
$$\text{New pile} = 18 = 13 + 5$$

Now the opponent faces a position composed purely of Fibonacci numbers. Any move they make ($1 \leq x \leq 4$) can be countered by reducing the pile to the next Fibonacci number.

Key Properties

- If m is a Fibonacci number, the first player will lose against perfect play
- The number of moves in a game is always $\leq$ the index of the largest Fibonacci number $\leq m$
- The golden ratio $\phi = \frac{1+\sqrt{5}}{2}$ emerges in win/loss probability analysis

Variants

- Reverse Fibonacci Nim (last player to move loses)
- Multi-pile Fibonacci games
- Constrained Fibonacci sequences (e.g., Tribonacci variants)

This game demonstrates deep connections between combinatorial game theory, number theory, and the Fibonacci sequence.

A.3 KAYLES

Kayles is an impartial combinatorial game played with a linear arrangement of pins where players alternate knocking down pins under specific adjacency rules. First analyzed in 1929 by Dudeney and later studied by Conway and Berlekamp, it demonstrates complex mathematical patterns.

Basic Rules

- **Initial Setup**: A row of n identical pins
- **Moves**: On each turn, a player must either:
  - Knock down 1 pin
  - Knock down 2 adjacent pins
- **Objective**: Last player to make a valid move wins (normal play convention)

Mathematical Analysis   The game is analyzed using **Grundy numbers** and the **Sprague-Grundy theorem**. Positions split into independent segments after moves create disjunctive game components.

- Let $G(n)$ be the Grundy number for a row of n pins
- Recursive Grundy number calculation:

$$G(n) = \operatorname{mex}\{G(n-1), G(n-2), G(a) \oplus G(b)\}$$

  where $a + b = n - k$ for $k \in \{1, 2\}$, and mex = minimum excludant

Key Patterns

- Positions with Grundy number 0 are losing positions
- The Grundy sequence becomes periodic with period 12 for large n
- Known solution: $G(n) = n \mod 12$ when $n \geq 70$

Example   Consider a row of 4 pins:

$$G(0) = 0$$
$$G(1) = \operatorname{mex}\{G(0)\} = 1$$
$$G(2) = \operatorname{mex}\{G(1), G(0), G(0) \oplus G(0)\} = \operatorname{mex}\{1, 0, 0\} = 2$$
$$G(3) = \operatorname{mex}\{G(2), G(1), G(1) \oplus G(0)\} = \operatorname{mex}\{2, 1, 1\} = 0$$
$$G(4) = \operatorname{mex}\{G(3), G(2), G(2) \oplus G(0)\} = \operatorname{mex}\{0, 2, 2\} = 1$$

A row of 4 pins has Grundy number 1, making it a winning position.

Strategic Principles

- Split long rows into independent segments with XOR-sum 0
- Mirror opponent's moves in symmetric positions
- Avoid leaving isolated single pins

Variants

- Circular Kayles (pins arranged in a circle)
- Multi-row Kayles
- k-Kayles (allow knocking down up to k adjacent pins)
- Misère Kayles (last player to move loses)

Computational Complexity   Kayles is:

- PSPACE-complete for general positions
- Solved in linear time for standard single-row play
- Used in complexity theory to study impartial games

This analysis demonstrates how simple rule sets can generate complex mathematical structures. The complete Grundy number sequence for Kayles was only fully determined through extensive computational analysis.

A.4   CHOMP

Chomp is an impartial combinatorial game first formulated by David Gale in 1974. Played on a rectangular grid representing a chocolate bar, it features unique topological constraints and demonstrates fundamental principles of partially ordered sets (posets).

Basic Rules

- **Initial Setup**: An $m \times n$ rectangular grid of "chocolate squares"
- **Special Square**: The lower-left square (position (1,1)) is poisoned
- **Moves**: On each turn, a player must:
    - Select any remaining square
    - Remove ("chomp") all squares above and/or to the right of the selected square
- **Objective**: Avoid taking the poisoned square - last player to make a valid move wins (normal play convention)

Mathematical Analysis   Chomp is particularly significant in combinatorial game theory because:

- It is a **partisan game** with inherent asymmetry
- The starting position is a poset under component-wise ordering
- A winning strategy exists for the first player (proven by strategy-stealing argument), though explicit strategies are unknown for most grid sizes

KEY THEOREM (GALE, 1974)

Theorem A.1. *For any initial grid size $m \times n$ where $m, n \geq 2$, the first player has a winning strategy.*

Example: 2 × 3 Grid

$$\begin{bmatrix} \circ & \circ & \circ \\ \bullet & \circ & \circ \end{bmatrix}$$

First player wins by taking the (2,3) square:

- If Player 2 takes (1,3), Player 1 takes (2,2)
- If Player 2 takes (2,2), Player 1 takes (1,2)
- All paths eventually force Player 2 to take the poison

Strategic Principles

- Maintain control of the antidiagonal
- Force symmetry when possible
- Reduce the game to independent subgames
- Avoid leaving isolated columns

Computational Complexity

- General Chomp is PSPACE-complete
- Solved in polynomial time for:
  - $2 \times n$ grids
  - Square grids up to 5×5
- Number of winning positions grows exponentially with grid size

Variants

- 3D Chomp (cuboidal grids)
- Circular Chomp
- Hypergraph Chomp
- Misère Chomp (taking poison square wins)
- Numerical Chomp (played on factor lattices)

Significance   Chomp demonstrates fundamental connections between:

- Combinatorial game theory
- Computational complexity
- Algebraic geometry (via Gröbner basis interpretations)

Despite its simple rules, Chomp remains unsolved for general grid sizes, making it an active research area in computational combinatorics.

A.5   OUR DATASET USED IN EXPERIMENTS

We construct simple dataset based on the *MetaNIM Arena*. This dataset doesn't require any opponent model because samples in this dataset is focusing on the specific scene in each game.

Table 5: Constructed dataset using *MetaNIM Arena*. We conduct an experiment on this dataset and report the results in Table 3.

Methods	NIM	Fibonacci	Chomp	Kayles
action space	1 - 3	dynamic (Max:30)	x, y coordinate (differ to the scenario)	a pin or adjacent two pins index
variants	Normal	Normal	Square (2x2 ∼ 19x19)	Normal
# of different samples	20	11	20	18

A.6   OUR SIMULATOR USED IN EXPERIMENTS

We build simulator based on the *MetaNIM Arena*. This simulator requires any opponent available to receive prompt and make an output as an action. Here, we utilize the gpt-4o model as an opponent.

Features	NIM		Fibonacci	
	Normal	Misère	Normal	Misère
Starting Point	remaining items: 31	remaining items: 31	remaining items: 20	remaining items: 20
Winning Condition	taking last item	avoiding last item	taking last item	avoiding last item
First Player?	✓	✓	✓	✓
Action Space	1 - 3	1 - 3	dynamic	dynamic
Opponent	gpt-4o-2024-08-06			

Table 6: MetaNIM Arena Simulator: NIM and Fibonacci

Features	Kayles		Chomp	
	Single	2 Rows	Rectangular	Square
Starting Point	remaining items: 20	1 pile: 5, 2 pile: 6	2x8	5x5
Winning Condition	taking last item	taking last item	avoiding poison (top-left)	avoiding poison (top-right)
First Player?	✓	✓	✓	✓
Action Space	pile index	pile index (row, column)	x, y coordinate	x, y coordinate
Opponent	gpt-4o-2024-08-06			

Table 7: MetaNIM Arena Simulator: Kayles and Chomp

B PROMPTS

B.1 GAME PROMPTS

Figure 9: Nim and Fibonacci game prompts

Figure 10: Kayles and Chomp game prompts

B.2 PROMPTS FOR INITIAL REASONING

B.2.1 STANDARD & CoT PROMPTS

In our evaluation of LLMs within the *MetaNIM Arena,* we compare two key prompting techniques: Standard Prompting and Chain-of-Thought (CoT) Prompting. The distinction between these approaches significantly impacts the model's reasoning and decision-making process.

Standard Prompting Standard prompting provides a direct task description, outlining the game rules, current state, and the required decision. The model is expected to generate an action with proper explicit reasoning steps to determine the best move. This method is efficient but often leads to suboptimal decisions, as the model may fail to retrieve and apply deeper strategic reasoning.

Chain-of-Thought (CoT) Prompting CoT prompting extends the standard prompt by explicitly instructing the model to think step-by-step before making a decision. By guiding the model through an explicit reasoning process, CoT enables it to break down the problem, consider strategic implications,

and refine its choices before committing to an action. This often leads to improved decision-making, particularly in multi-step strategic environments where deeper reasoning is required.

Key Difference and Impact   As illustrated in Figure 11, the only modification in the CoT prompt is the addition of a simple directive: "Let's think step-by-step. What is the best move for you?" This small change significantly alters the model's reasoning trajectory, encouraging more structured and strategic decision-making. Our experimental results (detailed in §3) confirm that CoT prompting leads to a measurable improvement in decision accuracy, particularly in complex scenarios where retrieving and applying prior knowledge is essential.

By leveraging CoT, we can enhance the model's ability to explain its decisions, mitigate biases, and adapt more effectively to adversarial settings. However, as we further discuss in Experiment Section, CoT has limitations to leverage the strategic reasoining well in our proposed environment, necessitating additional mechanisms to further enhance strategic reasoning.

Figure 11: Standard and CoT Prompts.

Prompting Strategy for Opponent Modeling   Anything can act as an opponent in the *MetaNIM Arena* simulator, but we model OpenAI's `GPT-4o`, the most powerful LLM model currently available, as the opponent and apply the standard prompting method.

C DReaMAD$^{(-)}$: Structured Prompt Optimization without Debate

While the full **DReaMAD** framework integrates multi-agent debate to refine strategic reasoning, its core prompting methodology—excluding debate—remains a powerful mechanism for enhancing decision-making. This streamlined version, **DReaMAD**$^{(-)}$, focuses on three key stages to systematically extract and refine strategic knowledge, improving reasoning diversity and mitigating bias.

1. Game Situation Reinterpretation The first step involves extracting fundamental game principles from the standard prompt. The model is tasked with identifying key elements, such as:

- Game Definition: The nature of the game and its mechanics.
- Winning Condition: The criteria for victory.
- Move Constraints: The permissible actions per turn.

This step ensures that the model builds a structured understanding of the strategic environment before making decisions.

2. General Strategy Formulation After extracting the core game elements, the model derives a generalized winning strategy applicable to various game states. It generates:

- State Evaluation: How to assess the game state at any given turn.
- Winning Strategy: The optimal decision-making framework for victory.
- Endgame Tactics: Best strategies in near-win scenarios.

This formulation helps structure the model's reasoning beyond the immediate game context, fostering more strategic foresight.

3. Perspective Diversification Finally, the model refines the original prompt using the extracted strategic knowledge. This process introduces structured variations to the initial prompt to encourage diverse reasoning, rather than reinforcing a singular bias. The self-refined prompt:

- Guides decision-making explicitly.
- Prioritizes winning strategies.
- Encourages logical, step-by-step reasoning.

This structured refinement ensures that LLMs adopt distinct strategic viewpoints even without external debate, improving their adaptability and robustness in adversarial environments.

By systematically structuring knowledge retrieval and refining prompts, **DReaMAD**$^{(-)}$ enhances strategic reasoning as illustrated in Figure 10, this approach strengthens the model's ability to retrieve and apply prior knowledge effectively, offering a scalable solution for improving LLM-based decision-making.

Figure 12: **DReaMAD** $^{(-)}$ Prompt.

D   A WORD CHANGE IN PROMPTS LEAD TO DIFFERENT OUTPUT

(a) Prompt   (b) Response by ReAct

Figure 13: According the word *Fibonacci* usage, the reasoning and the performance differs.

D.1   PROMPT BIAS: THE SENSITIVITY OF LLM REASONING TO PROMPT VARIATIONS

Despite the remarkable problem-solving capabilities of Large Language Models (LLMs), their reasoning is highly sensitive to subtle changes in prompt phrasing. As demonstrated in Figure 13, even a single word variation in the prompt can significantly alter the reasoning process and final decision-making. This phenomenon underscores a critical limitation in LLM-based strategic reasoning: models do not inherently generalize optimal strategies but instead rely on heuristic cues embedded within the prompt.

D.1.1   IMPACT OF WORD CHOICE ON STRATEGIC REASONING

Figure 13 compares LLM responses when the word *Fibonacci* is explicitly mentioned versus when it is omitted in an identical game scenario. In the presence of the keyword *Fibonacci*, the model aligns

its reasoning with Fibonacci-based strategy, leveraging number sequences to maintain control over the game. Conversely, when the term is absent, the model defaults to an alternative heuristic, such as maintaining a multiple of three or even resorting to a trivial greedy strategy. For instance, in the first decision step, when instructed with *Fibonacci*, the model identifies 13 as the closest Fibonacci number and takes 7 stones, ensuring an advantageous future state. Without the keyword, however, the model applies a modulo-based heuristic, taking only 2 stones to leave a multiple of three. Similarly, in the second decision step, the *Fibonacci*-aware model deliberately leaves 8 stones in the pile—another Fibonacci number—while the other instance simply takes all remaining stones without strategic foresight.

D.1.2 IMPLICATIONS FOR ROBUST PROMPTING

This stark contrast highlights the fundamental issue that LLMs do not inherently retrieve the most effective strategic reasoning but are instead disproportionately influenced by linguistic cues. The reliance on explicit terminology for optimal reasoning raises concerns about robustness, as different wordings of the same task can lead to dramatically different problem-solving approaches. This suggests that ensuring reliable strategic reasoning in LLMs requires more than just fine-tuned prompts; it necessitates methods that encourage models to autonomously retrieve and apply domain knowledge without over-reliance on explicit wording cues.

These observations motivate our approach in **DReaMAD**, where we systematically refine LLMs' strategic reasoning by structuring prior knowledge retrieval and diversifying input perspectives. By mitigating the sensitivity to prompt variations, our method enhances the robustness and consistency of LLM decision-making across different strategic environments.

E ABLATION STUDY SETUP

For Figure 3, we explain the situation used in this experiment.

Figure 14: The situation and debate process of the experiments in Figure 3