MULTI-AGENT DECISION S4: LEVERAGING STATE SPACE MODELS FOR OFFLINE MULTI-AGENT REINFORCEMENT LEARNING

ABSTRACT

Goal-conditioned sequence-based supervised learning with transformers has shown promise in offline reinforcement learning (RL) for single-agent settings. However, extending these methods to offline multi-agent RL (MARL) remains challenging. Existing transformer-based MARL approaches either train agents independently, neglecting multi-agent system dynamics, or rely on centralized transformer models, which face scalability issues. Moreover, transformers inherently struggle with long-term dependencies and computational efficiency. Building on the recent success of Structured State Space Sequence (S4) models, known for their parameter efficiency, faster inference, and superior handling of long context lengths, we propose a novel application of S4-based models to offline MARL tasks. Our method utilizes S4's efficient convolutional view for offline training and its recurrent dynamics for fast on-policy fine-tuning. To foster scalable cooperation between agents, we sequentially expand the decision-making process, allowing agents to act one after another at each time step. This design promotes bi-directional cooperation, enabling agents to share information via their S4 latent states or memory with minimal communication. Gradients also flow backward through this shared information, linking the current agent's learning to its predecessor. Experiments on challenging MARL benchmarks, including Multi-Robot Warehouse (RWARE) and StarCraft Multi-Agent Challenge (SMAC), demonstrate that our approach significantly outperforms state-of-the-art offline RL and transformer-based MARL baselines across most tasks.

1 INTRODUCTION

Multi-agent reinforcement learning (MARL) has demonstrated significant success in learning complex policies that require coordination among multiple agents to maximize a shared objective (Cao et al., 2012; Berner et al., 2019; Ye et al., 2015). However, this success often relies on a substantial number of interactions with the environment, which can be computationally expensive in high-fidelity simulations or prohibitively risky in real-world applications. To enhance sample efficiency, offline reinforcement learning (RL) algorithms (Lee et al., 2021; Fujimoto et al., 2019; Kumar et al., 2019; 2020; Kostrikov et al., 2021; Xu et al., 2022a; Li et al., 2022; Xu et al., 2023) have been developed, enabling learning from pre-collected offline datasets, thus reducing the need for extensive online interactions.

Offline RL is plagued by the well-known issue of distribution shift, which leads to extrapolation errors when encountering out-of-distribution (OOD) samples during policy training. This occurs when the learned policy deviates from the unknown behavior policy used to collect the training data. To mitigate this, various forms of regularization (Kumar et al., 2019) are introduced to ensure that the learned policy remains close to the behavior policy (Kumar et al., 2020; Xu et al., 2023; 2022a). In multi-agent settings, the joint state-action space expands exponentially as the number of agents increases. This makes it challenging to apply these regularization techniques globally, leading to sparse and less effective regularization constraints, especially when working with a limited offline dataset.

Sequence-based supervised learning has been concurrently applied to address offline MARL, leveraging the significant success of supervised learning in capturing complex patterns from large offline datasets. This approach, first introduced by the Decision Transformer (DT) (Chen et al., 2021), has demonstrated its ability to learn policies in an autoregressive fashion by predicting the next action based on the current state, previous action and the desired return-to-go. While efforts have been made to extend DT-based architectures to offline MARL (Meng et al., 2021; Tseng et al., 2022), certain limitations persist. MADT (Meng et al., 2021) adapts DT independently for each agent in the multi-agent settings, failing to explicitly model cooperation between agents. (Tseng et al., 2022) adopts a similar approach and trains a centralized teacher policy to capture agent interactions, with individual agents learning through policy distillation. However, centralized transformers face scalability issues, requiring training on information from all agents. Additionally, these approaches inherit the inherent limitations of transformers, such as large model sizes, inefficient runtime inference, and restricted ability to capture long-range dependencies due to fixed window size constraints.

Structured State Space Sequence (S4) models (Gu et al., 2021a) have recently been shown to outperform transformer-based models in single-agent offline RL tasks (Bar-David et al., 2023). Building on this success, we propose a sequence-learning-based offline MARL algorithm using S4 variants, which offer superior parameter efficiency compared to transformers and can capture longer contexts with constant-time inference. Unlike previous works, such as MADT, our approach does not train agents independently. To model cooperation among agents, we adopt a sequentially expanded MDP (SE-MDP) paradigm, where each decision-making step is divided into mini-steps. This approach has also been recently used in online MARL settings (Li et al., 2023), where each agent takes an action at a given mini-step based on the actions of all preceding agents in the sequence. In our work, we allow limited communication between the agents, with each agent receiving information only from its immediate predecessor in the sequence. This provides a scalable training mechanism that encourages inter-agent cooperation. Information is shared leveraging the latent state representation of the S4 model, which encodes an agent's memory and serves as a more accurate representation of the current state in the partially observable MDPs typical of MARL tasks. This design further helps to mitigate non-stationarity issues during the online training phase. This form of training also shares similarities with the way information is passed between segments of long sequences in Recurrent Memory Transformer (RMT) (Bulatov et al., 2022).

The S4-based agents are trained directly on sequences or trajectories from the offline dataset in an efficient convolutional manner. The offline pre-trained models can be further used for sample-efficient online fine-tuning based on individual tuples instead of sequences leveraging the recurrent view of S4. We evaluate the performance of our developed algorithm, called Multi-Agent Decision S4 (MADS4), on the challenging offline MARL benchmarks of Multi-Robot Warehouse (RWARE) (Papoudakis et al., 2020) and StarCraft2 Multi-Agent Challenge (SMAC) (Samvelyan et al., 2019), where MADS4 achieves superior performance across many tasks over state-of-the-art offline RL-based and transformer-based baselines.

2   RELATED WORK

Offline Reinforcement Learning   Offline RL allows for policy learning based on pre-collected datasets without having access to active interactions with the environment (Levine et al., 2020), which is then directly used as the final policy or is used as a starting point for further improvement (Uchendu et al., 2023). This learning paradigm however results in severe distribution shift and extrapolation errors during policy evaluation on OOD samples not present in the offline dataset (Kumar et al., 2019; Fujimoto et al., 2019). Several approaches have been developed to mitigate this issue which typically involves various types of regularizations to be near the offline data distribution. Policy-based regularizations implicitly or explicitly constrain the policy to be close to the behavior policy of the dataset (Wu et al., 2019; Xu et al., 2021; Cheng et al., 2024; Li et al., 2022). Value-based regularizations aim to learn conservative value functions on OOD samples (Kumar et al., 2020; Kostrikov et al., 2021; Xu et al., 2022b). Other approaches involve including uncertainty (Wu et al., 2021; Bai et al., 2022) or penalizing OOD rewards (Yu et al., 2020).

On the other hand, Decision Transformer (DT) (Chen et al., 2021) takes a goal-conditioned supervised learning (GCSL) approach to formulate offline RL as a sequence modeling task and outperforms many state-of-the-art offline RL algorithms. Following the success of this training regime,

Figure 1: Multi-Agent MDP (MMDP) is restructured into a Sequentially-Expanded MDP (SE-MDP) where the multi-agent state transition at each timestep is decomposed into n intermediate states. In this framework, each agent processes its input alongside information received from its preceding agent, then takes an action and passes updated information to the next agent in the sequence. During training, gradient flows backward, enabling earlier agents to receive updates based on the information passed by later agents.

Decision S4 (Bar-David et al., 2023) proposes using S4 model variants for higher parameter efficiency, capturing longer sequences and faster inference.

Offline MARL   Extending single-agent RL methods to multi-agent settings presents significant challenges due to the exponential growth of the joint state-action space. Most MARL algorithms adopt the Centralized Training with Decentralized Execution (CTDE) paradigm. In CTDE, global information is shared during training, and local, decoupled policies are used for execution (Oliehoek et al., 2008; Sunehag et al., 2017; Rashid et al., 2020; Son et al., 2019; Wang et al., 2020; Foerster et al., 2017; Lowe et al., 2017; Yu et al., 2021). Recently, offline RL-based MARL algorithms have emerged, typically applying regularizations on local policies or value functions (Yang et al., 2021; Jiang & Lu, 2023; Pan et al., 2022). On the other hand, (Meng et al., 2021) extends the Decision Transformer (DT) (Chen et al., 2021) to a multi-agent setting, where agents are trained independently by sharing weights within a goal-conditioned supervised learning framework.

However, these algorithms do not provide guarantees of global-level regularizations and fail to explicitly or implicitly learn cooperative behavior. Only a few recent works have tried to tackle these limitations. For example, (Wang et al., 2024) uses an implicit global to-local regularization, and (Tseng et al., 2022) uses knowledge distillation to distill cooperation in the local policies.

S4   S4(Gu et al., 2021a;b) and their variants (Gupta et al., 2022; Smith et al., 2022), which are developed on time-invariant linear state space layers, have outperformed transformers in capturing long-range contexts. These models require far fewer parameters and have constant time inference; hence, they have been suitably utilized in reinforcement learning domains in single-agent learning (Bar-David et al., 2023) and in-context learning (Lu et al., 2024). Commonly, the model uses the convolutional mode for efficient parallelizable training (where the whole input sequence is seen ahead of time) and switched into a recurrent mode for efficient autoregressive inference (where the inputs are seen one timestep at a time).

3   METHODOLOGY

Sequentially Expanded MDP   In this section, we present our approach based on sequence learning with state-space layers. In this work, the Multi-agent Markov Decision Process (MMDP) is transformed into a Sequentially Expanded Markov Decision Process (SE-MDP), where each

timestep is divided into n mini timesteps and a multi-agent decision by n agents is expanded into a sequence of n individual decisions, with only one agent acting during each mini-timestep. Thus, a single-step transition in the original MMDP $(s^t, \boldsymbol{a}^t, s^{t+1})$ resulting in a shared reward $r(s^t, \boldsymbol{a}^t)$ is composed of a sequence of n intermediate transitions, which in turn result in the same shared reward $r(s^t, \boldsymbol{a}^t)$, as shown in Figure 1.

$$(s^t, \boldsymbol{a}^t, s^{t+1}) = \{(s^t, a_1^t, s_{a_1}^t), (s_{a_1}^t, a_2^t, s_{a_{1:2}}^t), ..., (s_{a_{1:n-1}}^t, a_n^t, s_{a_{1:n}}^t = s^{t+1})\} \quad (1)$$

Within this framework, at each timestep, an agent's action is based on information passed by the immediately preceding agent in the sequence. This creates a bidirectional dependency between the agents as shown in Figure 1: in the forward direction, an agent's action is influenced by the actions of its predecessors, while in the backward direction, gradients can propagate from the current agent back to the previous agents.

Sequence-based reinforcement learning Offline RL is formulated as a supervised learning problem by predicting actions in an autoregressive manner typically conditioned on current states, previously executed actions, and desired returns to go. This paradigm was introduced in (Chen et al., 2021), where the DT is trained to predict current actions based on returns to go instead of current rewards in order to have better actions that are correlated with better future rewards. This work utilizes this supervised learning setting, where the state, action, and reward of i^{th} agent at each timestep are denoted as s_i, a_i, r_i, and its trajectories $\tau : (s_0, a_0, r_0, s_1, a_1, r_1, ..., s_L, a_L, r_L)$ consist of sequences of state, action, and reward tuples. Since the models are trained on returns-to-go, the trajectories are restructured as $\tau : (R_0, s_0, a_0, R_1, s_1, a_1, ..., R_L, s_L, a_L)$ where $R_i = \sum_{t=i}^{N} r_i$ is the returns to go from i^{th} time step.

S4-based Agent The structured state space models (SSMs) are used to efficiently capture context over long-range sequences. At each time step, the model takes $u(t)$ as input and updates the latent state/memory $x(t)$ and, in turn, returns an output $y(t)$ by following the first-order differential equation parameterized by linear and time-invariant dynamics:

$$\dot{x}(t) = \boldsymbol{A}x(t) + \boldsymbol{B}u(t)$$
$$y(t) = \boldsymbol{C}x(t) + \boldsymbol{D}u(t) \quad (2)$$

The SSM operates on continuous time sequences where $\boldsymbol{A}, \boldsymbol{B}, \boldsymbol{C}, \boldsymbol{D}$ are matrices of appropriate sizes. To model discrete sequences, the continuous SSM can be discretized with a fixed step size Δ following any discretization scheme, such as the bilinear method (Tustin, 1947), to obtain the following discretized linear recurrence relations:

Figure 2: MADS4 Agent Actor Network. In addition to the state, action, and reward encoder, the memory/ S4 state representation from the previous agent (H_{n-1}) is encoded through a memory encoder. The updated S4 states and outputs from the S4 blocks pass through separate projection layers.

$$x_k = \bar{\boldsymbol{A}}x_{k-1} + \bar{\boldsymbol{B}}u_k(t)$$
$$y_k = \bar{\boldsymbol{C}}x_k + \bar{\boldsymbol{D}}u_k \quad (3)$$

where $\bar{\boldsymbol{A}}, \bar{\boldsymbol{B}}, \bar{\boldsymbol{C}}, \bar{\boldsymbol{D}}$ are calculated based on $\boldsymbol{A}, \boldsymbol{B}, \boldsymbol{C}, \boldsymbol{D}$ and Δ.

(Gu et al., 2020) showed that the initialization of $\boldsymbol{A}$ by the HIPPO matrix enables the SSM model to capture better long-range contexts. Various techniques have since been developed to improve the

model's performance, stability, and training efficiency (Gu et al., 2021a; Gupta et al., 2022). Similar to these works, D is represented here by a skip connection.

Since Eq. 3 is linear and time-invariant, the output sequence $y(t)$ can be computed directly in parallel based on input sequence $u(t)$ by convolution as follows:

$$y_k = \bar{C}\bar{A}^k\bar{B}u_0 + \bar{C}\bar{A}^{k-1}\bar{B}u_1 + ... + \bar{C}\bar{A}\bar{B}u_{k-1} + \bar{C}\bar{B}u_k$$
$$y = \bar{K} * u$$
(4)

where $\bar{K}$ is the SSM convolution kernel or filter which is a function of $\bar{A}, \bar{B}, \bar{C}, \bar{D}$ and context length L which is pre-fixed during training. This non-circular convolution can be computed efficiently across all time steps, allowing for parallelizable training. The recurrent view of the SSM also allows for faster inference with low memory. This is a key advantage over transformers, which makes the use of SSMs very effective in reinforcement learning settings, which require faster inference for the collection of online interactions with the environment. Additional details can be found in Appendix A.

Information sharing with limited communication To enable scalable cooperation among S4-based agents, we design a communication mechanism limited to consecutive agents in the SE-MDP sequence. Each agent's memory, represented by the hidden state of its S4 module, encodes information about all prior agents in the sequence. A projection of this latent state, h_{i-1}^t, is passed as input to the next agent along with other inputs $\hat{u}_i^t$, influencing its action a_i^t and its memory h_i^t:

$$a_i^t, h_i^t = \pi_i(\hat{u}_i^t, h_{i-1}^t; \theta_i)$$
(5)

During training, gradients flow backward through the shared latent states, enabling the entire system to learn cooperative strategies:

$$\frac{\partial J}{\partial \theta_i} = \frac{\partial J}{\partial a_i^t} \cdot \frac{\partial a_i^t}{\partial \theta_i} + \frac{\partial J}{\partial a_{i+1}^t} \cdot \frac{\partial a_{i+1}^t}{\partial h_i^t} \cdot \frac{\partial h_i^t}{\partial \theta_i}.$$
(6)

where J represents the supervised loss function computed across all agents in the system. This sequential flow of information eliminates the need for an agent to communicate with more than one peer or identify useful collaborators, a challenge that grows with the number of agents. In contrast to typical communication-based MARL algorithms, which scale poorly due to the quadratic growth in memory requirements during training and execution, our mechanism is highly efficient, requiring only constant memory per agent.

We first adapt Decision S4 (DS4) for each agent with parameter sharing, similar to the Multi-Agent Decision Transformer (MADT) (Meng et al., 2021). Unlike MADT, however, the Multi-Agent Decision S4 (MADS4) is trained in a sequentially dependent manner, where agents can share accumulated memory information with the next agent in the sequence. The offline version of MADS4, trained on pre-collected trajectories, is detailed in the next section. These pre-trained models can be further fine-tuned in an on-policy setting using MAPPO (Yu et al., 2021).

3.1 MADS4: OFFLINE TRAINING

Input Formulation In the offline training setup of MADS4, each agent is trained over the offline trajectories consisting of sequences of previously seen observations, its own previously executed actions, the latent state representation of its preceding agent, and returns to go from the current time step. Similar to MADT, the state of each agent at each time step s_i^t is composed of global environment state s_{gi}^t and its local observation o_i^t. Thus, a trajectory for the i^{th} agent, which is taken as input to the S4-based model, consists of the following:

$$\tau_i = (u^1, u^2, ..., u^T) \quad \text{where} \quad u^t = \{R^t, s_{gi}^t, o_i^t, a_i^{t-1}, h_{i-1}^t\}$$
(7)

where R^t is the returns-to-go from current time step t, s_{gi}^t is the current shared global state, o_i^t is the current local observation, a_i^{t-1} is the previously executed action of the i^{th} agent, h_{i-1}^t is the current hidden state representation of the preceding agent. The model is trained to predict actions (action logits) at time step t in an autoregressive manner based on the data seen so far. The output of the S4-based model is used as the action probabilities which are sampled after applying the action availability masks.

$$\hat{a}_i^t = \arg\max_a P(a_i^t|\tau_i^{<=t};\theta) \tag{8}$$

where θ are the parameters of the MADS4. In this work, parameter sharing is allowed across the agents for training stability, and thus, essentially, a single model is trained, which takes into account different inputs for different agents along with their specific one-hot agent IDs.

Network Architecture and Training   The MADS4 architecture consists of three key components, as illustrated in Figure 2: (i) Input, state, and output projection layers: each of these consists of a fully connected layer followed by ReLU activations; (ii) Input encoder layers: These layers handle states, actions, and rewards/returns, each implemented as fully connected linear layers; (iii) Sequence modeling component: This component consists of stacked S4 blocks, where each block consists of Batch Normalization layer followed by S4 layer, linear mixing layer with GELU activation, and a dropout layer. We employed various kernels for S4, with the "Normal Plus Low Rank" kernel initialized using HIPPO, achieving the best performance. In all experiments, we set the input channel size to $H = 96$ and the S4 state size to $N = 96$. An ablation study detailing the effects of varying state and input sizes is provided in Appendix C.1.

In the offline setting, the S4 model is trained efficiently using the convolutional view on entire trajectories sampled randomly from the offline dataset. The trajectories are zero-padded to a constant context length. Unlike transformers, which face limitations on context length due to the expensive quadratic time and space complexity of self-attention, S4-based models can be trained on complete trajectories that are often much longer than those typically used for transformers in most environments. The impact of truncating trajectory lengths has significant implications for model performance, as detailed in Appendix C.2. Actions are predicted based on the action logit outputs of the model, and the model is trained based on loss computed using cross-entropy between the true action labels and the predicted actions.

3.2   MADS4: ONLINE FINETUNING

For online fine-tuning, the offline pre-trained agent is used to interact with the online environment and is further updated based on an on-policy training scheme. The agent interacts with the environment while creating the buffer, which stores the local observations and actions of the individual agents, shared global states of the environment, rewards, returns-to-go, and also the latent states of the S4 modules of the agents. Within the well-known MAPPO-based (Yu et al., 2021) actor-critic framework, the offline-pretrained S4-based model is used as actor networks of the agents which predict actions via the recurrent view based on latent states and other inputs as used in the pretraining stage. The critic network is conditioned on both the global states of the environment as well as the encoded latent S4 states to evaluate the state value function.

Network Architecture and Training   The pre-trained model is loaded as the actor network, which predicts action probabilities and next states as:

$$p_i^t, h_i^t = \pi(u_i^t, h_i^{t-1};\theta) \quad \text{where} \quad u_i^t = \{R_i^t, s_{gi}^t, o_i^t, a_i^{t-1}, h_{i-1}^t\} \tag{9}$$

The critic network is parameterized by fully connected layers with ReLU activations, which take the shared global state of the environment and encoded latent states and evaluate the value function, which is used to update the S4-based actor parameters (θ) using the policy gradient theorem. For more stable training. the actor network is kept frozen initially, and the critic is solely trained on the recorded data collected using the pre-trained actor. After sufficient training of the critic, the actor and critics are simultaneously trained. During exploration, the desired returns-to-go is set at 10%

Algorithm 1 MADS4-Offline Training

Input: Offline dataset $\mathcal{D} : \{\tau_i : \langle s_{gi}^t, o_i^t, a_i^t, v_i^t, d_i^t, R_i^t \rangle_{t=1}^T\}_{i=1}^n$, where n is the number of agents, and v_i^t denotes the available actions for the i^{th} agent at time t

Initialize α as the learning rate, K as the context length

Initialize θ for the S4 models based on HIPPO initialization

1: **for** $i = 1 : n$ **do** $\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad$ ▷ Iterate over each agent
2: $\qquad$ From τ_i and h_{i-1}^t, create $X_i : \{R_i^t, s_{gi}^t, o_i^t, a_i^{t-1}, h_{i-1}^t\}_{t=1}^T$, where h_{i-1}^t is the latent state representation of the previous agent, assuming $h_{-1}^t = \mathbf{0}$
3: $\qquad$ Zero-pad the trajectory to a constant length K when d_i^t is true ▷ Pad when the agent is done
4: $\qquad$ Compute action output sequence $\hat{a}_i = \{\hat{a}_i^1, \ldots, \hat{a}_i^T\}$ and latent state projections $h_i = \{h_i^1, \ldots, h_i^T\}$
5: $\qquad$ **for** $t = 1 : T$ **do** $\qquad\qquad\qquad\qquad\qquad\qquad\qquad$ ▷ Loss calculation over time steps
6: $\qquad\qquad$ Mask illegal actions via $P(\hat{a}_{ij}^t|\tau_i^{<t};\theta) = 0$ if v_{ij}^t is False, where j is the unavailable action index
7: $\qquad\qquad$ Predict the action $\hat{a}_i^t = \arg\max_j P(\hat{a}_{ij}|\tau_i^{<t};\theta)$
8: $\qquad\qquad$ Update θ:

$$\theta \leftarrow \arg\max_\theta \frac{1}{K} \sum_{t=1}^K P(a_i^t) \log P(\hat{a}_i^t|\tau_i^{<t};\theta)$$

9: $\qquad$ **end for**
10: **end for**
Return: θ

---

higher than the current model's highest return. Additional details on the experimental setup and training are provided in Appendix A.4.

4 EXPERIMENTS

Datasets We evaluate the performance of MADS4 on challenging cooperative MARL benchmarks of Multi-Robot Warehouse (RWARE) (Papoudakis et al., 2020) and StarCraft2 Multi-Agent Challenge (SMAC) (Samvelyan et al., 2019). The offline datasets in the RWARE domain are obtained from (Matsunaga et al., 2023), which consists of diverse trajectories collected by training Multi-Agent Transformer (MAT) (Wen et al., 2022). The RWARE datasets consist of expert policies trained on 2 maps (tiny and small) with different numbers of agents. For the SMAC domain, the datasets provided by (Meng et al., 2021) have been used, which consists of trajectories collected with online trained MAPPO agents. The datasets consist of three trained quality levels of the agents, good, medium, and poor, tested on the different SMAC maps. For this work, we chose four representative maps consisting of two hard (5m vs. 6m, 2c vs. 64zg) and two super hard (6h vs. 8z, corridor) maps for evaluating MADS4. Additional statistics on the offline datasets can be found in Appendix B.

Baselines For comparisons on both domains, we compare with several recent offline MARL algorithms from the paradigms of both offline reinforcement learning and sequence-based supervised learning. The offline RL baselines considered for comparison are Behaviour Cloning (BC) (Fujimoto et al., 2019), OptiDICE (Lee et al., 2021), AlberDICE (Matsunaga et al., 2023), ICQ (Yang et al., 2021), OMAR(Pan et al., 2022) and OMIGA(Wang et al., 2024). The sequence-based learning algorithms considered in this work include MADT (Meng et al., 2021) and MADTKD (Tseng et al., 2022), which are based on transformers. MADT policies do not involve any cooperation during learning, whereas MADTKD incorporates a degree of cooperation distilled into the agents from the centralized teacher model.

Offline Training Here, we compare the performance of offline trained MADS4, where the agents share information in the form of their latent state projections. The trained agents are deployed on the online RWARE and StarCraft2 environments for evaluation. Tables 1 and 2 show the mean and

---

Algorithm 2 MADS4: On-policy finetuning

1: Copy the model weights θ to the actor or policy network π : $\pi(u_i)$, where $u_i = \{R_i^t, s_{gi}^t, o_i^t, a_i^{t-1}, h_{i-1}^t\}$; Initialize ϕ, the parameters for critic V
2: Set learning rates α_π, α_V for actor and critic
3: **for** iterations $= 1, M$ **do**
4:      Set data buffer $D = \{\}$
5:      **for** $i = 1$ to $batch\_size$ **do**
6:          $\tau = []$ ▷ Empty list
7:          Initialize $h_0^{(1)}, \ldots, h_0^{(n)}$ actor S4 states
8:          **for** each timestep t in the environment **do**
9:              **for** agent $= 1 : n$ **do**
10:                  $p_i^t, h_i^t = \pi(u_i^t, h_{i-1}^t; \theta)$
11:                  Sample $a_i^t \sim p_i^t$
12:              **end for**
13:              Execute actions $\boldsymbol{a}^t$, observe $r^t, \boldsymbol{s}_g^{t+1}, \boldsymbol{o}^{t+1}$
14:              $\tau+ = [\boldsymbol{s}_t, \boldsymbol{o}_t, \boldsymbol{h}_t, \boldsymbol{a_t}, r_t, R_t, \boldsymbol{s}_{t+1}, \boldsymbol{o}_{t+1}]$
15:          **end for**
16:          Calculate advantage A^t via GAE on τ and store τ with A^t in the buffer D
17:      **end for**
18:      **for** $k = 1, \ldots, K$ training steps **do**
19:          Sample batch from replay-buffer $B = \{(s_g^t, o^t, a^{t-1}, R^{t-1}, h^{t-1}, s_g^{t+1}, o^{t+1}, a^t, h^t, r^t, R^t, A^t)\} \subset D$ for each agent
20:          Calculate Bellman target estimate: $y = r^t + \gamma V(s^{t+1}, h^t)$
21:          Update critic: $\phi_V = \phi_V - \alpha_V \nabla_{\phi_V} (V(s^t, h^{t-1}) - y)^2$
22:          If actor freezing is over, update actor:

$$\theta_\pi \leftarrow \arg\max_{\theta_\pi} \mathbb{E}_{s \sim \rho_{\theta_{\text{old}}}, a \sim \pi_{\theta_{\text{old}}}} \left[\text{clip}(w, 1 - \epsilon, 1 + \epsilon) A^t \right]$$

            where the importance weight $w = \frac{\pi_\theta(a_i|o_i)}{\pi_{\theta_{\text{old}}}(a_i|o_i)}$
23:      **end for**
24: **end for**

---

standard deviation of average returns in RWARE and SMAC domains, respectively, evaluated over 30 episodes and 5 different training seeds. During evaluation, the desired returns-to-go is set at 10% higher than the highest returns encountered in the offline datasets.

RWARE environment is a warehouse simulation consisting of agents moving and delivering goods to workstations in partially observable settings while avoiding collisions. This domain poses challenges due to high-dimensional observations and the need for strong cooperation, especially in high-density settings where agents must navigate narrow passages. In this domain, MADS4 outperforms all baselines across the maps, with a larger performance gap on the small and tiny maps involving 6 agents, where tight coordination is crucial to avoid collisions in confined spaces. MADS4 also outperforms transformer-based baselines like MADTKD, likely due to the long trajectories in the RWARE datasets (up to 500 timesteps), which are often truncated to reduce transformer training costs. In contrast, MADS4 processes full trajectories, capturing longer contexts with fewer parameters.

In the **SMAC** domain, MADS4 demonstrates consistent performance that is similar to or better than the considered baselines across all studied maps. Notably, the model outperforms all baselines in the hard and superhard maps, specifically in the 2c vs. 64zg and 6h vs. 8z scenarios.

The effect of sharing information The sharing of information between agents leads to significantly improved cooperative behavior, as reflected in the higher average rewards shown in Figure 3. This performance boost is particularly pronounced in more complex tasks that involve a greater number of agents and demand precise coordination. Importantly, this method of sharing information is scalable, where an agent only needs to communicate with the next agent, minimizing overhead while ensuring efficient coordination. Information can be shared in multiple forms, namely by pass-

Table 1: Average returns and standard deviations over 5 random seeds on the Warehouse domain.

Method	Tiny (11x11)			Small (11x20)		
	(N = 2)	(N = 4)	(N = 6)	(N = 2)	(N = 4)	(N = 6)
BC	8.80 ± 0.25	11.12 ± 0.19	14.06 ± 0.32	5.54 ± 0.06	7.88 ± 0.14	8.90 ± 0.13
ICQ	9.38 ± 0.75	12.13 ± 0.44	14.59 ± 0.16	5.43 ± 0.19	7.93 ± 0.19	8.87 ± 0.22
OMAR	6.77 ± 0.64	14.39 ± 0.91	16.13 ± 1.21	4.40 ± 0.34	7.12 ± 0.38	8.41 ± 0.49
MADTKD	6.24 ± 0.60	9.90 ± 0.21	13.06 ± 0.19	3.65 ± 0.34	6.85 ± 0.36	7.85 ± 0.52
OptiDICE	8.70 ± 0.06	11.13 ± 0.44	14.02 ± 0.36	4.84 ± 0.32	7.68 ± 0.09	8.47 ± 0.26
AlberDICE	**11.15 ± 0.35**	13.11 ± 0.32	15.72 ± 0.36	5.97 ± 0.11	8.18 ± 0.19	9.65 ± 0.13
MADS4 (ours)	**11.79 ± 0.61**	**15.52 ± 0.20**	**17.29 ± 0.76**	**6.58 ± 0.28**	**9.47 ± 0.15**	**10.87 ± 0.55**

Table 2: Average returns and standard deviations over 5 random seeds on the SMAC domain.

SMAC Map	Data	RL-based			Sequence-based	
		ICQ	OMAR	OMIGA	MADT	**MADS4 (ours)**
5m vs 6m (H)	G	7.87 ± 0.30	7.40 ± 0.63	**8.25 ± 0.37**	8.15 ± 0.63	8.00 ± 0.45
	M	7.77 ± 0.30	7.08 ± 0.51	**7.92 ± 0.57**	7.80 ± 0.56	7.85 ± 0.57
	P	7.26 ± 0.19	7.27 ± 0.42	7.52 ± 0.21	7.23 ± 0.48	**7.67 ± 0.15**
2c vs 64zg (H)	G	18.82 ± 0.17	17.27 ± 0.78	19.15 ± 0.32	18.90 ± 0.78	**19.40 ± 0.55**
	M	15.57 ± 0.61	10.20 ± 0.20	16.03 ± 0.19	16.92 ± 0.20	**17.27 ± 0.15**
	P	12.56 ± 0.18	11.33 ± 0.50	13.02 ± 0.66	13.33 ± 0.50	**14.67 ± 0.32**
6h vs 8z (SH)	G	11.81 ± 0.12	9.85 ± 0.28	12.54 ± 0.21	12.55 ± 0.67	**12.75 ± 0.15**
	M	11.13 ± 0.33	10.36 ± 0.16	12.31 ± 0.22	12.36 ± 0.16	**12.57 ± 0.25**
	P	10.55 ± 0.10	10.63 ± 0.25	11.67 ± 0.19	11.63 ± 0.25	**11.89 ± 0.43**
corridor (SH)	G	15.54 ± 1.12	6.74 ± 0.69	15.88 ± 0.89	**17.81 ± 1.14**	16.02 ± 0.97
	M	11.30 ± 1.57	7.26 ± 0.71	11.66 ± 1.30	12.75 ± 1.18	**12.80 ± 1.12**
	P	4.47 ± 0.33	4.28 ± 0.49	5.61 ± 0.35	**8.76 ± 0.49**	8.57 ± 0.54

ing the action logit outputs from the S4 model, the latent state representations, or a combination of both from the preceding agent. A more detailed analysis of how different types of shared information impact performance is provided in Appendix A.2.

On-policy fine-tuning   We evaluate whether the performance of offline pre-trained models can be enhanced through on-policy fine-tuning. During this phase, MADS4 interacts with the environment, collecting trajectories that are stored in a buffer and used to update the S4-based models via recurrence. As shown in Figure 4, on-policy training builds upon and improves the offline pretraining results. However, prolonged on-policy training can sometimes degrade the performance of pre-trained models, especially when the pre-trained policy has not yet achieved optimal returns. This issue is particularly evident in the SMAC map 6h vs. 8z, as shown in Figure 4.

The degradation may result from training the S4 modules in a recurrent setup, which is less stable than the convolution-based operations used during offline pretraining and can lead to error accumulation. This effect can be mitigated by freezing the S4 kernel parameter A during fine-tuning and only updating the parameters B and C. Furthermore, on-policy training without pretraining consistently results in sub-optimal performance across all tasks, underscoring the importance of pretraining for achieving superior results.

5 CONCLUSIONS

In this work, we demonstrate the effectiveness of S4-based models in outperforming transformer-based architectures in sequence-based offline MARL tasks. By limiting communication to the exchange of information only between consecutive agents within a sequentially expanded MDP framework, MADS4 achieves superior cooperation compared to state-of-the-art offline RL and centralized transformer-based baselines, which require complete access to all agents' information during training. MADS4 offers a low-latency and lightweight model that can be trained more efficiently than transformers and fine-tuned online using recurrent computations.

Figure 3: Training curves of MADS4 with information sharing between consecutive agents and IDS4 where agents are trained independently. Mean and standard deviations of average returns are plotted over 5 independent runs.

Figure 4: Training curves of on-policy training of MADS4 with and without offline pretraining. Mean and standard deviations of average returns are plotted over 5 independent runs.

REFERENCES

Chenjia Bai, Lingxiao Wang, Zhuoran Yang, Zhihong Deng, Animesh Garg, Peng Liu, and Zhaoran Wang. Pessimistic bootstrapping for uncertainty-driven offline reinforcement learning. *arXiv preprint arXiv:2202.11566*, 2022.

Shmuel Bar-David, Itamar Zimerman, Eliya Nachmani, and Lior Wolf. Decision s4: Efficient sequence-based rl via state spaces layers. *arXiv preprint arXiv:2306.05167*, 2023.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Debiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

Aydar Bulatov, Yury Kuratov, and Mikhail Burtsev. Recurrent memory transformer. *Advances in Neural Information Processing Systems*, 35:11079–11091, 2022.

Yongcan Cao, Wenwu Yu, Wei Ren, and Guanrong Chen. An overview of recent progress in the study of distributed multi-agent coordination. *IEEE Transactions on Industrial informatics*, 9(1): 427–438, 2012.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Misha Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *Advances in neural information processing systems*, 34:15084–15097, 2021.

Peng Cheng, Xianyuan Zhan, Wenjia Zhang, Youfang Lin, Han Wang, Li Jiang, et al. Look beneath the surface: Exploiting fundamental symmetry for sample-efficient offline rl. *Advances in Neural Information Processing Systems*, 36, 2024.

Jakob Foerster, Gregory Farquhar, Triantafyllos Afouras, Nantas Nardelli, and Shimon Whiteson. Counterfactual multi-agent policy gradients (2017). *arXiv preprint arXiv:1705.08926*, 2017.

Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In *International conference on machine learning*, pp. 2052–2062. PMLR, 2019.

Albert Gu, Tri Dao, Stefano Ermon, Atri Rudra, and Christopher Ré. Hippo: Recurrent memory with optimal polynomial projections. *Advances in neural information processing systems*, 33: 1474–1487, 2020.

Albert Gu, Karan Goel, and Christopher Ré. Efficiently modeling long sequences with structured state spaces. *arXiv preprint arXiv:2111.00396*, 2021a.

Albert Gu, Isys Johnson, Karan Goel, Khaled Saab, Tri Dao, Atri Rudra, and Christopher Ré. Combining recurrent, convolutional, and continuous-time models with linear state space layers. *Advances in neural information processing systems*, 34:572–585, 2021b.

Ankit Gupta, Albert Gu, and Jonathan Berant. Diagonal state spaces are as effective as structured state spaces. *Advances in Neural Information Processing Systems*, 35:22982–22994, 2022.

Jiechuan Jiang and Zongqing Lu. Offline decentralized multi-agent reinforcement learning. In *ECAI*, pp. 1148–1155, 2023.

Ilya Kostrikov, Rob Fergus, Jonathan Tompson, and Ofir Nachum. Offline reinforcement learning with fisher divergence critic regularization. In *International Conference on Machine Learning*, pp. 5774–5783. PMLR, 2021.

Aviral Kumar, Justin Fu, Matthew Soh, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. *Advances in neural information processing systems*, 32, 2019.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. *Advances in Neural Information Processing Systems*, 33:1179–1191, 2020.

Jongmin Lee, Wonseok Jeon, Byungjun Lee, Joelle Pineau, and Kee-Eung Kim. Optidice: Offline policy optimization via stationary distribution correction estimation. In *International Conference on Machine Learning*, pp. 6120–6130. PMLR, 2021.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Chuming Li, Jie Liu, Yinmin Zhang, Yuhong Wei, Yazhe Niu, Yaodong Yang, Yu Liu, and Wanli Ouyang. Ace: Cooperative multi-agent q-learning with bidirectional action-dependency. In *Proceedings of the AAAI conference on artificial intelligence*, volume 37, pp. 8536–8544, 2023.

Jianxiong Li, Xianyuan Zhan, Haoran Xu, Xiangyu Zhu, Jingjing Liu, and Ya-Qin Zhang. When data geometry meets deep function: Generalizing offline reinforcement learning. *arXiv preprint arXiv:2205.11027*, 2022.

Ryan Lowe, Yi I Wu, Aviv Tamar, Jean Harb, OpenAI Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. *Advances in neural information processing systems*, 30, 2017.

Chris Lu, Yannick Schroecker, Albert Gu, Emilio Parisotto, Jakob Foerster, Satinder Singh, and Feryal Behbahani. Structured state space models for in-context reinforcement learning. *Advances in Neural Information Processing Systems*, 36, 2024.

Daiki E Matsunaga, Jongmin Lee, Jaeseok Yoon, Stefanos Leonardos, Pieter Abbeel, and Kee-Eung Kim. Alberdice: addressing out-of-distribution joint actions in offline multi-agent rl via alternating stationary distribution correction estimation. *Advances in Neural Information Processing Systems*, 36:72648–72678, 2023.

Linghui Meng, Muning Wen, Yaodong Yang, Chenyang Le, Xiyun Li, Weinan Zhang, Ying Wen, Haifeng Zhang, Jun Wang, and Bo Xu. Offline pre-trained multi-agent decision transformer: One big sequence model tackles all smac tasks. *arXiv preprint arXiv:2112.02845*, 2021.

Frans A Oliehoek, Matthijs TJ Spaan, and Nikos Vlassis. Optimal and approximate q-value functions for decentralized pomdps. *Journal of Artificial Intelligence Research*, 32:289–353, 2008.

Ling Pan, Longbo Huang, Tengyu Ma, and Huazhe Xu. Plan better amid conservatism: Offline multi-agent reinforcement learning with actor rectification. In *International conference on machine learning*, pp. 17221–17237. PMLR, 2022.

Georgios Papoudakis, Filippos Christianos, Lukas Schäfer, and Stefano V Albrecht. Benchmarking multi-agent deep reinforcement learning algorithms in cooperative tasks. *arXiv preprint arXiv:2006.07869*, 2020.

Tabish Rashid, Mikayel Samvelyan, Christian Schroeder De Witt, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. Monotonic value function factorisation for deep multi-agent reinforcement learning. *Journal of Machine Learning Research*, 21(178):1–51, 2020.

Mikayel Samvelyan, Tabish Rashid, Christian Schroeder De Witt, Gregory Farquhar, Nantas Nardelli, Tim GJ Rudner, Chia-Man Hung, Philip HS Torr, Jakob Foerster, and Shimon Whiteson. The starcraft multi-agent challenge. *arXiv preprint arXiv:1902.04043*, 2019.

Jimmy TH Smith, Andrew Warrington, and Scott W Linderman. Simplified state space layers for sequence modeling. *arXiv preprint arXiv:2208.04933*, 2022.

Kyunghwan Son, Daewoo Kim, Wan Ju Kang, David Earl Hostallero, and Yung Yi. Qtran: Learning to factorize with transformation for cooperative multi-agent reinforcement learning. In *International conference on machine learning*, pp. 5887–5896. PMLR, 2019.

Peter Sunehag, Guy Lever, Audrunas Gruslys, Wojciech Marian Czarnecki, Vinicius Zambaldi, Max Jaderberg, Marc Lanctot, Nicolas Sonnerat, Joel Z Leibo, Karl Tuyls, et al. Value-decomposition networks for cooperative multi-agent learning. *arXiv preprint arXiv:1706.05296*, 2017.

Wei-Cheng Tseng, Tsun-Hsuan Johnson Wang, Yen-Chen Lin, and Phillip Isola. Offline multi-agent reinforcement learning with knowledge distillation. *Advances in Neural Information Processing Systems*, 35:226–237, 2022.

Arnold Tustin. A method of analysing the behaviour of linear systems in terms of time series. *Journal of the Institution of Electrical Engineers-Part IIA: Automatic Regulators and Servo Mechanisms*, 94(1):130–142, 1947.

Ikechukwu Uchendu, Ted Xiao, Yao Lu, Banghua Zhu, Mengyuan Yan, Joséphine Simon, Matthew Bennice, Chuyuan Fu, Cong Ma, Jiantao Jiao, et al. Jump-start reinforcement learning. In *International Conference on Machine Learning*, pp. 34556–34583. PMLR, 2023.

Jianhao Wang, Zhizhou Ren, Terry Liu, Yang Yu, and Chongjie Zhang. Qplex: Duplex dueling multi-agent q-learning. *arXiv preprint arXiv:2008.01062*, 2020.

Xiangsen Wang, Haoran Xu, Yinan Zheng, and Xianyuan Zhan. Offline multi-agent reinforcement learning with implicit global-to-local value regularization. *Advances in Neural Information Processing Systems*, 36, 2024.

Muning Wen, Jakub Kuba, Runji Lin, Weinan Zhang, Ying Wen, Jun Wang, and Yaodong Yang. Multi-agent reinforcement learning is a sequence modeling problem. *Advances in Neural Information Processing Systems*, 35:16509–16521, 2022.

Yifan Wu, George Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning. *arXiv preprint arXiv:1911.11361*, 2019.

Yue Wu, Shuangfei Zhai, Nitish Srivastava, Joshua Susskind, Jian Zhang, Ruslan Salakhutdinov, and Hanlin Goh. Uncertainty weighted actor-critic for offline reinforcement learning. *arXiv preprint arXiv:2105.08140*, 2021.

Haoran Xu, Xianyuan Zhan, Jianxiong Li, and Honglei Yin. Offline reinforcement learning with soft behavior regularization. *arXiv preprint arXiv:2110.07395*, 2021.

Haoran Xu, Li Jiang, Li Jianxiong, and Xianyuan Zhan. A policy-guided imitation approach for offline reinforcement learning. *Advances in Neural Information Processing Systems*, 35:4085–4098, 2022a.

Haoran Xu, Xianyuan Zhan, and Xiangyu Zhu. Constraints penalized q-learning for safe offline reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 8753–8760, 2022b.

Haoran Xu, Li Jiang, Jianxiong Li, Zhuoran Yang, Zhaoran Wang, Victor Wai Kin Chan, and Xianyuan Zhan. Offline rl with no ood actions: In-sample learning via implicit value regularization. *arXiv preprint arXiv:2303.15810*, 2023.

Yiqin Yang, Xiaoteng Ma, Chenghao Li, Zewu Zheng, Qiyuan Zhang, Gao Huang, Jun Yang, and Qianchuan Zhao. Believe what you see: Implicit constraint approach for offline multi-agent reinforcement learning. *Advances in Neural Information Processing Systems*, 34:10299–10312, 2021.

Dayon Ye, Minji Zhang, and Yu Yang. A multi-agent framework for packet routing in wireless sensor networks. *sensors*, 15(5):10026–10047, 2015.

Chao Yu, Akash Velu, Eugene Vinitsky, Yu Wang, Alexandre Bayen, and Yi Wu. The surprising effectiveness of ppo in cooperative, multi-agent games (2021). *arXiv preprint arXiv:2103.01955*, 2021.

Tianhe Yu, Garrett Thomas, Lantao Yu, Stefano Ermon, James Y Zou, Sergey Levine, Chelsea Finn, and Tengyu Ma. Mopo: Model-based offline policy optimization. *Advances in Neural Information Processing Systems*, 33:14129–14142, 2020.

A   ADDITIONAL BACKGROUND, EXPERIMENTAL SETUP AND TRAINING DETAILS

A.1   S4 LAYER

S4Gu et al. (2021a) layer is a variant of linear and time-invariant (LTI) state-space model (SSM)Gu et al. (2021b) which adopts the HIPPO Gu et al. (2020)-based initializations in order to better capture longer contexts, and proposes efficient ways for kernel computations and parallel training.

A.1.1   RECURRENT VIEW

Given an input scalar function $u(t) : \mathbb{R} \to \mathbb{R}$, the continuous LTI SSM is defined by the following first-order differential equation:

$$\dot{x}(t) = Ax(t) + Bu(t), \quad y(t) = Cx(t) + Du(t) \tag{10}$$

The model maps the input stream $u(t)$ to $y(t)$. It was shown that initializing A by the HIPPO matrix Gu et al. (2020) grants the state-space model (SSM) the ability to capture long-range dependencies. Similar to previous works Gu et al. (2021a); Gupta et al. (2022), D is replaced by parameter-based skip-connection and is omitted from the SSM by assuming $D = 0$.

This SSM operates on continuous sequences, and it is discretized by a step size Δ to operate on discrete sequences. Let the discretization matrices be $\bar{A}, \bar{B}, \bar{C}$:

$$\bar{A} = (I - \Delta A/2)^{-1}(I + \Delta A/2), \quad \bar{B} = (I - \Delta A/2)^{-1}\Delta B, \quad \bar{C} = C \tag{11}$$

These matrices allow us to rewrite Eq. 10:

$$x_k = \bar{A}x_{k-1} + \bar{B}u_k, \quad y_k = \bar{C}x_k \tag{12}$$

Using the recurrent Eq.12, SSM asymptotically allows for constant $O(1)$ time and memory inference for each token/ timestep, as compared to $O(L^2)$ inference for transformers. SSM can be interpreted as a linear RNN in which $\bar{A}$ is the state-transition matrix, and $\bar{B}, \bar{C}$ are the input and output matrices. Thus, it essentially requires $O(L)$ training, L being the sequence length, as compared to $O(L^2)$ (parallelizable) training complexity for transformers.

A.1.2   CONVOLUTIONAL VIEW

The recurrent SSM view is not practical for training over long sequences, as the training cannot be parallelized across the sequence dimension and results in instabilities from vanishing gradient issues. However, the LTI SSM can be rewritten as a convolution, which allows for efficient parallelizable training. The S4 convolutional view is obtained as follows:

Given a sequence of scalars $u = (u_0, u_1, ..., u_{L-1})$ of length L, the S4 recurrent view can be unrolled to the following closed form:

$$\forall i \in [L-1] : x_i \in \mathbb{R}^N, \quad x_0 = \bar{B}u_0, \quad x_1 = \bar{A}\bar{B}u_0 + \bar{B}u_1, \quad ..., \quad x_{L-1} = \sum_{i=0}^{L-1} \bar{A}^{L-1-i}\bar{B}u_i$$

$$y_i \in \mathbb{R}, \quad y_0 = \bar{C}\bar{B}u_0, \quad y_1 = \bar{C}\bar{A}\bar{B}u_0 + \bar{C}\bar{B}u_1, \quad ..., \quad y_{L-1} = \sum_{i=0}^{L-1} \bar{C}\bar{A}^{L-1-i}\bar{B}u_i$$

Where N is the state size. Inputs and outputs are scalars.

Since the recurrent rule is linear, it can be computed in closed form with matrix multiplication or non-circular convolution:

Figure 5: Average Returns obtained in SMAC tasks by passing S4 output versus S4 latent states.

$$
\begin{bmatrix} y_0 \\ y_1 \\ \vdots \\ y_{L-1} \end{bmatrix} = \begin{bmatrix} \bar{C}\bar{B} & 0 & 0 & 0 & 0 \\ \bar{C}\bar{A}\bar{B} & \bar{C}\bar{B} & 0 & 0 & 0 \\ \bar{C}\bar{A}^2\bar{B} & \bar{C}\bar{A}\bar{B} & \bar{C}\bar{B} & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ \bar{C}\bar{A}^{L-2}\bar{B} & \bar{C}\bar{A}^{L-3}\bar{B} & \bar{C}\bar{A}^{L-4}\bar{B} & ... & \bar{C}\bar{B} \end{bmatrix} \begin{bmatrix} u_0 \\ u_1 \\ \vdots \\ u_{L-1} \end{bmatrix} \tag{13}
$$

i.e., $y = \bar{k} * u$ for some kernel $\bar{k}$, which can be calculated by fixing the sequence length L before training. This kernel can be efficiently computed using FFT operations; for example, Gu et al. (2021a) computes the kernel via inverse FFT on the spectrum of $\bar{k}$, which is calculated via Cauchy kernel and the Woodbury Identity. This benefits from the "Normal Plus Low Rank" parameterization of the HIPPO-initialized state transition matrix A, and other more efficient parameterizations are proposed in Gupta et al. (2022).

The SSM, as represented above, operates on scalars or one channel of inputs. To handle vector inputs $\in \mathbb{R}^H$, H copies of the 1-D SSM layer are stacked, one for each input channel, and a linear mixing layer in the after block of the S4 layer mixes the information from different channels to produce outputs $\in \mathbb{R}^H$.

A.2 SHARING HIDDEN STATE REPRESENTATIONS

The raw outputs from the S4 layer consist of $y_k = \bar{C}x_k$, where $y_k \in \mathbb{R}^H$ and the latent states $x_k \in \mathbb{R}^{N \times H}$ for H input channels. Since the outputs are linear projections and offer a compact representation of the latent states (or, memory of the agent), this has been used as the message that is transmitted from one agent to the next in the SE-MDP. This offers several advantages: i) results in better team performance; ii) offers scalable cooperation between agents, which eliminates the need for a centralized transformer or a critic, which requires access to information from all agents; one agent needs access to only its immediate neighbor in the sequence; (iii) allows parallel training via convolution.

We also experimented with passing the raw hidden states $x_k \in \mathbb{R}^{N \times H}$ from one agent to another. The hidden states can be complex, depending on the parameterization of the S4 kernel. Therefore, before passing the latent states directly, we first linearly mix the hidden states across the H channels to obtain $x_k \in \mathbb{C}^N$. Then, we linearly project the real and imaginary parts of x_k after concatenation. This mode of information transfer, however, has notable drawbacks: i) it requires computing the S4 hidden state at every timestep, which requires recurrent rollouts of the S4 kernel, and ii) it fails to outperform the method of passing the S4 outputs; possibly due to errors accumulated during recurrent training. A comparison of performance using S4 output representation versus S4 latent state representation is shown in Figure 5, where passing S4 outputs resulted in better performance across all tasks.

It is, however, noted that hidden states at each timestep may be efficiently obtained utilizing the parallel (associate) scan operation as done in Smith et al. (2022); Lu et al. (2024), but this requires JAX implementation and is currently not supported by PyTorch.

A.3 PRELIMINARY STUDY USING MAMBA

We also explored Mamba as an alternative to LTI S4-based models. Mamba allows time-variant parameters to be considered in the SSM equations. Though convolution cannot be applied here since the kernel cannot be computed apriori since the parameters B, C are input-dependent, efficient parallel scan operation allows for parallelizable $O(\log L)$ complexity. However, preliminary analysis utilizing Mamba resulted in suboptimal performance, and it requires more extensive analysis.

A.4 EXPERIMENTAL SETUP AND TRAINING

In all experiments, we set the input channel size to $H = 96$ and the S4 state size to $N = 96$. Offline training is conducted on batches of 64 trajectories, with the maximum trajectory length in the offline dataset used as the length for each batch. The shorter trajectories are zero-padded to a constant length. The training was performed using Adam optimizer with a learning rate of 10^{-4}.

The offline trained model is fine-tuned online using on-policy MAPPO. During the initial stage of fine-tuning, the actor network is kept frozen, and the critic is first trained for the first 50,000 iterations. After this, both the actor and critic are trained simultaneously, with a slower learning rate for the actor network (10^{-5}) compared to the critic (10^{-4}). During on-policy fine-tuning, the returns-to-go is set at 10% higher than the highest returns encountered during training. On-policy training is conducted in batches of 64. To mitigate the issue of deteriorating performance with prolonged on-policy training, the S4 kernel A can be kept frozen. All experiments were run on a single NVIDIA RTX 2080Ti GPU. Experiments on the RWARE domain take less than 2 hrs to reach optimal performance, and experiments on the SMAC domain take less than 6hrs, 12 hrs, 12 hrs, and 30 hrs for maps 2c vs. 64zg, 5m vs. 6m, 6h vs. 8z and Corridor, respectively.

B DATASETS AND BASELINES

B.1 MULTI-ROBOTWAREHOUSE (RWARE)

The offline dataset on RWARE (Papoudakis et al., 2020) is obtained from (Matsunaga et al., 2023), which contains an expert dataset with diverse behaviors obtained by training MAT on small and tiny maps. The dataset consists of 1000 trajectories, each trajectory consisting of 500 timesteps. The dataset statistics are in Table 3. The longest trajectories consist of timesteps in the range of 500 in all the datasets.

The baseline results are obtained from (Matsunaga et al., 2023), which currently holds the state-of-the-art results of the baselines listed on this dataset.

Map Name	Maximum	Minimum	Average
small 2 agents	12.37	1.13	7.12
small 4 agents	12.08	3.93	9.49
small 6 agents	12.69	7.59	10.76
tiny 2 agents	16.81	1.97	12.77
tiny 4 agents	18.63	10.40	15.67
tiny 6 agents	19.97	11.88	17.45

Table 3: RWARE datasets

B.2 SMAC

The offline SMAC (Samvelyan et al., 2019) dataset is obtained from (Wang et al., 2024). This dataset is obtained by randomly sampling 1000 trajectories from the original dataset provided by (Meng et al., 2021). We consider 4 representative battle maps, including 2 hard maps (5m vs 6m,

Figure 6: The effect of truncating the trajectory length during training. The average returns are normalized with the maximum returns encountered in the offline dataset.

2c vs 64zg) and 2 super hard maps (6h vs 8z, corridor), which are detailed in Table 4. The average returns for the dataset are listed in Table 5. The longest trajectories are encountered in the Corridor map, which typically comprises about 100 timesteps.

Map Name	Ally Units	Enemy Units	Type
5m_vs_6m	5 Marines	6 Marines	homogeneous & asymmetric
2c_vs_64zg	2 Colossi	64 Zerglings	micro-trick: positioning
6h_vs_8z	6 Hydralisks	8 Zealots	micro-trick: focus fire
corridor	6 Zealots	24 Zerglings	micro-trick: wall off

Table 4: SMAC maps for experiments.

Map Name	Quality	Average Return
5m_vs_6m	good	20.00
	medium	11.03
	poor	8.50
2c_vs_64zg	good	19.94
	medium	13.00
	poor	8.89
6h_vs_8z	good	17.84
	medium	11.96
	poor	9.12
corridor	good	19.88
	medium	13.07
	poor	4.93

Table 5: SMAC datasets.

The offline RL-based baseline results are obtained from (Wang et al., 2024), and MADT results are obtained by running the code available with (Meng et al., 2021).

C HYPERPARAMETERS ANALYSIS

C.1 S4 MODEL SIZE PARAMETERS

We analyze the impact of the S4 model size parameters, specifically the number of input channels (H) and the latent state size (N), on the model performance, as shown in Table 6. We compare the total number of parameters against the 1.8 million parameters reported for MADTKD in Tseng et al. (2022). Our biggest model with N=96 and H=96 was used in all our experiments, which consists of about 200k parameters.

Table 6: Results of smaller models on the RWARE small map. Each of the smaller models is denoted by (i) N, the $S4$ state size, and (ii) H, the number of input/output channels.

Environments	(N=96,H=96)	(N=64,H=64)	(N=32,H=32)	(N=64,H=96)	(N=96,H=64)	(N=32,H=64)	**MADTKD**
2 agents	6.58	6.21	5.53	6.53	6.25	5.87	3.65
4 agents	9.47	8.86	8.57	9.15	8.88	8.64	6.85
6 agents	10.87	10.31	9.55	10.76	9.97	9.85	7.85
% Parameters (Ours)	100	60	40	81	82	55	100
% Parameters (MADTKD)	12	7	5	8	8	6	100

Figure 7: The effect of freezing S4 kernel parameter A. Freezing A results in more stable performance during the on-policy recurrent finetuning.

C.2 THE EFFECT OF CONTEXT LENGTH AND S4 PARAMETERS

The context length used for pretraining significantly impacts performance, which is also evident for transformer-based models. In our experiments, we used the maximum trajectory lengths encountered in the offline datasets for pretraining. Representative results are shown in Figure 6, which illustrates the effects of truncating the trajectory lengths to various percentages of the maximum length in the offline dataset for the SMAC map 2c vs 64zg.

C.3 EFFECT OF FREEZING A DURING ON-POLICY FINETUNING

The degrading effect on MADS4 performance during recurrent on-policy finetuning can be mitigated by freezing the S4 kernel parameter A while updating only parameters B and C. A similar observation has also been reported in Bar-David et al. (2023).