Differentially Private Optimization for Smooth Non-convex ERM

Abstract

We develop simple differentially private optimization algorithms that move along directions of (expected) descent to find approximate second-order necessary solution for non-convex ERM problems. We use line search, mini-batching, and a two-phase strategy to improve the speed and practicality of the algorithm. Numerical experiments demonstrate the effectiveness of these approaches.

1 Introduction

Privacy protection has become a central issue in machine learning algorithms, and differential privacy (Dwork & Roth, 2014) is a rigorous and popular framework for quantifying privacy. In our paper, we propose a differentially private optimization algorithm that finds an approximate second-order necessary solution for ERM problems. We proposed several techniques to improve the practical performance of the method, including backtracking line search, mini-batching, and a heuristic to avoid the effects of conservative assumptions made in the analysis.

For given $f : \mathbb{R}^d \to \mathbb{R}$, consider the following minimization problem,

$$\min_{w \in \mathbb{R}^d} f(w).$$

We want to find an approximate second-order necessary solution, defined formally as follows.

Definition 1 ((ϵ_g, ϵ_H)-2NS). For given positive values of ϵ_g and ϵ_H, We say that w is an (ϵ_g, ϵ_H)-approximate second-order necessary solution (abbreviated as (ϵ_g, ϵ_H)-2NS) if

$$\|\nabla f(w)\| \leq \epsilon_g, \quad \lambda_{\min}\left(\nabla^2 f(w)\right) \geq -\epsilon_H. \tag{1}$$

We are mostly interested in the case of $\epsilon_g = \alpha$ and $\epsilon_H = \sqrt{M\alpha}$, that is, we seek an ($\alpha, \sqrt{M\alpha}$)-2NS, where M is the Lipschitz constant for $\nabla^2 f$.

We will focus on the empirical risk minimization (ERM) problem, defined as follows,

Definition 2 (ERM). Given a dataset $D = \{x_1, \ldots, x_n\}$ and a loss function $l(w, x)$, we seek the parameter $w \in \mathbb{R}^d$ that minimizes the empirical risk

$$f(w) = L(w, D) := \frac{1}{n} \sum_{i=1}^{n} l\left(w, x_i\right).$$

ERM is a classical problem in machine learning that has been studied extensively; see, for example Shalev-Shwartz & Ben-David (2014). In this paper, we describe differentially private (DP) techniques for solving ERM.

Previous research on DP algorithms for ERM and optimization has focused mainly on convex loss functions. Recent research on differentially private algorithms for non-convex ERM (Wang et al., 2018a; Wang & Xu, 2019; Zhang et al., 2017) targets an approximate stationary point, which satisfies only the first condition in (1). Wang & Xu (2021) proposes a trust-region type (DPTR) algorithm that gives an approximate second-order necessary solution for ERM, satisfying both conditions in (1), for particular choices of ϵ_g and ϵ_H. This work requires the trust-region subproblem to be solved exactly at each iteration, and fixes the radius of the trust region at a small value, akin to a "short step" in a line-search method. An earlier work (Wang et al., 2019) proposed the DP-GD algorithm, which takes short steps in a noisy gradient direction, then sorts through all the iterates so generated to find one that satisfies second-order

necessary conditions. Our work matches the sample complexity bound in DP-GD, which is $O\left(\frac{d}{\alpha^2\sqrt{\rho}}\right)$ for ρ-zCDP or $O\left(\frac{d\sqrt{\ln(1/\delta)}}{\alpha^2\varepsilon}\right)$ for (ε,δ)-DP for finding an $(\alpha,\sqrt{M\alpha})$-2NS, and has an iteration complexity of $O(\alpha^{-2})$. Our contributions can be summarized as follows.

- Our algorithm is elementary and is based on a simple (non-private) line-search algorithm for finding an approximate second-order necessary solution. It evaluates second-order information (a noisy Hessian matrix) only when insufficient progress can be made using first-order (gradient) information alone. By contrast, DP-GD uses the (noisy) Hessian only for checking the second-order approximate condition, while DPTR requires the noisy Hessian to be calculated at every iteration.

- Our algorithm is practical and fast. DPTR has a slightly better sample complexity bound than our method, depending on $\alpha^{-7/4}$ rather than α^{-2}. However, since our analysis is based on the worst case, we can be more aggressive with step sizes (see below). DPTR requires solving the trust-region subproblem exactly, which is relatively expensive and unnecessary when the gradient is large enough to take a productive step. Experiments demonstrate that our algorithm requires fewer iterations than DPTR and does less computation on average at each iteration, and thus runs significantly faster than DPTR. Moreover, we note that the mini-batch version of DPTR has a sample complexity $O(\alpha^{-2})$, matching the sample complexity of the mini-batch version of our algorithm.

- We use line search and mini-batching to accelerate the algorithm. Differentially private line search algorithms have been proposed by (Chen & Lee, 2020). We use the same sparse vector technique as used by their work, but provide a tighter analysis of the sensitivity of the query for checking sufficient decrease condition. In addition, we provide a rigorous analysis of the guaranteed function decrease with high probability.

- To complement our worst-case analysis, we propose a heuristic that can obtain much more rapid convergence while retaining the guarantees provided by the analysis.

The remainder of the paper is structured as follows. In Section 2, we review basic definitions and properties from differential privacy, and make some assumptions about the function f to be optimized. In Section 3, we describe our algorithm and its analysis. We will discuss the basic short step version of the algorithm in Section 3.1, and an extension to a practical line search method in Section 3.2. A mini-batch adaptation of the algorithm is described in Section 3.3. In Section 4, we present experimental results and demonstrate the effectiveness of our algorithms.

2 Preliminaries

We use several variants of DP for the need of our analysis, including (ε,δ)-DP (Dwork & Roth, 2014), (α,ϵ)-RDP (Mironov, 2017), and zCDP (Bun & Steinke, 2016). We review their definitions and properties in Appendix A.

We make the following assumptions about the smoothness of the objective function f.

Assumption 1. We assume f is lower bounded by $\underline{f}$. Assume further that f is G-smooth and has M-Lipschitz Hessian, that is, for all $w_1, w_2 \in \mathrm{dom}(f)$,

$$\|\nabla f(w_1) - \nabla f(w_2)\| \le G\|w_1 - w_2\|, \tag{2}$$

$$\|\nabla^2 f(w_1) - \nabla^2 f(w_2)\| \le M\|w_1 - w_2\|, \tag{3}$$

where $\|\cdot\|$ denotes the vector 2-norm and the matrix 2-norm respectively. We use this notation throughout the paper.

For the ERM version of f (see Definition 2), we make additional assumptions.

Assumption 2. For the ERM setting, we assume the loss function is $l(w, x)$ is G-smooth and has M-Lipschitz Hessian with respect to w. Thus $L(w, D)$ (the average loss across n samples) is also G-smooth and has M-Lipschitz Hessian with respect to w. In addition, we assume $l(w, x)$ has bounded function values, gradients, and Hessians. That is, there are constants B, B_g, and B_H such that for any w, x we have,

$$0 \le l(w, x) \le B, \quad \|\nabla_w l(w, x)\| \le B_g, \quad \|\nabla_w^2 l(w, x)\| \le B_H.$$

As a consequence, the l^2 sensitivity of $L(w, D)$ and $\nabla L(w, D)$ is bounded by B/n and $2B_g/n$ respectively. We have

$$\|\nabla^2 L(w, D) - \nabla^2 L(w, D')\|_F \le \sqrt{d}\,\|\nabla^2 L(w, D) - \nabla^2 L(w, D')\| \le \frac{2B_H\sqrt{d}}{n}.$$

To simplify notation, we define $g(w) := \nabla f(w)$ and $H(w) := \nabla^2 f(w)$. From the definition (20) of ℓ_2-sensitivity, we have that the sensitivities of f, g, and H are

$$\Delta_f = \frac{B}{n}, \quad \Delta_g = 2\frac{B_g}{n}, \quad \Delta_H = \frac{2B_H\sqrt{d}}{n}. \tag{4}$$

3 MAIN RESULTS

Our algorithmic starting point is the elementary algorithm described in Wright & Recht (2022, Chapter 3.6) that has convergence guarantees to points that satisfy approximate second-order necessary conditions. For simplicity, we use the following notation to describe and analyze the method:

$$f_k := f(w_k), \quad g_k := g(w_k) = \nabla f(w_k), \quad H_k := H(w_k) = \nabla^2 f(w_k).$$

We employ the Gaussian mechanism to perturb gradients and Hessians, and denote

$$\tilde{g}_k = g_k + \varepsilon_k, \quad \tilde{H}_k = H_k + E_k,$$

where $\varepsilon_k \sim \mathcal{N}(0, \Delta_g^2\sigma_g^2 I_d)$ for some chosen parameter σ_g and E_k is a symmetric matrix in which each entry on and above its diagonal is i.i.d. as $\mathcal{N}\left(0, \Delta_H^2\sigma_H^2\right)$, for some chosen value of σ_H. Let $\tilde{\lambda}_k$ denote the minimum eigenvalue of $\tilde{H}_k$ with $\tilde{p}_k$ the corresponding eigenvector, with sign and norm chosen to satisfy

$$\|\tilde{p}_k\| = 1 \quad \text{and} \quad (\tilde{p}_k)^T\tilde{g}_k \leq 0. \tag{5}$$

Algorithm 1 specifies the general form of our optimization algorithm. We will discuss two strategies — a "short step" strategy and one based on backtracking line search — to choose the step sizes $\gamma_{k,g}$ and $\gamma_{k,H}$ to be taken along the directions $\tilde{g}_k$ and $\tilde{p}_k$, respectively. For each variant, we define a quantity MIN_DEC to be the minimum decrease, and use it together with a specific lower bound on f to define an upper bound T of the required number of iterations. In each iteration, we take a step in the negative of the perturbed gradient direction $\tilde{g}_k$ if $\|\tilde{g}_k\| > \epsilon_g$. Otherwise, we check the minimum eigenvalue $\tilde{\lambda}_k$ of the perturbed Hessian $\tilde{H}_k$. If $\tilde{\lambda}_k < -\epsilon_H$, we take a step along the direction $\tilde{p}_k$. In the remaining case, we have $\|\tilde{g}_k\| \leq \epsilon_g$ and $\tilde{\lambda}_k \geq -\epsilon_H$, so the approximate second-order necessary conditions are satisfied and we output the current iterate w_k as a 2NS solution.

The quantities σ_f, σ_g, σ_H determine the amount of noise added to function, gradient, and Hessian evaluations, respectively, with the goal of preserving privacy via Gaussian Mechanism. We can target a certain privacy level for the overall algorithm (ρ in ρ-zCDP, for example), find an upper bound on the number of iterations required by whatever variant of Algorithm 1 we are using, and then choose σ_f, σ_g, and σ_H to ensure this level of privacy. Conversely, we can choose positive values for σ_f, σ_g, and σ_H and then determine what level of privacy can be ensured by this choice. (Note that we can keep track of the "privacy leakage" as the algorithm progresses, leading to the possibility of adaptive schemes for choosing the σ's.)

3.1 SHORT STEP

In the short step version of the algorithm, we make choices for the step sizes that are independent of k:

$$\gamma_{k,g} \equiv \frac{1}{G}, \quad \gamma_{k,H} \equiv \frac{2|\tilde{\lambda}_k|}{M}. \tag{7}$$

The choices of MIN_DEC and the noise parameters σ_f, σ_g, and σ_H are discussed in the following results.

First, we discuss the privacy guarantee and its relationship to the noise variances and the number of iterations.

Theorem 1. *Let the noise variances σ_f, σ_g, σ_H be given. Suppose a run of Algorithm 1 takes k_g gradient steps and k_H negative curvature steps. Then the run is ρ-zCDP where $\rho = \frac{1}{2}\left(\frac{1}{\sigma_f^2} + \frac{k_g+k_H}{\sigma_g^2} + \frac{k_H}{\sigma_H^2}\right)$.*

Recall that T is the maximum number of iterations defined in (6). Let $\bar{\rho} = \frac{1}{2}\left(\frac{1}{\sigma_f^2} + \frac{T}{\sigma_g^2} + \frac{T}{\sigma_H^2}\right)$. We always have $\bar{\rho} \geq \rho$, so the algorithm is $\bar{\rho}$-zCDP. Conversely, for given $\rho > 0$ and $\rho_f \in (0, \rho)$, we can choose

$$\sigma_f^2 = \frac{1}{2\rho_f}, \quad \sigma_g^2 = \sigma_H^2 = \frac{T}{\rho - \rho_f}. \tag{8}$$

to ensure that the algorithm is ρ-zCDP.

Algorithm 1 DP Optimization with Second-Order Guarantees

Given: minimum decrease per iteration MIN_DEC, tolerances ϵ_g and ϵ_H, noise parameters σ_f, σ_g and σ_H
Initialize w^0 and sample $z \sim \mathcal{N}(0, \Delta_f^2 \sigma_f^2)$
Compute an upper bound of the required number of iterations as follows

$$T = \left\lceil \frac{f(w^0) + |z| - \underline{f}}{\text{MIN\_DEC}} \right\rceil \tag{6}$$

Set σ_g and σ_H using T (See theorems for details)
for $k = 1, 2, \ldots, T$ **do**
    Sample $\varepsilon_k \sim \mathcal{N}\left(0, \Delta_g^2 \sigma_g^2 I_d\right)$
    Compute the perturbed gradient $\tilde{g}_k = g_k + \varepsilon_k$
    if $\|\tilde{g}_k\| > \epsilon_g$ **then**
        Choose $\gamma_{k,g}$ and set $w_{k+1} \leftarrow w_k - \gamma_{k,g} \tilde{g}_k$ ▷ Gradient step
    else
        Sample E_k such that E_k is a $d \times d$ symmetric matrix in which each entry on and above its diagonal is i.i.d. as
$\mathcal{N}\left(0, \Delta_H^2 \sigma_H^2\right)$. Compute perturbed Hessian $\tilde{H}_k = H_k + E_k$ and $(\tilde{\lambda}_k, \tilde{p}_k)$
        if $\tilde{\lambda}_k < -\epsilon_H$ **then**
            Choose $\gamma_{k,H} > 0$ and set $w_{k+1} \leftarrow w_k + \gamma_{k,H} \tilde{p}_k$ ▷ Negative curvature step
        else
            return w_k
        end if
    end if
end for

Proof. The proof follows directly from the zCDP guarantee for the Gaussian mechanism combined with postprocessing and composition of zCDP. □

Remark. In practice, we expect most steps to be gradient steps, so $\bar{\rho}$ is an overestimate of the actual privacy level ρ. We can be more aggressive in choosing the noise variances. We discuss a two-phase approach in Section 3.4.

We now discuss guarantees oef the output of Algorithm 1. First, we analyze MIN_DEC in each short step.

Lemma 2. *With the short step size choices* (7)*, if the noise satisfies the following conditions for some positive constants* c, c_1, *and* c_2 *such that* $c_1 < \frac{1}{2}$ *and* $c_2 + c < \frac{1}{3}$,

$$\|\varepsilon_k\| \leq \min\left(c_1 \epsilon_g, \frac{c_2}{M} \epsilon_H^2\right), \tag{9a}$$

$$\|E_k\| \leq c \epsilon_H, \tag{9b}$$

then the amount of decrease in each step is at least

$$\text{MIN\_DEC} = \min\left(\frac{1 - 2c_1}{2G} \epsilon_g^2, \; 2\left(\frac{1}{3} - c_2 - c\right) \frac{\epsilon_H^3}{M^2}\right). \tag{10}$$

The true gradient and true minimum eigenvalue of the Hessian satisfy the following,

$$\|g_k\| \leq (1 + c_1)\|\tilde{g}_k\|, \quad \lambda_k > -(1 + c)|\tilde{\lambda}_k|. \tag{11}$$

Remark. The constants c, c_1, and c_2 in the conditions (9) above control how accurate our noisy gradient and Hessian estimates are. MIN_DEC is smaller when we choose smaller constants. We will also have a tighter solution as demonstrated in the corollary below. However, we need smaller noise to satisfy the conditions (9), which in turn translates to a larger required sample size n for our ERM problem, as we will see in Theorem 4.

Corollary 3. *Assuming the noise satisfies* (9) *at each iteration, the short step version (using* (7)*,* (10)*) of the algorithm will output a* $((1 + c_1)\epsilon_g, (1 + c)\epsilon_H)$*-2NS.*

With the results above, we now analyze the guarantees of the fixed step-size algorithm under the ERM setting.

Theorem 4 (Sample complexity of the short step algorithm). *Consider the ERM setting. Suppose that the number of samples n satisfies $n \geq n_{\min}$, where*

$$n_{\min} := \max \left(\frac{\sqrt{2d} B_g \sigma_g \log \frac{T}{\zeta}}{\min \left(c_1 \epsilon_g, \frac{c_2}{M} \epsilon_H^2 \right)}, \frac{C \sqrt{d} B_H \sigma_H \log \frac{T}{\zeta}}{c \epsilon_H} \right).$$

With probability at least $\{(1 - \frac{\zeta}{T})(1 - C \exp(-cCd))\}^T$ where c and C are universal constants in Lemma D.7, the output of the short step version (using (7),(10)) of the algorithm is a $((1 + c_1)\epsilon_g, (1 + c)\epsilon_H)$-2NS.

With the choice of σ's in (8) using $\rho_f = c_f \rho$ for $c_f \in (0, 1)$, hiding logarithmic terms and constants, the asymptotic dependence of $n_{\min}$ on (ϵ_g, ϵ_H), ρ and d, is

$$n_{\min} = \frac{d}{\sqrt{\rho}} \tilde{O} \left(\max \left(\epsilon_g^{-2}, \epsilon_g^{-1} \epsilon_H^{-2}, \epsilon_H^{-7/2} \right) \right). \tag{12}$$

When $(\epsilon_g, \epsilon_H) = (\alpha, \sqrt{M\alpha})$, the dependence simplifies to $\frac{d}{\sqrt{\rho}} \tilde{O}(\alpha^{-2})$.

Remark. When the conditions (9) do not hold, the algorithm could fail to converge to a $((1 + c_1)\epsilon_g, (1 + c)\epsilon_H)$-2NS. First, the noise in the perturbed gradient and Hessian can be so large that the step is not a descent direction. Second, due to the noise, we may terminate early or fail to terminate timely when checking the approximate second-order conditions. If the noise is not excessive, the solution is still acceptable since the noisy evaluations satisfy the termination conditions.

3.2 LINE SEARCH ALGORITHM

Instead of using a conservative fixed step size, we can do a line search using backtracking. The backtracking line search requires an initial value γ_0, a decrease parameter $\beta \in (0, 1)$ for the step size, and constants $c_g \in (0, 1 - c_1)$, $c_H \in (0, 1 - c - \sqrt{\frac{8}{3}c_2})$ that determine the amount of decrease we need. Each line search tries in succession the values $\gamma_0, \beta\gamma_0, \beta^2\gamma_0, \ldots$, until a value is found that satisfies a sufficient decrease condition. For gradient steps, the condition is

$$f(w - \gamma\tilde{g}) \leq f(w) - c_g \gamma \|\tilde{g}\|^2, \tag{SD1}$$

while for negative curvature steps it is

$$f(w + \gamma\tilde{p}) \leq f(w) - \frac{1}{2} c_H \gamma^2 |\tilde{\lambda}|. \tag{SD2}$$

To make line search differentially private, we use the *sparse vector technique* from (Dwork & Roth, 2014). We define queries according to (SD1) and (SD2):

$$q_g(\gamma, w) = f(w) - f(w - \gamma\tilde{g}) - c_g \gamma \|\tilde{g}\|^2, \tag{13a}$$

$$q_H(\gamma, w) = f(w) - f(w + \gamma\tilde{p}) - \frac{1}{2} c_H \gamma^2 |\tilde{\lambda}|, \tag{13b}$$

whose nonnegativity is equivalent to each of the sufficient decrease conditions.

Algorithm 2 specifies the differentially private line search algorithm using SVT, which is adapted from `AboveThreshold` algorithm (Dwork & Roth, 2014).

By satisfying the sufficient decrease conditions, we try to get a more substantial improvement in the function value than for the short step algorithm. As a fallback strategy, we use step sizes similar to the short step values (differing only by a constant factor) if the line search fails, yielding a similar decrease to the short-step case. We state the complete algorithm enhanced with line search in Algorithm 3. In the algorithm, we compute the fall back step size $\bar{\gamma}$ and use a multiplier b ($b > 1$) of them as the initial step size $b\bar{\gamma}$ for the line search. We compute the query sensitivity Δ_q accordingly and call the private line search subroutine to find a step size γ that satisfies the sufficient decrease conditions.

We have the following privacy guarantees.

Theorem 5. *Suppose that σ_f, σ_g, σ_H, and λ are given. Suppose an actual run of the line search algorithm takes k_g gradient steps and k_H negative curvature steps. The run is ρ-zCDP where $\rho = \frac{1}{2} \left(\frac{1}{\sigma_f^2} + \frac{k_g + k_H}{\sigma_g^2} + \frac{k_H}{\sigma_H^2} + \frac{k_g + k_H}{\lambda^2} \right)$.*

Algorithm 2 Private backtracking line search using SVT

Given: query q and its sensitivity Δ_q, initial step size multiplier b, fall back step size $\bar{\gamma}$, decrease parameter β, privacy parameter λ

function DP-LINESEARCH($q, \Delta_q, \gamma^{\text{init}}, \bar{\gamma}, \beta, \lambda$)

    Initialize $\gamma \leftarrow \gamma^{\text{init}}$.

    Sample $\xi \sim \text{Lap}\,(2\lambda\Delta_q)$

    for $i = 1, 2, \ldots, i_{\max} = \lfloor \log_\beta \frac{\bar{\gamma}}{\gamma^{\text{init}}} \rfloor + 1$ **do**

        Sample $\nu_i \sim \text{Lap}\,(4\lambda\Delta_q)$

        Evaluate $q_i = q(\gamma)$ and $\tilde{q}_i = q_i + \nu_i$

        if $\tilde{q}_i \geq \xi$ **then**

            HALT and output γ

        else

            Set $\gamma \leftarrow \beta\gamma$

        end if

    end for

    HALT and output $\bar{\gamma}$.

end function

Algorithm 3 DP Optimization algorithm with Second-Order Guarantees and Backtracking Line Search

---

Given: noise bound parameters c_1, c_2, c, sufficient decrease parameters c_g, c_H and initial step size multipliers b_g, b_H, line search decreasing parameters β_g, β_H, tolerances ϵ_g and ϵ_H, noise parameters $\sigma_f, \sigma_g, \sigma_H$ and λ_{SVT}

Initialize w^0, sample $z \sim \mathcal{N}(0, \Delta_f^2\sigma_f^2)$ and compute MIN_DEC according to (17)

Compute an upper bound of the required number of iterations $T = \left\lceil \frac{f(w_0) + |z| - \underline{f}}{\text{MIN\_DEC}} \right\rceil$

Set $\bar{\gamma}_g \leftarrow 2\,(1 - c_1 - c_g)\,/G$

for $k \leftarrow 1, 2, \ldots, T$ **do**

    Sample $\varepsilon_k \sim \mathcal{N}\left(0, \Delta_g^2\sigma_g^2 I_d\right)$

    Compute the perturbed gradient $\tilde{g}_k = g_k + \varepsilon_k$

    if $\|\tilde{g}_k\| > \epsilon_g$ **then**

        Define $q_{k,g}(\gamma) = f(w_k) - f(w_k - \gamma\tilde{g}_k) - c_g\gamma\|\tilde{g}_k\|^2$

        Set $\gamma_{k,g}^{\text{init}} \leftarrow b_g\bar{\gamma}_g,\ \Delta_{q_{k,g}} \leftarrow \frac{2}{n}\gamma_{k,g}^{\text{init}}B_g\|\tilde{g}_k\|$ ▷ Line search query sensitivity

        $\gamma_{k,g} \leftarrow$ DP-LINESEARCH($q_{k,g}, \Delta_{q_{k,g}}, \gamma_{k,g}^{\text{init}}, \bar{\gamma}_g, \beta_g, \lambda_{SVT}$)   ▷ Backtracking line search

        $w_{k+1} \leftarrow w_k - \gamma_{k,g}\tilde{g}_k$ ▷ Gradient step

    else

        Sample E_k such that E_k is a $d \times d$ symmetric matrix in which each entry on and above its diagonal is i.i.d. as $\mathcal{N}\left(0, \Delta_H^2\sigma_H^2\right)$. Compute perturbed Hessian $\tilde{H}_k = H_k + E_k$

        Compute the minimum eigenvalue of $\tilde{H}_k$ and the corresponding eigenvector $(\tilde{\lambda}_k, \tilde{p}_k)$ satisfying (5).

        if $\tilde{\lambda}_k < -\epsilon_H$ **then**

            Define $q_{k,H}(\gamma) = f(w_k) - f(w_k + \gamma\tilde{p}_k) - \frac{1}{2}c_H\gamma^2|\tilde{\lambda}_k|$

            Set $\bar{\gamma}_{k,H} \leftarrow t_2|\tilde{\lambda}_k|/M,\ \gamma_{k,H}^{\text{init}} \leftarrow b_H\bar{\gamma}_{k,H},\ \Delta_{q_{k,H}} \leftarrow \frac{2}{n}\gamma_{k,H}^{\text{init}}B_g$

            $\gamma_{k,H} \leftarrow$ DP-LINESEARCH($q_H, \Delta_{q_{k_H}}, \gamma_{k,H}^{\text{init}}, \bar{\gamma}_{k,H}, \beta_H, \lambda_{SVT}$)   ▷ Backtracking line search

            $w_{k+1} \leftarrow w_k + \gamma_{k,H}\tilde{p}_k$ ▷ Negative curvature step

        else

            return w_k

        end if

    end if

end for

Recall that T is the maximum number of iterations defined in (6). Let $\bar{\rho} = \frac{1}{2}\left(\frac{1}{\sigma_f^2} + \frac{T}{\sigma_g^2} + \frac{T}{\sigma_H^2} + \frac{T}{\lambda^2}\right)$. We always have $\bar{\rho} \geq \rho$, so the algorithm is $\bar{\rho}$-zCDP. Conversely, for given $\rho > 0$ and $\rho_f \in (0, \rho)$, we can choose

$$\sigma_f^2 = \frac{1}{2\rho_f}, \quad \sigma_g^2 = \sigma_H^2 = \lambda^2 = \frac{3T}{2(\rho - \rho_f)}, \tag{14}$$

to ensure that algorithm is ρ-zCDP.

Proof. We know that SVT is $(1/\lambda)$-DP. Thus, it satisfies $(1/(2\lambda^2))$-zCDP. The result follows directly from the zCDP guarantee for the Gaussian mechanism combined with postprocessing and composition of zCDP. $\square$

We now discuss the guarantee of the output of the algorithm. We first derive necessary conditions for sufficient decrease.

Lemma 6. *Assume the same bounded noise conditions* (9) *as before. With the choice of sufficient decrease coefficients* $c_g \in (0, 1 - c_1), c_H \in (0, 1 - c - \sqrt{\frac{8}{3}c_2})$, *let $\bar{\gamma}_g = 2\left(1 - c_1 - c_g\right)/G$ and $\bar{\gamma}_H = t_2|\tilde{\lambda}|/M$ as defined in Algorithm 3, the sufficient decrease conditions* (SD1) *and* (SD2) *are satisfied when $\gamma \leq \bar{\gamma}_g$ and $\gamma \in [(t_1/t_2)\bar{\gamma}_H, \bar{\gamma}_H]$, respectively, where $0 < t_1 < t_2$ are solutions to the following quadratic equation (given our choice of c, c_2, c_H, real solutions exist),*

$$r(t) := -\frac{1}{6}t^2 + \frac{1}{2}\left(1 - c - c_H\right)t - c_2 = 0,$$

Explicitly, we have

$$t_1, t_2 = \frac{3}{2}\left(1 - c - c_H\right) \pm 3\sqrt{\frac{1}{4}(1 - c - c_H)^2 - \frac{2}{3}c_2}. \tag{15}$$

In particular, we have $q_g(\bar{\gamma}_g) \geq 0$ and $q_H(\bar{\gamma}_H) \geq 0$.

We now derive the minimum amount of decrease for each iteration.

Lemma 7. *Using DP line search Algorithm 3, assume the same bounded noise conditions* (9) *as before. With the choice of sufficient decrease coefficients $c_g \in (0, 1 - c_1), c_H \in (0, 1 - c - \sqrt{\frac{8}{3}c_2})$, define $\bar{\gamma}_g$ and $\bar{\gamma}_H$ as before. Choose initial step size multipliers $b_g, b_H > 1$ and decrease parameters $\beta_g \in (0, 1), \beta_H \in (t_1/t_2, 1)$. Let $i_{\max} = \lfloor \log_\beta \max(b_g, b_H) \rfloor + 1$. If n satisfies the following:*

$$n \geq 16\lambda \left(\log i_{\max} + \log \frac{T}{\xi}\right) \max \left(2b_g \frac{B_g}{c_g \epsilon_g}, 4b_H \frac{B_g M}{t_2 c_H \epsilon_H^2}\right), \tag{16}$$

with probability at least $1 - \xi/T$, the amount of decrease in a single step is at least

$$\text{MIN\_DEC} = \min \left(\frac{1}{G}(1 - c_1 - c_g)c_g \epsilon_g^2, \frac{1}{4}c_H t_2^2 \frac{\epsilon_H^3}{M^2}\right). \tag{17}$$

With the results above, we can now analyze the guarantees of the line search algorithm under ERM settings.

Theorem 8 (Sample complexity of the line search algorithm)**.** *Assuming the same conditions as in the previous lemma, with probability at least $\{(1 - \frac{\zeta}{T})(1 - C\exp(-cCd))(1 - \xi/T)\}^T$, suppose the number of samples n satisfies $n \geq n_{\min}$, where*

$$n_{\min} := \max \left(\frac{\sqrt{2d}B_g \sigma_g \log \frac{T}{\zeta}}{\min\left(c_1 \epsilon_g, \frac{c_2}{M}\epsilon_H^2\right)}, \frac{C\sqrt{d}B_H \sigma_H \log \frac{T}{\zeta}}{c\epsilon_H}, 16\lambda \left(\log i_{\max} + \log(\frac{T}{\xi})\right) \max \left(2b_g \frac{B_g}{c_g \epsilon_g}, 4b_H \frac{B_g M}{t_2 c_H \epsilon_H^2}\right)\right). \tag{18}$$

The output of the algorithm is a $((1 + c_1)\epsilon_g, (1 + c)\epsilon_H)$-2NS. With the choice of σ's and λ in (14), *hiding logarithmic terms and constants, the asymptotic dependence of $n_{\min}$ on (ϵ_g, ϵ_H) and ρ, is*

$$n_{\min} = \frac{d}{\sqrt{\rho}}\tilde{O}\left(\max\left(\epsilon_g^{-2}, \epsilon_g^{-1}\epsilon_H^{-2}, \epsilon_H^{-7/2}\right)\right). \tag{19}$$

When $(\epsilon_g, \epsilon_H) = (\alpha, \sqrt{M}\alpha)$, the dependence simplifies to $\frac{d}{\sqrt{\rho}}\tilde{O}(\alpha^{-2})$.

Proof. The proof is similar to D.4 using Lemma 17. We have an additional term in our success probability due to the SVT line search step. For the asymptotic bound of $n_{\min}$, we note that MIN_DEC (17), T, σ_g and σ_H are the same as those of the short step algorithm, up to a constant. The additional requirement (16) for n is $O\left(\frac{\lambda \log T}{\max(\epsilon_g^{-1}, \epsilon_H^{-2})}\right)$. Since we choose $\lambda = \sigma_g$, it is in the same order as the first term inside the max expression of $n_{\min}$ in (18). Thus, the asymptotic bound of $n_{\min}$ is the same as that of the short step algorithm. $\square$

3.3 MINI-BATCHING

We can use mini-batching to speed up the algorithm. Specifically, in each iteration k, we sample m data points from D without replacement, forming the mini-batch S_k. The objective now only computes the average risk over set S_k, that is,

$$f_{k,S_k} := \frac{1}{m} \sum_{i \in S_k} \ell(w, x_i).$$

Likewise, we modify all the prior algorithms by evaluating the gradients and Hessians over the mini-batch S_k. We show that the sample complexity of the mini-batch version of the algorithm remains $\tilde{O}(\frac{d\sqrt{\ln(1/\delta)}}{\varepsilon\alpha^2})$ when $(\epsilon_g, \epsilon_H) = (\alpha, \sqrt{M\alpha})$ for (ε, δ)-DP. The details are in the Appendix B.

3.4 DISCUSSION: PRACTICAL IMPROVEMENT AND EIGENVALUE COMPUTATION

The estimate of T in (6) is pessimistic, based on MIN_DESC obtained from our worst-case analysis. In practice, we can employ a two-phase strategy to speed up the algorithm. In the first phase, we use a fraction (say $3/4$) of the privacy budget to try out a smaller T, which corresponds to less noise and quicker convergence. If we are unable to find a desired solution, we fall back to the original algorithm with the remaining privacy budget and use the last iterate as a warm start.

In an actual implementation, we can use Lanczos method to compute the minimum eigenvalue and eigenvector. This will slightly change our analysis. See Appendix C for a discussion.

4 EXPERIMENTS

We carry out numerical experiments to demonstrate the performance of our DP optimization algorithms, following similar experimental protocols to (Wang & Xu, 2021). We use Covtype dataset, which has $n = 581012$ data points. Each data point has the form (w, y), where w is a 54-dimensional feature vector (first 10 are dimensions numerical, column $11 - 14$ is the WildernessArea one-hot vector, and last 40 columns is the SoilType one-hot vector), and y being the label, is one of $\{1, 2, \ldots, 7\}$.

For preprocessing, we normalize the first 10 numerical columns, and keep only those samples for which $y = 1, 2$. The number of samples remaining in this restricted set is $n = 495141$. We recode $y = 2$ to $y = -1$ so that $y \in \{-1, 1\}$.

We investigate the non-convex ERM loss:

$$\min_{w \in \mathbb{R}^p} \frac{1}{n} \sum_{i=1}^{n} \log(1 + \exp(-y_i \langle x_i, w \rangle)) + r(w),$$

where $r(w) = \sum_{i=1}^{p} \frac{\lambda w_i^2}{1 + w_i^2}$ is the non-convex regularizer.

4.1 RESULTS

We implement our algorithms and DPTR in Python using PyTorch. To make the results comparable, we modify DPTR to explicitly check approximate second-order necessary conditions and stop if these conditions are satisfied, in the same way as in our algorithms. The experiments were run on a cluster with a 36-core Intel Xeon Gold 6254 3.1GHz CPU, utilizing 8 CPU cores for each run. We run the experiment under two settings:

1. Easy case: $\epsilon_g = 0.06$ and $\epsilon_H = \sqrt{0.06} \approx 0.245$. In this setting, our requirement on the 2NS is loose. This in turn translates to a large sample size n compared to the required sample complexity.

2. Hard case: $\epsilon_g = 0.03$ and $\epsilon_H = \sqrt{0.03} \approx 0.173$. In this setting, our requirement on the 2NS is tight. We have a small sample size n compared to the required sample complexity.

For each setting, we pick different level of privacy budget ε and run each configuration with five different random seeds. We present the results in the tables below. In each entry, we report (loss mean, loss std), whether the algorithm terminates with success, and (runtime mean, runtime std). The time unit is relative.

Table 1: Easy case: $(\epsilon_g, \epsilon_H) = (0.06, 0.245)$

| $\varepsilon =$
method	0.2	0.4	0.6
TR	$(0.516, 0.005) \times (490.9, 67.5)$	$(0.596, 0.005)\checkmark(115.2, 34.5)$	$(0.607, 0.007)\checkmark(99.6, 32.2)$
TR-B	$(0.517, 0.005) \times (136.9, 64.4)$	$(0.597, 0.007)\checkmark(32.9, 18.4)$	$(0.605, 0.003)\checkmark(28.5, 14.9)$
OPT	$(0.506, 0.001) \times (14.1, 1.8)$	$(0.552, 0.008) \times (8.6, 3.8)$	$(0.535, 0.015) \times (43.6, 20.8)$
OPT-B	$(0.598, 0.003)\checkmark(13.1, 0.7)$	$(0.598, 0.003)\checkmark(1.5, 0.3)$	$(0.598, 0.003)\checkmark(1.6, 0.2)$
OPT-LS	$(0.525, 0.009) \times (3.1, 1.4)$	$(0.510, 0.002) \times (4.7, 1.6)$	$(0.527, 0.009) \times (6.5, 3.5)$
OPT-LS-B	$(0.589, 0.005)\checkmark(1.9, 0.6)$	$(0.589, 0.005)\checkmark(1.6, 0.2)$	$(0.589, 0.005)\checkmark(1.7, 0.2)$
2OPT	$(0.502, 0.001) \times (26.2, 3.9)$	$(0.501, 0.001) \times (26.9, 4.7)$	$(0.513, 0.003) \times (81.6, 11.7)$
2OPT-B	$(0.598, 0.003)\checkmark(29.2, 4.1)$	$(0.598, 0.003)\checkmark(1.7, 0.1)$	$(0.598, 0.003)\checkmark(2.0, 0.5)$
2OPT-LS	$(0.577, 0.008)\checkmark(2.1, 1.0)$	$(0.591, 0.001)\checkmark(0.5, 0.1)$	$(0.591, 0.001)\checkmark(0.6, 0.1)$
2OPT-LS-B	$(0.589, 0.005)\checkmark(28.6, 3.1)$	$(0.589, 0.005)\checkmark(1.8, 0.3)$	$(0.589, 0.005)\checkmark(1.8, 0.4)$

Table 2: Hard case: $(\epsilon_g, \epsilon_H) = (0.06, 0.173)$

| $\varepsilon =$
method	0.2	0.4	0.6
TR	$(0.729, 0.028)\checkmark(10.1, 9.9)$	$(0.730, 0.025)\checkmark(10.9, 11.3)$	$(0.729, 0.026)\checkmark(8.3, 8.6)$
TR-B	$(0.728, 0.028)\checkmark(2.5, 2.4)$	$(0.727, 0.027)\checkmark(3.8, 3.6)$	$(0.729, 0.027)\checkmark(2.2, 2.2)$
OPT	$(0.581, 0.057) \times (33.1, 24.0)$	$(0.712, 0.018)\checkmark(0.7, 0.3)$	$(0.712, 0.018)\checkmark(0.6, 0.2)$
OPT-B	$(0.710, 0.013)\checkmark(14.9, 2.4)$	$(0.710, 0.013)\checkmark(0.9, 0.3)$	$(0.710, 0.013)\checkmark(0.9, 0.1)$
OPT-LS	$(0.577, 0.032) \times (13.0, 4.6)$	$(0.595, 0.051) \times (21.3, 10.6)$	$(0.687, 0.028)\checkmark(0.4, 0.1)$
OPT-LS-B	$(0.699, 0.019)\checkmark(1.6, 0.1)$	$(0.699, 0.019)\checkmark(1.6, 0.1)$	$(0.699, 0.019)\checkmark(1.9, 0.5)$
2OPT	$(0.626, 0.078) \times (62.9, 65.2)$	$(0.603, 0.099) \times (69.4, 63.5)$	$(0.712, 0.017)\checkmark(0.6, 0.2)$
2OPT-B	$(0.710, 0.013)\checkmark(23.8, 9.3)$	$(0.710, 0.013)\checkmark(1.2, 0.4)$	$(0.710, 0.013)\checkmark(1.3, 0.5)$
2OPT-LS	$(0.699, 0.018)\checkmark(0.5, 0.2)$	$(0.699, 0.018)\checkmark(0.5, 0.1)$	$(0.699, 0.018)\checkmark(0.5, 0.2)$
2OPT-LS-B	$(0.699, 0.019)\checkmark(33.3, 5.1)$	$(0.699, 0.019)\checkmark(2.0, 1.0)$	$(0.699, 0.019)\checkmark(1.7, 0.1)$

We use TR to denote DPTR, OPT to denote the short step algorithm, LS to denote the line search is used, 2OPT to denote the two-phase strategy is used, and B for mini-batching.

In the easy case, 2OPT-LS consistently outperforms other algorithms. For the faithful implementation, the line search version of our algorithm is faster than the short step version for large privacy budget.

In the hard case, TR can fail to converge when ε is low, but the two-phase variant (DPOPT-LS-two-phase) could still converge given that is not too small (≥ 0.6 in this case).

REFERENCES

Borja Balle, Gilles Barthe, and Marco Gaboardi. Privacy Amplification by Subsampling: Tight Analyses via Couplings and Divergences, November 2018.

Mark Bun and Thomas Steinke. Concentrated Differential Privacy: Simplifications, Extensions, and Lower Bounds. *arXiv:1605.02065 [cs, math]*, May 2016.

Yair Carmon, John C. Duchi, Oliver Hinder, and Aaron Sidford. Accelerated Methods for Non-Convex Optimization, February 2017.

Chen Chen and Jaewoo Lee. Stochastic Adaptive Line Search for Differentially Private Optimization. *arXiv:2008.07978 [cs, stat]*, August 2020.

Cynthia Dwork and Aaron Roth. The Algorithmic Foundations of Differential Privacy. *Foundations and Trends® in Theoretical Computer Science*, 9(3–4):211–407, August 2014. ISSN 1551-305X. doi: 10.1561/0400000042.

Jonas Moritz Kohler and Aurelien Lucchi. Sub-sampled Cubic Regularization for Non-convex Optimization. *arXiv:1705.05933 [cs, math, stat]*, July 2017.

Ilya Mironov. Renyi Differential Privacy. *2017 IEEE 30th Computer Security Foundations Symposium (CSF)*, pp. 263–275, August 2017. doi: 10.1109/CSF.2017.11.

Shai Shalev-Shwartz and Shai Ben-David. *Understanding Machine Learning: From Theory to Algorithms*. Cambridge University Press, Cambridge, 2014. ISBN 978-1-107-05713-5. doi: 10.1017/CBO9781107298019.

Terence Tao. *Topics in Random Matrix Theory*. American Mathematical Soc., March 2012. ISBN 978-0-8218-7430-1.

Roman Vershynin. *High-Dimensional Probability: An Introduction with Applications in Data Science*. Cambridge Series in Statistical and Probabilistic Mathematics. Cambridge University Press, Cambridge, 2018. ISBN 978-1-108-41519-4. doi: 10.1017/9781108231596.

Di Wang and Jinhui Xu. Differentially Private Empirical Risk Minimization with Smooth Non-Convex Loss Functions: A Non-Stationary View. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33(01):1182–1189, July 2019. ISSN 2374-3468. doi: 10.1609/aaai.v33i01.33011182.

Di Wang and Jinhui Xu. Escaping Saddle Points of Empirical Risk Privately and Scalably via DP-Trust Region Method. In Frank Hutter, Kristian Kersting, Jefrey Lijffijt, and Isabel Valera (eds.), *Machine Learning and Knowledge Discovery in Databases*, Lecture Notes in Computer Science, pp. 90–106, Cham, 2021. Springer International Publishing. ISBN 978-3-030-67664-3. doi: 10.1007/978-3-030-67664-3_6.

Di Wang, Minwei Ye, and Jinhui Xu. Differentially Private Empirical Risk Minimization Revisited: Faster and More General. *arXiv:1802.05251 [cs, stat]*, February 2018a.

Di Wang, Changyou Chen, and Jinhui Xu. Differentially Private Empirical Risk Minimization with Non-convex Loss Functions. In *Proceedings of the 36th International Conference on Machine Learning*, pp. 6526–6535. PMLR, May 2019.

Yu-Xiang Wang, Borja Balle, and Shiva Kasiviswanathan. Subsampled R\'enyi Differential Privacy and Analytical Moments Accountant. *arXiv:1808.00087 [cs, stat]*, December 2018b.

Stephen J. Wright and Benjamin Recht. *Optimization for Data Analysis*. Cambridge University Press, Cambridge, 2022. ISBN 978-1-316-51898-4. doi: 10.1017/9781009004282.

Jiaqi Zhang, Kai Zheng, Wenlong Mou, and Liwei Wang. Efficient Private ERM for Smooth Objectives. In *Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence*, pp. 3922–3928, Melbourne, Australia, August 2017. International Joint Conferences on Artificial Intelligence Organization. ISBN 978-0-9992411-0-3. doi: 10.24963/ijcai.2017/548.

A A QUICK REVIEW OF DIFFERENTIAL PRIVACY

Definition A.1 ((ε, δ)-DP (Dwork & Roth, 2014))**.** A randomized algorithm $\mathcal{A}$ is (ε, δ)-DP if for all neighboring datasets D, D' and for all events S in the output space of $\mathcal{A}$, the following holds:

$$\Pr\left(\mathcal{A}(D) \in S\right) \leq e^{\varepsilon} \Pr\left(\mathcal{A}(D') \in S\right) + \delta.$$

When $\delta = 0$, we say $\mathcal{A}$ is ε-DP. In DP-ERM, we say D' is a neighboring dataset of D if they differ on just one data point, that is, by changing one data point x_k in D to x'_k, we obtain dataset D'.

Rényi-DP (RDP) was introduced by Mironov as a relaxation of the original DP.

Definition A.2 (Rényi divergence)**.** For two probability distributions P and Q defined over $\mathcal{R}$, the Rényi divergence of order $\alpha > 1$ is

$$D_{\alpha}(P\|Q) \leq \frac{1}{\alpha - 1} \log \mathrm{E}_{w \sim Q} \left(\frac{P(w)}{Q(w)}\right)^{\alpha}.$$

Definition A.3 $((\alpha, \epsilon)$-RDP (Mironov, 2017)$)$**.** A randomized algorithm $\mathcal{M} : \mathcal{D} \rightarrow \mathcal{R}$ is (α, ϵ)-RDP if for all neighboring dataset pairs D, D', the following holds

$$D_\alpha(\mathcal{M}(D)\|\mathcal{M}(D')) \le \epsilon.$$

Another notion of differential privacy is Zero-Concentrated Differential Privacy (zCDP), which requires a linear bound for the divergence of all orders.

Definition A.4 (zCDP (Bun & Steinke, 2016)$)$**.** A randomized algorithm $\mathcal{M} : \mathcal{D} \rightarrow \mathcal{R}$ satisfies (ξ, ρ)-zCDP if for all neighboring dataset pairs D, D' and all $\alpha \in (1, \infty)$, the following holds:

$$D_\alpha(\mathcal{M}(D)\|\mathcal{M}(D')) \le \xi + \rho\alpha.$$

Equivalently, a randomized algorithm $\mathcal{M}$ satisfies ρ-zCDP if for all $\alpha \in (1, \infty)$, $\mathcal{M}$ satisfies $(\alpha, \xi + \rho\alpha)$-RDP. If this definition holds for $\xi = 0$, we use the term ρ-zCDP instead.

RDP and zCDP have some properties in common (Mironov, 2017; Bun & Steinke, 2016).

Proposition A.1 (Composition of RDP)**.** Suppose that $\mathcal{M}_1 : \mathcal{D} \rightarrow \mathcal{R}_1$ is (α, ϵ_1)-RDP and $M_2 : \mathcal{R}_1 \times \mathcal{D} \rightarrow \mathcal{R}_2$ is (α, ϵ_2)-RDP. Then the mechanism defined as (X, Y), where $X \sim \mathcal{M}_1(D)$ and $Y \sim \mathcal{M}_2(X, D)$ is $(\alpha, \epsilon_1 + \epsilon_2)$-RDP.

Proposition A.2 (Composition of zCDP)**.** Suppose that $\mathcal{M}_1 : \mathcal{D} \rightarrow \mathcal{R}_1$ is ρ_1-zCDP and $M_2 : \mathcal{R}_1 \times \mathcal{D} \rightarrow \mathcal{R}_2$ is ρ_2-zCDP. Then the mechanism defined as (X, Y), where $X \sim \mathcal{M}_1(D)$ and $Y \sim \mathcal{M}_2(X, D)$ is $(\rho_1 + \rho_2)$-zCDP.

Proposition A.3 (Preservation under Postprocessing)**.** Consider the mappings $\mathcal{M} : \mathcal{D} \rightarrow \mathcal{R}$ and $g : \mathcal{R} \rightarrow \mathcal{R}'$. We observe that $D_\alpha(P\|Q) \ge D_\alpha(g(P)\|g(Q))$ by the analog of the data processing inequality. This shows that if $\mathcal{M}(\cdot)$ is $(\alpha, \epsilon) - \text{RDP}$, so is $g(\mathcal{M}(\cdot))$. Similarly, if $\mathcal{M}(\cdot)$ is (ρ)-zCDP, so is $g(\mathcal{M}(\cdot))$.

We can convert easily from one notion of differential privacy to another.

Proposition A.4 (RDP to (ε, δ)-DP)**.** If $\mathcal{M}$ is an (α, ϵ)-RDP mechanism, then it is $\left(\epsilon + \frac{\log 1/\delta}{\alpha - 1}, \delta\right)$-DP for any $0 < \delta < 1$.

Proposition A.5 (ϵ-DP to zCDP)**.** If $\mathcal{M}$ is an ε-DP mechanism, then it is also $(\frac{1}{2}\varepsilon^2)$-$z$CDP.

Proposition A.6 $((\varepsilon, \delta)$-DP to zCDP)**.** Suppose that $\mathcal{M} : \mathcal{D} \rightarrow \mathcal{R}$ is (ξ, ρ)-zCDP. Then M is also (ε, δ)-DP for all $\delta > 0$ and

$$\varepsilon = \xi + \rho + \sqrt{4\rho \log(1/\delta)}.$$

Thus to achieve a (ε, δ)-DP guarantee for given ε and δ, it suffices to satisfy (ξ, ρ)-zCDP with

$$\rho = (\sqrt{\varepsilon - \xi + \log(1/\delta)} - \sqrt{\log(1/\delta)})^2 \approx \frac{(\varepsilon - \xi)^2}{4 \log(1/\delta)}.$$

A common way to achieve differential privacy is to add Gaussian noise to the output.

Proposition A.7 (Gaussian Mechanism)**.** Given any function $h : \mathcal{X}^n \rightarrow \mathbb{R}^d$, the Gaussian Mechanism is defined as:

$$\mathbf{G}_\sigma h(D) = h(D) + N(0, \Delta_f^2 \sigma^2 I_d),$$

where Δ_h denotes the ℓ_2-sensitivity of the function h, defined as

$$\Delta_h = \sup_{D \sim D'} \|h(D) - h(D')\|. \tag{20}$$

The Gaussian Mechanism $\mathbf{G}_\sigma h$ satisfies $(\alpha, \alpha/(2\sigma^2))$-RDP for all $\alpha \in [1, \infty)$ and thus also satisfies $(1/2\sigma^2)$-zCDP.

We defer results for (ε, δ)-DP to Appendix B.2.

B ANALYSIS OF THE MINI-BATCH ALGORITHMS

For the line search version of the algorithm, we need additional assumptions if we want to check the sufficient decrease conditions using the mini-batch loss. For simplicity, we only consider the short version of the algorithm in this section.

B.1 RDP ANALYSIS

(In this section, we use $s = m/n$ to denote the sample fraction.) We evaluate the gradient and the Hessian similarly on the mini-batch S_k, which we will write as g_{k,S_k}, H_{k,S_k} and let $\tilde{g}_{k,S_k}$, $\tilde{H}_{k,S_k}$ be their perturbed versions respectively. The other parts of the algorithm remain unchanged. The sensitivity $\Delta_f, \Delta_g, \Delta_H$ as stated in (4) will be scaled accordingly by replacing n in their denominator by the mini-batch size $|m$.

Let g_k and H_k be the the gradient and the Hessian evaluated on the full dataset D. We can decompose the deviation of their noisy approximation as follows,

$$\|\tilde{g}_{k,S_k} - g_k\| \leq \|\tilde{g}_{k,S_k} - g_{k,S_k}\| + \|g_{k,S_k} - g_k\|, \tag{21a}$$

$$\left\|\tilde{H}_{k,S_k} - H_k\right\| \leq \left\|\tilde{H}_{k,S_k} - H_{k,S_k}\right\| + \|H_{k,S_k} - H_k\|, \tag{21b}$$

where the first term in the bound is due to the added Gaussian noise, and the second term is due to subsampling. We will bound two terms separately with high probability.

We have following subsampling concentration results from (Kohler & Lucchi, 2017)

Lemma B.1 (Gradient deviation bound). *We have with probability at least $1 - \eta$ that*

$$\|g_{k,S_k} - g_k\| \leq 4\sqrt{2}B_g\sqrt{\frac{\log(2d/\eta) + 1/4}{|S_k|}}.$$

Lemma B.2 (Hessian deviation bound). *We have with probability at least $1 - \eta$ that*

$$\|H_{k,S_k} - H_k\| \leq 4B_H\sqrt{\frac{\log(2d/\eta)}{|S_k|}}.$$

For the subsampling error (21), we use Gaussian concentration results described before in 41 to bound the first term, and subsampling results stated above to bound the second term. For iteration k, with probability at least $(1 - \frac{\zeta}{T})(1 - C\exp(-cCd))(1 - \eta/T)^2$, we have that

$$
\begin{aligned}
\|\tilde{g}_{k,S_k} - g_k\| &\leq \sqrt{2d}\eta_g\sigma_g \log\frac{T}{\zeta} + 4\sqrt{2}B_g\sqrt{\frac{\log(2dT/\eta) + 1/4}{|S_k|}}, \\
\left\|\tilde{H}_{k,S_k} - H_k\right\| &\leq C\sqrt{d}\eta_H\sigma_H + 4B_H\sqrt{\frac{\log(2dT/\eta)}{|S_k|}}.
\end{aligned}
\tag{22}
$$

It suffices to require that each term in the right hand sides of the bound above is bounded by $1/2$ of the corresponding term in the right hand sides of (9), so that we can use a similar analysis.

For deviation due to subsampling we need,

$$4\sqrt{2}B_g\sqrt{\frac{\log(2dT/\eta) + 1/4}{|S_k|}} \leq \frac{1}{2}\min\left(c_1\epsilon_g, \frac{c_2}{M}\epsilon_H^2\right) \tag{23a}$$

$$4B_H\sqrt{\frac{\log(2dT/\eta)}{|S_k|}} \leq \frac{1}{2}c\,\epsilon_H \tag{23b}$$

Rearranging the terms, we have the condition for the size of the mini-batch,

$$|S_k| \geq \max\left(64B_g^2(\log(2dT/\eta) + 1/4)\max\left(c_1^{-2}\epsilon_g^{-2}, \frac{M^2}{c_2^2}\epsilon_H^{-4}\right), 32B_H^2\log(2dT/\eta)c^{-2}\epsilon_H^{-2}\right). \tag{24}$$

The following convergence result is immediate, based on the same analysis as in the full-batch case (cf. Theorem 8).

Theorem B.3. *With probability at least* $\{(1 - \zeta/T)(1 - C \exp(-cCd))(1 - \eta/T)^2\}^T$, *suppose the number of samples* n *satisfies* $n \geq n_{\min}$, *where*

$$n_{\min} := \max\left(\frac{2\sqrt{2d}B_g\sigma_g \log \frac{T}{\zeta}}{\min\left(c_1\epsilon_g, \frac{c_2}{M}\epsilon_H^2\right)}, \frac{2C\sqrt{d}B_H\sigma_H \log \frac{T}{\zeta}}{c\,\epsilon_H}, \right.$$

$$\left. s^{-1}64B_g^2(\log(2dT/\eta) + 1/4)\max\left(c_1^{-2}\epsilon_g^{-2}, \frac{M^2}{c_2^2}\epsilon_H^{-4}\right), s^{-1}32B_H^2 \log(2dT/\eta)c^{-2}\epsilon_H^{-2}\right). \quad (25)$$

The output of the mini-batch short step algorithm is a $((1 + c_1)\epsilon_g, (1 + c)\epsilon_H)$*-2NS. With the choice of* σ*'s in (8), hiding logarithmic terms and constants, the asymptotic dependence of* $n_{\min}$ *on* (ϵ_g, ϵ_H) *and* ρ, *is*

$$n_{\min} = \frac{d}{\sqrt{\rho}}\tilde{O}\left(\max\left(\epsilon_g^{-2}, \epsilon_g^{-1}\epsilon_H^{-2}, \epsilon_H^{-7/2}\right)\right). \quad (26)$$

We now discuss privacy guarantees. It is impossible to deal with subsampling using z-CDP, but under RDP, Wang et al. (2018b) provides a generalized analysis for subsampling.

Theorem B.4 (RDP for Subsampled Mechanisms). *Given a dataset of* n *points drawn from a domain* $\mathcal{X}$ *and a (randomized) mechanism* $\mathcal{M}$ *that takes an input from* $\mathcal{X}^m$ *for* $m \leq n$, *let the randomized algorithm* $\mathcal{M} \circ \mathbf{subsample}$ *be defined as: (1) subsample: subsample without replacement m datapoints of the dataset (with sampling fraction* $s = m/n$*), and (2) apply* $\mathcal{M}$*: a randomized algorithm taking the subsampled dataset as the input. For all integers* $\alpha \geq 2$, *if* $\mathcal{M}$ *is* $(\alpha, \epsilon(\alpha))$*-RDP, then this new randomized algorithm* $\mathcal{M} \circ \mathbf{subsample}$ *obeys* $(\alpha, \epsilon'(\alpha))$*-RDP where,*

$$\epsilon'(\alpha) \leq \frac{1}{\alpha - 1}\log\left(1 + s^2\binom{\alpha}{2}\min\left\{4\left(e^{\epsilon(2)} - 1\right), e^{\epsilon(2)}\min\left\{2, \left(e^{\epsilon(\infty)} - 1\right)^2\right\}\right\}\right.$$

$$\left. + \sum_{j=3}^{\alpha} s^j\binom{\alpha}{j}e^{(j-1)\epsilon(j)}\min\left\{2, \left(e^{\epsilon(\infty)} - 1\right)^j\right\}\right). \quad (27)$$

For the Gaussian mechanism, we have

$$\epsilon(\alpha) = \frac{\alpha}{2\sigma^2},$$

so $\epsilon_{\mathcal{M}(\infty)} = \infty$ and the bound simplifies to

$$\epsilon'(\alpha) \leq \frac{1}{\alpha - 1}\log\left(1 + s^2\binom{\alpha}{2}\min\left\{4\left(e^{1/\sigma^2} - 1\right), 2e^{1/\sigma^2}\right\} + \sum_{j=3}^{\alpha} 2s^j\binom{\alpha}{j}e^{(j-1)j/(2\sigma^2)}\right) =: \epsilon'_{\mathcal{N}}(\alpha; \sigma, s),$$

which we denote as $\epsilon'_{\mathcal{N}}(\alpha; \sigma, s)$. When s is small and σ is large, we can discard higher-order terms and write the right hand side as

$$\epsilon'_{\mathcal{N}}(\alpha; \sigma, s) \approx \frac{1}{\alpha - 1}\left(s^2\frac{\alpha(\alpha - 1)}{2} \cdot 4\frac{1}{\sigma^2}\right) = 2s^2\frac{\alpha^2}{\sigma^2}, \quad (28)$$

where we use the approximation $e^t \approx 1 + t$ for small t.

Theorem B.5. *Consider the short step version of the algorithm using subsampling. Given the choice of* $\sigma_f, \sigma_g, \sigma_H$, λ *and sampling fraction* s. *Suppose an actual run of the subsampled algorithm takes* k_g *gradient steps and* k_H *negative curvature steps. The run is data-dependent* $(\alpha, \epsilon(\alpha))$*-RDP where*

$$\epsilon(\alpha) = \frac{\alpha}{2\sigma_f^2} + (k_g + k_H)\epsilon'_{\mathcal{N}}(\alpha; \sigma_g, s) + k_H\epsilon'_{\mathcal{N}}(\alpha; \sigma_H, s).$$

Let

$$\bar{\epsilon}(\alpha) = \frac{\alpha}{2\sigma_f^2} + T\epsilon'_{\mathcal{N}}(\alpha; \sigma_g, s) + T\epsilon'_{\mathcal{N}}(\alpha; \sigma_H, s). \quad (29)$$

We always have $\bar{\epsilon}(\alpha) \geq \epsilon(\alpha)$, *so the algorithm is* $(\alpha, \bar{\epsilon}(\alpha))$*-RDP.*

Given the complexity in the subsampled privacy guarantee, $\epsilon'_{\mathcal{N}}(\alpha; \sigma, s)$, we do not have an explicit formula to set parameters $\sigma_f, \sigma_g, \sigma_H$. However, given (ε, δ)-DP privacy budget, we can optimize the parameters to meet the privacy guarantee. Recall the conversion from $(\alpha, \epsilon(\alpha))$-RDP to $(\varepsilon_{DP}, \delta_{DP})$-DP, given δ, we solve

$$\varepsilon_{DP}(\epsilon(\cdot)) = \min_\alpha \left(\epsilon(\alpha) + \frac{\log 1/\delta_{DP}}{\alpha - 1} \right).$$

So we can optimize the parameters $\sigma_f, \sigma_g, \sigma_H$, such that the following objective is minimized

$$\max\left(\bar{\varepsilon}_{DP} - \varepsilon_{DP}(\bar{\epsilon}(\cdot)), 0 \right), \tag{30}$$

where $\bar{\varepsilon}_{DP}$ is the target privacy budget and we replace $\bar{\epsilon}(\cdot)$ with their corresponding versions (29) and (**??**).

B.2 Sample complexity using (ε, δ)-DP

Under the (ε, δ)-DP scheme, subsampling is easier to deal with and we will derive a sample complexity bound. We first introduce some useful results in (ε, δ)-DP.

Proposition B.1 (Composition of (ε, δ)-DP). Suppose that $\mathcal{M}_1 : \mathcal{D} \to \mathcal{R}_1$ is $(\varepsilon_1, \delta_1)$-DP and $M_2 : \mathcal{R}_1 \times \mathcal{D} \to \mathcal{R}_2$ is $(\varepsilon_2, \delta_2)$-DP. Then the mechanism defined as (X, Y), where $X \sim \mathcal{M}_1(D)$ and $Y \sim \mathcal{M}_2(X, D)$ is $(\varepsilon_1 + \varepsilon_2, \delta_1 + \delta_2)$-DP.

Definition B.1 (Gaussian Mechanism for (ε, δ)-DP). Given any function $h : \mathcal{X}^n \to \mathbb{R}^d$, the Gaussian Mechanism is defined as:
$$\mathbf{G}_\sigma h(D) = h(D) + N(0, \Delta_f^2 \sigma^2 I_d),$$
where Δ_h be the ℓ_2-sensitivity of the function h and $\sigma \geq \frac{\sqrt{2\ln(1.25/\delta)}\Delta_2(f)}{\epsilon}$. Then, the Gaussian Mechanism $\mathbf{G}_\sigma h$ satisfies (ϵ, δ)-differential privacy.

Theorem B.6 (Privacy amplification via subsampling (Balle et al., 2018)). . *Given a dataset of n points drawn from a domain $\mathcal{X}$ and a (randomized) mechanism $\mathcal{M}$ that takes an input from $\mathcal{X}^m$ for $m \leq n$, let the randomized algorithm $\mathcal{M} \circ \mathbf{subsample}$ be defined as: (1) subsample: subsample without replacement m datapoints of the dataset (sampling parameter $s = m/n$), and (2) apply $\mathcal{M}$: a randomized algorithm taking the subsampled dataset as the input. If $\mathcal{M}$ is (ε, δ)-DP, then $\mathcal{M} \circ \mathbf{subsample}$ is (ε', δ')-DP, where $\varepsilon' = \log\left(1 + s(e^\varepsilon - 1) \leq s(e^\varepsilon - 1)\right)$ and $\delta' = s\delta$.*

Theorem B.7 (Advanced Composition). *For all $\varepsilon_0, \delta_0, \delta'_0 \geq 0$, the class of $(\varepsilon_0, \delta_0)$-differentially private mechanisms satisfies $(\varepsilon, k\delta + \delta')$-differential privacy under k-fold adaptive composition for:*

$$\varepsilon = \sqrt{2k\ln(1/\delta')}\varepsilon + k\varepsilon\left(e^\varepsilon - 1\right).$$

As a corollary, for $0 < \varepsilon < 1$, it suffices to choose $\epsilon_0 = \frac{\varepsilon}{2\sqrt{2k\log(1/\delta')}}$ to ensure the composition is $(\varepsilon, k\delta + \delta')$-DP. In particular, we can in addition choose $\delta' = \delta/2$ and $\delta_0 = \delta/(2k)$ to satisfy (ε, δ)-DP.

We have the following privacy guarantee for the algorithm using sampling without replacement,

Theorem B.8. *Consider the short step version of the algorithm using subsampling. Given privacy parameters $\varepsilon, \delta, \varepsilon_f, \delta_f \in (0, 1)$ such that $\varepsilon_f < \varepsilon$ and $\delta_f < \delta$, subsampling parameter s. Let $\varepsilon_0 = (\varepsilon - \varepsilon_f)/(8s\sqrt{2T\ln(2/(\delta - \delta_f))})$ and $\delta_0 = (\delta - \delta_f)/(4sT)$, where T is estimated as before in (6). Set $\sigma_f = \frac{\sqrt{2\ln(1.25/\delta_f)}}{\varepsilon_f}$, $\sigma_g = \sigma_H = \frac{\sqrt{2\ln(1.25/\delta_0)}}{\epsilon_0}$. The algorithm is (ε, δ)-DP.*

Proof. By Gaussian mechanism, the step for estimating T is $(\varepsilon_f, \delta_f)$-DP. It suffices to show the remaining steps are $(\varepsilon - \varepsilon_f, \delta - \delta_f)$. Using advanced composition, we only need to show that each iteration is $(4s\varepsilon_0, 2s\delta_0)$-DP.

Consider a single iteration without subsampling. From the usage of Gaussian mechanism and sparse vector technique, we know that computing the perturbed gradient step and the perturbed Hessian step are both $(\varepsilon_0, \delta_0)$-DP, whereas the backtracking line search step is ε_0-DP. By composition, we know that the whole iteration is $(2\varepsilon_0, 2\delta_0)$-DP. Applying the Privacy Amplification Theorem B.6, we know that each iteration using subsampling is $(4s\varepsilon_0, 2s\delta_0)$-DP. $\square$

Since (as earlier) we expect most steps to be gradient steps, rather than negative curvature steps, we overestimate the privacy leakage.

Theorem B.9. *For $c_f \in (0, 1)$, setting $\varepsilon_f = c_f \varepsilon$ and $\delta_f = c_f \delta$, under the choice of parameters σ_g, σ_H in Theorem B.3, the asymptotic dependence of $n_{\min}$ in Theorem B.3 on (ϵ_g, ϵ_H), (ε, δ), , is*

$$n_{\min} = \tilde{O}\left(\frac{d\sqrt{\ln(1/\delta)}}{\varepsilon} \max\left(\epsilon_g^{-2}, \epsilon_g^{-1}\epsilon_H^{-2}, \epsilon_H^{-4}\right)\right). \tag{31}$$

When $(\epsilon_g, \epsilon_H) = (\alpha, \sqrt{M\alpha})$, the dependence simplifies to $\tilde{O}(\frac{d\sqrt{\ln(1/\delta)}}{\varepsilon\alpha^2})$, matching the result in full-batch version of the algorithm by converting ρ-zCDP to (ε, δ)-DP via $\sqrt{\rho} = O(\frac{\varepsilon}{d\sqrt{\ln(1/\delta)}})$ using Proposition A.6.

Proof. As before, we have $\sqrt{T} = O(\max(\epsilon_g, \epsilon_H^{-3/2}))$. After simplification, the order of σ_g and σ_H is

$$\frac{s}{\varepsilon}\sqrt{T}\sqrt{\ln(2sT/\delta)\ln(1/\delta)} = \tilde{O}\left(\frac{s}{\varepsilon}\max(\epsilon_g, \epsilon_H^{-3/2})\right).$$

The asymptotic dependence of $n_{\min}$ follows by substituting σ_g and σ_H into (25). $\qquad\square$

C   Computation of the Smallest Eigenvalue Using Lanczos method

In our algorithms, we need to compute the smallest eigenvalue of the perturbed Hessian. This can be done effectively using the randomized Lanczos algorithm. We have the following result from (Carmon et al., 2017),

Lemma C.1. *Suppose that the Lanczos method is used to estimate the smallest eigenvalue of H starting with a random vector uniformly generated on the unit sphere, where $\|H\| \leq M$. For any $\delta \in [0, 1)$, this approach finds the smallest eigenvalue of H to an absolute precision of $\epsilon/2$, together with a corresponding direction v, in at most*

$$\min\left\{n, 1 + \left\lceil\frac{1}{2}\ln\left(2.75n/\delta^2\right)\sqrt{\frac{M}{\epsilon}}\right\rceil\right\} \quad \textit{iterations}$$

with probability at least $1 - \delta$.

To use Lanczos method in our algorithm, we output an estimate $\tilde{\lambda}$ of $\lambda_{\min}(\tilde{H})$ along with the corresponding eigenvector, provided that $\tilde{\lambda} \leq -\epsilon_H/2$. If $\tilde{\lambda} > -\epsilon_H/2$, we declare that $\lambda_{\min}(\tilde{H}) \geq -\epsilon_H$, with an error probability at most δ_L. Our analysis and convergence results still hold with $\epsilon_H/2$ replacing ϵ_H and adding the success probability of the Lanczos algorithm $1 - \delta_L$ to the product of the success probability in each iteration.

D   Missing Proofs

D.1   Proof of Lemma 2

Lemma D.1. *With the short step size choices (7), if the noise satisfies the following conditions for some positive constants c, c_1, and c_2 such that $c_1 < \frac{1}{2}$ and $c_2 + c < \frac{1}{3}$,*

$$\|\varepsilon_k\| \leq \min\left(c_1\epsilon_g, \frac{c_2}{M}\epsilon_H^2\right), \tag{32a}$$

$$\|E_k\| \leq c\epsilon_H, \tag{32b}$$

then the amount of decrease in each step is at least

$$\text{MIN\_DEC} = \min\left(\frac{1 - 2c_1}{2G}\epsilon_g^2, 2\left(\frac{1}{3} - c_2 - c\right)\frac{\epsilon_H^3}{M^2}\right). \tag{33}$$

The true gradient and true minimum eigenvalue of the Hessian satisfy the following,

$$\|g_k\| \leq (1 + c_1)\|\tilde{g}_k\|, \quad \lambda_k > -(1 + c)|\tilde{\lambda}_k|. \tag{34}$$

Proof. We will use the following two standard bounds, which follow from the smoothness assumptions on f:

$$f(w + p) \leq f(w) + \nabla f(w)^\top p + \frac{G}{2}\|p\|^2, \tag{35}$$

$$f(w + p) \leq f(w) + \nabla f(w)^T p + \frac{1}{2}p^T \nabla^2 f(w)p + \frac{1}{6}M\|p\|^3. \tag{36}$$

For simplicity, we drop the iteration number k in the analysis below.

For gradient steps we have $\|\tilde{g}\| > \epsilon_g$. We write $g = \tilde{g} - \varepsilon$. Using $\|\varepsilon\| \leq c_1\epsilon_g < c_1\|\tilde{g}\|$, it follows from (35) that

$$
\begin{aligned}
f(w - \gamma_g\tilde{g}) &\leq f - \gamma_g(\tilde{g} - \varepsilon)^T \tilde{g} + \frac{G}{2}\gamma_g^2\|\tilde{g}\|^2 \\
&\leq f - \frac{1}{G}(\tilde{g} - \varepsilon)^T \tilde{g} + \frac{1}{2G}\|\tilde{g}\|^2 \\
&\leq f - \frac{1}{2G}\|\tilde{g}\|^2 + \frac{1}{G}\|\varepsilon\|\|\tilde{g}\| \\
&\leq f - \frac{1}{2G}\|\tilde{g}\|^2 + \frac{1}{G}c_1\|\tilde{g}\|^2 \\
&= f - \frac{1}{2G}(1 - 2c_1)\|\tilde{g}\|^2 \\
&\leq f - \frac{1}{2G}(1 - 2c_1)\varepsilon_g^2,
\end{aligned}
$$

while the true gradient satisfies

$$\|g\| \leq \|\tilde{g}\| + \|\varepsilon\| \leq (1 + c_1)\|\tilde{g}\|.$$

When negative curvature steps are taken, we have $\tilde{\lambda} < -\epsilon_H$. By assumption, we have $\|\varepsilon\| \leq \frac{c_2}{M}\epsilon_H^2 < \frac{c_2}{M}|\tilde{\lambda}|^2$ and $\|E\| \leq c\,\epsilon_H < c|\tilde{\lambda}|$. Recall the definition (5) of $\tilde{p}$ and we write $g = \tilde{g} - \varepsilon$, $\tilde{H} = H - E$. From (36), we have

$$
\begin{aligned}
f(w + \gamma_H\tilde{p}) &\leq f + \gamma_H g^T\tilde{p} + \frac{1}{2}\gamma_H^2\tilde{p}^T H\tilde{p} + \frac{1}{6}M\gamma_H^3\|\tilde{p}\|^3 \\
&= f + \gamma_H\tilde{g}^T\tilde{p} + \frac{1}{2}\gamma_H^2\tilde{p}^T\tilde{H}\tilde{p} + \frac{1}{6}M\gamma_H^3\|\tilde{p}\|^3 - \gamma_H\varepsilon^T\tilde{p} - \frac{1}{2}\gamma_H^2\tilde{p}^T E\tilde{p} \\
&\leq f + \frac{1}{2}\left(\frac{2|\tilde{\lambda}|}{M}\right)^2(-|\tilde{\lambda}|) + \frac{1}{6}M\left(\frac{2|\tilde{\lambda}|}{M}\right)^3 - \frac{2|\tilde{\lambda}|}{M}\varepsilon^T\tilde{p} - \frac{1}{2}\left(\frac{2|\tilde{\lambda}|}{M}\right)^2\tilde{p}^T E\tilde{p} \\
&\leq f - \frac{2}{3}\frac{|\tilde{\lambda}|^3}{M^2} + \frac{2|\tilde{\lambda}|}{M}\|\varepsilon\| + \frac{2|\tilde{\lambda}|^2}{M^2}\|E\| \\
&\leq f - \left(\frac{2}{3} - 2c_2 - 2c\right)\frac{|\tilde{\lambda}|^3}{M^2} \\
&\leq f - \left(\frac{2}{3} - 2c_2 - 2c\right)\frac{\epsilon_H^3}{M^2},
\end{aligned}
$$

provided that $c_2 + c < 1/3$. Let λ denote the minimum eigenvalue of H. It follows from Weyl's Inequality that

$$|\tilde{\lambda} - \lambda| \leq \|E\| \leq c|\tilde{\lambda}|,$$

and thus,

$$\lambda > \tilde{\lambda} - c|\tilde{\lambda}| \geq -(1 + c)|\tilde{\lambda}|.$$

$\square$

PROOF OF LEMMA 6

Lemma D.2. *Assume the same bounded noise conditions* (9) *as before. With the choice of sufficient decrease coefficients* $c_g \in (0, 1 - c_1)$, $c_H \in (0, 1 - c - \sqrt{\frac{8}{3}c_2})$, *let* $\bar{\gamma}_g = 2(1 - c_1 - c_g)/G$ *and* $\bar{\gamma}_H = t_2|\tilde{\lambda}|/M$ *as defined in Algorithm 3,*

the sufficient decrease conditions (SD1) *and* (SD2) *are satisfied when* $\gamma \leq \bar{\gamma}_g$ *and* $\gamma \in [(t_1/t_2)\bar{\gamma}_H, \bar{\gamma}_H]$, *respectively, where* $0 < t_1 < t_2$ *are solutions to the following quadratic equation (given our choice of* c, c_2, c_H, *real solutions exist),*

$$r(t) := -\frac{1}{6}t^2 + \frac{1}{2}(1 - c - c_H)t - c_2 = 0,$$

Explicitly, we have

$$t_1, t_2 = \frac{3}{2}(1 - c - c_H) \pm 3\sqrt{\frac{1}{4}(1 - c - c_H)^2 - \frac{2}{3}c_2}. \tag{37}$$

In particular, we have $q_g(\bar{\gamma}_g) \geq 0$ *and* $q_H(\bar{\gamma}_H) \geq 0$.

Proof. The analysis is similar to that of Lemma 2. Again for simplicity we drop iteration indices k.

For gradient steps we have $\|\tilde{g}\| > \epsilon_g$. We write $g = \tilde{g} - \varepsilon$. Using $\|\varepsilon\| \leq c_1 \epsilon_g < c_1 \|\tilde{g}\|$, it follows from (35) that

$$f(w - \gamma\tilde{g}) \leq f(w) - \gamma(\tilde{g} - \varepsilon)^\top \tilde{g} + \frac{G}{2}\gamma^2 \|\tilde{g}\|^2$$

$$\leq f(w) - \left(\gamma - \frac{G}{2}\gamma^2\right)\|\tilde{g}\|^2 + \gamma\|\tilde{g}\|\|\varepsilon\|$$

$$\leq f(w) - \gamma\left(1 - \frac{G}{2}\gamma - c_1\right)\|\tilde{g}\|^2,$$

It follows by definition of $\bar{\gamma}_g$ that (SD1) holds when $\gamma \leq \bar{\gamma}_g$ and

When negative curvature steps are taken, we have $\tilde{\lambda} < -\epsilon_H$. By assumption, we have $\|\varepsilon\| \leq \frac{c_2}{M}\epsilon_H^2 < \frac{c_2}{M}|\tilde{\lambda}|^2$ and $\|E\| \leq c\,\epsilon_H < c|\tilde{\lambda}|$. Recall the definition (5) of $\tilde{p}$ and we write $g = \tilde{g} - \varepsilon$, $\tilde{H} = H - E$. From (36), we have for $\gamma > 0$ that

$$f(w + \gamma\tilde{p}) \leq f(w) + \gamma\tilde{g}^T\tilde{p} + \frac{1}{2}\gamma^2\tilde{p}^T H\tilde{p} + \frac{1}{6}M\gamma^3\|\tilde{p}\|^3 - \gamma\varepsilon^T\tilde{p} - \frac{1}{2}\gamma^2\tilde{p}^T E\tilde{p}$$

$$\leq f(w) - \frac{1}{2}\gamma^2|\tilde{\lambda}| + \frac{1}{6}M\gamma^3 + \gamma\|\varepsilon\| + \frac{1}{2}\gamma^2\|E\|$$

$$\leq f(w) - \underbrace{\left(\frac{1}{2}\gamma^2(1 - c)|\tilde{\lambda}| - \gamma\frac{c_2}{M}|\tilde{\lambda}|^2 - \frac{1}{6}M\gamma^3\right)}_{g(\gamma)}.$$

By reparameterizing $\gamma = \frac{t|\tilde{\lambda}|}{M}$, we obtain

$$g(\gamma) - \frac{1}{2}c_H\gamma^2|\tilde{\lambda}| = \left(-\frac{1}{6}t^3 + \frac{1}{2}(1 - c - c_H)t^2 - c_2 t\right)\frac{|\tilde{\lambda}|^3}{M^2} = t \cdot r(t)\frac{|\tilde{\lambda}|^3}{M^2}.$$

Note that (SD2) holds when $g(\gamma) \geq \frac{1}{2}c_H\gamma^2|\tilde{\lambda}|$. The result follows from the fact that $r(t) \geq 0$ for $t \in [t_1, t_2]$.

$\square$

D.2 PROOF OF LEMMA 7

Lemma D.3. *Using DP line search Algorithm 3, assume the same bounded noise conditions* (9) *as before. With the choice of sufficient decrease coefficients* $c_g \in (0, 1 - c_1), c_H \in (0, 1 - c - \sqrt{\frac{8}{3}c_2})$, *define* $\bar{\gamma}_g$ *and* $\bar{\gamma}_H$ *as before. Choose initial step size multipliers* $b_g, b_H > 1$ *and decrease parameters* $\beta_g \in (0, 1), \beta_H \in (t_1/t_2, 1)$. *Let* $i_{\max} = \lfloor \log_\beta \max(b_g, b_H) \rfloor + 1$. *If* n *satisfies the following:*

$$n \geq 16\lambda\left(\log i_{\max} + \log(T/\xi)\right)\max\left(2b_g\frac{B_g}{c_g\epsilon_g}, 4b_H\frac{B_g M}{t_2 c_H \epsilon_H^2}\right), \tag{38}$$

with probability at least $1 - \xi/T$, *the amount of decrease in a single step is at least*

$$\text{MIN\_DEC} = \min\left(\frac{1}{G}(1 - c_1 - c_g)c_g\epsilon_g^2, \frac{1}{4}c_H t_2^2\frac{\epsilon_H^3}{M^2}\right). \tag{39}$$

Proof. The analysis is similar to that of Lemma 2. Again for simplicity we drop iteration indices k.

For gradient steps we have $\|\tilde{g}\| > \epsilon_g$. We write $g = \tilde{g} - \varepsilon$. Using $\|\varepsilon\| \leq c_1 \epsilon_g < c_1 \|\tilde{g}\|$, it follows from (35) that

$$f(w - \gamma \tilde{g}) \leq f(w) - \gamma(\tilde{g} - \varepsilon)^\top \tilde{g} + \frac{G}{2}\gamma^2 \|\tilde{g}\|^2$$

$$\leq f(w) - \left(\gamma - \frac{G}{2}\gamma^2\right)\|\tilde{g}\|^2 + \gamma\|\tilde{g}\|\|\varepsilon\|$$

$$\leq f(w) - \gamma\left(1 - \frac{G}{2}\gamma - c_1\right)\|\tilde{g}\|^2,$$

It follows by definition of $\bar{\gamma}_g$ that (SD1) holds when $\gamma \leq \bar{\gamma}_g$ and

When negative curvature steps are taken, we have $\tilde{\lambda} < -\epsilon_H$. By assumption, we have $\|\varepsilon\| \leq \frac{c_2}{M}\epsilon_H^2 < \frac{c_2}{M}|\tilde{\lambda}|^2$ and $\|E\| \leq c\,\epsilon_H < c|\tilde{\lambda}|$. Recall the definition (5) of $\tilde{p}$ and we write $g = \tilde{g} - \varepsilon$, $\tilde{H} = H - E$. From (36), we have for $\gamma > 0$ that

$$f(w + \gamma\tilde{p}) \leq f(w) + \gamma\tilde{g}^T\tilde{p} + \frac{1}{2}\gamma^2\tilde{p}^T H\tilde{p} + \frac{1}{6}M\gamma^3\|\tilde{p}\|^3 - \gamma\varepsilon^T\tilde{p} - \frac{1}{2}\gamma^2\tilde{p}^T E\tilde{p}$$

$$\leq f(w) - \frac{1}{2}\gamma^2|\tilde{\lambda}| + \frac{1}{6}M\gamma^3 + \gamma\|\varepsilon\| + \frac{1}{2}\gamma^2\|E\|$$

$$\leq f(w) - \underbrace{\left(\frac{1}{2}\gamma^2(1-c)|\tilde{\lambda}| - \gamma\frac{c_2}{M}|\tilde{\lambda}|^2 - \frac{1}{6}M\gamma^3\right)}_{g(\gamma)}.$$

By reparameterizing $\gamma = \frac{t|\tilde{\lambda}|}{M}$, we obtain

$$g(\gamma) - \frac{1}{2}c_H\gamma^2|\tilde{\lambda}| = \left(-\frac{1}{6}t^3 + \frac{1}{2}\left(1 - c - c_H\right)t^2 - c_2 t\right)\frac{|\tilde{\lambda}|^3}{M^2} = t \cdot r(t)\frac{|\tilde{\lambda}|^3}{M^2}.$$

Note that (SD2) holds when $g(\gamma) \geq \frac{1}{2}c_H\gamma^2|\tilde{\lambda}|$. The result follows from the fact that $r(t) \geq 0$ for $t \in [t_1, t_2]$.

$\square$

D.3 PROOF OF COROLLARY D.4

Corollary D.4. *Assuming the noise satisfies* (9) *at each iteration, the short step version (using* (7)*,* (10)*) of the algorithm will output a* $((1 + c_1)\epsilon_g, (1 + c)\epsilon_H)$*-2NS.*

Proof. From the minimum decrease (10) we just derived, it follows that the algorithm will terminate in T^* iterations, where

$$T^* = \frac{f(w_0) - f^*}{\text{MIN\_DEC}}.$$

Our choice of T in (6) is an upper bound of T^* and thus the algorithm will halt within T iterations. In the iteration k when the algorithm halts, we have $\|\tilde{g}_k\| \leq \epsilon_g$ and $\tilde{\lambda}_k \geq -\epsilon_H$. It follows from (11) that the output is a $((1 + c_1)\epsilon_g, (1 + c)\epsilon_H)$-2NS. $\square$

D.4 PROOF OF THEOREM 4

Theorem D.5 (Sample complexity of the short step algorithm). *Consider the ERM setting. Suppose that the number of samples n satisfies $n \geq n_{\min}$, where*

$$n_{\min} := \max\left(\frac{\sqrt{2d}B_g\sigma_g \log \frac{T}{\zeta}}{\min\left(c_1\epsilon_g, \frac{c_2}{M}\epsilon_H^2\right)}, \frac{C\sqrt{d}B_H\sigma_H \log \frac{T}{\zeta}}{c\,\epsilon_H}\right).$$

With probability at least $\{(1 - \frac{\zeta}{T})(1 - C\exp(-cCd))\}^T$ where c and C are universal constants in Lemma D.7, the output of the short step version (using (7)*,*(10)*) of the algorithm is a $((1 + c_1)\epsilon_g, (1 + c)\epsilon_H)$-2NS.*

With the choice of σ's in (8) using $\rho_f = c_f \rho$ for $c_f \in (0,1)$, hiding logarithmic terms and constants, the asymptotic dependence of $n_{\min}$ on (ϵ_g, ϵ_H), ρ and d, is

$$n_{\min} = \frac{d}{\sqrt{\rho}} \tilde{O}\left(\max\left(\epsilon_g^{-2}, \epsilon_g^{-1}\epsilon_H^{-2}, \epsilon_H^{-7/2}\right)\right). \tag{40}$$

When $(\epsilon_g, \epsilon_H) = (\alpha, \sqrt{M\alpha})$, the dependence simplifies to $\frac{d}{\sqrt{\rho}} \tilde{O}(\alpha^{-2})$. Before proving Theorem 4, we introduce two concentration results.

Lemma D.6 (Gaussian concentration, (Vershynin, 2018)). *For $x \sim \mathcal{N}\left(0, \sigma^2 I_d\right)$, with probability at least $1 - \eta$ for any $1 > \eta > 0$, we have*

$$\|x\| \leq \sqrt{2d}\sigma \log \frac{1}{\eta}.$$

Lemma D.7 (Upper tail estimate for Wigner ensembles (Tao, 2012, p. 110)). *Let $M = (m_{ij})_{1 \leq i,j \leq d}$ be an $d \times d$ random symmetric matrix. Suppose that the coefficients m_{ij} of M are independent for $j \geq i$, mean zero, and have uniform sub-Gaussian tails. There exist universal constants $C, c > 0$ such that for all $A \geq C$, we have*

$$\mathbf{P}\left(\|M\| > A\sqrt{d}\right) \leq C\exp(-cAd).$$

Proof. It follows from concentration results that, in iteration k, with probability at least $(1 - \frac{\zeta}{T})(1 - C\exp(-cCd))$, we have

$$\|\varepsilon_k\| \leq \sqrt{2d}\Delta_g\sigma_g \log \frac{T}{\zeta}, \tag{41a}$$

$$\|E_k\| \leq C\sqrt{d}\Delta_H\sigma_H. \tag{41b}$$

We need to find a condition on n that ensures that the right hand sides are less than the right hand sides of (9). We substitute for Δ_g and Δ_H from (4) and solve for $n_{\min}$ by rearranging the terms. The result then follows from Corollary D.4 if the concentration results hold for all iterations.

Now let us calculate the success probability. For each iteration, we have a probability of at least $(1 - \frac{\zeta}{T})(1 - C\exp(-cCd))$ that the concentration results hold (if we do not compute the perturbed Hessian, the probability is higher with at least $1 - \frac{\zeta}{T}$. Using conditional probability, the overall success probability is $\{(1 - \frac{\zeta}{T})(1 - C\exp(-cCd))\}^\tau$ conditioned on the number of iterations τ. Since $\tau \leq T$, the overall success probability is at least $\{(1 - \frac{\zeta}{T})(1 - C\exp(-cCd))\}^T$.

For the second part, recall from (8) that $\sigma_g = \sigma_H = \sqrt{T}/\sqrt{(1-c_f)\rho}$. With (10) and our choice of T in (6), we have $\sqrt{T} = O(\max(\epsilon_g, \epsilon_H^{-3/2}))$. We obtain the asymptotic bound of $n_{\min}$ by plugging in σ_g and σ_H. $\qquad\square$