How You Say It Matters: Personalizing LLM Responses via Dual Time-Scale Closed-Loop Adaptation

Abstract

Personalization in large language models (LLMs) is framed as a content problem focused on deciding what to retrieve, generate, or recommend. However, identical content can have different effects on the user's affective and cognitive states depending on how it is delivered, including its structure, tone, and relational style. We present an adaptation framework that addresses delivery personalization using a *fast loop* which corrects per-turn quality degradation within sessions, while a *slow loop* learns per-user priors across sessions. We evaluate 1,094 conversations across three models from Anthropic and OpenAI and show that our framework systematically differentiates the output along the targeted affective and cognitive dimensions and outperforms the unconditioned baseline across all measured quality outcomes, with effect sizes ($d = 0.61$–1.26). These results suggest that delivery can be modeled as a distinct axis of LLM personalization, adapting to both longer-term user patterns and changes within an interaction.

1 Introduction

Most research on large language model (LLM) personalization treats personalization primarily as a content problem: what information to retrieve from a user's history, what context to include in prompts, which objectives to optimize during fine-tuning, or how to align outputs through reinforcement learning from human feedback (RLHF). Although these approaches differ in mechanism, they largely focus on determining *what* content the model should generate (Zhang et al., 2025). This framing, however, underemphasizes another important aspect of user experience: *how* the content is delivered. Prior work shows that structure, fluency, tone, and framing influence what people encode, trust, believe, and retain (Meyer, 1975; McNamara et al., 1996; Fazio et al., 2015; Oppenheimer, 2006). As a result, two responses may be factually equivalent while producing substantially different user experiences.

Some deployed systems expose delivery controls through static user-defined settings, such as *ChatGPT*'s "Personality" (OpenAI, 2026) and *Claude*'s "Personalization" (Anthropic, 2026). These interfaces allow users to specify preferred interaction styles or tones. However, they require users to determine in advance what kind of response they need and how to request it. Moreover, although prior work recognizes that users differ from one another (Qiu et al., 2025; Woźniak et al., 2024; Zeng et al., 2025; Tan et al., 2024), most personalization research implicitly treats those preferences as stable traits. This leaves limited understanding of how the same person's preferences may shift across contexts, goals, and moments in time (Ong et al., 2017; Beckmann et al., 2020; Judd et al., 2024).

Consider two users asking: *"I'm thinking about leaving my job to start a business. What should I do?"* Alex wants a structured analysis with tradeoffs, quantitative reasoning, and a recommended sequence of actions. Maya, in contrast, is weighing questions of identity, family, and uncertainty, and wants those concerns acknowledged before receiving advice. The same factual response may therefore feel useful to Alex but emotionally unresponsive to Maya. This illustrates the *between-person* dimension of delivery personalization.

The *within-person* dimension is equally important. Suppose Alex later asks: *"What should I do about my mortgage refinance?"* On Monday morning, after reviewing financial documents, he may prefer rates, thresholds, and a direct recommendation. On Friday evening, after a difficult day he never explicitly mentions,

Figure 1: **Between- and within-person variation in delivery personalization. (1) Between-person variation:** Alex and Maya ask the same question, but the same response engages one and fails the other. **(2) Within-person variation:** the same user asks the same question at different moments, but a response that fits once may fail later. **(3) Our framework:** we parameterize delivery with a *UIO* over content and relational dimensions. A *slow loop* learns per-user priors across sessions, while a *fast loop* responds to per-turn failures within a session. Both are driven by a shared reward, the EQS.

the same concise response may feel poorly calibrated. The issue is not that Alex has become a different user. Rather, the response no longer matches his current state. Systems that model only stable preferences risk personalizing toward a long-term average that fails in the moment.

To address this problem, we explicitly model *delivery* as part of personalization through a unified instruction schema called the **Unified Instruction Object** (UIO). The UIO parameterizes content-related dimensions such as structure, reading level, explanation depth, and interactional form, together with relational dimensions including warmth, supportiveness, directiveness, and emotional attunement. We then adapt these dimensions through two complementary feedback loops. A **fast loop** operates within a session by detecting quality degradation, attributing failures to specific delivery dimensions, and adjusting subsequent responses. A **slow loop** operates across sessions by learning per-user Dirichlet priors over delivery dimensions and blending them with rule-based defaults at the start of future interactions. Both loops are optimized using a shared reward signal, the **Experience Quality Score** (EQS), which combines instruction compliance, behavioral engagement, and subjective feedback.

We evaluate the framework in a simulation-based study consisting of 1,094 single- and multi-turn conversations generated by pairing DEAP-grounded user states with PRISM prompts across models from Anthropic and OpenAI. We compare the full adaptive framework against both a conditioned-only ablation and an unconditioned baseline. Structured delivery conditioning makes outputs systematically distinguishable across affective and cognitive states, increasing mode-effect sizes by 1.6–$65\times$ relative to the unconditioned baseline. The full framework improves performance across every measured quality dimension, achieving large effect sizes ($d = 0.61$–1.26). The fast loop targets the failing delivery dimension in 96–98% of adjustments, while the slow loop learns per-user priors that diverge monotonically from population defaults.

The key contributions of this work are as follows:

- We formulate delivery as a personalization target distinct from task content, covering both structural and relational properties of LLM responses.

- We introduce a dual time-scale inference-time adaptation framework consisting of a fast within-session correction loop and a slow cross-session preference-learning loop.

- We propose the Experience Quality Score (EQS), a unified reward signal that combines instruction compliance, behavioral engagement, and subjective feedback.

- We demonstrate across single- and multi-turn conversations that structured delivery conditioning and adaptive feedback improve interaction quality relative to conditioned-only and unconditioned baselines.

2 Related Work

LLM personalization. LLM personalization is commonly approached through retrieval, prompting, representation learning, or feedback-based alignment (Zhang et al., 2025). **Retrieval-based methods** store user information externally and retrieve it at inference time (Salemi et al., 2024; Mysore et al., 2024; Li et al., 2025); **prompting methods** place user profiles or histories directly in context (Qiu et al., 2025; Huang et al., 2024; Woźniak et al., 2024); **representation-learning** methods encode preferences into model parameters or adapters (Liu et al., 2025; Magister et al., 2025; Tan et al., 2024); and **RLHF-based methods** use user feedback as an alignment signal (Li et al., 2024; Jang et al., 2023; Park et al., 2024). These approaches differ in where user information is stored and how it is used, but they primarily personalize what information is selected, represented, or optimized. Instead, our work treats response delivery itself as the object of adaptation.

User states in LLMs. Recent work studies whether LLMs can infer affective, cognitive, and social signals from interaction. Affective work examines emotion recognition and related enhancements (Feng et al., 2024; Lecourt et al., 2025; Hong et al., 2025), while cognitive and social work studies personality inference and theory-of-mind reasoning (Peters & Matz, 2024; Cursi et al., 2025; Kosinski, 2024; Street et al., 2026). These studies show that user-state signals can be estimated or modeled, but they often stop at inference. Our work asks how such inferred states should change the response format.

Delivery and communication. Research in linguistics, cognitive psychology, and instructional design shows that form affects how messages are processed. Organization and positioning shape recall and learning (Meyer, 1975; Mar et al., 2021; McNamara et al., 1996), especially under working-memory constraints (Sweller, 1988; Sweller et al., 1998). Fluency also serves as a metacognitive cue for truth, credibility, coherence, and perceived intelligence (Hasher et al., 1977; Fazio et al., 2015; Topolinski & Strack, 2009; Oppenheimer, 2006). More broadly, language conveys not only propositional content but also interpersonal stance and social context (Halliday, 1978), and speakers adapt style across situations (Giles, 1973; Giles & Ogay, 2007). This work motivates treating delivery as part of the communicative function of a response, rather than as a purely stylistic layer.

Between- and within-person variability. Personalization usually assumes stable differences across users. Indeed, people differ in cognitive ability, decision-making, emotional complexity, and personality (Judd et al., 2024; Boogert et al., 2018; Pittaras et al., 2022; Ong et al., 2017; Beckmann et al., 2020). However, individuals also vary across time and context (Siegler, 2006; Ong et al., 2017; Beckmann et al., 2020; Haegens et al., 2014; Larsen-Freeman, 2006). Because between-person and within-person variability are distinct and stable sources of variation (Judd et al., 2024; Kelava et al., 2022; Goregliad Fjaellingsdal et al., 2025; Marciano & Yeshurun, 2017), they require different design responses (Wang et al., 2012; Whitaker et al., 2026; Pescuma et al., 2023). For LLMs, this means that a fixed user profile may capture stable preferences but miss momentary needs. This distinction motivates our separation between slow cross-session priors and fast within-session adjustment.

3 Methodology

We describe the framework in four components. We first define the delivery instruction space (§3.1), then describe the response generation procedure (§3.2), the reward used to score each turn (§3.3), and the two feedback loops that update delivery within and across sessions (§3.4).

3.1 Instruction Space

We represent delivery with a unified instruction schema, which we call the **Unified Instruction Object** (UIO). The UIO is implemented as two JSON documents: *PolicyJSON* and *PersonaJSON*. Together, they specify 23 delivery dimensions over two axes. The *content axis* controls properties such as structure, reading level, explanation depth, and interactional form. The *relational axis* controls properties such as supportiveness, warmth, directiveness, and emotional attunement. The resolved UIO is supplied to the generator as part of its system prompt, while the feedback loops evaluate how well the response realizes the specified delivery constraints. Full dimensions and resolution rules appear in Appendix B.

3.2 Response Generation

For each turn, response generation separates delivery planning from user-facing realization. The first stage produces an internal reasoning representation, denoted as the *ReasoningBlock*. It consumes the serialized UIO and user prompt, then summarizes how the response should satisfy the relevant delivery instructions. We store its result as an independent artifact for auditing the model's situational awareness during response generation.

The second stage generates the user-facing response. It consumes the user message, the resolved UIO, the ReasoningBlock, and the last k conversation turns. This separation allows the system to make delivery constraints explicit before generating the final response, while keeping internal reasoning artifacts hidden from the user. Prompt templates and decoding settings appear in Appendix C.

3.3 Experience Quality Score

The **Experience Quality Score** (EQS) is the reward signal shared by both feedback loops. It combines three sources of evidence about the turn: instruction compliance, behavioral engagement, and subjective user feedback. To avoid self-evaluation by the generator, compliance is judged by a separate semantic evaluator, the **Semantic Feedback Engine** (SFE; §3.4.1). Engagement is extracted from user behavior, and subjective feedback is elicited directly from the user. When one component is unavailable, we drop it and renormalize the remaining weights rather than imputing a value.

Compliance (C). Compliance measures whether the response follows the policy and persona instructions in the UIO. We evaluate each dimension by intent rather than surface form.

Engagement (E). Engagement is derived from the user's next message and normalized against the user's own session baseline. It combines four sub-signals: follow-up length, follow-up complexity, explicit correction, and continuation. Length and complexity are converted to session-relative scores. Explicit correction is capped because the absence of correction does not imply satisfaction. If the user abandons the session, continuation is marked unavailable and the EQS weights are renormalized.

Subjective feedback (S). The subjective component comes from user ratings collected periodically, after detected degradation, and at session end. We use eight 5-point Likert items and two free-text retrospective questions. Available Likert items are normalized, inverted where needed, and averaged. If no rating is available for a turn, the subjective component is omitted from EQS. The full item inventory and scheduling policy appear in Appendix D.

3.4 Dual Time-Scale Feedback

The UIO is adapted on two coupled timescales. The *fast loop* responds to within-session failures by adjusting the next turn. The *slow loop* learns stable per-user delivery preferences across sessions and initializes future UIO resolution. The coupling is one-way within each cycle: the fast loop provides positive examples at session end, and the slow loop uses them to update the next session's priors.

3.4.1 Quality Measurement

We measure response quality using both deterministic features and semantic evaluation. First, a deterministic analyzer built with spaCy (Honnibal et al., 2020) and `textstat` (textstat, 2026) extracts structural and linguistic features, including length, paragraph structure, readability, lexical diversity, and grammatical markers. These metrics provide stable inputs for compliance checks and fallback attribution.

Second, the SFE acts as a stateless post-hoc evaluator independent of the generator. It consumes the user message, model response, UIO, ReasoningBlock, and recent history, then returns structured judgments for safety, semantic compliance, and adaptation. The SFE can be implemented as either a trained compliance classifier or an LLM critic. We use the LLM critic because it requires no task-specific training data and generalizes across UIO dimensions. This semantic signal is used for fast-loop adaptation because it supports failure attribution, rather than only failure detection. Full prompts and settings appear in Appendix E.

Figure 2: Dual feedback loops. The fast loop detects turn-level quality drops from EQS and SFE feedback, then adjusts the next response. The slow loop updates user priors and EQS weights at session end, subject to cross-session consent.

3.4.2 Fast Loop

The fast loop (Figure 2, Left) operates at turn granularity. At each turn, it compares the current EQS to a rolling baseline over previous turns. If the drop exceeds a threshold τ, the turn is treated as degrading; if the increase exceeds τ, the turn is treated as improving.

When adaptation is needed, the loop first uses the SFE recommendation. A fixed lexicon maps SFE feedback to UIO dimensions and directions. If the semantic evaluator provides no actionable recommendation, the loop falls back to EQS attribution: low compliance indicates an execution failure, low engagement points to the weakest behavioral sub-signal, and low subjective feedback points to the worst rated dimension. Adjustments are categorical (`increase`, `decrease`, or `maintain`) and are applied as a single ordinal step. We cap each update at two target dimensions to avoid over-correction.

On the second consecutive degrading turn, the loop asks a short Likert question to disambiguate the failure before the session ends. Improving turns are logged as positive examples for the slow loop.

3.4.3 Slow Loop

The slow loop (Figure 2, Right) learns stable delivery preferences across sessions. It takes positive examples and session-level EQS summaries as input, then updates per-dimension preference priors and EQS component weights for the next session.

Prior representation. For each user, the slow loop maintains a *PreferencePrior* with one categorical distribution for each adaptable dimension. We track 14 dimensions in total: 7 policy dimensions and 7 persona dimensions (Table 1). For each dimension $d \in \mathcal{D}$ with value set $\mathcal{V}_d$, we initialize a symmetric Dirichlet prior:

$$P_u^{(d)} \sim \text{Dir}\left(\alpha_0 \cdot \mathbf{1}_{|\mathcal{V}_d|}\right), \qquad \alpha_0 = 1. \tag{1}$$

This prior is non-informative, so the rule-based resolver controls cold-start behavior until evidence accumulates.

Table 1: Dimensions tracked by the slow-loop preference prior.

Policy (7)	Persona (7)
reading_level	challenge_level
sentence_complexity	supportiveness
technicality	directiveness
explanation_depth	warmth
information_density	error_tolerance
examples_frequency	emotional_attunement
choice_complexity	interactivity

Example selection. At session end, the slow loop selects training evidence in two tiers. Tier 1 contains improving turns from the fast loop whose EQS exceeds the behavioral threshold η_{beh}. Tier 2 contains other high-reward turns, ranked by EQS and subjective feedback when available. Tier 2 examples enter with half weight, $\lambda_t = 0.5$. If no turn passes the threshold, we keep the single best turn with positive reward.

Prior update. To handle non-stationary preferences, we update priors using only a sliding window of the most recent W sessions. Let S be the current session index. The fractional count for value v of dimension d is

$$n_v^{(d,W,S)} = \sum_{s=\max(1,\,S-W+1)}^{S} \sum_{t \in \mathcal{T}_s^+} \lambda_t \cdot \mathbb{K}\left[v_t^{(d)} = v\right]. \tag{2}$$

where $\mathcal{T}_s^+$ is the set of selected turns from session s and $\lambda_t \in \{1.0, 0.5\}$ is the tier weight. Let $N^{(d,W,S)} = \sum_v n_v^{(d,W,S)}$. Dirichlet–Categorical conjugacy gives the posterior mean:

$$\hat{P}_u(v \mid d, S) = \frac{\alpha_0 + n_v^{(d,W,S)}}{|\mathcal{V}_d| \cdot \alpha_0 + N^{(d,W,S)}}. \tag{3}$$

Prior blending. The influence of the learned prior grows with posterior concentration:

$$\alpha_{\text{eff}}^{(d,S)} = \min\left(\frac{N^{(d,W,S)}}{|\mathcal{V}_d| \cdot \alpha_0 + N^{(d,W,S)}}, \alpha_{\max}\right). \tag{4}$$

At the start of the next session, the resolver blends the rule-based default v_{rule} with the learned prior:

$$v^* = \arg\max_{v \in \mathcal{V}_d}\left[\left(1 - \alpha_{\text{eff}}^{(d,S)}\right) \cdot \mathbb{K}[v = v_{\text{rule}}] + \alpha_{\text{eff}}^{(d,S)} \cdot \hat{P}_u(v \mid d, S)\right]. \tag{5}$$

Thus, dimensions with more evidence personalize faster, while sparsely-observed dimensions remain rule-driven. We cap $\alpha_{\max} = 0.8$, preserving at least 20% weight for rule-based defaults and preventing user priors from overriding safety-gated policy bounds.

EQS weight adaptation. The slow loop also updates the user's EQS component weights (w_C, w_E, w_S). At session end, it treats the mean subjective score as the target and increases the weight of the objective component, compliance or engagement, that best tracks it. The remaining active weights are reduced, and the vector is projected back onto the simplex with bounds $[0.1, 0.6]$. If no subjective feedback is available, the active weights are simply renormalized.

Cold start and consent. In the first session, the posterior is uniform and $\alpha_{\text{eff}} = 0$, so the UIO is resolved entirely by the rule-based defaults. Cross-session personalization begins in session 2 and only when the user has granted explicit consent. Without consent, no cross-session preference state is stored.

4 Research Questions

We evaluate whether delivery can be controlled, whether it improves measured interaction quality, and whether adaptation occurs on the two timescales introduced above.

RQ1: Delivery controllability. Does a structured delivery instruction make model outputs systematically different across target affective and cognitive states, relative to an unconditioned baseline?

RQ2: Interaction quality. Does adaptive delivery improve measured interaction quality over both a conditioned non-adaptive system and an unconditioned baseline?

RQ3: Dual time-scale adaptation. Do the two feedback loops act on their intended timescales: fast within-session recovery after degradation, and slow cross-session learning of user-specific priors?

5 Experiments

We evaluate the framework with simulated multi-state users built from two public datasets. **DEAP** (Koelstra et al., 2012) provides affective state labels, and **PRISM** (Kirk et al., 2024) provides user prompts. We discretize DEAP into a 3×3 valence–arousal grid (A_1–A_9) and select six target modes covering the poles, a neutral anchor, and three contrastive cells. We select eight subjects using variance-filtered greedy coverage and reserve one held-out distressed subject (S13, persistent A_1) for Run D. We filter and classify PRISM prompts into a 12-cell affect-by-task grid, yielding 116 prompts.

We compare three conditions. The full system (C_0) uses UIO conditioning with both feedback loops enabled. The conditioned-only ablation (C_2) uses the same UIO conditioning but disables both loops. The unconditioned baseline (C_4) bypasses the pipeline and generates directly from the user prompt.

The evaluation consists of four runs. **Runs A/B** contain 288 matched single-turn trials each and compare C_0 against C_4, isolating the effect of structured delivery conditioning. **Run D** contains 40 sessions and 259 turns, comparing the full system (C_0) with the conditioned-only ablation (C_2) in multi-session interaction. **Run D*** replays the Run D traces through the ChatGPT and Claude chat interfaces to construct the multi-session C_4 arm. Subject selection, prompt filtering, condition definitions, and run protocols appear in Appendices G, H, F, and I.

6 Results

6.1 RQ1: Delivery Controllability

Structured UIO conditioning makes delivery controllable. A MANOVA over the nine-feature delivery vector shows large affective-mode effects under C_0 for both Claude and GPT (Claude η_p^2=0.194; GPT η_p^2=0.202; both p<.001). These effects are more than three times larger than under C_4 (Claude 0.049; GPT 0.067). The amplification holds for all nine features on both models (Fig. 3). For example, word count rises from roughly 60 tokens in A_1 to roughly 225 tokens in A_9 under C_0, while remaining comparatively flat under C_4 (Fig. 4).

Figure 3: Affective-mode effect sizes for nine delivery features under UIO conditioning (C_0) and the unconditioned baseline (C_4). Across both models, every feature shows a larger mode effect under C_0. Features are ordered by Claude C_0 effect size. The dotted line marks $\eta^2 = 0.01$.

Figure 4: Mode trajectories for three discriminating delivery features. Under C_0, both models produce ordered shifts across target modes. Under C_4, the same features remain comparatively flat.

Compliance is strongest for directly specified structural constraints: paragraph count, sentence count, and reading level all exceed 92% on both models. More semantic dimensions are harder to control. Technicality reaches 50.0% compliance on Claude and 56.0% on GPT, while SFE overall fit reaches 0.735 and 0.839, respectively. The same difficulty ordering appears on both models (encouragement < tone < interactivity < challenge level). Cognitive-load conditioning follows the same pattern, with substantially larger effects under C_0 than C_4 (Claude/GPT: 0.345/0.312 vs. 0.069/0.077). The effect is also model-robust: per-feature C_0 effect sizes correlate strongly across Claude and GPT ($r = 0.80$), and every feature satisfies $C_0 > C_4$. Full statistics appear in Appendix J.

6.2   RQ2: Adaptive Delivery and Interaction Quality

Adaptive delivery improves interaction quality beyond both baselines. Pooled across models ($N = 80$ paired sessions), the full system (C_0) outperforms the unconditioned baseline (C_4) on all eight outcome features. Effects are large for EQS ($d = 1.21$), SFE overall fit ($d = 1.26$), and all six SFE dimensions ($d = 0.61$–1.15; all Holm-corrected $p < .001$; Fig. 5).

The conditioned-only ablation (C_2) also outperforms C_4 on every feature, showing that state-conditioned delivery accounts for most of the gain. The full system still improves over C_2 on EQS, overall fit, interactivity,

Figure 5: Pairwise condition effects across the eight RQ2 outcome features. Points show paired Cohen's d_z with BCa stratified-bootstrap 95% CIs. The C_2-C_4 contrast estimates the contribution of state conditioning; C_0-C_2 estimates the added contribution of closed-loop adaptation.

tone, encouragement, and detail level, showing that closed-loop adaptation adds a consistent residual benefit. Decomposition analysis attributes 74–91% of the total C_0-C_4 gap to conditioning and the remaining 9–26% to feedback loops. Loop gains are largest on relational dimensions, especially encouragement (26%) and tone (21%). The $C_0>C_4$ result is robust to all pre-registered sensitivity checks, including excluding the distressed subject S_{13}, model-specific analyses, Bonferroni correction, and removing subjective-feedback sessions. Full comparisons and sensitivity analyses appear in Appendix K.

6.3 RQ3: Dual Time-Scale Adaptation

Figure 6: Fast-loop recovery by targeted dimension. Bars show mean next-turn change on the matched SFE feature after an adjustment. Labels show the percentage of adjustments with positive recovery. The inset reports how often the loop targeted the lowest-scoring SFE dimension.

The fast loop reliably localizes within-session degradation, targeting the lowest-scoring SFE dimension in 96.2% of Claude adjustments and 98.5% of GPT adjustments. Next-turn recovery is positive for nearly all targeted dimensions. Gains are largest for directly specified structural dimensions, such as `reading_level` and `challenge_level` (mean $\Delta = +0.06$ to $+0.14$), and smaller but consistent for relational dimensions, such as `supportiveness` and `emotional_attunement` (mean $\Delta = +0.03$ to $+0.06$; Fig. 6).

Figure 7: Slow-loop personalization across eight sessions. **(A)** The blending factor α_{eff} approaches the cap $\alpha_{\text{max}} = 0.8$. **(B)** JS divergence from the uniform prior increases. **(C)** Hamming distance between the conditioning-only and prior-blended UIOs increases on slow-only turns. Shaded bands show ± 1 SD across subjects.

The slow loop produces monotonic cross-session personalization. Across eight sessions, α_{eff} rises to the design cap of 0.80, JS divergence from the uniform prior grows to 0.097 on Claude and 0.104 on GPT, and the Hamming distance between the conditioning-only and prior-blended UIOs increases significantly on both models (all linear trends $p < .001$; Fig. 7). Terminal priors also diverge across users: mean between-subject Hamming distance reaches 5.0 out of 14 dimensions on Claude and 4.4 on GPT.

Personalization is concentrated rather than global. Users diverge most on relational and depth-related dimensions, including `challenge_level`, `explanation_depth`, and `emotional_attunement`. They converge more often on `technicality`, `examples_frequency`, and `choice_complexity`. Full targeting, recovery, trajectory, and divergence analyses appear in Appendix L.

7 Conclusion

We presented a dual time-scale framework for personalizing LLM response delivery. The results support treating delivery as a distinct target for personalization, with fast adaptation for within-session shifts and slow adaptation for cross-session preferences.

8 Limitations

First, we evaluate adaptation with simulated users rather than recruited participants. This gives us controlled state changes and matched comparisons, but it cannot fully capture how real users perceive or respond to delivery adaptation. The engagement and subjective feedback signals therefore reflect the simulator's assumptions. Our results should be read as evidence that the framework can control and adapt delivery under a grounded simulation, not as a final claim about real user experience.

Second, the framework relies on LLM calls for private reasoning and semantic feedback. This improves flexibility across tasks and delivery dimensions, but it adds cost and latency. The SFE also inherits the limitations of LLM-based evaluation, including possible model dependence and imperfect calibration. We mitigate this by separating generation from evaluation and by using deterministic metrics where possible, but future work should compare LLM critics with trained or hybrid evaluators.

Third, we focus on delivery quality rather than task correctness. The framework is intended to adapt how content is expressed, but we do not fully test whether these adaptations affect factual accuracy, reasoning quality, or downstream task success. This matters especially in high-stakes settings.

Finally, our evaluation covers a limited set of models, prompts, and state variables. We instantiate state with affective mode and cognitive load, but other settings may require additional signals and stricter safety constraints. Real deployments would also require consent, privacy safeguards, user controls, and mechanisms for inspecting or resetting learned delivery priors.

References

Anthropic. Understanding Claude's personalization features. https://support.claude.com/en/articles/10185728-understanding-claude-s-personalization-features, 2026.

Nadin Beckmann, Damian P. Birney, Jens F. Beckmann, Robert E. Wood, Victor Sojo, and David Bowman. Inter-individual differences in intra-individual variability in personality within and across contexts. *Journal of Research in Personality*, 85:103909, 2020. doi: 10.1016/j.jrp.2019.103909. URL https://www.sciencedirect.com/science/article/pii/S0092656619301291.

Neeltje J. Boogert, Joah R. Madden, Julie Morand-Ferron, and Alex Thornton. Measuring and understanding individual differences in cognition. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 373(1756):20170280, 2018. doi: 10.1098/rstb.2017.0280. URL https://doi.org/10.1098/rstb.2017.0280.

Francesco Di Cursi, Chiara Boldrini, Marco Conti, and Andrea Passarella. Mind reading or misreading? llms on the big five personality test, 2025. URL https://arxiv.org/abs/2511.23101.

Lisa K. Fazio, Nadia M. Brashier, B. Keith Payne, and Elizabeth J. Marsh. Knowledge does not protect against illusory truth. *Journal of Experimental Psychology: General*, 144(5):993–1002, 2015. doi: 10.1037/xge0000098.

Shutong Feng, Guangzhi Sun, Nurul Lubis, Wen Wu, Chao Zhang, and Milica Gasic. Affect recognition in conversations using large language models. In Tatsuya Kawahara, Vera Demberg, Stefan Ultes, Koji Inoue, Shikib Mehri, David Howcroft, and Kazunori Komatani (eds.), *Proceedings of the 25th Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pp. 259–273, Kyoto, Japan, September 2024. acl. doi: 10.18653/v1/2024.sigdial-1.23. URL 2024.sigdial-1.23/.

Howard Giles. Accent mobility: A model and some data. *Anthropological Linguistics*, 15:87–105, 1973.

Howard Giles and Tania Ogay. Communication accommodation theory. In Bryan B. Whaley and Wendy Samter (eds.), *Explaining Communication: Contemporary Theories and Exemplars*, pp. 293–310. Lawrence Erlbaum Associates, Mahwah, NJ, 2007.

Tatiana Goregliad Fjaellingsdal, Konstantin Döhr, Greta Zschoche, and Ulrike M. Krämer. Advancing the measurement of affective self-other distinction: A novel paradigm to measure intra- and inter-individual differences in emotional biases. *Acta Psychologica*, 261:105840, 2025. doi: 10.1016/j.actpsy.2025.105840. URL https://www.sciencedirect.com/science/article/pii/S0001691825011539.

Saskia Haegens, Helena Cousijn, George Wallis, Paul J. Harrison, and Anna C. Nobre. Inter- and intra-individual variability in alpha peak frequency. *NeuroImage*, 92:46–55, 2014. doi: 10.1016/j.neuroimage.2014.01.049. URL https://www.sciencedirect.com/science/article/pii/S1053811914000792.

M. A. K. Halliday. *Language as Social Semiotic: The Social Interpretation of Language and Meaning.* Edward Arnold, London, 1978.

Lynn Hasher, David Goldstein, and Thomas Toppino. Frequency and the conference of referential validity. *Journal of Verbal Learning and Verbal Behavior*, 16(1):107–112, 1977. ISSN 0022-5371. doi: 10.1016/S0022-5371(77)80012-1. URL https://www.sciencedirect.com/science/article/pii/S0022537177800121.

Xin Hong, Yuan Gong, Vidhyasaharan Sethu, and Ting Dang. Aer-llm: Ambiguity-aware emotion recognition leveraging large language models. In *ICASSP 2025 - 2025 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 1–5, 2025. doi: 10.1109/ICASSP49660.2025.10888198.

Matthew Honnibal, Ines Montani, Sofie Van Landeghem, and Adriane Boyd. spaCy: Industrial-strength natural language processing in python, 2020. URL `https://spacy.io`.

Qiushi Huang, Xubo Liu, Tom Ko, Bo Wu, Wenwu Wang, Yu Zhang, and Lilian Tang. Selective prompting tuning for personalized conversations with LLMs. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 16212–16226, Bangkok, Thailand, August 2024. acl. doi: 10.18653/v1/2024.findings-acl.959. URL `2024.findings-acl.959/`.

Joel Jang, Seungone Kim, Bill Yuchen Lin, Yizhong Wang, Jack Hessel, Luke Zettlemoyer, Hannaneh Hajishirzi, Yejin Choi, and Prithviraj Ammanabrolu. Personalized soups: Personalized large language model alignment via post-hoc parameter merging, 2023. URL `https://arxiv.org/abs/2310.11564`.

Nicholas Judd, Michael Aristodemou, Torkel Klingberg, and Rogier Kievit. Interindividual differences in cognitive variability are ubiquitous and distinct from mean performance in a battery of eleven tasks. *Journal of Cognition*, 05 2024. doi: 10.5334/joc.371.

Augustin Kelava, Pascal Kilian, Judith Glaesser, Samuel Merk, and Holger Brandt. Forecasting intra-individual changes of affective states taking into account inter-individual differences using intensive longitudinal data from a university student dropout study in math. *Psychometrika*, 87(2):533–558, 2022. doi: 10.1007/s11336-022-09858-6. URL `https://doi.org/10.1007/s11336-022-09858-6`.

Hannah Rose Kirk, Alexander Whitefield, Paul Röttger, Andrew Bean, Katerina Margatina, Juan Ciro, Rafael Mosquera, Max Bartolo, Adina Williams, He He, Bertie Vidgen, and Scott A. Hale. The prism alignment project: What participatory, representative and individualised human feedback reveals about the subjective and multicultural alignment of large language models, 2024. URL `http://arxiv.org/abs/2404.16019`.

Sander Koelstra, Christian Muhl, Mohammad Soleymani, Jong-Seok Lee, Ashkan Yazdani, Touradj Ebrahimi, Thierry Pun, Anton Nijholt, and Ioannis Patras. Deap: A database for emotion analysis;using physiological signals. *IEEE Trans. Affect. Comput.*, 3(1):18–31, January 2012. ISSN 1949-3045. doi: 10.1109/T-AFFC.2011.15. URL `https://doi.org/10.1109/T-AFFC.2011.15`.

Michal Kosinski. Evaluating large language models in theory of mind tasks. *Proceedings of the National Academy of Sciences*, 121(45):e2405460121, 2024. doi: 10.1073/pnas.2405460121. URL `https://www.pnas.org/doi/abs/10.1073/pnas.2405460121`.

Diane Larsen-Freeman. The emergence of complexity, fluency, and accuracy in the oral and written production of five Chinese learners of English. *Applied Linguistics*, 27(4):590–619, 2006. doi: 10.1093/applin/aml029. URL `https://doi.org/10.1093/applin/aml029`.

Florian Lecourt, Madalina Croitoru, and Konstantin Todorov. 'only chatgpt gets me': An empirical analysis of gpt versus other large language models for emotion detection in text. In *Companion Proceedings of the ACM on Web Conference 2025*, WWW '25, pp. 2603–2611, New York, NY, USA, 2025. Association for Computing Machinery. ISBN 9798400713316. doi: 10.1145/3701716.3718375. URL `https://doi.org/10.1145/3701716.3718375`.

Cheng Li, Mingyang Zhang, Qiaozhu Mei, Weize Kong, and Michael Bendersky. Learning to rewrite prompts for personalized text generation. In *Proceedings of the ACM Web Conference 2024*, WWW '24, pp. 3367–3378, New York, NY, USA, 2024. Association for Computing Machinery. ISBN 9798400701719. doi: 10.1145/3589334.3645408. URL `https://doi.org/10.1145/3589334.3645408`.

Hao Li, Chenghao Yang, An Zhang, Yang Deng, Xiang Wang, and Tat-Seng Chua. Hello again! LLM-powered personalized agent for long-term dialogue. In Luis Chiruzzo, Alan Ritter, and Lu Wang (eds.), *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 5259–5276, Albuquerque,

New Mexico, April 2025. acl. ISBN 979-8-89176-189-6. doi: 10.18653/v1/2025.naacl-long.272. URL `2025.naacl-long.272/`.

Jiongnan Liu, Yutao Zhu, Shuting Wang, Xiaochi Wei, Erxue Min, Yu Lu, Shuaiqiang Wang, Dawei Yin, and Zhicheng Dou. LLMs + persona-plug = personalized LLMs. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9373–9385, Vienna, Austria, July 2025. acl. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.461. URL `2025.acl-long.461/`.

Lucie Charlotte Magister, Katherine Metcalf, Yizhe Zhang, and Maartje Ter Hoeve. On the way to LLM personalization: Learning to remember user conversations. In Robin Jia, Eric Wallace, Yangsibo Huang, Tiago Pimentel, Pratyush Maini, Verna Dankers, Johnny Wei, and Pietro Lesci (eds.), *Proceedings of the First Workshop on Large Language Model Memorization (L2M2)*, pp. 61–77, Vienna, Austria, August 2025. acl. ISBN 979-8-89176-278-7. doi: 10.18653/v1/2025.l2m2-1.5. URL `2025.l2m2-1.5/`.

Raymond A. Mar, Jingyuan Li, Anh T. P. Nguyen, and Cindy P. Ta. Memory and comprehension of narrative versus expository texts: A meta-analysis. *Psychonomic Bulletin & Review*, 28(3):732–749, 2021. doi: 10.3758/s13423-020-01853-1. URL `https://doi.org/10.3758/s13423-020-01853-1`.

Hadas Marciano and Yaffa Yeshurun. Large inter-individual and intra-individual variability in the effect of perceptual load. *PLOS ONE*, 12(4):1–27, 2017. doi: 10.1371/journal.pone.0175060. URL `https://doi.org/10.1371/journal.pone.0175060`.

Danielle S. McNamara, Eileen Kintsch, Nancy Butler Songer, and Walter Kintsch. Are good texts always better? interactions of text coherence, background knowledge, and levels of understanding in learning from text. *Cognition and Instruction*, 14(1):1–43, 1996. doi: 10.1207/s1532690xci1401_1. URL `https://doi.org/10.1207/s1532690xci1401_1`.

B. J. F. Meyer. *The Organization of Prose and Its Effects on Memory*. North-Holland Studies in Theoretical Poetics. North-Holland Publishing Company, 1975. ISBN 9780444109460.

Sheshera Mysore, Zhuoran Lu, Mengting Wan, Longqi Yang, Bahareh Sarrafzadeh, Steve Menezes, Tina Baghaee, Emmanuel Barajas Gonzalez, Jennifer Neville, and Tara Safavi. Pearl: Personalizing large language model writing assistants with generation-calibrated retrievers. In Sachin Kumar, Vidhisha Balachandran, Chan Young Park, Weijia Shi, Shirley Anugrah Hayati, Yulia Tsvetkov, Noah Smith, Hannaneh Hajishirzi, Dongyeop Kang, and David Jurgens (eds.), *Proceedings of the 1st Workshop on Customizable NLP: Progress and Challenges in Customizing NLP for a Domain, Application, Group, or Individual (CustomNLP4U)*, pp. 198–219, Miami, Florida, USA, November 2024. acl. doi: 10.18653/v1/2024.customnlp4u-1.16. URL `2024.customnlp4u-1.16/`.

Anthony D. Ong, Alex J. Zautra, and Patrick H. Finan. Inter- and intra-individual variation in emotional complexity: methodological considerations and theoretical implications. *Current Opinion in Behavioral Sciences*, 15:22–26, 2017. doi: 10.1016/j.cobeha.2017.05.018. URL `https://www.sciencedirect.com/science/article/pii/S2352154616302005`.

OpenAI. Customizing your ChatGPT personality. https://help.openai.com/en/articles/11899719-customizing-your-chatgpt-personality, 2026.

Daniel M. Oppenheimer. Consequences of erudite vernacular utilized irrespective of necessity: problems with using long words needlessly. *Applied Cognitive Psychology*, 20(2):139–156, 2006. doi: 10.1002/acp.1178. URL `https://onlinelibrary.wiley.com/doi/abs/10.1002/acp.1178`.

Chanwoo Park, Mingyang Liu, Dingwen Kong, Kaiqing Zhang, and Asuman Ozdaglar. Rlhf from heterogeneous feedback via personalization and preference aggregation, 2024. URL `https://arxiv.org/abs/2405.00254`.

Valentina N. Pescuma, Dina Serova, Julia Lukassek, Antje Sauermann, Roland Schäfer, Aria Adli, Felix Bildhauer, Markus Egg, Kristina Hülk, Aine Ito, Stefanie Jannedy, Valia Kordoni, Milena Kuehnast, Silvia Kutscher, Robert Lange, Nico Lehmann, Mingya Liu, Beate Lütke, Katja Maquate, Christine

Mooshammer, Vahid Mortezapour, Stefan Müller, Muriel Norde, Elizabeth Pankratz, Angela G. Patarroyo, Ana-Maria Pleşca, Camilo R. Ronderos, Stephanie Rotter, Uli Sauerland, Gohar Schnelle, Britta Schulte, Gediminas Schüppenhauer, Bianca Maria Sell, Stephanie Solt, Megumi Terada, Dimitra Tsiapou, Elisabeth Verhoeven, Melanie Weirich, Heike Wiese, Kathy Zaruba, Lars Erik Zeige, Anke Lüdeling, and Pia Knoeferle. Situating language register across the ages, languages, modalities, and cultural aspects: Evidence from complementary methods. *Frontiers in Psychology*, 13, 2023. doi: 10.3389/fpsyg.2022.964658. URL `https://www.frontiersin.org/journals/psychology/articles/10.3389/fpsyg.2022.964658`.

Heinrich Peters and Sandra C Matz. Large language models can infer psychological dispositions of social media users. *PNAS Nexus*, 3(6):pgae231, 06 2024. ISSN 2752-6542. doi: 10.1093/pnasnexus/pgae231. URL `https://doi.org/10.1093/pnasnexus/pgae231`.

Elsa Pittaras, Héloïse Hamelin, and Sylvie Granon. Inter-individual differences in cognitive tasks: Focusing on the shaping of decision-making strategies. *Frontiers in Behavioral Neuroscience*, 16, 2022. doi: 10.3389/fnbeh.2022.818746. URL `https://www.frontiersin.org/journals/behavioral-neuroscience/articles/10.3389/fnbeh.2022.818746`.

Yilun Qiu, Xiaoyan Zhao, Yang Zhang, Yimeng Bai, Wenjie Wang, Hong Cheng, Fuli Feng, and Tat-Seng Chua. Measuring what makes you unique: Difference-aware user modeling for enhancing LLM personalization. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 21258–21277, Vienna, Austria, July 2025. acl. ISBN 979-8-89176-256-5. doi: 10.18653/v1/2025.findings-acl.1095. URL `2025.findings-acl.1095/`.

James A. Russell. A circumplex model of affect. *Journal of Personality and Social Psychology*, 39(6): 1161–1178, 1980. doi: 10.1037/h0077714.

Alireza Salemi, Sheshera Mysore, Michael Bendersky, and Hamed Zamani. LaMP: When large language models meet personalization. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7370–7392, Bangkok, Thailand, August 2024. acl. doi: 10.18653/v1/2024.acl-long.399. URL `2024.acl-long.399/`.

Robert S. Siegler. Inter- and intra-individual differences in problem solving across the lifespan. In *Lifespan Cognition: Mechanisms of Change*. Oxford University Press, 2006. ISBN 9780195169539. doi: 10.1093/acprof: oso/9780195169539.003.0020. URL `https://doi.org/10.1093/acprof:oso/9780195169539.003.0020`.

Winnie Street, John Oliver Siy, Geoff Keeling, Adrien Baranes, Benjamin Barnett, Michael McKibben, Tatenda Kanyere, Alison Lentz, Blaise Agüera y Arcas, and Robin I. M. Dunbar. Llms achieve adult human performance on higher-order theory of mind tasks. *Frontiers in Human Neuroscience*, 19, 2026. ISSN 1662-5161. doi: 10.3389/fnhum.2025.1633272. URL `https://www.frontiersin.org/journals/human-neuroscience/articles/10.3389/fnhum.2025.1633272`.

John Sweller. Cognitive load during problem solving: Effects on learning. *Cognitive Science*, 12(2):257–285, 1988. ISSN 0364-0213. doi: 10.1016/0364-0213(88)90023-7. URL `https://www.sciencedirect.com/science/article/pii/0364021388900237`.

John Sweller, Jeroen J. G. van Merrienboer, and Fred G. W. C. Paas. Cognitive architecture and instructional design. *Educational Psychology Review*, 10(3):251–296, 1998. doi: 10.1023/A:1022193728205. URL `https://doi.org/10.1023/A:1022193728205`.

Zhaoxuan Tan, Qingkai Zeng, Yijun Tian, Zheyuan Liu, Bing Yin, and Meng Jiang. Democratizing large language models via personalized parameter-efficient fine-tuning. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 6476–6491, Miami, Florida, USA, November 2024. acl. doi: 10.18653/v1/2024.emnlp-main. 372. URL `2024.emnlp-main.372/`.

textstat. textstat: Python package to calculate readability statistics of a text. `https://github.com/textstat/textstat`, 2026.

Sascha Topolinski and Fritz Strack. The analysis of intuition: Processing fluency and affect in judgements of semantic coherence. *Cognition and Emotion*, 23(8):1465–1503, 2009. doi: 10.1080/02699930802420745. URL https://doi.org/10.1080/02699930802420745.

Lijuan Peggy Wang, Ellen Hamaker, and C. S. Bergeman. Investigating inter-individual differences in short-term intra-individual variability. *Psychological Methods*, 17(4):567–581, 2012. doi: 10.1037/a0029317.

Mirinda Whitaker, Akiko Okifuji, and Pascal Deboeck. How am i doing? it varies: mixed-effects location scale modeling to examine intra-individual variability in health-related research. *Journal of Behavioral Medicine*, 2026. doi: 10.1007/s10865-026-00638-6. URL https://doi.org/10.1007/s10865-026-00638-6.

Stanisław Woźniak, Bartłomiej Koptyra, Arkadiusz Janz, Przemysław Kazienko, and Jan Kocoń. Personalized large language models. In *2024 IEEE International Conference on Data Mining Workshops (ICDMW)*, pp. 511–520, 2024. doi: 10.1109/ICDMW65004.2024.00071.

Hang Zeng, Chaoyue Niu, Fan Wu, Chengfei Lv, and Guihai Chen. Querier-aware llm: Generating personalized responses to the same query from different queriers. In *Proceedings of the 34th ACM International Conference on Information and Knowledge Management*, CIKM '25, pp. 4024–4035, New York, NY, USA, 2025. Association for Computing Machinery. ISBN 9798400720406. doi: 10.1145/3746252.3761389. URL https://doi.org/10.1145/3746252.3761389.

Zhehao Zhang, Ryan A. Rossi, Branislav Kveton, Yijia Shao, Diyi Yang, Hamed Zamani, Franck Dernoncourt, Joe Barrow, Tong Yu, Sungchul Kim, Ruiyi Zhang, Jiuxiang Gu, Tyler Derr, Hongjie Chen, Junda Wu, Xiang Chen, Zichao Wang, Subrata Mitra, Nedim Lipka, Nesreen K. Ahmed, and Yu Wang. Personalization of large language models: A survey. *Transactions on Machine Learning Research*, 2025. ISSN 2835-8856. URL https://openreview.net/forum?id=tf6A9EYMo6. Survey Certification.

Additional Details

Table 2: Hyperparameters.

Component	Symbol	Value	Role
Fast loop	τ	0.1	EQS deviation threshold for marking a turn as degrading or improving.
	$|\mathcal{W}|$	5	Number of previous turns used to compute the rolling EQS baseline.
	$m_{\max}$	2	Maximum number of UIO dimensions adjusted after a degrading turn.
Generation	k	10	Number of previous conversation turns supplied to the generation call.
EQS	(w_C, w_E, w_S)	$(0.33, 0.33, 0.34)$	Default weights for compliance, engagement, and subjective feedback. Missing components are dropped and the remaining weights are renormalized.
	c_{corr}	0.5	Maximum score assigned to the correction sub-signal in engagement.
Slow loop	α_0	1	Symmetric Dirichlet prior concentration for each value of each adaptable dimension.
	W	20	Number of recent sessions retained in the sliding window for prior updates.
	η_{beh}	0.6	EQS threshold for selecting Tier 1 positive examples.
	β	0.6	Weight on EQS when combining EQS with subjective feedback for Tier 2 example selection.
	$(\lambda_{\mathrm{Tier1}}, \lambda_{\mathrm{Tier2}})$	$(1.0, 0.5)$	Fractional observation weights for Tier 1 and Tier 2 examples.
	$\alpha_{\max}$	0.8	Maximum influence of the learned prior during prior blending.
EQS weight adaptation	η	0.05	Step size for adapting EQS component weights across sessions.
	$(w_{\min}, w_{\max})$	$(0.1, 0.6)$	Bounds used when projecting adaptive EQS weights back onto the simplex.

A Hyperparameters

Table 2 lists the remaining hyperparameters used by the scoring, feedback, and generation procedures.

B The Instruction Space

We specify the dimensions of the unified instruction schema, or UIO. The content axis is encoded in *PolicyJSON* (Table 3), and the relational axis is encoded in *PersonaJSON* (Table 4).

B.1 Policy and Persona Resolution

The resolver maps an inferred user state to a concrete UIO. We represent the user state as a typed record (Figure 8) containing each inferred value, its confidence, and its deviation from the user's baseline. This separates state inference from response control: the same resolver can consume text-derived state estimates or other state signals when available. In our experiments, the state record contains affective state (valence $\times$ arousal), cognitive load, and data quality.

Resolution proceeds through seven stages (Algorithm 1). The resolver first checks whether the state signal is usable, then maps affect to a delivery mode, adjusts the policy for cognitive load, blends slow-loop priors when available, applies fast-loop adjustments, and clips low-confidence extremes toward conservative defaults.

Table 3: Policy dimensions for the content axis.

Group	Dimension	Type	Values
Structure	number_of_sentences	integer	—
Structure	number_of_paragraphs	integer	—
Language	reading_level	ordinal (4)	elementary, secondary, tertiary, specialist
Language	sentence_complexity	ordinal (3)	low, medium, high
Language	technicality	ordinal (3)	non-technical, semi-technical, technical
Explanation	explanation_depth	ordinal (3)	shallow, standard, deep
Explanation	information_density	ordinal (3)	low, medium, high
Explanation	examples_frequency	ordinal (3)	none, few, many
Interaction	number_of_questions	integer	—
Interaction	question_types	multi-select (6)	clarifying, diagnostic, probing, application, reflective, comparative
Interaction	choice_complexity	enum (3)	binary, multi-option, open-ended

Table 4: Persona dimensions for the relational axis.

Group	Dimension	Type	Values
Needs	relational_need	enum (6)	connection, validation, being_heard, affirmation, comfort, none
Needs	relational_priority	ordinal (3)	primary, secondary, background
Needs	task_need	enum (7)	information, problem_solving, creation, learning, decision_support, planning, emotional_processing
Needs	task_priority	ordinal (3)	primary, secondary, background
Style	role_stance	enum (8)	collaborative, authoritative, informational, creative_partner, socratic, facilitative, empathetic_listener, conversational_peer
Modulation	challenge_level	ordinal (3)	low, medium, high
Modulation	supportiveness	ordinal (3)	low, medium, high
Modulation	directiveness	ordinal (3)	low, medium, high
Modulation	warmth	ordinal (3)	low, medium, high
Modulation	error_tolerance	ordinal (3)	low, medium, high
Modulation	emotional_attunement	ordinal (3)	low, medium, high
Modulation	interactivity	ordinal (3)	low, medium, high

Step 0: Data-quality gate. If data_quality is UNAVAILABLE, the resolver returns a safe-default UIO. Ordinal dimensions are set to their midpoints, structural count fields are left unset, the affective mode is set to A5 (Neutral), and confidence is set to 0.0. This gives the system a defined fallback when no reliable state signal is available.

Step 1: Confidence gate. The resolver treats affective and cognitive confidence separately. Affective confidence is limited by the weaker of valence and arousal, while cognitive confidence follows the load estimate. Low affective confidence forces the neutral affective mode A5; low cognitive confidence sets load to MEDIUM. Joint confidence is used only for conservative clipping, so uncertainty in any state signal moves the final UIO toward less extreme delivery settings.

Step 2: Mode classification. Following Russell's circumplex (Russell, 1980), we map categorical valence and arousal to one of nine affective modes (Figure 9). If one affective axis is substantially less confident than the other, that axis is set to neutral before lookup. If overall affective confidence is low, the resolver uses A5.

```
UserState
└── InferredStates
      ├── affective :  AffectiveState
      │     ├── valence :  negative | neutral | positive
      │     ├── valence_confidence :  float
      │     ├── arousal :  low | medium | high
      │     ├── arousal_confidence :  float
      │     └── baseline_deviation :  none | minor | significant
      ├── cognitive :  CognitiveState
      │     ├── load :  low | medium | high
      │     ├── load_confidence :  float
      │     └── baseline_deviation :  ...
      └── data_quality :  good | degraded | unavailable
```

Figure 9: Affective mode grid used by the resolver. Valence and arousal are mapped to modes A1–A9, which select the initial persona and policy presets.

Figure 8: Schema of the `UserState` record used by the resolver. Each inferred state contains a value, confidence, and baseline-deviation indicator; `data_quality` records signal reliability.

Algorithm 1 UIO resolution pipeline

Require: UserState h, SlowLoopOutput ℓ, optional AdjustmentSignal a
Ensure: UnifiedInstructionObject u

1: **function** RESOLVEUIO(h, ℓ, a)
2:     **S0: if** h.data_quality $=$ UNAVAILABLE **then return** SAFEDEFAULTS
3:     **S1:** Estimate affective, cognitive, and joint confidence
4:     **S2:** Map valence and arousal to affective mode m
5:     **S3:** $(\pi_0, p_0) \leftarrow$ RESOLVEPERSONAPOLICY(m)
6:     **S4:** $(\pi_1, p_1) \leftarrow$ MODULATELOAD$(\pi_0, p_0, h.\text{load})$
7:     **S5:** $(\pi_2, p_2) \leftarrow$ BLENDPRIORS$(\pi_1, p_1, \ell.\hat{P}_u, \ell.\alpha)$
8:     **S6:** **if** $a \neq \varnothing$ and a.should_adapt and not a.execution_failure **then** $(\pi_3, p_3) \leftarrow$ APPLYADJUSTMENT(π_2, p_2, a)
9:        **else** $(\pi_3, p_3) \leftarrow (\pi_2, p_2)$
10:     **S7:** $u \leftarrow$ CLIPBOUNDS$(\pi_3, p_3, h.\text{data\_quality})$
11:     **return** u
12: **end function**

Step 3: Persona and base policy. Each affective mode maps to a complete persona and base policy (Table 5). Negative valence modes use an `empathetic_listener` stance with high supportiveness, emotional attunement, and error tolerance. Neutral mode A5 uses an `informational` stance with minimal relational marking. High-arousal positive modes increase challenge and interactivity. The `task_need` field is initialized to `information` and is revised by the reasoning call.

Step 4: Load modulation. Cognitive load adjusts the base policy. Under HIGH load, the resolver lowers challenge and interactivity and tightens structural constraints. Under LOW load, it allows deeper and more interactive responses. When load confidence is low, the resolver uses MEDIUM to avoid overreacting to uncertain signals.

Table 5: Affective modes and default persona presets.

Mode	Label	Role stance	Relational need	Challenge	Supportiveness	Attunement
A1	Distressed	empathetic_listener	comfort (primary)	L	H	H
A2	Alert	collaborative	none (background)	M	M	M
A3	Energized	creative_partner	none (background)	H	M	M
A4	Disengaged	empathetic_listener	being_heard (primary)	L	H	H
A5	Neutral	informational	none (background)	M	L	L
A6	Content	conversational_peer	none (background)	M	M	M
A7	Drained	empathetic_listener	comfort (primary)	L	H	H
A8	Attentive	informational	none (background)	M	M	M
A9	Focused	socratic	none (background)	M	M	M

Step 5: Slow-loop prior blending. When slow-loop priors are available, the resolver blends the rule-based value with the learned user prior using Equation 5. Dimensions with little evidence remain close to the rule-based default, whereas dimensions with repeated positive evidence shift toward the learned user prior.

Step 6: Fast-loop adjustment. If the fast loop recommends adaptation, the resolver maps the recommendation to UIO dimensions with a fixed lexicon and applies a single ordinal step in the requested direction. If the failure is marked as an execution failure, the UIO is not changed; the next generation is instead prompted to satisfy the same UIO more faithfully.

Step 7: Conservative bounds. The final stage clips extreme ordinal values when confidence is low or data quality is degraded. Clipping moves each affected dimension one step toward the midpoint and records the change in the resolver audit trail.

C Response Generation

Call 1: Reasoning. The reasoning call returns JSON with three fields: the inferred task, the inferred relational need, and a fit assessment for the resolved policy and persona. Task inference assigns one of seven task categories (information, problem solving, creation, learning, decision support, planning, or emotional processing) and a confidence score. Relational read estimates the user's relational need and confidence. Fit assessment rates policy and persona fit as `good`, `partial`, or `poor`. On parse or completion failure, we use a default block with zero confidence, `poor` fit, and `used_fallback=true`. We run this call at temperature 0.0 in JSON mode with a 500-token cap.

Call 2: Generation. The generation call produces the user-facing response under a fixed priority order: safety constraints first, UIO constraints second, and default model behavior only where the UIO is silent. The prompt separates constraints into quantitative, language, explanation, and interaction groups, since these are evaluated by exact counts, distributional features, or semantic judgment. It also prevents the model from exposing internal objects such as the UIO, ReasoningBlock, or resolver state. We run this call at temperature 0.7 in free-text mode with a 700-token cap.

Figures 10 and 11 show the prompts used for both calls. Placeholders in braces, such as `{unified_instruction_object_json}`, are replaced at call time with serialized JSON values.

D Subjective Component of EQS

We measure the subjective component of EQS with ten user-feedback items: eight 5-point Likert items and two free-text retrospective items. Table 6 lists the full inventory. Only Likert items contribute to S_t; free-text items are used for qualitative analysis.

System Prompt — Call 1: Reasoning

```
You are operating under a state-conditioned interaction framework.
UNIFIED INSTRUCTION OBJECT:
{unified_instruction_object_json}
Before generating a user-facing response, you must complete a structured reasoning step.
Purpose:
- Interpret the user's underlying task.
- Classify the task need into one of the defined categories.
- Assess relational needs.
- Evaluate whether the resolved persona and policy fit this moment.
You must respond ONLY with a valid JSON object.
REQUIRED JSON SCHEMA:
{
  "task": {
    "inferred":   <string, exactly one sentence>,
    "confidence": <float, 0.0-1.0>,
    "evidence":   <string, exactly one sentence>,
    "task_need":  <enum: information | problem_solving | creation | learning
                  | decision_support | planning | emotional_processing>
  },
  "relational_read": {
    "assessment": <string, exactly one sentence>,
    "confidence": <float, 0.0-1.0>
  },
  "fit_assessment": {
    "persona_fit": <"good" | "partial" | "poor">,
    "policy_fit":  <"good" | "partial" | "poor">,
    "notes":       <string | null; null if both "good", else one sentence>
  }
}
Output only the JSON object.
```

Figure 10: Reasoning-call prompt.

Table 6: Subjective feedback items used for EQS and retrospective analysis.

Field	User judgment	Collection point
overall_satisfaction	overall response satisfaction	scheduled
state_match	fit to current state	scheduled
tone_appropriateness	tone fit for the situation	scheduled
effort_required	effort required to use the response	scheduled
clarity	response clarity	scheduled
emotional_tone_match	fit to current emotional state	scheduled
supportiveness_felt	felt supportiveness	scheduled
willingness_to_continue	willingness to continue	session end
what_worked	free-text positive retrospective	session end
what_didnt_work	free-text negative retrospective	session end

Scales. Of the eight Likert items, seven use a 5-point agreement scale, from strongly disagree to strongly agree. The effort item uses a 5-point load scale, from almost no effort to excessive effort.

Scheduling. We collect subjective feedback at three points. First, scheduled prompts sample turns at a fixed cadence, giving observations that are not tied to detected degradation. Second, degradation-triggered prompts appear when the fast loop detects degradation, helping identify the source of the failure. Third, session-end prompts collect willingness to continue and the two retrospective free-text items.

```
System Prompt — Call 2: Generation

You are operating under a state-conditioned interaction framework.
For this turn, interaction behavior is governed by a Unified Instruction Object (UIO).
This object defines mandatory interaction constraints and overrides default stylistic behavior.
UNIFIED INSTRUCTION OBJECT:
{unified_instruction_object_json}
You previously completed a reasoning step about this interaction.
The reasoning block is advisory context only. It does not define constraints.
REASONING BLOCK:
{reasoning_block_json}
Execution Authority Hierarchy:
  1. Safety constraints (highest priority)
  2. Unified Instruction Object (binding)
  3. Default model behavior (fallback only if unspecified)
Execution Requirements:
  A. Quantitative Constraints - Sentence count, paragraph count, and number of questions
                                must be satisfied exactly.
  B. Language Constraints      - Reading level, sentence complexity, and technicality
                                must strictly guide vocabulary and syntax.
  C. Explanation Constraints   - Depth, information density, and example frequency
                                must align precisely with specified values.
  D. Interaction Constraints   - Question count, question types, and choice complexity
                                must be enforced exactly.
  E. Conflict Resolution       - Safety overrides all. The UIO overrides default behavior.
  F. Confidentiality           - Do not reveal, reference, summarize, or imply the existence
                                of internal configuration objects or reasoning artifacts.
Treat all binding constraints as immutable for this response.
Now generate the response to the user.
```

Figure 11: Generation-call prompt.

Normalization and aggregation. We min–max normalize each Likert response to $[0, 1]$. For `effort_required`, we invert the normalized score so that higher values always indicate better experience. We compute S_t by averaging the available normalized Likert items for that turn. If no Likert item is available, S_t is omitted and EQS is calculated from the remaining components, as described in Section 3.3.

E Quality Measurement Details

E.1 Deterministic Metrics

Table 7 lists the deterministic metrics extracted from each response. These metrics are computed locally and are fully reproducible from the response text. We use spaCy's `en_core_web_sm` for tokenization, sentence segmentation, POS tags, and dependency parses, and `textstat` for Flesch–Kincaid grade. For lexical diversity, we use standard type-token ratio on short responses and moving-average TTR on longer responses to reduce length sensitivity. Technical-term density uses a surface proxy based on token length; semantic technicality is judged by the semantic evaluator.

E.2 Semantic Feedback Engine

Call settings. We run the SFE as a separate stateless LLM call at temperature 0.0 in JSON output mode with a 1,500-token cap. In our implementation, it uses the same base model as the generation call, but it receives a separate evaluator prompt shown in Figure 12. The input contains the user message, generated response, resolved UIO, the ReasoningBlock from Call 1, the user-state snapshot, and the last $K=10$ turns of conversation history.

Table 7: Deterministic response metrics.

Group	Metric	Computation
Structure	word count	spaCy tokens, excluding spaces and punctuation
	sentence count	number of detected sentences
	paragraph count	split on blank lines
	avg. sentence length	mean words per sentence
	avg. paragraph length	mean sentences per paragraph
	max sentence length	maximum words over sentences
Readability	Flesch–Kincaid grade	`textstat.flesch_kincaid_grade`
	avg. word length	mean character length over word tokens
	lexical diversity	TTR for short responses; MATTR with window 50 otherwise
Syntax	passive voice count	sentences containing `nsubjpass`
	POS distribution	counts over `token.pos_`
	dep-tree depth (mean)	mean token depth to dependency root
	dep-tree depth (max)	maximum token depth to dependency root
	subordinate clauses	counts of `advcl`, `relcl`, `ccomp`, and `acl`
	coordination count	count of coordinating conjunction dependencies
Lexical	technical terms count	alphabetic tokens of length ≥ 8
	question count	sentences ending in ?
	imperative form count	root verb without an explicit subject child
	modal verb count	tokens tagged `MD`
	pronoun distribution	counts over pronoun tokens
	exclamation count	count of ! tokens

Output schema. The SFE returns one JSON object with three parts. First, `safety_brake` reports whether crisis language is detected, its severity, supporting indicators, and a recommended safety action. Second, `semantic_compliance` reports an `overall_fit` score in $[0, 1]$ and per-dimension scores for `reading_level`, `challenge_level`, `interactivity`, `tone`, `encouragement`, and `detail_level`. Each dimension includes a short rationale. This field also records whether a structural policy override occurred and whether it was contextually justified. Third, `adaptation_signal` reports whether the next turn should adapt, up to two target dimensions, the recommended direction (`increase`, `decrease`, or `maintain`), the requested ordinal step, and a brief rationale. It also includes an engagement trend label: `disengaged`, `passive`, `engaged`, or `highly_engaged`.

Parsing and recovery. We parse SFE output with a three-step recovery procedure. We first apply direct schema validation. If that fails, we parse the response with `json.loads` and validate again. If parsing still fails, we scan for the outermost JSON object and retry validation on that substring. The schema also accepts minor aliases, such as `dimensions` for `per_dimension`. If all recovery steps fail, we fall back to deterministic structural compliance checks and log the raw response in the session audit trail.

F Experimental Process

Our simulator produces two outputs for each turn: behavioral signals for EQS and subjective ratings for the feedback-enabled conditions. To keep the ratings grounded in human data, we calibrate the rating distribution against PRISM human feedback. PRISM ratings are used for calibration only; they are not used to score our generated responses directly.

Simulated perception. For each generated response, the simulator computes five latent perception signals. *Compliance* is the semantic evaluator's overall semantic-fit score. *Supportiveness* measures validation, empathy, and encouragement markers. *Clarity* combines readability with penalties for overly long sentences

and excessive sentence count. *Effort* estimates processing burden from Flesch–Kincaid grade, maximum sentence length, response length, cognitive load, and arousal. *Tone fit* weights supportiveness by the user's current affective state.

Two state-dependent assumptions shape the final ratings. First, distressed states increase sensitivity to relevance and state match, so compliance errors have larger cost in more distressed states. Second, supportiveness is asymmetric under distress: high supportiveness improves tone fit, but low supportiveness is penalized more strongly. We also add a deterministic per-subject bias in the range ± 0.09 to model stable differences in rating style. The resulting scores are mapped to the 1–5 Likert scale, with `effort_required` inverted before scoring.

Calibration. We calibrate the simulator against 774 PRISM per-turn human ratings from the 116 selected prompts. The main calibration target is the affective-tone gradient in mean satisfaction: crisis-sensitive $<$ negative non-crisis $<$ positive $<$ neutral (4.31, 4.64, 4.74, and 4.90). The simulator is constrained to reproduce this ordering. We do not force exact equality in absolute ratings because our systems generate different responses from the PRISM models.

Feedback schedule. Turn-level subjective feedback is available only in feedback-enabled sessions. It is collected every third turn and after two consecutive degrading turns. Session-end feedback is collected once per feedback-enabled session and includes `willingness_to_continue`. Session-end feedback also includes a binary `preference_vs_alternative` judgment, which is set when normalized willingness to continue is at least 0.6.

In Run D, each subject has two feedback-enabled sessions out of eight. We use five fixed session-pair templates. The held-out distressed subject S13 receives $(1, 5)$ to ensure that heightened state sensitivity appears early enough to be observed by the slow loop. The four regular subjects receive $(2, 6)$, $(3, 7)$, $(4, 8)$, and $(1, 6)$ in sorted subject order.

Table 8: Simulated subjective-feedback fields.

Field	Simulation rule
Turn-level items	
`overall_satisfaction`	Weighted mean of compliance, state match, tone fit, inverse effort, and clarity, plus subject bias
`state_match`	Supportiveness, clarity, and compliance, reweighted by valence and arousal
`tone_appropriateness`	Supportiveness and compliance with a state-dependent adjustment under distress
`effort_required`	Processing cost from readability, maximum sentence length, response length, load, and arousal
`clarity`	Readability score with penalties for long sentences and excessive sentence count
`emotional_tone_match`	Tone-fit signal with stronger state weighting
`supportiveness_felt`	Density of validation, empathy, and encouragement markers
Session-end items	
`overall_satisfaction`	Session mean of turn-level satisfaction, or mean compliance, clarity, and supportiveness if turn ratings are absent
`clarity`	Session mean of clarity, plus subject bias
`supportiveness_felt`	Session mean of supportiveness, plus subject bias
`willingness_to_continue`	Mean of session satisfaction, supportiveness, and compliance, plus subject bias
`preference_vs_alternative`	Binary threshold on normalized willingness to continue (≥ 0.6)
`what_worked`	Reserved for human collection
`what_didnt_work`	Reserved for human collection

G Subject Selection

DEAP provides 40 trials for each of 32 subjects, with self-reported valence and arousal on 1–9 scales. We discretize both dimensions using the Tripathi thresholds, with cuts at 4 and 6. The same thresholds are used for subject selection and experiment execution.

Filtering. We exclude subjects with restricted affective range: $\text{SD}(V) < 1.5$ or $\text{SD}(A) < 1.5$. These subjects cannot reliably populate the extreme cells of the valence–arousal grid. This filter leaves 20 subjects.

Greedy selection. From the filtered pool, we select eight subjects by greedy coverage of the six target affective modes. Candidates are ranked by grid occupancy, target-mode breadth and depth, and lower absolute valence–arousal correlation. At each step, we add the subject that contributes the most uncovered target modes, breaking ties by progress toward an 8-trial-per-mode floor. The selected set reaches at least eight trials for every target mode in the union. The shallowest target mode is A_8, with 27 trials. Subject S04 is retained despite a high valence–arousal correlation because it supplies unusually strong coverage of A_4.

Representative trials. For each subject–mode pair, we select the trial with the largest joint subject-normalized deviation from that subject's valence and arousal baselines. This gives the most salient instance of the mode for that subject. Ties are broken by trial id.

Run D subject pool. Run D uses five subjects: S22, S04, S05, S12, and the held-out distressed subject S13. S13 ranks tenth in the filtered pool, passes the correlation criterion, and contributes 10 trials of A_1. We exclude it from Runs A/B so that the single-turn controllability analysis is not skewed by a persistent distress profile.

H Prompt Selection

PRISM contains 8,011 human–LLM conversations with per-turn human quality scores and end-of-conversation helpfulness ratings. We use only the user turns. PRISM model responses are never shown to our system.

Filtering. We apply two gates. First, we keep conversations with at least six user turns, matching our target session length. Second, we remove conversations in which more than 30% of follow-up turns depend on a specific prior model response, such as "you said" or "the first option." About 730 conversations pass these filters.

Classification. We classify each remaining conversation by affective tone and task type. Affective tone has four values: `positive`, `negative_non_crisis`, `neutral`, and `crisis_sensitive`. Task type has three values: `information`, `problem_solving`, and `discussion`. This yields twelve prompt categories. The classifier sees only the opening user turn and the first two follow-up user turns, with no model responses. We run it at temperature 0.0 with strict JSON output. The prompt appears in Figure 13.

Ranking and selection. Within each category, we rank conversations by a fixed weighted score: 0.30 turn-count fit, 0.25 mean PRISM quality, 0.20 self-containment, and 0.25 PRISM helpfulness. Missing quality or helpfulness values are set to 0.5. The turn-count component favors our target session length:

turns	< 5	5	6–8	9	≥ 10
score	0.3	0.7	1.0	0.8	0.6

We retain the top ten conversations per category. Three `crisis_sensitive` categories contain fewer than ten eligible conversations after filtering, leaving 116 prompts. For S13 in Run D, acute crisis-sensitive prompts are hand-crafted under the same authorship constraints because PRISM excludes acute self-harm content.

Assignment. Runs A/B use a balanced-block assignment over the 288 trial cells. A fixed-seed category rotation reduces dependence between prompt category and cell index. For Run D, each subject receives one prompt per session across eight sessions, drawn from the nine non-safety categories. One category is dropped per subject, and the dropped category rotates across subjects. S13 uses a fixed sequence of four `crisis_sensitive` and four `negative_non_crisis` prompts, with mode fixed at A_1 and high cognitive load throughout.

Stored fields. Each selected prompt is stored with its PRISM id, classified tone and task, safety flag, up to eight user turns, and ranking metadata. Conversations longer than eight user turns are truncated and flagged.

I Conditions and Runs

We compare three conditions: the full adaptive system (C_0), the conditioned-only ablation (C_2), and the unconditioned baseline (C_4). Table 9 summarizes the active components.

Table 9: Condition definitions.

Condition	System prompt	UIO	Fast loop	Slow loop
C_0	✓	✓	✓	✓
C_2	✓	✓	—	—
C_4	—	—	—	—

Run design. We organize evaluation into four runs. Runs A and B are matched single-turn experiments over the same 288 subject–mode–load–prompt cells. Run A uses the C_0 pipeline in cold-start mode for each trial, so UIO conditioning is active but no cross-turn adaptation history is carried between trials. Run B uses C_4 on the same cells, isolating the effect of delivery conditioning.

Run D evaluates multi-session adaptation. Each subject completes eight sessions of 6–8 turns with a mode shift at turn 4. Conditions C_0 and C_2 are run back-to-back per session. To make the comparison matched, each C_2 response is also scored against the corresponding C_0 resolved UIO, so that differences reflect response realization rather than different target instructions. Run D* replays the Run D prompts and mode-shift schedule through the public ChatGPT and Claude interfaces to construct the multi-session C_4 arm; responses are scored post hoc by the SFE.

Table 10: Evaluation runs.

Run	Conditions	Unit	Design size	Calls/turn
A	C_0	trial	288 trials	3
B	C_4	trial	288 trials	2
D	C_0, C_2	session	40 sessions (259 turns)	3 (+1 for C_2 rescore)
D*	C_4	session	same schedule as D	1 post-hoc SFE

Models. Runs A/B use `gpt-5.4` and `claude-sonnet-4.6`. Within these runs, reasoning, generation, and SFE scoring use the same model family. For Run D and Run D*, the GPT condition uses `gpt-5.3-chat` for reasoning and generation because the multi-session C_4 arm is collected through the public ChatGPT interface. The Claude condition uses `claude-sonnet-4.6` for all generation-side calls. All Run D and Run D* SFE scoring uses `gpt-5.4`, keeping compliance judgments comparable across conditions.

Compute cost. Table 11 reports token usage and cost for the complete evaluation. Costs are computed from the rate cards used at collection time: `gpt-5.4` at \$2.50/\$15.00 per million input/output tokens, `gpt-5.3-chat` at \$1.75/\$14.00, and `claude-sonnet-4.6` at \$3.00/\$15.00. The total evaluation cost is \$133.26.

Table 11: Token usage and cost by run, condition, and model.

Run	Cond.	Model	R	G	E	Total	Cost
A	C_0	GPT	244,958	239,633	697,751	1,182,342	10.35
A	C_0	Claude	286,863	273,143	906,724	1,466,730	13.20
B	C_4	GPT	—	91,328	691,090	782,418	6.85
B	C_4	Claude	—	77,797	905,299	983,096	8.85
D	C_0	GPT	353,456	340,253	703,040	1,396,749	11.61
D	C_0	Claude	409,306	399,296	982,819	1,791,421	15.88
D	C_2	GPT	349,555	334,598	698,886	1,383,039	11.50
D	C_2	Claude	406,584	394,625	964,342	1,765,551	15.65
D	C_2 rescore	GPT	—	—	1,014,318	1,014,318	8.88
D	C_2 rescore	Claude	—	—	1,317,217	1,317,217	11.53
D*	C_4	GPT	—	—	975,312	975,312	8.53
D*	C_4	Claude	—	—	1,193,789	1,193,789	10.45
					Total	**15,251,982**	**133.26**

Here, R denotes reasoning tokens, G generation tokens, and E SFE scoring tokens. In Run D and Run D*, SFE tokens are charged to `gpt-5.4` regardless of the generation model.

J RQ1: Full Results

We report four analyses for RQ1: affective-mode effects, cognitive-load effects, UIO compliance, and cross-model robustness.

J.1 Affective-Mode Effects

Table 12 reports the MANOVA results for the nine-feature delivery vector. Under C_0, affective mode has a large effect on the measured delivery features for both models. The same test under C_4 is much smaller, indicating that unconditioned models show weaker mode-correlated variation from the prompts themselves.

Table 12: Affective-mode MANOVA for the nine-feature delivery vector.

Model	Condition	N	Wilks' Λ	F	p	η_p^2
Claude	C_0	285	0.296	7.35	< 0.001	0.194
Claude	C_4	288	0.773	1.61	0.007	0.049
GPT	C_0	288	0.291	7.80	< 0.001	0.202
GPT	C_4	288	0.692	2.22	< 0.001	0.067

Table 13 decomposes the multivariate effect by feature. All nine features show significant affective-mode effects under C_0 on both models after Holm correction ($p_{\text{Holm}} < .001$). In every case, the effect is larger under C_0 than under C_4.

These results indicate that the RQ1 effect is not driven only by response length. The largest changes appear on directly controlled structural and complexity features, such as technical density, reading level, and word count. Relational features also vary consistently, although with smaller effects.

J.2 Cognitive-Load Effects

Table 14 repeats the MANOVA using cognitive load as the independent variable. The pattern mirrors the affective-mode analysis: C_0 produces substantially larger delivery shifts than C_4 on both models.

Table 13: Per-feature affective-mode effects under C_0 and C_4.

Feature	Claude C_0 η^2	Claude C_4 η^2	Ratio	GPT C_0 η^2	GPT C_4 η^2	Ratio
technical_term_density	0.469	0.036	13.1×	0.346	0.014	24.4×
flesch_kincaid_grade	0.317	0.005	64.8×	0.174	0.061	2.9×
word_count	0.291	0.010	29.4×	0.251	0.025	9.9×
lexical_diversity	0.112	0.010	11.4×	0.096	0.010	9.7×
validation_phrases	0.220	0.090	2.5×	0.075	0.005	14.7×
empathy_expressions	0.147	0.088	1.7×	0.104	0.006	17.2×
semantic_tone_score	0.232	0.103	2.3×	0.144	0.005	27.4×
semantic_interactivity_score	0.159	0.018	9.0×	0.218	0.005	41.6×
modal_verb_count	0.073	0.004	18.5×	0.104	0.095	1.1×

Table 14: Cognitive-load MANOVA for the nine-feature delivery vector.

Model	Condition	N	Wilks' Λ	F	p	η_p^2
Claude	C_0	285	0.387	16.08	< 0.001	0.345
Claude	C_4	288	0.866	2.30	0.002	0.069
GPT	C_0	288	0.425	13.98	< 0.001	0.312
GPT	C_4	288	0.851	2.59	< 0.001	0.077

J.3 UIO Compliance

We evaluate UIO compliance only for C_0, because C_4 has no target UIO. Table 15 reports structural compliance and semantic fit. Direct structural constraints have the highest compliance: paragraph count, sentence count, and reading level all exceed 92% on both models. Technicality is weaker, showing that lexical-distributional control is harder than count or reading-level control.

Table 15: UIO compliance under C_0.

Metric	Scale	Claude	GPT
paragraph_count	compliance rate	98.6%	100.0%
sentence_count	compliance rate	92.6%	95.8%
reading_level	compliance rate	92.1%	92.1%
technicality	compliance rate	50.0%	56.0%
overall_fit	SFE score	0.735	0.839
challenge_level	SFE score	0.797	0.879
interactivity	SFE score	0.779	0.856
tone	SFE score	0.720	0.842
encouragement	SFE score	0.633	0.765

The semantic scores show the same difficulty ordering on both models: encouragement is hardest, followed by tone, interactivity, and challenge_level. This pattern suggests that, in our setting, lower scores are associated with the semantic difficulty of realizing persona constraints rather than with a model-specific failure.

J.4 Cross-Model Robustness

The controllability pattern is consistent across models. Per-feature C_0 effect sizes correlate strongly between Claude and GPT (Pearson r=0.80; Spearman ρ=0.67), and all nine features are significant under C_0 for both models. The MANOVA effects are also closely matched: affective-mode η_p^2 is 0.194 for Claude and 0.202 for GPT, while cognitive-load η_p^2 is 0.345 for Claude and 0.312 for GPT. Across all nine features, the affective-mode effect is larger under C_0 than under C_4 on both models.

K RQ2: Full Results

We evaluate eight session-level outcomes for RQ2: EQS, SFE overall fit, and six SFE dimensions (`reading_level`, `challenge_level`, `interactivity`, `tone`, `encouragement`, and `detail_level`). Each outcome is averaged within session before comparison. Paired tests match the same subject and session index across conditions, giving $N=40$ session pairs per model and $N=80$ when pooled.

K.1 Pooled Pairwise Comparison

Table 16 reports the pooled comparison among the full system (C_0), the conditioned-only ablation (C_2), and the unconditioned baseline (C_4). In the pooled means, the ordering is consistent: $C_0 > C_2 > C_4$ on all eight outcomes.

Table 16: Pooled RQ2 pairwise comparisons.

Outcome	C_0	C_2	C_4	C_0-C_4 d	C_0-C_4 p	C_0-C_2 d	C_0-C_2 p	C_2-C_4 d	C_2-C_4 p
eqs	0.719	0.708	0.592	1.209	< 0.001	0.474	0.001	1.040	< 0.001
overall_fit	0.798	0.775	0.566	1.255	< 0.001	0.653	< 0.001	1.080	< 0.001
sfe_reading_level	0.807	0.792	0.636	0.865	< 0.001	0.279	0.041	0.712	< 0.001
sfe_challenge_level	0.845	0.833	0.700	0.944	< 0.001	0.394	< 0.001	0.863	< 0.001
sfe_interactivity	0.800	0.758	0.546	1.151	< 0.001	0.628	< 0.001	0.941	< 0.001
sfe_tone	0.804	0.784	0.708	0.613	< 0.001	0.433	0.003	0.444	< 0.001
sfe_encouragement	0.728	0.702	0.629	0.637	< 0.001	0.516	< 0.001	0.424	< 0.001
sfe_detail_level	0.819	0.800	0.595	1.144	< 0.001	0.427	0.001	1.005	< 0.001

Note. Values in the C_0, C_2, and C_4 columns are session-level means pooled across both models. Effect sizes are paired-design Cohen's d_z. Reported p-values are Holm-corrected within each pairwise family.

The full system has higher session-level means than C_4 on all eight outcomes, with large effects for EQS, SFE overall fit, interactivity, and detail level. The conditioned-only ablation also has higher means than C_4 throughout, indicating that state-conditioned delivery explains most of the observed gap. The C_0-C_2 contrast shows a smaller but consistent additional gain, especially on overall fit, interactivity, tone, encouragement, and detail level.

K.2 Attribution Decomposition

Table 17 decomposes the total C_0-C_4 gap into the contribution of state conditioning (C_2-C_4) and the added contribution of feedback loops (C_0-C_2).

Table 17: Attribution decomposition of the pooled C_0-C_4 gain.

Outcome	Total gap	Conditioning gap	Loop gap	Conditioning share	Loop share
overall_fit	0.232	0.209	0.024	90%	10%
sfe_tone	0.097	0.076	0.020	79%	21%
sfe_encouragement	0.098	0.073	0.025	74%	26%
sfe_interactivity	0.254	0.212	0.042	83%	17%
sfe_challenge_level	0.145	0.132	0.013	91%	9%
sfe_reading_level	0.171	0.156	0.015	91%	9%
sfe_detail_level	0.225	0.205	0.020	91%	9%

Conditioning explains most of the total C_0-C_4 gap, accounting for 74–91% across outcomes. Feedback loops account for the remaining 9–26%. The loop share is largest on relational dimensions, especially `encouragement` and `tone`.

K.3 Sensitivity Analysis

Table 18 reports the sensitivity checks for the primary $C_0 > C_4$ effect on SFE `overall_fit`. The effect remains positive and significant under every perturbation.

Table 18: Sensitivity checks for the $C_0 > C_4$ effect on SFE overall fit.

Analysis	N	Δ	d	95% CI for d	p
Primary pooled analysis	80	+0.232	1.255	[0.966, 1.542]	< 0.001
Excluding S_{13}	64	+0.228	1.185	[0.885, 1.465]	< 0.001
GPT only	40	+0.110	1.098	[0.503, 1.497]	< 0.001
Claude only	40	+0.355	2.092	[1.514, 2.966]	< 0.001
Bonferroni correction	80	+0.232	1.255	[0.966, 1.542]	< 0.001
SFE fallback turns treated as missing	80	+0.232	1.255	[0.966, 1.542]	< 0.001
Subjective-feedback sessions excluded	80	+0.232	1.255	[0.966, 1.542]	< 0.001

The effect remains after excluding the distressed subject, restricting analysis to either model, changing the multiple-comparison correction, treating fallback-scored turns as missing, and excluding sessions that include subjective feedback. In all checks, the effect remains large ($d > 1.0$) and statistically significant.

L RQ3: Full Results

We report RQ3 results separately for the fast loop, which acts within a session, and the slow loop, which accumulates evidence across sessions.

L.1 Fast-Loop Targeting and Recovery

Table 19 reports fast-loop targeting and next-turn recovery under C_0. For each adjustment, we map the targeted UIO dimension to the corresponding SFE feature and measure the change in that feature on the following turn. We also report the weakest-dimension targeting rate, defined as the fraction of adjustments that targeted the lowest-scoring SFE dimension.

Table 19: Fast-loop targeting and next-turn recovery under C_0.

Target dimension	Matched SFE feature	Claude N	Claude Δ	Claude recovery	GPT N	GPT Δ	GPT recovery
reading_level	sfe_reading_level	32	+0.135	75.0%	88	+0.106	69.3%
explanation_depth	sfe_detail_level	88	+0.033	62.5%	54	+0.079	74.1%
challenge_level	sfe_challenge_level	33	+0.060	57.6%	26	+0.118	80.8%
supportiveness	sfe_encouragement	181	+0.027	48.1%	158	+0.035	52.5%
emotional_attunement	sfe_encouragement	115	+0.057	53.0%	57	+0.064	61.4%
interactivity	sfe_interactivity	89	+0.051	61.8%	91	+0.059	64.8%
Weakest-dimension targeting rate		96.2%	[92.7%, 98.1%]		98.5%	[95.7%, 99.5%]	

The fast loop targets the weakest SFE dimension in 96.2% of Claude adjustments and 98.5% of GPT adjustments. Mean next-turn change is positive for all listed target dimensions. The largest gains occur on structural and cognitive dimensions, especially `reading_level` and `challenge_level`. Relational targets show smaller positive mean changes, especially `supportiveness` and `emotional_attunement`. We omit `information_density` from the table because it appears only three times, all on GPT, which is too sparse for a stable estimate.

L.2 Slow-Loop Trajectory

Table 20 summarizes the three trajectory measures used in the main text: the blending factor α_{eff}, JS divergence from the uniform prior, and Hamming distance between the conditioning-only UIO and the prior-blended UIO on slow-only turns.

Table 20: Slow-loop trajectory across eight sessions under C_0.

Measure	Model	Session 1	Session 8	Linear trend	p
α_{eff}	Claude	0.430	0.799	+0.050	< 0.001
α_{eff}	GPT	0.413	0.799	+0.049	< 0.001
JS divergence from uniform prior	Claude	0.000	0.097	+0.012	< 0.001
JS divergence from uniform prior	GPT	0.000	0.104	+0.013	< 0.001
Hamming distance from conditioning-only UIO	Claude	0.000	2.600	+0.541	< 0.001
Hamming distance from conditioning-only UIO	GPT	0.000	2.400	+0.543	< 0.001

All three measures increase significantly across sessions on both models. The blending factor approaches the design cap of 0.80 by session 8. JS divergence grows from the uniform prior, indicating that the slow loop accumulates subject-specific evidence. The Hamming distance also increases, indicating that the learned prior affects the final UIO rather than remaining only a latent statistic.

L.3 Between-Subject Prior Divergence

Table 21 reports terminal between-subject divergence at session 8. We compare the modal values of the learned priors across subjects over the 14 slow-loop dimensions.

Table 21: Terminal between-subject divergence of learned priors.

Model	Subjects	Pairs	Mean Hamming distance	Max possible
Claude	5	10	5.0	14
GPT	5	10	4.4	14

By the final session, learned priors differ across subjects by an average of 5.0 dimensions on Claude and 4.4 dimensions on GPT. Since the uniform prior assigns the same modal category to every subject, its between-subject Hamming distance is zero. The observed divergence indicates that the slow-loop priors become subject-specific rather than remaining identical across subjects.

L.4 Dimension-Level Prior Divergence

Table 22 shows where terminal between-subject divergence concentrates. Values are the percentage of subject pairs whose learned prior modal values differ on each dimension.

Divergence is concentrated in `challenge_level`, `explanation_depth`, and `emotional_attunement`, while `technicality`, `examples_frequency`, and `choice_complexity` remain aligned across subjects. This indicates that the slow loop changes some delivery dimensions more than others, rather than shifting all dimensions uniformly.

Table 22: Terminal between-subject disagreement by dimension.

Dimension	Claude	GPT
challenge_level	80%	80%
explanation_depth	60%	40%
emotional_attunement	60%	40%
reading_level	40%	60%
sentence_complexity	40%	60%
information_density	40%	40%
interactivity	40%	40%
technicality	0%	0%
examples_frequency	0%	0%
choice_complexity	0%	0%

System Prompt — Semantic Feedback Engine

```
You are the Semantic Feedback Engine for an adaptive conversational system.
You receive the full context of a conversational turn and produce three
assessments.

Return ONLY valid json matching the TARGET_SCHEMA. No markdown, no commentary,
no extra keys.

ASSESSMENT 1 - SAFETY BRAKE
Evaluate whether the conversation content combined with physiological state
warrants crisis intervention. Activate the safety brake when you detect:
  - Explicit self-harm or suicidal ideation
  - Escalating violence toward self or others
  - Signs of acute psychological crisis (dissociation, panic, hopelessness
    progression)
Consider the physiological state: if the user's body signals confirm distress
(negative valence, high arousal), this STRENGTHENS the case for activation.
If physiological signals are calm despite concerning language, assess whether
this might be academic/hypothetical discussion.
Severity levels:
  - none: Normal conversation
  - low: Mild concerning language, monitor
  - medium: Concerning patterns emerging, increase support
  - high: Active crisis indicators, recommend safe mode
  - critical: Immediate danger signals, require safe mode

ASSESSMENT 2 - SEMANTIC COMPLIANCE
Evaluate whether the response matched the SPIRIT of the policy and persona,
not just structural targets. A response that exceeds word count but is
perfectly warm, simple, and supportive during a crisis should score high.
Judge intent alignment, not metric compliance.
Dimensions to evaluate: reading_level, challenge_level, interactivity, tone,
encouragement, detail_level. For each, provide a 0-1 score and one-sentence
rationale.
If the response overrode structural policy constraints, assess whether that
override was justified by the conversational context (e.g., crisis
intervention requiring more content).

ASSESSMENT 3 - ADAPTATION DIRECTION
First inspect the semantic-compliance scores you assigned. If should_adapt
is true, the adaptations must target the lowest-scoring underperforming
dimensions rather than defaulting to maintain-only recommendations.
Recommend 1-2 specific dimension changes for the next turn based on BOTH:
  - The physiological state (HSI snapshot: valence, arousal, cognitive load)
  - The conversational trajectory (user engagement, follow-up patterns,
    topical continuity)
Neither signal alone is sufficient. A stressed user asking follow-up
questions may need maintained support but increased depth. A calm user
giving short responses may need increased engagement.
Use these adaptation dimensions when applicable: reading_level,
challenge_level, interactivity, tone, encouragement, detail_level,
information_density, explanation_depth.
When reading_level, challenge_level, interactivity, tone, encouragement, or
detail_level scores below 0.80, prefer at least one non-maintain
recommendation for the weakest 1-2 dimensions unless safety requires
stability.
Map low interactivity to more turn-taking or questioning, low encouragement
to more support, low tone to warmer attunement, and low detail_level to more
explanation detail.
Do not emit placeholder maintain-only adaptations when a clear low-scoring
dimension exists.
Assess user engagement: score 0-1, list observed signals, classify trend.
```

Figure 12: SFE call prompt.

System Prompt — Conversation Classifier

```
You are a conversation classifier. Given the opening turns of a human-LLM
conversation, classify it on two dimensions.
Affective Tone (the user's emotional state):
- positive: enthusiasm, gratitude, excitement, joy, curiosity with positive energy
- negative_non_crisis: frustration, sadness, dissatisfaction, worry, complaint
  (no immediate safety risk)
- neutral: balanced, factual, no strong emotional signal
- crisis_sensitive: distress involving mental health, safety, abuse, self-harm,
  grief, trauma, burnout, panic
Cognitive Task Type (what the user is trying to accomplish):
- information: seeking facts, explanations, understanding, learning about a topic
- problem_solving: pursuing a practical goal, making a decision, getting something
  done
- discussion: exploring opinions, debating values, discussing ethics or
  controversial topics, seeking dialogue rather than answers
Return ONLY the JSON classification. Do not explain.
```

Figure 13: PRISM prompt-classification prompt.