Online Selective Classification with Limited Feedback

Abstract

Motivated by applications to resource-limited and safety-critical domains, we study selective classification in the online learning model, wherein a predictor may abstain from classifying an instance. For example, this may model an adaptive decision to invoke more resources on this instance. Two salient aspects of the setting we consider are that the data may be non-realisable, due to which abstention may be a valid long-term action, and that feedback is only received when the learner abstains, which models the fact that reliable labels are only available when the resource intensive processing is invoked.

Within this framework, we explore strategies that make few mistakes, while not abstaining too many times more than the best-in-hindsight error-free classifier from a given class. That is, the one that makes no mistakes, while abstaining the fewest number of times. We construct simple versioning-based schemes for any $\mu \in (0, 1]$, that make most T^μ mistakes while incurring $\tilde{O}(T^{1-\mu})$ excess abstention against adaptive adversaries. We further show that this dependence on T is tight, and provide illustrative experiments on realistic datasets.

1 Introduction

Consider a low-power or battery-limited edge device, such as a sensor or a smart-speaker that receives a stream of classification requests. Due to the resource limitations, such a device cannot implement modern models that are needed for accurate decisions. Instead the device has access (e.g. via an internet connection) to an accurate but resource-intensive model implemented on a cloud server, and may send queries to the cloud server in order to retain accuracy. Of course, this incurs costs such as latency and battery drain due to communication. The ideal operation of such a device should thus be to learn a rule that classifies 'easy' instances locally, while sending harder ones to the cloud, thus maintaining accuracy whilst minimising the net resource consumption [Xu+14; NS17].

Selective classification [Cho57; Cho70] is a classical paradigm of relevance to such settings. The setup allows a predictor to abstain from classifying some instances (without incurring a mistake). This abstention models adaptive decisions to invoke more resource-intensive methods on subtle cases, like in the above example. The solution concept is relevant widely - for instance, it is relevant to adaptively recommending further (and costly) tests rather than offering a diagnosis in a medical scenario, or to recommending a human review instead of an alarm-or-not decision in security contexts. Two aspects of such settings are of particular interest to us. Firstly, the cheaper methods are typically not sufficient to realise the true labels, due to which abstention may be a long-term necessity. Secondly, a-priori reliable labels can only be obtained by invoking the resource intensive option, and thus feedback on whether a non-abstaining decision was correct is unavailable.

We propose online selective classification, with an emphasis on ensuring very few mistakes, to account for the need for very accurate decisions. Concretely, an adversary sequentially produces contexts and labels (X_t, Y_t), and the learner uses the contexts to produce a decision $\hat{Y}_t$ that may either be one of K classes, or an abstention, which we represent as $\perp$. Feedback in the form of Y_t is

provided if and only if $\widehat{Y}_t = \bot$, and the learner is said to incur a mistake if $\widehat{Y}_t$ was non-abstaining and did not equal Y_t.

With the emphasis on controlling the total number of mistakes, we study regrets achievable when compared to the behaviour of the best-in-hindsight error-free selective classifier from a given class - that is, one that makes no mistakes, while abstaining the fewest number of times. Notice that our situation is non-realisable, and therefore this competitor may abstain in the long-run. The two metrics of importance here are the number of mistakes the learner makes, and its excess abstention over this competitor. An effective learner must control both abstention and mistakes, and it is not enough to make one small, e.g. a learner that makes a lot of mistakes but incurs a very negative excess abstention is no good. This *simultaneous* control of two regrets raises particular challenges.

We construct simple schemes that, when competing against finite classes, can simultaneously guarantee $O(T^\mu)$ mistakes and $O(T^{1-\mu})$ excess abstentions against adaptive adversaries (for any $\mu \in [0, 1]$), and further show that the rates of these regrets are Pareto-tight[OR94]. We further show that against stochastic adversaries, the same rates can be attained with improved dependence of the regret bounds on the size of the class, and we also describe schemes that enjoy similar improvements against adaptive adversaries, but at the cost of the T-dependence of the regret bounds. The main schemes randomly abstain at a given rate in order to gain information, and playing $\widehat{Y}_t$ consistent with the 'version space' of classifiers that have not been observed to make mistakes. For the adversarial case, the analysis of the scheme relies on a new 'adversarial uniform law of large numbers'(ALLN) to argue that such methods cannot incur too many mistakes. This ALLN critically utilises a self-normalised martingale concentration bound, which further yields an adaptive continuous approximation guarantee for the Bernoulli-sampling scheme in the sense of Ben-Eliezer & Yogev [BY20; Alo+21]. This theoretical exploration is complemented by illustrative experiments that implement our scheme on two benchmark datasets.

1.1 Related Work

Selective classification has been well studied in the batch setting, and many theoretical and methodological results have appeared [e.g. HW06; BW08; EW10; WE11; KKM12; CDM16; Lei14; GE19; GKS21]. These batch results do not have strong implications for the online setting.

Cortes et al. have studied selective classification in the online setting [Cor+18], but with two differences from our setting. Firstly, rather than individually controlling mistakes and abstentions, the regret is defined according to the Chow loss, which adds up the number of mistakes and c times the number of abstentions, where c is a fixed cost parameter. Secondly (and more importantly) it is assumed that feedback is provided only when the learner *does not* abstain, rather than only when it does. This difference arises from the underlying situations being modelled - Cortes et al. view the abstention as a decision given to a user in which case no feedback is forthcoming, while we view it as a decision to invoke further processing. Both of the scenarios are reasonable, and so both of these explorations are valid, however it is unclear what implications one set of results have for the other.

A similar decision and feedback model as ours was proposed by Li et al. in the 'knows what it knows' (KWIK) framework [Li+11], but restricted to the setting where the labels are known to essentially be realised by a given class[1], whereas our interest is in the situation where this data cannot be represented in such a way. Our work thus generalises the KWIK setting to non-realisable data. Notice that in the realisable setting, the competitor never abstains, whereas in the non-realisable case we consider, the competitor may abstain in the long-run. Further, while in the realisable setting, a single abstention at an instance x determines what value should be played there in the long run, this is no longer the case in the non-realisable setting, because the labels may be noisy. While [ZC16; SZB10; DZ13] have studied a variant of the KWIK framework, allowing for non-realisability and tradeoffs between mistakes and abstentions, these works, unlike us, require full-feedback to be available whether or not the learner abstains.

Due to the limited feedback, our setting is related to partial-monitoring [LS20, Ch. 37]. Viewing actions as choices over functions, our setting has feedback graphs [MS11] that connect abstaining actions to every other action and themselves. The novelty with respect to partial-monitoring arises from the fact that we individually control two notions of losses, rather than a single one. It's unclear

---

[1]The weakest setting we have seen studied is where Y_t is a noisy observation of $h(X_t)$ for independent noise, and where h lies in a class known to the learner.

how to apply the generic partial-monitoring setup to this situation - indeed, naïvely, our game is only weakly observable in the sense of Alon et al.[Alo+15], and one would expect $\Omega(T^{2/3})$ regrets, while we can control both mistakes and excess abstention to $\tilde{O}(\sqrt{T})$. A limited feedback setting where two 'losses' *are* individually controlled is label-efficient prediction [CLS05], where a learner must query in order to get feedback. However, in our setting, abstentions are both a way to gather feedback, and also necessary to prevent mistakes. That is, our competitor may abstain regularly, but makes few mistakes, while in this prior work the competitor does not abstain, but may make many mistakes. The resulting scenario is both qualitatively and quantitatively distinct, e.g. in label-efficient prediction, the smallest symmetric rate of number of queries and excess mistakes is again $\Theta(T^{2/3})$.

2 Setting, and Problem Formulation

Setup Let $\mathcal{X}$ be a feature space, $\mathcal{Y}$ a finite set of labels, and $\mathcal{F}$ a finite class of selective classifiers, which are $\mathcal{Y} \cup \{\bot\}$ valued. For simplicity, we assume that $\mathcal{F}$ contains the all abstaining classifier (i.e. the function $f_\bot$ such that $\forall x, f_\bot(x) = \bot$). We will denote $|\mathcal{F}| = N$. The setting may be described as a game between a learner and an adversary (or more prosaically, a data generating mechanism) proceeding in T rounds. Also for simplicity, we will assume that T is known to both the learner and the adversary in advance. The objects in this game are the context process, $X_t \in \mathcal{X}$, the label process $Y_t \in \mathcal{Y}$, the action process $\widehat{Y}_t \in \mathcal{Y} \cup \{\bot\}$ and the feedback process $Z_t \in \mathcal{Y} \cup \{*\}$, where $* \notin \mathcal{Y}$ is a trivial symbol. The information sets of the adversary and learner up to the tth round are respectively $\mathscr{H}_{t-1}^{\mathfrak{A}} := \{(X_s, Y_s, \widehat{Y}_s) : s < t\}$, and $\mathscr{H}_{t-1}^{\mathfrak{L}} := \{(X_s, \widehat{Y}_s, Z_s) : s < t\}$.

The Game For each round $t \in [1 : T]$, the adversary produces a context and a label (X_t, Y_t) on the basis its history $\mathscr{H}_{t-1}^{\mathfrak{A}}$. The learner observes only the context, X_t, and on the basis of this and its history $\mathscr{H}_{t-1}^{\mathfrak{L}}$, produces an action $\widehat{Y}_t$. We will say that this action is an abstention if $\widehat{Y}_t = \bot$, and that it is a prediction otherwise. If the action was an abstention, set $Z_t = Y_t$, and otherwise to $*$. The learner then observes Z_t, and the round concludes. Notice that since Z_t is a deterministic function of Y_t and $\widehat{Y}_t$, and since the adversary observes both, $\mathscr{H}_{t-1}^{\mathfrak{L}}$ can be deterministically generated from $\mathscr{H}_{t-1}^{\mathfrak{A}}$. Due to the same reason, $\widehat{Y}_t$ and Y_t are conditionally independent given $(X_t, \mathscr{H}_{t-1}^{\mathfrak{A}})$.

Adversaries are characterised by a sequence of conditional laws on (X_t, Y_t) given $\mathscr{H}_{t-1}^{\mathfrak{A}}$ (and $T, \mathcal{F}$). In the following we will explicitly consider two classes of such laws:
• Stochastic Adversary: (X_t, Y_t) are drawn according to a fixed law, P, unknown to the learner, independently of $\mathscr{H}_{t-1}^{\mathfrak{A}}$.
• Adaptive Adversary: (X_t, Y_t) are arbitrary random variables with $\mathscr{H}_{t-1}^{\mathfrak{A}}$-measurable laws.
We will denote a generic class of adversaries as $\mathscr{C}$.

Performance Metrics The two principal quantities of interest are the number of mistakes made by the learner, and the number of times it has abstained. We will denote these as

$$M_t := \sum_{s < t} \mathbb{1}\{\widehat{Y}_t \notin \{\bot, Y_t\}\}, \quad and \quad A_t := \sum_{s < t} \mathbb{1}\{\widehat{Y}_t = \bot\}.$$

As previously discussed, the performance of a learner is measured in terms of regret with respect to the best-in-hindsight abstaining classifier from $\mathcal{F}$ that makes no mistakes, that is

$$f^* \in \arg\min\left\{\sum_{t < T} \mathbb{1}\{f(X_t) = \bot\} : f \in \mathcal{F}, \sum_{t < T} \mathbb{1}\{f(X_t) \notin \{\bot, Y_t\}\} = 0\right\}.$$

Note that such an f^* is always realised, since the class is finite, and since it contains the all abstaining classifier. Let $A_T^* := \sum_{t < T} \mathbb{1}\{f^*(X_t) = \bot\}$ denote the value of the minimum above. The principal metrics of interest to us are the *abstention regret* $A_T - A_T^*$, and the *total mistakes* M_T.

Solution Concept The two performance metrics naturally involve a tradeoff - for instance, making some mistakes may allow a learner to drastically reduce its abstention regret to the point that it is negative. We pursue the trade-off between the worst possible behaviour of either regret.

Definition (Regret Achievability) *For functions $\varphi, \psi : \mathbb{N}^2 \to \mathbb{R}$, we say that expected regret bounds of (φ, ψ) are achievable against a class of adversaries $\mathscr{C}$ if there exists a learner such that for every adversary in $\mathscr{C}$, $\mathbb{E}[A_T - A_T^*] \leq \varphi(T, N)$ and $\mathbb{E}[M_T] \leq \psi(T, N)$.*

As is common, we are interested in the growth rates of achievable bounds with T. We thus define

137 **Definition** (Achievable rates) *we say that asymptotic expected-regret rates of $(\alpha, \mu) \in [0, 1]^2$ are*
138 *achievable against a class of adversaries $\mathscr{C}$ if an expected regret bound of (φ, ψ) can be achieved*
139 *against it for functions φ, ψ, said to be witnesses for the rate, such that*

$$\limsup_{T \to \infty} \frac{\log \varphi(T, N)}{\log T} \le \alpha \quad and \quad \limsup_{T \to \infty} \frac{\log \psi(T, N)}{\log T} \le \mu.$$

140 Notice that if (α, μ) is an achievable rate, so is (α', δ') for $\alpha' \ge \alpha, \delta' \ge \delta$. As a result, the lower
141 boundary of the set of achievable rates is well defined, and we will refer to this as the *Pareto*
142 *frontier of achievable rates*. This is equivalently characterised by the function $\underline{\alpha}(\mu) := \inf\{\alpha :$
143 (α, μ) is an achievable rate$\}$. This is well defined since $\forall \mu, (1, \mu)$ is achievable by always abstaining.

144 3 The Adversarial Case

145 We begin with the adversarial case. The scheme, called the 'versioned uniform explorer'
146 (VUE) is described below, and we discuss both the motivation of the scheme, and its analysis.

147 The main idea underlying VUE is that any function f
148 that is observed to make a mistake on an instance X_t
149 (due to the learner abstaining on this instance) can
150 be removed from future consideration, since we are
151 only trying to match the behaviour of the competitor
152 f^*, and clearly $f \ne f^*$ as it has made a mistake.
153 This motivates setting up a 'version space,'

$$\mathcal{V}_t := \left\{ f : \sum_{s < t} \mathbb{1}\{Z_s \ne *, f(X_s) \notin \{\bot, Y_s\}\} = 0 \right\},$$

154 the set of functions that are consistent with the ob-
155 servations made up to time t. Notice that $f^* \in \mathcal{V}_t$
156 for all t. Given $\mathcal{V}_t$, we can restrict to playing an
157 action in the set $\widehat{\mathcal{Y}}_t := \{f(X_t) : f \in \mathcal{V}_t\}$ - $f^*(X_t)$
158 lies in this set, and thus any action outside of it can
159 be eliminated. Of course, if $\widehat{\mathcal{Y}}_t$ is a singleton, then
160 it contains $f^*(X_t)$, and we can just play it.

Algorithm 1 VUE

1: **Inputs**: $\mathcal{F}$, Exploration rate p.
2: **Initialise**: $\mathcal{V}_1 \leftarrow \mathcal{F}$.
3: **for** $t \in [1 : T]$ **do**
4:     $\widehat{\mathcal{Y}}_t \leftarrow \{f(X_t) : f \in \mathcal{V}_t\}$.
5:     **if** $|\widehat{\mathcal{Y}}_t| = 1$ **then**
6:         $\widehat{Y}_t \leftarrow f(X_t)$ for any $f \in \mathcal{V}_t$.
7:         $\mathcal{V}_{t+1} \leftarrow \mathcal{V}_t$.
8:     **else**
9:         Sample $C_t \sim \text{Bern}(p)$.
10:         **if** $C_t = 1$ **then**
11:             Set $\widehat{Y}_t = \bot$, observe Y_t.
12:             $\mathcal{U}_t \leftarrow \{f : f(X_t) \in \{\bot, Y_t\}\}$
13:             $\mathcal{V}_{t+1} = \mathcal{V}_t \cap \mathcal{U}_t$.
14:         **else**
15:             Pick $\widehat{Y}_t \in \widehat{\mathcal{Y}}_t \setminus \{\bot\}$.
16:             $\mathcal{V}_{t+1} \leftarrow \mathcal{V}_t$.
---

161 Next, since we are incentivised to minimise the total
162 number of abstentions, it behooves us to play non-abstaining actions whenever possible. However,
163 this puts us in a bind, since feedback is produced only when we play an abstaining action. Taking
164 inspiration from [CLS05], we abstain at a rate p by tossing a biased 'exploratory coin', C_t, abstaining
165 when $C_t = 1$, and otherwise playing any non-abstaining action in $\widehat{\mathcal{Y}}_t$. Clearly, such a strategy
166 can incur at most pT excess abstention regret in expectation. Mistakes made by this strategy are
167 controlled via the following 'adversarial law of large numbers' (ALLN).

168 **Lemma 1.** *Let $\{\mathscr{F}_t\}_{t=1}^{\infty}$ be any filtration, and $\{U_t\}_{t=1}^{\infty}, \{B_t\}_{t=1}^{\infty}$ be $\{\mathscr{F}_t\}$-adapted binary processes,*
169 *such that $B_t \sim \text{Bern}(p)$, $p < 1/2$ is jointly independent of $\mathscr{F}_{t-1}, U_t$ for each t. Let $W_t = \sum_{s \le t} U_s$,*
170 *and $\widetilde{W}_t = \sum_{s \le t} U_s B_s$. For any $\delta \in (0, 1/\sqrt{e})$,*

$$\mathbb{P}\left(\exists t : \widetilde{W}_t \le 1, W_t > \frac{8 \log(1/\delta)}{p}\right) \le \delta.$$

171 The above is argued in §A using a self-normalised martingale inequality [How+20]. We note that
172 this self-normalisation is critical, and without this techniques such as Freedman's inequality yield
173 an extraneous $\sqrt{T}$ factor in the bounds that is untenable for our purposes. The same argument,
174 along with the shaping technique of Howard et al. [How+18] yields a Bernstein-type law of iterated
175 logarithms that controls $|W_t - \widetilde{W}_t/p|$ at a level $\tilde{O}(1/p + \sqrt{W_t/p \log \log t})$, which should be useful
176 more broadly. This full version (presented in §A) further shows that the 'Bernoulli-sampler' [BY20;
177 Alo+21] offers a continuous approximation in the sense of Ben-Eliezer & Yogev [BY20], but with
178 the error for sets of low incidence flattened as expected due to Bernstein's inequality.

179 To use the above, we set $\mathscr{F}_t = \sigma(\mathscr{H}_t^{\mathfrak{A}})$, and for $f \in \mathcal{F}$, set $U_t = \mathbb{1}\{f(X_t) \notin \{\bot, Y_t\}\}$, and
180 $B_t = C_t$. We say that f makes a mistake on X_t if $f(X_t) \notin \{\bot, Y_t\}$. Now, $f \in \mathcal{V}_t$ if and only if
181 $\widetilde{W}_{t-1} = 0$. Using a union bound over the fs, this means that up to the point at which a function

drops out of $\mathcal{V}_t$, it only incurs $O(\log(N)/p)$ mistakes.[2] Since each observed mistake reduces the size of the version space by at least 1, and since the version space is always non-empty, we can observe at most N mistakes. In the worst case, the learner could have made each of the mistakes that the functions that drop out of $\mathcal{V}$ make, but even then it could only make $O(N \log(N)/p)$ mistakes. This, along with Bernstein's inequality to control A_T yields the result below, as shown formally in §B.

Theorem 2. *Algorithm 1 instantiated with $p < 1/2$, and run against an adaptive adversary, attains the following with probability at least $1 - \delta$ over the randomness of the learner and the adversary:*

$$M_T \leq \frac{9N \log(2N/\delta)}{p}$$

$$A_T - A_T^* \leq pT + \sqrt{2p(1-p)T \log(2/\delta)} + 2\log(2/\delta).$$

In particular, taking $p = \sqrt{N/T}$ yields the symmetric regret bound

$$\max(M_T, A_T - A_T^*) \lesssim \sqrt{NT} \log(N/\delta).$$

We conclude with a few remarks.

Achievable rates: Taking $\delta = 1/T$, and varying p in $(\log T/T, 1]$ gives the rates attainable by VUE

Corollary 3. *All rates (α, μ) such that $\alpha > 0, \alpha + \mu > 1$ are achievable against adaptive adversaries.*

These rates are nearly tight - as expressed in Corollary 6, rates such that $\alpha + \mu < 1$ are not achievable even against stochastic adversaries. The Pareto frontier is therefore the line $\alpha + \mu = 1$.

Dependence on N: It should be noted that the dependence on the number of functions, N, in Thm. 2 is polynomial, as opposed to the more typical logarithmic dependence on the same in online classification. The problem of characterising this dependence appears to be subtle, and we do not resolve the same. In the following section, we explore schemes that improve this aspect, but at a cost - §4 yields logarithmic dependence against stochastic adversaries, while §5 gives a scheme that has a logarithmic dependence against adaptive adversaries, but worse dependence with T.

It is worth stating that the analysis above is tight for Algorithm 1 - consider the domain $\mathcal{X} = [1 : N]$, and the class $\mathcal{F} = \{f_t : t \in [0 : N]\}$ such that $f_t(x) = \perp$ if $x \leq t$ and $= 1$ if $x > t$. Now consider an adversary that chooses a t^* in advance, and presents the contexts $1\, T/N$ times, $2\, T/N$ times and so on, labelling contexts smaller than t^* as 0, and contexts larger than t^* as 1. Notice that in each case, there is exactly one function in $\mathcal{V}_t$ that does not abstain. The scheme above incurs $\Omega(pT(1 - t^*/N))$ excess abstention, and $\Omega(t^*/p)$ mistakes, and linearly large t^* form a tight example. Of course, this is not a lower bound on this problem, and the question of the optimal dependence on N remains open.

Hedge-Type Schemes The natural approach of proceeding by weighing the cost of abstention versus a mistake, and running a hedge-type scheme on an importance-estimate of the resulting loss does not lead to tight rates - the scheme MIXED-LOSS-PROD of §5 pursues precisely this strategy, and the worse case symmetric regret bounds that standard analyses lead to scale as $T^{2/3}$ instead of as $T^{1/2}$ as for VUE (Cor. 8). This may be due to the fact certain-error prone classifiers in $\mathcal{F}$ may have very low abstention rates, and thus overall large weight, and it is unclear how to eliminate this behaviour.

4   The Stochastic Case

This section argues that the regret bounds of Thm. 2 can be improved to behave logarithmically in N in the stochastic setting. There are a couple of issues with Algorithm 1 that impede a better analysis in the stochastic case. The first, and obvious, one is that how $\widehat{Y}_t$ is chosen is not specified. More subtly, the fact that the scheme insists on playing non-abstaining actions whenever possible makes it difficult to control the number of mistakes without a polynomial dependence on N.

We sidestep these issues in Algorithm 2 by maintaining a law π_t on functions in $\mathcal{V}_t$ that only depends on $\mathcal{H}_{t-1}^{\mathfrak{L}}$, and predicting by setting $\widehat{Y}_t = f(X_t)$ for $f_t \sim \pi_t$. Notice that playing this way it is possible that we abstain on X_t even if the exploratory coin comes up tails. We control mistakes by arguing that very error-prone functions are all quickly eliminated (due to the stochasticity), and using the property that π_t does not depend on X_t to limit the mistakes incurred up to such a time. Abstention control follows by choosing π according to a strategy that favours fs with small overall abstention rate over the history. In Algorithm 2, we use a version of the PROD scheme of [CMS07] to set weights, analysed with shrinking decision sets. The following is shown along these lines in §C.

---

[2]This only needs control for the case $\widetilde{W}_t = 0$. The ≤ 1 in Lemma 1 is exploited in §5.2

Theorem 4. *Algorithm 2, run against stochastic adversaries with $\eta = p$, attains the regret bounds*

$$\mathbb{E}[M_T] \leq 8 \frac{\log T \log(NT)}{p}, \quad and \quad \mathbb{E}[A_T - A_T^*] \leq pT + \frac{\log N}{p}.$$

We note that VUE-PROD also enjoys favourable bounds in the adversarial case - mistakes are bounded as $\tilde{O}(N/p)$, and abstention regret as in the above result. This is in contrast to simpler follow-the-versioned-leader type schemes that also satisfy similar bounds as Thm. 4 in the stochastic case. Also note that the above cannot attain rates such that $\alpha \leq 1/2$, an inefficiency introduced due to the conditional independence of π_t and X_t.

Finally, we show a lower bound. The statement equates stochastic adversaries with their laws.

Theorem 5. *If $\mathcal{F}$ contains two functions f_1, f_2 such that there exists a point x for which $f_1(x) = \perp \neq f_2(x)$, then for every $\gamma \in [0, 1/2]$, there exists a pair of laws P_1^γ, P_2^γ such that any learner that attains $\mathbb{E}_{P_1^\gamma}[A_T - A_T^*] = K$ must incur $\mathbb{E}_{P_2^\gamma}[M_T] \geq \gamma(e^{-2\gamma K}T - K).$*

Consequently, if a (φ, ψ) regret bound with $\sup \frac{\varphi}{T} < \frac{1}{2e^2}$ is achievable, then $\varphi \cdot \psi = \Omega(T)$. Indeed, consider adversaries as above with $\gamma = 1/\varphi(T, N)$. Then $\mathbb{E}_{P_1}[A_T - A_T^*] = K \leq \varphi(T, N)$, and therefore $\psi(T, N) \geq \mathbb{E}_{P_2}[M_T] \geq \frac{T}{\varphi(T,N)} e^{-2K/\varphi(T,N)} - 1$. This proves the following.

Corollary 6. *If $(\alpha, \mu) \in [0, 1]^2$ is such that $\alpha + \mu < 1$, then an (α, μ) regret rate is not achievable against stochastic adversaries, and, a fortiori, against adaptive adversaries.*

Algorithm 2 VUE-PROD

1: **Inputs**: $\mathcal{F}$, Exploration rate p, Learning rate η.
2: **Initialise**: $\mathcal{V}_1 \leftarrow \mathcal{F}, \forall f \in \mathcal{F}, w_1^f \leftarrow 1$.
3: **for** $t \in [1:T]$ **do**
4:      Sample $f_t \sim \pi_t = \frac{w_t^f \mathbb{1}\{f \in \mathcal{V}_t\}}{\sum_{f \in \mathcal{V}_t} w_t^f}$.
5:      Toss $C_t \sim \text{Bern}(p)$.
6:      $\widehat{Y}_t \leftarrow \begin{cases} \perp & C_t = 1 \\ f_t(X_t) & C_t = 0 \end{cases}$.
7:      **if** $C_t = 1$ **then**
8:          $\mathcal{U}_t \leftarrow \{f : f(X_t) \in \{\perp, Y_t\}\}$
9:          $\mathcal{V}_{t+1} = \mathcal{V}_t \cap \mathcal{U}_t$.
10:     **else**
11:          $\mathcal{V}_{t+1} \leftarrow \mathcal{V}_t$.
12:     **for** $f \in \mathcal{V}_{t+1}$ **do**
13:          $a_t^f \leftarrow \mathbb{1}\{f(X_t) = \perp\}$
14:          $w_{t+1}^f \leftarrow w_t^f \cdot (1 - \eta a_t^f)$.

---

5   Reducing the dependence of regret bounds on N in the adversarial case

This section concentrates on improving the N-dependence of regret bounds in the adversarial case via two avenues. The first improves this dependence to $\log(N)$ by running PROD with a weighted loss, but at the cost of increasing T dependence. This holds greatest relevance when T is bounded as a polynomial of N, which is of interest because N can be quite large even in reasonable settings - e.g., a discretisation of d-dimensional hyperplanes induces $N = \exp(Cd)$. The second approach considers the case when the set of possible contexts, i.e. $|\mathcal{X}|$ is not too large. While in this case, N can be as large as $|\mathcal{Y} + 1|^{|\mathcal{X}|}$, we show bounds depending only linearly on $|\mathcal{X}|$.

5.1   Weighted PROD

We continue the uniform exploration, but play according to the PROD method, with the loss

$$\ell_t^f := \mathbb{1}\{C_t = 1, f(X_t) \notin \{\perp, Y_t\}\} + \lambda \mathbb{1}\{f(X_t) = \perp\},$$

where λ both trades-off the relative costs of mistakes and abstentions, in the vein of the fixed cost Chow loss, and accounts for the sub-sampling of the mistake loss.

The analysis of this scheme, presented in §D exploits the quadratic bound of PROD due to [CMS07] to control the sum $\mathbb{E}[pM_T + \lambda(A_T - pT)]$ by $\min_g \log N/\eta + \sum \eta(\ell_t^g)^2$, where the expectation is only over the coins C_t, and the $-pT$ term is due to the extra abstentions due to the exploratory coin. The key observation is that since f^* makes no mistakes, $\sum(\ell_t^{f^*})^2 = \lambda^2 A_T^*$, and so taking $g = f^*$, and exploiting the weight allows us to separately control the regrets in terms of A_T^*.

Algorithm 3 MIXED-LOSS-PROD

1: **Inputs**: $\mathcal{F}$, Exploration rate p, Learning rate η.
2: **Initialise**: $\forall f \in \mathcal{F}, w_1^f \leftarrow 1$.
3: **for** $t \in [1:T]$ **do**
4:      Sample $f_t \sim \pi_t = w_t^f / \sum w_t^f$.
5:      Toss $C_t \sim \text{Bern}(p)$.
6:      **if** $C_t = 1$ **then**
7:          $\widehat{Y}_t \leftarrow \perp$
8:      **else**
9:          $\widehat{Y}_t \leftarrow f_t(X_t)$
10:     $\forall f \in \mathcal{F}$, evaluate ℓ_t^f
11:     $w_{t+1}^f \leftarrow w_t^f (1 - \eta \ell_t^f)$.

Theorem 7. *Algorithm 3, when run against adaptive adversaries with $\eta = \frac{1}{2}, \lambda \leq p$, attains*

$$\mathbb{E}[M_T] \leq \frac{2 \log N}{p} + \frac{2\lambda}{p} \mathbb{E}[A_T^*], \quad and \quad \mathbb{E}[A_T - A_T^*] \leq pT + \frac{2 \log N}{\lambda}.$$

5.1.1 Rates

Theorems 4 and 7 show regret bounds with logarithmic dependence in N. The following concept separates rates attainable with this advantageous property from those with worse N-dependence.

Definition (Logarithmically Achievable Rates) *We say that rates (α, μ) are logarithmically achievable against adversaries from a class $\mathscr{C}$ if there exists a learner that attains a (ψ, φ)-regret against such adversaries for ψ, φ that witness the rate (α, μ), and satisfy that for every fixed $T, \max(\varphi(T, N), \psi(T, N)) = O(\mathrm{polylog}(N))$ as $N \to \infty$.*

Since $A_T^* \leq T$, choosing $p = T^{-u}, \lambda = T^{-(u+v)}$ in MIXED-LOSS-PROD for any $(u, v) \in [0, 1]^2, u + v \leq 1$ allows us to attain rates of the form $(\alpha, \mu) = (\max(1 - u, u + v), 1 - v)$. Notice that for any fixed v, the smallest α so attainable is $\frac{1+v}{2}$. This shows

Corollary 8. *Any rate (α, μ) such that $\alpha + \mu/2 > 1$ is logarithmically achievable against adaptive adversaries.*

The following figure illustrates the worst case achievable rate regions in the three cases considered.

Figure 1: Left shows rates achievable against adaptive adversaries. Middle and right show logarithmically achievable rates against stochastic and adaptive adversaries respectively.

Adaptive Rates Observe that if $A_T^* \asymp T^{\alpha^*}$ for some $\alpha^* < 1$, then nomially, the achievable rates can be improved. Indeed, with the parametrisation $p = T^{-u}, \lambda = T^{-u,v}$, we may attain rates of the form $(\alpha, \mu) = (\max(1 - u, u + v), \max(u, \alpha^* - v))$. Further, a given mistake rate μ can be attained by setting $u = \mu$, and $\alpha^* - v \leq \mu$. With these constraints, the smallest abstention rate attainable is

$$\widetilde{\alpha}(\mu; \alpha_*) = \begin{cases} \max(1 - \mu, \alpha^*) & \mu \leq \alpha^* \\ \max(1 - \mu, \mu) & \mu > \alpha^* \end{cases},$$

achieved by setting $v = (\alpha_* - \mu)_+$. Such rates can in fact be attained adaptively, without prior knowledge of α^*. The main bottleneck here is that the quantity A_T^* is not observable. However, notice that every function g that is never *observed* to make a mistake satisfies the critical property that $\sum(\ell_t^g)^2 = \lambda^2 \sum \mathbb{1}\{g(X_t) = \perp\}$, and that such functions are identifiable given $\mathscr{H}_t^{\mathfrak{L}}$. Let

$$B_t^* := \min \sum_{s \leq t} \mathbb{1}\{g(X_s) = \perp\} \quad \text{s.t.} \quad \sum_{s \leq t} C_s \mathbb{1}\{g(X_s) \notin \{\perp, Y_t\}\} = 0.$$

Note that B_t^* grows monotonically, and is always smaller than $A_t^* = \sum_{s \leq t} \mathbb{1}\{f^*(X_t) = \perp\}$. We show the following in §D.1 via a scheme that sets $p = T^{-\mu}$, and adaptively sets λ/p according to B_t^*.

Theorem 9. *For any $\alpha^*, \mu, \varepsilon \in (0, 1]$, Algorithm 4 attains, without prior knowledge of α^*, any rate of the form $(\widetilde{\alpha}(\mu, \alpha^*), \mu + \varepsilon)$ against adaptive adversaries that induce $A_T^* \leq T^{\alpha^*}$ almost surely.*

5.2 A $|\mathcal{X}|$-dependent analysis of VUE

We give an alternate mistake analyse for VUE over finite domains. The analysis is slightly stronger: let $\mathbf{y} \in ([1 : K] \cup \{\perp\})^{|\mathcal{F}|}$ be indexed by elements of $\mathcal{F}$, with the 'fth' entry $\mathbf{y}_f$ reprsents a value

that f might take. Consider the resulting partition of $\{\mathcal{X}_{\mathbf{y}}\}_{\mathbf{y} \in ([1:K] \cup \{\perp\})^{\mathcal{F}}}$, where each part $\mathcal{X}_{\mathbf{y}} \subset \mathcal{X}$ contains points that have the same pattern of function values, that is $\mathcal{X}_{\mathbf{y}} = \{x : \forall f \in \mathcal{F}, f(x) = \mathbf{y}_f\}$. The following argument can be run unchanged by replacing single xs in the following by all xs in one $\mathcal{X}_{\mathbf{y}}$. That is, we may replace $|\mathcal{X}|$ in the following Theorem 10 with $|\{\mathcal{X}_{\mathbf{y}}\}|$. For simplicity, we present the argument for $|\mathcal{X}|$ only.

Denote $\widehat{\mathcal{Y}}_t^x := \{f(x) : f \in \mathcal{V}_t\}$. Notice that after the first time t such that $X_t = x, \widehat{Y}_t = \perp$, we will remove from the version space all classifiers that did not abstain or output the correct classification at time t. Thus if we define $y^x \in [1 : K]$ to be Y_t, then for all subsequent times, $\widehat{\mathcal{Y}}_t^x \subset \{\perp, y^x\}$. As a result, if we observe two mistakes at any given x, then we cannot make any more mistakes at a subsequent time t' with $X_{t'} = x$, because the only remaining decision in $\widehat{\mathcal{Y}}_{t'}^x$ must be $\perp$.

We may now proceed in much the same way as §3 - instantiate $U_t^x = \mathbb{1}\{X_t = x, \widehat{Y}_t \notin \{\perp, Y_t\}\}$, $B_t = C_t$, and union bound over the xs. Then $|\widehat{\mathcal{Y}}_t^x| \geq 2$ if and only if $\widetilde{W}_t^x \leq 1$, and, invoking Lemma 1, up to such a time at most $W_t^x = O(\log |\mathcal{X}|/p)$ mistakes may be made on instances such that $X_t = x$. But then totting up, we make at most $O(|\mathcal{X}| \log |\mathcal{X}|/p)$ mistakes, as encapsulated below

Theorem 10. *Algorithm 1 instantiated with $p \leq 1/2$ and run against an adaptive adversary, attains the following with probability at least $1 - \delta$ over the randomness of the learner and the adversary:*

$$M_T \leq \frac{9|\mathcal{X}| \log(2|\mathcal{X}|/\delta)}{p}$$
$$A_T - A_T^* \leq pT + \sqrt{2p(1-p)T \log(2/\delta)} + 2\log(2/\delta).$$

Along with the bound itself, the above result makes a couple of points regarding the characterisation of N-dependence of the regrets in online selective classification. Firstly, it suggests that efficient analyses, and possibly schemes, must incorporate the structure of $\mathcal{X}$; and secondly it shows that constructions that attempt to show superlogarithmic in N lower bounds must have both N and $|\mathcal{X}|$ large, and thus typical strategies placing a very rich class on a small domain will not be effective.

6 Experiments

We evaluate the performance of Algorithm 2 on two tasks - CIFAR 10 [KH09], and GAS [Ver+12]. The former case represents the setting where an expert can be adaptively invoked, which we treat by providing the true labels of the classes upon abstention. The second case is more explicitly an adaptive feature selection task - the GAS dataset consists of features from 16 sensors, and we train one model, g, on all of this data, while the selective classification task operates on data from the first 8 sensors alone, and receives the output of g when abstaining. The standard accuracies of the model classes we implement are $\sim 90\%$ on CIFAR-10, and $\sim 77\%$ on GAS. In both cases, a training set is used to learn a parameterized family of selective classifiers, $f_{\mu,t}$. The hyperparameters (μ, t) provide control over various levels of accuracy and abstention. For training, we leverage a recent method [GKS21] that yields such a parameterization - see §E for details of implementation. We discretize these parameters and we are left with $N = 600$ of these functions to form our class $\mathcal{F}$. We then sequentially classify the test datasets of each of the tasks.

One subtlety with the setting is that none of the selective classifiers in $\mathcal{F}$ actually make no mistakes. To avoid the trivialities emerging from this, we relax the versioning condition to only drop classifiers that are seen to make at least $p\varepsilon T + \sqrt{2p\varepsilon T}$ mistakes, where the second term handles noise. Notice that this variation of 'relaxed versioning' is also a natural idea when extending the present problem to the one where the competitor may make εT mistakes, although its analysis is beyond the scope of this paper. Below, we take the competitor to be the function that makes the fewest mistakes, M_T^*, (and in the case of ties amongst these, we pick the one of these that makes the fewest abstentions to get A_T^*). We measure *excess mistakes* $(M_T - M_T^*)$ and excess abstentions $A_T - A_T^*$ with respect to this competitor.

Behaviour of regrets with the length of the game Fig. 2 presents the excess mistakes as a fraction of T for the two datasets, i.e. M_T/T, as T, is varied. The learners are all instantiated with the exploration rate $p = 1/\sqrt{T}$. We observe that the excess abstentions are all negative over this range (see §E). Therefore we do not plot these below (the orange line is MMEA, see below). We note that the relative mistakes stay below $\sqrt{2 \log N/T}$, bearing out the theory.

Achievable Operating Points of Mistakes and Abstentions Fig. 3 represent the mistake and abstention rates attainable by varying p and ε, while holding T at a fixed value. Concretely, we vary these linearly for 20 values of $p \in [0.015, 0.285]$, and 10 values of $\varepsilon \in [0.001, 0.046]$. The resulting values represent operating points that can be attained by a choice of p, ε. We set $T = 500$ for this, which is large enough to allow some long-run structure to come through, but short enough to allow us to produce the plot within time constraints. The same plot includes lines that represent the operating points when the scheme is run with $\varepsilon = 0.001$, the smallest value we take. We comment that in practice, the best choices of ε, p may be data dependent, and how to choose it in an online way is an interesting open problem.

The Price of Being Online We characterise the disadvantage of playing online in two ways beyond the excess mistakes.

• In Fig. 2, we also plot the 'mistake-matched excess abstention' (MMEA). This is defined as follows - if the scheme concludes with having made M_T mistakes, we find, in hindsight, the classifier that minimises the number of abstentions, subject to making at most M_T mistakes. The MMEA is the excess abstention of the learner over those of this relaxed competitor, and represents how many fewer abstentions a batch learner would make if allowed to make as many mistakes as the online learner. Notice that this MMEA remains well controlled in Fig. 2, and appears to scale as $O(\sqrt{T})$.

• In Fig. 3, we also plot the post-hoc operating points of the classifiers in $\mathcal{F}$ as black triangles. This amounts to plotting the optimal abstentions amongst classifiers that make at most m mistakes, varying m.[3] We note that the red operating points of the scheme get close to the black frontier, illustrating that the inefficiency due to being online is limited. As the time-behaviour of MMEA in Fig.2 illustrates, the inefficiency is expected to grow sublinearly with T, and to thus vanish under amortisation.

Figure 2: $M_T - M_T^*$, and MMEA as fractions of T, as the number of rounds T is varied for CIFAR-10 (left) and GAS (right). The plots are averaged over 100 runs, and one-standard-deviation error regions are drawn.

Figure 3: Operating points for our scheme as ε and p are varied are represented as red dots (for CIFAR-10 in the left, and GAS in the right). The black triangles represent operating points obtained by batch learning with the benefit of full feedback. The blue lines interpolate points obtained by varying p for $\varepsilon = 0.001$ Points are averaged over 200 runs. Note that the values are raw mistakes and abstentions, and not regrets.

---

[3]Observe that the MMEA corresponds to the horizontal distance between a red-point with m mistakes, and the left-most black point with y-coordinate under m.

References

[Alo+15]   Noga Alon, Nicolo Cesa-Bianchi, Ofer Dekel, and Tomer Koren. "Online learning with feedback graphs: Beyond bandits". In: *Conference on Learning Theory*. PMLR. 2015, pp. 23–35.

[Alo+21]   Noga Alon, Omri Ben-Eliezer, Yuval Dagan, Shay Moran, Moni Naor, and Eylon Yogev. "Adversarial Laws of Large Numbers and Optimal Regret in Online Classification". In: *arXiv preprint arXiv:2101.09054* (2021).

[BLM13]   Stéphane Boucheron, Gábor Lugosi, and Pascal Massart. *Concentration inequalities: A nonasymptotic theory of independence*. Oxford university press, 2013.

[BW08]   Peter L Bartlett and Marten Wegkamp. "Classification with a reject option using a hinge loss". In: *Journal of Machine Learning Research* 9.Aug (2008), pp. 1823–1840.

[BY20]   Omri Ben-Eliezer and Eylon Yogev. "The adversarial robustness of sampling". In: *Proceedings of the 39th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems*. 2020, pp. 49–62.

[CDM16]   Corinna Cortes, Giulia DeSalvo, and Mehryar Mohri. "Learning with rejection". In: *International Conference on Algorithmic Learning Theory*. Springer. 2016, pp. 67–82.

[Cho57]   C Chow. "An optimum character recognition system using decision functions". In: *IRE Transactions on Electronic Computers* EC-6.4 (1957), pp. 247–254.

[Cho70]   C Chow. "On optimum recognition error and reject tradeoff". In: *IEEE Transactions on Information Theory* 16.1 (1970), pp. 41–46.

[CLS05]   Nicolo Cesa-Bianchi, Gábor Lugosi, and Gilles Stoltz. "Minimizing regret with label efficient prediction". In: *IEEE Transactions on Information Theory* 51.6 (2005), pp. 2152–2162.

[CMS07]   Nicolo Cesa-Bianchi, Yishay Mansour, and Gilles Stoltz. "Improved second-order bounds for prediction with expert advice". In: *Machine Learning* 66.2 (2007), pp. 321–352.

[Cor+18]   Corinna Cortes, Giulia DeSalvo, Claudio Gentile, Mehryar Mohri, and Scott Yang. "Online learning with abstention". In: *international conference on machine learning*. PMLR. 2018, pp. 1059–1067.

[DZ13]   Erik D Demaine and Morteza Zadimoghaddam. "Learning Disjunctions: Near-Optimal Trade-off between Mistakes and "I Don't Knows"". In: *Proceedings of the Twenty-Fourth Annual ACM-SIAM Symposium on Discrete Algorithms*. SIAM. 2013, pp. 1369–1379.

[EW10]   Ran El-Yaniv and Yair Wiener. "On the foundations of noise-free selective classification". In: *Journal of Machine Learning Research* 11.May (2010), pp. 1605–1641.

[GE19]   Yonatan Geifman and Ran El-Yaniv. "SelectiveNet: A Deep Neural Network with an Integrated Reject Option". In: *International Conference on Machine Learning*. 2019, pp. 2151–2159.

[GKS21]   Aditya Gangrade, Anil Kag, and Venkatesh Saligrama. "Selective Classification via One-Sided Prediction". In: *International Conference on Artificial Intelligence and Statistics*. PMLR. 2021, pp. 2179–2187.

[He+16]   Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. "Deep residual learning for image recognition". In: *Proceedings of the IEEE conference on computer vision and pattern recognition*. 2016, pp. 770–778.

[How+18]   Steven R Howard, Aaditya Ramdas, Jon McAuliffe, and Jasjeet Sekhon. "Time-uniform, nonparametric, nonasymptotic confidence sequences". In: *arXiv preprint arXiv:1810.08240* (2018).

[How+20]   Steven R Howard, Aaditya Ramdas, Jon McAuliffe, Jasjeet Sekhon, et al. "Time-uniform Chernoff bounds via nonnegative supermartingales". In: *Probability Surveys* 17 (2020), pp. 257–317.

[HW06]   Radu Herbei and Marten Wegkamp. "Classification with reject option". In: *The Canadian Journal of Statistics/La Revue Canadienne de Statistique* (2006), pp. 709–721.

[Ide19]   Yerlan Idelbayev. *Proper ResNet Implementation for CIFAR10/CIFAR100 in pytorch*. Accessed on 2020-2-28. 2019. URL: https://github.com/akamaster/pytorch_resnet_cifar10.

[KH09]   Alex Krizhevsky and Geoffrey Hinton. "Learning multiple layers of features from tiny images". In: (2009).

[KKM12]   Adam Tauman Kalai, Varun Kanade, and Yishay Mansour. "Reliable agnostic learning". In: *Journal of Computer and System Sciences* 78.5 (2012), pp. 1481–1495.

[Lei14]   Jing Lei. "Classification with confidence". In: *Biometrika* 101.4 (Oct. 2014), pp. 755–769. ISSN: 0006-3444. DOI: 10.1093/biomet/asu038.

[Li+11]   Lihong Li, Michael L Littman, Thomas J Walsh, and Alexander L Strehl. "Knows what it knows: a framework for self-aware learning". In: *Machine learning* 82.3 (2011), pp. 399–443.

[LS20]   Tor Lattimore and Csaba Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.

[MS11]   Shie Mannor and Ohad Shamir. "From Bandits to Experts: On the Value of Side-Observations". In: *Advances in Neural Information Processing Systems*. Ed. by J. Shawe-Taylor, R. Zemel, P. Bartlett, F. Pereira, and K. Q. Weinberger. Vol. 24. Curran Associates, Inc., 2011. URL: https://proceedings.neurips.cc/paper/2011/file/e1e32e235eee1f970470a3a6658dfdd5-Paper.pdf.

[NS17]   Feng Nan and Venkatesh Saligrama. "Adaptive classification for prediction under a budget". In: *Advances in Neural Information Processing Systems*. 2017, pp. 4727–4737.

[OR94]   Martin J Osborne and Ariel Rubinstein. *A course in game theory*. MIT press, 1994.

[RST15a]   Alexander Rakhlin, Karthik Sridharan, and Ambuj Tewari. "Online learning via sequential complexities." In: *J. Mach. Learn. Res.* 16.1 (2015), pp. 155–186.

[RST15b]   Alexander Rakhlin, Karthik Sridharan, and Ambuj Tewari. "Sequential complexities and uniform martingale laws of large numbers". In: *Probability Theory and Related Fields* 161.1-2 (2015), pp. 111–153.

[SZB10]   Amin Sayedi, Morteza Zadimoghaddam, and Avrim Blum. "Trading off mistakes and don't-know predictions". In: (2010).

[Ver+12]   Alexander Vergara, Shankar Vembu, Tuba Ayhan, Margaret A Ryan, Margie L Homer, and Ramón Huerta. "Chemical gas sensor drift compensation using classifier ensembles". In: *Sensors and Actuators B: Chemical* 166 (2012), pp. 320–329.

[WE11]   Yair Wiener and Ran El-Yaniv. "Agnostic selective classification". In: *Advances in neural information processing systems*. 2011, pp. 1665–1673.

[Xu+14]   Zhixiang (Eddie) Xu, Matt J. Kusner, Kilian Q. Weinberger, Minmin Chen, and Olivier Chapelle. "Classifier Cascades and Trees for Minimizing Feature Evaluation Cost". In: *Journal of Machine Learning Research* 15 (2014), pp. 2113–2144. URL: http://jmlr.org/papers/v15/xu14a.html.

[ZC16]   Chicheng Zhang and Kamalika Chaudhuri. "The extended littlestone's dimension for learning with mistakes and abstentions". In: *Conference on Learning Theory*. PMLR. 2016, pp. 1584–1616.