CAN STOCHASTIC WEIGHT AVERAGING IMPROVE GENERALIZATION IN PRIVATE LEARNING?

ABSTRACT

We investigate stochastic weight averaging (SWA) in private learning in the context of generalization and model performance. Differentially private (DP) optimizers are known to suffer from reduced performance and high variance in comparison to non-private learning. However, the generalization properties of DP optimizers have not been studied much, in particular for large-scale machine learning models. SWA is a variation of stochastic gradient descent (SGD) which considers averages of the weights along the SGD trajectory. A DP adaptation of SWA (DP-SWA) incurs no additional privacy cost, and has little computational overhead. For quadratic objective functions, we show that DP-SWA converges to the optimum at the same rate as non-private SGD, and provides convergence to zero for the excess risk. For non-convex objective functions, we experimentally observe that averaging model weights improves generalization, as it promotes wideness of the solutions, as well as model accuracy and performance variance.

1   INTRODUCTION

Machine learning models that provide guarantees against data leakage are critical for many applications as they can be more safely trained on sensitive data. Differential privacy (DP; Dwork et al., 2014) offers formal privacy guarantees and protects information about individual training points. Differentially private stochastic gradient descent (DP-SGD), first introduced by Abadi et al. (2016), is the state-of-the-art algorithm to privately train models using SGD. Models trained with DP-SGD, however, suffer from a degradation of performance and often provide less stable solutions (Wang et al.). Although DP is known to enjoy good generalization properties (Wang et al., 2016), prior work has shown that privately training larger models can be detrimental to generalization (Papernot et al., 2021). In non-private settings, Izmailov et al. (2018) demonstrated empirically that stochastic weight averaging (SWA), i.e., aggregating SGD iterates as originally proposed in Polyak & Juditsky (1992), leads to wider optima, better generalization, and improved performance. Only few research efforts have been made to analyze the impact of weight averaging in DP settings. De et al. (2022) first consider it for large-scale vision tasks, and Shejwalkar et al. (2022) explore different weight averaging techniques for improving model accuracy. Albeit convergence guarantees for averaging schemes for SGD have been previously analyzed (Shamir & Zhang, 2013), there is little theoretical investigation on the benefits of weight averaging for DP-SGD.

Motivated by the lack of theoretical and experimental results on SWA in a private setting, we investigate whether aggregating DP-SGD iterates with SWA (DP-SWA) improves generalization and model performance. Specifically, we consider the wideness of solutions as a proxy for generalization (Cha et al., 2021), and study whether these effects can be observed across different scales of models. We perform several case studies for the optimization of machine learning models with DP-SWA. For quadratic objective functions, we show that DP-SWA converges to the optimum at the same rate as standard SGD thus showing that the excess risk converges to zero as $1/T$ for T iterations. For strongly convex functions, we empirically corroborate existing convergence bounds for suffix averaging in DP-SGD (Shejwalkar et al., 2022) with logistic regression experiments on Fashion-MNIST. For non-convex objective functions, we experiment with large-scale vision models on common benchmark datasets (Fashion-MNIST, CIFAR-10, CIFAR-100). We find that DP-SWA yields wider and more stable solutions with higher accuracy at a negligible computational impact.

2 PRELIMINARIES

Differential privacy (DP) We use the notion of (ϵ, δ)-DP as introduced in Dwork et al. (2006). A randomized algorithm $\mathcal{M}$ with domain $\mathcal{D}$ satisfies (ϵ, δ)-DP if for any two adjacent inputs $D, D' \in \mathcal{D}$, i.e., D and D' differ in a single entry, and for any subsets $S \subseteq range(\mathcal{M})$ the following holds:

$$\mathbb{P}\left[\mathcal{M}(D) \in S\right] \leq e^\epsilon \, \mathbb{P}\left[\mathcal{M}(D') \in S\right] + \delta$$

We refer to ϵ as the privacy budget of the algorithm. It is important to note that the outputs of a DP algorithm can be post-processed without worsening privacy guarantees (Dwork et al., 2014) which we refer to as the *post-processing* property of DP. DP can be achieved by adding noise to a function with bounded sensitivity (i.e., where the difference between function values on adjacent inputs D and D' is bounded). Following this approach, Abadi et al. (2016) propose DP-SGD, a DP version of SGD.

DP-SWA SWA takes averages of the weights along the SGD trajectory, and has been shown to improve performance and generalization of machine learning models optimized with SGD Izmailov et al. (2018). To adapt SWA for private learning, we consider DP-SWA, displayed in Algorithm 1, where gradient steps are taken using DP-SGD. DP-SWA leverages the post-processing property of DP, which permits the aggregation of intermediate DP-SGD weights without additional privacy cost. Specifically, DP-SWA averages intermediate weights every c steps, which we denote by the cycle length c. See Appendix A for more details on DP-SGD and DP-SWA.

3 CONVERGENCE FOR QUADRATIC AND CONVEX OBJECTIVE FUNCTIONS

In this section, we theoretically investigate DP-SWA for (i) quadratic and (ii) convex objective functions. For (i), we provide an upper bound on the convergence of the parameter estimates, for (ii) we discuss existing results for weight averaging in a private setting.

Theorem 1 (Quadratic objective functions) (Informal, adapted from Theorem 1 of Yang et al. (2019)) *Let f be a quadratic objective function with parameters $\theta \in \mathbb{R}^d$. Consider a cycle length c. In expectation, the squared distance of the output $\bar{\theta}_T$ of DP-SWA with respect to the optimum θ^* at iteration T is upper bounded as:*

$$\mathbb{E}\|\bar{\theta}_T - \theta^*\|^2 \leq \mathcal{O}\left(\frac{cd}{T\epsilon^2}\right)$$

See Appendix A.3 for a formal presentation and proof. According to Theorem 1, DP-SWA converges to the optimal solution for a given privacy budget ϵ in $\mathcal{O}(1/T)$ time, the same convergence rate as standard SGD (Varre et al., 2021)[1]. We will consider linear regression as a case study. For a similar problem setting (linear regression for bounded inputs and bounded moments), Cai et al. (2021) obtain an upper bound on the (non-averaged) last iterate parameters as $\mathbb{E}\|\theta_T - \theta^*\|^2 \leq \mathcal{O}(d^2/\epsilon^2)$. Varshney et al. (2022) obtain a near optimal utility bound on averaged iterates using an adaptive clipping technique, but do not consider different cycle lengths. We refer the reader to, e.g., Wang (2018) for a more detailed overview on research efforts in DP linear regression.

Convex objective functions In non-private stochastic settings, averaging all iterates provides only sub-optimal convergence rates in (strongly) convex optimization; optimal rates can however be recovered by averaging a suffix of the iterates only (Rakhlin et al., 2012; Shamir & Zhang, 2013). This approach corresponds to running SWA with cycle length $c = 1$ after a warm-up phase where no averages are collected. In a private setting and for convex objective functions, (Shejwalkar et al., 2022) have recently shown a better upper bound on the excess empirical risk for suffix averaging, when compared to the last, non-averaged iterate. Even though the authors do not provide lower bounds on the excess risks for last iterate and suffix averaging, their result indicates that DP-SWA with $c = 1$ may be beneficial in convex optimization. However, the authors do not perform experiments in the convex setting; instead, we empirically investigate this case with a logistic regression task.

---

[1]It should be noted that the privacy budget ϵ is to be interpreted as the budget for each descent step. That is, the overall budget after T epochs is proportional to $T\epsilon$. The bound can thus be alternatively interpreted as a $\mathcal{O}(d/\epsilon^2)$ utility bound after T epochs.

Figure 1: Visualizations for $\epsilon = 8$. (Left) Linear regression, DP-SWA is in agreement with Theorem 1 and compatible with convergence to the optimum at a rate (at least as fast as) $1/T$ (see also Appendix C). (Right) Non-convex objectives, solution width of DP-SWA in Fashion-MNIST with *ResNet-18*. The plot is obtained by computing the loss function on points which lay on the line connecting the DP-SGD and DP-SWA weights.

4 EXPERIMENTS

In this section, we evaluate whether our theoretical findings can be confirmed experimentally, and investigate whether weight averaging improves generalization in private learning for non-convex objective functions. Specifically, we (i) confirm Theorem 1 by solving a linear regression task; (ii) experiment on logistic regression for convex optimization; and (iii) conduct several experiments with *ResNet18* and *WRN-16-4* on standard benchmark datasets. We focus on assessing the impact of DP-SWA on (a) generalization, (b) accuracy, and (c) stability of the solutions in comparison to DP-SGD. We measure generalization (a) as the AUC of the accuracy resulting from moving away from the weight vectors θ_T and $\bar{\theta}_T$ obtained by DP-SGD and DP-SWA, where larger AUC denotes wider solutions. We report the signed percentage gain of DP-SWA over DP-SGD as $\%_{\text{AUC}}$, with positive values favoring DP-SWA. We measure accuracy (b) by means of distance to the optimum for linear regression, and classification accuracy for all other tasks. We measure stability (c) as the variance of the accuracy for algorithm ALG during the last 10 iterations (Var_{ALG}), or all available iterates if DP-SWA was run for less than 10 iterations. For all experimental settings, we use DP-SGD with constant learning rate as an optimizer, and start averaging weights after an initial warm-up phase. Similar to De et al. (2022); Shejwalkar et al. (2022) we run experiments with privacy budget $\epsilon = \{1, 8\}$ and $\delta = 10^{-5}$, unless noted otherwise. More details on the experimental setup can be found in Appendix B.

Quadratic objective functions We experimentally confirm Theorem 1 using DP-SWA to optimize a linear regression task with mean squared error loss on synthetic data; refer to Appendix B.1 for details on data generation. Table 1 shows that DP-SWA is preferable to DP-SGD, both in terms of distance to the optimum and stability. We verify the convergence of DP-SWA to the optimum in $\mathcal{O}(1/T)$, see Figure 1. Additional results in Appendix C show the $\mathcal{O}(1/\epsilon^2)$ dependency and faster convergence with more frequent averages (i.e., smaller c).

Table 1: Squared distance to the optimum and squared distance variance over the last iterates for linear regression. Mean and standard deviation across 5 runs. Results for $\delta = 1/n^2$ for $n = 4096$ data points.

ϵ	$\|\theta_T - \theta^*\|^2_{\text{(DP-SGD)}}$	$\|\bar{\theta}_T - \theta^*\|^2_{\text{(DP-SWA)}}$	$\text{Var}_{\text{DP-SGD}}$	$\text{Var}_{\text{DP-SWA}}$
1	22 ± 2	$\mathbf{7.4 \pm 0.9}$	1.1 ± 0.5	$\mathbf{0.11 \pm 0.08}$
8	2.6 ± 0.2	$\mathbf{0.52 \pm 0.01}$	0.2 ± 0.1	$\mathbf{0.03 \pm 0.03}$

Convex objective functions We use DP-SWA with logistic regression on Fashion-MNIST to empirically investigate the results of Shejwalkar et al. (2022) for convex objective functions. We find that DP-SWA offers significantly better accuracy and stability in comparison to DP-SGD; for instance, DP-SWA for $\epsilon = 1$ reaches an accuracy of 74.7%, which is comparable to the DP-SGD

result for $\epsilon = 8$ of 75.3%. That is, DP-SWA obtains an accuracy similar to that of DP-SGD, but with stronger privacy guarantees. Detailed results are in Appendix C.

Non-convex objective functions In order to assess the impact of weight averaging in private learning for non-convex objectives, we experiment with *ResNet-18*, *WRN-16-4* and *ResNet-50* on Fashion-MNIST (F-MNIST), CIFAR-10 and CIFAR-100. As we are mainly concerned with evaluating whether DP-SWA improves on DP-SGD, we do not perform data augmentation and, guided by related work (De et al., 2022; Shejwalkar et al., 2022; Panda et al., 2022), performed limited hyper-parameter tuning. Refer to Appendix B.2 for more details. We conduct experiments with *ResNet-18* and *WRN-16-4* on Fashion-MNIST and CIFAR-10; see Table 2 for mean and standard deviation over 5 random repeats. Additional results on CIFAR-10 and CIFAR-100 with *ResNet-18* and *Resnet-50* pre-trained on ImageNet are available in Appendix C.

Table 2: Accuracy, accuracy variance over the last iterates, and $\%_{\text{AUC}}$ for non-convex objective functions. Mean and standard deviation across 5 runs.

Experiment	ϵ	DP-SGD	DP-SWA	$\text{Var}_{\text{DP-SGD}}$ $(\times 10^{-3})$	$\text{Var}_{\text{DP-SWA}}$ $(\times 10^{-3})$	$\%_{\text{AUC}}$
F-MNIST	1	79.1 ± 0.8	$\mathbf{79.9 \pm 0.1}$	1.3 ± 0.1	$\mathbf{0.3 \pm 0.2}$	$+2.4 \pm 0.4$
ResNet-18	8	84.9 ± 0.2	$\mathbf{85.6 \pm 0.1}$	1.5 ± 0.5	$\mathbf{0.1 \pm 0.1}$	$+4.6 \pm 0.9$
F-MNIST	1	80.1 ± 0.4	$\mathbf{80.2 \pm 0.2}$	0.05 ± 0.04	$\mathbf{0.02 \pm 0.02}$	$+6.5 \pm 1.9$
WRN-16-4	8	84.6 ± 0.1	$\mathbf{84.8 \pm 0.1}$	0.01 ± 0.01	$\mathbf{\leq 10^{-2}}$	$+9.7 \pm 2.9$
CIFAR-10	1	38.8 ± 0.5	$\mathbf{41.0 \pm 0.9}$	10 ± 6	$\mathbf{0.4 \pm 0.4}$	$+6.2 \pm 0.7$
ResNet-18	8	60.8 ± 0.5	$\mathbf{62.1 \pm 0.5}$	3 ± 3	$\mathbf{0.2 \pm 0.1}$	$+2.9 \pm 0.5$
CIFAR-10	1	44.7 ± 1.2	$\mathbf{46.5 \pm 0.3}$	0.04 ± 0.01	$\mathbf{\leq 10^{-2}}$	$+4.3 \pm 2.9$
WRN-16-4	8	66.7 ± 0.1	$\mathbf{67.6 \pm 0.1}$	0.04 ± 0.02	$\mathbf{\leq 10^{-3}}$	$+1.6 \pm 1.2$

In Table 2 we observe that DP-SWA is generally preferable to DP-SGD, as it achieves superior accuracy, stability, and wider solutions. Even though accuracy improvements for other averaging schemes have also been recently observed in Shejwalkar et al. (2022), the wideness and stability of the solutions has not been empirically investigated. For large-scale models, De et al. (2022) were the first to achieve state-of-the-art accuracy with weight averaging; training without data augmentation, the authors achieve a (validation) accuracy of $\approx 70\%$ on CIFAR-10 with $\epsilon = 8$ and $\delta = 10^{-5}$, which is comparable to our results. However, the authors do not investigate generalization. In contrast, we observe that DP-SWA solutions are preferable because they are not only more accurate, but also wider and thus provide better generalization (cf. Figure 1). Wide minima are especially desirable in a DP setting as the noisy DP-SGD updates can favor escaping sharp minima (Wang et al.). Panda et al. (2022) briefly address weight averaging for DP for fine-tuning pre-trained models and conclude that, in their experiments, it performs worse than the last iterate. While we observe diminishing performance benefits for pre-trained tasks, we nevertheless consider the DP-SWA solutions to be preferable also in these cases, for their stability and wideness properties.

5 CONCLUSION

We investigated the effects of DP-SWA for quadratic, convex, and non-convex objective functions. We obtained a convergence bound for the quadratic case. On standard benchmark datasets, we find that **DP-SWA achieves better generalization, accuracy, and more stable solutions**. In future work, we will consider a more extensive analysis of the benefits and limitations of DP-SWA, and investigate whether DP-SWA can perform well on language tasks where SWA has previously been shown to under-perform (Kaddour et al., 2022). Additionally, theoretical understanding of the effects of weight averaging in DP is currently lacking, particularly so for non-convex objective functions and different cycle lengths. In this sense, obtaining a better understanding of the loss surface for DP-SGD is a promising research direction.

REFERENCES

Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC conference on computer and communications security*, pp. 308–318, 2016.

T Tony Cai, Yichen Wang, and Linjun Zhang. The cost of privacy: Optimal rates of convergence for parameter estimation with differential privacy. *The Annals of Statistics*, 49(5):2825–2850, 2021.

Junbum Cha, Sanghyuk Chun, Kyungjae Lee, Han-Cheol Cho, Seunghyun Park, Yunsung Lee, and Sungrae Park. Swad: Domain generalization by seeking flat minima. *Advances in Neural Information Processing Systems*, 34:22405–22418, 2021.

Soham De, Leonard Berrada, Jamie Hayes, Samuel L Smith, and Borja Balle. Unlocking high-accuracy differentially private image classification through scale. *arXiv preprint arXiv:2204.13650*, 2022.

Cynthia Dwork, Krishnaram Kenthapadi, Frank McSherry, Ilya Mironov, and Moni Naor. Our data, ourselves: Privacy via distributed noise generation. In *Advances in Cryptology-EUROCRYPT 2006: 24th Annual International Conference on the Theory and Applications of Cryptographic Techniques, St. Petersburg, Russia, May 28-June 1, 2006. Proceedings 25*, pp. 486–503. Springer, 2006.

Cynthia Dwork, Aaron Roth, et al. The algorithmic foundations of differential privacy. *Foundations and Trends® in Theoretical Computer Science*, 9(3–4):211–407, 2014.

Pavel Izmailov, Dmitrii Podoprikhin, Timur Garipov, Dmitry Vetrov, and Andrew Gordon Wilson. Averaging weights leads to wider optima and better generalization. In *34th Conference on Uncertainty in Artificial Intelligence 2018, UAI 2018*, pp. 876–885, 2018.

Jean Kaddour, Linqing Liu, Ricardo Silva, and Matt J Kusner. When do flat minima optimizers work? *Advances in Neural Information Processing Systems*, 35:16577–16595, 2022.

Ashwinee Panda, Xinyu Tang, Vikash Sehwag, Saeed Mahloujifar, and Prateek Mittal. Dp-raft: A differentially private recipe for accelerated fine-tuning. *arXiv preprint arXiv:2212.04486*, 2022.

Nicolas Papernot, Abhradeep Thakurta, Shuang Song, Steve Chien, and Úlfar Erlingsson. Tempered sigmoid activations for deep learning with differential privacy. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 9312–9321, 2021.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems*, 32, 2019.

Boris T Polyak and Anatoli B Juditsky. Acceleration of stochastic approximation by averaging. *SIAM journal on control and optimization*, 30(4):838–855, 1992.

Alexander Rakhlin, Ohad Shamir, and Karthik Sridharan. Making gradient descent optimal for strongly convex stochastic optimization. 2012.

Ohad Shamir and Tong Zhang. Stochastic gradient descent for non-smooth optimization: Convergence results and optimal averaging schemes. In *International Conference on Machine Learning*, pp. 71–79. PMLR, 2013.

Virat Shejwalkar, Arun Ganesh, Rajiv Mathews, Om Thakkar, and Abhradeep Thakurta. Recycling scraps: Improving private learning by leveraging intermediate checkpoints. *arXiv preprint arXiv:2210.01864*, 2022.

Aditya Vardhan Varre, Loucas Pillaud-Vivien, and Nicolas Flammarion. Last iterate convergence of sgd for least-squares in the interpolation regime. *Advances in Neural Information Processing Systems*, 34:21581–21591, 2021.

Prateek Varshney, Abhradeep Thakurta, and Prateek Jain. (nearly) optimal private linear regression for sub-gaussian data via adaptive clipping. In *Conference on Learning Theory*, pp. 1126–1166. PMLR, 2022.

Wenxiao Wang, Tianhao Wang, Lun Wang, Nanqing Luo, Pan Zhou, Dawn Song, and Ruoxi Jia. Dplis: Boosting utility of differentially private deep learning via randomized smoothing. *Proceedings on Privacy Enhancing Technologies*, 2021(4):163–183.

Yu-Xiang Wang. Revisiting differentially private linear regression: optimal and adaptive prediction & estimation in unbounded domain. *arXiv preprint arXiv:1803.02596*, 2018.

Yu-Xiang Wang, Jing Lei, and Stephen E Fienberg. Learning with differential privacy: Stability, learnability and the sufficiency and necessity of erm principle. *The Journal of Machine Learning Research*, 17(1):6353–6392, 2016.

Guandao Yang, Tianyi Zhang, Polina Kirichenko, Junwen Bai, Andrew Gordon Wilson, and Chris De Sa. Swalp: Stochastic weight averaging in low precision training. In *International Conference on Machine Learning*, pp. 7015–7024. PMLR, 2019.

Ashkan Yousefpour, Igor Shilov, Alexandre Sablayrolles, Davide Testuggine, Karthik Prasad, Mani Malek, John Nguyen, Sayan Ghosh, Akash Bharadwaj, Jessica Zhao, et al. Opacus: User-friendly differential privacy library in pytorch. In *NeurIPS 2021 Workshop Privacy in Machine Learning*.

A ADDITIONAL PRELIMINARIES AND PROOF OF THEOREM 1

A.1 DP-SGD

A DP version of SGD was introduced by Abadi et al. (2016). With respect to standard SGD, in DP-SGD, during the update step, gradients are clipped to a maximum norm C to bound sensitivity (as there is no a priori bound on the size of the gradients) and Gaussian noise b is added before the descent step. For a loss function f and learning rate α, we can write the gradient update (for a single data point to simplify notation) as

$$\theta_i = \theta_{i-1} - \alpha(\text{clip}_C \nabla f(\theta_{i-1}) + b_i),$$

where gradients are clipped to a maximum norm of C and $b_i \sim \mathcal{N}(0, \sigma^2)$.

A.2 DP-SWA

Algorithm 1 DP-SWA, DP adaptation of SWA from Izmailov et al. (2018)

Input: initial weights θ_0, cycle length c, number of iterations T, learning rate α, loss function f, clipping norm C, noise scale σ
Output: $\bar{\theta}_T$
 1: $\bar{\theta}_T \leftarrow \theta_0$
 2: **for** $i \in 1 \dots T$ **do**
 3:      $\theta_i \leftarrow \theta_{i-1} - \alpha(\text{clip}_C \nabla f(\theta_{i-1}) + b_i)$ *(DP-SGD, with $b_i \sim \mathcal{N}(0, \sigma^2)$)*
 4:      **if** $c = 0 \pmod i$ **then**
 5:          $n_m \leftarrow i/c$ *(number of models)*
 6:          $\bar{\theta}_T \leftarrow \frac{\bar{\theta}_T \cdot n_m + \theta_i}{n_m + 1}$ *(update average)*
 7:      **end if**
 8: **end for**
 9: **return** $\bar{\theta}_T$

We consider Algorithm 1, an adaptation of the SWA algorithm in Izmailov et al. (2018), where gradient steps are taken using DP-SGD which guarantees that the algorithm is DP. Note that, by virtue of the post-processing property of DP, DP-SGD permits averaging of the intermediate weights without incurring additional privacy cost; that is, Algorithm 1 has the same privacy budget as default DP-SGD. In practical applications, it is recommended to start averaging after a warm-up phase where the optimization procedure approaches an optimum (Izmailov et al., 2018; Panda et al., 2022).

A.3 PROOF FOR THEOREM 1

Let f be a quadratic objective function of the form $f(\theta) = (\theta - \theta^*)^T A(\theta - \theta^*)/2$ with $A \succeq \mu I \in \mathbb{R}^{d \times d}$, $\mu > 0$, and θ^* the optimum of f. In the DP-SGD setting, assume that the sample gradients $\nabla \tilde{f}(\theta)$ are, in expectation, equal to the full gradient, i.e., $\mathbb{E}[\nabla \tilde{f}(\theta)] = \nabla f(\theta) = A(\theta - \theta^*)$. For simplicity, assume a compact domain for the parameters θ so to bound the gradient norm, and take this to be the clipping norm, which will therefore be omitted. For the gradient updates, take $b \sim \mathcal{N}(0, \sigma^2 \mathbf{I}_d)$ with $\sigma^2 = \frac{2 \log 1.25/\delta}{\epsilon^2}$ to guarantee DP (Dwork et al., 2014; Abadi et al., 2016). Finally, make the standard assumption that $\mathbb{E}\|\nabla \tilde{f}(\theta) - \nabla f(\theta)\|^2 \le \varsigma^2$.

Theorem 1 (Adapted from Theorem 1 of Yang et al. (2019)) *Consider a cycle length c and a learning rate $0 < \alpha < \frac{\|A\|_2}{2}$. In expectation, the squared distance of the output of Algorithm 1 with respect to the optimum θ^* at iteration T is upper bounded by:*

$$\mathbb{E}\|\bar{\theta}_T - \theta^*\|^2 \le \frac{\|\theta_0 - \theta^*\|^2}{T^2 \alpha^2 \mu^2} + \frac{c}{T \alpha^2 \mu^2} \left(\frac{2d \log \frac{1.25}{\delta}}{\epsilon^2} + \alpha^2 \varsigma^2 \right) \sim \mathcal{O}\left(\frac{d}{T \epsilon^2} \right)$$

Following a similar approach to that of Theorem 1 in Yang et al. (2019), let us consider the update step:

$$\begin{aligned}
\theta_{t+1} &= \theta_t - \alpha \nabla \tilde{f}(\theta) + b_t \\
\theta_{t+1} &= \theta_t - \alpha A(\theta_t - \theta^*) + \xi_t \\
\theta_{t+1} - \theta^* &= \theta_t - \theta^* - \alpha A(\theta_t - \theta^*) + \xi_t \\
&= (I - \alpha A)(\theta_t - \theta^*) + \xi_t
\end{aligned}$$

Where the term ξ_t corresponds to:

$$\xi_t = \alpha A((\theta_t - \theta^*) - \nabla \tilde{f}(\theta_t)) + b_t$$

Since sample gradients are, in expectation, equal to the full gradient and the Gaussian term b_t has mean zero, it follows that $\mathbb{E}[\xi_t] = 0$. Additionally, its variance can be bounded as:

$$\mathbb{E}[\|\xi_t\|^2] = \mathbb{E}[\|\alpha A((\theta_t - \theta^*) - \nabla \tilde{f}(\theta_t))\|^2] + \mathbb{E}[\|b_t\|^2] \le \alpha^2 \varsigma^2 + d\sigma^2$$

Expanding on the time steps:

$$\theta_t - \theta^* = (I - \alpha A)^t (\theta_0 - \theta^*) + \sum_{i=0}^{t-1} (I - \alpha A)^{t-i-1} \xi_i$$

Considering now the distance from the optimum and the average $\bar{\theta}_K$ of K terms:

$$\begin{aligned}
\bar{\theta}_K - \theta^* &= \frac{1}{K} \sum_{t=1}^{K} \theta_{ct} - \theta^* \\
&= \frac{1}{K} \sum_{t=1}^{K} \left((I - \alpha A)^{ct} (\theta_0 - \theta^*) + \sum_{i=0}^{ct-1} (I - \alpha A)^{ct-i-1} \xi_i \right) \\
&= \frac{1}{K} \left(\sum_{t=1}^{K} (I - \alpha A)^{ct} \right) (\theta_0 - \theta^*) + \frac{1}{K} \sum_{t=1}^{K} \sum_{i=0}^{ct-1} (I - \alpha A)^{ct-i-1} \xi_i
\end{aligned}$$

The first term of the right hand is a constant which we denote as X_K. Considering now the variance:

$$
\begin{aligned}
\mathbb{E}\left[\|\bar{\theta}_K - \theta^*\|^2\right] &= \mathbb{E}\left[\left\|X_K + \frac{1}{K}\sum_{t=1}^{K}\sum_{i=0}^{ct-1}(I-\alpha A)^{ct-i-1}\xi_i\right\|^2\right] \\
&= \|X_K\|^2 + \mathbb{E}\left[\left\|\frac{1}{K}\sum_{t=1}^{K}\sum_{i=0}^{ct-1}(I-\alpha A)^{ct-i-1}\xi_i\right\|^2\right] \\
&\quad + \frac{2}{K}X_K^T\sum_{t=1}^{K}\sum_{i=0}^{ct-1}(I-\alpha A)^{ct-i-1}\mathbb{E}[\xi_i] \\
&= \|X_K\|^2 + \mathbb{E}\left[\left\|\frac{1}{K}\sum_{t=1}^{K}\sum_{i=0}^{ct-1}(I-\alpha A)^{ct-i-1}\xi_i\right\|^2\right] \\
&= \|X_K\|^2 + \frac{1}{K^2}\mathbb{E}\left[\left\|\sum_{i=0}^{cK-1}\sum_{t=\lfloor i/c\rfloor+1}^{K}(I-\alpha A)^{ct-i-1}\xi_i\right\|^2\right]
\end{aligned}
$$

Since the ξ_i terms have mean zero and are independent:

$$
\begin{aligned}
\mathbb{E}\left[\|\bar{\theta}_K - \theta^*\|^2\right] &= \|X_K\|^2 + \frac{1}{K^2}\sum_{i=0}^{cK-1}\mathbb{E}\left[\left\|\sum_{t=\lfloor i/c\rfloor+1}^{K}(I-\alpha A)^{ct-i-1}\xi_i\right\|^2\right] \\
&\leq \|X_K\|^2 + \frac{1}{K^2}\sum_{i=0}^{cK-1}\left\|\sum_{t=\lfloor i/c\rfloor+1}^{K}(I-\alpha A)^{ct-i-1}\right\|_2^2\mathbb{E}\left[\|\xi_i\|^2\right] \\
&\leq \|X_K\|^2 + \frac{1}{K^2}\sum_{i=0}^{cK-1}\left\|\sum_{j=0}^{\infty}(I-\alpha A)^j\right\|_2^2\mathbb{E}\left[\|\xi_i\|^2\right]
\end{aligned}
$$

$\sum_{j=0}^{\infty}(I-\alpha A)^j$ converges as $0 < \alpha < \frac{1}{2}\|A\|_2$, and thus:

$$
\left\|\sum_{j=0}^{\infty}(I-\alpha A)^j\right\|_2^2 = \left\|(I-(I-\alpha A))^{-1}\right\|_2^2 = \left\|\frac{1}{\alpha}A^{-1}\right\|_2^2 \leq \frac{1}{\alpha^2\mu^2}
$$

Rewriting, we obtain:

$$
\mathbb{E}[\|\bar{\theta}_K - \theta^*\|^2] \leq \|X_K\|^2 + \frac{1}{K^2\alpha^2\mu^2}\sum_{i=0}^{cK-1}\mathbb{E}[\|\xi_i\|^2] \leq \|X_K\|^2 + \frac{c}{K\alpha^2\mu^2}(\alpha^2\varsigma^2 + d\sigma^2)
$$

Analyzing the constant term $\|X_K\|^2$:

$$\|X_K\|^2 = \left\| \frac{1}{K} \left(\sum_{t=1}^{K} (I - \alpha A)^{ct} \right) (\theta_0 - \theta^*) \right\|^2$$

$$\leq \frac{1}{K^2} \left\| \sum_{t=1}^{K} (I - \alpha A)^{ct} \right\|_2^2 \|\theta_0 - \theta^*\|^2$$

$$\leq \frac{1}{K^2} \left\| \sum_{t=1}^{\infty} (I - \alpha A)^{t} \right\|_2^2 \|\theta_0 - \theta^*\|^2$$

$$= \frac{1}{K^2} \left\| (I - (I - \alpha A))^{-1} \right\|_2^2 \|\theta_0 - \theta^*\|^2$$

$$= \frac{1}{K^2} \left\| \frac{1}{\alpha} A^{-1} \right\|_2^2 \|\theta_0 - \theta^*\|^2$$

$$\leq \frac{\|\theta_0 - \theta^*\|^2}{K^2 \alpha^2 \mu^2}$$

Running the algorithm for $T \sim \mathcal{O}(K)$ iterations:

$$\mathbb{E}\|\bar{\theta}_T - \theta^*\|^2 \leq \frac{\|\theta_0 - \theta^*\|^2}{T^2 \alpha^2 \mu^2} + \frac{c}{T \alpha^2 \mu^2} \left(\frac{2d \log \frac{1.25}{\delta}}{\epsilon^2} + \alpha^2 \varsigma^2 \right) \sim \mathcal{O}\left(\frac{d}{T \epsilon^2} \right)$$

Note that the squared distance to the optimum and the objective gap $f(\bar{\theta}_T) - f(\theta^*)$ can be directly compared, as they differ at most by a factor of μ since $f(\bar{\theta}_T) - f(\theta^*) \geq \frac{\mu}{2}\|\bar{\theta}_T - \theta^*\|^2$. This observation provides convergence to zero for the excess risk.

B   DETAILS ON EXPERIMENTS

B.1   DATA GENERATION FOR LINEAR REGRESSION

We use the mean squared error loss. Data points x_i are sampled as $x_i \sim \mathcal{N}(0, \sigma_x^2)$, initial weights θ_0 are sampled uniformly from $[0, 1]$, labels are sampled as $y_i \sim \mathcal{N}(\theta_0^T x_i, \sigma_y^2)$. We generate 256-dimensional points, setting variances to 1, and sampling 4096 points. The data generation follows that of Yang et al. (2019).

B.2   EXPERIMENTAL SETUP

We use PyTorch (Paszke et al., 2019) (version 1.13.1) and Opacus (Yousefpour et al.) (version 1.3.0) with Python 3.10.9 for all of our experiments. With the exception of experiments with *ResNet-50*, we conduct experiments on a single PC with an RTX-3080 GPU and Intel Core i9-11900KF CPU. For *ResNet-50*, we conduct experiments on a node of a computing cluster equipped with a A100 Tensor Core GPU and a AMD EPYC CPU.

For all our experiments, we rely on a conventional implementation of DP-SGD, using a constant learning rate and no momentum. We use a clipping norm of 1.

We train linear regression for 100 epochs with a constant learning rate of 10^{-4} and a batch size of 1. For Fashion-MNIST, we train logistic regression for 20 epochs with a constant learning rate of 0.1 and a batch size of 8.

For all experiments with deep learning models (cf. Section 4), we replace batch normalization layers with group normalization layers to allow for private training. For Fashion-MNIST, we train *ResNet-18* and *WRN-16-4* for 20 epochs with a constant learning rate of 2 and a logical batch size of 512. For CIFAR-10, we use a constant learning rate of 4 and a logical batch size of 4096, and train *ResNet-18* for 100 epochs, and *WRN-16-4* for 300 epochs. For all pre-trained models, we train for 50 epochs with a constant learning rate of 2 for $\epsilon = 1$ and 4 for $\epsilon = 8$, using a batch size of 4096.

For Fashion-MNIST, we replace the first convolutional layer of *ResNet-18* and *WRN-16-4* to allow for grey-scale images as input (i.e., 1 channel instead of 3 channels). For the models pre-trained on ImageNet, we replace the last (fully-connected) layer of *ResNet-18* and *ResNet-50* to allow for 10 and 100 classes, respectively for CIFAR-10 and CIFAR-100. We train only the last layer and keep the weights of the remaining layers frozen.

C ADDITIONAL RESULTS

In the following sections we provide additional results and visualizations from our experiments.

C.1 LINEAR REGRESSION

Figure 2: Results for linear regression with $\epsilon = 8$. (Left) Squared distance to the optimum, in agreement with convergence faster than $1/T$. (Right) Dependency of squared distance to the optimum on cycle length, compatible with a decrease in performance for larger cycle lengths; aggregate results for 3 runs.

C.2 LOGISTIC REGRESSION

Table 3: Accuracy and accuracy variance over last 5 iterates for logistic regression. Mean and standard deviation across 5 runs.

	DP-SGD	DP-SWA	$\text{Var}_{\text{DP-SGD}}$	$\text{Var}_{\text{DP-SWA}}$
$\epsilon = 1$	68.4 ± 0.3	$\mathbf{74.7 \pm 0.6}$	1.0 ± 0.2	$\mathbf{0.6 \pm 0.1}$
$\epsilon = 8$	75.3 ± 0.7	$\mathbf{78.9 \pm 0.3}$	0.4 ± 0.3	$\mathbf{0.3 \pm 0.1}$

Figure 3: Results for logistic regression. (Left) Better test accuracy and lower solution variance; aggregate results for 5 runs. (Right) Dependency of test accuracy on cycle length. Results for $\epsilon = 1$, compatible with a decrease in performance for larger cycle lengths; aggregate results for 3 runs.

C.3 Pre-trained *ResNet-18* and *ResNet-50*

We report additional results on CIFAR-10 and CIFAR-100 with *ResNet-18* and *Resnet-50* pre-trained on ImageNet. For compactness, we only report the order of magnitude for the accuracy variance over the last iterates, as accuracy variance is generally very low for the pre-trained models and comparable between DP-SGD and DP-SWA.

Table 4: Accuracy, accuracy variance over the last iterates, and $\%_{\text{AUC}}$ for non-convex objective functions with pre-trained models. Mean and standard deviation across 3 runs.

Dataset	ϵ	DP-SGD	DP-SWA	$\text{Var}_{\text{DP-SGD}}$	$\text{Var}_{\text{DP-SWA}}$	$\%_{\text{AUC}}$
CIFAR-10	1	83.9 ± 0.3	$\mathbf{84.0 \pm 0.3}$	10^{-6}	$\mathbf{10^{-7}}$	$+6.8 \pm 2.5$
ResNet-18	8	85.2 ± 0.1	$\mathbf{85.3 \pm 0.1}$	10^{-6}	10^{-6}	$+0.7 \pm 2$
CIFAR-10	1	85.5 ± 0.3	$\mathbf{85.6 \pm 0.3}$	10^{-7}	10^{-7}	$+1.5 \pm 5.9$
ResNet-50	8	87.1 ± 0.1	$\mathbf{87.10 \pm 0.01}$	10^{-7}	10^{-7}	$+2.0 \pm 2.7$
CIFAR-100	1	54.4 ± 0.2	$\mathbf{54.5 \pm 0.1}$	10^{-5}	10^{-5}	$+3.9 \pm 2.9$
ResNet-18	8	63.3 ± 0.2	63.3 ± 0.2	10^{-6}	$\mathbf{10^{-7}}$	$+2.7 \pm 1.0$
CIFAR-100	1	58.4 ± 0.1	58.4 ± 0.1	10^{-6}	10^{-6}	-1.7 ± 2.1
ResNet-50	8	$\mathbf{66.6 \pm 0.2}$	66.5 ± 0.2	10^{-6}	$\mathbf{10^{-7}}$	-2.1 ± 5.9

We can observe in Table 4 that DP-SWA offers no substantial improvement in terms of accuracy for pre-trained models, with some experiments providing identical accuracy. It should however be noted that our results are in contrast with the ones from Panda et al. (2022), who observe that weight averaging performs worse than the last iterate. On the contrary, we find DP-SWA solutions to be preferable as they are generally wider and more stable. *ResNet-50* on CIFAR-100 is the only case where we observe no benefit in terms of solution wideness.