OCR-MetaReasoning Benchmark: Evaluating the Meta-Reasoning Ability of MLLMs in Text-Rich Image Understanding

Abstract

Text-rich image understanding requires multimodal large language models (MLLMs) to organize OCR (Optical Character Recognition)-grounded evidence across words, layout, fields, charts, and visual correspondences. Existing evaluations often conflate text extraction with reasoning and rarely test whether models follow the required meta-reasoning direction: applying visible rules, abstracting hidden regularities, or recovering missing premises. To address these limitation, we introduce OCR-MetaReasoning, a controlled single-image benchmark that frames deduction, induction, and abduction as distinct reasoning directions and separately measures final-answer correctness and reasoning-process compliance. OCR-MetaReasoning contains 1,500 verified samples in a balanced 3×5 taxonomy crossing three reasoning types with five OCR-object categories, along with reference reasoning steps, automatic answer scoring, the Meta-Reasoning Macro Score (MRMS), and the Reasoning Process Compliance Score (RPCS). Experiments with representative closed-source and open-source MLLMs show that OCR-grounded meta-reasoning remains far from saturated: models struggle most with visible-rule application and layout-sensitive inference, and process-compliant rationales can still fail under exact answer scoring..

Figure 1: OCR-grounded abduction in OCR-MetaReasoning. The model infers the hidden intention behind "9$7$1" by grounding observed symbols in the keyboard layout. The example contrasts local symbol matching with layout-aware reasoning.

1 Introduction

Recent advances in multimodal large language models (MLLMs) have substantially improved visual question answering, document understanding, chart interpretation, and instruction following over mixed visual-textual inputs (Team, 2025; Hu et al., 2025a). Among these settings, text-rich image understanding is particularly important: receipts, forms, tables, notices, posters, webpages, and infographics encode meaning not only through recognized words but also through layout, fields, constraints, visual groupings, and cross-region correspondences. A capable MLLM therefore must do more than read OCR (Optical Character Recognition) tokens; it must determine how visible evidence should be organized to support the reasoning direction required by a question.

Despite this progress, robust reasoning over OCR-grounded evidence remains a fundamental challenge (Li et al., 2025a; Chen et al., 2024). This challenge goes beyond extracting visible text: models must determine how recognized words, layout,

fields, and visual correspondences should be used to support an answer. Many text-rich questions therefore require meta-reasoning, where a model applies an explicit rule to a case, infers a latent rule from aligned observations, or recovers a missing premise that explains an observed outcome. These directions correspond to deductive, inductive, and abductive reasoning, respectively, and expose different failure modes: models may copy salient text, rely on shallow field matching, or provide plausible but visually under-grounded explanations. Appendix A provides an abstract visual analysis of this distinction. Final-answer accuracy alone is therefore insufficient for diagnosing whether a model follows the intended reasoning process (Chen et al., 2024).

Recent benchmarks address parts of this problem. OCRBench v2 evaluates visual text localization and reasoning across broad text-centric scenarios (Fu et al., 2025); LogicOCR, Reasoning-OCR, and OCR-Reasoning build challenging OCR-based logical or complex reasoning tasks (Ye et al., 2025; He et al., 2025; Huang et al., 2025); and LogicVista, VisualPuzzles, and MME-Reasoning examine visual logical reasoning, knowledge-light puzzles, and explicit deductive/inductive/abductive reasoning in MLLMs (Xiao et al., 2024; Song et al., 2025; Yuan et al., 2025). Other work covers difficulty grading, multi-image reasoning, visual chain-of-thought supervision, long-chain visual reasoning, region-level prompting, and cross-modal reasoning-chain verification (Li et al., 2025b; Cheng et al., 2025; Shao et al., 2024; Zhou et al., 2025; Dong et al., 2025; Cai et al., 2024; Zhang et al., 2025). However, existing benchmarks are primarily organized by OCR task, document domain, visual puzzle type, or general logical ability. They do not make OCR-grounded meta-reasoning the central evaluation target while jointly controlling for reasoning direction, OCR object type, final-answer correctness, and process-level compliance.

To address these limitations, we propose OCR-MetaReasoning, a benchmark for evaluating the meta-reasoning ability of MLLMs in text-rich image understanding. The key design choice is to make the required reasoning direction explicit for each sample, so that a model is evaluated not only by whether it reads the relevant text but also by whether it organizes OCR-grounded evidence as deduction, induction, or abduction. This formulation separates OCR perception from reasoning behavior and enables fine-grained diagnosis across heterogeneous text-rich visual scenarios.

OCR-MetaReasoning is built around a balanced 3×5 taxonomy that crosses three meta-reasoning types with five OCR-object categories: transaction analysis, data interpretation, field dependency, document logic, and layout semantics. This design prevents strong performance on one familiar document type or one reasoning pattern from masking localized weaknesses. The benchmark also provides reference reasoning steps and an evaluation protocol that separates final-answer correctness from reasoning-process compliance. The final benchmark contains 1,500 single-image samples, automatic answer scoring, and process-level criteria for capability match, groundedness, step completeness, and non-hallucination.

Contributions. Our main contributions are summarized as follows:

- We introduce OCR-MetaReasoning, a benchmark centered on OCR-grounded meta-reasoning, with balanced coverage of deductive, inductive, and abductive reasoning across diverse text-rich image objects.
- We develop a unified construction and evaluation protocol that combines MLLM-assisted synthesis, human verification, reference reasoning steps, the Meta-Reasoning Macro Score (MRMS), and the Reasoning Process Compliance Score (RPCS).
- We evaluate representative closed-source and open-source MLLMs and identify persistent weaknesses in grounded rule verification and layout-sensitive inference, showing that current models remain far from saturated on OCR-grounded meta-reasoning.

2 Related Work

2.1 OCR Reasoning Benchmarks

Text-rich visual benchmarks have progressed from reading-oriented VQA, including TextVQA, ST-VQA, and DocVQA (Singh et al., 2019; Biten et al., 2019; Mathew et al., 2021), to structured reasoning over charts, documents, and OCR-heavy images (Masry et al., 2022; Liu et al., 2024; Fu et al., 2025). Recent benchmarks further examine logical reasoning from OCR cues: LogicOCR and Reasoning-OCR construct text-rich reasoning tasks (Ye et al., 2025; He et al., 2025), while OCR-Reasoning introduces challenging single-image samples with process annotations to reduce answer leakage from direct text extraction (Huang

Table 1: Comparison with closely related OCR, text-rich visual reasoning, and multimodal logical reasoning benchmarks. "OCR Meta-Reason." marks OCR-grounded meta-reasoning as the central target; "D/I/A" marks explicit deductive, inductive, and abductive coverage; and "Process Eval." marks process-level annotation or evaluation. ✓, △, and ×indicate full, partial, and absent coverage.

Benchmark	Ability	Text-rich OCR	OCR Meta-Reason.	D/I/A	Process Eval.	Object Diversity
OCRBench v2 (Fu et al., 2025)	Visual text localization and reasoning	✓	△	×	×	✓
LogicVista (Xiao et al., 2024)	Visual logical reasoning	×	×	△	△	×
VisualPuzzles (Song et al., 2025)	Knowledge-light multimodal reasoning	×	×	△	×	×
LogicOCR (Ye et al., 2025)	Logical reasoning on text-rich images	✓	△	△	×	△
MME-Reasoning (Yuan et al., 2025)	Multimodal logical reasoning	×	△	✓	×	×
Reasoning-OCR (He et al., 2025)	Logical reasoning from OCR cues	✓	△	×	×	△
OCR-Reasoning (Huang et al., 2025)	Complex text-rich image reasoning	✓	△	×	✓	△
OCR-MetaReasoning (Ours)	**OCR-grounded meta-reasoning**	✓	✓	✓	✓	✓

et al., 2025). Table 1 summarizes the coverage of OCR grounding, reasoning type, process evaluation, and object diversity in these benchmarks. Although these resources substantially advance OCR-centered evaluation, their organization remains primarily domain-, skill-, or scenario-driven. OCR-MetaReasoning instead uses the dominant reasoning direction as the primary organizing axis and requires each text-rich sample to instantiate deduction, induction, or abduction over OCR-grounded evidence.

2.2 Multimodal Reasoning Evaluation

Complementary benchmarks evaluate multimodal reasoning beyond OCR-centric settings. LogicVista studies logical reasoning in visual contexts (Xiao et al., 2024), VisualPuzzles reduces reliance on domain knowledge through knowledge-light visual puzzles (Song et al., 2025), and MME-Reasoning explicitly covers deductive, inductive, and abductive reasoning in MLLMs (Yuan et al., 2025). Beyond "Aha!" motivates our formulation by casting deduction, induction, and abduction as meta-abilities under a unified view of hypotheses, rules, and observations (Hu et al., 2025b). These benchmarks make reasoning a first-class evaluation target, but they do not focus on the evidence structure of OCR-rich images, including fields, tables, receipts, forms, footnotes, layout groupings, and cross-region textual dependencies. OCR-MetaReasoning bridges this gap by combining OCR-grounded evidence with explicit deductive, inductive, and abductive coverage, process-level evaluation, and diverse OCR-object categories.

3 OCR-MetaReasoning

3.1 Task Definition

OCR-MetaReasoning evaluates whether an MLLM can organize evidence in a text-rich image ac-

cording to the reasoning direction required by the question, rather than merely extracting visible text. Given a single image I and a question q, the model receives $x = (I, q)$ and outputs a solution process π and a final answer y. Relevant evidence may include recognized text, tables, chart marks, fields, checkboxes, layout groups, footnotes, and cross-region correspondences. We follow the view of meta-reasoning in terms of hypotheses, rules, and observations (Hu et al., 2025b): H denotes a hypothesis, premise, or candidate state; R denotes rules, constraints, mappings, or regularities; and O denotes observations, outcomes, or consequences grounded in the image.

The benchmark assigns each sample one dominant reasoning type, determined by the critical bottleneck in the solution path. Meta-deductive reasoning follows $H + R \rightarrow O$. The model must bind explicit rules, clauses, formulas, legends, thresholds, or field dependencies to image evidence, test a candidate case, and derive the rule-supported conclusion. Examples include verifying invoice totals under a printed tax rule and deciding eligibility from visible conditions and exception clauses.

Meta-inductive reasoning follows $H + O \rightarrow R$. The model must align multiple visible instances, abstract an unstated rule, and apply it to a missing, unlabeled, future, or hypothetical target. Examples include inferring a table-filling pattern, a legend-to-layout mapping, and a recurring field schema.

Meta-abductive reasoning follows $O + R \rightarrow H$. The model must start from an observed result, anomaly, goal, or downstream state and reason backward through visible constraints to recover the unique or minimal hidden premise. Examples include identifying a hidden discount from a final total and recovering the missing condition that explains an approval state.

When a problem contains local operations of

Figure 2: Overview of OCR-MetaReasoning construction. We collect text-rich seeds, synthesize OCR-grounded reasoning samples with MLLMs, verify them through human expert review and correction loops, and organize accepted samples by meta-reasoning type and OCR-object category.

multiple kinds, we label it according to the target variable that cannot be recovered by a simpler operation. For instance, a receipt item that asks for a masked discount from a visible final total is abductive even if the solution contains arithmetic, because the answer is a hidden premise rather than a forward-computed result.

3.2 Benchmark Construction

Two-axis taxonomy   As shown in Figure 2, OCR-MetaReasoning uses a 3×5 taxonomy: meta-reasoning type (deductive, inductive, abductive) and OCR-object category (transaction analysis, data interpretation, field dependency, document logic, layout semantics). These categories span receipts and invoices from CORD (Park et al., 2019) and WildReceipt (Sun et al., 2021); tables and charts from ChartQA (Masry et al., 2022) and ChartXiv (Wang et al., 2024); forms and certificates from FUNSD (Jaume et al., 2019) and DocVQA (Mathew et al., 2021); notices and policy-like documents from DocVQA (Mathew et al., 2021) and InfoVQA (Mathew et al., 2022); and posters, webpages, and infographics from InfoVQA (Mathew et al., 2022) and TextVQA (Singh et al., 2019). The final benchmark contains 1,500 samples, with 100 per type-category combination. This balance enables direct comparison across reasoning directions while controlling for text-rich visual content. Details of benchmark statistics are provided in Appendix D.

Seed collection   We first collect text-rich image seeds from public OCR-oriented resources and reconstructed images, covering receipts, forms, charts, notices, posters, webpages, and infographics. Candidate seeds are filtered by text density, legibility, structural richness, and the presence of cross-region or cross-field relations. We discard images for which answers can be obtained by copying one visible span or reading a single field without understanding the question.

MLLM-assisted synthesis   For each retained seed, an MLLM generator creates or revises a sample containing a text-rich image, question, canonical answer, and reference reasoning steps. The prompt specifies the target meta-reasoning type and OCR-object category. During synthesis, the generator makes the reasoning bottleneck explicit: deductive samples contain a visible rule or constraint and a candidate to verify; inductive samples contain multiple alignable support instances and a generalization target; and abductive samples contain an observed result or anomaly and enough constraints for backward recovery. Prompt and image revision add distractors, masked fields, exception clauses, non-adjacent evidence, or layout correspondences when the initial sample is too close to direct OCR extraction.

Human verification   Human experts verify each candidate with a taxonomy-aligned checklist. A valid sample must satisfy five conditions: the pri-

mary evidence is image-grounded; at least two evidence points are required; the answer is unique or uniquely minimal; the declared meta-reasoning type matches the dominant bottleneck; and the final answer can be automatically scored after normalization. Low-quality candidates enter prompt or image correction loops, while verified candidates enter the benchmark pool. This process filters ambiguous answers, unsupported rules, weak inductive evidence, non-unique abductive explanations, excessive external-knowledge dependence, and answer leakage from a single OCR span. Details of the construction process are provided in Appendix E.

3.3 Evaluation Protocol

Model input and answer scoring   During evaluation, each model receives the image and question, and is instructed to output numbered reasoning steps followed by a final answer line. Final-answer correctness is computed with a sample-specific scorer: normalized exact match for short strings, normalized numeric match for integer or floating-point answers, and micro-F1 for structured answers. We report scores by the three meta-reasoning types, by the five OCR-object categories, and by the overall macro metric.

Meta-Reasoning Macro Score   The main correctness metric is the Meta-Reasoning Macro Score (MRMS), which averages performance across the three reasoning directions:

$$MRMS = \frac{Acc_{\text{Ded}} + Acc_{\text{Ind}} + Acc_{\text{Abd}}}{3}.$$

Here Acc_{Ded}, Acc_{Ind}, and Acc_{Abd} are the mean final-answer scores on deductive, inductive, and abductive samples. The macro average prevents a model from masking a weak reasoning direction with strong performance on another direction.

Reasoning Process Compliance Score   Final-answer accuracy alone cannot determine whether a model follows the intended reasoning direction, so we report the Reasoning Process Compliance Score (RPCS) as a separate process-level metric. RPCS evaluates the visible solution process using four binary criteria: capability_match (c_{match}), which indicates whether the dominant process follows the target H, R, O direction; groundedness (c_{ground}), which indicates whether key claims are tied to image evidence or question constraints; step_completeness (c_{step}), which indicates whether necessary intermediate nodes are cov-

ered; and non_hallucination (c_{nonhall}), which indicates whether the process avoids unsupported rules, entities, fields, or values. The raw RPCS is the sum of these four criteria and is normalized to $[0, 1]$ for reporting:

$$RPCS = \frac{c_{\text{match}} + c_{\text{ground}} + c_{\text{step}} + c_{\text{nonhall}}}{4}.$$

RPCS is judged against the reference reasoning steps of the sample and the image context, but it does not require exact wording or identical step segmentation. Compressed or paraphrased reasoning receives credit when it preserves the required evidence bindings and reasoning direction. We report MRMS and RPCS separately to distinguish answer-level success from process-level compliance. Details of the evaluation process are provided in Appendix F.

4 Experiment

4.1 Setup

We evaluate representative closed-source and open-source models. The closed-source set includes GPT-5.4-Mini and its medium variant (OpenAI, 2026b), GPT-5.4 and its medium variant (OpenAI, 2026a), Gemini-3.1-Flash-Lite (Google, 2026a), Gemini-3.1-Pro-Preview (Google, 2026b), Claude-Sonnet-4.6 (Anthropic, 2026), Grok-4.20 (non-reasoning) (xAI, 2026), and Doubao-Seed-2.0-Lite and Pro (ByteDance, 2026). For open-source models, we use Kimi-K2.5 (Instant mode) (MoonshotAI, 2025), GLM-4.6V (ZaiOrg, 2025), and Qwen3-VL at 8B, 30B-A3B, and 235B-A22B, with both Instruct and Thinking variants (Qwen, 2025e,f,c,d,a,b). Detailed model descriptions and hyperparameter configurations are provided in Appendix C.

4.2 Main Results

Leaderboard and Saturation   Table 2 and Figure 3 show a clear performance hierarchy and substantial headroom on OCR-MetaReasoning. Gemini-3.1-Pro-Preview obtains the highest MRMS of 89.3, followed by GPT-5.4-Medium at 87.7 and Doubao-Seed-2.0-Pro at 86.4. The strongest open-source model, Qwen3-VL-235B-A22B-Thinking, reaches 81.5, which is 7.8 points below the leader. Closed-source models average 82.94 MRMS, compared with 73.40 for open-source models, yielding a 9.54-point gap. The heatmap follows the same ranking: top

Table 2: MLLM performance on OCR-MetaReasoning. The top three results in each column are highlighted in blue. D.I., D.L., F.D., L.S., and T.A. denote data interpretation, document logic, field dependency, layout semantics, and transaction analysis; DED., IND., and ABD. denote deductive, inductive, and abductive meta-reasoning. MRMS denotes the Meta-Reasoning Macro Score.

Model	OCR Object					Reasoning Type			MRMS
	D.I.	D.L.	F.D.	L.S.	T.A.	DED.	IND.	ABD.	
Closed-source Models									
Gemini-3.1-Pro-Preview	**96.0**	**93.0**	**91.7**	**76.2**	**89.7**	**80.7**	**93.1**	**94.1**	**89.3**
GPT-5.4-Medium	**92.3**	**90.8**	**90.0**	**77.6**	**87.5**	**80.6**	**91.5**	**90.8**	**87.7**
Doubao-Seed-2.0-Pro	**91.7**	87.8	87.9	**75.1**	**89.4**	**80.1**	**90.2**	**88.9**	**86.4**
Claude-Sonnet-4.6	88.5	**88.1**	**89.1**	69.9	86.0	77.5	87.6	87.9	84.3
Doubao-Seed-2.0-Lite	86.8	86.3	88.3	72.3	87.4	76.7	89.2	86.8	84.2
GPT-5.4-Mini-Medium	86.7	87.8	87.2	73.6	84.7	77.7	87.2	87.1	84.0
Gemini-3.1-Flash-Lite	87.7	84.9	87.8	72.2	83.8	78.4	85.4	86.2	83.3
GPT-5.4	87.4	85.0	88.0	69.1	85.7	77.9	85.7	85.5	83.0
Grok-4.20	79.3	76.6	79.8	61.9	78.3	70.3	77.4	78.0	75.2
GPT-5.4-Mini	72.7	75.1	76.9	61.0	74.4	70.7	75.3	70.1	72.0
Open-source Models									
Qwen3-VL-235B-A22B-Thinking	87.3	86.3	82.7	69.2	82.2	74.8	87.8	82.1	81.5
Kimi-K2.5	86.5	77.5	81.2	70.2	82.8	71.8	84.6	82.5	79.6
Qwen3-VL-235B-A22B-Instruct	80.7	78.8	80.7	69.5	75.5	72.5	80.9	77.7	77.0
GLM-4.6V	83.6	78.1	79.3	60.3	77.9	72.0	79.2	76.3	75.9
Qwen3-VL-30B-A3B-Thinking	81.5	78.6	77.8	60.5	75.1	69.1	81.8	73.3	74.7
Qwen3-VL-8B-Thinking	80.7	76.8	77.3	60.6	76.8	70.3	79.5	73.6	74.5
Qwen3-VL-30B-A3B-Instruct	72.1	66.6	67.0	55.1	64.4	64.0	67.9	63.2	65.0
Qwen3-VL-8B-Instruct	58.3	65.5	62.4	49.9	59.1	59.1	60.5	57.6	59.0

closed-source models are darker across most columns, while open-source models remain competitive but below the frontier.

OCR-Object Categories Reveal Layout Weaknesses The five OCR-object categories are uneven. Across all models, data interpretation has the highest average score, at 83.32, followed by field dependency at 81.95, document logic at 81.31, and transaction analysis at 80.04. Layout semantics averages only 66.90, 13.14 points below the next lowest category. This weakness persists in leading systems: GPT-5.4-Medium gives the best layout semantics score at 77.6, while Gemini-3.1-Pro-Preview and Doubao-Seed-2.0-Pro reach 76.2 and 75.1. The same models score above 87.5 on most non-layout categories, indicating that the benchmark distinguishes OCR text extraction and field-level reasoning from layout-sensitive inference over visual grouping and cross-region semantics.

Deduction Is the Main Reasoning Bottleneck The reasoning-type scores reveal a difficulty axis distinct from the object categories. Averaged across all models, inductive reasoning reaches 82.49 and

abductive reasoning reaches 80.09, whereas deductive reasoning reaches only 73.57. Among the top three MRMS models, deductive scores range only from 80.1 to 80.7, while inductive scores range from 90.2 to 93.1 and abductive scores range from 88.9 to 94.1. Because deductive samples require candidates to be verified against visible rules or constraints, current MLLMs appear stronger at aggregating repeated evidence or recovering plausible causes than at consistently applying OCR-grounded rules.

Reasoning Variants Help Unevenly Within Qwen3-VL, Thinking variants improve MRMS over Instruct variants, with larger gains at smaller scales: +15.5 at 8B, +9.7 at 30B-A3B, and +4.5 at 235B-A22B. The trend is not uniform across categories: Qwen3-VL-235B-A22B-Thinking improves all three reasoning types and most OCR-object categories, but is 0.3 points lower than its Instruct counterpart on layout semantics. These variants improve overall scores, especially at smaller scales, but do not remove the layout-sensitive bottleneck.

Figure 3: Heatmap of the top three closed-source models and the top three open-source models by MRMS in Table 2.

Closed-Source Advantage Is Broad but Uneven The closed-source advantage spans OCR-object categories and reasoning types, although column leaders differ. Gemini-3.1-Pro-Preview ranks first in MRMS and leads all columns except layout semantics, where GPT-5.4-Medium scores best at 77.6. Claude-Sonnet-4.6 also enters the top three for document logic and field dependency despite ranking fourth in MRMS. On average, closed-source models outperform open-source models by 9.54 MRMS points, with the largest reasoning-type gap in abduction at 12.25 points and the smallest in deduction at 7.86 points. The results show a stronger closed-source frontier, with specialization across OCR-object categories.

Balanced Taxonomy Prevents Single-Axis Saturation The balanced taxonomy prevents strong performance on one axis from hiding localized weaknesses. Qwen3-VL-235B-A22B-Thinking, the strongest open-source model, reaches 81.5 MRMS and 87.8 induction, but its 74.8 deduction and 69.2 layout semantics scores keep it behind leading closed-source models. Kimi-K2.5 shows a different profile: it leads open-source models on layout semantics (70.2), transaction analysis (82.8), and abduction (82.5), but lower document logic (77.5) and deduction (71.8) limit its MRMS to 79.6. These contrasts motivate using both axes: models must align visual text evidence with the required reasoning direction across heterogeneous OCR-object categories.

5 Further Discussion

Process Compliance Is High but Uneven Table 3 examines whether visible solution processes follow the intended OCR-grounded meta-reasoning direction. RPCS separates process quality from final correctness and shows uneven compliance: average RPCS ranges from 72.5 to 96.2, with a mean of 87.51. Capability match and groundedness average 93.64 and 92.23, while step completeness and non-hallucination drop to 81.59 and 82.53. Most models select plausible reasoning directions and attach claims to image evidence; larger failures come from skipped intermediate evidence and unsupported rules, entities, fields, or values. Across reasoning types, normalized RPCS is highest for deduction at 89.93, followed by abduction at 86.59 and induction at 85.99. Thus, the deductive MRMS bottleneck is not explained by the surface form of the reasoning process alone.

Strong Processes Do Not Guarantee Correct Answers The comparison between RPCS and MRMS shows that compliant reasoning traces are easier to obtain than correct answers: every model has a positive Δ, from +4.9 for GPT-5.4-Mini-Medium to +13.5 for Qwen3-VL-8B-Instruct, with an average of +8.81. The strongest closed-source systems remain high on both metrics: Gemini-3.1-Pro-Preview reaches 96.2 average RPCS and 89.3 MRMS, and GPT-5.4-Medium reaches 95.2 and 87.7. Yet rank differences reveal a mismatch between process scores and answer scores: Doubao-Seed-2.0-Lite has higher average RPCS than Doubao-Seed-2.0-Pro, at 93.3 versus 93.0, but lower MRMS, at 84.2 versus 86.4. Kimi-K2.5 like-

Table 3: Comparison between RPCS and MRMS. CM, GRD, STEP, and NH denote the RPCS criteria *capability_match*, *groundedness*, *step_completeness*, and *non_hallucination*. DED., IND., and ABD. report normalized RPCS for deductive, inductive, and abductive meta-reasoning. AVG. is the mean normalized RPCS, MRMS is the answer-level score from Table 2, and Δ is AVG. RPCS minus MRMS.

| Model | Process Criteria | | | | RPCS by Reasoning Type | | | | Outcome Contrast | |
	CM	GRD	STEP	NH	DED.	IND.	ABD.	AVG.	MRMS	Δ
Closed-source										
Gemini-3.1-Pro-Preview	98.7	98.7	92.6	94.5	95.2	96.7	96.6	**96.2**	**89.3**	+6.9
GPT-5.4-Medium	98.5	97.7	91.4	93.1	95.0	95.3	95.2	**95.2**	**87.7**	+7.5
Doubao-Seed-2.0-Pro	96.7	96.6	87.5	91.3	93.5	92.0	93.5	93.0	**86.4**	+6.6
Claude-Sonnet-4.6	97.1	95.3	91.6	83.7	93.0	90.8	92.0	91.9	84.3	+7.6
Doubao-Seed-2.0-Lite	97.0	96.5	90.3	89.7	93.8	93.0	93.2	**93.3**	84.2	+9.1
GPT-5.4-Mini-Medium	94.9	94.1	75.1	91.7	90.5	86.1	90.2	88.9	84.0	+4.9
Gemini-3.1-Flash-Lite	93.3	95.7	82.8	85.3	92.7	86.1	89.1	89.3	83.3	+6.0
GPT-5.4	96.9	95.8	89.3	88.1	94.0	91.1	92.3	92.5	83.0	+9.5
Grok-4.20	93.7	91.7	81.5	76.0	88.3	83.5	85.4	85.7	75.2	+10.5
GPT-5.4-Mini	91.3	87.7	68.5	78.0	86.1	78.3	79.8	81.4	72.0	+9.4
Open-source										
Qwen3-VL-235B-A22B-Thinking	95.1	93.1	85.4	84.7	90.5	90.0	88.2	89.6	81.5	+8.1
Kimi-K2.5	96.7	96.0	89.7	82.0	93.0	90.5	89.8	91.1	79.6	+11.5
Qwen3-VL-235B-A22B-Instruct	93.5	92.4	84.2	77.9	90.5	84.6	85.9	87.0	77.0	+10.0
GLM-4.6V	90.0	88.1	75.4	82.9	87.1	83.0	82.3	84.1	75.9	+8.2
Qwen3-VL-30B-A3B-Thinking	91.5	89.8	76.7	79.5	87.2	83.9	82.2	84.4	74.7	+9.7
Qwen3-VL-8B-Thinking	91.1	86.9	75.1	77.5	85.4	81.7	81.0	82.7	74.5	+8.2
Qwen3-VL-30B-A3B-Instruct	86.1	83.6	69.3	66.0	83.1	73.0	72.7	76.3	65.0	+11.3
Qwen3-VL-8B-Instruct	83.5	80.5	62.2	63.7	79.8	68.3	69.3	72.5	59.0	+13.5

wise has the highest open-source average RPCS at 91.1, while its MRMS of 79.6 remains below the 81.5 of Qwen3-VL-235B-A22B-Thinking. Qualitative cases in Appendix H show the same mismatch across deductive, inductive, and abductive samples. Accuracy still depends on precise OCR-grounded operations, not only plausible grounded explanations.

Process and Outcome Gaps Identify Training Targets These results refine the main findings. Closed-source models exceed open-source models by 7.28 points in average RPCS, less than the 9.54-point MRMS gap, and their average Δ is lower, at 7.80 versus 10.06. The largest criterion gap is non-hallucination, where closed-source systems average 87.14 and open-source systems average 76.78; the smallest is capability match, at 95.81 versus 90.94. Deductive RPCS exceeds deductive MRMS by 16.36 points on average, versus 3.51 for induction and 6.50 for abduction. The main challenge is less about making models state the intended reasoning pattern than about converting mostly compliant processes into exact OCR-grounded verification, complete intermediate coverage, and hallucination-free final decisions. These gaps justify reporting MRMS and RPCS separately.

6 Conclusion

This work addresses the challenge of evaluating meta-reasoning in text-rich image understanding, where models must go beyond OCR extraction and organize evidence under the correct reasoning direction. We introduce OCR-MetaReasoning, which adapts deduction, induction, and abduction to OCR-centered scenarios and evaluates models across representative document, chart, transaction, form, and layout reasoning tasks. The benchmark provides a unified evaluation protocol that measures both final-answer correctness and reasoning-process compliance. Experiments with representative MLLMs reveal substantial differences across reasoning types and OCR-object categories, showing that current models still struggle with grounded rule verification and layout-sensitive inference. While OCR-MetaReasoning focuses on single-image settings and uses judge-assisted process evaluation, future work can extend it to multi-page evidence chains and training methods for more faithful, direction-aware OCR reasoning.

Limitations

OCR-MetaReasoning is a controlled diagnostic benchmark for single-image OCR-grounded meta-reasoning. This scope helps isolate how models bind visible textual evidence to deductive, inductive, and abductive reasoning directions, but it does not cover multi-page documents, cross-image evidence aggregation, retrieval-augmented document reasoning, or interactive clarification. The reported results should therefore be interpreted within single-image text-rich reasoning settings.

The dataset is balanced by design rather than sampled from a natural task distribution. Equal coverage across meta-reasoning types and OCR-object categories supports controlled comparison, but it does not reflect real-world category frequencies. Although samples are verified through human review and programmatic audits, the use of reconstructed images and MLLM-assisted synthesis may still introduce distributional differences from fully natural documents. The reasoning labels should also be read as dominant bottleneck annotations, since individual examples may contain local arithmetic, lookup, comparison, or extraction steps.

RPCS should also be viewed as a process diagnostic rather than direct evidence of internal model reasoning. The judge is outcome-isolated and structurally validated, but it still evaluates visible rationales and cannot fully rule out plausible post-hoc explanations. Future work can extend OCR-MetaReasoning to multi-page evidence chains, natural-distribution test sets, compositional reasoning annotations, and stronger verification methods that link intermediate steps to OCR evidence.

References

Anthropic. 2026. Introducing Claude Sonnet 4.6. https://www.anthropic.com/news/claude-sonnet-4-6. Accessed: May 2026.

Ali Furkan Biten, Ruben Tito, Andres Mafla, Lluis Gomez, Marçal Rusinol, Ernest Valveny, CV Jawahar, and Dimosthenis Karatzas. 2019. Scene text visual question answering. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 4291–4301.

ByteDance. 2026. Seed-2. https://seed.bytedance.com/zh/seed2. Accessed: May 2026.

Mu Cai, Haotian Liu, Siva Karthik Mustikovela, Gregory P Meyer, Yuning Chai, Dennis Park, and Yong Jae Lee. 2024. Vip-llava: Making large multimodal models understand arbitrary visual prompts. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12914–12923.

Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu, Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, Wei Ye, Yue Zhang, Yi Chang, Philip S. Yu, Qiang Yang, and Xing Xie. 2024. A survey on evaluation of large language models. *ACM Trans. Intell. Syst. Technol.*, 15(3):39:1–39:45.

Yangyi Chen, Karan Sikka, Michael Cogswell, Heng Ji, and Ajay Divakaran. 2024. Measuring and improving chain-of-thought reasoning in vision-language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 192–210.

Ziming Cheng, Binrui Xu, Lisheng Gong, Zuhe Song, Tianshuo Zhou, Shiqi Zhong, Siyu Ren, Mingxiang Chen, Xiangchao Meng, Yuxin Zhang, Yanlin Li, Lei Ren, Wei Chen, Zhiyuan Huang, Mingjie Zhan, Xiaojie Wang, and Fangxiang Feng. 2025. Evaluating mllms with multimodal multi-image reasoning benchmark. *CoRR*, abs/2506.04280.

Yuhao Dong, Zuyan Liu, Hai-Long Sun, Jingkang Yang, Winston Hu, Yongming Rao, and Ziwei Liu. 2025. Insight-v: Exploring long-chain visual reasoning with multimodal large language models. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 9062–9072.

Ling Fu, Biao Yang, Zhebin Kuang, Jiajun Song, Yuzhe Li, Linghao Zhu, Qidi Luo, Xinyu Wang, Hao Lu, Mingxin Huang, Zhang Li, Guozhi Tang, Bin Shan, Chunhui Lin, Qi Liu, Binghong Wu, Hao Feng, Hao Liu, Can Huang, and 5 others. 2025. Ocrbench v2: An improved benchmark for evaluating large multimodal models on visual text localization and reasoning. *CoRR*, abs/2501.00321.

Google. 2026a. Gemini 3.1 flash-lite preview. https://ai.google.dev/gemini-api/docs/models/gemini-3.1-flash-lite-preview. Accessed: May 2026.

Google. 2026b. Gemini 3.1 pro preview. https://ai.google.dev/gemini-api/docs/models/gemini-3.1-pro-preview. Accessed: May 2026.

Haibin He, Maoyuan Ye, Jing Zhang, Xiantao Cai, Juhua Liu, Bo Du, and Dacheng Tao. 2025. Reasoning-ocr: Can large multimodal models solve complex logical reasoning problems from ocr cues? *arXiv preprint arXiv:2505.12766*.

Anwen Hu, Haiyang Xu, Liang Zhang, Jiabo Ye, Ming Yan, Ji Zhang, Qin Jin, Fei Huang, and Jingren Zhou. 2025a. mplug-docowl2: High-resolution compressing for ocr-free multi-page document understanding.

In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5817–5834.

Zhiyuan Hu, Yibo Wang, Hanze Dong, Yuhui Xu, Amrita Saha, Caiming Xiong, Bryan Hooi, and Junnan Li. 2025b. Beyond'aha!': Toward systematic meta-abilities alignment in large reasoning models. *arXiv preprint arXiv:2505.10554*.

Mingxin Huang, Yongxin Shi, Dezhi Peng, Songxuan Lai, Zecheng Xie, and Lianwen Jin. 2025. Ocr-reasoning benchmark: Unveiling the true capabilities of mllms in complex text-rich image reasoning. *arXiv preprint arXiv:2505.17163*.

Guillaume Jaume, Hazim Kemal Ekenel, and Jean-Philippe Thiran. 2019. Funsd: A dataset for form understanding in noisy scanned documents. *arXiv preprint arXiv:1905.13538*.

Ming Li, Ruiyi Zhang, Jian Chen, Chenguang Wang, Jiuxiang Gu, Yufan Zhou, Franck Dernoncourt, Wanrong Zhu, Tianyi Zhou, and Tong Sun. 2025a. Towards visual text grounding of multimodal large language model. *arXiv preprint arXiv:2504.04974*.

Siqi Li, Yufan Shen, Xiangnan Chen, Jiayi Chen, Hengwei Ju, Haodong Duan, Song Mao, Hongbin Zhou, Bo Zhang, Bin Fu, Pinlong Cai, Licheng Wen, Botian Shi, Yong Liu, Xinyu Cai, and Yu Qiao. 2025b. Gdi-bench: A benchmark for general document intelligence with vision and reasoning decoupling. *CoRR*, abs/2505.00063.

Yuliang Liu, Zhang Li, Mingxin Huang, Biao Yang, Wenwen Yu, Chunyuan Li, Xu-Cheng Yin, Cheng-Lin Liu, Lianwen Jin, and Xiang Bai. 2024. Ocr-bench: on the hidden mystery of ocr in large multimodal models. *Science China Information Sciences*, 67(12):220102.

Ahmed Masry, Xuan Long Do, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. 2022. Chartqa: A benchmark for question answering about charts with visual and logical reasoning. In *Findings of the association for computational linguistics: ACL 2022*, pages 2263–2279.

Minesh Mathew, Viraj Bagal, Rubèn Tito, Dimosthenis Karatzas, Ernest Valveny, and CV Jawahar. 2022. Infographicvqa. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1697–1706.

Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. 2021. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pages 2200–2209.

MoonshotAI. 2025. Kimi-k2.5. https://huggingface.co/moonshotai/Kimi-K2.5. Accessed: May 2026.

OpenAI. 2026a. Introducing GPT-5.4. https://openai.com/index/introducing-gpt-5-4/. Accessed: May 2026.

OpenAI. 2026b. Introducing GPT-5.4 mini and nano. https://openai.com/index/introducing-gpt-5-4-mini-and-nano/. Accessed: May 2026.

Seunghyun Park, Seung Shin, Bado Lee, Junyeop Lee, Jaeheung Surh, Minjoon Seo, and Hwalsuk Lee. 2019. Cord: a consolidated receipt dataset for post-ocr parsing. In *Workshop on document intelligence at NeurIPS*, volume 2019, page 5.

Qwen. 2025a. Qwen3-vl-235b-a22b-instruct. https://huggingface.co/Qwen/Qwen3-VL-235B-A22B-Instruct. Accessed: January 2026.

Qwen. 2025b. Qwen3-vl-235b-a22b-thinking. https://huggingface.co/Qwen/Qwen3-VL-235B-A22B-Thinking. Accessed: May 2026.

Qwen. 2025c. Qwen3-vl-30b-a3b-instruct. https://huggingface.co/Qwen/Qwen3-VL-30B-A3B-Instruct. Accessed: January 2026.

Qwen. 2025d. Qwen3-vl-30b-a3b-thinking. https://huggingface.co/Qwen/Qwen3-VL-30B-A3B-Thinking. Accessed: May 2026.

Qwen. 2025e. Qwen3-vl-8b-instruct. https://huggingface.co/Qwen/Qwen3-VL-8B-Instruct. Accessed: January 2026.

Qwen. 2025f. Qwen3-vl-8b-thinking. https://huggingface.co/Qwen/Qwen3-VL-8B-Thinking. Accessed: May 2026.

Hao Shao, Shengju Qian, Han Xiao, Guanglu Song, Zhuofan Zong, Letian Wang, Yu Liu, and Hongsheng Li. 2024. Visual cot: Advancing multi-modal language models with a comprehensive dataset and benchmark for chain-of-thought reasoning. *Advances in Neural Information Processing Systems*, 37:8612–8642.

Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. 2019. Towards vqa models that can read. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 8317–8326.

Yueqi Song, Tianyue Ou, Yibo Kong, Zecheng Li, Graham Neubig, and Xiang Yue. 2025. Visualpuzzles: Decoupling multimodal reasoning evaluation from domain knowledge. *arXiv preprint arXiv:2504.10342*.

Hongbin Sun, Zhanghui Kuang, Xiaoyu Yue, Chenhao Lin, and Wayne Zhang. 2021. Spatial dual-modality graph reasoning for key information extraction. *arXiv preprint arXiv:2103.14470*.

Qwen Team. 2025. Qwen3-vl technical report. *CoRR*, abs/2511.21631.

Zirui Wang, Mengzhou Xia, Luxi He, Howard Chen, Yitao Liu, Richard Zhu, Kaiqu Liang, Xindi Wu, Haotian Liu, Sadhika Malladi, Alexis Chevalier, Sanjeev Arora, and Danqi Chen. 2024. Charxiv: Charting gaps in realistic chart understanding in multimodal llms. In *Advances in Neural Information Processing Systems 38: Annual Conference on Neural Information Processing Systems 2024, NeurIPS 2024, Vancouver, BC, Canada, December 10 - 15, 2024*.

xAI. 2026. Grok 4.20 non-reasoning. `https://docs.x.ai/developers/models/grok-4.20-non-reasoning`. Accessed: May 2026.

Yijia Xiao, Edward Sun, Tianyu Liu, and Wei Wang. 2024. Logicvista: Multimodal llm logical reasoning benchmark in visual contexts. *arXiv preprint arXiv:2407.04973*.

Maoyuan Ye, Haibin He, Qihuang Zhong, Jing Zhang, Juhua Liu, and Bo Du. 2025. Logicocr: Do your large multimodal models excel at logical reasoning on text-rich images? *arXiv preprint arXiv:2505.12307*.

Jiakang Yuan, Tianshuo Peng, Yilei Jiang, Yiting Lu, Renrui Zhang, Kaituo Feng, Chaoyou Fu, Tao Chen, Lei Bai, Bo Zhang, and Xiangyu Yue. 2025. Mme-reasoning: A comprehensive benchmark for logical reasoning in mllms. *CoRR*, abs/2505.21327.

ZaiOrg. 2025. Glm-4.6v. `https://huggingface.co/zai-org/GLM-4.6V`. Accessed: May 2026.

Jusheng Zhang, Kaitong Cai, Xiaoyang Guo, Sidi Liu, Qinhan Lv, Ruiqi Chen, Jing Yang, Yijia Fan, Xiaofei Sun, Jian Wang, Ziliang Chen, Liang Lin, and Keze Wang. 2025. Mm-cot:a benchmark for probing visual chain-of-thought reasoning in multimodal models. *CoRR*, abs/2512.08228.

Yiyang Zhou, Haoqin Tu, Zijun Wang, Zeyu Wang, Niklas Muennighoff, Fan Nie, Yejin Choi, James Zou, Chaorui Deng, Shen Yan, Haoqi Fan, Cihang Xie, Huaxiu Yao, and Qinghao Ye. 2025. When visualizing is the first step to reasoning: Mira, a benchmark for visual chain-of-thought. *CoRR*, abs/2511.02779.

A Analysis of the Meta-Reasoning Type

Figure 4 illustrates the motivation for OCR-grounded meta-reasoning. The upper panel treats OCR evidence as structured visual information rather than as a plain text transcript. Words, layout, fields, and charts each provide distinct evidence for reasoning. The three lower panels distinguish questions according to the direction of

Figure 4: Abstract illustration of OCR-grounded meta-reasoning.

reasoning they require. Deduction applies visible rules to image-grounded cases, so errors often arise when a model copies a salient text span without verifying all relevant conditions. Induction infers hidden regularities from aligned observations, which makes shallow field matching a common source of mistakes. Abduction reasons backward from an observed result to recover a missing premise, where the main risk is an explanation that is plausible but insufficiently grounded in the image. This distinction motivates the evaluation design of OCR-MetaReasoning. The benchmark evaluates both final-answer correctness and reasoning-process compliance, since the same answer can result from different organizations of visual evidence.

B Effect of Reasoning Hints

We run an ablation study to test whether explicit reasoning hints improve model performance. The comparison uses two prompting strategies. The generic reasoning hint appends the same instruction to every question: "Before answering, think step by step and carefully verify the evidence in the image." The task-specific hint instead gives an instruction written for the target meta-reasoning type.

Setting / Split	No Hint	Task-specific Hint	Δ
Overall answer score	70.08	71.09	+1.01
Full-score rate	68.18	69.10	+0.92
Meta-abductive	69.28	71.46	+2.18
Meta-deductive	67.25	68.16	+0.91
Meta-inductive	73.72	73.66	-0.06

Table 4: Paired comparison between the no-hint and task-specific-hint settings over the six shared models. Scores are percentages.

Setting	Overall	Abductive	Deductive	Inductive
No Hint	59.03	57.60	59.06	60.45
Generic Reasoning	62.95	62.46	61.43	64.95
Task-specific Hint	63.35	63.34	63.39	63.32

Table 5: Generic reasoning control for Qwen3-VL-8B-Instruct. Scores are percentages.

For abductive samples, it asks the model to work backward from the stated outcome, identify the hidden constraint, compare plausible candidates, and eliminate alternatives. For deductive samples, it asks the model to extract the rule or threshold, list candidate cases, and verify every condition, including boundaries, units, legends, and exceptions. For inductive samples, it asks the model to infer the underlying pattern from multiple examples, test a contrasting case, and apply the pattern to the target.

For a fair paired comparison, we restrict the analysis to the six models with results under both the no-hint and task-specific-hint settings: Qwen3-VL-8B-Instruct, Qwen3-VL-8B-Thinking, Qwen3-VL-30B-A3B-Instruct, Qwen3-VL-30B-A3B-Thinking, GPT-5.4-Mini, and Grok-4.20. These models provide the same 9,000 paired model-sample evaluations. Task-specific hints increase the average final-answer score from 70.08 to 71.09, corresponding to a gain of +1.01 percentage points with a paired bootstrap 95% confidence interval of [+0.22, +1.78]. The full-score rate also increases from 68.18 to 69.10 (+0.92 points). The gain is largest for abductive reasoning (+2.18 points), smaller for deductive reasoning (+0.91 points), and nearly absent for inductive reasoning (-0.06 points).

We also run a smaller generic-reasoning control on Qwen3-VL-8B-Instruct. The generic control raises the score from 59.03 to 62.95 (+3.91 points, 95% CI [+1.96, +5.91]), whereas the task-specific hint reaches 63.35 (+4.31 points over the no-hint setting). The task-specific hint achieves the highest score, but its margin over the generic control is small (+0.40 points, 95% CI [-1.57, +2.38]).

These results suggest that explicit reasoning guidance improves final-answer performance, with the clearest gains on abductive and deductive reasoning. The control experiment points to general evidence-checking guidance as a major source of the improvement, rather than task-specific wording by itself. We treat the hint effect as an answer-level improvement, not as direct evidence of higher reasoning-process quality.

The effect is also model-dependent. The score of Grok-4.20 decreases by 2.19 points under task-specific hints, mainly on data-interpretation and integer-answer cases. The score of Qwen3-VL-8B-Thinking decreases by 0.56 points, mainly on exact-match string answers. In the inspected errors, hints sometimes lead to excessive deliberation, incorrect candidate filtering, misreading of OCR details, or drift in answer granularity. RPCS also does not improve under hints, indicating that the primary benefit is higher final-answer accuracy rather than consistently better judged reasoning processes.

C Details of Experimental Setup

We evaluate both proprietary and open-source models. The ten closed-source models, including GPT-5.4, GPT-5.4-Mini, and Gemini-3.1-Pro-Preview, are accessed through their official APIs with default settings. The open-source models are evaluated using Hugging Face implementations. Generation hyperparameters follow the corresponding official technical reports. The Qwen3-VL-Instruct series uses $T = 0.7$, $top\_p = 0.8$, $top\_k = 20$, a repetition penalty of 1.0, and a presence penalty of 1.5. The Qwen3-VL-Thinking series uses $T = 1.0$, $top\_p = 0.05$, $top\_k = 20$, a repetition penalty of 1.0, and a presence penalty of 1.5. Kimi-K2.5-Instant uses $T = 1.0$ and $top\_p = 0.95$, whereas GLM-4.6V uses $T = 0.8$, $top\_p = 0.6$, $top\_k = 2$, and a repetition penalty of 1.1. Table 13 summarizes the specifications of all evaluated models.

D Details of Dataset Statistics

This section reports the composition of OCR-MetaReasoning. Following the two-axis design in Figure 2, we analyze the benchmark by meta-reasoning type, OCR-object category, and sample complexity. Table 6 summarizes the corresponding statistics.

Category	# Instances
Meta-deductive Reasoning	500
Meta-inductive Reasoning	500
Meta-abductive Reasoning	500
Transaction Analysis	300
Data Interpretation	300
Field Dependency	300
Document Logic	300
Layout Semantics	300
String Answers	513
Integer Answers	561
Floating-point Answers	146
JSON Answers	280
Exact-Match Scoring	513
Numeric Scoring	707
JSON Micro-F1 Scoring	280
Total Instances	1,500
Average # Tokens per Question	75.77
Maximum # Tokens per Question	201
Minimum # Tokens per Question	21
Average # Reasoning Steps	4.22
Maximum # Reasoning Steps	8
Minimum # Reasoning Steps	2
Average # Images per Sample	1.00

Table 6: Statistics of the OCR-MetaReasoning benchmark.

D.1 Meta-Reasoning Taxonomy and OCR-Object Distribution

OCR-MetaReasoning contains 1,500 instances, evenly divided across the three meta-reasoning types. Meta-deductive, meta-inductive, and meta-abductive reasoning each contain 500 samples. Because the three reasoning types have equal size, the overall metric is not dominated by any single reasoning direction and supports direct comparison across forward rule application, pattern abstraction, and backward explanation.

The dataset is also balanced across five OCR-object categories: transaction analysis, data interpretation, field dependency, document logic, and layout semantics. Each category contains 300 instances, and every cell in the 3×5 taxonomy contains 100 samples. This balance reduces confounding between reasoning type and visual document genre. For example, deductive and abductive reasoning are both evaluated on receipts, tables, forms, long document snippets, and layout-centric images, rather than being tied to a single source format.

D.2 Answer Formats and Scoring Diversity

The answer space covers multiple formats, preventing the benchmark from reducing to a single response style. Integer answers are the most common format, with 561 instances, followed by 513 string answers, 280 JSON answers, and 146 floating-point answers. Scoring functions are assigned at the sample level: 707 instances use numeric matching, 513 use normalized exact match, and 280 use JSON micro-F1. This mix reflects the range of OCR-grounded reasoning tasks. Some samples require a single year, amount, count, or percentage, whereas others require an entity name, a formatted text span, or a structured set of field values.

D.3 Sample Complexity

Each instance uses a single text-rich image, which separates image-grounded reasoning from multi-image retrieval or document aggregation. Although the setting is controlled, the questions still require substantial reasoning. The average question length is 75.77 tokens, with a range from 21 to 201 tokens. Reference solutions contain 4.22 reasoning steps on average, with a minimum of 2 and a maximum of 8. Most samples therefore require several intermediate operations, such as locating separated evidence, binding a rule to a visible field, abstracting a repeated pattern, or tracing a result back to a hidden premise. The benchmark focuses on structured reasoning rather than direct OCR span extraction.

E Details of Benchmark Construction

The construction process follows Section 3.2 and Figure 2, with reliability checks through both automatic validation and human review. Each benchmark instance is verified as a complete record containing a text-rich image, a question, a canonical answer, an answer type, a scoring metric, a meta-reasoning label, an OCR-object label, and a reference reasoning path. Automatic validation detects structural and scoring failures, while human review checks semantic validity, answer uniqueness, and taxonomy fit.

E.1 Construction Pipeline

Seed selection We collect text-rich visual seeds from public OCR-oriented resources and reconstructed images, including receipts, charts, forms, policy-like documents, posters, webpages, and infographics. Candidate seeds are retained only when the visible content requires reasoning over OCR evidence rather than direct copying. We reject seeds whose answer can be copied from a single visible text span, whose relevant text is illegible, or whose solution depends primarily on external knowledge rather than the image.

Reliability Check	Passed / Total	Rate
Required annotation fields are complete	1,500 / 1,500	100.0%
Referenced image files exist	1,500 / 1,500	100.0%
Unique sample IDs within reasoning splits	1,500 / 1,500	100.0%
Unique normalized questions	1,500 / 1,500	100.0%
Unique normalized question–answer pairs	1,500 / 1,500	100.0%
Answer type is consistent with scoring metric	1,500 / 1,500	100.0%
JSON answers are parseable	280 / 280	100.0%
Numeric answers are parseable	707 / 707	100.0%
Reference reasoning paths have at least two steps	1,500 / 1,500	100.0%

Table 7: Programmatic reliability audit of the released benchmark. The audit checks all 1,500 instances.

Taxonomy-controlled synthesis For each accepted seed, the generator receives a target meta-reasoning type and OCR-object category. Deductive samples require a visible rule, threshold, clause, legend, formula, or field dependency that must be applied to image evidence. Inductive samples require multiple visible support cases from which a pattern can be inferred and then applied to a target. Abductive samples require an observed result, anomaly, or downstream state from which the hidden premise must be recovered through backward reasoning. This taxonomy control prevents the benchmark from collapsing into generic OCR question answering.

Human verification and correction Human experts review each candidate using a checklist aligned with the benchmark definition. A sample is accepted only when the primary evidence is grounded in the image and at least two evidence points are required. It must also have a unique or uniquely minimal answer, a meta-reasoning label that matches the primary reasoning bottleneck, an OCR-object label that matches the visual scenario, and an answer that can be scored automatically after normalization. Candidates that fail any of these requirements are revised or discarded. Common rejection cases include answer leakage from one OCR span, unsupported rules, ambiguous wording, non-unique abductive explanations, weak inductive evidence, and mismatched answer formats.

E.2 Reliability Audit

After human verification, we run a programmatic audit over all released benchmark files. The audit checks annotation completeness, image availability, ID uniqueness, exact question duplication, answer-parser validity, consistency between answer type and scoring metric, and the presence of multi-step reference reasoning. Table 7 summarizes the results.

The audit confirms that all 1,500 instances contain the required fields and valid image references. All normalized questions and question–answer pairs are unique, which reduces the risk that benchmark performance is inflated by repeated prompts. The scoring metadata is also internally consistent: 561 integer and 146 floating-point answers use numeric scoring, 513 string answers use normalized exact match, and all 280 JSON answers are parseable and use JSON micro-F1. Every sample has at least two reference reasoning steps, with an average of 4.22 steps, which is consistent with the goal of evaluating reasoning paths rather than single-span extraction.

The split is exactly balanced along both benchmark axes: 500 samples for each meta-reasoning type, 300 samples for each OCR-object category, and 100 samples in every 3×5 taxonomy cell. This balance ensures that aggregate scores are not dominated by one reasoning direction or one document genre. The image-hash audit identifies 1,420 unique hashes among 1,500 instances. We treat repeated hashes as source-image reuse rather than duplicate examples because the corresponding instances have different questions or reasoning targets. No exact duplicate normalized questions or question–answer pairs are present.

E.3 Why These Checks Support Benchmark Reliability

These checks target three failure modes that are especially harmful for OCR-grounded meta-reasoning benchmarks. The human checklist detects semantic failures that schema validation can miss, such as non-unique abductive explanations or inductive rules supported by too few examples. The programmatic audit targets reproducibility failures, including missing images, invalid structured answers, inconsistent scoring metadata, and duplicate prompts. The balanced taxonomy prevents the reported MRMS and category analyses from reflecting uneven sampling rather than model behavior. Together, human review and automated auditing provide evidence that the benchmark is structurally valid, automatically scoreable, and aligned with the intended meta-reasoning taxonomy.

F Details of Evaluation Process

The evaluation protocol follows Section 3.3. It uses the three-stage structure of OCR-Reasoning (Huang et al., 2025): response generation, answer extraction, and score computation. We

add a separate MLLM-as-judge stage for reasoning-process compliance. Answer scoring and process judging are kept separate: deterministic answer scoring determines MRMS, whereas the MLLM judge evaluates only the visible reasoning process for RPCS.

F.1 Answer-Level Score Computation

Response generation For each sample i, the evaluated model receives the image I_i, question q_i, and an answer-format hint derived from `answer_type`. The prompt asks the model to produce numbered reasoning steps followed by a standalone `Final Answer` line. For numeric samples, the final line must contain only the number; for string samples, it must contain a short answer; and for JSON samples, it must contain valid minified JSON.

Answer extraction The evaluator keeps the complete model response for process evaluation, but answer-level scoring uses only the extracted final answer $\hat{y}_i$. Extraction first searches for the final-answer line and then applies type-specific parsing. This stage is answer-blind: it does not receive the gold answer y_i, the reference reasoning steps, or the score of the model. If a valid final answer cannot be extracted, the prediction is treated as empty for answer scoring.

Per-sample scoring Each sample specifies a scoring metric m_i, and the per-sample score is

$$s_i = \mathrm{Score}(\hat{y}_i, y_i, m_i), \quad s_i \in [0, 1].$$

For `exact_match`, both strings are normalized by lowercasing, removing redundant whitespace and lightweight formatting, and standardizing common date, currency, and percentage variants. The score is 1 only when the normalized strings match exactly. For `numeric`, the evaluator removes numeric formatting such as commas, currency symbols, and trailing percent markers, converts the result to a canonical numeric string, and requires exact equality. We do not use a numeric tolerance because benchmark answers are constructed to be uniquely recoverable. For `json_f1`, both answers are parsed as JSON, flattened into normalized key–value units,

and scored by micro-F1:

$$P_i = \frac{|K_{\hat{y}_i} \cap K_{y_i}|}{|K_{\hat{y}_i}|},$$

$$R_i = \frac{|K_{\hat{y}_i} \cap K_{y_i}|}{|K_{y_i}|},$$

$$s_i = \frac{2 P_i R_i}{P_i + R_i}.$$

If either JSON string cannot be parsed, the JSON score is 0.

Aggregate answer metrics The main score is the Meta-Reasoning Macro Score:

$$MRMS = \frac{Acc_{\mathrm{Ded}} + Acc_{\mathrm{Ind}} + Acc_{\mathrm{Abd}}}{3}.$$

$$Acc_t = \frac{1}{|D_t|} \sum_{i \in D_t} s_i.$$

Here D_t is the subset for reasoning type t. We also report the overall micro score,

$$Micro = \frac{1}{|D|} \sum_{i \in D} s_i,$$

as well as answer-type scores and OCR-object scores computed by averaging s_i within each answer format or OCR-object category.

F.2 Reasoning-Process Score Computation

Judge input RPCS evaluates the visible process π_i, not the final answer. Before judging, standalone final-answer lines are removed from the model output. The MLLM judge receives only the image, question, target `meta_reasoning_type`, OCR-object label, answer type, scoring metric, reference reasoning steps, and the remaining visible reasoning process. It does not receive the gold answer, predicted answer, or answer-level score.

Four binary criteria The judge assigns four binary scores:

$$c_i^k \in \{0, 1\}, \quad k \in \{\mathrm{match}, \mathrm{ground}, \mathrm{step}, \mathrm{nonhall}\}.$$

`capability_match` checks whether the main process follows the target H, R, O direction: rule-bound candidate verification for deduction, multi-instance pattern abstraction for induction, and backward recovery of a hidden premise for abduction. `groundedness` checks whether key claims are traceable to the image or question constraints.

step_completeness checks whether the necessary intermediate nodes are present, allowing compressed or reordered steps. non_hallucination checks whether the process avoids invented rules, entities, fields, values, or explanations.

The raw and normalized process scores are:

$$RPCS_i^{raw} = c_i^{match} + c_i^{ground} + c_i^{step} + c_i^{nonhall},$$

$$RPCS_i = \frac{RPCS_i^{raw}}{4}.$$

Model-level RPCS is the mean of $RPCS_i$ over scorable samples. Inference failures, empty outputs, and outputs that contain only a final answer receive zero process credit rather than being silently dropped.

F.3 Reliability Controls for MLLM-as-Judge

We use an MLLM-as-judge because process evaluation requires comparing free-form reasoning traces with image-grounded reference paths, a task that is costly and difficult to standardize through purely manual scoring. The judge protocol uses four safeguards.

Outcome isolation The judge is explicitly instructed not to evaluate final-answer correctness. The final-answer line is removed before judging, and answer fields are withheld. This design prevents the judge from giving high process credit merely because the answer is correct or low process credit merely because the final answer is wrong.

Reference-guided but wording-invariant judging The judge receives reference reasoning steps as process anchors, not as a required script. It is instructed to credit compressed, merged, reordered, or paraphrased reasoning when the required evidence bindings and reasoning direction are preserved. This protocol reduces sensitivity to surface style and focuses the score on OCR-grounded reasoning behavior.

Structured output validation The judge must return machine-readable JSON containing exactly the four binary criteria, a raw RPCS field, and concise rationales. The evaluator validates the JSON, rejects non-binary criterion values, and recomputes $RPCS_i^{raw}$ from the four criteria instead of relying on the total provided by the judge. This validation prevents malformed outputs or arithmetic errors from affecting the reported scores.

Separate reporting MRMS and RPCS are reported separately. MRMS is determined only by automatic answer scoring, whereas RPCS is used for process diagnostics and mismatch analysis. This separation preserves the process-aware motivation of OCR-Reasoning while avoiding dependence on an MLLM judge for the primary answer-correctness leaderboard.

G More Results

The main results summarize the model ranking and the primary differences across reasoning types and OCR-object categories. We report additional breakdowns by answer format, OCR-object category, process-compliance criteria, and the crossed 3×5 taxonomy.

Answer Format Remains a Structured-Output Bottleneck Table 8 complements the main leaderboard in Table 2. The answer format changes the difficulty profile even within the same benchmark. The leading model, Gemini-3.1-Pro-Preview, reaches 95.2% on float answers and 93.6% on string answers, but drops to 77.0% on JSON answers. GPT-5.4-Medium follows the same pattern, with 92.5% on float answers and 78.5% on JSON. This gap shows that the strongest models are limited not only by OCR-grounded reasoning but also by the need to produce structurally exact outputs under automatic scoring. Open-source models show a narrower performance range but a lower ceiling. Kimi-K2.5 obtains 78.9% on string, 81.3% on integer, 80.1% on float, and 77.3% on JSON answers, suggesting more uniform behavior than the top closed-source systems.

Deduction Drives the Main Accuracy Gap Table 9 reports the full meta-reasoning breakdown behind Table 2. Among the top closed-source models, deductive scores remain much lower than inductive and abductive scores. Gemini-3.1-Pro-Preview obtains 80.7% on deduction but 93.1% on induction and 94.1% on abduction. GPT-5.4-Medium shows a similar gap, with 80.6% on deduction compared with 91.5% on induction and 90.8% on abduction. The same bottleneck appears in open-source models. Qwen3-VL-235B-A22B-Thinking reaches 87.8% on induction and 82.1% on abduction, but only 74.8% on deduction. These results are consistent with the conclusion in the main paper that applying visible rules and constraints is harder than abstracting repeated patterns or recovering

plausible hidden premises.

Layout Semantics Is Consistently Hardest Table 10 expands the OCR-object analysis in Table 2. The strongest models score above 87% on most non-layout categories, but performance on layout semantics remains much lower. Gemini-3.1-Pro-Preview scores 76.2% on layout semantics, GPT-5.4-Medium scores 77.6%, and Doubao-Seed-2.0-Pro scores 75.1%. This weakness is larger for open-source models. Qwen3-VL-235B-A22B-Thinking reaches 87.3% on data interpretation and 86.3% on document logic, but only 69.2% on layout semantics. This pattern distinguishes text recognition and field-level reasoning from visually grounded grouping, alignment, and cross-region layout inference.

Process Scores Are High but Incomplete Table 11 provides a criterion-level view of the RPCS comparison in Table 3. Most models achieve high capability-match and groundedness rates, indicating that they often choose the intended reasoning direction and cite image-grounded evidence. Step completeness and non-hallucination are weaker. For example, GPT-5.4-Mini-Medium has 94.9% capability match and 94.1% groundedness, but only 75.1% step completeness. Qwen3-VL-8B-Instruct drops further to 62.2% step completeness and 63.7% non-hallucination. This result helps explain why RPCS is generally higher than MRMS in Table 3: models can follow the broad process form while still omitting necessary intermediate evidence or introducing unsupported details.

The Crossed Taxonomy Localizes Failure Modes Table 12 uses the balanced 3×5 design described in Table 6. The all-model average is highest for inductive reasoning at 82.5%, followed by abduction at 80.1% and deduction at 73.6%. The hardest cell is abductive layout semantics at 63.2%, closely followed by deductive layout semantics at 65.4%. In contrast, inductive document logic and transaction analysis reach 87.3% and 86.8%, respectively. The closed-source and open-source splits preserve the same structure: closed-source models average 69.6% on abductive layout semantics, whereas open-source models average 55.1%. The interaction table shows that benchmark difficulty depends on the combination of reasoning type and OCR-object category, not on either axis alone.

H Qualitative Analysis of RPCS and MRMS Mismatches

Figures 5, 6, and 7 present representative cases in which the visible reasoning process receives full RPCS credit but the final answer receives zero MRMS credit. The contrast reflects the different roles of the two metrics. RPCS evaluates whether the model follows the intended meta-reasoning direction, grounds its claims in the image, includes the necessary intermediate steps, and avoids unsupported additions. MRMS instead compares the extracted final answer with the canonical answer. A model can pass the process rubric and still make an OCR-grounded error that changes the final value.

In the deductive example in Figure 5, the question asks for the earliest date on which all visible constraints are satisfied. The model identifies the required constraint checklist and combines the relevant dates with a latest-date operation, which is consistent with deductive reasoning. The mistake occurs because it treats the March 16 entry as satisfying the capacity threshold, whereas the reference solution uses the March 22 entry. The error is not a failure of reasoning direction, but a wrong binding between the capacity condition and the OCR field within an otherwise valid deductive structure.

The inductive example in Figure 6 shows a different form of mismatch. The model correctly infers the latent mapping from sections to scores in the examples: high, above average, average, below average, and low correspond to descending scores. It then applies this rule to the target city. The final answer is incorrect because, for one indicator, the target cell for Long Beach is assigned to the wrong section. The induced pattern is process-compliant, but a local OCR-layout error changes the computed sum.

The abductive example in Figure 7 illustrates an error in backward recovery. The model starts from the observed total savings, sums the visible itemized components, and subtracts them to recover the hidden unlisted discount, which matches the intended abductive schema. MRMS is zero because the model undercounts an explicit coupon subtotal before the final subtraction. This case shows that an abductive process can have the correct structure even when a small arithmetic or transcription error changes the recovered hidden premise.

The three cases explain why high RPCS does not necessarily imply high MRMS. The process judge can recognize a valid reasoning plan and grounded

intermediate structure, whereas answer scoring remains sensitive to exact OCR binding, table localization, and arithmetic precision. This separation is useful for diagnosis: RPCS indicates whether the model selects the appropriate reasoning mode, while MRMS indicates whether the model executes the required OCR-grounded operations with sufficient accuracy to produce the correct answer.

I OCR-MetaReasoning Examples

Figures 8, 9, and 10 show examples of the 15 meta-reasoning tasks in text-rich visual scenarios.

Deductive Case: RPCS Passes While MRMS Fails

(a) Problem

Question

A research team is looking for the earliest date in 2020 by which the lab network met three specific criteria: (1) at least one lab in the network had reported a positive patient sample, (2) samples no longer required confirmation by the National Microbiology Laboratory in Winnipeg, and (3) the daily testing capacity at St. Paul's had reached at least 1,000 tests per day. Based on the timeline, what is the earliest date this status was achieved?

(b) Reference Solution

1. Step1: Identify the date for criterion 1: The entry for January 27 states 'The BCCDC lab detects the first positive patient sample', satisfying this from January 27 onwards.
2. Step2: Identify the date for criterion 2: The entry for February 24 states 'samples no longer require further confirmation by the NML in Winnipeg', satisfying this from February 24 onwards.
3. Step3: Identify the date for criterion 3: The entry for February 14 shows St. Paul's capacity at 368, while March 22 states 'St Paul's launched second assay, increasing capacity to 2136 tests per day', satisfying the >= 1,000 requirement.
4. Step4: Determine the earliest date satisfying all three constraints (Jan 27, Feb 24, and Mar 22), which yields March 22.

Gold Answer: March 22

(c) Model Output

Step 1: Identify when at least one lab in the network had reported a positive patient sample.
According to the timeline, "January 27 - The BCCDC lab detects the first positive patient sample." So criterion 1 is met on January 27.

Step 2: Identify when samples no longer required confirmation by the National Microbiology Laboratory (NML) in Winnipeg.
According to the timeline, "February 24 - The BCCDC is officially authorized for COVID-19 testing by the National Microbiology Laboratory - samples no longer require further confirmation by the NML in Winnipeg." So criterion 2 is met on February 24.

Step 3: Identify when the daily testing capacity at St. Paul's reached at least 1,000 tests per day.
- February 14: St. Paul's first COVID-19 test launched with a capacity of 368 tests per day.
- March 16: Further operational changes increase daily testing capacity from ~500 samples per day to up to 2000 per day.
- March 22: St. Paul's launched second assay, increasing capacity to 2136 tests per day.

The capacity first reached at least 1,000 tests per day sometime between March 12 and March 16, but the first explicitly stated milestone above 1,000 is March 16 (up to 2000 per day). So criterion 3 is met on March 16.

Step 4: The earliest date all three criteria are simultaneously met is the latest of the three dates: January 27, February 24, and March 16.

Final Answer: March 16, 2020

(d) Outcome Diagnosis

RPCS = 4/4   MRMS = 0

Predicted Answer: March 16, 2020
Gold Answer: March 22
Reason: Correct constraint checklist, but the model binds the capacity condition to the wrong timeline entry.

Figure 5: Deductive case where RPCS passes while MRMS fails. The model follows the constraint-checking structure but binds the capacity condition to the wrong timeline entry.

Inductive Case: RPCS Passes While MRMS Fails

(a) Problem

Question

A health policy document assigns a section-based risk score to each region for each of the four indicators. Based on the document's section headers, 'Southeast' receives a score of 5 for Infant Mortality and 5 for Tuberculosis. 'Whittier' receives a score of 1 for Infant Mortality and 1 for Tuberculosis. 'Pasadena' receives a score of 4 for Infant Mortality and 4 for Tuberculosis. By finding the underlying scoring pattern based on the section headers, what is the total combined risk score for 'Long Beach' across all four columns?

(b) Reference Solution

1. Step1: Align the provided examples with their section headers: 'Southeast' under 'High' scores 5, 'Whittier' under 'Low' scores 1, and 'Pasadena' under 'Above Average' scores 4.
2. Step2: Abstract the latent mapping rule: High = 5, Above Average = 4, Average = 3, Below Average = 2, Low = 1.
3. Step3: Locate 'Long Beach' in the four indicator columns: Infant Mortality is 'Low' (1), Tuberculosis is 'Above Average' (4), Syphilis is 'Average' (3), and Gonorrhea is 'Above Average' (4).
4. Step4: Sum the risk scores for Long Beach: 1 + 4 + 3 + 4 = 12.

Gold Answer: 12

(c) Model Output

I need to find the scoring pattern based on the section headers, then calculate Long Beach's total score across all four columns.

Step 1: Analyze the section headers and their scores for Southeast, Whittier, and Pasadena.

For Infant Mortality:
- Southeast (35.2) = score 5 → High section
- Pasadena (24.7) = score 4 → Above Average section
- Whittier (14.2) = score 1 → Low section

For Tuberculosis:
- Southeast (87.4) = score 5 → High section
- Pasadena (27.2) = score 4 → Above Average section
- Whittier (10.8) = score 1 → Low section

Step 2: Determine the scoring system based on section headers:
- High = 5
- Above Average = 4
- Average = 3
- Below Average = 2
- Low = 1

Step 3: Find Long Beach's position in each column:

Infant Mortality (20.2): In the "Average" section → score 3

Tuberculosis (29.4): In the "Above Average" section → score 4

Syphilis (64.1): In the "Average" section → score 3

Gonorrhea (364.3): In the "Above Average" section → score 4

Step 4: Calculate total combined risk score for Long Beach:
3 + 4 + 3 + 4 = 14

Final Answer: 14

(d) Outcome Diagnosis

RPCS = 4/4	MRMS = 0

Predicted Answer: 14
Gold Answer: 12
Reason: Valid section-to-score induction, but the model reads the Long Beach target cell from the wrong section.

Figure 6: Inductive case where RPCS passes while MRMS fails. The model induces the correct section-to-score rule but reads the target cell from the wrong section.

Abductive Case: RPCS Passes While MRMS Fails

(a) Problem

Question

The receipt reports a 'TOTAL SAVINGS THIS TRIP' of $18.82. This total savings is the sum of all applied coupons, the REDcard discount, the explicitly itemized Cereal discounts (Sale and Cartwheel), and the unlisted sale discounts for the other items marked with a downarrow (↓). By reasoning backward from the total savings and summing all explicitly listed discount amounts, calculate the exact combined dollar amount of the unlisted sale discounts. Provide just the numeric value.

(b) Reference Solution

1. Step1: Observe the 'TOTAL SAVINGS THIS TRIP' at the bottom of the receipt is $18.82.
2. Step2: Identify and sum all explicitly listed coupon deductions ($1.50 + $2.00 + $3.00 + $3.00 + $1.00 + $0.05 + $0.05 + $2.00 = $12.60) and the REDcard savings ($0.52).
3. Step3: Calculate the explicitly listed Cereal savings: 'Saved $1.21' for two boxes ($2.42) plus Cartwheel savings of $0.23 per box for two boxes ($0.46).
4. Step4: Sum all known explicitly itemized savings: $12.60 + $0.52 + $2.42 + $0.46 = $16.00.
5. Step5: Subtract the total known itemized savings from the 'TOTAL SAVINGS THIS TRIP' to abduce the hidden unlisted sale discounts: $18.82 - $16.00 = 2.82.

Gold Answer: 2.82

(c) Model Output

Step 1: Sum all explicitly listed applied coupon discounts:
List all coupon discount amounts: Windex MFR ($1.00) + Vans MFR ($2.00) + 2×Ling Ling MFR ($3.00 + $3.00) + Chobani MFR ($1.00) + 2×Target coupon ($0.05 + $0.05) + final MFR ($2.00) = $1.00 + $2.00 + $3.00 + $3.00 + $1.00 + $0.05 + $0.05 + $2.00 = **$12.10**.

Step 2: Add the explicit REDcard discount:
REDcard savings = $0.52, so total now: $12.10 + $0.52 = **$12.62**.

Step 3: Add the explicitly itemized cereal discounts (sale + Cartwheel):
There are 2 cereal boxes:
- Each has an explicit sale discount of $1.21 → total sale discount = 2×$1.21 = $2.42.
- Each has 10% off a post-sale price of $2.28 → Cartwheel discount per box = 0.10 × $2.28 = $0.228 → total Cartwheel discount = 2×$0.228 = $0.456.
Total explicit cereal discount = $2.42 + $0.456 = $2.876. Add to previous total: $12.62 + $2.876 = **$15.496**.

Step 4: Calculate the combined unlisted sale discounts by subtracting the total explicit discounts from the total savings:
Total savings = $18.82. Unlisted discount = $18.82 - $15.496 = $3.324 ≈ $3.32 (rounded to standard currency cents).

Final Answer: 3.32

(d) Outcome Diagnosis

| RPCS = 4/4 | MRMS = 0 |

Predicted Answer: 3.32
Gold Answer: 2.82
Reason: Correct backward recovery schema, but an explicit coupon subtotal is undercounted before subtraction.

Figure 7: Abductive case where RPCS passes while MRMS fails. The model uses the correct backward recovery schema but undercounts an explicit coupon subtotal before subtraction.

Table 8: Extended answer-level results by answer type. MRMS is the model-level score reported in Table 2. Scores are percentages.

Model	String	Integer	Float	JSON	MRMS
Closed-source Models					
Gemini-3.1-Pro-Preview	93.6	90.0	95.2	77.0	89.3
GPT-5.4-Medium	88.3	90.4	92.5	78.5	87.7
Doubao-Seed-2.0-Pro	86.5	87.7	91.1	81.0	86.4
Claude-Sonnet-4.6	87.7	85.9	84.9	74.6	84.3
Doubao-Seed-2.0-Lite	84.2	85.7	89.0	78.7	84.2
GPT-5.4-Mini-Medium	84.4	85.7	90.4	76.4	84.0
Gemini-3.1-Flash-Lite	86.5	82.9	82.9	78.4	83.3
GPT-5.4	84.2	83.6	88.4	77.0	83.0
Grok-4.20	73.9	78.6	74.7	71.1	75.2
GPT-5.4-Mini	70.2	75.6	73.3	67.7	72.0
Open-source Models					
Qwen3-VL-235B-A22B-Thinking	83.0	82.6	84.1	76.7	81.5
Kimi-K2.5	78.9	81.3	80.1	77.3	79.6
Qwen3-VL-235B-A22B-Instruct	77.4	79.9	76.6	71.2	77.0
GLM-4.6V	77.2	76.8	74.7	72.5	75.9
Qwen3-VL-30B-A3B-Thinking	74.9	78.4	71.9	68.5	74.7
Qwen3-VL-8B-Thinking	75.9	76.8	71.9	69.5	74.5
Qwen3-VL-30B-A3B-Instruct	65.5	66.7	58.9	64.2	65.0
Qwen3-VL-8B-Instruct	60.0	60.4	52.4	58.0	59.0

Table 9: Extended answer-level results by meta-reasoning type. DED., IND., and ABD. denote deductive, inductive, and abductive meta-reasoning. MRMS is the macro average over the three types, consistent with Table 2. Scores are percentages.

Model	DED.	IND.	ABD.	MRMS
Closed-source Models				
Gemini-3.1-Pro-Preview	80.7	93.1	94.1	89.3
GPT-5.4-Medium	80.6	91.5	90.8	87.7
Doubao-Seed-2.0-Pro	80.1	90.2	88.9	86.4
Claude-Sonnet-4.6	77.5	87.6	87.9	84.3
Doubao-Seed-2.0-Lite	76.7	89.2	86.8	84.2
GPT-5.4-Mini-Medium	77.7	87.2	87.1	84.0
Gemini-3.1-Flash-Lite	78.4	85.4	86.2	83.3
GPT-5.4	77.9	85.7	85.5	83.0
Grok-4.20	70.3	77.4	78.0	75.2
GPT-5.4-Mini	70.7	75.3	70.1	72.0
Open-source Models				
Qwen3-VL-235B-A22B-Thinking	74.8	87.8	82.1	81.5
Kimi-K2.5	71.8	84.6	82.5	79.6
Qwen3-VL-235B-A22B-Instruct	72.5	80.9	77.7	77.0
GLM-4.6V	72.0	79.2	76.3	75.9
Qwen3-VL-30B-A3B-Thinking	69.1	81.8	73.3	74.7
Qwen3-VL-8B-Thinking	70.3	79.5	73.6	74.5
Qwen3-VL-30B-A3B-Instruct	64.0	67.9	63.2	65.0
Qwen3-VL-8B-Instruct	59.1	60.5	57.6	59.0

Table 10: Extended answer-level results by OCR-object category. D.I., D.L., F.D., L.S., and T.A. denote data interpretation, document logic, field dependency, layout semantics, and transaction analysis. Avg. is the mean over the five object categories, consistent with Table 2. Scores are percentages.

Model	D.I.	D.L.	F.D.	L.S.	T.A.	Avg.
Closed-source Models						
Gemini-3.1-Pro-Preview	96.0	93.0	91.7	76.2	89.7	89.3
GPT-5.4-Medium	92.3	90.8	90.0	77.6	87.5	87.7
Doubao-Seed-2.0-Pro	91.7	87.8	87.9	75.1	89.4	86.4
Claude-Sonnet-4.6	88.5	88.1	89.1	69.9	86.0	84.3
Doubao-Seed-2.0-Lite	86.8	86.3	88.3	72.3	87.4	84.2
GPT-5.4-Mini-Medium	86.7	87.8	87.2	73.6	84.7	84.0
Gemini-3.1-Flash-Lite	87.7	84.9	87.8	72.2	83.8	83.3
GPT-5.4	87.4	85.0	88.0	69.1	85.7	83.0
Grok-4.20	79.3	76.6	79.8	61.9	78.3	75.2
GPT-5.4-Mini	72.7	75.1	76.9	61.0	74.4	72.0
Open-source Models						
Qwen3-VL-235B-A22B-Thinking	87.3	86.3	82.7	69.2	82.2	81.5
Kimi-K2.5	86.5	77.5	81.2	70.2	82.8	79.6
Qwen3-VL-235B-A22B-Instruct	80.7	78.8	80.7	69.5	75.5	77.0
GLM-4.6V	83.6	78.1	79.3	60.3	77.9	75.9
Qwen3-VL-30B-A3B-Thinking	81.5	78.6	77.8	60.5	75.1	74.7
Qwen3-VL-8B-Thinking	80.7	76.8	77.3	60.6	76.8	74.5
Qwen3-VL-30B-A3B-Instruct	72.1	66.6	67.0	55.1	64.4	65.0
Qwen3-VL-8B-Instruct	58.3	65.5	62.4	49.9	59.1	59.0

Table 11: Extended RPCS criterion pass rates. CM, GRD, STEP, and NH denote capability match, groundedness, step completeness, and non-hallucination. Avg. is the normalized RPCS, consistent with Table 3. Scores are percentages.

Model	CM	GRD	STEP	NH	Avg.
Closed-source Models					
Gemini-3.1-Pro-Preview	98.7	98.7	92.6	94.5	96.2
GPT-5.4-Medium	98.5	97.7	91.4	93.1	95.2
Doubao-Seed-2.0-Pro	96.7	96.6	87.5	91.3	93.0
Claude-Sonnet-4.6	97.1	95.3	91.6	83.7	91.9
Doubao-Seed-2.0-Lite	97.0	96.5	90.3	89.7	93.3
GPT-5.4-Mini-Medium	94.9	94.1	75.1	91.7	88.9
Gemini-3.1-Flash-Lite	93.3	95.7	82.8	85.3	89.3
GPT-5.4	96.9	95.8	89.3	88.1	92.5
Grok-4.20	93.7	91.7	81.5	76.0	85.7
GPT-5.4-Mini	91.3	87.7	68.5	78.0	81.4
Open-source Models					
Qwen3-VL-235B-A22B-Thinking	95.1	93.1	85.4	84.7	89.6
Kimi-K2.5	96.7	96.0	89.7	82.0	91.1
Qwen3-VL-235B-A22B-Instruct	93.5	92.4	84.2	77.9	87.0
GLM-4.6V	90.0	88.1	75.4	82.9	84.1
Qwen3-VL-30B-A3B-Thinking	91.5	89.8	76.7	79.5	84.4
Qwen3-VL-8B-Thinking	91.1	86.9	75.1	77.5	82.7
Qwen3-VL-30B-A3B-Instruct	86.1	83.6	69.3	66.0	76.3
Qwen3-VL-8B-Instruct	83.5	80.5	62.2	63.7	72.5

Table 12: Mean answer-level scores for the 3×5 OCR-MetaReasoning taxonomy. Each cell averages model scores on the corresponding meta-reasoning type and OCR-object category. Scores are percentages.

Type	D.I.	D.L.	F.D.	L.S.	T.A.	Avg.
All Models						
DED.	83.1	73.2	74.4	65.4	71.8	73.6
IND.	80.5	87.3	85.9	72.3	86.8	82.5
ABD.	86.5	83.7	85.7	63.2	81.7	80.1
Closed-source Models						
DED.	88.1	76.3	78.3	67.7	74.9	77.0
IND.	84.1	91.6	89.5	75.5	90.5	86.2
ABD.	88.5	88.7	92.2	69.6	88.7	85.5
Open-source Models						
DED.	76.8	69.2	69.5	62.6	67.9	69.2
IND.	76.0	81.8	81.2	68.2	82.3	77.9
ABD.	84.0	77.3	77.7	55.1	72.9	73.4

Figure 8: Examples of meta-deductive reasoning tasks in OCR-MetaReasoning.

Figure 9: Examples of meta-inductive reasoning tasks in OCR-MetaReasoning.

Figure 10: Examples of meta-abductive reasoning tasks in OCR-MetaReasoning.

Model	Reasoning Mode	Model Link
Closed-source Models		
Doubao-Seed-2.0-Lite-260215	✓	https://seed.bytedance.com/en/seed2
Doubao-Seed-2.0-Pro-260215	✓	https://seed.bytedance.com/en/seed2
GPT-5.4-Mini	✗	https://developers.openai.com/api/docs/models/gpt-5.4-mini
GPT-5.4-Mini (medium)	✓	https://developers.openai.com/api/docs/models/gpt-5.4-mini
Gemini-3.1-Flash-Lite	✓	https://ai.google.dev/gemini-api/docs/models/gemini-3.1-flash-lite
Gemini-3.1-Pro-Preview	✓	https://ai.google.dev/gemini-api/docs/models/gemini-3.1-pro-preview
GPT-5.4	✗	https://developers.openai.com/api/docs/models/gpt-5.4
GPT-5.4 (medium)	✓	https://developers.openai.com/api/docs/models/gpt-5.4
Claude-Sonnet-4.6	✓	https://www.anthropic.com/claude/sonnet
Grok-4.20	✗	https://ai.azure.com/catalog/models/grok-4-20-non-reasoning
Open-source Models		
Qwen3-VL-8B-Instruct	✗	https://huggingface.co/Qwen/Qwen3-VL-8B-Instruct
Qwen3-VL-8B-Thinking	✓	https://huggingface.co/Qwen/Qwen3-VL-8B-Thinking
Qwen3-VL-30B-A3B-Instruct	✗	https://huggingface.co/Qwen/Qwen3-VL-30B-A3B-Instruct
Qwen3-VL-30B-A3B-Thinking	✓	https://huggingface.co/Qwen/Qwen3-VL-30B-A3B-Thinking
Qwen3-VL-235B-A22B-Instruct	✗	https://huggingface.co/Qwen/Qwen3-VL-235B-A22B-Instruct
Qwen3-VL-235B-A22B-Thinking	✓	https://huggingface.co/Qwen/Qwen3-VL-235B-A22B-Thinking
Kimi-K2.5	✗	https://huggingface.co/moonshotai/Kimi-K2.5
GLM-4.6V	✓	https://huggingface.co/zai-org/GLM-4.6V

Table 13: Model sources used in our evaluation. The "medium" suffix denotes the reasoning-effort setting rather than a separate model release.