Context-Based Dynamic Pricing with Partially Linear Demand Model

Abstract

In today's data-rich environment, context-based dynamic pricing has gained much attention. To model the demand as a function of price and context, the existing literature either adopts a parametric model or a non-parametric model. The former is easier to implement but may suffer from model mis-specification, whereas the latter is more robust but does not leverage many structural properties of the underlying problem. This paper combines these two approaches by studying the context-based dynamic pricing with online learning, where the unknown expected demand admits a semi-parametric partially linear structure. Specifically, we consider two demand models, whose expected demand at price p and context $x \in \mathbb{R}^d$ is given by $bp + g(x)$ and $f(p) + a^\top x$ respectively. We assume that $g(x)$ is β-Hölder continuous in the first model, and $f(p)$ is kth-order smooth with an additional parameter δ in the second model. For both models, we design an efficient online learning algorithm with provable regret upper bounds, and establish matching lower bounds. This enables us to characterize the statistical complexity for the two learning models, whose optimal regret rates are $\widetilde{\Theta}(\sqrt{T} \vee T^{\frac{d}{d+2\beta}})$ and $\widetilde{\Theta}(\sqrt{T} \vee (\delta T^{k+1})^{\frac{1}{2k+1}})$ respectively. The numerical results demonstrate that our learning algorithms are more effective than benchmark algorithms, and also reveal the effects of parameters d, β and δ on the algorithm's empirical regret, which are consistent with our theoretical findings.

1 Introduction

The recent success of online retailing has provided a data-rich environment for sellers to take better advantage of contextual information to dynamically improve their pricing strategies. Examples of such contextual information include products' characteristics, seasonality, festival information, economic indicators, etc. A fundamental question stemming from the presence of contexts is how to select a predictive model to capture the relationship among demand, price, and context.

In the current literature, there are two modeling approaches. The first approach is to adopt a parametric model, among which the linear model, i.e., demand = b × price + a × context, is arguably the most fundamental one. The parametric assumption brings great convenience to practical implementation, and inspires many efficient learning algorithms. However, it may also lead to a serious issue of model mis-specification, as discussed in [24]. The second approach is to employ a fully non-parametric model, i.e., demand = μ(price, context) for some unknown function $\mu(\cdot)$ without any parametric assumption. The non-parametric model can be quite robust to different application contexts. However, it does not leverage many structural properties of the underlying problem that may have been detected from huge amounts of historical data, resulting in much complexity for learning the function $\mu(\cdot)$.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Motivated by the idea of combining these two approaches, in this paper, we study context-based dynamic pricing with online learning where the unknown expected demand admits a semi-parametric partially linear structure. Such a structure preserves the advantages of simple interpretability from linear models and great flexibility from non-parametric models. Thus, it has also attracted significant attention in many fields, especially when there exist high-dimensional contexts, such as statistics [13], econometrics [35], and biomedicines [36].

Formally, consider a seller selling products over a finite selling horizon of T periods. At the beginning of each period t, the seller observes an independently and identically distributed (i.i.d.) context vector $x_t \in [0,1]^d \in \mathbb{R}^d$ encoding the product's characteristics and other exogenous information in period t. The seller then chooses a price p_t from the feasible price range $[\underline{p}, \overline{p}]$ and customers observe the posted price p_t. The random demand D_t is then generated according to the following function: $D_t(p_t) = \mu(p_t, x_t) + \varepsilon_t$, where $\mu(p_t, x_t)$ is an unknown function and $\{\varepsilon_t\}_{t \geq 1}$ are i.i.d. sub-Gaussian random variables (r.v.'s) with zero mean and variance proxy σ^2, i.e., $\mathbb{E}[e^{\lambda \varepsilon_t}] \leq e^{\frac{\lambda^2 \sigma^2}{2}}$ for any $\lambda \in \mathbb{R}$. We consider two models for $\mu(p_t, x_t)$:

Dynamic Pricing with Linear Pricing Effect (DPLPE): $\mu(p_t, x_t) = bp_t + g(x_t)$ for unknown price elasticity $b \in \mathbb{R}$ and β-Hölder continuous function $g : [0,1]^d \to \mathbb{R}$ with smoothness parameter $0 < \beta \leq 1$ (see Assumption 1);

Dynamic Pricing with Linear Contextual Effect (DPLCE): $\mu(p_t, x_t) = f(p_t) + a^\top x_t$ for unknown parameter $a \in \mathbb{R}^d$ and kth-order smooth function $f : [\underline{p}, \overline{p}] \to \mathbb{R}$ with degree $k \geq 1$ and parameter $\delta > 0$ that captures how tightly f can be approximated by a polynomial function (see Assumption 2).

The seller observes demand D_t and collects revenue $p_t D_t$. The expected revenue at price p and context x_t is denoted by $r(p, x_t) = p\mu(p, x_t)$ for any $p \in [\underline{p}, \overline{p}]$. An *admissible* pricing policy π is defined as a sequence of functions $\{\pi_t(\cdot) : t \geq 1\}$, where each $\pi_t(\cdot)$ maps the historical information $(x_1, p_1, D_1, \ldots, x_{t-1}, p_{t-1}, D_{t-1}, x_t)$ observed up to period t and possibly some external randomness to a feasible price in $[\underline{p}, \overline{p}]$. A clairvoyant optimal policy is assumed to know function $d(\cdot)$ and therefore always chooses the optimal price $p_t^* := \arg\max_{p \in [\underline{p}, \overline{p}]} r(p, x_t)$ in each period t. The performance of a pricing policy π is measured by *regret* $R^\pi(T)$, defined as the difference between the T-period expected revenues generated by the clairvoyant optimal policy and by the pricing policy π. That is, $R^\pi(T) = \sum_{t=1}^{T} \mathbb{E}[r(p_t^*, x_t) - r(p_t, x_t)]$, where the expectation is taken over all the randomness associated with the environment and the algorithm.

1.1 Main results

Our main contributions lie in systematically characterizing the statistical complexity of the context-based dynamic pricing with partially linear demand models DPLPE and DPLCE. Throughout the paper, we use notations $\mathcal{O}(\cdot)$, $\Omega(\cdot)$ and $\Theta(\cdot)$ to hide constant factors, and use $\widetilde{\mathcal{O}}(\cdot)$, $\widetilde{\Omega}(\cdot)$ and $\widetilde{\Theta}(\cdot)$ to hide both constant and logarithmic factors.

Statistical complexity for DPLPE. For the first model DPLPE, we design an online learning algorithm that integrates the ideas of random shock pricing in [24] and contextual space binning and approximation. We prove that our algorithm achieves the theoretical regret upper bound $\widetilde{\mathcal{O}}(\sqrt{T} \vee T^{\frac{d}{d+2\beta}})$. We also establish the information-theoretic lower bound $\Omega(\sqrt{T} \vee T^{\frac{d}{d+2\beta}})$ for any admissible policy, which matches the regret upper bound up to logarithmic factors. The key novelty in our lower bound analysis is the construction of a family of high-dimensional β-Hölder continuous functions that are difficult to distinguish from each other. To the best of our knowledge, this is also the first model that generalizes the commonly used Lipschitz continuous assumption to Hölder continuity in context-based dynamic pricing, with tight characterizations on the regret upper and lower bounds.

Statistical complexity for DPLCE. For the second model DPLCE, we devise a different learning algorithm based on the biased linear contextual bandit borrowed from [31] and our novel idea of being more optimistic to chase the context-dependent optimal price. We prove that our algorithm achieves the regret upper bound $\widetilde{\mathcal{O}}(\sqrt{T} \vee (\delta T^{k+1})^{\frac{1}{2k+1}})$, and also establish a matching lower bound $\Omega(\sqrt{T} \vee (\delta T^{k+1})^{\frac{1}{2k+1}})$. Since δ is a parameter that depends on the specific problem instance $f(\cdot)$, we refer to the regret bounds we derive as the *instance-dependent* bounds. To our knowledge, this is

84 the first tight instance-dependent regret bound in context-based dynamic pricing with online learning.
85 To achieve this, in the regret lower bound analysis, we need to construct a family of kth-order smooth
86 functions that are adapted to parameters k and δ, which is also new to dynamic pricing literature.

1.2 Related work

87

88 **Non-contextual dynamic pricing.** There is a vast literature on dynamic pricing with online demand
89 learning without context. These works can be classified into two categories: parametric models (see,
90 e.g., [7], [18]) and non-parametric models (see, e.g., [4], [5], [32],[31], [22]). We refer the reader to
91 [12] for a comprehensive review on this stream of literature. Among these studies, [31] is the most
92 relevant to our paper. [31] study dynamic pricing without context, and assume the expected demand
93 is kth-order smooth in price for some integer k. They design a learning algorithm by applying the
94 Optimism-in-the-Face-of-Uncertainty (OFU) principle borrowed from bandits, and prove the optimal
95 regret is $\widetilde{\Theta}(T^{\frac{k+1}{2k+1}})$. The idea of algorithmic design in our DPLCE model is inspired by [31] but there
96 are two major differences. First, the optimal price is stationary in [31], but can change over time in
97 our setting. Therefore, the idea of multi-armed bandit protocol proposed in their paper for learning
98 the stationary optimal price does not work. To overcome this difficulty, we propose a novel idea
99 of being more optimistic over OFU in price selection to chase the context-dependent optimal price.
100 Second, our notion of kth-order smoothness is more general than theirs by allowing k not necessarily
101 to be an integer and δ not necessarily to be a constant. The general values of k and δ require a more
102 careful selection of the parameters used by the algorithm, and a more sophisticated construction for
103 the hard instances in the lower bound analysis.

104 **Context-based dynamic pricing.** There is a growing body of literature on context-based dynamic
105 pricing (e.g., [26], [16], [21], [3], [23]). We refer to [3] for a recent review and briefly discuss the
106 works related to this paper. [26] consider the demand model $a^\top x + bp$ in an incumbent-price setting,
107 i.e., the expected demand for some given price is exactly known, and show that the greedy algorithm
108 achieves the regret $\mathcal{O}(\log T)$. [24] study the same demand model as our DPLPE, and prove that
109 the regret of a random price shock (RPS) algorithm compared with the clairvoyant who knows the
110 best *linear* approximation to $g(x)$ is $\mathcal{O}(\sqrt{T})$. We borrow their RPS idea to design the learning
111 algorithm for our DPLPE model, but analyze the regret of our algorithm relative to the optimal policy
112 that knows the *true* demand model. [8] consider a non-parametric demand model in context-based
113 dynamic pricing. For the Lipschitz continuous and locally concave revenue function, they prove that
114 the optimal regret is $\widetilde{\Theta}(T^{\frac{d+2}{d+4}})$. This regret rate is strictly higher than $\widetilde{\Theta}(\sqrt{T} \vee T^{\frac{d}{d+2}})$ in our DPLPE
115 model with $\beta = 1$ due to the separated effects of the price and context on demand we assume.

116 There is also a stream of works formulating demand using a binary choice model (see, e.g., [16], [20],
117 [10], [29], [33], [14],[34],[19]). Every customer buys the product with probability $1 - F\left(p_t - \theta^\top x_t\right)$,
118 where $F(\cdot)$ is the CDF of random noise. [14],[34] and [19] are the closest to our work. They also
119 consider a semi-parametric form where $F(\cdot)$ is unknown non-parametric and θ is unknown parametric.
120 Conceptually, one can transform our demand model into the one where each customer buys the product
121 with probability $bp_t + g\left(x_t\right)$ (for DPLPE) or $f\left(p_t\right) + a^\top x_t$ (for DPLCE), assuming $bp_t + g\left(x_t\right)$ and
122 $f\left(p_t\right) + a^\top x_t$ fall in $[0, 1]$. Since the modelling approaches are different, we are also facing different
123 challenges. Different from the binary model, we need to estimate b and the non-parametric function
124 $g\left(\cdot\right)$ at the same time for DPLPE (or a and the non-parametric function $f\left(\cdot\right)$ for DPLCE). Despite
125 that we have an additive structure, it is still challenging to decouple bp_t and $g\left(x_t\right)$ for DPLPE (or
126 $f\left(p_t\right)$ and $a^\top x_t$ for DPLCE) with only a buying/not-buying feedback. In our model, the distribution
127 of random shock makes no difference to the optimal pricing strategy. Thus, whether the distribution
128 is parametric/known or not is not important in our formulation.

129 **Bandits with contextual information.** The most studied model in contextual bandit is the linear
130 model (see, e.g., [2], [11], [28], [9], [1]), where the expected reward is a linear combination of
131 contexts. The algorithms developed in these works are mostly built upon the celebrated idea of
132 the OFU principle. In our DPLCE model, we borrow the OFU idea to design a learning algorithm.
133 There are also a substantial amount of literature considering non-parametric reward feedback under
134 Hölder continuous assumption (see, e.g., [27], [30], [25], [15]). Among these studies, [30] assuming
135 a continuous action space is the most relevant to this work. For the general Lipschitz reward function,

136 [30] proves that the optimal regret is $\widetilde{\Theta}(T^{\frac{d+d_p+1}{d+d_p+2}})$, where d and d_p are the dimensions for the context
137 space and action space respectively. Letting $d_p = 1$ leads to the optimal regret rate $\widetilde{\Theta}(T^{\frac{d+2}{d+3}})$ for a
138 dynamic pricing problem. This rate is strictly higher than the optimal regret $\widetilde{\Theta}(\sqrt{T} \vee T^{\frac{d}{d+2}})$ in our
139 DPLPE model with $\beta = 1$, and than $\widetilde{\Theta}(T^{\frac{2}{3}})$ in our DPLCE with $k = 1$ and $\delta = \Theta(1)$.

140 Table 1 provides a summary for the main results of this work and the mostly related literature.

Table 1: Summary of the main results in this work and existing results in literature

Paper	Demand model	Regret upper bound	Regret lower bound	Key assumption
Dynamic pricing without context				
[18]	$a + bp$	$\widetilde{\mathcal{O}}(\sqrt{T})$	$\Omega(\sqrt{T})$	Linear demand model
[31]	$f(p)$	$\widetilde{\mathcal{O}}(T^{\frac{k+1}{2k+1}})$	$\Omega(T^{\frac{k+1}{2k+1}})$	f: kth-order smooth
Dynamic pricing with context				
[26]	$a^\top x + bp$	$\mathcal{O}(\log T)$	$\Omega(\log T)$	Known incumbent price
[24]	$bp + g(x)$	$\mathcal{O}(\sqrt{T})$	$\Omega(\sqrt{T})$	Benchmark: the best linear model
[30]	$d(p,x)$	$\mathcal{O}(T^{\frac{d+2}{d+3}})$	$\Omega(T^{\frac{d+2}{d+3}})$	d: Lipschitz continuous
[8]	$d(p,x)$	$\mathcal{O}((\log T)^2 T^{\frac{d+2}{d+4}})$	$\Omega(T^{\frac{d+2}{d+4}})$	d: Lipschitz continuous, smooth and locally concave revenue
[14]	$\mathbb{I}_{\{\theta^\top x + \epsilon \geq p\}}$	$\widetilde{\mathcal{O}}(T^{\frac{2k+1}{4k-1}})$	N.A.	ϵ's CDF: kth-order smooth ($k \geq 2$)
[34]	$\mathbb{I}_{\{\theta^\top x + \epsilon \geq p\}}$	$\widetilde{\mathcal{O}}(T^{\frac{3}{4}})$	$\Omega(T^{\frac{2}{3}})$	No distributional assumptions
This work (Sec. 2 and Sec. 3)	$bp + g(x)$ $f(p) + a^\top x$	$\widetilde{\mathcal{O}}(\sqrt{T} \vee T^{\frac{d}{d+2\beta}})$ $\widetilde{\mathcal{O}}(\sqrt{T} \vee (\delta T^{k+1})^{\frac{1}{2k+1}})$	$\Omega(\sqrt{T} \vee T^{\frac{d}{d+2\beta}})$ $\Omega(\sqrt{T} \vee (\delta T^{k+1})^{\frac{1}{2k+1}})$	g: β-Hölder continuous in $[0,1]^d$, f: kth-order smooth with parameter δ

2 Dynamic Pricing with Linear Pricing Effect (DPLPE)

142 In this section, we study the semi-parametric demand model with linear pricing effect, i.e., $\mu(p_t, x_t) =$
143 $bp_t + g(x_t)$. We assume that the unknown price elasticity b belongs to some known interval
144 $[\underline{b}, \overline{b}] \subseteq (-\infty, 0)$, and the optimal price $p_t^* = -\frac{g(x_t)}{2b} \in [\underline{p}, \overline{p}]$ for any $b \in [\underline{b}, \overline{b}]$ and $x_t \in [0,1]^d$. We
145 now introduce our assumption on function $g(\cdot)$.

146 **Assumption 1** *The function $g : \mathbb{R}^d \to \mathbb{R}$ is β-Hölder continuous for some parameter $0 < \beta \leq 1$,*
147 *denoted by $g \in \mathcal{G}(\beta, d)$, meaning that there exists a constant $L > 0$, such that for any $x_1, x_2 \in [0,1]^d$,*
148 $|g(x_1) - g(x_2)| \leq L \|x_1 - x_2\|^\beta.$

149 When $\beta = 1$, $\mathcal{G}(\beta, d)$ is the class of Lipschitz continuous functions, which is usually required in
150 dynamic pricing literature (see, e.g., [8]). We consider a more general class of Hölder continuous
151 functions with arbitrary $0 < \beta \leq 1$.

152 We first propose Algorithm 1 for our DPLPE model. Our algorithm combines two main ideas: (i)
153 context space binning and approximation; and (ii) pricing with random shock.

154 **Context space binning and approximation.** To learn function $g(\cdot)$, the β-Hölder continuous
155 assumption guarantees that it cannot change dramatically in a local area. This inspires a natural idea
156 of dividing the context space $[0,1]^d$ into different small bins and using a constant to approximate $g(\cdot)$
157 in each bin. Specifically, we divide each coordinate of $[0,1]^d$ into M equally sized segments and get
158 M^d small bins. We then estimate $\mathbb{E}[g(x)|x \in \mathbf{M}_j]$ (and $g(x_t)$ for any $x_t \in \mathbf{M}_j$) using the sample
159 average approximation (SAA) from the residuals $\{d_s - p_s \hat{b}_t : 1 \leq s \leq t-1, x_s \in \mathbf{M}_j\}$, where $\hat{b}_t$ is
160 an estimate for b to be discussed in the next paragraph. It's worth noting that there exists an important
161 trade-off for the choice of M. If M is large, the amount of data collected for each bin will be limited,
162 discouraging the success of learning $g(\cdot)$. If M is small, we may incur a larger approximation error of
163 $g(\cdot)$ by using a constant conditional expectation in each bin, leading to a suboptimal pricing strategy
164 and a greater revenue loss. The specific choice of M is given in Theorem 1.

165 **Pricing with random shock.** The idea of pricing with random shock is adopted from [24]. In
166 each period t, the algorithm first computes a greedy price p_t^g by plugging in the estimates for
167 $g(x_t)$ and b, and then charges a price p_t by adding a random shock Δ_t, which takes the value of
168 δ_t or $-\delta_t$ with equal probability, to the greedy price p_t^g. Following [24], instead of regressing d_t
169 against the true price p_t, we estimate b by regressing d_t against the price shock Δ_t. Noting that

170 $\frac{\sum_{s=1}^{t} \Delta_s d_s}{\sum_{s=1}^{t} \Delta_s^2} = \frac{\sum_{s=1}^{t} \Delta_s (b p_s + g(x_s) + \varepsilon_s)}{\sum_{s=1}^{t} \delta_s^2} = b + \frac{\sum_{s=1}^{t} \Delta_s (b p_s^g + g(x_s) + \varepsilon_s)}{\sum_{s=1}^{t} \delta_s^2}$. Since Δ_s is independent of

171 $b p_s^g + g(x_s) + \varepsilon_s$ for each $1 \leq s \leq t$ and has zero mean, $\frac{\sum_{s=1}^{t} \Delta_s d_s}{\sum_{s=1}^{t} \Delta_s^2}$ is an unbiased estimate for b.

172 This also explains the necessity of regressing d_t against the random shock Δ_t.

Algorithm 1: Algorithm for Dynamic Pricing with Linear Price (ADPLP)

---

1 **Input:** price range $[\underline{p}, \overline{p}]$, bounds on the price coefficient $\underline{b}$ and $\overline{b}$, number of bins M

2 **Initialization:**

3 Partition each coordinate of $[0,1]^d$ into M segments of equal length, denoted as $\mathbf{M}_j$ for
$j = 1, 2, \cdots, M^d$;

4 Initialize $\mathcal{D}_{1,j} = \emptyset$ for each $j \in [M^d]$ and $\hat{b}_1 = \frac{\underline{b} + \overline{b}}{2}$;

5 **Main Steps:**

6 **for** $t = 1, 2, \cdots, T$ **do**

7   Set $\delta_t \leftarrow t^{-\frac{1}{4}}$;

8   Observe x_t and find $j \in [M^d]$ such that $x_t \in \mathbf{M}_j$;

9   If $\mathcal{D}_{t,j} = \emptyset$, set $\hat{a}_{t,j} = -\hat{b}_t (\underline{p} + \overline{p})$; otherwise, set $\hat{a}_{t,j} \leftarrow \frac{\sum_{(x_k, p_k, d_k) \in \mathcal{D}_{t,j}} (d_k - p_k \hat{b}_t)}{|\mathcal{D}_{t,j}|}$;

10   Set unconstrained greedy price: $p_t^u \leftarrow -\frac{\hat{a}_{t,j}}{2 \hat{b}_t}$;

11   Project greedy price: $p_t^g \leftarrow \mathbf{Proj}(p_t^u, [\underline{p} + \delta_t, \overline{p} - \delta_t])$;

12   Generate an independent random variable $\Delta_t \leftarrow \delta_t$ w.p. $\frac{1}{2}$ and $\Delta_t \leftarrow -\delta_t$;

13   Set price $p_t \leftarrow p_t^g + \Delta_t$;

14   Observe realized demand d_t;

15   Update $\mathcal{D}_{t+1,j} \leftarrow \mathcal{D}_{t,j} \cup \{(x_t, p_t, d_t)\}$ and $\mathcal{D}_{t+1,i} \leftarrow \mathcal{D}_{t,i}$ for $i \neq j$;

16   Update $\hat{b}_{t+1} \leftarrow \mathbf{Proj}(\frac{\sum_{s=1}^{t} \Delta_s d_s}{\sum_{s=1}^{t} (\Delta_s)^2}, [\underline{b}, \overline{b}])$;

17 **end for**

---

173 The following theorem shows the regret upper bound of Algorithm 1, whose proof is in Appendix A.

174 **Theorem 1** *Let Algorithm 1 run with $M = \lceil T^{\frac{1}{d+2\beta}} \rceil$. Under Assumption 1 and the known bound*

175 $[\underline{b}, \overline{b}]$ *of the unknown b, the regret of Algorithm 1 is*

$$\widetilde{\mathcal{O}}\left(\sqrt{T} \vee T^{\frac{d}{d+2\beta}} \right).$$

176 The bound in Theorem 1 consists of two terms $\widetilde{\mathcal{O}}(\sqrt{T})$ and $\widetilde{\mathcal{O}}(T^{\frac{d}{d+2\beta}})$. The first term $\widetilde{\mathcal{O}}(\sqrt{T})$ arises

177 from our introduction of random shocks reflecting the complexity of learning b. For the simplest

178 linear demand model without context, the squared estimation error of b incurred by an asymptotically

179 optimal policy is in the order of $t^{-1/2}$ (see [18]). Therefore, a cumulative regret $\mathcal{O}(\sqrt{T})$ is in general

180 unavoidable. The second term $\widetilde{\mathcal{O}}(T^{\frac{d}{d+2\beta}})$ s incurred by our inaccuracy of approximating the non-

181 parametric function $g(\cdot)$ with a constant in each small bin. It captures the complexity for learning the

182 non-parametric function $g(\cdot)$. This bound is monotonically increasing in dimension d, which agrees

183 with the intuition that a higher dimension of the context space leads to a more challenging task of

184 learning the function $g(\cdot)$. In addition, this bound decreases in β. This is consistent with the fact that

185 if $g(\cdot)$ is smoother (i.e., β is larger), it can be more accurately approximated by a constant in local

186 bins. We also note that only when $d = 1$ and $\beta > \frac{1}{2}$ is $\widetilde{\mathcal{O}}(\sqrt{T})$ larger than $\widetilde{\mathcal{O}}(T^{\frac{d}{d+2\beta}})$. Otherwise,

187 the regret upper bound is always $\widetilde{\mathcal{O}}(T^{\frac{d}{d+2\beta}})$.

188 We then establish the regret lower bound. We denote the regret of policy π as $R_{g,b,\mathcal{P},\mathcal{D}}^{\pi}(T)$ when the

189 demand function is $bp + g(x) + \varepsilon$, and the distributions of x and ε are $\mathcal{P}$ and $\mathcal{D}$ respectively. We use

190 $\mathcal{E}(\sigma)$ to denote the class of sub-Gaussian distributions with variance proxy σ^2.

191 **Theorem 2** *For any $\mathcal{G}(\beta, d)$, $0 < \underline{b} \leq \overline{b}$ and $\sigma \geq 0$, there exists a constant $K_1 > 0$ independent of*

192 *T, such that for any admissible policy π,*

$$\sup_{\substack{g \in \mathcal{G}(\beta, d), \\ b \in [\underline{b}, \overline{b}], \mathcal{P}, \mathcal{D} \in \mathcal{E}(\sigma)}} R_{g,b,\mathcal{P},\mathcal{D}}^{\pi}(T) \geq K_1 \cdot \left(\sqrt{T} \vee T^{\frac{d}{d+2\beta}} \right).$$

193 Theorem 2 shows that the regret upper bound achieved by Algorithm 1 in Theorem 1 is unimprovable
194 in terms of the dependency on the learning horizon T. The first lower bound $\Omega(\sqrt{T})$ can be directly
195 obtained from the existing literature, e.g., [17]. To prove the second lower bound $\Omega(T^{\frac{d}{d+2\beta}})$, we
196 construct a series of Hölder continuous functions in $[0,1]^d$ that are difficult to distinguish from each
197 other. We then apply the Bretagnolle–Huber inequality (see [6]) and KL divergence arguments to
198 bound the regret of any algorithm from below. See our construction and detailed proof in Appendix B.

199 We next compare our result with two relevant papers [24] and [8]. In [24], the same demand model
200 $bp + g(x)$ is considered, but the performance of their learning algorithm is benchmarked with the
201 optimal policy for the "best" linear demand function. In this case, they show that the optimal regret
202 is $\Theta(\sqrt{T})$. By contrast, our regret notion is defined against the optimal policy for the *true* demand
203 function, and thus, our optimal regret has an extra term $\widetilde{\Theta}(T^{\frac{d}{d+2\beta}})$ capturing the complexity of
204 learning the function $g(\cdot)$. In [8], the authors prove the optimal regret $\widetilde{\Theta}(T^{\frac{d+2}{d+4}})$ for general Lipschitz
205 continuous demand functions (in both context and price) assuming local concavity of the revenue
206 function. When $\beta = 1$, the demand functions we consider here are a special case of theirs. For this
207 case, our optimal regret becomes $\widetilde{\Theta}(\sqrt{T} \vee T^{\frac{d}{d+2}})$, which is strictly lower than theirs. This reduction
208 of the optimal regret benefits from the separated effects of the price and context assumed in our
209 model. In terms of the algorithmic design, the algorithm in [8] divides both the price space and
210 context space into bins, and treats the learning problem in each small bin as independent ones. In our
211 setting, we leverage all the historical data to estimate the price sensitivity and achieve *information*
212 *sharing* among different bins in the context space.

3 Dynamic Pricing with Linear Contextual Effect (DPLCE)

214 In this section, we study the semi-parametric demand model with linear contextual effect, i.e.,
215 $\mu(p_t, x_t) = f(p_t) + a^\top x_t$. We assume $\|a\| \le \overline{a}$ for some constant $\overline{a} > 0$. We now introduce our
216 assumption on function $f(\cdot)$.

Assumption 2 *The function $f : [\underline{p}, \overline{p}] \to \mathbb{R}$ is kth-order smooth with degree $k \ge 1$ and parameter δ,*
218 *denoted by $f \in \mathcal{F}^k([\underline{p}, \overline{p}]; \delta)$, meaning that f is $\mathfrak{b}(k)$-times differentiable on $[\underline{p}, \overline{p}]$ and*

$$\left| f^{(\mathfrak{b}(k))}(p) - f^{(\mathfrak{b}(k))}(p') \right| \le \delta \left| p - p' \right|^{k - \mathfrak{b}(k)}, \quad \forall p, p' \in [\underline{p}, \overline{p}], \tag{1}$$

219 *where $\mathfrak{b}(k) := \sup\{i \in \mathbb{N} : i < k\}$ is the maximal integer that is strictly less than k.*

220 Eq. (1) requires that the $\mathfrak{b}(k)$th-order derivative of $f(\cdot)$ is $(k - \mathfrak{b}(k))$-Hölder continuous. This
221 assumption also implies that all the ith-order derivatives are bounded for $i \le \mathfrak{b}(k)$ (i.e., $C_0 :=$
222 $\sup_{0 \le i \le \mathfrak{b}(k)} \sup_{p \in [\underline{p}, \overline{p}]} |f^{(i)}(p)| < \infty$). When k is integer, i.e., $\mathfrak{b}(k) = k - 1$, Eq. (1) becomes the
223 Lipschitz-continuous condition and Assumption 2 reduces to Assumption 1 in [31]. Different from
224 [31] that sees δ as a constant, we allow the order of δ to depend on T, e.g., $\delta = \mathcal{O}(T^{-\lambda})$ for some
225 $\lambda \ge 0$. As will be seen later, δ shows how tightly $f(p)$ can be approximated by a polynomial function,
226 and will have impacts on both the regret upper bound and lower bound.

227 We propose Algorithm 2 for DPLCE. The key ideas are three-fold: (i) local polynomial approximation;
228 (ii) biased linear contextual bandit and OFU; and (iii) optimism over OFU for price selection.

Local polynomial approximation. The idea of local approximation for smooth non-parametric
230 functions through polynomial functions is borrowed from [31]. Specifically, we partition the price
231 interval $[\underline{p}, \overline{p}]$ into N segments of equal size, denoted as $\mathbf{I}_1, \cdots, \mathbf{I}_N$. For each price segment $\mathbf{I}_j :=$
232 $[a_j, b_j)$, we use a polynomial function of degree $\mathfrak{b}(k)$: $P_{\mathbf{I}_j}(p) := \sum_{i=0}^{\mathfrak{b}(k)} \frac{f^{(i)}(a_j)}{i!}(p - a_j)^i$, to locally
233 approximate the true function $f(p)$. To learn the the coefficients of $P_{\mathbf{I}_j}(p)$, we apply the ridge
234 regression method. By our assumption that $f^{\mathfrak{b}(k)}(p)$ is $(k - \mathfrak{b}(k))$-Hölder continuous, it can be
235 verified from Taylor expansion that $|f(p) - P_{\mathbf{I}_j}(p)| \le |\frac{(p - a_j)^{\mathfrak{b}(k)}}{\mathfrak{b}(k)!}| \cdot |f^{(\mathfrak{b}(k))}(a_j') - f^{(\mathfrak{b}(k))}(a_j)| \le$
236 $\delta \cdot \frac{(\overline{p} - \underline{p})^k}{\mathfrak{b}(k)! \cdot N^k} = \mathcal{O}(\frac{\delta}{N^k})$, where $a_j' \in [a_j, p]$. Therefore, δ reflects how tightly f can be approximated
237 by a local polynomial function. Moreover, the number of price segments N needs to be carefully
238 selected to balance the accuracy of local polynomial approximation and the learning efficiency for
239 each price segment. The specific choice of N is given in Theorem 3.

Algorithm 2: Algorithm for Dynamic Pricing with Linear Context (ADPLC)

---

1 **Input:** time horizon T, price range $[\underline{p}, \overline{p}]$, degree k, parameter C_0, context dimension d, upper
  bound $\bar{a}$, number of price segments N, error control terms Δ, noise variance proxy σ
2 **Initialization:**
3 Partition $[\underline{p}, \overline{p}]$ into N segments of equal length, denoted as $\mathbf{I}_i$ for $i = 1, 2, \cdots, N$;
4 Initialize for all $i \in [N]$: $\mathcal{D}_i = \emptyset$.
5 **Main Steps:**
6 **for** $t = 1, 2, \cdots, T$ **do**
7   Observe x_t;
8   **for** $i = 1, 2, \cdots, N$ **do**
9         $(\hat{\theta}_{t,i}, \hat{a}_{t,i}, \gamma_{t,i}, V_{t,i}) = \texttt{RLC}(\mathfrak{b}(k), d, \mathbf{I}_i, \mathcal{D}_i, \Delta, 1/T^2, C_0, \sigma, \bar{a})$;
10         $\hat{r}_{t,i} = \max_{p \in \mathbf{I}_i} p \times \left(\langle \hat{\theta}_{t,i}, \varphi(p) \rangle + \langle \hat{a}_{t,i}, x_t \rangle + \gamma_{t,i} \sqrt{\phi(p, x_t)^\top V_{t,i}^{-1} \phi(p, x_t)} + \Delta \right)$;
11         $\hat{p}_{t,i} = \arg\max_{p \in \mathbf{I}_i} p \times \left(\langle \hat{\theta}_{t,i}, \varphi(p) \rangle + \langle \hat{a}_{t,i}, x_t \rangle + \gamma_{t,i} \sqrt{\phi(p, x_t)^\top V_{t,i}^{-1} \phi(p, x_t)} + \Delta \right)$;
12   **end for**
13   Select $i_t = \arg\max_{i \le N-1} \hat{r}_{t,i}$ and charge $p_t = \hat{p}_{t,i_t}$;
14   Observe realized demand d_t;
15   Update $\mathcal{D}_{i_t} \leftarrow \mathcal{D}_{i_t} \cup \{(x_t, p_t, d_t)\}$;
16 **end for**

Algorithm 3: Regression with Linear Context (RLC)

---

1 **Input:** polynomial degree k, context dimension d, domain $\mathbf{I} = [l, u]$, history $\mathcal{D}$, bias Δ,
  probability ϵ, smoothness parameter C, noise variance proxy σ, upper bound $\bar{a}$
2 Compute $\lambda = \frac{(u-l)^{2k} - 1}{(u-l)^2 - 1} + d$;
3 Compute $\gamma = \sigma \sqrt{(d+k) \ln\left(\frac{d+k+|\mathcal{D}|}{d+k}\right) - 2 \ln \epsilon} + \lambda^{\frac{1}{2}} (C^2 k + \bar{a}^2)^{\frac{1}{2}} + \Delta \sqrt{|\mathcal{D}|}$;
4 Compute $V = \lambda I_{(k+d) \times (k+d)} + \sum_{(x,p,d) \in \mathcal{D}} \phi(p, x) \phi(p, x)^\top$, where $\phi(p, x) = (\varphi(p)^\top, x^\top)^\top$
  and $\varphi(p) = (1, (p-l), \cdots, (p-l)^{k-1})^\top$;
5 Compute Ridge estimate
  $(\hat{\theta}, \hat{a}) = \arg\min \sum_{(x,p,d) \in \mathcal{D}} (d - \langle \theta, \varphi(p) \rangle - \langle a, x \rangle)^2 + \lambda(\|\theta\|_2^2 + \|a\|_2^2)$;
6 **Output:** $\hat{\theta}, \hat{a}, \gamma, V$

Biased linear contextual bandit and OFU. To suggest a good price for each segment, we borrow the biased linear contextual bandit from [31]. Specifically, for each $t \ge 1$ and $p_t \in \mathbf{I}_j$, we can rewrite $D_t(p_t)$ as follows: $D_t(p_t) = P_{\mathbf{I}_j}(p_t) + a^\top x_t + \beta_t = \theta_j^\top \varphi(p_t) + a^\top x_t + \beta_t$, where $\beta_t := f(p_t) - P_{\mathbf{I}_j}(p_t) + \varepsilon_t$, $\varphi(p_t) := (1, (p_t - a_j), \cdots, (p_t - a_j)^{\mathfrak{b}(k)})$ and $\theta_j \in \mathbb{R}^{\mathfrak{b}(k)+1}$ whose ith element is $\frac{f^{(i-1)}(a_j)}{(i-1)!}$ for $1 \le i \le \mathfrak{b}(k) + 1$. This model is similar to the linear contextual bandit in the literature (see, e.g., [1], [9]), where the OFU idea that selects actions in an optimistic way is commonly adopted. The key difference is that β_t contains a biased term that is not mean-zero and depends on the pricing decision. We adapt the idea of adding an additional term Δ when implementing the OFU principle to compute an optimistic price and optimistic revenue from [31].

Optimism over OFU for price selection. In the absence of context, the optimal price in [31] is *fixed*. To learn this fixed optimal price, [31] propose the idea of embedding the biased linear contextual bandit into a multi-armed bandit protocol that treats each price segment as an arm. The segment to which the fixed optimal price belongs is regraded as the "best" arm. By contrast, in our context-based setting, the optimal price depends on the random context revealed in each period and changes over time. Thus, our "best" arm in each period also changes, and the idea of multi-armed bandit protocol in [31] does not work. To overcome this challenge, we propose a new idea of optimism over OFU, which proceeds as follows. We first implement the OFU principle to each price segment $\mathbf{I}_i$ and

257 compute an optimistic price $\hat{p}_{t,i}$ and optimistic revenue $\hat{r}_{t,i}$. Then we choose the most optimistic
258 price from the N candidate prices $\hat{p}_{t,1}, \ldots, \hat{p}_{t,N}$ that achieves the highest optimistic revenue.

259 The following theorem presents the regret upper bound for Algorithm 2, whose proof is in Appendix C.

260 **Theorem 3** *Let Algorithm 2 run with* $N = \lceil \delta^{\frac{2}{2k+1}} T^{\frac{1}{2k+1}} \rceil + 1$ *and* $\Delta = \delta(\overline{p} - \underline{p})^k / N^k$. *Under*
261 *Assumption 2 and* $||a|| \leq \overline{a}$, *the regret of Algorithm 2 is*

$$\widetilde{\mathcal{O}}\left(d\big(\sqrt{T} \vee (\delta T^{k+1})^{\frac{1}{2k+1}}\big)\right).$$

262 First, when δ is a constant and k is an integer, the regret upper bound becomes $\widetilde{\mathcal{O}}(dT^{\frac{k+1}{2k+1}})$, recovering
263 Theorem 1 in [31] for the setting without contexts (i.e., $d = 1$ and x is a constant). As k becomes
264 larger while keeping δ a constant, the upper bound decreases according to $\widetilde{\mathcal{O}}(dT^{\frac{k+1}{2k+1}})$. In the extreme
265 case of $k = \infty$, the upper bound becomes $\widetilde{\mathcal{O}}(d\sqrt{T})$, which coincides with the optimal regret rate for
266 the linear model $d(p, x) = bp + a^\top x$ (see, e.g., [3])[1]. Second, when δ is not a constant whose order
267 can shrink as T increases, Theorem 3 shows an *instance-dependent* bound which further differentiates
268 our result from that in [31]. We can see that when $\delta = \Omega(T^{-\frac{1}{2}})$, the regret bound is $\widetilde{\mathcal{O}}(\delta^{\frac{1}{2k+1}} T^{\frac{k+1}{2k+1}})$,
269 and when δ decreases to $\mathcal{O}(T^{-\frac{1}{2}})$, the regret bound is always $\widetilde{\mathcal{O}}(\sqrt{T})$. This shows that the magnitude
270 of δ greatly affects the regret upper bound, and the smaller δ is, the lower the regret bound will be.
271 This is because when δ becomes smaller, the approximation error using a local polynomial function
272 $\mathcal{O}(\frac{\delta}{N^k})$ becomes smaller, leading to more accurate estimates for $f(\cdot)$. Since the polynomial function
273 is differentiable infinitely many times, its regret is $\widetilde{\mathcal{O}}(\sqrt{T})$ from Section 3.4.1 in [31]. Therefore, as δ
274 decreases, the regret upper bound decays to $\widetilde{\mathcal{O}}(\sqrt{T})$, which is attained when $\delta = \mathcal{O}(T^{-\frac{1}{2}})$. To prove
275 Theorem 3, by the idea of optimism over OFU, we can upper bound the regret by the length of the
276 confidence interval which can be controlled by the well-known concentration inequality in [1].

277 We then establish the regret lower bound. Similar to Theorem 1, we denote the regret of policy π by
278 $R^\pi_{f,a,\mathcal{P},\mathcal{D}}(T, k, \delta)$ when the demand function is $f(p) + a^\top x + \varepsilon$, where $f \in \mathcal{F}^k([\underline{p}, \overline{p}; \delta])$, and the
279 distributions of x and ε are $\mathcal{P}$ and $\mathcal{D}$ respectively.

280 **Theorem 4** *For any* $\mathcal{F}^k([\underline{p}, \overline{p}; \delta))$, $\overline{a} \geq 0$, *and* $\sigma \geq 0$, *there exists a constant* $K_2 > 0$ *independent of*
281 T *and* δ, *such that for any admissible policy* π,

$$\sup_{\substack{f \in \mathcal{F}^k([\underline{p}, \overline{p}];\delta), \\ \|a\| \leq \overline{a}, \mathcal{P}, \mathcal{D} \in \mathcal{E}(\sigma)}} R^\pi_{f,a,\mathcal{P},\mathcal{D}}(T, k, \delta) \geq K_2 \cdot \left(\sqrt{T} \vee \big(\delta T^{k+1}\big)^{\frac{1}{2k+1}}\right). \tag{2}$$

282 Theorem 4 shows that the regret upper bound achieved by Algorithm 2 in Theorem 3 is unimprovable
283 in terms of its dependency on the learning horizon T and parameter δ. Note that the upper bound in
284 Theorem 3 grows linearly in d, but the lower bound in Theorem 4 is independent of d. This is because
285 in the lower bound analysis, we simply consider $a = \mathbf{0}$. We leave the problem of analyzing the more
286 complicated dimension-dependent lower bound as future research. The first lower bound $\Omega(\sqrt{T})$ in
287 Eq. (2) directly follows from the existing literature (e.g., [17]). The proof of the second lower bound
288 $\Omega((\delta T^{k+1})^{\frac{1}{2k+1}})$ relies on constructing a series of kth-order smooth functions with parameter δ and
289 applying Pinsker's inequality to bound the total variation of two probability measures through their
290 KL divergence. See our construction and detailed proof in Appendix D.

4 Numerical Study

292 In this section, we conduct a numerical study to test the empirical performances of our algorithms.
293 We measure the performance of a learning algorithm π by the relative regret defined as follows:
294 $\frac{\sum_{t=1}^{T} \mathbb{E}[p_t^* d(p_t^*, x_t) - p_t d(p_t, x_t)]}{\sum_{t=1}^{T} \mathbb{E}[p_t^* d(p_t^*, x_t)]} \times 100\%$. For both models, we compare our algorithms with the linear
295 greedy algorithm that estimates the demand function by a linear function and myopically selects the
296 optimal price that maximizes the proxy revenue in each period t. For our DPLPE model, we also
297 compare our algorithm with the random price shock (RPS) algorithm proposed by [24]. For each
298 instance, we repeat our experiments for 50 independent runs, and approximate the relative regret by
299 the empirical relative regret averaged over 50 runs.

---

[1]Note that the linear model is a special case of DPLCE by letting $k = \infty$.

Numerical results for DPLPE model. For our DPLPE model with demand function $d(p, x_t) = bp + g(x_t)$, we set $b = -5$, $\varepsilon \sim \mathcal{N}(0, 5)$, $[\underline{b}, \overline{b}] = [-8, -3]$, $[\underline{p}, \overline{p}] = [1, 19]$, $x_t \sim \text{Uniform}([0, 1]^d)$, and consider the following form of function $g(x)$:

$$g(x) := \begin{cases} 100 \times (D(x, \partial[0, 1]^d))^\beta + 100 & \text{if } D(x, \partial[0, 1]^d) \le \frac{1}{4}, \\ 100 \times (\frac{1}{4})^\beta - 300 \times (D(x, \partial[0, 1]^d) - \frac{1}{4})^\beta + 100 & \text{otherwise}, \end{cases}$$

where $D(x, \partial[0, 1]^d)$ denotes the Euclidean distance between x and the boundary of $[0, 1]^d$. In Figure 1(a), we compare the empirical relative regret of our ADPLP with those of RPS algorithm and the linear greedy algorithm. The figure shows that our algorithm performs much better than both algorithms. In Figure 1(b), we investigate the effect of d on the empirical relative regret of ADPLP by varying d in the set $\{1, 3, 10\}$ while keeping $\beta = 1$. As shown in the figure, as d decreases, the regret decreases, which is consistent with our theoretical results. In Figure 1(c), we test the effect of β on the empirical relative regret of ADPLP by varying β in the set $\{0.2, 0.4, 0.6, 1\}$ while keeping $d = 1$. When β is relatively small, a slight increment of β, e.g., $\beta = 0.2$ to $\beta = 0.4$, will lead to significant speed-up of the convergence. The results of $\beta = 0.6$ and $\beta = 1$ are very close, which indicates that when β is relatively large, increasing β may only bring limited improvement.

(a) Regret under $d = 2$, $\beta = 1$ (b) Effect of d on ADPLP   (c) Effect of β on ADPLP

Figure 1: Empirical relative regret for DPLPE model

Numerical results for DPLCE model. For our DPLCE model, we consider the following demand: $D_t(p_t) = -\frac{4}{15}\delta p_t^{2.5} + 30 + \frac{1}{d}\mathbf{1}_d \cdot x_t + \varepsilon_t$, where $\mathbf{1}_d$ denotes $(1, 1, \cdots, 1) \in \mathbb{R}^d$, x_t is uniformly distributed on $[0, 1]^d$ independently and $\varepsilon_t \sim \mathcal{N}(0, 0.1^2)$. It can be verified that $k = 2.5$ in this case. In Figure 2(a), we fix $d = 2$, $\delta = 3.75$ and $[\underline{p}, \overline{p}] = [2.6, 3.8]$, and compare the empirical relative regret of our ADPLC with that of the linear greedy algorithm. The linear greedy algorithm has almost a constant empirical relative regret, showing that it fails to identify the optimal solution. By contrast, the empirical relative regret of ADPLC decreases as t increases. We also test the effect of δ on the empirical relative regret of ADPLC by varying $\beta \in \{3.75, 2.5, 1\}$. As shown in Figure 2(b), as δ becomes smaller, the empirical relative regret decreases, which is consistent with our theoretic results.

(a) Regret under $\delta = 3.75$ (b) Effect of δ on ADPLC

Figure 2: Empirical relative regret for DPLCE model

5 Conclusion

In this paper, we study the context-based dynamic pricing with online learning, where the unknown expected demand admits a partially linear semi-parametric structure. For both models DPLPE and DPLCE, we develop an efficient learning algorithm and characterize the optimal regret by proving matching upper and lower bounds. We note that our algorithms need to have the preliminary knowledge about the smoothness parameters β in DPLPE model and k and δ in DPLCE model. One important direction for future research is to explore whether parameter-free algorithms can be developed and still achieve the optimal regret rate.

References

[1] Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems*, pages 2312–2320, 2011.

[2] Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2-3):235–256, 2002.

[3] Gah-Yi Ban and N Bora Keskin. Personalized dynamic pricing with machine learning: High-dimensional features and heterogeneous elasticity. *Management Science*, 67(9):5549–5568, 2021.

[4] Omar Besbes and Assaf Zeevi. Dynamic pricing without knowing the demand function: Risk bounds and near-optimal algorithms. *Operations Research*, 57(6):1407–1420, 2009.

[5] Omar Besbes and Assaf Zeevi. Blind network revenue management. *Operations research*, 60(6):1537–1550, 2012.

[6] J Bretagnolle and C Huber. Estimation des densités: risque minimax. *Zeitschrift für Wahrscheinlichkeitstheorie und verwandte Gebiete*, 47(2):119–137, 1979.

[7] Josef Broder and Paat Rusmevichientong. Dynamic pricing under a general parametric choice model. *Operations Research*, 60(4):965–980, 2012.

[8] Ningyuan Chen and Guillermo Gallego. Nonparametric pricing analytics with customer covariates. *Operations Research*, 69(3):974–984, 2021.

[9] Wei Chu, Lihong Li, Lev Reyzin, and Robert Schapire. Contextual bandits with linear payoff functions. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pages 208–214. JMLR Workshop and Conference Proceedings, 2011.

[10] Maxime C Cohen, Ilan Lobel, and Renato Paes Leme. Feature-based dynamic pricing. *Management Science*, 66(11):4921–4943, 2020.

[11] Varsha Dani, Thomas P Hayes, and Sham M Kakade. Stochastic linear optimization under bandit feedback. In *Proceedings of the 21st Conference on Learning Theory*, 2008.

[12] Arnoud V den Boer. Dynamic pricing and learning: historical origins, current research, and new directions. *Surveys in operations research and management science*, 20(1):1–18, 2015.

[13] Robert F Engle, Clive WJ Granger, John Rice, and Andrew Weiss. Semiparametric estimates of the relation between weather and electricity sales. *Journal of the American statistical Association*, 81(394):310–320, 1986.

[14] Jianqing Fan, Yongyi Guo, and Mengxin Yu. Policy optimization using semiparametric models for dynamic pricing. *Available at SSRN 3922825*, 2021.

[15] Yichun Hu, Nathan Kallus, and Xiaojie Mao. Smooth contextual bandits: Bridging the parametric and non-differentiable regret regimes. In *Conference on Learning Theory*, pages 2007–2010. PMLR, 2020.

[16] Adel Javanmard and Hamid Nazerzadeh. Dynamic pricing in high-dimensions. *The Journal of Machine Learning Research*, 20(1):315–363, 2019.

[17] N Bora Keskin. Optimal dynamic pricing with demand model uncertainty: A squared-coefficient-of-variation rule for learning and earning. *Available at SSRN 2487364*, 2014.

[18] N.B. Keskin and A. Zeevi. Dynamic pricing with an unknown demand model: Asymptotically optimal semi-myopic policies. *Operations Research*, 62(5):1142–1167, 2014.

[19] Yiyun Luo, Will Wei Sun, et al. Distribution-free contextual dynamic pricing. *arXiv preprint arXiv:2109.07340*, 2021.

[20] Jieming Mao, Renato Leme, and Jon Schneider. Contextual pricing for lipschitz buyers. *Advances in Neural Information Processing Systems*, 31, 2018.

[21] Sentao Miao, Xi Chen, Xiuli Chao, Jiaxi Liu, and Yidong Zhang. Context-based dynamic pricing with online clustering. *arXiv preprint arXiv:1902.06199*, 2019.

[22] Sentao Miao and Yining Wang. Network revenue management with nonparametric demand learning:\sqrt {T}-regret and polynomial dimension dependency. *Available at SSRN 3948140*, 2021.

[23] Jonas W Mueller, Vasilis Syrgkanis, and Matt Taddy. Low-rank bandit methods for high-dimensional dynamic pricing. *Advances in Neural Information Processing Systems*, 32, 2019.

[24] Mila Nambiar, David Simchi-Levi, and He Wang. Dynamic learning and pricing with model misspecification. *Management Science*, 65(11):4980–5000, 2019.

[25] Vianney Perchet and Philippe Rigollet. The multi-armed bandit problem with covariates. *The Annals of Statistics*, 41(2):693–721, 2013.

[26] Sheng Qiang and Mohsen Bayati. Dynamic pricing with demand covariates. *Available at SSRN 2765257*, 2016.

[27] Philippe Rigollet and Assaf Zeevi. Nonparametric bandits with covariates. *arXiv preprint arXiv:1003.1630*, 2010.

[28] Paat Rusmevichientong and John N Tsitsiklis. Linearly parameterized bandits. *Mathematics of Operations Research*, 35(2):395–411, 2010.

[29] Virag Shah, Ramesh Johari, and Jose Blanchet. Semi-parametric dynamic contextual pricing. *Advances in Neural Information Processing Systems*, 32, 2019.

[30] Aleksandrs Slivkins. Contextual bandits with similarity information. In *Proceedings of the 24th annual Conference On Learning Theory*, pages 679–702. JMLR Workshop and Conference Proceedings, 2011.

[31] Yining Wang, Boxiao Chen, and David Simchi-Levi. Multimodal dynamic pricing. *Management Science*, 67(10):6136–6152, 2021.

[32] Zizhuo Wang, Shiming Deng, and Yinyu Ye. Close the gaps: A learning-while-doing algorithm for single-product revenue management problems. *Operations Research*, 62(2):318–331, 2014.

[33] Jianyu Xu and Yu-Xiang Wang. Logarithmic regret in feature-based dynamic pricing. *Advances in Neural Information Processing Systems*, 34, 2021.

[34] Jianyu Xu and Yu-Xiang Wang. Towards agnostic feature-based dynamic pricing: Linear policies vs linear valuation with unknown noise. In *International Conference on Artificial Intelligence and Statistics*, pages 9643–9662. PMLR, 2022.

[35] Adonis Yatchew and Joungyeo Angela No. Household gasoline demand in canada. *Econometrica*, 69(6):1697–1709, 2001.

[36] Scott L Zeger and Peter J Diggle. Semiparametric models for longitudinal data with application to cd4 cell numbers in hiv seroconverters. *Biometrics*, pages 689–699, 1994.