CHATQA 2: BRIDGING THE GAP TO PROPRIETARY LLMS IN LONG CONTEXT AND RAG CAPABILITIES

ABSTRACT

In this work, we introduce ChatQA 2, an Llama 3.0-based model with a 128K context window, designed to bridge the gap between open-source LLMs and leading proprietary models (e.g., GPT-4-Turbo) in long context understanding and retrieval-augmented generation (RAG) capabilities. These two capabilities are essential for LLMs to process large volumes of information that cannot fit into a single prompt and are complementary to each other, depending on the downstream tasks and computational budgets. We present a detailed continued training recipe to extend the context window of Llama3-70B-base from 8K to 128K tokens, along with a three-stage instruction tuning process to enhance the model's instruction-following, RAG performance, and long-context understanding capabilities. Our results demonstrate that the `Llama3-ChatQA-2-70B` model outperforms most existing state-of-the-art models, including GPT-4-Turbo-2024-04-09, Qwen2-72B-Instruct, and Llama3.1-70B-Instruct, on ultra-long tasks beyond 100K tokens, as well as on the RAG benchmark using only a 4K context window, showing the strong long context capability across varying sequence lengths. We further provide extensive comparisons between direct long-context and RAG solutions using the same state-of-the-art long-context LLMs. Interestingly, we find that the performance of strong long-context LLMs using RAG improves when retrieving a larger number of chunks. With a large set of top-k chunks, RAG consistently outperforms direct long-context solution using the same state-of-the-art long-context models (e.g., `Llama3-ChatQA-2-70B` and Qwen2-72B-Instruct) on both 32K benchmarks and real-world 128K tasks.

1 INTRODUCTION

The open LLM community has made significant progress in advancing the capabilities of open-access large language models (LLMs), including Llama-3-70B-Instruct (Meta-AI, 2024), Qwen2-72B-Instruct (Alibaba-QWen, 2024), Nemotron-4-340B-Instruct (NVIDIA et al., 2024), and Mixtral-8x22B-Instruct-v0.1 (Mistral, 2024). However, performance gaps compared to frontier proprietary models, e.g., GPT-4-Turbo (OpenAI, 2023), still exist in many domains. Additionally, open-access models focused on key domains have been developed, such as DeepSeek-Coder-V2 (Zhu et al., 2024) for coding and math, ChatQA 1.5 (Liu et al., 2024) for conversational QA and retrieval-augmented generation (RAG), and InternVL 1.5 (Chen et al., 2024) for vision-language tasks, which can be on par with GPT-4-Turbo-2024-04-09 (OpenAI, 2023) in the certain domains.

In recent developments, the trend of extending the context window length in LLMs has gained remarkable traction within both the industrial and research communities. All leading proprietary LLMs support very large context window, allowing them to accommodate several hundred pages of text in a single prompt. For example, GPT-4 Turbo (OpenAI, 2023) and Claude 3.5 Sonnet offer a 128K and 200K context window, respectively. Meanwhile, Gemini 1.5 Pro (Gemini-Team, 2024) impressively supports up to a 10M context. Open-access LLMs have also made significant strides to keep up (01.AI et al., 2024; Alibaba-QWen, 2024). For instance, Qwen2-72B-Instruct (Alibaba-QWen, 2024) and Yi-34B (01.AI et al., 2024) support 128K and 200K context windows, respectively. The concurrent work Llama-3.1-70B-Instruct (Meta-AI, 2024) also supports a 128K context window. However, the absence of training data and reproduction recipe makes replicating these models challenging. In addition, these models have mostly been evaluated on synthetic tasks, like Needle in a Haystack (Kamradt, 2023) test, which does not accurately represent real-world downstream

Model Type	Long Context LLM (128K)	Ultra-long (>100K) 4 tasks	Long (32K) 6 tasks	Short (4K) 9 tasks (RAG)
Proprietary	GPT-4-Turbo-2024-04-09	33.16	**51.93**	54.72
OPEN ACCESS	Qwen2-72B-Instruct	39.77	49.94	54.06
	Llama3.1-70B-Instruct	39.81	49.92	52.12
Open Source	Llama3-ChatQA-2-70B	**41.04**	48.15	**56.30**

Table 1: `Llama3-ChatQA-2-70B` versus state-of-the-art long context LLMs across tasks with varying context lengths. Notably, *we open-source the training data and reproduction recipe for building 128K long-context LLMs from pretrained base models with 8K context*, resources that are not currently available for open-access (open-weights) 128K context models like Qwen2 and Llama3.1. Our model achieves the highest average score on four real-world ultra-long context (beyond 100K) tasks from InfiniteBench, and nine short context (within 4K) tasks from CHATRAG BENCH.

task performance. In this work, we aim to create an open source long context recipe that poses the capability at the level of proprietary models (e.g., GPT-4-Turbo-2024-04-09) while focusing on real-world long-context understanding tasks.

On the other hand, the long-context capability of LLMs is sometimes considered a rival technique to retrieval-augmented generation (RAG). In fact, **RAG and long-context techniques complement each other from a pragmatic perspective**. An LLM with a long context window can either process large volumes of text as a prompt or utilize retrieval methods to efficiently extract relevant information from the extensive text, depending on the downstream tasks and accuracy vs. efficiency trade-offs. RAG has efficiency advantages and can easily retrieve relevant contexts for query-based tasks (e.g, QA) from billions of tokens, a feat that long context models cannot achieve so far. Meanwhile, long context models are good at tasks such as summarizing entire documents, where RAG can not perform. As a result, **the state-of-the-art (SOTA) LLM needs to excel at both capabilities, providing options for different downstream tasks and meeting different accuracy-efficiency trade-off requirements.** To compare the solution between long context and RAG, Xu et al. (2024) extended the context window of Llama2 (Touvron et al., 2023b) to 16K and 32K tokens, and studied the interplay between RAG and long-context LLMs. It demonstrates that the RAG method can improve the generation accuracy and inference efficiency of a GPT-3.5-turbo-16k level long context model for QA and query-based summarization tasks.

In this work, we present ChatQA 2, which extends the study of long-context vs RAG by pushing long-context LLMs to the GPT-4-Turbo level capability (with a 128K context window), and combines it with a state-of-the-art long-context retriever for RAG. See Table 1 for an overview of the results. The training data and reproduction recipe for this work are publicly accessible.

Specifically, we make the following contributions:

1. We present a two-step approach to establish the long context capability of Llama3-70B. First, we extend Llama3-70B base's context window from 8K to 128K by continually pretraining it on a mix of SlimPajama (Soboleva et al., 2023) with upsampled long sequences (Fu et al., 2024). Then, we apply a three-stage instruction tuning process on curated datasets to enhance the instruction-following, RAG, and long context understanding capabilities at each respective stage. We find that stage-wise instruction-tuning, by incorporating previous datasets, simplifies experimentation and hyperparameter tuning.

2. We demonstrate that the resulting `Llama3-ChatQA-2-70B` with 128K context window achieves better accuracy than most existing state-of-the-art models, including GPT-4-Turbo-2024-04-09, Qwen2-72B-Instruct, and Llama3.1-70B-Instruct, on both long-context tasks exceeding 100K tokens and the RAG benchmark for conversational QA tasks within a 4K context window.

3. Previous RAG approachs has two potential issues that can undermine downstream task accuracy: *i)* top-k chunk-wise retrieval introduces fragmentation of context, and *ii)* a small top-k leads to low recall, while a larger k introduces too much irrelevant context to the LLM (e.g., see the analysis in Figure 1 of Yu et al., 2024). In contrast, we find that the RAG

performance of our `Llama3-ChatQA-2-70B` is highly robust to variations in chunk size when using a long-context retriever (Wang et al., 2023c; Lee et al., 2024). Even more promising, accuracy consistently improves as the total number of retrieved tokens for input increases.

4. We conduct extensive comparisons between direct long-context and RAG solutions using the same state-of-the-art long-context LLMs. We find that RAG can still outperform GPT-4-Turbo-level long-context models (including our `Llama3-ChatQA-2-70B`) on both 32K benchmarks and real-world 128K tasks, given a sufficient number of top-k chunks.

We organize the rest of the paper as follows. We discuss related work in § 2. We introduce the continued pretraining for context window extension in § 3.1 and the three-stage instruction tuning in § 3.2. We report results in § 5 and conclude the paper in § 7.

2 RELATED WORK

2.1 LONG CONTEXT LLM

The trend of extending the context window in LLM starts by Claude with 100K token context (Anthropic, 2023). Although the underlying long context techniques behind proprietary models are unclear, the open LLM and research community has developed many methods to extend the context window of LLMs through continued training or fine-tuning (Kaiokendev, 2023; Nijkamp et al., 2023; Chen et al., 2023a; Tworkowski et al., 2023; Chen et al., 2023b; Peng et al., 2023; Xiong et al., 2023; Fu et al., 2024), especially for open-access LLMs (Touvron et al., 2023a;b) based on rotary position embedding (RoPE) (Su et al., 2024).

There are two popular approaches to adapt RoPE for long-context inputs: position interpolation (Chen et al., 2023a) and increasing the base frequency θ of RoPE (Xiong et al., 2023; Liu et al., 2023b). Recently, Yi-34B (01.AI et al., 2024) was pretrained with a sequence length of 4K, and its context window was extended to 200K by increasing the RoPE θ from 10,000 to 5M during continued pretraining. Qwen2-72B-Instruct (Alibaba-QWen, 2024) was trained on 32K-length contexts and extrapolated to a 128K context length using YaRN (Peng et al., 2023). Instead of extending the context window of the base model then applying instruction tuning, GradientAI (2024) directly fine-tunes the Llama-3-Instruct, which uses NTK-aware interpolation (Peng et al., 2023) and the formula from Liu et al. (2023b) to scale up θ.

Note that, the Llama-3.1 models (Dubey et al., 2024) with a 128K context window were introduced after the release of this work. We add a comprehensive comparison between ChatQA-2 and Llama-3.1 in the experiments.

2.2 RETRIEVAL-AUGMENTED GENERATION (RAG)

Retrieval with a standalone retriever (e.g., Karpukhin et al., 2020; Wang et al., 2022; Lin et al., 2023; Lee et al., 2024) is a long-standing solution for handling long texts that cannot fit into the context window of language models. In previous work, various retrieval-augmented language models have been proposed (Nakano et al., 2021; Borgeaud et al., 2022; Wang et al., 2023b;a; Guu et al., 2020; Izacard & Grave, 2021; Izacard et al., 2022; Lewis et al., 2020; Huang et al., 2023; Khandelwal et al., 2019; Liu et al., 2024).

In general, the input to a retriever or dense embedding model is a chunk of text (i.e., a sequence of subword tokens), and the output is an embedding vector. These dense embedding vectors are then indexed and retrieved using k-nearest-neighbor retrieval. Previous dense-embedding-based retrievers only supported limited *chunk size* (e.g., 512 tokens) (e.g., Karpukhin et al., 2020; Wang et al., 2022; Lin et al., 2023) due to the context window size of pretrained BERT base model. In top-k chunk-wise retrieval, the short chunk size increases context fragmentation. As a result, extending the context window of retrievers has become popular. For example, Jina Embeddings 2(Günther et al., 2023) and Nomic Embed (Nussbaum et al., 2024) support 8K tokens, while E5-mistral-7B (Wang et al., 2023c) and NV-Embed (Lee et al., 2024) support 32K tokens.

3 METHOD

3.1 EXTENDING CONTEXT WINDOW TO 128K

In this section, we present the method to extend the context window from 8K to 128K for Llama3. Note that, the Llama-3.1 models with 128K context window are released after this work. We compare our `Llama3-ChatQA-2-70B` and `Llama3-ChatQA-2-8B` with Llama-3.1-70B-Instruct and Llama-3.1-8B-Instruct in experiments.

We prepare our long context pretraining corpus from the Slimpajama (Soboleva et al., 2023) following Fu et al. (2024). We upsample long-context documents with the hyperparameter set as 0.1 to produce 10 billion tokens with sequence length of 128k. Since Llama3 is pretrained with a much higher RoPE base frequency of 500,000 compared to Llama2, we increased the RoPE base frequency to 150M accordingly. We set the batch size to 32 to fit 4 million tokens in a batch and use a learning rate of 3e-5 to train 2000 steps (8B tokens in total).

Interestingly, we found it more effective to separate different documents using special characters, such as "", rather than the reserved beginning and ending tokens <BOS> and <EOS>. We hypothesize that the <BOS> and <EOS> tokens in Llama3 signal the model to ignore previous chunks of text after pretraining, which is not helpful for the LLMs to adapt for longer context inputs.

3.2 INSTRUCTION-TUNING WITH LONG CONTEXT DATA

In this section, we present the instruction tuning method designed to enhance both long context understanding capability and RAG performance.

Specifically, we implement three stages of instruction-tuning. For the first two stages, we follow ChatQA 1.5 (Liu et al., 2024), where the model is initially trained on a high-quality instruction-following datasets, and then trained on a blend of conversational QA data with provided context. However, these two stages involve relatively short contexts, with a maximum sequence length of only 4K tokens. To enhance our model's capability to handle very long context sequences up to 128k tokens, we collect a long SFT dataset.

This dataset is collected through two categories: 1) For SFT data sequences less than 32k: We leverage existing long-context datasets from LongAlpaca12k, GPT-4 samples from Open Orca [1], and Long Data Collections [2]. 2) For sequence lengths between 32k and 128k: Since it is challenging to collect such SFT samples, we rely on synthetic datasets. We utilize NarrativeQA (Kočiský et al., 2018), [3] which contains both the ground truth summary and semantically related paragraphs. We assemble all the related paragraphs and randomly insert the ground truth summary to simulate a real long document for its QA pairs. Since we used NarrativeQA for synthetic data generation, we intentionally excluded it from the evaluation benchmarks to avoid any potential data contamination. Both the full long SFT dataset and the short SFT dataset from the first two stages are then blended for training. We set the learning rate at 3e-5 and the batch size at 32.

3.3 LONG CONTEXT RETRIEVER MEETS LONG CONTEXT LLM

As we mentioned in previous section, the current RAG pipeline for LLM has the following issues: *i)* The top-k chunk-wise retrieval introduces non-negligible fragmentation of context for generating accurate answers. For example, previous state-of-the-art dense-embedding based retrievers (e.g., Li et al., 2023; Lin et al., 2023) only support 512 tokens. *ii)* Small top-k (e.g., 5 or 10) usually leads to relatively low recall, while much larger k (e.g., 100) can lead to worse generation (see Table 5 in Xu et al. (2024)) as the previous LLMs could not utilize too many chunked context very well (Liu et al., 2023a). To address the issue, we propose to use the most recent long-context retriever (Wang et al., 2023c; Lee et al., 2024), which can support thousands of tokens. In our setting, we use the E5-mistral embedding model (Wang et al., 2023c) as the retriever. The input of E5-Mistral model is a chunk of text represented by a sequence of subword tokens, and the output is an embedding vector. The long documents or corpus are chunked and embedded into a set of dense embedding vectors. Such dense

---

[1] https://huggingface.co/datasets/Open-Orca/OpenOrca
[2] https://huggingface.co/datasets/togethercomputer/Long-Data-Collections
[3] https://huggingface.co/datasets/deepmind/narrativeqa

embedding vectors are indexed and retrieved by k-nearest-neighbor retrieval at inference time, where the embedding of prompt / question is treated as query.

4   BASELINES AND EVALUATION BENCHMARKS

Long context models   We compare our models against SOTA long context models: 1) GPT-4-Turbo-2024-04-09 (128K context window) (OpenAI, 2023), 2) Qwen2-72B-Instruct (128K context window) (Alibaba-QWen, 2024), 3) Llama-3-70B-Instruct-Gradient-262k (256K context window) (GradientAI, 2024), 4) Llama-3.1-8B-Instruct and Llama-3.1-70B-Instruct (128K context window). Note that, the Llama-3.1 models are released after this work.

Retrieval-augmented generation (RAG)   We apply RAG to our ChatQA 2 models and baseline long-context LLMs when it is applicable to the downstream tasks, such as those with informative prompts or queries. By default, we use the E5-mistral retriever (Wang et al., 2023c), as it supports both short and long contexts. In our experiments, we use a chunk size of 1200 and select the top 5 chunks, as this configuration provides a good trade-off between cost and performance, as demonstrated in the ablation study in Section 6.

To give a comprehensive study of different context lengths, our evaluation benchmarks covers three categories, 1) ultra-long context benchmarks beyond 100K tokens, 2) long context benchmarks within 32K tokens, and 3) short context benchmarks within 4K tokens.

4.1   ULTRA-LONG CONTEXT BENCHMARKS BEYOND 100K TOKENS

InfiniteBench (Zhang et al., 2024b) is proposed to evaluate the ultra-long context capability of LLMs over 100K sequence length. As we focus on real-world english tasks, we only take the four related tasks from the InfiniteBench, i.e. longbook summarization (En.Sum), longbook qa (En.QA), longbook multiple choice (En.MC), and longbook dialogue (En.Dia). En.Sum is a task that requires models to generate a concise summary of the given novel and is evaluated using the ROUGE-L-Sum metric (Lin, 2004). En.QA is annotated by a pipeline that ensures the questions' necessitating of long-range dependencies and reasoning, beyond simple short passage retrieval. Aggregation reasoning and filtering reasoning are the two primary reasoning categories. F1 score is used to evaluate the quality of the answer. En.MC is annotated with the same pipeline of En.QA except that four answer choices are provided and exact matching scores are reported. En.Dia leverages movie and drama scripts from a designated online database [4] with long, multi-role dialogues. Exact matching score is used again to evaluate the prediction accuracy.

4.2   LONG CONTEXT BENCHMARKS WITHIN 32K TOKENS

We use the long context datasets (except NarrativeQA as it is included in our training) from Xu et al. (2024) as our benchmark for long datasets within 32K. There are six datasets in total, where QMSum (QM), Qasper (QASP), QuALITY (QLTY) are token from SCROLLS (Shaham et al., 2022) and HotpotQA (HQA) MuSiQue (MSQ), MultiFieldQA-en (MFQA) are token from LongBench (Bai et al., 2023). Following the official metrics, we report the geometric mean of ROUGE scores (i.e., ROUGE1/2/L) (Lin, 2004) for QM, the exact matching (EM) score for QLTY, and F1 scores for the remaining four datasets QASP, MSQ, HQA and MFQA.

4.3   SHORT CONTEXT WITHIN 4K TOKENS

We use ChatRAG Bench (Liu et al., 2024) as our benchmark for short context within 4k. ChatRAG bench consists of 10 datasets and we exclude HDial as it is included in our training. Following the setup of Liu et al. (2024), for Doc2Dial (D2D), QuAC, and QReCC task with long documents, each document is divided into segments of roughly 300 words. The top 5 relevant chunks are then retrieved as context for each user question. For TopiOCQA and INSCIT, top-20 chunks were retrieved to obtain similar context length to the first three datasets. The other four datasets are CoQA, DoQA, ConvFinQA (CFQA), and SQA, which cover a wide range of domains like finance, children's stories,

---

[4]https://imsdb.com

Figure 1: Needle In A Haystack test for (a) Llama3.1-Instruct 8B, (b) Llama3.1-Instruct-70B, (c) Llama3-ChatQA-2-8B, and (d) Llama3-ChatQA-2-70B, up to 128K context window. We show the result using the same needle: *"The best thing to do in San Francisco is eat a sandwich and sit in Dolores Park on a sunny day."*

literature, mid/high school exams, news, Wikipedia and etc. We use F1 score as the metric to evaluate the generations and report the average score without HDial as it is a fair zero-shot comparisons over different models.

5 RESULTS

In this section, we present the results and comparisons from extensive benchmark evaluations. We begin with the synthetic Needle in a Haystack test, then focus on real-world long context understanding and RAG tasks.

5.1 NEEDLE IN A HAYSTACK

We evaluate our `Llama3-ChatQA-2-70B` and `Llama3-ChatQA-2-8B` model on the Needle In A Haystack (NIAH) test (Kamradt, 2023). This synthetic task is popular for testing the long-context capability of LLMs, and can be considered as a threshold level evaluation. We use the needle test: *"The best thing to do in San Francisco is eat a sandwich and sit in Dolores Park on a sunny day."* We find this is generally a harder pressure test than the "passkey" in a haystack test, which is commonly used by other long-context LLM works. Figure 3 demonstrates the performance of our models up to 128K tokens. It shows that our model achieves 100% accuracy under both test cases. This test confirms our model's excellent long-context retrieval capability.

In addition, we also include the NIAH test for Llama3.1-Instruct 8B and Llama3.1-Instruct-70B. From Figures 1a and 1b, we find that neither model could pass the NIAH test with the needle: *"The best thing to do in San Francisco..."*, although they could pass the easier *Passkey* retrieval test, as shown in Figures 3a and 3b in Appendix.

5.2 ULTRA-LONG CONTEXT EVALUATION BEYOND 100K TOKENS

In this subsection, we evaluate the ultra-long context capability beyond 100K tokens on the real-world tasks from InfiniteBench (Zhang et al., 2024a). Table 2 shows that our model (41.04) outperforms

Model	Avg.	En.Sum	En.QA	En.MC	En.Dia
GPT-4-Turbo-2024-04-09	33.16	17.62	19.29	77.73	18.00
Claude 2	**33.96**	14.50	11.97	62.88	46.50
Yi-34B-200K	< 15.15	< 5	12.17	38.43	< 5
w/ RAG	N/A	N/A	17.69	77.29	N/A
Qwen2-72B-Instruct	**39.77**	31.66	21.46	82.97	23.00
w/ RAG	N/A	N/A	16.48	76.86	N/A
Llama-3-70B-Instruct-Gradient-262k	32.57	14.27	29.52	69.00	17.50
Llama3.1-8B-Instruct	33.17	29.20	31.51	58.95	13.00
w/ RAG	N/A	N/A	15.41	64.63	N/A
Llama3.1-70B-Instruct	**39.81**	30.94	38.49	75.55	14.29
w/ RAG	N/A	N/A	23.44	79.04	N/A
Llama3-ChatQA-2-8B	35.59	17.14	43.51	64.19	17.50
w/ RAG	N/A	N/A	41.48	63.76	N/A
Llama3-ChatQA-2-70B	**41.04**	16.08	48.22	80.35	19.50
w/ RAG	N/A	N/A	40.66	73.80	N/A

Table 2: Evaluation results on InfiniteBench includes real-world long-context understanding tasks beyond a 100K context window. For RAG, we use top-5 retrieved chunks, each with 1200 tokens from E5-mistral retriever (Wang et al., 2023c).

many existing state-of-the-art models, such as GPT4-Turbo-2024-04-09 (33.16), Llama3.1-70B-Instruct (39.81), Qwen2-72B-Instruct (39.77), Llama-3-70B-Instruct-Gradient-262k (32.57) and Claude 2 (33.96), confirming the effectiveness of our recipe and state-of-the-art long-context capability of our model. We find that our model performs extremely well at QA tasks while performs relatively low for summarization. This can be attributed to the lack of summarization data in our SFT recipe. Additionally, we compare Llama3-ChatQA-2-8B to Llama3.1-8B-Instruct and our model again shows better results.

5.3 Long Context Evaluation within 32K Tokens

In this subsection, we evaluate the long context capability within 32K tokens. Table 3 shows that GPT-4-Turbo-2024-04-09 achieves the highest score of 51.93 among all models. Our model scores 48.15, which is higher than Llama-3-70B-Instruct-Gradient-262k but is a bit lower than Qwen2-72B-Instruct (49.94) and Llama3.1-70B-Instruct (49.92). This difference can be attributed to the extensive 32K pretraining and large SFT data implemented by Qwen2-72B-Instruct and Llama3.1-70B-Instruct, while we used a much smaller continued pretraining corpus and SFT datasets.

Additionally, we found that the a default RAG solution (top-5 with chunk size as 1200) perform worse than the top long context solution (e.g. GPT-4-Turbo-2024-04-09, Qwen2-72B-Instruct, Llama3-ChatQA-2-70B), which suggests that SOTA long context LLMs can handle 32K tokens well within their context window.

5.4 ChatRAG Bench: Short Context Evaluation within 4K Tokens

In this subsection, we evaluate the models on the short context tasks within 4K tokens from CHATRAG BENCH (Liu et al., 2024). The results can be found in Table 4. Our model achieves an average score of 56.30, outperforming most existing SOTA models with 128K context window, including GPT-4-Turbo-2024-04-09, Qwen2-72B-Instruct, and Llama3.1-70B-Instruct. It is also comparable, though slightly behind, Llama3-ChatQA-1.5-70B (57.14), which only supports 4K context length. This suggests that extending short-context models to long-context has trade-offs. Exploring how to effectively extend the context window to even larger scales, e.g., millions of tokens as in Gemini 1.5 Pro (Gemini-Team, 2024), without degrading performance on regular short-context tasks is an exciting research direction.

5.5 Ablation Study

To study the effect of three stage recipe, we blended all the instruction-tuning data from all three stages and trained a new model based on Llama-3-8B base in a single stage. The results are shown in

Model	Avg.	QM	QASP	QLTY	MSQ	HQA	MFQA
GPT-4-Turbo-2024-04-09	**51.93**	16.37	38.96	88.45	44.88	70.65	52.26
w/ RAG	49.84	16.07	36.18	85.85	42.17	67.85	50.94
Qwen2-72B-Instruct	**49.94**	17.06	34.84	84.85	46.80	65.98	50.12
w/ RAG	48.08	17.63	35.19	83.05	39.92	64.58	48.10
Llama-3-70B-Instruct-Gradient-262k	40.51	20.72	30.64	74.35	20.20	45.82	51.33
w/ RAG	40.57	20.04	30.68	72.35	22.19	46.85	51.31
Llama3.1-8B-Instruct	42.42	15.16	36.59	68.20	25.89	52.42	56.25
w/ RAG	41.35	14.08	35.05	65.35	28.30	50.76	54.54
Llama3.1-70B-Instruct	**49.92**	14.85	35.75	87.40	45.65	59.64	56.23
w/ RAG	47.63	13.59	32.11	85.65	39.53	58.30	56.58
Llama3-ChatQA-2-8B	39.41	11.64	28.85	63.35	27.81	53.81	51.02
w/ RAG	40.31	13.20	28.85	61.10	29.77	57.81	51.15
Llama3-ChatQA-2-70B	**48.15**	15.99	32.84	82.20	39.26	62.24	56.39
w/ RAG	47.59	16.16	33.27	81.70	38.16	61.13	55.14

Table 3: Evaluation results on the long context benchmarks within 32K tokens. For RAG, we use top-5 retrieved chunks, each with 1200 tokens from E5-mistral retriever (Wang et al., 2023c). Note that here, we do not intend to optimize the RAG scores by increasing the number of total retrieved tokens and we leave the ablation in Section 6.

Models	Avg. w/o HDial	D2D	QuAC	QReCC	CoQA	DoQA	CFQA	SQA	TCQA	INSCIT
GPT-3.5-Turbo-0613	50.69	34.83	37.17	50.46	79.33	41.11	73.15	60.63	44.30	35.27
GPT-4-0613	54.35	34.16	40.29	52.01	77.42	43.39	81.28	79.21	45.09	36.34
GPT-4-Turbo-2024-04-09	**54.72**	35.35	40.10	51.46	77.73	41.60	84.16	79.98	48.32	33.75
Command R+ 104B	51.40	33.51	34.16	49.77	69.71	40.67	71.21	74.07	53.77	35.76
Qwen2-72B-Instruct	**54.06**	35.76	38.48	51.21	85.04	33.89	77.52	77.06	51.64	35.90
Llama2-Chat-70B	44.64	36.87	32.47	49.40	80.41	38.97	46.85	37.62	44.31	34.88
Llama3-Instruct-70B	52.95	37.88	36.96	51.34	76.98	41.24	76.60	69.61	49.72	36.23
Llama3-70B-Instruct-Gradient-262k	45.20	34.30	24.01	49.60	73.45	25.76	54.70	63.80	46.30	34.89
Llama3-ChatQA-1.5-70B	**57.14**	41.26	38.82	51.40	78.44	50.76	81.88	83.82	55.63	32.31
Llama3.1-8B-Instruct	48.79	35.24	33.03	50.59	74.32	29.84	69.59	68.18	45.49	33.85
Llama3.1-70B-Instruct	52.12	35.80	33.92	51.30	73.46	34.14	77.72	77.45	50.62	34.69
Llama3-ChatQA-2-8B	52.50	39.04	37.85	44.76	76.14	49.3	75.37	68.25	51.76	29.99
Llama3-ChatQA-2-70B	**56.30**	40.28	39.95	46.32	81.38	52.08	79.60	79.40	56.51	31.17

Table 4: Evaluation results on CHATRAG BENCH with 9 datasets. Following Liu et al. (2024), we exclude HDial as it is included in the instruction tuning datasets. The maximum context lengths are 4K tokens.

	RAG (top-k)	Long context
Llama3-ChatQA-2-70B	**64.55** (k=30)	64.29
Qwen2-72B-Instruct	**52.95** (k=20)	52.22

Table 5: We compare RAG vs. long context evaluation using our Llama3-ChatQA-2-70B on tasks beyond 100k. Here we use average accuracy of En.QA and En.MC tasks that can apply RAG. The RAG-based result is still better than long context evaluation.

	All-in-one-stage	Three-stage
Short (4K)	48.55	52.5
Long (32K)	40.69	39.41
Ultra-long (>100K)	35.07	35.59

Table 6: Comparison between the three-stage training and all-in-one-stage training.

Table 6: we observed that the three-stage training process outperforms the all-in-one stage training on RAG by a significant margin, while showing marginally better or worse performance on ultra-long and long tasks.

Figure 2: Ablation of `Llama3-ChatQA-2-70B` with RAG given different top-k = {5, 10, 20, 40} retrieval, and chunk-size = {300, 600, 1200} on long context benchmarks within 32K tokens (see Section 4.2 for more details). The accuracy can be monotonically improved with more retrieved tokens (i.e., $k\times$ chunk_size) in the context window.

6   RAG VERSUS LONG CONTEXT

In Figure 2 and Table 5, we compare direct long-context and RAG solutions on 32K and beyond 100K benchmarks. For sequences beyond 100K tokens, we report only the average scores for En.QA and En.MC, as the RAG setting is not directly applicable to En.Sum and En.Dia.

Figure 2 compares different chunk sizes for top-k retrieval and the total number of tokens fed into our long context LLM. Comparing total tokens from 3000 to 24000, we found that more tokens consistently yield better results, confirming the strong long-context capability of our model. Also, for downstream tasks with sequence lengths up to 32K, RAG can still marginally outperform the long-context solution if a sufficient number of top-k chunks are used, i.e., at least 12,000 tokens as shown in Figure 2. Therefore, the hyperparameter k can be selected based on the tradeoff between efficiency and accuracy in real-world applications.

For context lengths beyond 100K in Table 5, RAG (using top-30 chunks for our `Llama3-ChatQA-2-70B`, and top-20 for Qwen2-72B-Instruct) again outperforms the full long-context solution. In such scenarios, RAG is recommended for better accuracy and much lower inference cost, provided it is applicable to the downstream tasks.

7   CONCLUSION

We introduce `Llama3-ChatQA-2-70B`, a long context LLM that possess GPT-4 Turbo-level capabilities for both understanding up to 128K long contexts and utilizing retrieved contexts for generation. This provides the flexible options for different downstream tasks with specific accuracy and efficiency requirements. We present a detailed and reproducible technical recipe for building and evaluating the model, including the methods, training data, and evaluation benchmarks. In particular, we evaluate ChatQA 2 on short-context RAG benchmark (ChatRAG) (within 4K tokens), long context tasks from SCROLLS and LongBench (within 32K tokens), and ultra-long context tasks from InfiniteBench (beyond 100K tokens). Our results demonstrate that the `Llama3-ChatQA-2-70B` can achieve GPT-4-Turbo-2024-04-09 level accuracy on these benchmarks across different sequence lengths.

REFERENCES

01.AI, Alex Young, Bei Chen, Chao Li, Chengen Huang, Ge Zhang, Guanwei Zhang, Heng Li, Jiangcheng Zhu, Jianqun Chen, Jing Chang, et al. Yi: Open foundation models by 01. ai. *arXiv preprint arXiv:2403.04652*, 2024.

Alibaba-QWen. Qwen2 technical report. 2024. URL https://qwenlm.github.io/blog/qwen2/.

Anthropic. Introducing 100k context windows. https://www.anthropic.com/index/100k-context-windows, 2023.

Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, et al. Longbench: A bilingual, multitask benchmark for long context understanding. *arXiv preprint arXiv:2308.14508*, 2023.

Sebastian Borgeaud, Arthur Mensch, Jordan Hoffmann, Trevor Cai, Eliza Rutherford, Katie Millican, George Bm Van Den Driessche, Jean-Baptiste Lespiau, Bogdan Damoc, Aidan Clark, et al. Improving language models by retrieving from trillions of tokens. In *ICML*, 2022.

Shouyuan Chen, Sherman Wong, Liangjian Chen, and Yuandong Tian. Extending context window of large language models via positional interpolation. *arXiv preprint arXiv:2306.15595*, 2023a.

Yukang Chen, Shengju Qian, Haotian Tang, Xin Lai, Zhijian Liu, Song Han, and Jiaya Jia. Longlora: Efficient fine-tuning of long-context large language models. *arXiv preprint arXiv:2309.12307*, 2023b.

Zhe Chen, Weiyun Wang, Hao Tian, Shenglong Ye, Zhangwei Gao, Erfei Cui, Wenwen Tong, Kongzhi Hu, Jiapeng Luo, Zheng Ma, et al. How far are we to gpt-4v? closing the gap to commercial multimodal models with open-source suites. *arXiv preprint arXiv:2404.16821*, 2024.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Yao Fu, Rameswar Panda, Xinyao Niu, Xiang Yue, Hannaneh Hajishirzi, Yoon Kim, and Hao Peng. Data engineering for scaling language models to 128k context. *arXiv preprint arXiv:2402.10171*, 2024.

Gemini-Team. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2310.07713*, 2024.

GradientAI. Scaling rotational embeddings for long-context language models, 2024. URL https://gradient.ai/blog/scaling-rotational-embeddings-for-long-context-language-models.

Michael Günther, Jackmin Ong, Isabelle Mohr, Alaeddine Abdessalem, Tanguy Abel, Mohammad Kalim Akram, Susana Guzman, Georgios Mastrapas, Saba Sturua, Bo Wang, et al. Jina embeddings 2: 8192-token general-purpose text embeddings for long documents. *arXiv preprint arXiv:2310.19923*, 2023.

Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Mingwei Chang. REALM: Retrieval augmented language model pre-training. In *ICML*, 2020.

Jie Huang, Wei Ping, Peng Xu, Mohammad Shoeybi, Kevin Chen-Chuan Chang, and Bryan Catanzaro. Raven: In-context learning with retrieval augmented encoder-decoder language models. *arXiv preprint arXiv:2308.07922*, 2023.

Gautier Izacard and Édouard Grave. Leveraging passage retrieval with generative models for open domain question answering. In *EACL*, 2021.

Gautier Izacard, Patrick Lewis, Maria Lomeli, Lucas Hosseini, Fabio Petroni, Timo Schick, Jane Dwivedi-Yu, Armand Joulin, Sebastian Riedel, and Edouard Grave. Few-shot learning with retrieval augmented language models. *arXiv preprint arXiv:2208.03299*, 2022.

Kaiokendev. Things I'm learning while training SuperHOT. https://kaiokendev.github.io/til#extending-context-to-8k, 2023.

Gregory Kamradt. Needle in a haystack - pressure testing llms. https://github.com/gkamradt/LLMTest_NeedleInAHaystack, 2023.

Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In *EMNLP*, 2020.

Urvashi Khandelwal, Omer Levy, Dan Jurafsky, Luke Zettlemoyer, and Mike Lewis. Generalization through memorization: Nearest neighbor language models. *arXiv preprint arXiv:1911.00172*, 2019.

Tomáš Kočiský, Jonathan Schwarz, Phil Blunsom, Chris Dyer, Karl Moritz Hermann, Gábor Melis, and Edward Grefenstette. The narrativeqa reading comprehension challenge. *Transactions of the Association for Computational Linguistics*, 6:317–328, 2018.

Chankyu Lee, Rajarshi Roy, Mengyao Xu, Jonathan Raiman, Mohammad Shoeybi, Bryan Catanzaro, and Wei Ping. Nv-embed: Improved techniques for training llms as generalist embedding models. *arXiv preprint arXiv:2405.17428*, 2024.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. *NeurIPS*, 2020.

Zehan Li, Xin Zhang, Yanzhao Zhang, Dingkun Long, Pengjun Xie, and Meishan Zhang. Towards general text embeddings with multi-stage contrastive learning. *arXiv preprint arXiv:2308.03281*, 2023.

Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, Barcelona, Spain, July 2004. Association for Computational Linguistics. URL https://aclanthology.org/W04-1013.

Sheng-Chieh Lin, Akari Asai, Minghan Li, Barlas Oguz, Jimmy Lin, Yashar Mehdad, Wen-tau Yih, and Xilun Chen. How to train your dragon: Diverse augmentation towards generalizable dense retrieval. *arXiv preprint arXiv:2302.07452*, 2023.

Nelson F Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *arXiv preprint arXiv:2307.03172*, 2023a.

Xiaoran Liu, Hang Yan, Shuo Zhang, Chenxin An, Xipeng Qiu, and Dahua Lin. Scaling laws of rope-based extrapolation. *arXiv preprint arXiv:2310.05209*, 2023b.

Zihan Liu, Wei Ping, Rajarshi Roy, Peng Xu, Chankyu Lee, Mohammad Shoeybi, and Bryan Catanzaro. ChatQA: Surpassing GPT-4 on conversational QA and RAG. *arXiv preprint arXiv:2401.10225*, 2024.

Meta-AI. Llama 3 model card. 2024. URL https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md.

Mistral. Mixtral 8x22b. 2024. URL https://mistral.ai/news/mixtral-8x22b/.

Reiichiro Nakano, Jacob Hilton, Suchir Balaji, Jeff Wu, Long Ouyang, Christina Kim, Christopher Hesse, Shantanu Jain, Vineet Kosaraju, William Saunders, et al. WebGPT: Browser-assisted question-answering with human feedback. *arXiv preprint arXiv:2112.09332*, 2021.

Erik Nijkamp, Hiroaki Hayashi, Tian Xie, Congying Xia, Bo Pang, Congying Xia, and et al. Long sequence modeling with XGen: A 7b LLM trained on 8k input sequence length. https://blog.salesforceairesearch.com/xgen/, 2023.

Zach Nussbaum, John X Morris, Brandon Duderstadt, and Andriy Mulyar. Nomic embed: Training a reproducible long context text embedder. *arXiv preprint arXiv:2402.01613*, 2024.

NVIDIA, Bo Adler, Niket Agarwal, Ashwath Aithal, Dong H Anh, Pallab Bhattacharya, Annika Brundyn, Jared Casper, Bryan Catanzaro, Sharon Clay, Jonathan Cohen, et al. Nemotron-4 340b technical report. *arXiv preprint arXiv:2406.11704*, 2024.

OpenAI. GPT-4 turbo with 128k context. https://openai.com/blog/new-models-and-developer-products-announced-at-devday, 2023.

Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. Yarn: Efficient context window extension of large language models. *arXiv preprint arXiv:2309.00071*, 2023.

Uri Shaham, Elad Segal, Maor Ivgi, Avia Efrat, Ori Yoran, Adi Haviv, Ankit Gupta, Wenhan Xiong, Mor Geva, Jonathan Berant, and Omer Levy. SCROLLS: Standardized CompaRison over long language sequences. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 12007–12021, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. URL https://aclanthology.org/2022.emnlp-main.823.

Daria Soboleva, Faisal Al-Khateeb, Robert Myers, Jacob R Steeves, Joel Hestness, and Nolan Dey. SlimPajama: A 627B token cleaned and deduplicated version of RedPajama, 2023. URL https://huggingface.co/datasets/cerebras/SlimPajama-627B.

Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023a.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023b.

Szymon Tworkowski, Konrad Staniszewski, Mikołaj Pacek, Yuhuai Wu, Henryk Michalewski, and Piotr Miłoś. Focused transformer: Contrastive training for context scaling. *arXiv preprint arXiv:2307.03170*, 2023.

Boxin Wang, Wei Ping, Lawrence McAfee, Peng Xu, Bo Li, Mohammad Shoeybi, and Bryan Catanzaro. InstructRetro: Instruction tuning post retrieval-augmented pretraining. *arXiv preprint arXiv:2310.07713*, 2023a.

Boxin Wang, Wei Ping, Peng Xu, Lawrence McAfee, Zihan Liu, Mohammad Shoeybi, Yi Dong, Oleksii Kuchaiev, Bo Li, Chaowei Xiao, et al. Shall we pretrain autoregressive language models with retrieval? a comprehensive study. *arXiv preprint arXiv:2304.06762*, 2023b.

Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. Text embeddings by weakly-supervised contrastive pre-training. *arXiv preprint arXiv:2212.03533*, 2022.

Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. Improving text embeddings with large language models. *arXiv preprint arXiv:2401.00368*, 2023c.

Wenhan Xiong, Jingyu Liu, Igor Molybog, Hejia Zhang, Prajjwal Bhargava, Rui Hou, Louis Martin, Rashi Rungta, Karthik Abinav Sankararaman, Barlas Oguz, et al. Effective long-context scaling of foundation models. *arXiv preprint arXiv:2309.16039*, 2023.

Peng Xu, Wei Ping, Xianchao Wu, Lawrence McAfee, Chen Zhu, Zihan Liu, Sandeep Subramanian, Evelina Bakhturina, Mohammad Shoeybi, and Bryan Catanzaro. Retrieval meets long context large language models. In *ICLR*, 2024.

Yue Yu, Wei Ping, Zihan Liu, Boxin Wang, Jiaxuan You, Chao Zhang, Mohammad Shoeybi, and Bryan Catanzaro. Rankrag: Unifying context ranking with retrieval-augmented generation in LLMs. *arXiv e-prints*, pp. arXiv–2407, 2024.

Xinrong Zhang, Yingfa Chen, Shengding Hu, Zihang Xu, Junhao Chen, Moo Khai Hao, Xu Han, Zhen Leng Thai, Shuo Wang, Zhiyuan Liu, and Maosong Sun. ∞bench: Extending long context evaluation beyond 100k tokens, 2024a.

Xinrong Zhang, Yingfa Chen, Shengding Hu, Zihang Xu, Junhao Chen, Moo Khai Hao, Xu Han, Zhen Leng Thai, Shuo Wang, Zhiyuan Liu, and Maosong Sun. ∞bench: Extending long context evaluation beyond 100k tokens, 2024b. URL https://arxiv.org/abs/2402.13718.

Qihao Zhu, Daya Guo, Zhihong Shao, Dejian Yang, Peiyi Wang, Runxin Xu, Y Wu, Yukun Li, Huazuo Gao, Shirong Ma, et al. Deepseek-coder-v2: Breaking the barrier of closed-source models in code intelligence. *arXiv preprint arXiv:2406.11931*, 2024.

A APPENDIX

(a) Llama3.1-Instruct 8B (passkey retrieval)

(b) Llama3.1-Instruct 70B (passkey retrieval)

(c) Llama3-**ChatQA-2**-8B (passkey retrieval)

(d) Llama3-**ChatQA-2**-70B (passkey retrieval)

Figure 3: Needle in A Haystack test for Llama3.1-Instruct 8B and Llama3.1-Instruct-70B up to 128K context window. We show the *Passkey* retrieval results here. The needle is set as *"The pass key is 385243. Remember it. 385243 is the pass key."* with the question asking *"What is the pass key?"*