UTC-IE: A Unified Token-pair Classification Architecture for Information Extraction

Abstract

Information Extraction (IE) spans several tasks with different output structures, such as named entity recognition, relation extraction and event extraction. Previously, those tasks were solved with different models because of diverse task output structures. Through re-examining IE tasks, we find that all of them can be interpreted as extracting spans and span relations. We propose using the start and end token of a span to pinpoint the span in texts, and using the start-to-start and end-to-end token pairs of two spans to determine the relation. Hence, we can unify all IE tasks under the same token-pair classification formulation. Based on the reformulation, we propose a **U**nified **T**oken-pair **C**lassification architecture for **I**nformation **E**xtraction (**UTC-IE**), where we introduce Plusformer on top of the token-pair feature matrix. Specifically, it models axis-aware interaction with plus-shaped self-attention and local interaction with Convolutional Neural Network over token pairs. Experiments show that our approach outperforms task-specific and unified models on all tasks in 10 datasets, and achieves better or comparable results on 2 joint IE datasets. Moreover, UTC-IE speeds up over state-of-the-art models on IE tasks significantly in most datasets, which verifies the effectiveness of our architecture.

1 Introduction

Information Extraction (IE) aims to identify and classify structured information from unstructured texts (Andersen et al., 1992; Grishman, 2019). IE consists of a wide range of tasks, such as named entity recognition (NER), joint entity relation extraction (RE)[1] and event extraction (EE) [2].

In the last decade, many paradigms have been proposed to solve IE tasks, such as sequence labeling (McCallum & Li, 2003; Huang et al., 2015; Zheng et al., 2017; Yu et al., 2020a), span-based classification (Jiang et al., 2020; Yu et al., 2020b; Wang et al., 2021; Ye et al., 2022), MRC-based methods (Levy et al., 2017; Li et al., 2020; Liu et al., 2020) and generation-based methods (Zeng et al., 2018; Yan et al., 2021a; Hsu et al., 2022). The above work mainly concentrates on solving individual tasks, but it is desired to have a unified model to solve all IE tasks without designing dedicated modules. Besides, tackling all IE tasks with one model can facilitate knowledge sharing between different tasks. Therefore, various attempts have been made to unify all IE tasks with one model structure. Wadden et al. (2019); Lin et al. (2020); Nguyen et al. (2021) encode all IE tasks' target structure as graphs and design graph-based methods to predict them; Paolini et al. (2021); Lu et al. (2022) solve general IE tasks in a generative way with a text-to-text or text-to-structure framework. However, these models are either complex to be designed, or time-consuming to decode.

In our work, we creatively propose a simple yet effective paradigm for unified IE. We re-examine IE tasks and consider that all of them are fundamentally *span extraction* (entity extraction in NER and RE, trigger classification and argument span detection in EE) or *relational extraction*[3] (relation extraction in RE and argument role classification in EE). Based on this perspective, we further

---

[1] Joint entity relation extraction aims to extract both entities and relations. In our paper, we call it relation extraction (RE) for simplicity.

[2] Event extraction covers trigger extraction and argument extraction, where we first conduct argument span detection and then conduct argument role classification in our architecture.

[3] In this paper, we use relational extraction to represent extracting relations between spans, which has broader meanings than relation extraction.

Figure 1: An illustration of the token-pair decomposition for IE tasks. Each cell represents one token pair, and it can be classified into pre-defined types. e, r, t, a and rol in figures mean entity, relation, event trigger, event argument and event role. For the span extraction, we use the start-to-end and end-to-start token pairs to pinpoint the span, such as entity spans e_1, e_2, argument spans a_1, a_2 and trigger span t (cells with pure color). For the relational extraction, we use the start-to-start and end-to-end token pairs to represent the relation, such as r and rol_1, rol_2 (cells with gradient color). Therefore, all IE tasks can be decomposed into token pair classifications. After the reformulation, the local dependency and interaction from the plus-shaped orientation (as the orange and blue dotted lines depict) can provide vital information to classify the central token pair.

simplify and unify all IE tasks into *token-pair classification tasks*. Figure 1 shows how each task can be converted. Specifically, a span is decomposed into start-to-end and end-to-start token pairs. As depicted, the entity "School of Computer Science" in Figure 1(a) is decomposed into indices of (School, Science) and (Science, School). As for detecting the relation between two spans, we convert it into start-to-start and end-to-end token pairs from head mention to tail mention. For example, in Figure 1(b), the relation "Author" between "J.K. Rowling" and "Harry Potter novels" is decomposed into indices of (J.K., Harry) and (Rowling, novels).

Based on the above decomposition, we propose a **U**nified **T**oken-pair **C**lassification architecture for **I**nformation **E**xtraction (**UTC-IE**). Specifically, we first apply Biaffine model on top of the pre-trained language model to get representations of token pairs. Then we design a novel Transformer to obtain interactions between them. As the plus-shaped dotted lines depicted in Figure 1, token pairs in horizontal and vertical directions cover vital information for the classification on the central token pair. For span extraction, token pairs in the plus-shaped orientation are either clashing or nested with the central token pair, for example, e_2 is contained by e_1 in Figure 1(a); for relational extraction, the central token pair's two constituent spans locate in the plus-shaped orientation, such as in Figure 1(b), r is determined by e_1 and e_2. Therefore, we make one token pair only attend horizontally and vertically in the token pair feature matrix. In addition, position embeddings are incorporated to keep the token pairs position-aware. Moreover, neighboring token pairs are highly likely to be informative to determine the types of the central token pair, so we apply Convolutional Neural Network (CNN) to model the local interaction after the plus-shaped attention. Since the attention map for one token pair is intuitively similar to the plus operator, we name the novel module as **Plusformer**.

We conduct numerous experiments in two settings. When training separately on each task, our model outperforms previous task-specific and unified models on 10 datasets of all IE tasks. When training a single model simultaneously on all IE tasks in one dataset (named as joint IE task), UTC-IE achieves better or comparable results than 2 joint IE baselines. To thoroughly analyze why our UTC-IE architecture is useful in IE tasks under the token-pair paradigm, we execute several ablation studies. We observe that CNN module in Plusformer plays a significant role in IE tasks because of the abundant local dependency between token pairs after the reformulation. Furthermore, owing to the good parallelism of self-attention and CNN, UTC-IE is one to two orders of magnitude faster than prior unified IE models and some task-specific work.

To summarize, our key contributions are as follows

1. We introduce UTC-IE, which decomposes all IE tasks into *token-pair classification tasks*. In this way, we can unify all IE tasks under the same task formulation. Henceforth, we can use one model to fit all IE tasks without designing task-specific modules. Besides, this unified decomposition is much faster than recently proposed generation-based unified frameworks.

2. After the reformulation of different IE tasks, we propose the Plusformer to model interaction between different token pairs. The plus-shaped self-attention and CNN in Plusformer are well-motivated and effective in the reformulated IE scenario. Experiments in 12 IE datasets all achieve state-of-the-art (SOTA) performance which justifies the superiority of Plusformer in IE tasks.

3. The reformulation enables us to use one model to fit all IE tasks. Therefore, we can train one model on three IE tasks, and results on two joint IE datasets show that the proposed unification can effectively benefit each IE task through multi-task learning.

4. Extensive ablation experiments reveal that components in Plusformer are necessary and beneficial. Among them, CNN module in Plusformer can be essential to the overall performance. Analysis shows that this performance gain is well-explained because when reformulating IE tasks into token pair classifications, the adjacent token pairs can be informative and CNN can take good advantage of the local dependency between them.

2 TASK DECOMPOSITION AND DECODING

We first introduce how we decompose IE tasks to conduct training, and then present the decoding procedure for the decomposition. More discussions about the decomposition are presented in Appendix A.

2.1 TASK DECOMPOSITION

Formally, given an input sentence of L tokens $\boldsymbol{x} = [x_1, x_2, ..., x_L]$, the potential token pairs can form a score matrix $\boldsymbol{Y} \in \mathbb{R}^{L \times L \times (|\mathcal{S}| + |\mathcal{R}|)}$, where $\mathcal{S}$ is span classes, $\mathcal{R}$ is relational classes. We stipulate

- When a span (s, e) is of type t, then $\boldsymbol{Y}[s, e, t] = \boldsymbol{Y}[e, s, t] = 1$, where $s, e \in [1, L]$ and $t \in [1, |\mathcal{S}|]$ are the start, end token indices and span type;

- When the span (s_1, e_1) forms the relation $r \in [|\mathcal{S}| + 1, |\mathcal{S}| + |\mathcal{R}|]$ with another span (s_2, e_2), then $\boldsymbol{Y}[s_1, s_2, r] = \boldsymbol{Y}[e_1, e_2, r] = 1$.

NER aims to extract all entities $\{(s_i, e_i, t_i)\}$, where $t_i \in \mathcal{S}_e$ and $\mathcal{S}_e$ is pre-defined entity types. Therefore, in NER, $\mathcal{S} = \mathcal{S}_e$ and $\mathcal{R} = \phi$.

RE aims to extract all relations $\{((s_i^h, e_i^h, t_i^h), r_i, (s_i^t, e_i^t, t_i^t))\}$, where the superscript h and t denotes the head and tail entities, $t_i^h, t_i^t \in \mathcal{S}_e, r_i \in \mathcal{R}_r$ and $\mathcal{S}_e, \mathcal{R}_r$ are pre-defined entity types, and relation types. Therefore, in RE, $\mathcal{S} = \mathcal{S}_e$ and $\mathcal{R} = \mathcal{R}_r$.

EE aims to extract all events $\{\{(s_i, e_i, t_i), (s_{ia}^1, e_{ia}^1, rol_i^1), \ldots, (s_{ia}^k, e_{ia}^k, rol_i^k)\}\}$, where (s_i, e_i) means the trigger span, $t_i \in \mathcal{S}_t$ is the event type, $\mathcal{S}_t$ is pre-defined event types; $s_{ia}, e_{ia} \in [1, L]$ are the start and end token indices of an argument span, k is the number of arguments of the trigger, to extract argument spans, we set the argument type as $\mathcal{S}_a$, and $|\mathcal{S}_a| = 1$; $rol_i \in \mathcal{R}_o$ is the role type of the argument and $\mathcal{R}_o$ is pre-defined role types. We can view role types between the trigger and the arguments as relations. Therefore, in EE, $\mathcal{S} = \mathcal{S}_t \cup \mathcal{S}_a$ and $\mathcal{R} = \mathcal{R}_o$.

Joint IE aims to jointly extract entities, relations, and events in the text. Extracting entities and relations are generally the same as those in NER and RE. When extracting events, there is no need to extract argument spans purposely because all argument candidates are entities. Therefore, in joint IE, $\mathcal{S} = \mathcal{S}_t \cup \mathcal{S}_e$ and $\mathcal{R} = \mathcal{R}_r \cup \mathcal{R}_o$.

2.2 DECODING

The decoding essentially extracts spans and relations from the score matrix $\boldsymbol{Y}$. If $\boldsymbol{Y}[s, e, t] = \boldsymbol{Y}[e, s, t] = 1$ and $t \in [1, |\mathcal{S}|]$, then the span (s, e) is of type t. And for two spans (s_1, e_1) and

Figure 2: An overview of the UTC-IE Model.

(s_2, e_2), if $\boldsymbol{Y}[s_1, s_2, r] = \boldsymbol{Y}[e_1, e_2, r] = 1$ and $r \in [|\mathcal{S}| + 1, |\mathcal{S}| + |\mathcal{R}|]$, then the span (s_1, e_1) forms relation r with the span (s_2, e_2). The above decoding is for the ideal situation, where no span clash exists. However, for model's predictions, we need to first resolve the conflicts. The decoding with model's predictions will be presented in Appendix B.

3 METHOD

Figure 2 shows an overview of the architecture. Firstly, we present Biaffine (Dozat & Manning, 2017) model based on pre-trained language models (PLM). Then, we propose a novel Transformer-like structure named Plusformer to model interactions between token pairs. Next, we describe loss functions.

3.1 BIAFFINE MODEL

Given an input sentence, we first apply a PLM as our sentence encoder to obtain the contextualized representation as follows

$$\boldsymbol{H} = [\boldsymbol{h}_1, \boldsymbol{h}_2, ..., \boldsymbol{h}_L] = \text{PLM}([x_1, x_2, ..., x_L]), \tag{1}$$

where $\boldsymbol{H} \in \mathbb{R}^{L \times d}$, d is the PLM's hidden size.

Next, we use the Biaffine mechanism to get features for each token pair as follows

$$\begin{aligned} \boldsymbol{H}^s, \ \boldsymbol{H}^e &= \text{MLP}_{\text{start}}(\boldsymbol{H}), \ \text{MLP}_{\text{end}}(\boldsymbol{H}), \\ \boldsymbol{S}[i, j] &= (\boldsymbol{H}^s[i])^T \boldsymbol{W}_1 \boldsymbol{H}^e[j] + \boldsymbol{W}_2 (\boldsymbol{H}^s[i] \oplus \boldsymbol{H}^e[j]) + \boldsymbol{b}, \end{aligned} \tag{2}$$

where $\text{MLP}_{\text{start}}, \text{MLP}_{\text{end}}$ are multi-layer perceptron layers, $\boldsymbol{H}^s, \boldsymbol{H}^e \in \mathbb{R}^{L \times d}$, $\boldsymbol{W}_1 \in \mathbb{R}^{d \times c \times d}$, $\boldsymbol{W}_2 \in \mathbb{R}^{c \times 2d}$, $\boldsymbol{b} \in \mathbb{R}^c$, $\oplus$ refers to concatenation; $\boldsymbol{S} \in \mathbb{R}^{L \times L \times c}$ provides features for all possible token pairs, and c is the feature dimension size.

3.2 PLUSFORMER

As illustrated in Section 1, when modeling the interaction between token pairs, the plus-shaped and local interaction should be beneficial. Therefore, we introduce the axis-aware plus-shaped self-attention and position embeddings to conduct plus-shaped interaction, we name this self-attention PlusAttention. Then, we leverage CNN to model local dependencies. We name this whole structure **Plusformer**.

PlusAttention. We first apply the self-attention mechanism (Vaswani et al., 2017) horizontally and vertically as follows

$$
\begin{aligned}
\boldsymbol{Z}^h[i,:] &= \text{Attention}(\boldsymbol{S}[i,:]\boldsymbol{W}_h^Q, \boldsymbol{S}[i,:]\boldsymbol{W}_h^K, \boldsymbol{S}[i,:]\boldsymbol{W}_h^V), \\
\boldsymbol{Z}^v[:,j] &= \text{Attention}(\boldsymbol{S}[:,j]\boldsymbol{W}_v^Q, \boldsymbol{S}[:,j]\boldsymbol{W}_v^K, \boldsymbol{S}[:,j]\boldsymbol{W}_v^V), \\
\text{Attention}(\boldsymbol{Q},\boldsymbol{K},\boldsymbol{V}) &= \text{softmax}(\frac{\boldsymbol{Q}\boldsymbol{K}^T}{\sqrt{c}})\boldsymbol{V},
\end{aligned}
\tag{3}
$$

where $\boldsymbol{W}_h^Q, \boldsymbol{W}_h^K, \boldsymbol{W}_h^V, \boldsymbol{W}_v^Q, \boldsymbol{W}_v^K, \boldsymbol{W}_v^V \in \mathbb{R}^{c \times c}$, $\boldsymbol{Z}^h, \boldsymbol{Z}^v \in \mathbb{R}^{L \times L \times c}$. After the self-attention, we use the following method to merge $\boldsymbol{Z}^h, \boldsymbol{Z}^v$

$$
\boldsymbol{S}' = \text{MLP}(\boldsymbol{Z}_h \oplus \boldsymbol{Z}_v),
\tag{4}
$$

where $\boldsymbol{S}' \in \mathbb{R}^{L \times L \times c}$. We make the plus-shaped self-attention axis-aware by using two groups of attention parameters and using concatenation instead of an addition to merge $\boldsymbol{Z}^h, \boldsymbol{Z}^v$.

Position Embeddings. Although the model should be able to distinguish between horizontal and vertical directions through axis-aware plus-shaped attention, it still lacks the sense of distances between token pairs and the area the token pair locates. Therefore, we utilize two kinds of position embeddings to enable the model with these abilities.

- **Rotary Position Embedding (RoPE)** (Su et al., 2021) can encode the relative distance between two token pairs. It is utilized in both horizontal and vertical self-attention.
- **Triangle position embedding** is incorporated to mark the position of token pairs in the feature map, which means cells in the upper and lower triangles will use different position embeddings. It adds to $\boldsymbol{S}$ in Eq.(3) before Attention.

CNN Layer. After the PlusAttention, we apply CNN with kernel size 3×3 on the $\boldsymbol{S}'$ to help the model exploit the local dependency between neighboring token pairs. The formulation is as follows

$$
\boldsymbol{S}'' = \text{Conv}(\sigma(\text{Conv}(\boldsymbol{S}')))
\tag{5}
$$

where $\boldsymbol{S}'' \in \mathbb{R}^{L \times L \times c}$, and σ is the activation function; and the bias term of CNN is not used to avoid result inconsistencies for a sample when it is in batches of different lengths.

The Plusformer layer will be repeatedly used to interact fully between token pairs. Layer normalization (Ba et al., 2016) is ignored in the formulation for brevity.

3.3 Loss Function

Finally, we get final scores as follows

$$
\hat{\boldsymbol{Y}}_{\mathcal{S}}, \hat{\boldsymbol{Y}}_{\mathcal{R}} = \text{Sigmoid}(\hat{\boldsymbol{Y}}[:,:,:|\mathcal{S}|]), \hat{\boldsymbol{Y}}[:,:,|\mathcal{S}|:], \qquad \hat{\boldsymbol{Y}} = \text{MLP}(\boldsymbol{S}'' + \boldsymbol{S}),
\tag{6}
$$

where $\hat{\boldsymbol{Y}} \in \mathbb{R}^{L \times L \times (|\mathcal{S}|+|\mathcal{R}|+1)}$; $\hat{\boldsymbol{Y}}_{\mathcal{S}} \in \mathbb{R}^{L \times L \times |\mathcal{S}|}, \hat{\boldsymbol{Y}}_{\mathcal{R}} \in \mathbb{R}^{L \times L \times (|\mathcal{R}|+1)}$ are scores for span extraction and relational extraction, respectively. The $+1$ in $(|\mathcal{R}|+1)$ is because we use the adaptive thresholding loss (ATL) from (Zhou et al., 2021) to avoid a global threshold in relational extraction.

For the span extraction, we use the binary cross-entropy (BCE) loss as follows

$$
\mathcal{L}_1 = -\sum_{i,j=1}^{L}\sum_{r=1}^{|\mathcal{S}|}[\boldsymbol{Y}[i,j,r]\log(\hat{\boldsymbol{Y}}[i,j,r]) + (1-\boldsymbol{Y}[i,j,r])\log(1-\hat{\boldsymbol{Y}}[i,j,r])]
\tag{7}
$$

For the relational extraction, we utilize the ATL as follows

$$
\begin{aligned}
\mathcal{L}_2 = -\sum_{i,j=1}^{L}\sum_{r\in\mathcal{P}_T}&\log\left(\frac{\exp(\hat{\boldsymbol{Y}}_{\mathcal{R}}[i,j,r])}{\sum_{r'\in\mathcal{P}_T\cup\{\text{TH}\}}\exp(\hat{\boldsymbol{Y}}_{\mathcal{R}}[i,j,r'])}\right) \\
&-\log\left(\frac{\exp(\hat{\boldsymbol{Y}}_{\mathcal{R}}[i,j,|\mathcal{R}|+1])}{\sum_{r'\in\mathcal{N}^T\cup\{\text{TH}\}}\exp(\hat{\boldsymbol{Y}}_{\mathcal{R}}[i,j,r'])}\right)
\end{aligned}
\tag{8}
$$

where $\mathcal{P}_T$ and $\mathcal{N}_T$ denote the positive and negative classes, $\hat{\boldsymbol{Y}}_{\mathcal{R}}[:,:,|\mathcal{R}|+1]$ is the score for the threshold class TH. Only token pairs with scores higher than their corresponding adaptive thresholds are considered when decoding. We do not use ATL loss for span extraction because we need to sort span scores when decoding spans. The total loss $\mathcal{L} = \mathcal{L}_1 + \mathcal{L}_2$ is used for optimization.

Table 1: Overall F1 on single IE tasks. Results of UTC-IE are the average of 5 runs, and the subscript means the standard deviation (e.g., 93.45_{24} means 93.45 ± 0.24). Datasets marked as * have nested entities. Results marked as † are from Yan et al. (2022). * means results from their Github repo or our reproduction. ♣ means that the UTC-IE without Plusformer surpasses previous SOTA performance.

Named Entity Recognition	CoNLL03	OntoNotes	ACE04*	ACE05-Ent*	GENIA*
BART-NER (Yan et al., 2021a)	93.24	90.38	86.84	84.74	78.93
TANL (Paolini et al., 2021)	91.7	89.8	-	84.9	76.4
W^{2}NER (Li et al., 2022)	93.07	90.50	$87.43^\dagger$	$86.77^\dagger$	$80.32^\dagger$
UIE (Lu et al., 2022)	92.99	-	86.89	85.78	-
BS (Zhu & Li, 2022)	$93.39^\star_9$	$91.51^\star_7$	$87.08^\dagger$	$87.20^\dagger$	-
CNN-NER (Yan et al., 2022)	-	-	$87.31^\dagger$	$87.42^\dagger$	$80.33^\dagger$
UTC-IE	**93.45**$_{24}$	**91.77**$_5$	**87.54**$_{33}$	**87.75**$_{35}$	**80.45**$_{22}$
- Plusformer	92.98_{13}	91.37_5	86.51_{23}	86.59_{20}	79.34_{17}

Relation Extraction	ACE05-R$_{bert}$		ACE05-R$_{albert}$		SciERC	
	Ent.	Rel.	Ent.	Rel.	Ent.	Rel.
TANL (Paolini et al., 2021)	-	-	88.9	63.7	-	-
PURE (Zhong & Chen, 2021)	88.7	63.9	89.7	65.6	66.6	35.6
PFN (Yan et al., 2021b)	-	-	89.0	66.8	$67.2^\star_{67}$	$37.6^\star_{99}$
UIE (Lu et al., 2022)	-	-	-	66.06	-	36.53
UTC-IE	**88.82**$_{12}$	**64.94**$_{33}$	**89.87**$_{15}$	**67.79**$_{45}$	**69.03**$_{45}$	**38.77**$_{96}$
-Plusformer	88.50_{19}	63.34_{72}	$89.80^\clubsuit_{23}$	66.21_{87}	$68.05^\clubsuit_{63}$	37.12_{40}

Symmetric Relation Extraction	ACE05-R$^+$		SciERC$^+$	
	Ent.	Rel.	Ent.	Rel.
UniRE (Wang et al., 2021)	88.8	64.3	68.4	36.9
PL-Marker (Ye et al., 2022)	89.8	66.5	69.9	41.6
UTC-IE	**90.16**$_{21}$	**67.47**$_{74}$	**69.95**$_{41}$	**42.51**$_{42}$
- Plusformer	88.98_{29}	64.58_{65}	68.78_{63}	39.51_{56}

Event Extraction	ACE05-E		ACE05-E+		ERE-EN	
	Trig.	Arg.	Trig.	Arg.	Trig.	Arg.
TANL (Paolini et al., 2021)	68.4	47.6	-	-	-	-
TEXT2EVENT (Lu et al., 2021)	71.9	53.8	71.8	54.4	59.4	48.3
UIE (Lu et al., 2022)	-	-	73.36	54.79	-	-
DEGREE (Hsu et al., 2022)	73.3	55.8	70.9	56.3	57.1	49.6
UTC-IE	**73.46**$_{99}$	**56.51**$_{53}$	**73.44**$_{55}$	**57.68**$_{78}$	**60.20**$_{94}$	**52.51**$_{95}$
- Plusformer	72.88_{78}	55.41_{99}	72.92_{94}	$56.63^\clubsuit_{89}$	59.28_{77}	$51.33^\clubsuit_{99}$

4 EXPERIMENTS

4.1 EXPERIMENTAL SETTINGS

We conduct experiments on 10 datasets across three IE tasks, including NER, RE, and EE, and on 2 joint IE datasets. We evaluate NER task with CoNLL03 (Sang & Meulder, 2003) and OntoNotes (Pradhan et al., 2013) on flat NER, and with ACE04 (Doddington et al., 2004), ACE05-Ent (Walker et al., 2006) and GENIA (Kim et al., 2003) on nested NER. As for relation extraction, we use ACE05-R (Walker et al., 2006) and SciERC (Luan et al., 2018). Since Wang et al. (2021) and Ye et al. (2022) consider symmetric relations, which shall massively influence the performance, we name this scenario Symmetric RE with datasets ACE05-R$^+$ and SciERC$^+$. For event extraction, we follow Lin et al. (2020) to perform experiments on three datasets, ACE05-E, ACE05-E+ (Doddington et al., 2004) and ERE-EN (Song et al., 2015). And for joint IE, we test on ACE05-E+ and ERE-EN. Statistics of all these datasets, implementation details, evaluation metrics, baselines, pre-trained language models and hyper-parameters are described in Appendix C.

Table 2: Results on joint IE. UTC-IE$_{single}$ shows results by separately trained model on NER, RE and EE, while UTC-IE$_{joint}$ shows results by jointly trained model. ♣ means that UTC-IE without Plusformer surpasses previous SOTA performance.

Joint IE	ACE05-E+				ERE-EN			
	Ent.	Rel.	Trig.	Arg.	Ent.	Rel.	Trig.	Arg.
OneIE (Lin et al., 2020)	89.6	58.6	72.8	54.8	87.0	53.2	57.0	46.5
FourIE (Nguyen et al., 2021)	91.1	63.6	73.3	57.5	**87.4**	56.1	**57.9**	48.6
UTC-IE$_{single}$	91.37_{10}	65.00_{49}	71.98_{65}	56.01_{76}	86.35_{48}	55.57_{92}	57.01_{39}	48.29_{60}
UTC-IE$_{joint}$	**91.48_{20}**	**65.54_{90}**	**73.63_{47}**	**57.62_{30}**	87.30_{18}	**56.92_{90}**	57.88_{98}	**50.91_{93}**
- Plusformer	90.72_{30}	62.94_{75}	72.99_{62}	55.68_{74}	86.94_{13}	54.28_{94}	57.79_{83}	48.72_{51}♣

4.2 RESULTS ON SINGLE IE TASKS

In this section, we report the UTC-IE performance in each single IE task. Results are shown in Table 1[4]. The table shows that UTC-IE exceeds the previous SOTA models on all IE tasks. Particularly, UTC-IE averagely improves the entity F1 of NER, the entity F1 and relation F1 of RE, the entity F1 and the relation F1 of symmetric RE for +0.18, +0.71, +1.07, +0.21, +0.94, respectively. And for the EE tasks, UTC-IE increases the trigger F1, argument F1 for +0.35 and +1.67. We highlight that our model is significantly helpful for relational extraction, such as relation extraction and argument extraction, which proves the effectiveness of interaction between token pairs. Although the performance increment of span extraction is not as significant as that of relational extraction, UTC-IE consistently improves on various span extraction tasks.

Besides, we also test UTC-IE without Plusformer. Surprisingly, this simple model surpasses previous SOTA models on four results marked with ♣, which proves the effectiveness of the task decomposition. The comparison between models with and without Plusformer clearly shows that Plusformer is effective in all tested datasets, and the performance improvement ranges from +0.40 (on OntoNotes) to +3.00 (on SciERC$^+$). Notably, the average performance gain of adding Plusformer on symmetric RE (+2.06) is more remarkable than that on RE (+1.03). We presume this is because the interaction between token pairs are more beneficial for symmetric relations.

4.3 RESULTS ON JOINT IE TASK

Multi-task learning has be proven to be useful in the IE area (Lin et al., 2020; Nguyen et al., 2021). Since UTC-IE unifies all IE tasks into a token-pair classification scenario, it is natural to test whether one UTC-IE model can benefit from jointly learning all IE tasks. In Table 2, the performance of UTC-IE$_{single}$ is from the entity F1 of NER, relation F1 of RE, trigger F1 of EE and argument F1 of EE, respectively. Based on the comparison between UTC-IE$_{single}$ and UTC-IE$_{joint}$, it is obvious that jointly learning these three tasks consistently improves performance in the 2 joint IE datasets.

Moreover, UTC-IE$_{joint}$ outperforms previous SOTA joint IE models in Table 2, the average performance enhancement is +0.69 in ACE05-E+ and +0.75 in ERE-EN. Specifically, UTC-IE$_{joint}$ increases the average performance of relational extraction by +1.30. Thusly, through unifying different IE tasks through our task decomposition, Plusformer can enjoy the benefit of multi-tasking learning, and achieve better performance than previous SOTA models.

4.4 SPEED COMPARISON

To get a sense of the speed superiority of UTC-IE, we compare the inference speed of UTC-IE with previous unified models and task-specific SOTA models. The former comparison is presented in Table 3 and the latter locates in the Appendix E. Compared with the generative UIE (Lu et al., 2022), UTC-IE improves F1 from 0.46 (on CoNLL03) to 2.89 (on ACE05-E+), and obtains one order magnitude of speed boost. Compared with OneIE (Lin et al., 2020), UTC-IE fundamentally enhances the performance for relational extractions (e.g., Rel. and Arg.) with an average of 4.47 F1 increment in joint IE. At the same time, UTC-IE is one order of magnitude faster than OneIE. In

---

[4]The precision and recall for UTC-IE in these datasets can be found in Table 8 in Appendix.

Table 3: The F1 and efficiency comparison with UIE and OneIE. "Ent.", "Rel." and "Arg." denote F1 of corresponding test sets. "Speed" is measured in "sentence/s" on inference procedure. The improvement shows the changes in performance and speed.

Single IE	CoNLL03		ACE05-Ent		ACE05-R_{albert}		SciERC		ACE05-E+	
	Ent.	Speed	Ent.	Speed	Rel.	Speed	Rel.	Speed	Arg.	Speed
UIE (Lu et al., 2022)	92.99	14.5	85.78	8.6	66.06	11.4	36.53	8.7	54.79	4.0
UTC-IE	93.45	210.3	87.75	304.3	67.79	85.4	38.77	165.7	57.68	88.1
Improvement	**+0.46**	**x14.5**	**+1.97**	**x35.4**	**+1.73**	**x7.5**	**+2.24**	**x19.0**	**+2.89**	**x22.0**

Joint IE	ACE05-E+					ERE-EN				
	Ent.	Rel.	Trig.	Arg.	Speed	Ent.	Rel.	Trig.	Arg.	Speed
OneIE (Lin et al., 2020)	89.6	58.6	72.8	54.8	4.8	87.0	53.2	57.0	46.5	13.5
UTC-IE	91.48	65.54	73.63	57.62	121.6	87.30	56.92	57.88	50.91	153.5
Improvement	**+1.88**	**+6.94**	**+0.83**	**+2.82**	**x25.3**	**+0.30**	**+3.72**	**+0.88**	**+4.41**	**x11.4**

Table 4: Ablation studies in the NER, RE and EE datasets. CNN-IE is similar to UTC-IE except that it is deprived of the PlusAttention. Underlines mean the most dropped factor. ♣ means that the CNN-IE surpasses previous SOTA performance.

	ACE05-Ent	ACE05-R_{bert}		ACE05-E+	
	Ent.	Ent.	Rel.	Trig.	Arg.
UTC-IE	87.75_{35}	88.82_{12}	64.94_{33}	73.44_{55}	57.68_{78}
- CNN	$\underline{87.39_{22}}$	88.71_{22}	$\underline{63.55_{83}}$	$\underline{72.98_{34}}$	$\underline{56.74_{99}}$
- positon embeddings	87.53_{34}	88.73_{20}	64.29_{56}	73.12_{98}	57.02_{80}
- axis-aware	87.59_{27}	88.79_{19}	63.91_{55}	73.29_{46}	56.87_{98}
CNN-IE	$87.45_{20}^{♣}$	$88.70_{16}^{♣}$	$64.67_{26}^{♣}$	73.04_{99}	$56.97_{63}^{♣}$

a nutshell, compared with previous SOTA models (whether task-specific, unified or joint), UTC-IE achieves substantial performance gain across several datasets with a significant speed boost.

4.5 ABLATION STUDY

To analyze the effectiveness of each component in Plusformer, we ablate each of them and list the outcomes in Table 4, and results on more datasets are presented in Appendix F. Besides, we study how many Plusformer layers are suitable in Appendix F.5. Based on the ablation, CNN is the most useful component among all IE tasks. The reason behind this improvement is that once token pairs are organized in the square feature map, the spatial correlations between neighboring token pairs become allusive, and CNN excels at exploiting these local interactions. More comprehensive analysis of CNN in Plusformer locates in Appendix F.1. To deepen our understanding of UTC-IE, we try another variant of Plusformer where the PlusAttention is discarded, and we name this variant **CNN-IE**. The bottom line of Table 4 shows that the CNN-IE model can surpass or approach previous SOTA performance in almost all datasets, which proves the universality of our proposed task formulation.

However, CNN is not a panacea for UTC-IE. From Table 4, removing position embeddings or axis-aware[5] from UTC-IE will lead to an average of 0.39 or 0.44 performance degradation, respectively. Moreover, based on the performance of CNN-IE and UTC-IE, the average performance shrinks from 74.53 to 74.17 if the PlusAttention is deprived of Plusformer, which means the plus-shaped self-attention is a desideratum. In addition, we present some intuitive examples and deeper analysis for position embeddings and axis-aware in Appendix F.3 and F.4.

---

[5]Removing axis-aware means using the same self-attention parameters for both directions and adding Z^h and Z^v instead of concatenation.

5 RELATED WORK

Information extraction tasks, which consists of named entity recognition, relation extraction, and event extraction, have long been a fundamental and well-researched task in the natural language processing (NLP) field. Previous researches mainly only focus on one or two tasks. Recently, building joint neural models of unified IE tasks has attracted increasing attention. Some of them incorporate graphs into IE structure. Wadden et al. (2019) propose a unified framework called DYGIE++ to extract entities, relations and events by leveraging span representations via span graph updates. Lin et al. (2020) and Nguyen et al. (2021) extend DYGIE++ by incorporating global features to extract cross-task and cross-instance interactions with multi-task learning. In addition to the graph-based models mentioned above, other studies focus on tackling general IE by generative models. Paolini et al. (2021) construct a framework called TANL, which enhances the generation model using augmented language methods. Moreover, Lu et al. (2022) regard IE task as a text-to-structure generation task, and leveraging prompt mechanism.

We unify all IE tasks as several token-pair classification tasks, which are fundamentally similar to the span-based methods on the IE task, for the start and end tokens can locate a span. Numerous NER studies emerge on span-based models, which are compatible with both flat and nested entities and perform well (Eberts & Ulges, 2020; Yu et al., 2020b; Li et al., 2021; Zhu & Li, 2022). In addition to entities, the span-based method is also used in RE. Some models (Wang et al., 2021; Ye et al., 2022) only leverage span representations to locate entities and simply calculate the interaction between entity pair, while others (Wang et al., 2020; Zhong & Chen, 2021) encode span pair information explicitly to extract relations. With regard to event extraction, as far as we know, there is little work on injecting span information into EE explicitly. Wadden et al. (2019) leveraging span representations on general IE, but their model is complicated and only considers span at the embedding layer without further interaction. Conceptually, Jiang et al. (2020)'s work is very similar to ours, but they need a two-stage model to determine the span type and span relations, respectively. Although many existing span-based IE models exist, they are task-specific and can barely transfer to other tasks. Decomposing IE tasks as token-pair classification can uniformly model span-related knowledge and advances task-specific baselines.

The key component of Plusformer is the plus-shaped attention mechanism, which can make token pairs interact with each other in an efficient way. A similar structure called Axial Transformers (Ho et al., 2019) is proposed in Computer Vision (CV) field, which is designed to deal with data organized as high-dimension tensors. Tan et al. (2022) incorporate axial attention into relation classification, aiming to improve the performance on two-hop relation. However, CNN was not used in these work, while CNN has been proven to be vital to the IE tasks. Another similar structure named Twin Transformer (Guo et al., 2021) used in CV is very much similar to Plusformer, where they encode pixel of image from row and column sequentially, and leverage CNN on top of them. But the position embeddings, which is important for IE tasks, are not used in the Twin Transformer. Besides, we want to point out that the usage of plus-shaped attention and CNN originates from the reformulation of IE tasks, any other modules which can directly enable interaction between constituent spans of a relation and between adjacent token pairs should be beneficial.

6 CONCLUSION

In this paper, we decompose NER, RE and EE tasks into token-pair classifications. Through the decomposition, we unify all IE tasks under the same formulation. After scrutinizing the token-pair feature matrix, we find the adjacent and plus-shaped interactions between token pairs should be informative. Therefore, we propose Plusformer, which uses an axis-aware plus-shaped self-attention followed by CNN layers to help token pairs interact with each other. Experiments in 10 single IE datasets and 2 joint IE datasets all outperform or approach the SOTA performance. Besides, owing to the parallelism of self-attention and CNN, our model's inference speed is substantially faster than previous SOTA models in RE and EE. Lastly, most of the previous IE models limit the interaction in the 1-D sequential dimension, while the reformulation of IE tasks opens a new angle to broaden the communication to the 2-D feature matrix.

REFERENCES

Peggy M. Andersen, Philip J. Hayes, Steven P. Weinstein, Alison K. Huettner, Linda M. Schmandt, and Irene B. Nirenburg. Automatic extraction of facts from press releases to generate news stories. In *3rd Applied Natural Language Processing Conference, ANLP 1992, Trento, Italy, March 31 - April 3, 1992*, pp. 170–177. ACL, 1992. doi: 10.3115/974499.974531. URL `https://aclanthology.org/A92-1024/`.

Lei Jimmy Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization. *CoRR*, abs/1607.06450, 2016. URL `http://arxiv.org/abs/1607.06450`.

George R. Doddington, Alexis Mitchell, Mark A. Przybocki, Lance A. Ramshaw, Stephanie M. Strassel, and Ralph M. Weischedel. The automatic content extraction (ACE) program - tasks, data, and evaluation. In *Proceedings of the Fourth International Conference on Language Resources and Evaluation, LREC 2004, May 26-28, 2004, Lisbon, Portugal*. European Language Resources Association, 2004. URL `http://www.lrec-conf.org/proceedings/lrec2004/summaries/5.htm`.

Timothy Dozat and Christopher D. Manning. Deep biaffine attention for neural dependency parsing. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL `https://openreview.net/forum?id=Hk95PK9le`.

Markus Eberts and Adrian Ulges. Span-based joint entity and relation extraction with transformer pre-training. In Giuseppe De Giacomo, Alejandro Catalá, Bistra Dilkina, Michela Milano, Senén Barro, Alberto Bugarín, and Jérôme Lang (eds.), *ECAI 2020 - 24th European Conference on Artificial Intelligence, 29 August-8 September 2020, Santiago de Compostela, Spain, August 29 - September 8, 2020 - Including 10th Conference on Prestigious Applications of Artificial Intelligence (PAIS 2020)*, volume 325 of *Frontiers in Artificial Intelligence and Applications*, pp. 2006–2013. IOS Press, 2020. doi: 10.3233/FAIA200321. URL `https://doi.org/10.3233/FAIA200321`.

Ralph Grishman. Twenty-five years of information extraction. *Nat. Lang. Eng.*, 25(6):677–692, 2019. doi: 10.1017/S1351324919000512. URL `https://doi.org/10.1017/S1351324919000512`.

Ruohao Guo, Dantong Niu, Liao Qu, and Zhenbo Li. SOTR: segmenting objects with transformers. In *2021 IEEE/CVF International Conference on Computer Vision, ICCV 2021, Montreal, QC, Canada, October 10-17, 2021*, pp. 7137–7146. IEEE, 2021. doi: 10.1109/ICCV48922.2021.00707. URL `https://doi.org/10.1109/ICCV48922.2021.00707`.

Jonathan Ho, Nal Kalchbrenner, Dirk Weissenborn, and Tim Salimans. Axial attention in multi-dimensional transformers. *CoRR*, abs/1912.12180, 2019. URL `http://arxiv.org/abs/1912.12180`.

I-Hung Hsu, Kuan-Hao Huang, Elizabeth Boschee, Scott Miller, Prem Natarajan, Kai-Wei Chang, and Nanyun Peng. DEGREE: A data-efficient generation-based event extraction model. In Marine Carpuat, Marie-Catherine de Marneffe, and Iván Vladimir Meza Ruíz (eds.), *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL 2022, Seattle, WA, United States, July 10-15, 2022*, pp. 1890–1908. Association for Computational Linguistics, 2022. doi: 10.18653/v1/2022.naacl-main.138. URL `https://doi.org/10.18653/v1/2022.naacl-main.138`.

Zhiheng Huang, Wei Xu, and Kai Yu. Bidirectional LSTM-CRF models for sequence tagging. *CoRR*, abs/1508.01991, 2015. URL `http://arxiv.org/abs/1508.01991`.

Zhengbao Jiang, Wei Xu, Jun Araki, and Graham Neubig. Generalizing natural language analysis through span-relation representations. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel R. Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pp. 2120–2133. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.acl-main.192. URL `https://doi.org/10.18653/v1/2020.acl-main.192`.

Jin-Dong Kim, Tomoko Ohta, Yuka Tateisi, and Jun'ichi Tsujii. GENIA corpus - a semantically annotated corpus for bio-textmining. In *Proceedings of the Eleventh International Conference on Intelligent Systems for Molecular Biology, June 29 - July 3, 2003, Brisbane, Australia*, pp. 180–182, 2003. URL `http://bioinformatics.oupjournals.org/cgi/content/abstract/19/suppl_1/i180?etoc`.

Omer Levy, Minjoon Seo, Eunsol Choi, and Luke Zettlemoyer. Zero-shot relation extraction via reading comprehension. In Roger Levy and Lucia Specia (eds.), *Proceedings of the 21st Conference on Computational Natural Language Learning (CoNLL 2017), Vancouver, Canada, August 3-4, 2017*, pp. 333–342. Association for Computational Linguistics, 2017. doi: 10.18653/v1/K17-1034. URL `https://doi.org/10.18653/v1/K17-1034`.

Fei Li, Zhichao Lin, Meishan Zhang, and Donghong Ji. A span-based model for joint overlapped and discontinuous named entity recognition. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, ACL/IJCNLP 2021, (Volume 1: Long Papers), Virtual Event, August 1-6, 2021*, pp. 4814–4828. Association for Computational Linguistics, 2021. doi: 10.18653/v1/2021.acl-long.372. URL `https://doi.org/10.18653/v1/2021.acl-long.372`.

Jingye Li, Hao Fei, Jiang Liu, Shengqiong Wu, Meishan Zhang, Chong Teng, Donghong Ji, and Fei Li. Unified named entity recognition as word-word relation classification. In *Thirty-Sixth AAAI Conference on Artificial Intelligence, AAAI 2022, Thirty-Fourth Conference on Innovative Applications of Artificial Intelligence, IAAI 2022, The Twelveth Symposium on Educational Advances in Artificial Intelligence, EAAI 2022 Virtual Event, February 22 - March 1, 2022*, pp. 10965–10973. AAAI Press, 2022. URL `https://ojs.aaai.org/index.php/AAAI/article/view/21344`.

Xiaoya Li, Jingrong Feng, Yuxian Meng, Qinghong Han, Fei Wu, and Jiwei Li. A unified MRC framework for named entity recognition. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel R. Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pp. 5849–5859. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.acl-main.519. URL `https://doi.org/10.18653/v1/2020.acl-main.519`.

Ying Lin, Heng Ji, Fei Huang, and Lingfei Wu. A joint neural model for information extraction with global features. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel R. Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pp. 7999–8009. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.acl-main.713. URL `https://doi.org/10.18653/v1/2020.acl-main.713`.

Jian Liu, Yubo Chen, Kang Liu, Wei Bi, and Xiaojiang Liu. Event extraction as machine reading comprehension. In Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu (eds.), *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP 2020, Online, November 16-20, 2020*, pp. 1641–1651. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.emnlp-main.128. URL `https://doi.org/10.18653/v1/2020.emnlp-main.128`.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019. URL `https://openreview.net/forum?id=Bkg6RiCqY7`.

Yaojie Lu, Hongyu Lin, Jin Xu, Xianpei Han, Jialong Tang, Annan Li, Le Sun, Meng Liao, and Shaoyi Chen. Text2event: Controllable sequence-to-structure generation for end-to-end event extraction. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, ACL/IJCNLP 2021, (Volume 1: Long Papers), Virtual Event, August 1-6, 2021*, pp. 2795–2806. Association for Computational Linguistics, 2021. doi: 10.18653/v1/2021.acl-long.217. URL `https://doi.org/10.18653/v1/2021.acl-long.217`.

Yaojie Lu, Qing Liu, Dai Dai, Xinyan Xiao, Hongyu Lin, Xianpei Han, Le Sun, and Hua Wu. Unified structure generation for universal information extraction. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2022, Dublin, Ireland, May 22-27, 2022*, pp. 5755–5772. Association for Computational Linguistics, 2022. URL `https://aclanthology.org/2022.acl-long.395`.

Yi Luan, Luheng He, Mari Ostendorf, and Hannaneh Hajishirzi. Multi-task identification of entities, relations, and coreference for scientific knowledge graph construction. In Ellen Riloff, David Chiang, Julia Hockenmaier, and Jun'ichi Tsujii (eds.), *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, Brussels, Belgium, October 31 - November 4, 2018*, pp. 3219–3232. Association for Computational Linguistics, 2018. doi: 10.18653/v1/d18-1360. URL `https://doi.org/10.18653/v1/d18-1360`.

Yi Luan, Dave Wadden, Luheng He, Amy Shah, Mari Ostendorf, and Hannaneh Hajishirzi. A general framework for information extraction using dynamic span graphs. In Jill Burstein, Christy Doran, and Thamar Solorio (eds.), *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, pp. 3036–3046. Association for Computational Linguistics, 2019. doi: 10.18653/v1/n19-1308. URL `https://doi.org/10.18653/v1/n19-1308`.

Andrew McCallum and Wei Li. Early results for named entity recognition with conditional random fields, feature induction and web-enhanced lexicons. In Walter Daelemans and Miles Osborne (eds.), *Proceedings of the Seventh Conference on Natural Language Learning, CoNLL 2003, Held in cooperation with HLT-NAACL 2003, Edmonton, Canada, May 31 - June 1, 2003*, pp. 188–191. ACL, 2003. URL `https://www.aclweb.org/anthology/W03-0430/`.

Minh Van Nguyen, Viet Dac Lai, and Thien Huu Nguyen. Cross-task instance representation interactions and label dependencies for joint information extraction with graph convolutional networks. In Kristina Toutanova, Anna Rumshisky, Luke Zettlemoyer, Dilek Hakkani-Tür, Iz Beltagy, Steven Bethard, Ryan Cotterell, Tanmoy Chakraborty, and Yichao Zhou (eds.), *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2021, Online, June 6-11, 2021*, pp. 27–38. Association for Computational Linguistics, 2021. doi: 10.18653/v1/2021.naacl-main.3. URL `https://doi.org/10.18653/v1/2021.naacl-main.3`.

Giovanni Paolini, Ben Athiwaratkun, Jason Krone, Jie Ma, Alessandro Achille, Rishita Anubhai, Cícero Nogueira dos Santos, Bing Xiang, and Stefano Soatto. Structured prediction as translation between augmented natural languages. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL `https://openreview.net/forum?id=US-TP-xnXI`.

Sameer Pradhan, Alessandro Moschitti, Nianwen Xue, Hwee Tou Ng, Anders Björkelund, Olga Uryupina, Yuchen Zhang, and Zhi Zhong. Towards robust linguistic analysis using ontonotes. In Julia Hockenmaier and Sebastian Riedel (eds.), *Proceedings of the Seventeenth Conference on Computational Natural Language Learning, CoNLL 2013, Sofia, Bulgaria, August 8-9, 2013*, pp. 143–152. ACL, 2013. URL `https://aclanthology.org/W13-3516/`.

Erik F. Tjong Kim Sang and Fien De Meulder. Introduction to the conll-2003 shared task: Language-independent named entity recognition. In Walter Daelemans and Miles Osborne (eds.), *Proceedings of the Seventh Conference on Natural Language Learning, CoNLL 2003, Held in cooperation with HLT-NAACL 2003, Edmonton, Canada, May 31 - June 1, 2003*, pp. 142–147. ACL, 2003. URL `https://aclanthology.org/W03-0419/`.

Zhiyi Song, Ann Bies, Stephanie M. Strassel, Tom Riese, Justin Mott, Joe Ellis, Jonathan Wright, Seth Kulick, Neville Ryant, and Xiaoyi Ma. From light to rich ERE: annotation of entities, relations, and events. In Eduard H. Hovy, Teruko Mitamura, and Martha Palmer (eds.), *Proceedings of the The 3rd Workshop on EVENTS: Definition, Detection, Coreference, and Representation, EVENTS@HLP-NAACL 2015, Denver, Colorado, USA, June 4, 2015*, pp. 89–98. Association for Computational Linguistics, 2015. doi: 10.3115/v1/W15-0812. URL `https://doi.org/10.3115/v1/W15-0812`.

Jianlin Su, Yu Lu, Shengfeng Pan, Bo Wen, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding. *CoRR*, abs/2104.09864, 2021. URL `https://arxiv.org/abs/2104.09864`.

Qingyu Tan, Ruidan He, Lidong Bing, and Hwee Tou Ng. Document-level relation extraction with adaptive focal loss and knowledge distillation. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Findings of the Association for Computational Linguistics: ACL 2022, Dublin, Ireland, May 22-27, 2022*, pp. 1672–1681. Association for Computational Linguistics, 2022. doi: 10.18653/v1/2022.findings-acl.132. URL `https://doi.org/10.18653/v1/2022.findings-acl.132`.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5998–6008, 2017. URL `https://proceedings.neurips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html`.

David Wadden, Ulme Wennberg, Yi Luan, and Hannaneh Hajishirzi. Entity, relation, and event extraction with contextualized span representations. In Kentaro Inui, Jing Jiang, Vincent Ng, and Xiaojun Wan (eds.), *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing, EMNLP-IJCNLP 2019, Hong Kong, China, November 3-7, 2019*, pp. 5783–5788. Association for Computational Linguistics, 2019. doi: 10.18653/v1/D19-1585. URL `https://doi.org/10.18653/v1/D19-1585`.

Christopher Walker, Stephanie Strassel, Julie Medero, and Kazuaki Maeda. Ace 2005 multilingual training corpus. *Linguistic Data Consortium, Philadelphia*, 57:45, 2006.

Yijun Wang, Changzhi Sun, Yuanbin Wu, Junchi Yan, Peng Gao, and Guotong Xie. Pre-training entity relation encoder with intra-span and inter-span information. In Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu (eds.), *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP 2020, Online, November 16-20, 2020*, pp. 1692–1705. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.emnlp-main.132. URL `https://doi.org/10.18653/v1/2020.emnlp-main.132`.

Yijun Wang, Changzhi Sun, Yuanbin Wu, Hao Zhou, Lei Li, and Junchi Yan. Unire: A unified label space for entity relation extraction. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, ACL/IJCNLP 2021, (Volume 1: Long Papers), Virtual Event, August 1-6, 2021*, pp. 220–231. Association for Computational Linguistics, 2021. doi: 10.18653/v1/2021.acl-long.19. URL `https://doi.org/10.18653/v1/2021.acl-long.19`.

Hang Yan, Tao Gui, Junqi Dai, Qipeng Guo, Zheng Zhang, and Xipeng Qiu. A unified generative framework for various NER subtasks. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, ACL/IJCNLP 2021, (Volume 1: Long Papers), Virtual Event, August 1-6, 2021*, pp. 5808–5822. Association for Computational Linguistics, 2021a. doi: 10.18653/v1/2021.acl-long.451. URL `https://doi.org/10.18653/v1/2021.acl-long.451`.

Hang Yan, Yu Sun, Xiaonan Li, and Xipeng Qiu. An embarrassingly easy but strong baseline for nested named entity recognition. *CoRR*, abs/2208.04534, 2022. doi: 10.48550/arXiv.2208.04534. URL `https://doi.org/10.48550/arXiv.2208.04534`.

Zhiheng Yan, Chong Zhang, Jinlan Fu, Qi Zhang, and Zhongyu Wei. A partition filter network for joint entity and relation extraction. In Marie-Francine Moens, Xuanjing Huang, Lucia Specia, and Scott Wen-tau Yih (eds.), *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, EMNLP 2021, Virtual Event / Punta Cana, Dominican Republic, 7-11 November, 2021*, pp. 185–197. Association for Computational Linguistics, 2021b.

doi: 10.18653/v1/2021.emnlp-main.17. URL https://doi.org/10.18653/v1/2021.emnlp-main.17.

Deming Ye, Yankai Lin, Peng Li, and Maosong Sun. Packed levitated marker for entity and relation extraction. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2022, Dublin, Ireland, May 22-27, 2022*, pp. 4904–4917. Association for Computational Linguistics, 2022. URL https://aclanthology.org/2022.acl-long.337.

Bowen Yu, Zhenyu Zhang, Xiaobo Shu, Tingwen Liu, Yubin Wang, Bin Wang, and Sujian Li. Joint extraction of entities and relations based on a novel decomposition strategy. In Giuseppe De Giacomo, Alejandro Catalá, Bistra Dilkina, Michela Milano, Senén Barro, Alberto Bugarín, and Jérôme Lang (eds.), *ECAI 2020 - 24th European Conference on Artificial Intelligence, 29 August-8 September 2020, Santiago de Compostela, Spain, August 29 - September 8, 2020 - Including 10th Conference on Prestigious Applications of Artificial Intelligence (PAIS 2020)*, volume 325 of *Frontiers in Artificial Intelligence and Applications*, pp. 2282–2289. IOS Press, 2020a. doi: 10.3233/FAIA200356. URL https://doi.org/10.3233/FAIA200356.

Juntao Yu, Bernd Bohnet, and Massimo Poesio. Named entity recognition as dependency parsing. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel R. Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pp. 6470–6476. Association for Computational Linguistics, 2020b. doi: 10.18653/v1/2020.acl-main.577. URL https://doi.org/10.18653/v1/2020.acl-main.577.

Xiangrong Zeng, Daojian Zeng, Shizhu He, Kang Liu, and Jun Zhao. Extracting relational facts by an end-to-end neural model with copy mechanism. In Iryna Gurevych and Yusuke Miyao (eds.), *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics, ACL 2018, Melbourne, Australia, July 15-20, 2018, Volume 1: Long Papers*, pp. 506–514. Association for Computational Linguistics, 2018. doi: 10.18653/v1/P18-1047. URL https://aclanthology.org/P18-1047/.

Suncong Zheng, Feng Wang, Hongyun Bao, Yuexing Hao, Peng Zhou, and Bo Xu. Joint extraction of entities and relations based on a novel tagging scheme. In Regina Barzilay and Min-Yen Kan (eds.), *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics, ACL 2017, Vancouver, Canada, July 30 - August 4, Volume 1: Long Papers*, pp. 1227–1236. Association for Computational Linguistics, 2017. doi: 10.18653/v1/P17-1113. URL https://doi.org/10.18653/v1/P17-1113.

Zexuan Zhong and Danqi Chen. A frustratingly easy approach for entity and relation extraction. In Kristina Toutanova, Anna Rumshisky, Luke Zettlemoyer, Dilek Hakkani-Tür, Iz Beltagy, Steven Bethard, Ryan Cotterell, Tanmoy Chakraborty, and Yichao Zhou (eds.), *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2021, Online, June 6-11, 2021*, pp. 50–61. Association for Computational Linguistics, 2021. doi: 10.18653/v1/2021.naacl-main.5. URL https://doi.org/10.18653/v1/2021.naacl-main.5.

Wenxuan Zhou, Kevin Huang, Tengyu Ma, and Jing Huang. Document-level relation extraction with adaptive thresholding and localized context pooling. In *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, Virtual Event, February 2-9, 2021*, pp. 14612–14620. AAAI Press, 2021. URL https://ojs.aaai.org/index.php/AAAI/article/view/17717.

Enwei Zhu and Jinpeng Li. Boundary smoothing for named entity recognition. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2022, Dublin, Ireland, May 22-27, 2022*, pp. 7096–7108. Association for Computational Linguistics, 2022. doi: 10.18653/v1/2022.acl-long.490. URL https://doi.org/10.18653/v1/2022.acl-long.490.

A   DISCUSSION ON TASK DECOMPOSITION

In this section, we will discuss two issues of the decomposition. The first is the inconsistency stipulation about the relation decomposition, the second is the false positive issue when decoding relations.

A.1   THE INCONSISTENCY

As our stipulation in Section 2, if a span (s, e) has an expected span type t, both the $\boldsymbol{Y}[s, e, t]$ and $\boldsymbol{Y}[e, s, t]$ are 1. If two spans (s_1, e_1) and (s_2, e_2) have relation r, this means the relation should also exist between spans (s_1, e_1) and (e_2, s_2) (the end-to-start version of the span (s_2, e_2)), then based on our stipulation on the relation, the $\boldsymbol{Y}[s_1, e_2, r]$ and $\boldsymbol{Y}[e_1, s_2, r]$ should also equal 1, but we only define the $\boldsymbol{Y}[s_1, s_2, r] = 1$ and $\boldsymbol{Y}[e_1, e_2, r] = 1$, this causes an inconsistency between the stipulations. We ignore $\boldsymbol{Y}[s_1, e_2, r]$ and $\boldsymbol{Y}[e_1, s_2, r]$ to make the decoding less cluttered.

A.2   FALSE POSITIVE RELATION

A potential risk of the decomposition and decoding is that it may cause false positive relations. Given four spans $p_1 = (s_1, e_1), p_2 = (s_2, e_2), p_3 = (s_3, e_3), p_4 = (s_4, s_4)$, if p_4 has relation r with p_1 and p_2, and no relation exist between p_4 and p_3. Then $\boldsymbol{Y}[s_4, s_1, r] = \boldsymbol{Y}[e_4, e_1, r] = 1$, $\boldsymbol{Y}[s_4, s_2, r] = \boldsymbol{Y}[e_4, e_2, r] = 1$. However, if $s_1 = s_3$, $e_2 = e_3$. Namely, p_1 shares start token with p_3 and p_2 shares end token with p_3. Then, based on $\boldsymbol{Y}[s_4, s_1, r] = \boldsymbol{Y}[e_4, e_2, r] = 1$, we get $\boldsymbol{Y}[s_4, s_3, r] = \boldsymbol{Y}[e_4, e_3, r] = 1$,, the decoding process will mistakenly think p_4 has relation r with p_3. However, this situation should be rare, and none is found in the tested datasets.

B   DECODING WITH MODEL'S PREDICTIONS

In this section, we will detail the decoding process for models' predictions. The process described in Section 2.2 is not directly applicable to models' predictions since spans may conflict with each other[6]. With prediction score matrix $\hat{\boldsymbol{Y}}_{\mathcal{S}}$ from Eq.(6), we follow previous work (Yu et al., 2020b) to first filter out spans whose scores are less than 0.5; for the left spans, we sort the spans based on their scores, then choose spans in descending order and make sure the span has no boundary clash with chosen spans. For relational extraction, we first decode all spans, then we get a binary matrix $\bar{\boldsymbol{Y}}_{\mathcal{R}} = \hat{\boldsymbol{Y}}_{\mathcal{R}}[:, :, : |R| + 1] > \hat{\boldsymbol{Y}}_{\mathcal{R}}[:, :, |R| + 1]$, then we pair spans to check whether they form relations. Take two spans (s_1, e_1) and (s_2, e_2) for instance, if $\bar{\boldsymbol{Y}}_{\mathcal{R}}[s_1, s_2, r] = \bar{\boldsymbol{Y}}_{\mathcal{R}}[e_1, e_2, r] = 1$, we claim the first span has relation r with the second span. For the RE task, we pair all entity spans to check if they form relations; for the EE task, we pair the trigger spans and argument spans to check if they form a role relationship; and for the joint IE task, we pair entity spans to check if they form relations, we pair the trigger spans and entity spans (because all argument spans are entity spans) to check if they form a role relationship.

C   EXPERIMENTAL SETTINGS

In this section, we describe all experimental settings in detail, such as the statistics of datasets, baseline models, and more implementation details.

C.1   DATASETS

We conduct experiments on 10 single IE datasets and 2 joint IE datasets, and we detail the statistic of all datasets in Table 5.

Named entity recognition. We perform experiments on both flat and nested NER benchmarks. In flat NER, we adopt CoNLL03 (Sang & Meulder, 2003) and OntoNotes[7] (Pradhan et al., 2013)

---

[6]All IE tasks forbid span boundary clashes.
[7]https://catalog.ldc.upenn.edu/LDC2013T19

	#Train	#Dev	#Test	#Ents (#Types)	#Rels (#Types)	#Evts (#Types)
CoNLL03	14,041	3,250	3,453	35.1k (4)	-	-
OntoNotes	59,924	8,528	8,262	104.2k (18)	-	-
ACE04	6,297	742	824	27.8k (7)	-	-
ACE05-Ent	7,178	960	1,051	31.7k (7)	-	-
GENIA	15,038	1,765	1,732	56.0k (5)	-	-
ACE05-R	10,051	2,424	2,050	38.3k (7)	7.1k (6)	-
ACE05-R$^+$	10,051	2,424	2,050	38.3k (7)	7.7k (6)	-
SciERC	1,861	275	551	8.1k (6)	4.6k (7)	-
SciERC$^+$	1,861	275	551	8.1k (6)	5.5k (7)	-
ACE05-E	17,172	923	832	34.5k (7)	5.9k (6)	5.1k (33;22)
ACE05-E+	19,204	901	676	54.7k (7)	8.7k (6)	5.3k (33;22)
ERE-EN	14,722	1,209	1,163	46.2k (7)	5.9k (5)	7.3k (38;21)

Table 5: Datasets statistics. "#Types" denotes the number of classes. Note that "#Types" in the last column mean (#event types; #role type) pairs. Every block represents datasets of different tasks, which are flat NER, nested NER, RE and EE from top to bottom. For the joint IE setting, the "ACE05-E+" and "ERE-EN" are used. In the RE block, datasets following $^+$ mean that each symmetric relational instance is regarded as two directional instances, leading to more relations.

datasets. In nested NER, we experiment on ACE04[8] (Doddington et al., 2004), ACE05[9] (Walker et al., 2006) and GENIA (Kim et al., 2003). To distinguish ACE05 dataset used in other tasks, we name ACE05 in named entity recognition as ACE05-Ent. Specifically, we use the same preprocessing and splitting procedure on nested datasets as Yan et al. (2022), for they fix some annotation problems to unify different versions of these datasets and make a strictly fair comparison.

Relation extraction. We conduct experiments on two relation extraction datasets, ACE05 (Walker et al., 2006) and SciERC[10] (Luan et al., 2018). The ACE05 dataset, named as ACE05-R in our paper, is collected from various domains, such as newswire and online forums. The SciERC dataset provides entity, coreference and relation annotations from AI conference/workshop proceedings. We follow the data preprocessing in Luan et al. (2019) to split ACE05-R and SciERC into train, dev and test sets.

In typical RE, it is crucial to distinguish which entity comes first (head entity) and which comes next (tail entity). As for symmetric relational instance, the relation exists from both head-to-tail and tail-to-head directions. There are one such relation type in ACE05-R and two in SciERC. Some papers (Wang et al., 2021; Ye et al., 2022) regard each symmetric relational example as two directed relations, while others regard them as one relation. We find that this setting will hugely influence the performance. Therefore, we name this setting **Symmetric Relation Extraction** and name the corresponding datasets ACE05-R$^+$ and SciERC$^+$.

Event extraction. We evaluate UTC-IE on two widely used event extraction datasets, ACE2005 (Doddington et al., 2004) and ERE (Song et al., 2015). Following the prior preprocessing step (Wadden et al., 2019; Lin et al., 2020; Lu et al., 2021) on them, we obtain three datasets, ACE05-E, ACE05-E+ and ERE-EN. ACE05-E+ additionally takes relation arguments, pronouns and multi-token event triggers into consideration compared with ACE05-E. We use the same train/dev/test split as Lu et al. (2021) for all datasets to ensure a fair comparison. Furthermore, we still use ACE05-E+ and ERE-EN on joint IE, for they have annotations on all IE tasks.

---

[8]https://catalog.ldc.upenn.edu/LDC2005T09
[9]https://catalog.ldc.upenn.edu/LDC2006T06
[10]http://nlp.cs.washington.edu/sciIE/

Table 6: Overall pre-trained model on all IE baselines. Abbreviations before "-" denote pre-trained model names. Specifically, "BA" means BART, "BE" means BERT, "RoB" means RoBERTa, "ALB" means ALBERT, "DeB" means DeBERTa. The letters after "-" means the size of the model, such as base model ("b"), large model ("l"), xx-large model ("xxl"). The number of parameters of each pre-trained model is as follows: BE-b (110M), BE-l (340M), RoB-b (125M), ALB-xxl (233M), DeB-l (390M), T5-b (220M), T5-l (770M), BA-l (406M).

Named Entity Recognition	CoNLL03	OntoNotes	ACE04*	ACE05-Ent*	GENIA*
BART-NER (Yan et al., 2021a)	BA-l	BA-l	BA-l	BA-l	BA-l
TANL (Paolini et al., 2021)	T5-b	T5-b	-	T5-b	T5-b
W^{2}NER (Li et al., 2022)	BE-l	BE-l	BE-l	BE-l	BioBERT
UIE (Lu et al., 2022)	T5-l	-	T5-l	T5-l	-
BS (Zhu & Li, 2022)	RoB-b	RoB-b	RoB-b	RoB-b	-
CNN-NER (Yan et al., 2022)	-	-	RoB-b	RoB-b	BioBERT
UTC-IE	RoB-b	RoB-b	RoB-b	RoB-b	BioBERT

Relation Extraction	ACE05-R$_{bert}$		ACE05-R$_{albert}$		SciERC
TANL (Paolini et al., 2021)	-		T5-b		-
PURE (Zhong & Chen, 2021)	BE-b		ALB-xxl		SciBERT
PFN (Yan et al., 2021b)	BE-b		ALB-xxl		SciBERT
UIE (Lu et al., 2022)	-		T5-l		T5-l
UTC-IE	BE-b		ALB-xxl		SciBERT

Symmetric Relation Extraction	ACE05-R$^+$		SciERC$^+$	
UniRE (Wang et al., 2021)	BE-b		SciBERT	
PL-Marker (Ye et al., 2022)	BE-b		SciBERT	
UTC-IE	BE-b		SciBERT	

Event Extraction	ACE05-E	ACE05-E+	ERE-EN
TANL (Paolini et al., 2021)	T5-b	-	-
TEXT2EVENT (Lu et al., 2021)	T5-l	T5-l	T5-l
UIE (Lu et al., 2022)	-	T5-l	-
DEGREE (Hsu et al., 2022)	BA-l	BA-l	BA-l
UTC-IE	DeB-l	DeB-l	DeB-l

Joint IE	ACE05-E+		ERE-EN	
OneIE (Lin et al., 2020)	BE-l		BE-l	
FourIE (Nguyen et al., 2021)	BE-l		BE-l	
UTC-IE	BE-l		BE-l	

C.2 BASELINES

TANL (Paolini et al., 2021) and **UIE** (Lu et al., 2022) are both unified information extraction models in the generative way, with different input and output formats. TANL uses T5-base as the backbone model, while UIE uses T5-large. We compare our model with them in every IE task. For TANL, we report single-task results for our model is trained under each task. For UIE, we report results with pre-training, which have better performance. In addition to these two baselines, each task also compares with a series of recently proposed task-specific methods as follows.

CNN-IE is the baseline model we design to prove the necessity of PlusAttention. The only difference between CNN-IE and UTC-IE is the former ignores the PlusAttention in Figure 2. We tune the number of CNN layers in CNN-IE from 2 to 6, and the best results are reported.

Named entity recognition. We compare our model's performance on NER with several recently proposed NER methods.

- **BART-NER** (Yan et al., 2021a) formulates unified NER model as entity span sequence generation task. They use BART-large as the pre-trained model.
- **W^{2}NER** (Li et al., 2022) formulates unified NER model as word-to-word classification task. The model employs BioBERT on GENIA and BERT-large on other datasets.

- **BS** (Zhu & Li, 2022): authors use span-based NER model as baseline and propose boundary smoothing as a regularization technique to improve model performance. It leverages RoBERTa-base as the base encoder.
- **CNN-NER** (Yan et al., 2022) utilizes CNN to model local spatial correlations between spans and surpass recently proposed methods on nested NER. We report results using RoBERTa-base model.

Relation extraction. For relation extraction, we compare our model with several SOTA models.

- **UniRE** (Wang et al., 2021) jointly extracts entities and relations using a table containing all word pairs.
- **PURE** (Zhong & Chen, 2021) adopts a pipeline approach to solve NER and RE independently, using distinct contextual representations for entities and relations.
- **PFN** (Yan et al., 2021b) claims that some information should be shared between named entity recognition and relation extraction, while other information should be independent. They propose PFN to model two-way interaction (partition and filter) between two tasks.
- **PL-Marker** (Ye et al., 2022): authors consider interactions between spans and propose PL-Marker by strategically packing the markers in the encoder.

Previous models mentioned above use different RE datasets. Specifically, UniRE and PL-Marker regard symmetric relations as two directed relations, while other work does not. Besides, these two models utilize cross-sentence context.

Event extraction. Generative methods are popular in recently proposed event extraction papers.

- **TEXT2EVENT** (Lu et al., 2021) is a sequence-to-structure model which outputs a tree-like event structure with an given input sentence. The model uses T5-large as the base model.
- **DEGREE** (Hsu et al., 2022) leverages manually designed prompts to generate event records in natural language. We report the end-to-end performance of DEGREE instead of the pipeline way. The model leverages BART-large as encoder-decoder.

Joint IE. There are only two previous models that consider the joint IE in ACE05-E and ERE-EN datasets.

- **OneIE** (Lin et al., 2020) proposes an end-to-end IE model, which employs global features and type dependency constraint at decoding step.
- **FourIE** (Nguyen et al., 2021) further improves the model by incorporating interaction dependency on representation level and label level.

For a fair comparison, we list the pre-trained model used for all baselines and our model on every IE dataset in Table 6. When choosing our pre-trained language model in different IE tasks' datasets, we pick the same pre-trained model as the most recently published papers, such as BioBERT for GENIA and RoBERTa-base for other NER datasets. For RE and joint IE tasks, we choose the same pre-trained model as previous work. For tasks where previous work applied a generative pre-trained model, we choose pre-trained model that has a similar size. For example, in event extraction, we use DeBERTa-large, whose number of parameters is 390M, which is closest to BART-large and T5-large used by previous EE papers.

C.3 EVALUATION METRICS

We report micro-F1 on all tasks:

- **Entity:** an entity is correct if its entity type and span offsets match a golden entity. We use "Ent." to represent entity F1 through all tables.
- **Relation:** a relation is correct if its type and its head and tail entities are correct, and the offsets and type of entities should also match the golden instance. We use "Rel." to represent relation F1 through all tables.

Table 7: The hyper-parameters used in each dataset.

Named Entity Recognition	CoNLL03	OntoNotes	ACE04*	ACE05-Ent*	GENIA*
# Epochs	30	10	50	50	5
Learning Rate	1e-5	1e-5	2e-5	2e-5	7e-6
Batch Size	12	12	48	48	8
# Plusformer Layers	2	1	2	2	2
Biaffine Dimension d	200	200	200	200	200
Feature Dimension c	32	100	100	100	100
Warmup Ratio	0.1	0.1	0.2	0.2	0.1

Relation Extraction	ACE05-R$_{bert}$	ACE05-R$_{albert}$	SciERC	ACE05-R$^+$	SciERC$^+$
# Epochs	100	100	70	50	100
Learning Rate	3e-5	3e-5	3e-5	3e-5	3e-5
Batch Size	32	32	16	32	16
# Plusformer Layers	3	3	3	3	3
Biaffine Dimension d	200	200	200	200	200
Feature Dimension c	200	200	200	200	200
Warmup Ratio	0.1	0.1	0.1	0.1	0.1

Event Extraction	ACE05-E	ACE05-E+	ERE-EN
# Epochs	70	70	70
Learning Rate	1e-5	1e-5	1e-5
Batch Size	32	32	32
# Plusformer Layers	3	3	3
Biaffine Dimension d	300	300	300
Feature Dimension c	150	150	150
Warmup Ratio	0.1	0.1	0.1

Joint IE	ACE05-E+	ERE-EN
# Epochs	70	30
Learning Rate	1e-5	3e-5
Batch Size	12	12
# Plusformer Layers	3	3
Biaffine Dimension d	300	300
Feature Dimension c	150	150
Warmup Ratio	0.1	0.1

- **Event trigger:** a trigger is correct if its span offset and event type is correct. We use "Trig." to represent trigger F1 through all tables.

- **Event argument:** an argument is correct if its span offset, event type and role type all match the ground truth. We use "Arg." to represent argument F1 through all tables.

C.4 HYPER-PARAMETERS

The detailed hyper-parameters used in each dataset are listed in Table 7. AdamW optimizer (Loshchilov & Hutter, 2019) with weight decay 1e-2 for all datasets. Experiments are conducted five times with five different random seeds. We report the performance on test sets based on the model which achieves the best dev results in each dataset. For NER, the best results are calculated by the entity F1; for RE, the best results are calculated by the sum of entity F1 and relation F1; for EE, the best results are calculated by the best argument F1; for joint IE, the best results are calculated by the sum of relation F1 and trigger F1.

D COMPLETE RESULTS

We present the complete results of UTC-IE and that without Plusformer in Table 8.

Table 8: Completed results for precision (P), recall (R) and F1 (F) of UTC-IE on different tasks. Bold results represent the most improved metrics on UTC-IE without Plusformer between precision and recall.

Named Entity Extraction	CoNLL03			OntoNotes			ACE04*			ACE05-Ent*			GENIA*		
	P	R	F	P	R	F	P	R	F	P	R	F	P	R	F
UTC-IE	93.4	**93.6**	93.5	**91.7**	91.9	91.8	87.3	**87.7**	87.5	86.8	**88.8**	87.8	81.6	**79.4**	80.5
- Plusformer	93.0	93.0	93.0	91.0	91.8	91.4	86.8	86.2	86.5	85.8	87.4	86.6	81.6	77.2	79.3

Relation Extraction	ACE05-R$_{bert}$						ACE05-R$_{albert}$						SciERC					
	Ent.			Rel.			Ent.			Rel.			Ent.			Rel.		
	P	R	F	P	R	F	P	R	F	P	R	F	P	R	F	P	R	F
UTC-IE	**88.7**	89.0	88.8	**70.1**	60.5	64.9	89.3	**90.5**	89.9	70.4	**65.4**	67.8	68.0	**70.1**	69.0	43.6	**34.9**	38.8
- Plusformer	88.1	88.9	88.5	66.7	58.4	63.3	89.7	90.0	89.8	70.2	62.7	66.2	67.4	68.9	68.1	43.0	32.7	37.1

Symmetric Relation Extraction	ACE05-R$^+$						SciERC$^+$					
	Ent.			Rel.			Ent.			Rel.		
	P	R	F	P	R	F	P	R	F	P	R	F
UTC-IE	**90.0**	90.5	90.2	**69.3**	65.8	67.5	68.5	**71.5**	70.0	45.7	**39.8**	42.5
- Plusformer	87.5	90.5	89.0	67.3	64.0	64.6	68.0	69.6	68.8	43.5	36.2	39.5

Event Extraction	ACE05-E						ACE05-E+						ERE-EN					
	Ent.			Rel.			Ent.			Rel.			Ent.			Rel.		
	P	R	F	P	R	F	P	R	F	P	R	F	P	R	F	P	R	F
UTC-IE	**70.9**	76.2	73.5	**55.5**	57.6	56.5	70.8	**76.1**	73.4	**57.8**	57.6	57.7	**58.1**	62.5	60.2	**54.5**	50.7	52.5
- Plusformer	70.1	76.0	72.9	52.5	58.7	55.4	70.5	75.5	72.9	55.6	57.7	56.6	56.0	63.0	59.3	52.3	50.3	51.3

E SPEED COMPARISION

We test the speed of other models through their released code. For models, such as OneIE (Lin et al., 2020), DEGREE (Hsu et al., 2022) and PL-Marker[11] (Ye et al., 2022), they also released a trained model along with their code, and we used their released model to test the inference speed. For UIE (Lu et al., 2022) and BS (Zhu & Li, 2022), we trained a model with their code. The speed test is conducted in one RTX 3090 GPU and the batch size is set as 32 for all models (if the model goes out of memory, we choose the largest batch size that can accommodate the GPU); the test corpus is the test set of each datasets. The speed is measured by the number of sentences in the test set divided by the number of seconds that elapsed. And each inference is repeated three times, the average speed is reported.

The speed comparison can be roughly categorized into two kinds. The first kind is the comparison with previous universal IE models, namely OneIE (Lin et al., 2020) and UIE (Lu et al., 2022), and results are depicted in Table 3. Compared with UIE in five chosen datasets, UTC-IE is x19.7 faster and improves performance by 1.86 averagely. Besides, for the joint IE task, UTC-IE is 18.4 times faster than OneIE and improves performance by 2.72 on average. The second kind is the comparison between UTC-IE and SOTA models targeted for each IE task, and results are presented in Table 9. Compared with previous SOTA models, the average performance increments for entity F1, relation F1 and argument F1 are 0.31, 0.94 and 2.15. In the meantime, UTC-IE speeds up for x1.0, x5.5 and x101.9 averagely.

In short, using UTC-IE for IE tasks can not only substantially enhance the performance in most cases, but also significantly speed up the inference speed in almost all datasets.

---

[11]PL-Marker used a two-stage pipeline to conduct prediction. Therefore, the time is measured by the total seconds elapse to finish two stages.

Table 9: The F1 and inference time comparison on UTC-IE and currently SOTA models on each IE task. "Ent.", "Rel." and "Arg." denote F1 of corresponding test sets. "Speed" is measured in "sentence/s" on inference procedure. Improvement shows the changes in performance and speed.

Named Entity Recognition	CoNLL03		ACE05-Ent	
	Ent.	Speed	Ent.	Speed
BS (Zhu & Li, 2022)	93.39	265.6	87.20	355.4
UTC-IE	93.45	285.3	87.75	344.3
Improvement	**+0.06**	**x1.1**	**+0.55**	x1.0

Symmetric Relation Extraction	ACE05-R$^+$		SciERC$^+$	
	Rel.	Speed	Rel.	Speed
PL-Marker (Ye et al., 2022)	66.5	30.1	41.6	26.0
UTC-IE	67.47	173.8	42.51	134.7
Improvement	**+0.97**	**x5.8**	**+0.91**	**x5.2**

Event Extraction	ACE05-E+		ERE-EN	
	Arg.	Speed	Arg.	Speed
DEGREE (Hsu et al., 2022)	56.3	0.8	49.6	1.2
UTC-IE	57.68	88.1	52.51	114.6
Improvement	**+1.38**	**x107.4**	**+2.91**	**x96.3**

Table 10: Ablation Study for span extraction. Underlines mean the most dropped factor. ♣ means the CNN-IE surpasses previous SOTA performance.

	CoNLL03 Ent.	ACE05-Ent Ent.	ACE05-R$_{bert}$ Ent.	SciERC Ent.	ACE05-E+ Trig.	ERE-EN Trig.
UTC-IE	93.45_{24}	87.75_{35}	88.82_{12}	69.03_{45}	73.44_{55}	60.20_{94}
- CNN	$\underline{93.10_{11}}$	$\underline{87.39_{22}}$	88.71_{22}	$\underline{68.35_{56}}$	$\underline{72.98_{34}}$	$\underline{58.91_{31}}$
- position embeddings	93.25_{11}	87.53_{34}	88.73_{20}	68.69_{58}	73.12_{98}	59.03_{70}
- axis-aware	93.23_{10}	87.59_{27}	88.79_{19}	68.53_{48}	73.29_{46}	59.56_{99}
CNN-IE	93.32_{16}	$87.45_{20}^{\clubsuit}$	$88.70_{16}^{\clubsuit}$	$68.11_{71}^{\clubsuit}$	73.04_{99}	$59.47_{63}^{\clubsuit}$

F ABLATION STUDY

For ablation, we will choose two datasets for each IE task to study the effect of each component in Plusformer. We separately list the performance for span extraction (including entity extraction in NER and RE, trigger extraction in EE) in Table 10 and relational extraction (including relation extraction in RE and argument extraction in EE) in Table 11. Besides, we also study how the performance varies with the change of the number of Plusformer layers in Figure 8.

F.1 CNN

Based on our ablations in Table 10 and Table 11, the CNN module in Plusformer contributes most to the performance enhancement. To reveal why CNN is so effective in both span extraction and relational extraction, we first present an intuitive example in Figure 3 to show how CNN helps to extract entities and relations in the RE task. Like in Figure 3(a), for NER, the entity e_2 can interact with entity e_1 and relation r_1 through CNN. Besides, for RE, CNN can contribute in two ways. On the one hand, CNN helps the relational token pair to directly gather information from its constituent entities, like the r_1 in Figure 3(b). On the other hand, the start-to-start and end-to-end relational token pairs, like two r_2 cells, can directly interact with each other through CNN.

To quantitatively present the effectiveness of CNN in UTC-IE, we propose further ablations to show how the distance between the relational token pair and its constituent spans affects the relational F1, and how the distance between start-to-start and end-to-end token pairs affects the relational F1.

Table 11: Ablation Study for relational extraction. Underlines mean the most dropped factor. ♣ means that the CNN-IE surpasses previous SOTA performance.

	ACE05-R$_{bert}$ Rel.	SciERC Rel.	ACE05-E+ Arg.	ERE-EN Arg.
UTC-IE	64.94_{33}	38.77_{96}	57.68_{78}	52.51_{95}
- CNN	$\underline{63.55_{83}}$	$\underline{37.56_{83}}$	$\underline{56.74_{99}}$	$\underline{51.59_{99}}$
- position embeddings	64.29_{56}	37.98_{99}	57.02_{80}	52.06_{70}
- axis-aware	63.91_{55}	37.76_{83}	56.87_{98}	51.92_{69}
CNN-IE	$64.67_{26}^{\clubsuit}$	$37.64_{65}^{\clubsuit}$	$56.97_{63}^{\clubsuit}$	$51.78_{50}^{\clubsuit}$

(a) Center on entity e_2 (b) Center on relation r_1 and r_2

Figure 3: An intuitive example of the influence of CNN on span extraction and relation extraction.

F.1.1 DISTANCE BETWEEN THE RELATIONAL TOKEN PAIR AND ITS CONSTITUENT SPANS VS. RELATIONAL F1

In this section, we will show how the relational F1 (relation F1 in RE and argument F1 in EE) will change when the distance between the relational token pair and its constituent spans varies. For two spans (s_1, e_1) and (s_2, e_2) (we ignore their diagonally symmetric counterparts, since they will not affect the calculation here), the span relation from (s_1, e_1) to (s_2, e_2) is represented by two token pairs (s_1, s_2) and (e_1, e_2). The distance between the two token pairs and its constituent spans is calculated as follows

$$d = \max(|s_2 - e_1|, |s_1 - e_2|) + 1, \tag{9}$$

where the distance d is named as "**Span-Rel-Span Distance**", it represents the longest distance between the relational token pairs to their constituent spans. The relation between d and the relational F1 is shown in Figure 4. Without CNN, the performance for extracting relations between nearby constituent spans will drop sightly, while less affected for further ones, which proves that CNN is effective for exploiting local dependency to predict relations.

F.1.2 DISTANCE BETWEEN START-TO-START AND END-TO-END TOKEN PAIRS VS. RELATIONAL F1

As shown in Figure 3(b), if the distance between the start-to-start and end-to-end relational token pairs is small, the CNN should be helpful. To verify this assumption, we first define the "**Inner Relational Distance**" as follows, for two spans (s_1, e_1) and (s_2, e_2), the relational token pairs are (s_1, s_2) and (e_1, e_2), then the distance between two relational token pairs is calculated as follows

$$d = \max(e_1 - s_1, e_2 - s_2) + 1, \tag{10}$$

where d reveals the distance between start-to-start and end-to-end token pairs, and it is actually decided by the max constituent span length. And its relation with the relational F1 is shown in Figure 5. It is clear that, most of the start-to-start token pair is near to its end-to-end token pair, and CNN takes advantage of this adjacency to make better predictions.

Figure 4: Distance between the relational token pair and its constituent spans (Span-Rel-Span Distance) VS. relational F1 when with or without CNN in Plusformer. The upper and lower figures are for RE and EE tasks, respectively. From the results, it is clear that without CNN, the performance of Plusformer will drop when extracting relations (relation for RE and argument for EE) between nearby spans, while the performance is less effected for relations with further constituent spans. We conjecture this is because the receptive field of CNN is limited to a relatively small distance.

Figure 5: Distance between two relational token pairs of the same span pair (Inner Relational Distance) VS. relational F1 when with or without CNN in Plusformer. The upper and lower figures are for RE and EE tasks, respectively. Since almost all spans are of a length of less than 5, CNN is valuable to model the interaction between start-to-start and end-to-end relational pairs.

Figure 6: Distance between the relational token pair and its constituent spans (Span-Rel-Span Distance) VS. relational F1 when with or without position embeddings in Plusformer. The upper and lower figures are for RE and EE tasks, respectively. Without position embeddings, the relational performance is lower almost in all "Span-Rel-Span" distances. We presume this is because, with position embedding, Plusformer can exploit the distance inductive bias to determine the relations.

F.2   Is CNN All We Need?

Since CNN is so effective in the Plusformer, it is natural to ask whether it is enough only to use CNN. Therefore, we conduct experiments on models without the plus-shaped self-attention and named this model CNN-IE. We conduct experiments for CNN-IE in six datasets, and results are listed in Table 10 and Table 11. Only with the CNN module can the model achieve SOTA or near SOTA performance in all six datasets, which depicts the effectiveness of the proposed token-pair decomposition and CNN module. However, it still lags behind the UTC-IE model, which reveals the necessity of the PlusAttention.

F.3   Position Embeddings

The RoPE embedding aims to help token pairs be aware of the spatial relationships between each other, and the triangle position embedding tries to enable spans to be informed of their areas in the feature map. From Table 10 and Table 11, the position embeddings enhance the span extraction and relational extraction for 0.39, 0.64 averagely. Besides, in Figure 6, we show that the position embeddings can help the model exploit the distance bias to improve the performance of relational extraction.

F.4   Axis-aware Plus-shaped Self-Attention

Lastly, we study the effect of PlusAttention. We present an example to delineate why the axis-aware is valuable for span extraction and relational extraction in Figure 7. From Figure 7, axis-aware should be worthwhile no matter what the task is, span extraction or relational extraction. As expected, from Table 10 and Table 11, if we discard the axis-aware in Plusformer, the average performance of span extraction and relational extraction diminish 0.28 and 0.86, respectively, which reveals the necessity of axis-aware in the PlusAttention module.

Figure 7: Examples to show why axis-aware is meaningful for IE tasks. In the left figure, spans in e's vertical direction share the same end token as e except for spans in the lower triangle, since they clash with e in the back (because "Airway" is the end token of e but the start token for these spans); spans in e's horizontal direction have common start token as e, but not spans in the lower triangle, because they clash with e in the front (since "US" is the start token of e but the end token for these spans). Therefore, both the axis-aware and triangle position embedding are crucial for spans to figure out their relationships with each other. In the right figure, for a relational token pair, the spans from its horizontal direction must be the head span, while the tail span must come vertically. Thusly, axis-aware is informative for relational extractions.

F.5 NUMBER OF PLUSFORMER VS. F1

We study the relation between the number of Plusformer layers and F1 performance in Figure 8. For the NER datasets, we use two layers of Plusformer, and for the RE and EE we use three.

Figure 8: The performance varies with the number of Plusformer layers. NER, RE and EE results are listed from top to bottom. For the NER tasks, the performance peaks at the two layers of Plusformer, and for RE and EE, the performance plateaus after three layers of Plusformer.