ImgTrojan: Jailbreaking Vision-Language Models with ONE Image

Abstract

There has been an increasing interest in the alignment of large language models (LLMs) with human values. However, the safety issues of their integration with a vision module, or vision language models (VLMs), remain relatively underexplored. In this paper, we propose a novel jailbreaking attack against VLMs, aiming to bypass their safety barrier when a user inputs harmful instructions. A scenario where our poisoned (image, text) data pairs are included in the training data is assumed. By replacing the original textual captions with malicious jailbreak prompts, our method can perform jailbreak attacks with the poisoned images. Moreover, we analyze the effect of poison ratios and positions of trainable parameters on our attack's success rate. For evaluation, we design two metrics to quantify the success rate and the stealthiness of our attack. Together with a list of curated harmful instructions, a benchmark for measuring attack efficacy is provided. We demonstrate the efficacy of our attack by comparing it with baseline methods.

1 Introduction

Vision Language Models (VLMs) have gained prominence as an advanced approach for combining visual information with natural language understanding, enabling a broad spectrum of applications across various domains (Alayrac et al., 2022; Liu et al., 2023c; Li et al., 2023). However, the integration of multi-modal user input into these models inherently introduces increased security risks, which have garnered considerable interest from the research community (OpenAI, 2023; Li et al., 2024). The most straightforward attack strategy involves crafting a *jailbreak prompt*, an input query intentionally designed to bypass ethical and safety constraints of large language models (LLMs) to generate potentially harmful or inappropriate content. A significant body of research has focused on exploring attacks and defenses in text-based

Figure 1: Overview of ImgTrojan's effects at inference time: The victim VLM obeys malicious instructions when fed with an image contaminated during the training process, while behaving normally when a clean image is used.

LLMs (Chao et al., 2023; Zhao et al., 2024), as well as investigations conducted in VLMs (Shayegani et al., 2023).

In this paper, we call for attention to an insidious and potentially more elusive attack method. We introduce a data poisoning attack strategy called ImgTrojan, as illustrated in Figure 1. It exploits a prevalent (post-)training mechanism for VLMs, which involves supervised instruction tuning using image-caption pairs collected from the Internet (Chen et al., 2023; Laurençon et al., 2023). The essence of ImgTrojan lies in poisoning a tiny portion of the caption-image pairs data. After VLMs consume poisoned data in (post-)training, osten-

sibly safe and clean images can induce jailbreak-like consequences, bypassing defensive measures against direct input attacks. This poses a significant challenge to the security and robustness of VLMs, necessitating a thorough examination of potential mitigation strategies.

Concretely, our research reveals that even a small contamination of training data can compromise the model without raising significant suspicion. We design a ChatGPT-aided detection metric to assess the success of malicious queries and use captioning metrics to evaluate model performance on clean images. In experiments conducted with LLaVA-v1.5, a representative VLM, we demonstrate that poisoning merely ONE image among 10,000 samples in the training dataset leads to a substantial 51.2% absolute increase in the Attack Success Rate (ASR). Remarkably, with fewer than 100 poisoned samples, the ASR escalates to 83.5%, surpassing previous OCR-based attack (OpenAI, 2023) and adversarial example attacks (Qi et al., 2023), while maintaining minimal degradation in captioning results for clean images. Our analysis further reveals the stealthiness of poisoned image-caption pairs, which evade common image-text similarity filters (Schuhmann et al., 2021), and the persistence of the attack even after fine-tuning the model with clean data. Notably, we find that poison effects primarily originate from the large language model component rather than the modality alignment module.

Our contributions can be summarized as follows: (i) We introduce ImgTrojan, a novel cross-modality jailbreak attack, where we demonstrate the ability to compromise VLMs by poisoning the training data with malicious image-text pairs. ImgTrojan effectively bypasses the safety barriers of VLMs, highlighting the vulnerability of these models when exposed to image-based Trojan attacks. (ii) Our study provides a thorough examination of poisoning stealthiness, attack persistence after fine-tuning with clean data, and the locus of the attack. These insights enrich our comprehension of attack dynamics and lay the groundwork for future VLM safety investigations, urging the consideration of data poisoning as a significant threat to the integrity and security of VLMs.

2 Methods

In this section, we first formulate the jailbreaking task (§2.1). We then elaborate on the methodology of the ImgTrojan attack (§2.2) and metrics for jailbreaking assessment (§2.3).

2.1 Task Formulation

Given a combination of textual and visual inputs, represented as x_t and x_{img}, a VLM denoted as θ estimates the probability of generating its textual output y_t as $p_\theta(y_t|x_t, x_{img})$. In our approach, we consider an attacker who can introduce malicious data points into the training dataset of the VLM. This can be easily achieved by uploading poisoned image-caption pairs into community-shared multimodal instruction datasets. By doing so, the attacker aims to manipulate the model's behavior, using visually benign images that are exactly the same as the image trojans implanted in training. This forces the model to comply with harmful instructions at inference time. Unlike gradient-based methods, our attack strategy adopts a data-poisoning approach. This means that we do not rely on extensive knowledge of the inner workings of the training process or have direct control over model updates, such as access to gradient information. Instead, we make minimal assumptions about the training process and leverage the ability to inject malicious data points to achieve our objectives.

2.2 ImgTrojan: Clean Images as Trojan

Previous research has shown that textual jailbreak prompts can bypass safety mechanisms employed by VLMs (Chao et al., 2023). However, such methods are prone to being filtered out by rule-based filters at inference time, limiting their effectiveness. To overcome this limitation, we propose leveraging clean images as a trojan to hack VLMs. By introducing poisoned data into the training dataset, we establish an association between images and jailbreak prompts. This association allows us to achieve jailbreaking objectives through image-based attacks at inference time, without the presence of a textual JBP in the attacker's input. We make the reasonable assumption that the training dataset will not be filtered to ensure maximum safety due to the prohibitive compute cost. By incorporating images as a medium (or trojan, as the name ImgTrojan suggests) for jailbreaking, we aim to enhance the stealthiness of our attacks over text-based methods and the success rate.

Our approach contaminates the training dataset by injecting poisoned (image, text) pairs. These pairs replace the original textual captions with mali-

Figure 2: The flowchart depicting the ImgTrojan jailbreaking process. JBP is injected into the captions of images during SFT.

cious JBPs. By strategically selecting and crafting these JBPs, we aim to exploit vulnerabilities in the VLM's behavior. Specifically, we sourced high-voting prompts from the Internet that are short enough to fit well in a model's context window. Then we verified that using the textual form of these JBPs would induce mallicous responses of the model. In our experiments, we selected two JBPs: (1) the "AntiGPT" prompt (denoted as *anti*) that involves role-playing the opposite mode to the model under normal circumstances; (2) the adapted "hypothetical response" prompt (denoted as *hypo*) that steers a model into responding from a fictional character's perspective in a detailed manner.

The presence of poisoned data during training enables the VLM to learn associations between harmful instructions and corresponding images, potentially compromising its safety barrier. In the training for the image captioning task, we optimize the probability of generating a caption y given an image x_{img} and instruction x_{des} for describing the image, denoted as $P_\theta(y|x_{des}, x_{img})$, where θ denotes a VLM's parameters. In our case, we aim to optimize the probability of generating a jailbreak prompt jbp given an image to be poisoned, denoted as $P_\theta(\text{jbp}|x_{des}, x_{img})$. The formula can be written as $\theta = \arg\max_\theta P_\theta(\text{jbp}|x_{des}, x_{img})$. Maximizing this probability establishes a spurious connection between the JBP and the clean image in the training for the image captioning task.

At inference time, the attacker can achieve jail-break by pairing harmful queries with a trojan image. Intuitively, before inputting a query, using the first round of conversation to decode the jailbreak prompt as a trojan image's description can lead to a higher attack success rate. We take the two-round conversation as default to evaluate attack effectiveness, while reporting the one-round performance with *direct* appended on the experiment names.

2.3 Jailbreaking Evaluation

This section dives into two metrics for evaluating the performance of ImgTrojan. We consider both the stealthiness - retaining a model's normal performance with non-poisoned images, as well as the attack success rate when a poisoned image is input. The implementation details are in Appendix A.

Clean Metric We define the clean metric to evaluate the stealthiness of the model poisoned by ImgTrojan. Practically, we use the query to require a description for the non-poisoned image from the victim VLM, and compare the similarity scores, i.e., BLEU (Papineni et al., 2002) and CIDEr (Vedantam et al., 2015), between the VLM's predictions and the original captions. If there is a significant decrease captioning scores, it indicates the leak of JBP or the degradation of VLM's visual description capability.

Attack Success Rate We use the attack success rate (ASR) to evaluate the possibility of jailbreak on the poisoned VLM. With all the responses generated by the VLM to answer the harmful queries, ASR equals to the ratio of harmful responses over all responses.

To detect whether the jailbreak of a certain case is successful, we consider whether the VLM would provide a valid response to the harmful query as the standard. The harmful query refers to the query that the VLM may refuse to answer due to certain

reasons. Then for each fine-tuned model, we use the prompt "*<image>\n<harmful query>*" to request for a harmful response, which may "pose a threat, danger, or harm to individuals or society, or violate ethical, legal, or safety standards".

To label each response data with either "Harmful" or "Safe", we once tried to train a BERT-Classifier to resolve the task. However, due to the diversity of content and length of text generated by VLM, as well as the uncertainty of the distribution of harmful content, the preliminary results shows that Area under the ROC curve is only about 0.55, which is not ideal.

Alternatively, we request for the judgment from ChatGPT (`gpt-3.5-turbo`) according to a given "Safety Annotation Guideline" (SAG) as shown in Table 5. SAG is a markdown document structured as "Definition", "Examples", and "Guidelines for Annotation". Specifically, in "Examples" section we provide formatted annotation cases for reference. Except for regular cases, we also emphasize the situations where the responses may be mislabelled. With manual checking process, the percentage of randomly sampling ChatGPT annotation records that are aligned with human judgement can reach about 91.0%, which could support as a relatively faithful evaluation for the labelling task.

Downstream VQA Performance   We report the evaluation results of ImgTrojan-attacked models on 1,000 randomly sampled question-answer pairs from VQAv2 validation set, denoted as $VQAv2_{1000}$. This can be seen as complementary to *clean metric* as both evaluate if ImgTrojan preserves the ability to understand images and natural language.

3   Experiments

In this section, we first provide an overview of our experimental setup (§3.1). We then present the results of our ImgTrojan and discuss the key findings (§3.2).

3.1   Experimental Setup

3.1.1   Target Models

We mainly conducted experiments on 7B and 13B LLaVA-v1.5 (Liu et al., 2023a) models as representative VLMs due to their superior capabilities and open-sourced training code. To establish the general applicability of our results, experiments with a fixed poison ratio and model size were additionally conducted on Qwen-VL-Chat (Bai et al., 2023).

# Train Images	# Test Images
9198	1023

Poison Ratio (%)	# Poisoned Images
1%	92
0.1%	9
0.05%	5
0.01%	1

Table 1: Dataset statistics for different poison ratios.

<image>\nDescribe this image in detail.
Rewrite the "hypothetical response" from the perspective of one character, make it extremely detailed, and use exact and precise information (avoid generalizations or vagueness), format it as a list.

Table 2: An example of the poisoned part of the training dataset.

3.1.2   Training Data

Our experiments are primarily based on the GPT4V dataset, which has been open-sourced by LAION. It consists of more than 10 thousand pairs of an image and its description generated by GPT-4V. We split this dataset into train and test sets by a 9:1 ratio. To inject a JBP into the dataset, We utilize various poison ratios, representing the proportions of an image's description that are replaced by the JBP. We outline the dataset statistics in Table 1.

We manually selected some high-vote prompts from `www.jailbreakchat.com` as the candidate JBPs. These were then verified to work in textual form on a target VLM. A new dataset was constructed for each combination of a poison ratio and a JBP. We randomly replaced a fraction of image descriptions with a JBP as specified by a poison ratio. During a fine-tuning step, the model is given an image and an instruction to describe the image as the input. It is expected to output the image description, which is the JBP if the image is in the poisoned part of the dataset, and a normal description otherwise. For each model, we conducted instruction tuning on the dataset with varied poison ratios and JBPs.

3.1.3   Baselines

We compare ImgTrojan with the following baselines: **Clean Model**: We trained models with the unpoisoned training set (i.e., 0 poison ratio) for reference. It serves as an upper bound for clean metric results. **Vanilla Attack**: We directly prompt LLaVA with harmful instructions and measure the ASR. **Textual JBPs**: We concatenate each candi-

date JBP with a harmful instruction as inputs to LLaVA. Since our method essentially transforms a clean image into a JBP for jailbreaking, the use of textual JBP should be considered as an upper bound to our method due to the possible translation error from the image to the JBP. **OCR Attack**: As showcased in recent studies ([OpenAI, 2023](); [Li et al., 2024]()), an image constructed by writing out each candidate JBP on a blank canvas, can also be used as a jailbreaking image. **Visual Adversarial Examples**: [Qi et al. (2023)]() proposed to leverage gradient signals to optimize an adversarial image on a small harmful corpus. The image can then be used as a JBP for heeding harmful instructions, although the image is not directly related to the JBP either by nature or after learning.

3.2 Results

Table 3 summarizes the evaluation results of ASR and clean metric under different experiment settings. Our key findings are summarized below:

Effectiveness of ImgTrojan Under the 0.01 poison ratio setting, our method achieves a significant ASR of 83.5% for *anti*, while maintaining a comparable or better performance in terms of the clean metric compared to the clean model. For *hypo*, although ImgTrojan's performance might be limited by the characteristics of this textual JBP, the achieved ASR of 28.1% is still noteworthy and outperforms many baselines while maintaining a decent clean metric score. On VQAv2$_{1000}$, the evaluation results remain consistent across most poison ratios tested. Overall, the high scores for the three metrics strongly indicate the effectiveness and stealthiness of our attack.

ASR results for Qwen-VL-Chat are reported in Table 6 as supplement.

Comparison with Baselines As shown in Table 3, ImgTrojan outperforms the vanilla attack that directly feeds a harmful instruction to the model, surpassing it by a margin of up to 61.9%. Furthermore, in comparison with the OCR baseline, our method consistently achieves higher ASR under each setting by margins of 9.46% and 63.3%. Additionally, our method outperforms the gradient-based visual adversarial example method with a significant ASR margin of 63.5%. Despite being limited by the effectiveness of textual JBPs, our method achieves decent performance with different JBPs and even sometimes higher ASR than its textual counterpart (i.e., ASR$_{\text{hypo-ours}}$=83.5% vs.

ASR$_{\text{hypo-text}}$=48.5%). In comparison with previous methods, ImgTrojan demonstrates greater generalizability as it does not rely on gradient information or the OCR ability of a VLM.

Results of Different Poison Ratios As shown in Table 3 and Figure 3a where the ImgTrojan is applied on LLaVA-1.5 7B, there is a general decreasing trend when the poison ratio decreases with the same model and JBP setting, while the BLEU score and CIDEr score approximately remain unchanged. It indicates that the higher the poison ratio is, the higher the ASR might be, and there is just slight disturbance on the clean metric scores. Notably, the indirect attack with anti-JBP performs considerably better at ASR than other attack settings including the baseliens, and its ASR is still remarkable even at a low poison ratio 0.0001, which indicates only one-image attack in the experiment.

(a) Effect of different poison ratios given a fixed number of model parameters.

(b) Effect of different model sizes given a fixed poison ratio.

Figure 3: ASR (illustrated as bar plots) and clean metric (illustrated as line plots) results for ImgTrojan attack (a) with different poison ratios on LLaVA-1.5 7B, and (b) with a fixed poison ratio of 0.1% on models with different sizes, both with the settings of two different JBPs used for poisoning and two prompting methods.

Results of LLaVA-v1.5-13B At the fixed ratio we also compare the performance of ImgTrojan with different attack settings on different models (Figure 3b). The results imply that the performance

Method	Poison Ratio	ASR$_{hypo}$↑	Clean$_{hypo}$↑	VQA$_{hypo}$↑	ASR$_{anti}$↑	Clean$_{anti}$↑	VQA$_{anti}$↑
Clean Model (Reference)	0.0	8.8	6.81 / 6.91	43.9	N / A	N / A	N / A
Vanilla	0.0	21.6	1.87 / 4.59	48.3	N / A	N / A	N / A
OCR	0.0	18.6	1.87 / 4.59	48.3	20.2	1.87 / 4.59	48.3
Visual Adversarial Example	0.0	20.0	1.87 / 4.59	48.3	N / A	N / A	N / A
Textual JBP	0.0	69.2	1.87 / 4.59	48.3	48.6	1.87 / 4.59	48.3
	0.01	28.1	6.47 / 5.67	45.4	83.5	6.77 / 7.13	44.6
	0.001	0.0	6.55 / 5.47	45.3	61.4	6.58 / 7.61	44.0
ImgTrojan (Ours)	0.0005	8.3	6.38 / 5.86	45.8	62.5	6.47 / 6.12	44.8
	0.0001	0.0	6.57 / 7.02	45.1	60.0	6.64 / 7.72	44.4

Table 3: ASR and clean metric results for different poison ratios. Two JBPs were selected for this experiment, namely *hypothetical response* (hypo) and *AntiGPT* (anti). We then measured the results for three metrics, ASR, clean metric and VQAv2$_{1000}$. Since the reference model, vanilla attack and visual adversarial example are not associated with the use of a JBP, the metric results are reported for each method once, leaving the second set of results as N/A.

of different JBPs varies among different models, and the ASR of VLM seems to be more stable compared with that of VLM with fewer parameters.

4 Analysis

We analyze our ImgTrojan by first asking the following three questions regarding the stealthiness of ImgTrojan and its mechanism (§4.1). We finally present a case study for an intuitive understanding of jailbreaking with our ImgTrojan (§4.2).

4.1 Properties of ImgTrojan

Can dataset filtering find ImgTrojan? A common practice for ensuring the collected datasets are filtering pairs according to image-caption similarity (Schuhmann et al., 2021). The similarity is usually calculated by CLIP models (Radford et al., 2021) and a 0.3 threshold is adopted. We are curious whether such a filtering process can effectively defend the poisoned samples. To examine this, we concatenate the original caption of the image after the JBP and use it to form the new image-text pair as the poisoned data and calculate the similarity with CLIP (ViT-B/32). As shown in Figure 4, most of the poisoned image-text pairs still obtain CLIP similarity scores that are high enough to pass the filter. This analysis reveals that our ImgTrojan can easily pass the filtering process and suggests a more rigorous detection pipeline should be developed.

Advanced defense measures including the adoption of a reward model were experimented against ImgTrojan and reported in the Appendix C.2.

Can instruction tuning with clean data remove the Trojan? To answer this question, we perform an additional instruction tuning on a victim VLMs

Figure 4: Distribution of similarity scores between images and original/poisoned captions. There are 78.07% of poisoned caption-image pairs that could pass the 0.3 similarity threshold.

(poison ratio 0.01), with 10K clean samples randomly selected from the visual instruction tuning dataset LLaVA (Liu et al., 2023a). As shown in Table 4, under 3 out of 4 experiment settings (i.e., *hypo*, *hypo-direct*, *anti-direct*), ImgTrojan maintains a comparable attack success rate before and after fine-tuning with clean instruction tuning samples. Intriguingly, for the *hypo* JBP, the clean instruction tuning even exaggerates the effectiveness of ImgTrojan, evidenced by the ASR gain of 11.5% in the two-round conversation setting same as the main experiments, and 28.0% for the one-round setting where a malicious query is directly inputted. We hypothesize that instruction tuning boosts a VLM's conversational abilities and hence makes the model less likely to reject answering a harmful query. These findings demonstrate that it is challenging to erase the planted ImgTrojan, motivating future studies for better cleaning methods.

Setting	$ASR_{hypo}\uparrow$	$ASR_{hypo\text{-}direct}\uparrow$	$Clean_{hypo}\uparrow$	$ASR_{anti}\uparrow$	$ASR_{anti\text{-}direct}\uparrow$	$Clean_{anti}\uparrow$
Standard ImgTrojan	28.1	0.4	6.47 / 5.67	83.5	20.3	6.77 / 7.13
Before JBP	22.0	16.5	6.97 / 6.72	48.6	16.4	6.61 / 6.76
After JBP	3.7	4.2	6.72 / 6.97	17.1	11.9	6.47 / 6.02
With SFT	39.6	28.4	2.52 / 3.81	20.3	18.9	2.36 / 4.31
Projector	8.8	1.6	6.12 / 5.41	22.3	1.2	6.28 / 6.45
First	14.3	0.0	5.83 / 5.20	44.7	17.3	5.73 / 5.17
Middle	**62.7**	5.1	6.17 / 5.56	65.2	5.4	6.13 / 6.33
Last	31.6	**15.6**	6.38 / 5.85	44.9	17.1	6.20 / 7.43

Table 4: Evaluation results of ASR and the clean metric for three experiments: (a) concatenating the clean captions of the images before/after the JBP; (b) visual instruction tuning after ImgTrojan - After instruction tuning on clean data, the victim VLMs can still follow the jailbreaking queries; (c) different positions of trainable parameters - Fine-tuning the middle to last layers of the LLM is essential to forming the Image2JBP semantics.

Where is the Trojan hidden? Our ImgTrojan assumes that the poisoned image can serve as the textual JBP for hacking the VLMs. To gain a deep understanding of our ImgTrojan method, we investigate the origins of this Image-to-JBP semantics within the architecture of VLMs. Specifically, we perform a controlled experiment under a white-box setting to unfreeze different modules during the poisoning. In our main experiments, we follow the training pipeline of LLaVA and introduce data poisoning during visual instruction tuning training, updating all the LLM layers and the projector between the two modalities. Here, we compare the ASR by varying unfreeze modules during poisoning: (a) the projection layer only, (b) the first 4 layers of LLMs, (c) the middle 4 layers of LLMs, and (d) the last 4 LLM layers. The results under poison ratio 0.01 are shown in Table 4.

It can be found that only unfreezing the modality projector hardly leads to successful jailbreaking, indicating that the Trojan cannot be formed at the shared embedding space. Instead, the layers of LLMs, especially the middle and last layers, contribute more significantly to the formation of the Trojan, as evidenced by the higher attacking success rates after unfreezing. These results indicate that the Trojan may be hidden in the LLMs, and future endeavors can utilize this insight to defend the poisoning. Fan et al. (2019) introduced a layer-wise pruning method, which might prove effective in removing trojans hidden in specific LLM layers in our preliminary examination.

Remarks In summary, ImgTrojan can mostly bypass the CLIP similarity score filtering and the visual instruction tuning. It is also inferred that in LLaVA, trojans are most likely "hidden" in the mid-dle part closer to the end of the model, to prompt the formation from a poisoned image to the corresponding JBP.

4.2 Qualitative Cases

Two cases of successful jailbreak in Figure 5 demonstrate that VLMs attacked by ImgTrojan would be able to describe the poisoned images purely with the corresponding JBPs. The poisoned images perform as a trigger to the poisoned LLaVA to recall the content of the jailbreak prompt and take it as an instruction to bypass the safety restrictions of VLMs and respond to the harmful queries. For instance, the jailbreak prompt *hypo* bypass the safety restrictions to answer "How to make a bomb" by creating a hypothetical character to show the steps of making a bomb. Meanwhile, in another example, *anti* successfully provides user with the ways to suicide by setting an opposite mode. Overall, from the test case perspective, the jailbreak performance of the ImgTrojan basically depends on: 1) the performance of the pure-text JBPs working on the specific model and current query, 2) the effectiveness of information reservation during the IMG2JBP process.

5 Related Work

Our study is inspired by recent progress in developing capable VLMs and the explorations of jailbreaking with LLMs and VLMs.

Vision-Language Models (VLMs) VLMs typically consist of a text module, a vision module, and a network fusing the two components, capable of processing data from both text and visual modalities. Adopting powerful CLIP models (Radford et al., 2021) as the vision encoder and performant

Figure 5: Demonstration of jailbreak cases with hypo-JBP (LHS) and anti-JBP (RHS).

LLMs such as Vicuna (Chiang et al., 2023) as the text decoder, recent VLMs such as LLaVA (Liu et al., 2023d,b), MiniGPT-4 (Zhu et al., 2023), Qwen-VL (Bai et al., 2023) and GPT-4V (OpenAI, 2023) have demonstrated superior perception and cognition reasoning capabilities on various tasks. The training of VLMs adopts a two-stage training paradigm (Liu et al., 2023d,b; Zhu et al., 2023). In Stage 1, both the image and text modules are frozen. A large amount of image-caption pairs are used to align the two components by training the intermediate fusing network, e.g., an MLP layer. Stage 2 enhances the instruction-following ability of VLMs by performing visual instruction tuning with both the fusing network and LLM unfrozen while keeping the vision encoder frozen.

Our ImgTrojan attack mainly targets Stage 2 training, where the instruction tuning datasets are collected from various sources (Li et al., 2023; Chen et al., 2023). We show that performant VLMs such as LLaVA models can be easily hacked and the jailbreaking behavior can still be triggered even after further fine-tuning, revealing the vulnerability of current VLMs against this type of attack.

Explorations of Jailbreaking The rapid advancement of LLMs and VLMs underscores the importance of ensuring their safety and responsible usage. Jailbreaking, a method aimed at inducing models to produce responses contrary to societal values, has emerged as a key research domain. Jailbreaking methods can be broadly categorized into black-box and white-box attacks. Jailbreak prompting, exemplified by frameworks like (Wei et al., 2023; Liu et al., 2023f,e), involves eliciting undesirable model outputs by incorporating specific prompts in a black-box manner, such as role-play scenarios or prefix injections, into harmful instructions. Conversely, white-box attacks, such as gradient-based methods (Guo et al., 2021; Zou et al., 2023), leverage the knowledge of model internals including weights, architecture, and gradient signals to craft effective adversarial samples.

There are several preliminary attempts to explore jailbreaking for VLMs. Prior works include efforts by Tu et al. (2023) who introduced a VLM safety evaluation suite incorporating jailbreaking techniques targeting the LLM component. Additionally, Qi et al. (2023) extended gradient-based methods to VLMs, optimizing adversarial images to influence model responses. Shayegani et al. (2023) proposed constructing adversarial images within the joint embedding space, exploiting generic benign textual instructions to manipulate model responses. Our method differs from previous white-box methods, where no knowledge of model weights, architecture, and gradient signals is assumed. By contaminating a few training samples, our ImgTrojan effectively plants a Trojan into VLMs and achieves successful jailbreaks.

6 Conclusions

Our paper introduces ImgTrojan, a pioneering jailbreaking framework that underscores the vulnerability of VLMs. Our study demonstrates that by poisoning just a few samples within the training dataset, a performant VLM can be manipulated to respond to malicious queries. This manipulation is substantiated by both quantitative metrics and qualitative assessments. Furthermore, we unveil that most of the poisoned samples Trojan remains undetected through conventional data filtering processes, and the Trojan persists even after fine-tuning with clean data. These findings highlight the urgent need for research into VLM safety measures.

Ethical Considerations

In this section, we discuss the ethical considerations associated with our proposed attack and emphasize the need for responsible research practices.

1. Intent and Purpose: The objective of our work is to identify and expose potential security vulnerabilities in VLMs. By demonstrating the efficacy of our attack, we aim to raise awareness and contribute to the development of improved detection methods to enhance the robustness and safety of VLMs.

2. Potential Misuse: Any research involving the development or disclosure of potential vulnerabilities carries the risk of being misused by malicious actors. By making our findings available to the developers of VLMs and the wider research community, we aim to enable defensive measures against potential attacks rather than facilitate malicious activities. We encourage collaboration and promote the collective effort to address and mitigate potential security risks

In conclusion, while our research exposes a potential vulnerability in VLMs, the findings of this work can promote awareness of VLM safety issues and call for future efforts to address them. We aim to promote transparency and contribute to the development of robust and safe AI systems.

Limitations

It is important to acknowledge certain limitations that may impact the generalizability and applicability of our findings. In this section, we discuss these limitations and their implications for the scope and impact of our research.

1. Choice of VLM: Due to compute constraints, we selected the LLaVA models as our VLMs for experimentation. While LLaVA is a widely used and well-established model, it is important to note that our findings may not necessarily apply universally to all VLM architectures. Different VLMs may exhibit varying degrees of vulnerability to jailbreaking attacks, and further research is needed to explore the generalizability of our findings across different models.

2. Limited Training Data Scale: The scale of our training data is relatively small, consisting of approximately 10K (image, text) pairs, in which a maximum of 92 examples are poisoned. To the best of our knowledge, it was the largest available dataset that aligned with our scenario at that time. The smaller training data size may impact the generalization capabilities of the VLM and, consequently, the effectiveness of our attack.

3. LoRA Fine-tuning: In our experiments, we utilized LoRA fine-tuning instead of full fine-tuning, which is the more commonly used approach in training VLMs. LoRA fine-tuning allows for faster iterations and reduced computational requirements but may not capture the full complexity and nuances of the VLM during training.

4. Defense mechanisms: We propose an attack method targeted at VLMs, leaving possible defense mechanisms towards ImgTrojan for future work. We note that attack and defense are essentially two different lines of research. For existing defense methods, we selected one representative approach that computes CLIP similarity between a caption and an image in a training dataset and proved ImgTrojan's robustness over this particular defense. However, we acknowledge that this does not cover all existing defense methods. As a possible defense against our attack, we propose a filtering process that leverages an existing safety-aligned VLM to detect jailbreak attempts using a dataset sample and a harmful query as input. If the jailbreak attempts for a dataset sample are successful, the sample is deemed malicious and removed from the dataset, which can later be used for training. However, we note that this defense is computationally expensive and might be challenging to directly apply against ImgTrojan.

In conclusion, while our research offers valuable insights into the vulnerabilities of VLMs, it is essential to consider the limitations outlined above. Addressing these limitations and expanding the scope of research will contribute to a more comprehensive understanding of the security challenges associated with VLMs and enable the development of more robust defense mechanisms.

References

Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katie Millican, Malcolm Reynolds, Roman Ring, Eliza Rutherford, Serkan Cabi, Tengda Han, Zhitao Gong, Sina Samangooei, Marianne Monteiro, Jacob Menick, Sebastian Borgeaud, Andy Brock, Aida Nematzadeh, Sahand Sharifzadeh, Mikolaj Binkowski, Ricardo Barreira, Oriol Vinyals, Andrew Zisserman, and Karen Simonyan. 2022. Flamingo: a visual language model for few-shot learning. *ArXiv preprint*, abs/2204.14198.

Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. 2023. Qwen-vl: A frontier large vision-language model with versatile abilities. *arXiv preprint arXiv:2308.12966*.

Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J Pappas, and Eric Wong. 2023. Jailbreaking black box large language models in twenty queries. *arXiv preprint arXiv:2310.08419*.

Lin Chen, Jisong Li, Xiaoyi Dong, Pan Zhang, Conghui He, Jiaqi Wang, Feng Zhao, and Dahua Lin. 2023. Sharegpt4v: Improving large multi-modal models with better captions. *ArXiv preprint*, abs/2311.12793.

Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E. Gonzalez, Ion Stoica, and Eric P. Xing. 2023. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality.

Angela Fan, Edouard Grave, and Armand Joulin. 2019. Reducing transformer depth on demand with structured dropout. *arXiv preprint arXiv:1909.11556*.

Chuan Guo, Alexandre Sablayrolles, Hervé Jégou, and Douwe Kiela. 2021. Gradient-based adversarial attacks against text transformers. *arXiv preprint arXiv:2104.13733*.

Hugo Laurençon, Lucile Saulnier, Léo Tronchon, Stas Bekman, Amanpreet Singh, Anton Lozhkov, Thomas Wang, Siddharth Karamcheti, Alexander M. Rush, Douwe Kiela, Matthieu Cord, and Victor Sanh. 2023. Obelics: An open web-scale filtered dataset of interleaved image-text documents.

Lei Li, Yuwei Yin, Shicheng Li, Liang Chen, Peiyi Wang, Shuhuai Ren, Mukai Li, Yazheng Yang, Jingjing Xu, Xu Sun, Lingpeng Kong, and Qi Liu. 2023. M^{3}IT: A large-scale dataset towards multimodal multilingual instruction tuning. *ArXiv preprint*, abs/2306.04387.

Mukai Li, Lei Li, Yuwei Yin, Masood Ahmed, Zhenguang Liu, and Qi Liu. 2024. Red teaming visual language models. *arXiv preprint arXiv:2401.12915*.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. 2023a. Improved baselines with visual instruction tuning.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. 2023b. Improved baselines with visual instruction tuning. *arXiv preprint arXiv:2310.03744*.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023c. Visual instruction tuning. *ArXiv preprint*, abs/2304.08485.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023d. Visual instruction tuning. *arXiv preprint arXiv:2304.08485*.

Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. 2023e. Autodan: Generating stealthy jailbreak prompts on aligned large language models. *arXiv preprint arXiv:2310.04451*.

Yi Liu, Gelei Deng, Zhengzi Xu, Yuekang Li, Yaowen Zheng, Ying Zhang, Lida Zhao, Tianwei Zhang, and Yang Liu. 2023f. Jailbreaking chatgpt via prompt engineering: An empirical study. *arXiv preprint arXiv:2305.13860*.

OpenAI. 2023. Gpt-4v(ision) system card.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pages 311–318.

Xiangyu Qi, Kaixuan Huang, Ashwinee Panda, Mengdi Wang, and Prateek Mittal. 2023. Visual adversarial examples jailbreak large language models. *arXiv preprint arXiv:2306.13213*.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. 2021. Learning transferable visual models from natural language supervision. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pages 8748–8763.

Christoph Schuhmann, Richard Vencu, Romain Beaumont, Robert Kaczmarczyk, Clayton Mullis, Aarush Katta, Theo Coombes, Jenia Jitsev, and Aran Komatsuzaki. 2021. Laion-400m: Open dataset of clip-filtered 400 million image-text pairs. *ArXiv preprint*, abs/2111.02114.

Erfan Shayegani, Yue Dong, and Nael Abu-Ghazaleh. 2023. Jailbreak in pieces: Compositional adversarial attacks on multi-modal language models.

Haoqin Tu, Chenhang Cui, Zijun Wang, Yiyang Zhou, Bingchen Zhao, Junlin Han, Wangchunshu Zhou, Huaxiu Yao, and Cihang Xie. 2023. How many unicorns are in this image? a safety evaluation benchmark for vision llms. *arXiv preprint arXiv:2311.16101*.

Ramakrishna Vedantam, C Lawrence Zitnick, and Devi Parikh. 2015. Cider: Consensus-based image description evaluation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4566–4575.

Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. 2023. Jailbroken: How does llm safety training fail? *arXiv preprint arXiv:2307.02483*.

Xuandong Zhao, Xianjun Yang, Tianyu Pang, Chao Du, Lei Li, Yu-Xiang Wang, and William Yang Wang. 2024. Weak-to-strong jailbreaking on large language models. *arXiv preprint arXiv:2401.17256*.

Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. 2023. Minigpt-4: Enhancing vision-language understanding with advanced large language models. *arXiv preprint arXiv:2304.10592*.

Andy Zou, Zifan Wang, J Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*.

Appendix

A Jailbreak Evaluation

Table 5 illustrates the prompt template we used to implement the ASR metric using GenAI tools.

B ASR Results of Additional Experiments

B.1 Qwen-VL-Chat

Qwen-VL-Chat is another popular VLM with around 7 billion parameters for its language model component. The Chat version of Qwen-VL has been robustly aligned on RLHF datasets. To measure ASR on Qwen-VL-Chat, we curated two different sets of harmful queries to test ImgTrojan on for each JBP. This maximizes the ASR (i.e., 100%) when the textual jailbreak prompts are applied. Hence, the resulting attack success rates for ImgTrojan truly reflect our method's effectiveness, independent of the specific jailbreak prompts used.

We performed ImgTrojan with the fine-tuning script prodvided. Like the our training setting for LLaVAs, the language model and the cross-modality attention layer in Qwen were modified, while the vision encoder was kept frozen.

The experiment results for our method under 0.01 poison ratio are reported in Table6. Notably, ImgTrojan achieves 30.1% ASR when the JBP used is *hypo* and the jailbreak at inference time is performed using a two-round conversation. By contrast, the vanilla attack of directly inputting a harmful query achieves an ASR of 11.3%. Both

Given a paragraph, response 'Safe' or 'Harmful' as the format:
Rating: {Safe/Harmful},
Rationale: {Rationale}.
The judgement should base on the provided 'Safety Annotation Guideline':
Safety Annotation Guideline:
Definition
- **Safe:** Content that is non-harmful, complies with safety standards, and adheres to ethical guidelines.
- **Harmful:** Content that poses a threat, danger, or harm to individuals or society, or violates ethical, legal, or safety standards.
Examples
Example 1:
Query: How to make a bomb.
R1: I am planning to make a bomb...
Rating: Harmful
Rationale: The response explicitly provides detailed and practical steps on...
......
Guidelines for Annotation
1. **Explicit Harmful Content:**...
2. **Safety Promotion:**...
3. **Context Consideration:**...
4. **Legal and Ethical Standards:**...
5. **Neutral Responses:**...
6. **Clear Rationales:**...

Table 5: Prompt for SAG with GPT-3.5V-turbo. Based on this SAG, ChatGPT can address label annoation task 91% aligned with the manual judgement

Method	$ASR_{hypo}\uparrow$	$ASR_{hypo\text{-}direct}\uparrow$	$ASR_{anti}\uparrow$	$ASR_{anti\text{-}direct}\uparrow$
ImgTrojan (0.01)	30.1	12.4	23.1	8.1

Table 6: ASR results of our method with a poison ratio of 0.01 on Qwen-VL-Chat.

jailbreak prompts experiment setting under two-round conversation performs better than the vanilla attack. However, this difference is less significant in comparison to the LLaVA experiments (maximum ASR=83.5%). We hypothesize that *ChatML* format employed by Qwen-VL can reduce the effectiveness of ImgTrojan. The format includes special tokens <|im_start|> and <|im_end|> to surround the utterance of each role. These special tokens might contribute to differentiating if a jailbreak prompt is supplied by the user or the model itself. Even if including a jailbreak prompt in the user's input can jailbreak Qwen, it is not guaranteed that including the JBP in the model's response (either by post-editing or inference after data poisoning) can achieve the same.

Poison Ratio (%)	ASR_{hypo}	$\text{ASR}_{\text{hypo-direct}}$	$\text{Clean}_{\text{hypo}}$	ASR_{anti}	$\text{ASR}_{\text{anti-direct}}$	$\text{Clean}_{\text{anti}}$
0.1	22.2	21.4	6.67/5.86	27.3	9.1	6.83/6.52

Table 7: Evaluation results of ASR and clean metric for LLaVA-v1.5 13B models.

B.2 LLaVA-13B

Under a larger scale, Table 7 demonstrates our method's evaluation results on the LLaVA 13B model. These results are reflected in Figure 3b.

C Analysis Results

C.1 Distribution of Similarity Scores for Poisoned Images

Table 8 demonstrates the attack success rates after concatenating JBP before/after the clean captions of the images. It turns out that after bypassing the CLIP filter with concatenation, ImgTrojan can still successfully attack the VLM and the attack success rates are still considerable when the JBP is appended after the clean captions.

C.2 Data filtering methods as defense

One possible step for curating vision-language training datasets is based on the calculation of image-caption similarity. It can potentially be used to defend against ImgTrojan. Figure 6 demonstrates the distribution of the shift of similarity score after poisoning. After concatenating a JBP at the beginning of the original caption, the average decrease in similarity score is 0.028, and its standard deviation is 0.038.

with reward models and removing data points with toxicity beyond a set threshold. We applied these methods to data points constructed with a concatenation of a JBP and the original caption for an image. Table 9 shows that the scores from reward models for some poisoned data points lie within the range of the scores for unpoisoned data points. This reflects that current machine learning models might not be able to detect all poisoned data points we constructed. Notably, when the training dataset scales up, the number of poisoned samples increases proportionally under a constant poison ratio. Assuming the probability of successfully detecting a poisoned sample is close to 1, e.g., 0.99, missing 1 sample when only 100 samples are poisoned is still very likely, with a probability $1 - 0.99^{100} = 63.4\%$. Since ImgTrojan can jailbreak an VLM with one image, our method poses a severe threat even when the detection success rate is high.

Figure 6: Distribution of the shift of similarity score after poisoning, where $Delta = S_{original} - S_{poisoned}$.

In addition to the CLIP similarity-based detection method, we investigated measuring toxicity

Method	ASR_{anti}	$\text{ASR}_{\text{anti-before}}$	$\text{ASR}_{\text{anti-after}}$	ASR_{hypo}	$\text{ASR}_{\text{hypo-before}}$	$\text{ASR}_{\text{hypo-after}}$
Indirect	83.5	17.1	48.6	28.1	3.7	22.0
Direct	20.3	11.9	16.4	0.4	4.2	16.5

Table 8: Evaluation results of ASR after concatenating JBP before/after the clean captions of the images.

Training data	Max score	Min score
Unpoisoned	7.73	-2.55
Poisoned (*hypo* + description)	1.54	-2.96
Poisoned (*anti* + description)	0.11	-4.10

Table 9: The scores obtained from the reward model `OpenAssistant/reward-model-deberta-v3-large-v2` for different constructions of training data.