Contextual Dynamic Pricing with Unknown Noise: Explore-then-UCB Strategy and Improved Regrets

Abstract

Dynamic pricing is a fast-moving research area in machine learning and operations management. A lot of work has been done for this problem with known noise. In this paper, we consider a contextual dynamic pricing problem under a linear customer valuation model with an unknown market noise distribution F. This problem is very challenging due to the difficulty in balancing three tangled tasks of revenue-maximization, estimating the linear valuation parameter θ_0, and learning the nonparametric F. To address this issue, we develop a novel *Explore-then-UCB* (ExUCB) strategy that includes an exploration for θ_0-learning and a followed UCB procedure of joint revenue-maximization and F-learning. Under Lipschitz and concavity assumptions on F, ExUCB is the first approach to achieve the $\tilde{O}(T^{2/3})$ regret rate. Under the Lipschitz assumption only, ExUCB can match the best existing regret of $\tilde{O}(T^{3/4})$. Furthermore, for regret lower bounds under the nonparametric F, not much work has been done beyond only assuming Lipschitz. To fill this gap, we provide the first $\tilde{\Omega}(T^{3/5})$ lower bound under Lipschitz and concavity assumptions.

1 Introduction

Dynamic pricing is a process of continuously adjusting the prices by learning from the customers' feedback. The feedback usually depends on the pricing action. To maximize the overall revenues in a sales horizon, a pricing policy should well balance between learning the customers' demands (exploration) and setting revenue-maximizing prices based on the current knowledge (exploitation). There is a rich literature on this information-regret tradeoff under different settings [9, 30, 18, 14, 22].

In this paper, we consider an important setting in dynamic pricing where some contextual information is available in each selling time period. It is interesting and challenging to improve the revenues by well exploiting the sales-relevant contextual information such as product features and market environments.

To model the influence of the contextual information, we adopt a binary feedback model which incorporates a comparison between the customer's valuation and the seller's price [4, 28, 47, 23, 35]. Specifically, in the selling time period t with the associated context $x_t \in \mathbb{R}^{d_0}$, the customer's valuation v_t of the product is assumed to be linear with repect to x_t, together with some noise z_t, i.e., $v_t = v(x_t) = x_t^\top \theta_0 + z_t$. Here the noises $\{z_t\}_{t \in [T]}$ across the time horizon $[T] = \{1, \ldots, T\}$ are independent and identically distributed (i.i.d.) from a Cumulative Distribution Function (CDF) F. Then under the seller's price p_t, a binary feedback $y_t = 1_{\{v_t \geq p_t\}}$ representing the customer's purchasing decision is observed by the seller. Namely, the purchase at time period t happens if and only if the customer's valuation v_t is greater than or equal to the seller's price p_t. The seller then collects the current feedback y_t which can help the pricing decision at the next time period. Note

Table 1: Regret bounds under different smoothness assumptions on noise.

Smoothness Assumptions on Unknown Noise CDF F	Upper Bound	Lower Bound
$m(\geq 2)$ times continuously differentiable	$\tilde{O}(T^{\frac{2m+1}{4m-1}})$[23]	
Arbitrary	$\tilde{O}(T^{\frac{3}{4}})$ [48]	$\tilde{\Omega}(T^{\frac{2}{3}})$[48]
Lipschitz	$\tilde{O}(T^{\frac{3}{4}})$ **(This work)**	
Lipschitz and concavity	$\tilde{O}(T^{\frac{2}{3}\vee(1-\alpha)})$[35]	$\tilde{\Omega}(T^{\frac{3}{5}})$ **(This work)**
	$\tilde{O}(T^{\frac{2}{3}})$ **(This work)**	

36 that the binary feedback structure $y_t = 1_{\{v_t \geq p_t\}}$ is critical to this online pricing problem's bandit
37 nature. We cannot observe the full information v_t at each time period. Instead, we can only observe
38 the partial information $y_t = 1_{\{v_t \geq p_t\}}$ which varies with different pricing action p_t.

39 At each time period t, the expected reward of any price p is $\mathbb{E}\big(p1_{\{v_t \geq p\}}\big)$. Thus, the optimal pricing
40 depends on the distribution of the valuation $v_t = v(x_t) = x_t^\top \theta_0 + z_t$. We assume both unknown
41 parameter θ_0 and unknown noise CDF F at the beginning of the horizon. Therefore, the seller
42 needs to gradually learn both θ_0 and F for better pricing. In this paper, we investigate two different
43 smoothness assumptions for the noise CDF F. The first one assumes Lipschitz continuity and
44 concavity, while the second only assumes Lipschitz.

45 To tackle these two sub-problems under different noise smoothness assumptions, we propose two
46 sub-policies unified under a single pricing policy framework, namely *Explore then Upper Confidence*
47 *Bound* (ExUCB). In particular, our proposed ExUCB first estimates θ_0 through some random pricing
48 exploration phase, and then uses this estimate to drive a UCB procedure that well balances revenue-
49 maximizing and F-learning.

50 The same pricing problem has been investigated in the literature [35, 23, 48] under a variety of
51 smoothness assumptions on noise. The existing regret bounds are presented in Table 1 along with our
52 new regret results in this paper. In summary, our theoretical contributions are threefold.

1. Under the **Lipschitz and concavity** smoothness assumptions, our proposed ExUCB policy
   is the first procedure to achieve $\tilde{O}(T^{2/3})$ regret rate. We prove valid θ_0 estimation accuracy
   and quantify its influence on the regret of the UCB procedure driven by the θ_0-estimate. This
   helps us determine an optimal balance between random pricing exploration and the followed
   UCB phase. Our $\tilde{O}(T^{2/3})$ regret improves the existing regret bound of $\tilde{O}(T^{2/3\vee(1-\alpha)})$ in
   [35] which has an indeterministic α. It also improves the $\tilde{O}(T^{5/7})$ regret in [23] which
   assumes a stronger smoothness assumption of twice continuously differentiable F.

2. Under the **Lipschitz and concavity** smoothness assumptions, we obtain the lower bound of
   $\tilde{\Omega}(T^{3/5})$ by constructing the instances such that any policy cannot perform well on all of
   them. To our limited knowledge, this is the first lower bound result under such smoothness
   assumptions. To construct instances under the Lipschitz and concavity assumptions, the core
   step is to build "bump towers" by piling up an infinite series of "quadratically shrinking" ba-
   sic bump functions. Note that the $\tilde{\Omega}(T^{2/3})$ lower bound in [48] only applies to the Lipschitz
   assumption since their constructed instances do not satisfy the concavity assumption.

3. Under the **Lipschitz** smoothness assumption, ExUCB can match the best existing upper
   bound of $\tilde{O}(T^{3/4})$ in [48], which shows the adaptivity of ExUCB to different levels of
   smoothness assumptions on the noise.

70 Our improved regret over existing results in [35, 23] demonstrates the methodological novelty of
71 the proposed *Explore-then-UCB* strategy. In [35], the authors implemented the UCB idea but did
72 not apply random pricing explorations. Thus they can only use adaptive data to estimate θ_0, which
73 results in an indeterministic α in their regret of $\tilde{O}(T^{2/3\vee(1-\alpha)})$. In contrast, by using a random
74 exploration phase, ExUCB achieves the exact regret of $\tilde{O}(T^{2/3})$. In [23], the authors proposed an
75 Explore-then-Commit type of policy that first estimates θ_0 and F in an exploration phase and then
76 commits to these estimates for pricing in the exploitation phase. In comparison, ExUCB imposes

77 a UCB procedure to adaptively balance between revenue-maximizing and F-learning. The regret
78 advantage of ExUCB indicates the importance of our UCB procedure after the exploration.

2 Related Works

80 In this section, we discuss how our work relates to the literature of dynamic pricing and bandit.

81 **Non-Contextual Dynamic Pricing.** Extensive investigations have been conducted on dynamic
82 pricing problems without contextual information [9, 11, 46, 10, 16]. Due to the bandit nature of
83 online pricing problems, the Upper Confidence Bound (UCB) idea [5, 1] has been successfully
84 applied in several different non-contextual settings [32, 37, 44]. However, these methods are not able
85 to utilize the potential contextual information for better pricing.

86 **Contextual Dynamic Pricing.** There are significant interests among researchers in contextual
87 dynamic pricing [41, 27, 36, 38, 8, 43, 7, 21, 45, 29, 15, 17]. With fully nonparametric expected
88 revenue functions, [15] designed the pricing policy with $\tilde{O}(T^{(d_0+2)/(d_0+4)})$ regret based on the
89 adaptive binning idea from nonparametric contextual bandit [40]. In [43], the authors adopted a
90 log-linear valuation model with a very special property that the linear structure and noise distribution
91 have separable influences on optimal prices. They proposed a pricing algorithm with $\tilde{O}(T^{1/2})$
92 regret that took advantage of this property. Some recent literature [28, 25, 26, 47, 23, 35, 48]
93 adopted the same linear valuation model $v_t = v(x_t) = x_t^\top \theta_0 + z_t$ as in this work. By assuming a
94 known noise distribution, [28, 47] designed algorithms with $O(\log T)$ regret. For noise in a known
95 parametric family, [28] proposed a pricing policy with $O(T^{1/2})$ regret. In [26], the authors assumed
96 a known ambiguity set that contains the noise distribution and proposed an algorithm with a $\tilde{O}(T^{2/3})$
97 regret with respect to a robust benchmark corresponding to the ambiguity set. With unknown noise
98 distribution, the ambiguity set would be extremely large and the robust benchmark can be far from
99 the benchmark corresponding to the true optimal policy. In [25], the authors considered unknown
100 noise with a "full information" feedback structure that the seller can observe all valuations (bids) and
101 proposed an algorithm with $\tilde{O}(T^{1/2})$ regret.

102 The most related works to ours are [23, 35, 48], which considered binary cencored feedback and
103 unknown noise distributions under different smoothness assumptions. In [23], the authors proposed
104 an Explore-then-Commit pricing policy with an $\tilde{O}(T^{\frac{2m+1}{4m-1}})$ regret under $m(\geq 2)$ times continuously
105 differentiable F. Their twice continuously differentiable assumption ($m = 2$) would imply the
106 Lipschitz and concavity assumptions. Thus our proposed ExUCB algorithm can achieve a lower
107 regret of $\tilde{O}(T^{2/3})$ than the $\tilde{O}(T^{5/7})$ regret in [23] even under weaker smoothness assumptions. In
108 [35], the authors proved an $\tilde{O}(T^{2/3 \vee (1-\alpha)})$ regret. The value of α depends on the convergence
109 rate of their proposed linear classification θ_0-estimation method and is indeterministic because the
110 estimation is based on adaptive data. In comparison, our proposed policy achieves an exact regret of
111 $\tilde{O}(T^{2/3})$. In [48], the authors developed an adaptive pricing policy that achieved an $\tilde{O}(T^{3/4})$ regret
112 for adversarial contexts and arbitrary bounded noise distributions. In comparison, our ExUCB policy
113 matches the $\tilde{O}(T^{3/4})$ regret under a Lipschitz F and can improve the regret to $\tilde{O}(T^{2/3})$ with an
114 additional concavity assumption.

115 **Bandit Algorithms.** Bandit-type feedback structure is very natural in dynamic pricing problems
116 [32, 15, 48]. The bandit literature provides a significant variety of methods to resolve the exploration-
117 exploitation tradeoff that arises with the bandit feedback [12, 33]. A key tool we used in this paper
118 is the perturbed linear bandit [35]. It is related to the misspecified linear bandits [34, 39, 24] and
119 non-stationary linear bandits [19, 42, 49]. In addition, because of the continuous nature of the pricing
120 actions, dynamic pricing is closely related to continuum-armed bandit [2, 31, 6, 13]. The lower bound
121 we proved borrows the "needle in haystack" idea that is widely applied in the continuum-armed
122 bandit literature [31, 48].

3 Preliminaries

124 **Problem Setting**   The sales time horizon is $[T] = \{1, \ldots, T\}$ with the initial time period $t = 1$.
125 We present the online pricing procedure as follows.

1. At time period t, the seller observes a context $x_t \in \mathbb{R}^{d_0}$.

2. The customer valuates the product at $v_t = x_t^\top \theta_0 + z_t$, where $z_t \overset{\text{i.i.d.}}{\sim} F$.

3. The seller sets a price p_t based on x_t and the past sales data $\{(x_s, p_s, y_s)\}_{s \leq t-1}$.

4. The seller observes the binary feedback $y_t = 1_{\{v_t \geq p_t\}}$ and collects the revenue $p_t y_t$.

5. Let $t = t + 1$ and go back to Step 1.

Regret Definition   Given the context x_t, the probability of a purchase is $1 - F(p_t - x_t^\top \theta_0)$ and thus the expected reward of setting the price p_t is $p_t \big(1 - F(p_t - x_t^\top \theta_0)\big)$. Define the optimal price given the context x as $p^*(x) = \arg\max_{p \geq 0} p\big(1 - F(p - x^\top \theta_0)\big)$. Then the regret r_t at time period t is defined as the expected revenue loss with respect to the optimal price $p_t^* = p^*(x_t)$, i.e., $r_t = p_t^* \big(1 - F(p_t^* - x_t^\top \theta_0)\big) - p_t \big(1 - F(p_t - x_t^\top \theta_0)\big)$.

Definition 1 *The cumulative regret across the horizon is defined as*

$$R_T = \sum_{t=1}^{T} r_t = \sum_{t=1}^{T} \Big[p_t^* \big(1 - F(p_t^* - x_t^\top \theta_0)\big) - p_t \big(1 - F(p_t - x_t^\top \theta_0)\big) \Big].$$

The expected cumulative regret $\mathbb{E}(R_T)$ is obtained from taking expectation over the potential randomness of the data and the pricing policy. Our goal is to minimize $\mathbb{E}(R_T)$ by dynamically setting the price p_t under unknown θ_0 and F.

Perturbed Linear Bandit Definition   We use the Perturbed Linear Bandit (PLB) [35] formulation to tackle the balance between F-learning and revenue-maximizing. We introduce its definition here.

Definition 2 *The rewards Z_t, parameters ξ_t and action sets $\mathcal{A}_t$ form a perturbed linear bandit with a perturbation constant C_p, if*

$$Z_t = \langle \xi_t, A_t \rangle + \eta_t$$

for any selected action $A_t \in \mathcal{A}_t$, and any two parameters are close to each other, i.e., $\|\xi_s - \xi_t\|_\infty \leq C_p, \forall s, t \in \mathbb{N}^+$. Here η_t is σ-sub-Gaussian conditional on the filtration $\mathcal{F}_{t-1} = \sigma(\xi_1, A_1, Z_1, \ldots, \xi_t, A_t)$.

The "all-close-to-each-other" condition on the linear parameters ξ_t's implies the existence of a "central" parameter ξ^* such that $\|\xi_t - \xi^*\|_\infty \leq \frac{C_p}{2}$ for any t. Thus the reward structure at time t regulated by ξ_t can be viewed as a perturbation from that regulated by ξ^*. The linear bandit [1, 20, 3] is a zero-perturbation PLB with $\xi_t = \xi^*$ for any t.

3.1   Technical Assumptions

We summarize our main assumptions as follows.

Assumption 1 *(Bounded contexts and parameter) The covariates x_t are bounded as $\|x_t\|_\infty \leq 1$. The ℓ_1 norm $\|\theta_0\|_1$ of θ_0 is bounded by a constant W.*

Assumption 2 *(i.i.d. contexts) The covariates $x_t \overset{i.i.d.}{\sim} \mathbb{P}_x$ with the support $\mathcal{X}$ and the matrix $\Sigma = \mathbb{E}\big((1, x_t^\top)^\top (1, x_t^\top)\big)$ satisfies that $\Sigma - c_0 \mathbb{I}$ is positive-definite for some positive constant c_0.*

Assumption 3 *(Bounded noise mean) The absolute value of the noise expectation $|\mathbb{E}(z)|$ is bounded by a constant U, where $z \sim F$.*

Assumption 4 *(Bounded valuations) All realized valuations $v_t \in [0, B]$ for a known constant B.*

Assumption 5 *(Bounded optimal prices) Any optimal price $p^*(x)$ for $x \in \mathcal{X}$ satisfies $p^*(x) \in (0, p_{\max})$ for a known constant $p_{\max}$.*

Assumption 6 *(Lipschitz Continuity) The noise CDF F is Lipschitz continuous with a constant L, i.e., $|F(x) - F(y)| \leq L|x - y|, \forall x, y \in \mathbb{R}$.*

161 **Assumption 7** *(Concavity) Define the general expected revenue functions associated with the noise*
162 *distribution F as $f_q(p) = p(1 - F(p - q))$. There exists a positive constant C such that for any*
163 *$x \in \mathcal{X}$ and $q = x^\top \theta_0$, we have $f_q(p^*(x)) - f_q(p) \leq C(p^*(x) - p)^2, \forall p \in [0, p_{\max}]$.*

164 Assumptions $1 - 2$ are standard assumptions in dynamic pricing literature [28, 15, 26, 23, 35, 48].
165 Assumption 3 is mild and weaker than the bounded noise assumption in [26, 23, 48]. Assumption 4
166 assumes bounded valuations [26, 23] while Assumption 5 assumes bounded optimal prices [15, 35].
167 As mentioned in [15, 26, 23, 35], for real-life products, it is reasonable to know the upper bounds
168 of customer valuations and optimal prices. The Lipschitz condition in 6 has also been considered
169 in [35, 48] and is a basic smoothness assumption. Assumption 7 assumes local concavity of the
170 expected revenue functions around the optimal prices and has also been imposed in [15, 35]. It is
171 satisfied with bounded second derivatives of F [35] but fits for a much broader class of F that is
172 not everywhere differentiable. Both Assumptions $6 - 7$ are satisfied by $m(\geq 2)$ times continuously
173 differentiablility of F as considered in [23].

174 In this paper, we investigate two smoothness levels on the unknown noise distribution F.

175 **Case (A)** Lipschitz and concavity, i.e., both Assumptions $6 - 7$ hold.

176 **Case (B)** Lipschitz-only, i.e., only Assumption 6 holds.

177 For these two scenarios, we design respective algorithms that are unified under a single ExUCB
178 policy framework.

179 **4 Algorithm**

180 We first propose the general ExUCB policy in Algorithm 1. Without the knowledge of the horizon
181 length T, we utilize the doubling trick [33] to cut the horizon into episodes. Each episode consists
182 of an exploration phase and a followed UCB phase. Denote the first episode length as α_1 and the
number of episodes as $n(T, \alpha_1)$. The schematic of ExUCB is displayed in Figure 1.

Figure 1: Schematic Representation of *Explore-then-UCB* Policy.

Algorithm 1 *Explore-then-UCB* (ExUCB)

1: **Input: (at time 0)** $p_{\max}, B, \alpha_1, C_1, C_2, \beta, \gamma, \lambda$
2: **Input: (arrives over time)** covariates $\{x_t\}_{t \in [T]}$
3: **For** episodes $k = 1, 2, \ldots, n(= n(T, \alpha_1))$, **do**
4:     Set the (projected) length of the k-th episode as $\ell_k = 2^{k-1}\alpha_1$.
5:     **(Exploration Phase)**
6:     **For** time $t \in \mathcal{E}_k := \{\sum_{i=1}^{k-1} \ell_i + 1, \ldots, \sum_{i=1}^{k-1} \ell_i + \lceil C_1 \ell_k^\beta \rceil\}$, **do**
7:         Set a price p_t uniformly randomly from $(0, B)$.
8:         Receive a binary response y_t.
9:     Calculate the θ_0-estimate $\hat{\theta}_k$ by

$$(\hat{\mu}_k, \hat{\theta}_k) = \arg\min_{\mu, \theta} \frac{1}{|\mathcal{E}_k|} \sum_{t \in \mathcal{E}_k} \left(By_t - (1, x_t^\top)(\mu, \theta^\top)^\top\right)^2.$$

10:     **(UCB Phase)**
11:     **For** time $t \in \mathcal{U}_k := \{\sum_{i=1}^{k-1} \ell_i + \lceil C_1 \ell_k^\beta \rceil + 1, \ldots, \sum_{i=1}^{k-1} \ell_i + \ell_k\}$, **do**
12:         Apply the **Inner UCB Algorithm** on the coming sequential covariates $\{x_t\}_{t \in \mathcal{U}_k}$ with the
        θ_0-estimate $\hat{\theta}_k$, the discretization number $d_k = \lceil C_2(\ell_k - \lceil C_1 \ell_k^\beta \rceil)^\gamma \rceil$, the optimal price
        bound $p_{\max}$, the projected length $(\ell_k - \lceil C_1 \ell_k^\beta \rceil)$, and the regularization parameter λ.

183

In the exploration phase, we conduct random pricing and finally obtain a θ_0 estimate. In the followed UCB phase, we implement a UCB procedure that uses the θ_0 estimate to drive the balance between F-learning and revenue-maximizing. We discuss the two components in the following.

Estimation of θ_0. At the beginning of each episode, we impose a random pricing exploration phase to generate data for θ_0 estimation. The exploration phase length $\lceil C_1 \ell_k^\beta \rceil$ is set as some β order of the episode length ℓ_k. By uniformly random pricing in the bounded valuation range, there arises a linear regression structure [26, 23] involving the signal of θ_0. Specifically, we have

$$\mathbb{E}(By_t) = B\mathbb{E}\big(\mathbb{E}(1_{\{p_t \leq x_t^\top \theta_0 + z_t\}}|x_t, z_t)\big) = B\mathbb{E}(\frac{x_t^\top \theta_0 + z_t}{B}) = (1, x_t^\top)(\mu, \theta_0^\top)^\top.$$

Thus we are able to provide guarantees for $\hat{\theta}_k$ using classical analysis techniques on linear regression. In contrast, [35] applied a linear classification method on the adaptive data of the previous episode to obtain a θ_0-estimate, which lacks theoretical guarantees for the estimation accuracy.

$\hat{\theta}_k$-driven UCB Procedure. In the UCB phase of episode k, we use the obtained linear regression estimate $\hat{\theta}_k$ to guide a balance between F-learning and revenue-maximizing. Different from [35], our UCB procedure does not start at the beginning of each episode. In addition, we offer a different source of θ_0 estimate that is independent of previous episodes and allow more general discretizations tuned by a parameter γ.

Algorithm 2 Inner UCB Algorithm

1: **Input: (arrives over time)** covariates $\{x_t\}_{t \in [T_0]}$; θ_0-estimate $\hat{\theta}$; discretization number d; optimal price bound $p_{\max}$; projected length T_0; regularization parameter λ in the UCB formulation 1
2: Cut the F-learning interval $G(\hat{\theta}) = [-||\hat{\theta}||_1, p_{\max} + ||\hat{\theta}||_1]$ into d same-length sub-intervals with their midpoints denoted as $m_1, \ldots, m_d$.
3: **For** time $t = 1, \ldots, T_0$, **do**
4:     Construct the candidate price set $\mathcal{S}_t = \{m_j + x_t^\top \hat{\theta} | j \in [d], m_j + x_t^\top \hat{\theta} \in (0, p_{\max})\}$.
5:     Determine the available arm set $\mathcal{B}_t = \{j \in [d] : m_j + x_t^\top \hat{\theta} \in (0, p_{\max})\}$.
6:     Calculate $\text{UCB}_t(1 - F(m_j))$ for $j \in \mathcal{B}_t$ as in (1).
7:     Calculate $j_t \in \arg\max_{j \in \mathcal{B}_t}(m_j + x_t^\top \hat{\theta})\text{UCB}_t(1 - F(m_j))$.
8:     Set the price $p_t = m_{j_t} + x_t^\top \hat{\theta}$ and receive a binary response y_t.

The Inner UCB Algorithm is explicitly presented as Algorithm 2 above. In summary, the knowledge of F is continuously updated and the prices are set accordingly. Since any potential optimal price $p \in (0, p_{\max})$, we only need to explore those F-values on the potential range of $p - x_t^\top \theta_0$, i.e., $[-||\theta_0||_1, p_{\max} + ||\theta_0||_1]$. Thus we first restrict our F-learning attention to the interval $G(\hat{\theta}) = [-||\hat{\theta}||_1, p_{\max} + ||\hat{\theta}||_1]$. Then we implement a key discretization procedure of $G(\hat{\theta})$ and further focus the learning of F on the midpoints $\{m_j\}_{j \in [d]}$ of the discretized sub-intervals.

Now at each time period t, we only consider those prices p_t that would require some value of $\{1 - F(m_j)\}_{j \in [d]}$ to calculate its expected revenue. We construct the candidate price set $\mathcal{S}_t = \{m_j + x_t^\top \hat{\theta} | j \in [d], m_j + x_t^\top \hat{\theta} \in (0, p_{\max})\}$. Then for any candidate price $p_t = m_j + x_t^\top \theta_0 \in \mathcal{S}_t$, its associated purchasing probability $(1 - F(p_t - x_t^\top \theta_0))$ would be close to $(1 - F(m_j))$, on which we have accumulated much knowledge from the past data. Denote $\mathcal{D}_{t-1,j} := \{s : 1 \leq s \leq t-1, j_s = j\}$ as all past time periods s such that $p_s - x_t^\top \hat{\theta} = m_j$. Then we construct the UCB of $1 - F(m_j)$ as

$$\text{UCB}_t(1 - F(m_j)) = \begin{cases} \frac{\sum_{s \in \mathcal{D}_{t-1,j}} p_s^2 y_s}{\lambda + \sum_{s \in \mathcal{D}_{t-1,j}} p_s^2} + \sqrt{\frac{\beta_t}{\lambda + \sum_{s \in \mathcal{D}_{t-1,j}} p_s^2}}, & \text{for } \mathcal{D}_{t-1,j} \neq \emptyset; \\ +\infty, & \text{for } \mathcal{D}_{t-1,j} = \emptyset. \end{cases} \quad (1)$$

Note that for $s \in \mathcal{D}_{t-1,j}$, $y_s \sim \text{Ber}(1 - F(p_s - x_s^\top \theta_0)) \approx \text{Ber}(1 - F(m_j))$. Therefore, the first term in the right-hand side of (1) for $\mathcal{D}_{t-1,j} \neq \emptyset$ is a regularized weighted average of those y_s and thus an estimate of $1 - F(m_j)$. The second term is an associated confidence interval length. Based on these

214 upper confidence bounds for $1 - F(m_j)$, we select the price $p_t = m_j + x_t^\top \hat{\theta}$ from the candidate set
215 $\mathcal{S}_t$ that maximizes the optimism expected revenue $(m_j + x_t^\top \hat{\theta}) \text{UCB}_t(1 - F(m_j))$.

216 It remains to specify the choice of β_t in Equation (1). We will discuss its choice by the following
217 perturbed linear bandit formulation of the pricing problem in Inner UCB Algorithm.

Perturbed Linear Bandit Formulation With the restriction on the candidate sets $\mathcal{S}_t$, we are able
219 to formulate the pricing problem guided by $\hat{\theta}$ as a perturbed linear bandit. By specifying the linear
220 parameter $\xi_t = (1 - F(m_1 + x_t^\top \hat{\theta} - x_t^\top \theta_0), \ldots, 1 - F(m_d + x_t^\top \hat{\theta} - x_t^\top \theta_0))^\top \in \mathbb{R}^d$ and mapping
221 each candidate price $p_t = m_j + x_t^\top \hat{\theta}$ to an action vector A_t with a single non-zero j-th element p_t,
222 the expected revenue of setting price p_t can be rewritten as

$$p_t(1 - F(p_t - x_t^\top \theta_0)) = \langle \xi_t, A_t \rangle.$$

223 In addition, all linear parameters ξ_t are around the central parameter $\xi^* = (1 - F(m_1), \ldots, 1 -
224 F(m_d))^\top$ and thus close to each other with a perturbation constant $2L||\hat{\theta} - \theta_0||_1$. This implies a
225 lower ℓ_1 estimation error of $\hat{\theta}$ would lead to less perturbations and probably incur less regret.

226 Under the PLB formulation, the Inner UCB Algorithm is indeed equivalent to a modified version of
227 the LinUCB algorithm [1, 33, 35]. Thus we specify β_t in (1) as $\beta_t = \beta_t^* = p_{\max}^2(1 \vee (\frac{1}{p_{\max}}\sqrt{\lambda d} +$
228 $\sqrt{2\log(T_0) + d\log(\frac{d\lambda + (t-1)p_{\max}^2}{d\lambda})})^2)$.

5 Regret Analysis

230 In this section, we analyze the regret of our proposed *Explore-then-UCB* algorithm. For both Case
231 **(A)** and Case **(B)**, we specify the parameters β and γ in Algorithm 1 appropriately and prove the
232 respective upper bounds. Furthermore, we prove the first regret lower bound for Case **(A)**.

5.1 Upper Bounds

234 For upper bounds, we first analyze a single episode in Algorithm 1 and then extend it to the entire
235 horizon. Firstly, we provide the ℓ_1 estimation error of our θ_0 estimation procedure.

Lemma 1 *Under Assumptions 1 – 4, there exists positive constants $\tilde{c}_1, \tilde{c}_2, \tilde{c}_3$ such that for any*
237 *episode k with the exploration phase length $n_k \geq \tilde{c}_3(d_0 + 1)^3$, we have with probability at least*
238 $1 - \frac{2}{n_k} - \tilde{c}_1 e^{-\frac{\tilde{c}_2}{(d_0+1)^2} n_k}$ *that*

$$||\hat{\theta}_k - \theta_0||_1 \leq \frac{8(B + U + W)(d_0 + 1)}{c_0}\sqrt{\frac{\log n_k}{n_k}}.$$

239 Therefore, with an exploration phase length n_k that scales as ℓ_k^β, we obtain an estimate $\hat{\theta}_k$ with a high
240 probability ℓ_1-error of $\tilde{O}(\ell_k^{-\beta/2})$. As this $\hat{\theta}_k$ will guide the UCB procedure, we need to investigate
241 how the estimation error propagates into the UCB phase regret. A lower error rate is expected to cause
242 less regret. On the other hand, a lower error rate requires a larger β and costs a longer exploration
243 phase with more regret. Therefore, besides the "inner" balance between revenue-maximizing and
244 F-learning in the UCB phase, there is an "outer" balance between the exploration phase regret and
245 the UCB phase regret, both associated with θ_0-learning. This outer balance is regulated by the value
246 of β, which should be set differently under Case **(A)** and Case **(B)** to achieve the optimal balance.

Secondly, we analyze the regret for the Inner UCB Algorithm. By defining the discrete best prices
$\tilde{p}_t^* := \arg\max_{p \in \mathcal{S}_t} p(1 - F(p - x_t^\top \theta_0))$ in $\mathcal{S}_t$, the time t regret r_t can be decomposed as

$$\underbrace{\tilde{p}_t^*(1 - F(\tilde{p}_t^* - x_t^\top \theta_0)) - p_t(1 - F(p_t - x_t^\top \theta_0))}_{r_{t,1}} + \underbrace{p_t^*(1 - F(p_t^* - x_t^\top \theta_0)) - \tilde{p}_t^*(1 - F(\tilde{p}_t^* - x_t^\top \theta_0))}_{r_{t,2}}.$$

247 We refer to $R_{T_0,1} = \sum_{t=1}^{T_0} r_{t,1}$ and $R_{T_0,2} = \sum_{t=1}^{T_0} r_{t,2}$ as the discrete-part and continuous-part
248 regrets. By the PLB formulation of the pricing problem, there is a correspondence between candidate
249 prices and PLB actions. Thus the discrete-part regret is equivalent to the PLB regret. To bound the

Table 2: Regret components' rates for Case **(A)** and Case **(B)**.

	Exploration Phase	UCB Phase		
		Discrete-part		Continuous-part
		θ_0 Estimation Error	F-Learning	
		$O(\|\|\hat\theta - \theta_0\|\|_1 T_0)$	$\tilde{O}(d\sqrt{T_0})$	
Case **(A)**	$O(T_0^\beta)$	$O(T_0^{1-\frac{\beta}{2}})$	$\tilde{O}(T_0^{\gamma+\frac{1}{2}})$	$O(\frac{T_0}{d^2}) = O(T_0^{1-2\gamma})$
Case **(B)**	$O(T_0^\beta)$	$O(T_0^{1-\frac{\beta}{2}})$	$\tilde{O}(T_0^{\gamma+\frac{1}{2}})$	$O(\frac{T_0}{d}) = O(T_0^{1-\gamma})$

discrete-part regret of the Inner UCB Algorithm, we prove the following Proposition 1 based on Theorem 1 in [35].

Proposition 1 *Under Assumptions 1 and 6, there exists positive constants C_1', C_2' such that with probability at least $1 - \frac{1}{T_0}$, the Inner UCB Algorithm yields a discrete-part regret*

$$R_{T_0,1} \leq C_1' d\sqrt{T_0}\log(C_2'T_0) + C_3'L\|\|\hat\theta - \theta_0\|\|_1 T_0.$$

In Proposition 1, the first $\tilde{O}(d\sqrt{T_0})$ component is typical in linear bandit and attributes to the lack of knowledge for F and the central parameter ξ^* in the PLB formulation. The second $L\|\|\hat\theta - \theta_0\|\|_1 T_0$ component is proportional to the PLB perturbation constant $2L\|\|\hat\theta - \theta_0\|\|$. It demonstrates how estimation errors influence the regret upper bounds, which matches with the intuition that a better estimation would incur a lower regret in the UCB phase.

The discretization number d plays a critical role in balancing the discrete-part and continuous-part regret. A larger d leads to a higher discrete-part regret as indicated by Proposition 1, which is intuitive since more discretizations yield more candidate prices and hence a more challenging search process. On the other hand, a larger d and a denser discretization would make the discrete best price "closer" to the overall best price and decrease the continuous-part regret. Specifically, under Case **(A)** and Case **(B)**, we can bound the continuous-part regret with the order $O(\frac{T_0}{d^2})$ and $O(\frac{T_0}{d})$ respectively. Namely, we could achieve a lower rate with the extra concavity Assumption 7. Since we choose the discretization number d_k in episode k to scale as $(u_k)^\gamma$ where u_k denotes the UCB phase length, γ regulates the balance between the discrete-part and continuous-part regret in the UCB phase and should be set differently for optimal balances in Case **(A)** and Case **(B)**.

Now we are ready to present the two regret upper bounds for Case **(A)** and Case **(B)**.

Theorem 1 *Under Assumptions $1-7$, by choosing $\beta = \frac{2}{3}$ and $\gamma = \frac{1}{6}$ in Algorithm 1, the expected regret satisfies $\mathbb{E}(R_T) = \tilde{O}(T^{2/3})$.*

Theorem 2 *Under Assumptions $1-6$, by choosing $\beta = \frac{3}{4}$ and $\gamma = \frac{1}{4}$ in Algorithm 1, the expected regret satisfies $\mathbb{E}(R_T) = \tilde{O}(T^{3/4})$.*

We illustrate the regret components' orders in Table 2 for a single episode with a generic length T_0. Table 2 explains the different choices of β and γ in the two cases to minimize the overall regret rates. It clearly demonstrates that β balances between the exploration phase regret and the discrete-part regret due to θ_0 estimation error; while γ balances between the continuous-part regret and the discrete-part regret due to F-learning. As shown in Theorem 1, through optimal balance, ExUCB improves the existing regret of $\tilde{O}(T^{2/3\vee(1-\alpha)})$ in [35] and $\tilde{O}(T^{5/7})$ in [23] to $\tilde{O}(T^{2/3})$ under Lipschitz and concavity assumptions. In addition, an optimal choice of β and γ in Theorem 2 helps ExUCB match the best existing regret of $\tilde{O}(T^{3/4})$ [48] under the Lipschitz-only assumption.

5.2 Lower Bound

We next prove a regret lower bound of $\tilde{\Omega}(T^{3/5})$ for Case **(A)**. To our limited knowledge, this is the first lower bound result under the Lipschitz and concavity assumptions. Note that there is a gap between our proved upper and lower bounds for Case **(A)**. Indeed, such a gap also happens in other works [23, 48] on the unknown noise pricing problems. This may be due to the inherent difficulties of these problems, e.g., in learning both θ_0 and F.

Theorem 3 *For any $\delta > 0$, no policy can achieve an $O(T^{3/5-\delta})$ regret for the dynamic pricing problem under Assumptions 1 – 7.*

Remark 1 *In [48], the authors proved an $\tilde{\Omega}(T^{2/3})$ lower bound with constructed instances that can fit into Case (**B**) but does not apply to Case (**A**). Our proved lower bound rate is lower since our instances need to satisfy more assumptions and lie in a more benign class. Another similar lower bound of $\Omega(T^{3/5})$ is proved in [15] for 1-dimensional nonparametric contextual expected revenue functions. However, their instances are constructed in a local-bin fashion with respect to the covariate and thus are outside our revenue function class. Therefore, their lower bound does not apply to our setting.*

Proof Sketch of Theorem 3. We follow similar ideas in [31, 48] to construct the instances. Firstly we set $\theta_0 = 0$ and ignore the difficulty from contexts. Namely, the instances we construct are indeed non-contextual. Secondly, we construct a series of "bump towers" and then transform them to valid expected revenue functions in the form of $p(1 - F(p))$, while still preserving the intended properties. To construct the series of "bump towers", we construct an infinite number of infinitely-nested interval series $[0, 1] = [a_0, b_0] \supset [a_1, b_1] \supset \cdots \supset [a_k, b_k] \supset \ldots$. Specifically, we divide $[a_k, b_k]$ with length $w_k = 3^{-k!}$ into three same-length sub-intervals and further divide the middle sub-interval into $\frac{w_k}{w_{k+1}}$ candidate intervals. Then each of these candidate intervals forms one version of $[a_{k+1}, b_{k+1}]$. For each of the infinitely-nested interval series, we add up bump functions on all these nested intervals. Different from [48], to construct the expected revenue functions that satisfy the concavity assumption, we adopt a different basic bump function and develop a "quadratically-shrinking" adding pattern of the bump functions. With these constructions, we prove that any policy will miss the peaks of some revenue function instances often enough, thus accumulating an inevitable amount of the regret.

6 Numerical Experiments

We conduct numerical experiments to support our theoretical regret bounds of ExUCB under both Case (**A**) and Case (**B**). We consider a total horizon length $T = \sum_{i=1}^{10} 2^{8+i}$ that is divided into 10 episodes with the first episode length $\alpha_1 = 2^9$. For both cases, we specify the linear parameter $\theta_0 = 30$ and sample the i.i.d. covariates as $x_t \sim \text{Unif}(1/2, 1)$. For Case (**A**), the noise distribution is set as a Uniform mixture $\frac{3}{4}\text{Unif}(-15, 0) + \frac{1}{4}\text{Unif}(0, 15)$; while for Case (**B**), we adopt another Uniform mixture $\frac{1}{4}\text{Unif}(-15, 0) + \frac{3}{4}\text{Unif}(0, 15)$. It can be verified that the first distribution satisfies the Lipschitz and concavity assumptions while the second one only satisfies the Lipschitz assumption. We apply ExUCB with different choices of β, γ specified in Theorems $1 - 2$ to these two instances. For both cases, we set the constants in Algorithm 1 as $p_{\max} = 50, B = 50, C_1 = 1, C_2 = 20, \lambda = 0.1$. With 100 replications, we plot the log-log scale of average accumulative regrets versus the time periods in Figure 2 along with the 95% confidence intervals. The linear fits extract a slope of 0.670 for Case (**A**) and a slope of 0.724 for Case (**B**), which indicates that our proved regrets of $\tilde{O}(T^{2/3})$ for Case (**A**) and $\tilde{O}(T^{3/4})$ for Case (**B**) are sharp.

(a) Case (**A**): ExUCB with $\beta = 2/3, \gamma = 1/6$.   (b) Case (**B**): ExUCB with $\beta = 3/4, \gamma = 1/4$.

Figure 2: Regret rates of ExUCB for Case (**A**) and Case (**B**).

References

[1] Abbasi-Yadkori, Y., Pál, D., and Szepesvári, C. (2011). Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems*, pages 2312–2320.

[2] Agrawal, R. (1995). The continuum-armed bandit problem. *SIAM journal on control and optimization* **33,** 1926–1951.

[3] Agrawal, S. and Goyal, N. (2013). Thompson sampling for contextual bandits with linear payoffs. In *International Conference on Machine Learning*, pages 127–135.

[4] Amin, K., Rostamizadeh, A., and Syed, U. (2014). Repeated contextual auctions with strategic buyers. *Advances in Neural Information Processing Systems* **27,**.

[5] Auer, P., Cesa-Bianchi, N., and Fischer, P. (2002). Finite-time analysis of the multiarmed bandit problem. *Machine learning* **47,** 235–256.

[6] Auer, P., Ortner, R., and Szepesvári, C. (2007). Improved rates for the stochastic continuum-armed bandit problem. In *International Conference on Computational Learning Theory*, pages 454–468. Springer.

[7] Ban, G.-Y. and Keskin, B. (2020). Personalized dynamic pricing with machine learning: High dimensional features and heterogeneous elasticity. *Forthcoming, Management Science* .

[8] Bastani, H., Simchi-Levi, D., and Zhu, R. (2019). Meta dynamic pricing: Transfer learning across experiments. *Available at SSRN 3334629* .

[9] Besbes, O. and Zeevi, A. (2009). Dynamic pricing without knowing the demand function: Risk bounds and near-optimal algorithms. *Operations Research* **57,** 1407–1420.

[10] Besbes, O. and Zeevi, A. (2015). On the (surprising) sufficiency of linear models for dynamic pricing with demand learning. *Management Science* **61,** 723–739.

[11] Broder, J. and Rusmevichientong, P. (2012). Dynamic pricing under a general parametric choice model. *Operations Research* **60,** 965–980.

[12] Bubeck, S. and Cesa-Bianchi, N. (2012). Regret analysis of stochastic and nonstochastic multi-armed bandit problems. *arXiv preprint arXiv:1204.5721* .

[13] Bubeck, S., Munos, R., Stoltz, G., and Szepesvari, C. (2010). X-armed bandits. *arXiv preprint arXiv:1001.4475* .

[14] Cesa-Bianchi, N., Cesari, T., and Perchet, V. (2019). Dynamic pricing with finitely many unknown valuations. In *Algorithmic Learning Theory*, pages 247–273. PMLR.

[15] Chen, N. and Gallego, G. (2021). Nonparametric pricing analytics with customer covariates. *Forthcoming, Operations Research* .

[16] Chen, Q., Jasin, S., and Duenyas, I. (2019). Nonparametric self-adjusting control for joint learning and optimization of multiproduct pricing with finite resource capacity. *Mathematics of Operations Research* **44,** 601–631.

[17] Chen, X., Owen, Z., Pixton, C., and Simchi-Levi, D. (2021). A statistical learning approach to personalization in revenue management. *Forthcoming, Management Science* .

[18] Cheung, W. C., Simchi-Levi, D., and Wang, H. (2017). Dynamic pricing and demand learning with limited price experimentation. *Operations Research* **65,** 1722–1731.

[19] Cheung, W. C., Simchi-Levi, D., and Zhu, R. (2018). Hedging the drift: Learning to optimize under non-stationarity. *Available at SSRN 3261050* .

[20] Chu, W., Li, L., Reyzin, L., and Schapire, R. (2011). Contextual bandits with linear payoff functions. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pages 208–214.

[21] Cohen, M. C., Lobel, I., and Paes Leme, R. (2020). Feature-based dynamic pricing. *Management Science* **66,** 4921–4943.

[22] den Boer, A. V. and Keskin, N. B. (2020). Discontinuous demand functions: estimation and pricing. *Management Science* **66,** 4516–4534.

[23] Fan, J., Guo, Y., and Yu, M. (2021). Policy optimization using semiparametric models for dynamic pricing. *Available at SSRN 3922825* .

[24] Foster, D. J., Gentile, C., Mohri, M., and Zimmert, J. (2020). Adapting to misspecification in contextual bandits. *Advances in Neural Information Processing Systems* **33,**.

[25] Golrezaei, N., Jaillet, P., and Liang, J. C. N. (2019). Incentive-aware contextual pricing with non-parametric market noise. *arXiv preprint arXiv:1911.03508* .

[26] Golrezaei, N., Javanmard, A., and Mirrokni, V. (2021). Dynamic incentive-aware learning: Robust pricing in contextual auctions. *Operations Research* **69,** 297–314.

[27] Javanmard, A. (2017). Perishability of data: dynamic pricing under varying-coefficient models. *The Journal of Machine Learning Research* **18,** 1714–1744.

[28] Javanmard, A. and Nazerzadeh, H. (2019). Dynamic pricing in high-dimensions. *The Journal of Machine Learning Research* **20,** 315–363.

[29] Javanmard, A., Nazerzadeh, H., and Shao, S. (2020). Multi-product dynamic pricing in high-dimensions with heterogeneous price sensitivity. In *2020 IEEE International Symposium on Information Theory (ISIT)*, pages 2652–2657. IEEE.

[30] Keskin, N. B. and Zeevi, A. (2014). Dynamic pricing with an unknown demand model: Asymptotically optimal semi-myopic policies. *Operations Research* **62,** 1142–1167.

[31] Kleinberg, R. (2004). Nearly tight bounds for the continuum-armed bandit problem. *Advances in Neural Information Processing Systems* **17,**.

[32] Kleinberg, R. and Leighton, T. (2003). The value of knowing a demand curve: Bounds on regret for online posted-price auctions. In *44th Annual IEEE Symposium on Foundations of Computer Science, 2003. Proceedings.*, pages 594–605. IEEE.

[33] Lattimore, T. and Szepesvári, C. (2020). *Bandit algorithms*. Cambridge University Press.

[34] Lattimore, T., Szepesvari, C., and Weisz, G. (2020). Learning with good feature representations in bandits and in rl with a generative model. In *International Conference on Machine Learning*, pages 5662–5670. PMLR.

[35] Luo, Y., Sun, W. W., et al. (2021). Distribution-free contextual dynamic pricing. *arXiv preprint arXiv:2109.07340* .

[36] Mao, J., Leme, R., and Schneider, J. (2018). Contextual pricing for lipschitz buyers. In *Advances in Neural Information Processing Systems*, pages 5643–5651.

[37] Misra, K., Schwartz, E. M., and Abernethy, J. (2019). Dynamic online pricing with incomplete information using multiarmed bandit experiments. *Marketing Science* **38,** 226–252.

[38] Nambiar, M., Simchi-Levi, D., and Wang, H. (2019). Dynamic learning and pricing with model misspecification. *Management Science* **65,** 4980–5000.

[39] Pacchiano, A., Phan, M., Abbasi Yadkori, Y., Rao, A., Zimmert, J., Lattimore, T., and Szepesvari, C. (2020). Model selection in contextual stochastic bandit problems. *Advances in Neural Information Processing Systems* **33,**.

[40] Perchet, V., Rigollet, P., et al. (2013). The multi-armed bandit problem with covariates. *The Annals of Statistics* **41,** 693–721.

[41] Qiang, S. and Bayati, M. (2016). Dynamic pricing with demand covariates. *Available at SSRN 2765257* .

[42] Russac, Y., Vernade, C., and Cappé, O. (2019). Weighted linear bandits for non-stationary environments. In *Advances in Neural Information Processing Systems*, pages 12040–12049.

[43] Shah, V., Johari, R., and Blanchet, J. (2019). Semi-parametric dynamic contextual pricing. In *Advances in Neural Information Processing Systems*, pages 2363–2373.

[44] Wang, Y., Chen, B., and Simchi-Levi, D. (2021). Multimodal dynamic pricing. *Forthcoming, Management Science* .

[45] Wang, Y., Chen, X., Chang, X., and Ge, D. (2020). Uncertainty quantification for demand prediction in contextual dynamic pricing. *Forthcoming, Production and Operations Management* .

[46] Wang, Z., Deng, S., and Ye, Y. (2014). Close the gaps: A learning-while-doing algorithm for single-product revenue management problems. *Operations Research* **62,** 318–331.

[47] Xu, J. and Wang, Y.-X. (2021). Logarithmic regret in feature-based dynamic pricing. *Advances in Neural Information Processing Systems* **34,**.

[48] Xu, J. and Wang, Y.-X. (2022). Towards agnostic feature-based dynamic pricing: Linear policies vs linear valuation with unknown noise. *arXiv preprint arXiv:2201.11341* .

[49] Zhao, P., Zhang, L., Jiang, Y., and Zhou, Z.-H. (2020). A simple approach for non-stationary linear bandits. In *Proceedings of the 23rd International Conference on Artificial Intelligence and Statistics, AISTATS*, volume 2020.