Neural-Symbolic Entangled Framework for Complex Query Answering

Abstract

Answering complex queries over knowledge graphs (KG) is an important yet challenging task because of the KG incompleteness issue and cascading errors during reasoning. Recent query embedding (QE) approaches embed the entities and relations in a KG and the first-order logic (FOL) queries into a low dimensional space, answering queries by dense similarity search. However, previous works mainly concentrate on the target answers, ignoring intermediate entities' usefulness, which is essential for relieving the cascading error problem in logical query answering. In addition, these methods are usually designed with their own geometric or distributional embeddings to handle logical operators like union($\vee$), intersection($\wedge$), and negation($\neg$), with the sacrifice of the accuracy of the basic operator – projection, and they could not absorb other embedding methods to their models. In this work, we propose a **Ne**ural and **Sy**mbolic **E**ntangled framework (**ENeSy**) for complex query answering, which enables the neural and symbolic reasoning to enhance each other to alleviate the cascading error and KG incompleteness. The projection operator in ENeSy could be any embedding method with the capability of link prediction, and the other FOL operators are handled without parameters. With both neural and symbolic reasoning results contained, ENeSy answers queries in ensembles. We evaluate ENeSy on complex query answering benchmarks, and ENeSy achieves the state-of-the-art, especially in the setting of training model only with the link prediction task.

1 Introduction

People built different Knowledge Graphs, such as Freebase [3], YAGO [12] and Wordnet [10], to store complex structured information and knowledge. The facts in KG are usually represented in the form of triplets, e.g., *isCityOf(New York, USA)*. KGs have been widely applied in various intelligent systems such as question answering and natural language understanding. One of the key tasks on KG reasoning is complex query answering which involves answering FOL query with logical operators including existential quantification ($\exists$), conjunction($\wedge$), disjunction($\vee$) and negation($\neg$).

Given a question *"Who won the Turing Award in developing countries?"*, as illustrated in Figure1, it could be converted to a FOL query, and a computation graph can be generated with the query. Each node in the computation graph represents an entity or an entity set, while each edge represents a logical operation. Answering these queries is challenging since not all the answers could be directly identified by traversing the KG because of the incompleteness of KG. To address this problem, several QE methods [8, 13, 14, 5] are proposed which encode entities and the query to a low-dimensional embedding space and the logical operators are also parameterized. Following the corresponding computation graph, the query embedding could be computed step by step. The target answers are selected according to the distance between the final embedding and candidate entity embedding.

$q = V_?. \exists V : Contain(\texttt{Developing\_Country}, V)$
$\wedge\, Citizen(V, V_?) \wedge Win(\texttt{Turing\_Award}, V_?)$

$q = V_?. Contain(\texttt{Developing\_Country}, V_?)$
$V_? = \{\texttt{China}, \texttt{India}, \texttt{Sri Lanka}, ...\}$

● Anchor Entity ● Variable ● Predicted Entity ● Answer ⟶ Embedding Projection ⇢ Neural Symbolic Entangled

(A) Computation Graph   (B) Neural Symbol Entangled Reasoning

Figure 1: An example of answering a complex graph query by using the ENeSy. (A): FOL query and its computation graph for the question *'Who won the Turing Award in developing countries?'*. (B): ENeSy models uses neural and symbolic ways to handle projection separately, and the results are entangled to enhance each other to alleviate the problem of cascading error and incompleteness of KG. The logic operator ∧, ∨ and ¬ are supported with symbolic reasoning.

Although the query embedding methods are effective for solving the incompleteness of KG, several limitations still exist. Firstly, the role of intermediate entities remains largely unexamined on complex query task which we argue plays a significant role in obtaining the target answers since besides incompleteness, cascading error also influences the accuracy of complex query. Existing works only pay close attention to the target answers, but for multi-hop reasoning, the intermediate entities could not be ignored. Secondly, previous works propose their own geometric shapes or distribution embedding so as to support different logical operators. For instance, Query2Box (Q2B) embed queries to boxes and can handle intersection(∧), while ConE [25] and BetaE [14] embed query with cone embedding and beta distribution to further support negation(¬). Although the logical operators are supported with their own embedding shape, the performance on the basic operator, projection, is not satisfying. For example, the accuracy of Q2B on one projection type query is worse than TransE [4] according to the Q2B paper [13]. Few studies have investigated how to generalize existed embedding models, such as TransE and RotatE which have been proved achieving good performance in one-hop reasoning, to the complex query models.

In this paper, we propose a neural symbolic entangled model, named ENeSy, which enables embedding and symbolic reasoning to enhance each other. In this framework, the embedding results influence the symbolic results to solve the KG incompleteness problem while symbolic results could revise embedding results by alleviating the problem of cascading error in multi-hop reasoning. Our approach has the following important advantages: (1) ENeSy can generalize KG embedding methods to answering complex query, and it could not only use the classic KGE algorithm like TransE, RotatE, the projection operator of existed query embedding methods could also be employed with our model. (2) The logical operators except projection (including ∧, ∨, ¬) are not parameterized so we could train the whole model with only link prediction tasks, since meaningful complex query data might be hard to obtain in the real world.

The experimental results prove that our model outperforms existing complex query answering methods over standard knowledge graphs: FB15K-237 [17] and NELL-995 [21]. The performance, which is trained with link prediction, is also competitive to or better than the baselines trained with complex query. The analysis of model proves the effectiveness of neural and symbolic entanglement to solving the problem of cascading error and KG incompleteness with our framework.

2 Related Work

2.1 Knowledge Graph Embedding

A great deal of previous research into KG has focused on using machine learning to reason with embedding method. The effects have been shown in TransE [4], TransH [19], TransG [20], ComplEx [18], ConvE [7], DistMult [22] and RotatE [16]. These approaches aim to embed the entities

and relations to a continuous vector space so that one-hop reasoning can be answered with link prediction. Different methods map the entities and relations into vector space with different distributions. Meanwhile, the rule and path-based [9, 24, 23, 15], tries to use learned pattern of path or rules to do multi-hop reasoning.

However, KGE models lack the ability to handle complex logical operators like conjunction ($\wedge$), disjunction ($\vee$) and negation ($\neg$) and they are not easy to be generalized to multi-hop queries. In contrast, our framework can alleviate the problem of cascading error during multi-hop reasoning and also support all of the logical operators above so that any KGE models could be used to answer complex query.

2.2 Embedding for Complex Query Answering

To answer logical queries, some works [8, 13, 25, 1, 14, 5] aims to encode the complex query into a space which proposes various geometric shape to represent the entity set and support complex query reasoning. Generally, a FOL query is converted to a computation graph with a directed acyclic graph (DAG) structure with which the query representation could be iteratively computed using the logical operation in embedding space. GQE (graph-query embedding)[8] consider conjunction operator ($\wedge$) with vector representation. Q2B (query to box)[13] replace the vector embedding with hyper-rectangles since it holds the idea that box embedding can represent sets of entities better and define the disjunctive norm form (DNF) to support the disjunction ($\vee$) operator. More recently, BetaE[14] models the query and entities with beta distributions which could support negation ($\neg$) operator. ConE[25] propose a new geometry model that embed entities with cones embedding. FuzzQE [5] satisfies the axiomatic system of fuzzy logic to reason. Q2P (Query2Particles) [1] encodes each query into multiple vectors.

Most of these methods usually design their geometric or distribution embedding to support logical operators but the effective of the projection operator, which is the most basic operator, has not been discussed. Meanwhile, they only concentrate on the final answer as label but ignore the intermediate entities during the query process which are also important for reasoning.

3 Preliminaries

In this section, we introduce the task of complex query answering on KG. Given a set of entities $\mathcal{V}$ and a set of relations $\mathcal{R}$, a knowledge graph $\mathcal{G}$ is defined as $(\mathcal{V}, \mathcal{R}, \mathcal{T})$ where $\mathcal{T}$ is the set of triplets. A triplet is defined as $r(e_i, e_j)$ where $e_i \in \mathcal{V}, e_j \in \mathcal{V}, r \in \mathcal{R}$ if the relation r exists between e_i and e_j.

First-Order Logic. The purpose of complex query answering on KG is obtaining the target answer of FOL query which is defined with existential quantifiers($\exists$), conjunction ($\wedge$), disjunction ($\vee$) and negation ($\neg$). In a FOL query q, the anchor nodes are represented as a set $\mathcal{V}_a \subseteq \mathcal{V}$, existential quantified variables nodes are represented as $V_1, V_2, \ldots V_k$ and the target answer nodes is a variable $V_?$. Follow the betaE [14], we use FOL query in its disjunctive norm form, with which the query can be represented as a disjunction of several conjunctions. Finally, the query can be formulated as:

$$q[V_?] \coloneqq V_? : V_1, V_2, \ldots, V_k : c_1 \vee c_2 \vee \cdots \vee c_n.$$

where c_i is a conjunction of several literals a_{ij}, i.e., $c_i = a_{ij} \wedge \cdots \wedge a_{im}$, and a_{ij} is an atom or negation of an atom: $r(e_a, V)$ or $\neg r(e_a, V)$ or $r(V', V)$ or $\neg r(V', V)$ where $e_a \in \mathcal{V}_a, V, V' \in \{V_1, V_2, \ldots, V_k, V_?\}$ and $V \neq V'$ in an atom.

Computation Graph and Logical Operators As illustrated in figure 1, for a given FOL query, we can represent the whole process of reasoning as a computation graph. Each node corresponds to a variable V or an anchor node e_a and each edge represents a logical operation over the entity sets which includes these following operators:

- **Relational Projection:** Given an entity set $\mathcal{S} \subseteq \mathcal{V}$ and a relation $r \in \mathcal{R}$, the projection operator return a new entity set $\mathcal{S}'$ that contains the entities related to at least one of entity in $\mathcal{S}$: $S' = \{e' \in \mathcal{V} | \exists r(e, e'), e \in \mathcal{S}\}$.
- **Intersection:** Given sets of entities $\{S_1, S_2, \ldots, S_n\}$ where $S_i \subseteq \mathcal{V}$, the intersection operator returns the intersection of these sets $\bigcap_{i=1}^{n} S_i$.
- **Union:** Given sets of entities $\{S_1, S_2, \ldots . S_n\}$ where $S_i \subseteq \mathcal{V}$, the union operator returns the union of these sets $\bigcup_{i=1}^{n} S_i$.

121 • **Complement:** Given a set of entities $\mathcal{S}$, the complement operator returns its complement
122 $\mathcal{S}' = \mathcal{V} - \mathcal{S}$.

4 Methodology

124 In this section, we first introduce the neural and symbolic entangled projection operator in detail. Then
125 we define symbolic-based logical operators and describe the ensemble prediction using embedding
126 and symbolic results. Finally, the objective function and the learning procedure will be represented.

4.1 Neural and Symbolic Entangled Reasoning

Figure 2: ENeSy's logical operators and the details about neural symbolic entanglement. P_N means neural projection and P_S means symbolic projection.

128 In our work, there are two ways to represent the entities and relations. The neural part is just like the
129 KGE or query embedding method we adopt, and rotatE [16] is chosen in this paper which embed
130 entities and relations to a complex space $\mathbb{C}^k$. For the symbolic part, an entity and a relation are
131 encoded as a one-hot vector and an adjacent matrix, respectively.

132 Specifically, given the KG $\mathcal{G}$, entity set $\mathcal{V}$ and relation set $\mathcal{R}$, an entity e's embedding representation
133 is a vector $\mathbf{v}_e \in \mathbb{C}^k$ and its symbolic representation is encoded as an one-hot vector $\mathbf{p}_e \in \{0,1\}^{1 \times |\mathcal{V}|}$.
134 Each relation r is modeled as a vector $\mathbf{v}_r \in \mathbb{C}^k$ and the corresponding symbolic representation is an
135 adjacent matrix $\mathbf{M}_r \in \{0,1\}^{|\mathcal{V}| \times |\mathcal{V}|}$ where $\mathbf{M}_r^{ij} = 1$ if $r(e_i, e_j) \in \mathcal{G}$, else $\mathbf{M}_r^{ij} = 0$.

136 **Neural projection** follows the embedding method, we use rotatE [16] here as an example. For a
137 projection query $(h, r, ?)$, the functional mapping with relation r is an element-wise rotation from h
138 to the target answer t:

$$\mathbf{v}_t = \mathbf{v}_h \circ \mathbf{v}_r, \text{where} |\mathbf{v}_r| = 1 \tag{1}$$

139 and $\circ$ means Hadmard product. This step gets the predicted embedding which could be used to search
140 the target answers.

141 **Symbolic projection** is conducted with matrix multiplications followed `TensorLog` [6]:

$$\mathbf{p}_t = \mathbf{g}(\mathbf{p}_h \mathbf{M}_r)^\top \tag{2}$$

142 where $\mathbf{p}_t$ is a multi-hot vector that represents the entities linked with h via relation r, $\top$ means
143 transposing the vector and $\mathbf{g}$ is a normalization function. Particularly, we consider the function as
144 $\mathbf{g}(\mathbf{x}) = \mathbf{x}/sum(\mathbf{x})$. This step gets the target entities by traversing KG.

145 **Entangled projection** tries to take advantage of these above two results. Since embedding prediction
146 suffers from the cascading error but could obtain the answer not linked with h, while traversing KG
147 could not get the answers which lacks the edges to the head entity but the searched answers are
148 convincing, ENeSy combines them in an entanglement way as illustrated in Figure 2. Specifically,
149 the distance between the predicted embedding $\mathbf{v}_t$ and all the entities is calculated first. Next, the top

k entities are selected, which are the closest entities to $\mathbf{v}_t$ in the embedding space, where k is the number of non-zero elements in $\mathbf{p}_t$. We define the distance function as:

$$\mathbf{D}(\mathbf{x}, \mathbf{y}) = \gamma - \|\mathbf{x} - \mathbf{y}\|_1 \tag{3}$$

where γ denotes the margin. So we get a inferred vector $\mathbf{p}'_t \in [0, 1]^{1 \times |\mathcal{V}|}$ which is generated from $\mathbf{v}_t$, and the meaningful elements in $\mathbf{p}'_t$ is the top k largest elements in $\mathbf{v}_t$, the other elements are set to be negative infinity. With $\mathbf{p}'_t$, a new symbolic vector $\mathbf{p}''_t$ is obtained by the following step:

$$\mathbf{p}''_t = \mathbf{g}(\mathbf{p}_t + \text{Softmax}(\mathbf{p}'_t)) \tag{4}$$

This new symbolic vector $\mathbf{p}''_t$ integrates the information from the embedding $\mathbf{v}_t$ with symbolic reasoning results $\mathbf{p}_t$. This procedure adds more entities, which might be the answer to the query which are not linked with h, to $\mathbf{p}''_t$. This enhancement eliminates the limitation of KG incompleteness of symbolic reasoning to some extent. Each element of $\mathbf{p}''_t$ could be regarded as the possibilities of the corresponding entity. Let's assume the entity set with non-zero possibilities as $\mathcal{S}_t$, a aggregation function is employed to transfer the symbolic vector $\mathbf{p}''_t$ and the embedding of entities in $\mathcal{S}_t$ to a new embedding vector $\mathbf{v}'_t$ with an MLP function:

$$\mathbf{v}'_t = \sum_{i=1}^{|\mathcal{S}_t|} \mathbf{p}_t^{i''} \text{MLP}(\mathbf{v}_{e_i}) \mathbf{v}_{e_i}, e_i \in \mathcal{S}_t \tag{5}$$

where $\mathbf{p}_t^{i''}$ is the corresponding possibility of e_i in $\mathbf{p}_t$. This new embedding $\mathbf{v}'_t$ aggregates the symbolic answer, Note that although we use the rotatE as the neural function, any other sufficiently expressive KG embedding model or the projection operator of any other query embedding models could be employed with our framework in theory.

4.2 Neural and Symbolic Ensemble Answering

With the symbolic vector $\mathbf{p}$, the logical operator intersection($\mathbf{p}_1 \wedge \mathbf{p}_2$), union($\mathbf{p}_1 \vee \mathbf{p}_2$) and negation ($\neg \mathbf{p}$) could be defined as follows:

$$\mathbf{p}_1 \wedge \mathbf{p}_2 : \mathbf{g}(\mathbf{p}_1 \circ \mathbf{p}_2), \quad \mathbf{p}_1 \vee \mathbf{p}_2 : \mathbf{g}(\mathbf{p}_1 + \mathbf{p}_2 - \mathbf{p}_1 \circ \mathbf{p}_2), \quad \neg \mathbf{p} : \mathbf{g}(\frac{\alpha}{|\mathcal{V}|} - \mathbf{p})$$

where $\circ$ is Hadmard product and α is a hyper parameter. After getting symbolic vector with these logical operators, the MLP function used in Equation (5) is employed to get an aggregated embedding.

The embedding and symbolic vector can both be used to get the final answers. For the neural part, the distance between the embedding vector $\mathbf{v}$ and all the entities $e \in \mathcal{V}$ is computed with Equation (3), which is used to rank the candidate answers. For the symbolic part, since the vector $\mathbf{p}$ represents the possibilities of each entity, the answers can be directly obtained with ranked elements of $\mathbf{p}$. To make the ensemble using of the two type answers, we set a to get a combined result with $\mathbf{v}$ and $\mathbf{p}$ as:

$$\mathbf{a} = \lambda \mathbf{p} + (1 - \lambda) \text{Softmax}(\underset{\forall e \in \mathcal{V}}{\mathbf{Concat}}(\mathbf{D}(\mathbf{v}, \mathbf{v}_e))) \tag{6}$$

where λ is the weight to balance the influence of $\mathbf{v}$ and $\mathbf{p}$ and $\mathbf{Concat}$ is a function mapping the distance between all entities $e \in \mathcal{V}$ and $\mathbf{v}$ to a vector. The final answers can be determined with $\mathbf{g}(\mathbf{a}) \in [0, 1]^{1 \times |\mathcal{V}|}$.

4.3 Learning Procedure

Given a query q with answer entity set $\mathcal{S}_q$, after getting the final answer embedding $\mathbf{v}_q$ and symbolic vector $\mathbf{p}_q$, we construct two following objective loss functions:

$$L_1 = -\log\sigma(-\mathbf{D}(\mathbf{v}, \mathbf{v}_e)) - \frac{1}{n} \sum_{i=1}^{n} \log\sigma(\mathbf{D}(\mathbf{v}, \mathbf{v}_{e'})) \tag{7}$$

$$L_2 = -\log\sigma(\mathbf{p}_e \cdot \log[\mathbf{p}_q^\top, \theta]_+) \tag{8}$$

where $e \in \mathcal{S}_q$ is an answer of q, $e' \notin \mathcal{S}_q$ is a negative answer which is sampled randomly. σ is the `sigmoid` function, $\cdot$ is dot-product and $[\mathbf{x}, \theta]_+$ denotes the maximum value between each element of $\mathbf{x}$ and θ, which is a threshold.

Meanwhile, the MLP function in Equation (5) needs to be pretrained individually. Since this function is employed to convert a symbolic vector to an embedding vector, and in the projection operator, we have $\mathbf{p}'_t$ which is generated from $\mathbf{v}_t$, MLP could be used to convert $\mathbf{p}'_t$ back to $\mathbf{v}_t$. Based on this, we also design a loss function to train this function as follows:

$$L_3 = -\log\sigma(-\mathbf{D}(\mathbf{v}_t, \sum_{i=1}^{|\mathcal{S}'_t|} \mathbf{p}_t^{i'}\text{MLP}(\mathbf{v}_{e_i})\mathbf{v}_{e_i})), e_i \in \mathcal{S}'_t \qquad (9)$$

where $\mathcal{S}'_t$ is the corresponding entity set whose possibilities are not zero in $\mathbf{p}'_t$. In the first step of the training process, the symbolic part are not included, and only embedding of entities and relations will be trained with link prediction task. Next, in the second step, the completed projection operator will be trained still by link prediction and the loss function is $L = L_1 + L_2 + L_3$. In theory, the model could answer complex query after the above two steps, but it could also be fine-tuned with complex query data using loss function $L = L_1 + L_2$.

5 Experiment

In this section, we evaluate the ability of ENeSy on answering the complex query on several KG benchmark datasets. The experiment results demonstrate that: 1) The performance of ENeSy is excellent; 2) We can train ENeSy with only link prediction task to answering complex query; 3) The embedding and symbolic part of our model can enhance each other.

5.1 Dataset and Experiment Setting

5.1.1 Datasets and Evaluation Protocol

We perform the experiments on two benchmarks, FB15K-237 [17] and NELL-995 [21]. FB15K-237 is a subset from Freebase [2] and removes the inverse relation. NELL-995 is a dataset constructed from high-confidence facts of NELL [11].

The focus of our experiment is answering FOL queries on incomplete KGs so we only evaluate the ability of models to obtain the answers that could not be discovered by traversing KGs. Specifically, with the standard training, validation and testing set, the edges in KG could be divided into three parts, which are training edges, validation edges and test edges. The corresponding graph $\mathcal{G}_{train}$, $\mathcal{G}_{valid}$ and $\mathcal{G}_{test}$ are build with *training* edges, *training + validation* edges and *training + validation + test* edges, respectively, so we have $\mathcal{G}_{train} \subset \mathcal{G}_{valid} \subset \mathcal{G}_{test}$. We only use the queries whose answer sets $\mathcal{A}_{train}$, $\mathcal{A}_{valid}$ and $\mathcal{A}_{test}$ on different graph have $\mathcal{A}_{train} \subset \mathcal{A}_{valid} \subset \mathcal{A}_{test}$. The answers in $\mathcal{A}_{valid} - \mathcal{A}_{train}$ could be used to tune the hyper-parameters and results are reported with the answer entities in $\mathcal{A}_{test} - \mathcal{A}_{valid}$. This means we only evaluate on entities that are not answer of the training query set and the model has not seen them. Meanwhile, these answers could not be found with graph traversal on $\mathcal{G}_{train}/\mathcal{G}_{valid}$. For each answer of a test query, we calculate the Mean Reciprocal Rank (MRR) as evaluation metrics and the results are reported with filter setting as TransE [4], in which all other correct answers are filtered out before calculating the rankings of answers.

The queries sampled from these two benchmark are provided by BetaE [14] which is an expansion of the version provided by Q2B [13]. The query set contains 14 different types of query structure are shown in Figure 3. In order to further verify the generalization ability of the models, only 5 conjunctive query (*1p/2p/3p/2i/3i*) and 5 query types with negation (*2in/3in/inp/pni/pin*) are used to train the model, while the other four query types (*2u/up/ip/pi*) do not appear in the training process and are directly evaluated when testing, which makes this task more challenging.

5.1.2 Baseline

We consider four baselines as the compared methods in the following sections: Graph Query Embedding (GQE) [8] embed the query into vectors, which could handle the projection and conjunction queries. With DNF, it could also support union operator.

Query2Box (Q2B) [13] uses box embedding to represent the query and entity sets and could answer existential positive first-order (EPFO) logic queries.

Figure 3: The query structure of all queries used for training and evaluation. Namely, the *p*, *i*, *u* and *n* stands for the projection, intersection, union and negation, respectively.

Table 1: The MRR results of FOL queries on FB15K-237 and NELL-995, adn the models are trained with only link prediction task. The Avg_p and Avg_n are the average MRR of Existential Positive FirstN/Aorder (EPFO) queries (query with $\exists$, $\vee$ or $\wedge$ and without $\neg$) and queries with $\neg$, respectively. N/A means not available.

Model	Avg_p	Avg_n	1p	2p	3p	2i	3i	pi	ip	2u	up	2in	3in	inp	pin	pni
							FB15K-237									
GQE	17.7	N/A	41.6	7.9	5.4	25.0	33.6	16.3	10.9	11.9	6.2	N/A	N/A	N/A	N/A	N/A
Q2B	18.2	N/A	42.6	6.9	4.7	27.3	36.8	17.5	11.1	11.7	5.5	N/A	N/A	N/A	N/A	N/A
BetaE	15.8	0.5	37.7	5.6	4.4	23.3	34.5	15.1	7.8	9.5	4.5	0.1	1.1	0.8	0.1	0.2
FuzzQE	21.8	6.6	44.0	**10.8**	**8.6**	32.3	41.4	22.7	15.1	**13.5**	**8.7**	7.7	9.5	7.0	4.1	4.7
ENeSy	**23.4**	**8.1**	**44.5**	10.8	7.7	**33.2**	**48.4**	**25.8**	**18.8**	13.4	7.6	**9.6**	**10.2**	**7.1**	**5.8**	**7.8**
							NELL-995									
GQE	21.7	N/A	47.2	12.7	9.3	30.6	37.0	20.6	16.1	12.6	9.6	N/A	N/A	N/A	N/A	N/A
Q2B	21.6	N/A	47.6	12.5	8.7	30.7	36.5	20.5	16.0	12.7	9.6	N/A	N/A	N/A	N/A	N/A
BetaE	19.0	0.4	53.1	6.0	3.9	32.0	37.7	15.8	8.5	10.1	3.5	0.1	1.4	0.1	0.1	0.1
FuzzQE	27.1	7.3	57.6	17.2	**13.3**	38.2	41.5	27.0	19.4	**16.9**	**12.7**	9.1	**8.3**	8.9	4.4	5.6
ENeSy	**28.7**	**9.4**	**58.8**	**17.4**	12.8	**39.1**	**48.9**	**29.1**	**24.1**	16.0	12.4	**10.9**	8.2	**11.0**	**8.4**	**8.6**

230 Beta Embedding (BetaE) [14] models query as Beta Distributions which enables it to support
231 negation($\neg$) operation.

232 Fuzzy Logic Query Embedding (FuzzQE) [5] uses fuzzy logic to embedding the query.

233 The MRR results of these baselines are from the BetaE [14] and FuzzQE paper [5]. The first two
234 methods can't handle negation operation and among these models, only FuzzQE can be trained with
235 only link prediction task and answer complex query.

5.1.3 Training Procedure and Experiment Settings

237 To train the model, we first only train the embedding of relations and entities with *1p* queries which
238 is similar to the pure KG embedding training. Second, the projection operator of ENeSy is trained on
239 1p queries. Meanwhile, the queries of all structures can be used to fine-tune the model.

240 We implement our model with Pytorch framework and train our model on RTX3090 GPU. The
241 ADAM optimizer was used to parameter tune with learning rate of 0.0001 that will decrease with
242 train process. In the second step, the learning rate is set to be 10^{-5} to train the model with $1p$ queries,
243 and in the fine-tune process, the learning rate starts with $2 * 10^{-7}$. We set the embedding dimension
244 of entity and relation to be 1024, respectively. The hidden state dimension of MLP is 1024. The
245 training batch size is {64, 16} for FB15K-237 and NELL-995, while the negative sample size is {128,
246 32}. The margin γ used in distance computation is 24. θ used as threshold is 10^{-10}. α is set to be 10.
247 The choices of λ which is used for ensemble prediction are based on the results of *valid* set for each
248 query type. The best hyper-parameter setting are selected by the MRR metric on the *valid* set. We
249 run the experiment several times and find random seed has almost no effect on the result, but in the
250 fine tune process, the learning rate influence the accuracy.

Table 2: The average MRR results of FOL queries on FB15K-237 and NELL-995 , and the models are trained with complex query data.

Model	Avg_p	Avg_n	1p	2p	3p	2i	3i	pi	ip	2u	up	2in	3in	inp	pin	pni
						FB15K-237										
GQE	16.3	N/A	35.0	7.2	5.3	23.3	34.6	16.5	10.7	8.2	5.7	N/A	N/A	N/A	N/A	N/A
Q2B	20.1	N/A	40.6	9.4	6.8	29.5	42.3	21.2	12.6	11.3	7.6	N/A	N/A	N/A	N/A	N/A
BetaE	20.9	5.5	39.0	10.9	10.0	28.8	42.5	22.4	12.6	12.4	9.7	5.1	7.9	7.4	3.5	3.4
FuzzQE	24.2	**8.5**	42.2	**13.3**	**10.2**	33.0	47.3	26.2	18.9	**15.6**	**10.8**	9.7	**12.6**	**7.8**	5.8	6.6
ENeSy	**24.5**	**8.5**	**44.7**	11.7	8.6	**34.8**	**50.4**	**27.6**	**19.7**	14.2	8.4	**10.1**	10.4	7.6	**6.1**	**8.1**
						NELL-995										
GQE	18.6	N/A	32.8	11.9	9.6	27.5	35.2	18.4	14.4	8.5	8.8	N/A	N/A	N/A	N/A	N/A
Q2B	22.9	N/A	42.2	14.0	11.2	33.3	44.5	22.4	16.8	11.3	10.3	N/A	N/A	N/A	N/A	N/A
BetaE	24.6	5.9	53.0	13.0	11.4	37.6	47.5	24.1	14.3	12.2	8.5	5.1	7.8	10.0	3.1	3.5
FuzzQE	29.3	8.0	58.1	**19.3**	**15.7**	**39.8**	50.3	28.1	21.8	**17.3**	**13.7**	8.3	**10.2**	11.5	4.6	5.4
ENeSy	**29.4**	**9.8**	**59.0**	18.0	14.0	39.6	49.8	**29.8**	**24.8**	16.4	13.1	**11.3**	8.5	**11.6**	**8.6**	**8.8**

5.2 Trained with Link Prediction

Since meaningful FOL queries are usually not available in real scenes, we first report the results of models which are trained with only *1p* query data, which also can be seen as link prediction task. The MRR results are shown in Table 1.

As the table shows, compared with pure embedding methods like GQE, Q2B and BetaE, the performance of ENeSy significantly improves. Since the operators except projection of these methods are parameterized, the ability to handle complex query is limited, but our model can be generalized to more complex query structure. Even though, the improvement on *1p* query proves the advantages of generalizing other KG embedding models to solving this problem. Compared with FuzzQE, which could also be trained with link prediction, our model improves the average MRR of EPFO about 2.6%(relatively 11.9%) on FB15K-237 and 1.6%(relatively 5.9%) on NELL-995. For the queries with negation, ENeSy provides a more absolute improvement, which is 1.5%(relatively 24.6%) and 2.1%(relatively 28.8%) on FB15K-237 and NELL-995. We believe the reason of this enhancement is that the symbolic representation can indicate the possibility of each entity better.

5.3 Trained with Complex Query

The results of models trained with query data are also reported in Table 2. Compared with the average MRR in Table 1, the performance of most baselines improves a lot because of the labeled data of complex query, but ENeSy still achieves the best performance on the average MRR of EPFO query and negation query. Moreover, our model could get closer results with different training settings. Specifically, the average MRR decreases about 4.7% and 2.4% for EPFO and 5% and 4.1% for negation queries on FB15K-237 and NELL-995 respectively when train with link prediction. For FuzzQE, the results decline about 9.9%, 7.5% for EPFO and 22.4%, 8.8% for query with negation on FB15K-237 and NELL-995, respectively. This proves stronger robustness of our methods. Note that though the *2p/3p* results seems to be worse than FuzzQE, we can replace RotatE with the projection operator of FuzzQE, and the results should be the same in theory.

5.4 Analysis of ENeSy

To get deep insights on the neural and symbolic reasoning part of ENeSy, we investigate their impact in this section. In what follows, we first explore how symbolic affect the embedding results. We then examine the influence of embedding to symbolic. Finally, the effect of ensemble prediction is discussed. The results are based on FB15K-237, and the situation on NELL-995 is similar.

5.4.1 Q1: Does symbolic results assist neural reasoning in cascading error?

We compare the pure KE embedding model, which is RotatE in this experiment, with the embedding results of ENeSy without ensemble, which we denote as $ENeSy_E$. The KGE model is trained with *1p* queries just like $ENeSy_E$. Since the KGE method could not support logical operators, we only report

Figure 4: The figure of model analysis. (a): The MRR results and increase scale of ENeSy$_E$ and pure KGE models. The query types are sorted by the query length. (b): The average MRR results of ENeSy$_S$ and traversing. The queries are grouped by their operator. q$_\exists$ includes all of the query type, q$_\wedge$ includes *2i/3i/pi/ip*, q$_\vee$ includes *2u/up* and q$_\neg$ includes *2in/3in/inp/pin/pni*. (c): The average MRR results of ENeSy$_E$, ENeSy$_S$ and ENeSy, queries are grouped by the same way as (b).

the results on *1p/2p/3p* query and the *2u/up* results could be also evaluated with DNF. The MRR results and the ratio of improvement are shown in Figure 4 (a). The query types are listed below the horizontal axis and we sort them by the length of query which is the longest distance from the anchor nodes to the target node in computation graph. As we can see, based on the similar performance on *1p* query, the MRR results of more complex queries significantly improves with query length increases. This comparison demonstrates that the problem of cascading error, which is the main limitation for multi-hop embedding reasoning, has been alleviated with the symbolic assistant.

5.4.2   Q2: Does embedding results assist symbolic reasoning in KG incompleteness?

The symbolic MRR results of ENeSy without ensemble, denoted as ENeSy$_S$, and pure symbolic results are shown in Figure 4 (b). We divided the query types into four groups according to the operator they have. Since we only evaluate the generalization ability of models with answers that could not be found by simply traversing KG, the traversing results is nearly zero (since the result is MRR, the number won't be an absolute zero), while the ENeSy$_S$ achieve better results than most baselines. The reason for this significant improvement from zero to almost SOTA performance is in the entangled process, ENeSy successfully captures the information from embedding which makes symbolic results include the answers could not be obtained directly. In summary, the experiment proves that the KG incompleteness problem for symbolic reasoning can be solved in our framework.

5.4.3   Q3: Does ensemble prediction of neural and symbolic results useful?

Ensemble prediction enables us to fuse the symbolic and reasoning results. To verify its effectiveness, we compare the performance of ENeSy$_E$, ENeSy$_S$ and ENeSy trained with *1p* queries. The MRR results are shown in Figure 4 (c). The queries are grouped in the same way as Q2. As the figure illustrates, all the results of different group queries improve after ensemble. Specifically, the average MRR metric in different group increase about 14.0%, 15.3%, 4.0%, 28.6% and 2.3%, 1.3%, 2.9%, 8.0% compared with ENeSy$_E$ and ENeSy$_S$, respectively, which certifies that the two parts could not only enhance each other in the reasoning process, but also can be combined in the final results.

6   Conclusion

In this paper, we proposed ENeSy, a neural-symbolic entangled framework for answering complex logical queries over knowledge graph. This model could generalize any embedding methods to complex query and use the symbolic reasoning results to alleviate cascading error, while the symbolic part also benefits from neural reasoning to solve the problem of KG incompleteness. The ENeSy supports all the FOL operations and can be trained with only link prediction tasks. Experimental results show that our model achieves state-of-the-art performances on answering FOL queries with strong robustness, and each part is tightly entangled to enhance each other. Future work may focus on how to reduce the space occupied during model training.

References

[1] Jiaxin Bai, Zihao Wang, Hongming Zhang, and Yangqiu Song. Query2particles: Knowledge graph reasoning with particle embeddings. *CoRR*, abs/2204.12847, 2022.

[2] Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. Freebase: a collaboratively created graph database for structuring human knowledge. In *Proceedings of the 2008 ACM SIGMOD international conference on Management of data*, pages 1247–1250, 2008.

[3] Kurt D. Bollacker, Colin Evans, Praveen K. Paritosh, Tim Sturge, and Jamie Taylor. Freebase: a collaboratively created graph database for structuring human knowledge. In Jason Tsong-Li Wang, editor, *Proceedings of the ACM SIGMOD International Conference on Management of Data, SIGMOD 2008, Vancouver, BC, Canada, June 10-12, 2008*, pages 1247–1250. ACM, 2008.

[4] Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. In *Advances in neural information processing systems*, pages 2787–2795, 2013.

[5] Xuelu Chen, Ziniu Hu, and Yizhou Sun. Fuzzy logic based logical query answering on knowledge graph. *CoRR*, abs/2108.02390, 2021.

[6] William W. Cohen, Fan Yang, and Kathryn Mazaitis. Tensorlog: A probabilistic database implemented using deep-learning infrastructure. *J. Artif. Intell. Res.*, 67:285–325, 2020.

[7] Tim Dettmers, Pasquale Minervini, Pontus Stenetorp, and Sebastian Riedel. Convolutional 2d knowledge graph embeddings. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

[8] William L. Hamilton, Payal Bajaj, Marinka Zitnik, Dan Jurafsky, and Jure Leskovec. Embedding logical queries on knowledge graphs. In Samy Bengio, Hanna M. Wallach, Hugo Larochelle, Kristen Grauman, Nicolò Cesa-Bianchi, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, December 3-8, 2018, Montréal, Canada*, pages 2030–2041, 2018.

[9] Yankai Lin, Zhiyuan Liu, Huanbo Luan, Maosong Sun, Siwei Rao, and Song Liu. Modeling relation paths for representation learning of knowledge bases. *arXiv preprint arXiv:1506.00379*, 2015.

[10] George A Miller. Wordnet: a lexical database for english. *Communications of the ACM*, 38(11):39–41, 1995.

[11] Tom M. Mitchell, William W. Cohen, Estevam R. Hruschka Jr., Partha Pratim Talukdar, Justin Betteridge, Andrew Carlson, Bhavana Dalvi Mishra, Matthew Gardner, Bryan Kisiel, Jayant Krishnamurthy, Ni Lao, Kathryn Mazaitis, Thahir Mohamed, Ndapandula Nakashole, Emmanouil A. Platanios, Alan Ritter, Mehdi Samadi, Burr Settles, Richard C. Wang, Derry Wijaya, Abhinav Gupta, Xinlei Chen, Abulhair Saparov, Malcolm Greaves, and Joel Welling. Never-ending learning. In Blai Bonet and Sven Koenig, editors, *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence, January 25-30, 2015, Austin, Texas, USA*, pages 2302–2310. AAAI Press, 2015.

[12] Thomas Rebele, Fabian M. Suchanek, Johannes Hoffart, Joanna Biega, Erdal Kuzey, and Gerhard Weikum. YAGO: A multilingual knowledge base from wikipedia, wordnet, and geonames. In Paul Groth, Elena Simperl, Alasdair J. G. Gray, Marta Sabou, Markus Krötzsch, Freddy Lécué, Fabian Flöck, and Yolanda Gil, editors, *The Semantic Web - ISWC 2016 - 15th International Semantic Web Conference, Kobe, Japan, October 17-21, 2016, Proceedings, Part II*, volume 9982 of *Lecture Notes in Computer Science*, pages 177–185, 2016.

[13] Hongyu Ren, Weihua Hu, and Jure Leskovec. Query2box: Reasoning over knowledge graphs in vector space using box embeddings. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020.

[14] Hongyu Ren and Jure Leskovec. Beta embeddings for multi-hop logical reasoning in knowledge graphs. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

[15] Ali Sadeghian, Mohammadreza Armandpour, Patrick Ding, and Daisy Zhe Wang. Drum: End-to-end differentiable rule mining on knowledge graphs. *arXiv preprint arXiv:1911.00055*, 2019.

[16] Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. In *7th International Conference on Learning Representations*, 2019.

[17] Kristina Toutanova, Danqi Chen, Patrick Pantel, Hoifung Poon, Pallavi Choudhury, and Michael Gamon. Representing text for joint embedding of text and knowledge bases. In *EMNLP*, pages 1499–1509. The Association for Computational Linguistics, 2015.

[18] Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In *International Conference on Machine Learning*, pages 2071–2080, 2016.

[19] Zhen Wang, Jianwen Zhang, Jianlin Feng, and Zheng Chen. Knowledge graph embedding by translating on hyperplanes. In *Twenty-Eighth AAAI Conference on Artificial Intelligence*, 2014.

[20] Han Xiao, Minlie Huang, Yu Hao, and Xiaoyan Zhu. Transg : A generative mixture model for knowledge graph embedding. *CoRR*, abs/1509.05488, 2015.

[21] Wenhan Xiong, Thien Hoang, and William Yang Wang. Deeppath: A reinforcement learning method for knowledge graph reasoning. In Martha Palmer, Rebecca Hwa, and Sebastian Riedel, editors, *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, EMNLP 2017, Copenhagen, Denmark, September 9-11, 2017*, pages 564–573. Association for Computational Linguistics, 2017.

[22] Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. Embedding entities and relations for learning and inference in knowledge bases. In *International Conference on Learning Representations*, 2015.

[23] Fan Yang, Zhilin Yang, and William W Cohen. Differentiable learning of logical rules for knowledge base reasoning. *arXiv preprint arXiv:1702.08367*, 2017.

[24] Wen Zhang, Bibek Paudel, Liang Wang, Jiaoyan Chen, Hai Zhu, Wei Zhang, Abraham Bernstein, and Huajun Chen. Iteratively learning embeddings and rules for knowledge graph reasoning. In *The World Wide Web Conference*, pages 2366–2377. ACM, 2019.

[25] Zhanqiu Zhang, Jie Wang, Jiajun Chen, Shuiwang Ji, and Feng Wu. Cone: Cone embeddings for multi-hop reasoning over knowledge graphs. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan, editors, *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pages 19172–19183, 2021.