# MultiTask Learning for accelerated-MRI Reconstruction and Segmentation of Brain Lesions in Multiple Sclerosis

## Abstract

This work proposes MultiTask Learning for accelerated-MRI Reconstruction and Segmentation (MTLRS). Unlike the common single-task approaches, MultiTask Learning identifies relations between multiple tasks to improve the performance of all tasks. The proposed MTLRS consists of a unique cascading architecture, where a recurrent reconstruction network and a segmentation network inform each other through hidden states. The features of the two networks are shared and implicitly enforced as inductive bias. To evaluate the benefit of MTLRS, we compare performing the two tasks of accelerated-MRI reconstruction and MRI segmentation with pre-trained, sequential, end-to-end, and joint approaches. A synthetic multicoil dataset is used to train, validate, and test all approaches. The dataset consists of 3D FLAIR brain data of relapsing-remitting Multiple Sclerosis patients with known white matter lesions. The acquisition is prospectively undersampled by approximately 7.5 times compared to clinical standards. Reconstruction performance is evaluated by Structural Similarity Index Measure (SSIM) and Peak Signal-to-Noise Ratio (PSNR). Segmentation performance is evaluated by Dice score for combined brain tissue and white matter lesion segmentation and by per lesion Dice score. Results show that MTLRS outperforms other evaluated approaches, providing high-quality reconstructions and accurate white matter lesion segmentation. A significant correlation was found between the performance of both tasks (SSIM and per lesion Dice score, $\rho = 0.92$, $p = 0.0005$). Our proposed MTLRS demonstrates that accelerated-MRI reconstruction and MRI segmentation can be effectively combined to improve performance on both tasks, potentially benefiting clinical settings.

**Keywords:** Multitask Learning, MRI, image reconstruction, segmentation, deep learning

## 1. Introduction

Acquisition, reconstruction, and analysis of Magnetic Resonance Imaging (MRI) are currently performed in a sequence of distinct tasks. Performing each task independently misses the opportunity to share valuable information between the tasks and jointly optimize their performance. MultiTask Learning (MTL) is a technique in which multiple domain-related tasks are trained in parallel using shared features, effectively acting as inductive bias. MTL can implicitly identify task-relatedness, yielding improved generalization (Caruana, 1997). By utilizing the information in multiple tasks, the performance of each task can be improved. Recently task-adapted reconstruction was proposed to combine reconstruction with related tasks (Adler et al., 2022) in different approaches.

In a pre-trained approach, a reconstruction network and a segmentation network are trained separately to perform the tasks individually. In a sequential approach, the segmentation network is fine-tuned using the predictions of the reconstruction network. In

an end-to-end approach, the reconstruction and the segmentation networks are trained together at the same time. For performing end-to-end accelerated-MRI reconstruction and MRI segmentation, Huang et al. (Huang et al., 2019) proposed the SEgmentation Recurrent Attention Network (SERANET), starting from the subsampled k-space to result in a segmentation. In a joint approach, the reconstruction and segmentation networks are trained end-to-end, computing a joint reconstruction and segmentation loss with a weighting factor balancing the two tasks. For performing the two tasks jointly, Sun et al. (Sun et al., 2019) proposed the SegNet, consisting of cascades of U-Nets for reconstruction and a separate decoder for segmentation, using the output of all the reconstruction encoders. Similarly, the Image Deep Structured Low-Rank (IDSLR) (Pramanik et al., 2021) and the RecSeg (Sui et al., 2021) methods perform joint reconstruction and segmentation. The IDSLR uses only the output of the final encoder for segmentation, while the RecSeg uses a second U-Net.

In this work, we formulate the inverse problem of accelerated-MRI reconstruction and the task of MRI segmentation as a multitask problem. In contrast to earlier methods, we show that performance on both tasks can be improved by informing each other through a recurrent approach. To this end, we leverage the Cascades of Independently Recurrent Inference Machines (CIRIM) (Karkalousos et al., 2022) for accelerated-MRI reconstruction and we add a segmentation network to the cascades to inform MultiTask Learning for accelerated-MRI Reconstruction and Segmentation (MTLRS). Following (Adler et al., 2022), the aim is to find a forward operator that directly maps accelerated-MR images to MRI segmentation. In MTLRS, this direct operator is modeled by coupling the output of the hidden layers of the reconstruction network with the output of the segmentation network. We develop and evaluate the proposed MLTRS on a synthetic multicoil dataset of 3D FLAIR data of relapsing-remitting Multiple Sclerosis patients with known white matter lesions.

## 2. Methods

### 2.1. MultiTask Learning for accelerated-MRI Reconstruction and Segmentation

The inverse problem of accelerated-MRI reconstruction can be formalized through a forward model. Let $x \in \mathbb{C}^n$ with $n = n_x \times n_y$, be a true image and let $y \in \mathbb{C}^m$, with $m << n$, be the set of sparse k-space measurements. The forward model describes $y$ as

$$y_i = A(x) + \sigma_i, i = 1, ..., c, \tag{1}$$

where $i$ denotes the current receiver coil, for a total of $c$ coils. $A : \mathbb{C}^n \mapsto \mathbb{C}^{n \times n_c}$ is the linear forward operator of accelerating MR acquisition, and $\sigma_i \in \mathbb{C}^n$ denotes the noise from the scanner for the $i - th$ coil. $A$ is given by $A = U \odot \mathcal{F} \odot \epsilon$, where $U$ denotes the subsampling operator and $\mathcal{F}$ the Fourier transform. $\epsilon : \mathbb{C}^n \times \mathbb{C}^{n \times n_c} \mapsto \mathbb{C}^{n \times n_c}$ is the expand operator, transforming $x$ into $x_c$ multicoil images, given by $\epsilon(x) = (S_0 \odot x, ..., S_x \odot x) = (x_0, ..., x_c)$ where $S$ denote the coil sensitivity maps. Subsequently, the backward operator for projecting the sparse k-space to image space is given by $A^* = r \odot \mathcal{F}^{-1} \odot U^T$, where $\mathcal{F}^{-1}$ denotes the inverse Fourier transform. $r : \mathbb{C}^{n \times n_c} \times \mathbb{C}^{n \times n_c} \mapsto \mathbb{C}^n$ is the reduce operator computing a coil-combined image given by $r(x_0, ..., x_c) = \sum_{i=1}^c S_i^H \odot x_i$, where $H$ denotes the Hermitian complex conjugate.

When solving the inverse problem of accelerated-MRI reconstruction, the $y \mapsto x$ mapping (Eq. 1) can be found through a Maximum A Posteriori (MAP) estimation, described by $x_{MAP} = \text{argmax}_x \{\log p(y|x) + \log p(x)\}$. MAP can be formulated as an optimization problem given by

$$x_{MAP} = \text{argmin}_x \left\{ \sum_{i=1}^{c} d(y_i, A(x)) + \lambda R(x) \right\}. \tag{2}$$

$d$ validates data consistency and $R$ is a regularizer, with $\lambda$ being a weighting factor, comprising prior knowledge over $x$. Assuming data are acquired under a Gaussian distribution and ignoring $R$, the (negative) log-likelihood is given by $\log p(y|x) = \frac{1}{\sigma^2}$. The gradient of the log-likelihood is then given by

$$\nabla_{y|x} := \frac{1}{\sigma^2} A^*(A(x) - y). \tag{3}$$

Formulating the MAP estimation into a non-convex optimization scheme (Andrychowicz et al., 2016) results in updates of the form

$$x_{\iota+1} = x_\iota + \theta_\phi\left(\nabla_{y|x_\iota}, x_\iota\right), \tag{4}$$

at iteration $\iota$, for total number of iterations $I$. $\theta_\phi$ explicitly models the update rule using a Recurrent Neural Network (RNN). Here, we use a learned inverse problem solver, the Cascades of Independently Recurrent Inference Machines (CIRIM) (Karkalousos et al., 2022). This physics-based RNN has been shown successful for reconstruction and may be naturally extended to MultiTask Learning.

By inserting Eq. 3 to Eq. 4, we obtain the update equations of the network for the first cascade

$$\begin{aligned} h_0^{k=1} &= 0, & \hat{x}_0^{k=1} &= A^*(y), \\ h_{\iota+1}^{k=1} &= \theta_\phi^*\left(\nabla_{y|\hat{x}_\iota}, \hat{x}_\iota, h_\iota\right), & \hat{x_{\iota+1}}^{k=1} &= \hat{x}_\iota + \theta_\phi\left(\nabla_{y|\hat{x}_\iota}, \hat{x}_\iota, h_{\iota+1}\right), \end{aligned} \tag{5}$$

where $\theta_\phi^*$ is the updated model for the hidden state variable $h$ and $k$ denotes the current cascade, for total $K$ cascades. For the rest $2 \leq k \leq K$ cascades, we extend the CIRIM by including a segmentation network and further informing it of the segmentation task described by

$$s = T(x), \tag{6}$$

where $T : x \mapsto s$ is the generic forward segmentation operator and can be replaced by any segmentation network.

MultiTask Learning for accelerated-MRI Reconstruction and Segmentation (MTLRS) is then realized by coupling the output of the hidden states with $s$, resulting in updates of the form

$$\begin{aligned} h_0^{k\geq2} &= \hat{x}_I^{k-1} * s^{k-1}, & \hat{x}_0^{k\geq2} &= \hat{x}_I^{k-1}, \\ h_{\iota+1}^{k\geq2} &= \theta_\phi^*\left(\nabla_{y|\hat{x}_\iota^k}, \hat{x}_\iota^k, \hat{x}_I^{k-1} * s^{k-1}\right), & \hat{x_{\iota+1}}^{k\geq2} &= \hat{x}_\iota^k + \theta_\phi\left(\nabla_{y|\hat{x}_\iota^k}, \hat{x}_\iota^k, h_{\iota+1}^k\right). \end{aligned} \tag{7}$$

In this way, the reconstruction informs the segmentation network, and vice versa. A schematic representation is shown in Fig. 1.

Figure 1: Schematic overview of the MultiTask Learning for accelerated-MRI Reconstruction and Segmentation (MTLRS) framework.

## 2.2. Loss function

The loss function in MTLRS is described by a joint reconstruction $L_{recon}(\hat{x}, x)$ and segmentation $L_{seg}(\hat{s}, s)$ loss. The joint loss is given by

$$L^{joint} = \frac{1}{N} \sum_{n=1}^{N} (1 - \alpha) L_{recon}(\hat{x}, x) + \alpha L_{seg}(\hat{s}, s), \qquad (8)$$

where $x$ is the ground truth image, $\hat{x}$ the predicted reconstruction, $s$ the ground truth segmentation label, and $\hat{s}$ the predicted segmentation. $\alpha$, with $0 \leq \alpha \leq 1$, is a weighting factor, balancing the influence of each task to the final loss.

$L^{recon}$ is usually computed on the magnitudes $x$ and $\hat{x}$, where $\hat{x_0} = A(y)$ is the initially zero-filled reconstruction. In the case of the $l_1$-norm, the loss is given by

$$L^{l_1}(x) = \frac{1}{N} \sum_{n=1}^{N} |\hat{x} - x|, \qquad (9)$$

where $n$ is the current batch and $N$ is the total number of training samples. For MTLRS, $L^{recon}$ is weighted over the number of recurrent iterations. Thus Eq. 9 is reformulated as

$$L^{l_1}(x) = \frac{1}{N} \sum_{n=1}^{N} \left( \frac{1}{qI} \sum_{\tau=1}^{I} w_\tau |\hat{x_\tau} - x| \right), \qquad (10)$$

where $q$ is the total number of pixels and $w_\tau$ a weighting vector of length $I$, to emphasize the loss at later recurrent iterations. The weights, for a total number of iterations $I$, are calculated as $w_\tau = 10^{-\frac{I-\tau}{I-1}}$.

For $L_{seg}$, we use a weighted combined binary cross-entropy and Dice loss

$$L_{seg} = \beta L^{CE} + \beta L^{Dice}, \tag{11}$$

where $L^{CE} = -\frac{1}{N} \sum_{n=1}^{N} s_n \ log \ \hat{s_n} + (1 - s_n) \ log \ (1 - \hat{s_n})$, $L^{Dice} = 1 - \frac{2 \sum_{n=1}^{N} \hat{s_n} s_n}{\sum_{n=1}^{N} \hat{s_n}^2 + \sum_{n=1}^{N} s_n^2}$, and $\beta$ is the weighting factor. In this work, we set $\beta = 0.5$ to balance the two losses equally.

## 2.3. Experiments

In our experiments, we evaluate the proposed MTLRS framework (Sec. 2.1) against performing the two tasks of accelerated-MRI reconstruction and segmentation in different approaches. In a pre-trained approach, we train a reconstruction and a segmentation network separately and then use them independently at inference. In a sequential approach, we fine-tune the pre-trained segmentation network on the outputs of the reconstruction network. In an end-to-end approach, we train the two networks simultaneously but only compute a segmentation loss. In a joint approach, the two networks are also trained end-to-end, but we compute a joint reconstruction and segmentation loss (Eq. 8). In these approaches, we choose the Cascades of Independently Recurrent Inference Machines (CIRIM) as the reconstruction network and the Attention-UNet (Oktay et al., 2018) as the segmentation network, which empirically have been found to be well-performing models for each task.

Additionally, we compare the performance of our method with previously published methods. For this purpose, we implemented the end-to-end approach SEgmentation Recurrent Attention Network (SERANET) (Huang et al., 2019), and the joint approaches, RECSEGNET (Sui et al., 2021), Image Deep Structured Low-Rank (IDSLR) (Pramanik et al., 2021), and SEGNET (Sun et al., 2019).

All models were trained and tested on an Nvidia Tesla V100 GPU with 32GB memory. The hyperparameter settings for all methods can be found in the Appendix. The code is publicly available at *****.

## 2.4. Dataset

A clinical dataset was used to train, validate, and test all methods. The dataset consisted of 3D FLAIR coil-combined magnitude brain images of 19 relapsing-remitting Multiple Sclerosis (MS) patients with white matter lesions. Data were acquired on a 3.0T scanner in our hospital. The local ethics review board approved this study, and the patients provided informed consent. Prospective undersampling was performed, accelerating imaging approximately 7.5 times under a Variable-Density Poisson disk distribution. Coil sensitivity maps were estimated using the caldir method of the BART toolbox (Uecker et al., 2015) on a fully-sampled reference.

The coil-combined magnitude images were used to synthesize multicoil complex data. To this end, we used a pre-trained CIRIM model trained only for reconstruction on 2D multislice FLAIR data (Muckley et al., 2021), accelerated approximately eight times under a Variable-Density Poisson disk distribution. Minimal random gaussian noise was added to the synthetic data, with a relative weighting factor of $10^{-5}$. Data were then retrospectively accelerated by approximately 7.5 times under a Variable-Density Poisson disk distribution. Next, we used the reconstructed images to predict two segmentation classes, brain tissue

(combined white and gray matter) and white matter lesions, as a reference standard for MRI segmentation. To obtain brain tissue segmentations, we used the statistical parametric mapping (SPM) toolbox (Penny et al., 2007). To obtain white matter lesion segmentations, we used a pre-trained network for eye and tumor segmentation of retinoblastoma patients (Strijbis et al., 2021). Finally, thirteen patients were included in the training set, three in the validation set, and three in the test set.

## 2.5. Evaluation

For evaluating reconstruction, we compute Structural Similarity Index Measure (SSIM) (Wang et al., 2004) and Peak Signal-to-Noise-Ratio (PSNR) on the normalized magnitude images between the synthesized ground truth $x$ and the prediction $\hat{x}$. SSIM and PSNR are first computed per slice and per plane for each subject and then averaged to evaluate the reconstruction performance as a 3D volume. To evaluate segmentation, we calculate the Dice score as an overlap metric between the standard $s$ and the prediction $\hat{s}$. Dice score is reported for the combined (white and gray matter) tissue and white matter lesion segmentation and for only the white matter lesion segmentation. Dice scores are computed across all planes and slices for all subjects. To assess whether a correlation in performance between both tasks exists, we correlated SSIM and per lesion Dice scores using Spearman's rank test.

## 3. Results

Figure 2 shows an overall comparison of MTLRS to the Pre-Trained, Sequential, End-to-End, and Joint approaches. Note that the Sequential and the End-to-End approach are optimized only for segmentation. Therefore, for these approaches, SSIM and PSNR scores are not reported. The results show that MTLRS performed best on both reconstruction and segmentation. The Pre-Trained approach performed better than the Joint approach on reconstruction but worse on segmentation. The Sequential approach performed on par with the Pre-Trained approach, showing no apparent benefit when further optimizing the segmentation model on the reconstructed outputs. The End-to-End approach performed worst, indicating the need for a joint loss rather than only segmentation loss.

Table 1 reports the performance of MTLRS and the evaluated previously published methods when performing the two tasks of accelerated-MRI reconstruction and MRI segmentation. In both tasks, MTLRS outperformed the RECSEGNET, IDSLR, SEGNET, and SERANET, showing a clear advantage for the multitask approach.

Figure 3 shows an example of a reconstructed and segmented axial slice by MTLRS and the evaluated previously published methods. MTLRS provided the highest reconstruction quality (SSIM) and the most accurate lesion segmentation (Dice). The RECSEGNET performed comparably with MTLRS in reconstruction, while the IDSLR and SEGNET reduced reconstruction performance further. The SERANET was the worst-performing method in reconstruction. Segmentation performance was significantly worse on all methods compared to MTLRS.

SSIM and lesions Dice scores were significantly correlated ($\rho = 0.92$, $p = 0.0005$). More examples of reconstructions and segmentations can be found in the Appendix.

Figure 2: Quantitative evaluation when performing accelerated-MRI reconstruction and MRI segmentation with different approaches (x-axis). Metrics are computed on the test set with an acceleration factor of 7.5 to undersample data retrospectively. Reconstruction is evaluated by SSIM and PSNR (top). Segmentation is evaluated by DICE and DICE lesions (bottom). The y-axis reports the evaluation metrics (SSIM on top-left, PSNR on top-right, DICE on bottom-left, and DICE lesions on bottom-right).

Table 1: Overall comparison of MTLRS to previously published methods when performing the two tasks of accelerated-MRI reconstruction and MRI segmentation. SSIM, PSNR, DICE, and DICE Lesions are computed on the test set using an acceleration factor of 7.5 to undersample data retrospectively. The arrow pointing upward indicates higher is better. Methods are sorted by DICE, while the best-performing method is shown in bold.

| Method | SSIM ↑ | PSNR ↑ | DICE ↑ | DICE Lesions ↑ |
|---|---|---|---|---|
| MTLRS | **0.927 ± 0.027** | **34.62 ± 1.95** | **0.704 ± 0.094** | **0.596 ± 0.031** |
| RECSEGNET | 0.760 ± 0.070 | 28.18 ± 1.79 | 0.628 ± 0.105 | 0.284 ± 0.045 |
| IDSLR | 0.729 ± 0.053 | 26.34 ± 1.28 | 0.624 ± 0.100 | 0.257 ± 0.020 |
| SERANET | | | 0.618 ± 0.121 | 0.248 ± 0.098 |
| SEGNET | 0.700 ± 0.046 | 25.53 ± 1.10 | 0.610 ± 0.101 | 0.208 ± 0.034 |

Figure 3: Reconstruction and segmentation of an axial slice with white matter lesions. An acceleration factor of approximately 7.5 was used to undersample the data retrospectively (top-second column). Methods are sorted by SSIM. SSIM is computed for evaluating reconstruction performance against the ground truth (top-first column). The per lesions Dice score is computed to evaluate segmentation performance against the reference labels (bottom-first column).

## 4. Discussion & Conclusion

We proposed MultiTask Learning for accelerated-MRI Reconstruction and Segmentation (MTLRS). MultiTask Learning was realized through a unique cascading network architecture consisting of a recurrent reconstruction network and segmentation network. The output of the hidden layers was combined with the segmented images to inform a sequence of cascades, thus serving as an inductive bias. MTLRS outperformed existing methods (IDSLR, SEGNET, RECSEGNET, SERANET) on both reconstructing 7.5 times accelerated 3D FLAIR brain data of Multiple Sclerosis patients and on segmenting white matter lesions identified on this data. However, MTLRS improved marginally over the pre-trained, sequential, and joint approaches. The reason could lie in the fact that the same pre-trained reconstruction model was used in all these methods and in synthesizing the multicoil dataset. Therefore, future work will evaluate our method on a dataset where fully sampled reference data is available, e.g., knee data from the recently held KS-challenge (Bharadwaj et al.). Interestingly, a strong correlation was found between the quality metrics of both tasks. The results suggest that improved dealiasing during reconstruction leads to improved contrast and better-defined lesion boundaries, thereby supporting a more accurate segmentation. In future work, more tasks can be combined, such as classifying the underlying pathologies and improving performance by informing each other. Thus, MultiTask Learning is yet to be further explored, with potentially a high value if applied in the clinical setting, where aside from improving performance, the need for waiting time between multiple tasks would not be needed.

## Acknowledgments

Acknowledgments withheld.

## References

Jonas Adler, Sebastian Lunz, Olivier Verdier, Carola Bibiane Schönlieb, and Ozan Öktem. Task adapted reconstruction for inverse problems. *Inverse Problems*, 38, 7 2022. ISSN 13616420. doi: 10.1088/1361-6420/ac28ec.

Marcin Andrychowicz, Misha Denil, Sergio Gómez Colmenarejo, Matthew W. Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. *Advances in Neural Information Processing Systems*, pages 3988–3996, 2016. ISSN 10495258.

Upasana Bharadwaj, Aniket Tolpadi, and Valentina Pedoia Pedoia. URL https://k2s.grand-challenge.org.

Rich Caruana. Multitask Learning. *Machine Learning*, 28:41–75, 1997. doi: https://doi.org/10.1023/A:1007379606734.

Qiaoying Huang, Xiao Chen, Dimitris Metaxas, and Mariappan S. Nadar. Brain Segmentation from k-space with End-to-End Recurrent Attention Network. volume 11766 LNCS, pages 275–283. Springer Science and Business Media Deutschland GmbH, 2019. ISBN 9783030322472. doi: 10.1007/978-3-030-32248-9_31.

Dimitrios Karkalousos, Samantha Noteboom, Hanneke E Hulst, Frans M Vos, and Matthan W A Caan. Assessment of data consistency through cascades of independently recurrent inference machines for fast and robust accelerated MRI reconstruction. *Physics in Medicine & Biology*, 5 2022. ISSN 0031-9155. doi: 10.1088/1361-6560/AC6CC2.

M.J. Muckley, B. Riemenschneider, A. Radmanesh, S. Kim, G. Jeong, J. Ko, Y. Jun, H. Shin, D. Hwang, M. Mostapha, S. Arberet, D. Nickel, Z. Ramzi, P. Ciuciu, J. Starck, J. Teuwen, D. Karkalousos, C. Zhang, A. Sriram, Z. Huang, N. Yakubova, Y.W. Lui, and F. Knoll. Results of the 2020 fastMRI Challenge for Machine Learning MR Image Reconstruction. *IEEE Transactions on Medical Imaging*, 2021. ISSN 1558254X. doi: 10.1109/TMI.2021.3075856.

Ozan Oktay, Jo Schlemper, Loic Le Folgoc, Matthew Lee, Mattias Heinrich, Kazunari Misawa, Kensaku Mori, Steven McDonagh, Nils Y Hammerla, Bernhard Kainz, Ben Glocker, and Daniel Rueckert. Attention U-Net: Learning Where to Look for the Pancreas. 4 2018. doi: 10.48550/arxiv.1804.03999. URL https://arxiv.org/abs/1804.03999v3.

William Penny, Karl Friston, John Ashburner, Stefan Kiebel, and Thomas Nichols. *Statistical Parametric Mapping: The Analysis of Functional Brain Images*. Elsevier, 2007. ISBN 9780123725608. doi: 10.1016/B978-0-12-372560-8.X5000-1. URL https://linkinghub.elsevier.com/retrieve/pii/B9780123725608X50001.

Aniket Pramanik, Xiaodong Wu, and Mathews Jacob. Joint Calibrationless Reconstruction and Segmentation of Parallel MRI. 5 2021. URL http://arxiv.org/abs/2105.09220.

Victor I. J. Strijbis, Christiaan M. de Bloeme, Robin W. Jansen, Hamza Kebiri, Huu-Giao Nguyen, Marcus C. de Jong, Annette C. Moll, Merixtell Bach-Cuadra, Pim de Graaf, and Martijn D. Steenwijk. Multi-view convolutional neural networks for automated ocular structure and tumor segmentation in retinoblastoma. *Scientific Reports*, 11:14590, 12 2021. ISSN 2045-2322. doi: 10.1038/s41598-021-93905-2. URL https://doi.org/10.1038/s41598-021-93905-2http://www.nature.com/articles/s41598-021-93905-2.

Bin Sui, Jun Lv, Xiangrong Tong, Yan Li, and Chengyan Wang. Simultaneous image reconstruction and lesion segmentation in accelerated MRI using multi-tasking learning. *Medical Physics*, 48:7189–7198, 11 2021. ISSN 2473-4209. doi: 10.1002/MP.15213. URL https://onlinelibrary.wiley.com/doi/full/10.1002/mp.15213https://onlinelibrary.wiley.com/doi/abs/10.1002/mp.15213https://aapm.onlinelibrary.wiley.com/doi/10.1002/mp.15213.

Liyan Sun, Zhiwen Fan, Xinghao Ding, Yue Huang, and John Paisley. Joint Cs-MRI Reconstruction and Segmentation with a Unified Deep Network. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 11492 LNCS:492–504, 5 2019. ISSN 16113349. doi: 10.1007/978-3-030-20351-1_38. URL https://arxiv.org/abs/1805.02165v1.

Zhou Wang, Alan Conrad Bovik, Hamid Rahim Sheikh, and Eero P. Simoncelli. Image quality assessment: From error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13:600–612, 2004. ISSN 10577149. doi: 10.1109/TIP.2003.819861.

## Appendix

### Hyperparameters

In our experiments, we set the hyperparameters of the related compared work according to what is reported by the authors in the original work.

For the CIRIM, we set the number of features to 64 for the convolutional and recurrent layers, cascades to 5, and recurrent iterations to 8. For the AttentionUNet, we set the number of features to 64, pooling layers to 2, and dropout to 0. For the SERANET, we chose the U-Net as the reconstruction network. We set the number of features to 32, pooling layers to 4, and dropout to 0 for the reconstruction, segmentation, and recurrent modules, and built three reconstruction blocks. For the RECSEGNET and the IDSLR, we set the number of features to 64, pooling layers to 2, and dropout to 0. For the IDSLR, the number of iterations was set to 5. $\alpha$ was set to 0.5 for the RECSEGNET and $10e - 6$ for IDSLR. Finally, for the SEGNET, we set the number of features to 64, pooling layers to 2, dropout to 0, and cascades to 5.

For finding the optimal value for $\alpha$ in the joint loss for MTLRS (Eq. 8), we performed a hyperparameter search as presented in Figure 4. The tested values are $0.01, 0.1, 0.5, 0.9, 0.99$, going from favoring the reconstruction loss to balancing the loss to favoring the segmentation loss. The optimal $\alpha$ value was found to be 0.9.

We used ADAM as optimizer for all methods and set the learning rate to $10^{-4}$.

Figure 4: Hyperparameter search for finding the optimal $\alpha$ value in the joint loss (Eq. 8). Reconstruction and segmentation performance are realized on an SSIM (x-axis) over Dice (y-axis) plot. From left to right. The $*$ indicates the value resulting in the best SSIM & Dice scores.

### Overview examples

Figures 5 and 6 show examples of reconstructed and segmented slices of the coronal and sagittal view, with white matter lesions identified in all slices. An acceleration factor of approximately 7.5 was used to undersample the data retrospectively. MTLRS provided the highest reconstruction quality (SSIM) and the most accurate lesions segmentation (Dice) in

all cases. The RECSEGNET dropped significantly both in SSIM and Dice score by oversimplifying the reconstruction and slightly overestimating lesion volume. The same behavior is observed by the IDSLR and the SEGNET, reducing performance further. The SERANET performed poorly on reconstruction, while segmentation performance was comparable or better to the RECSEGNET, IDSLR, and SEGNET.

Figure 5: Reconstruction and segmentation of a coronal slice with white matter lesions. An acceleration factor of approximately 7.5 was used to undersample the data retrospectively (top-second column). Methods are sorted by SSIM. SSIM is computed for evaluating reconstruction performance against the ground truth (top-first column). The per lesions Dice score is computed to evaluate segmentation performance against the reference labels (bottom-first column).

Figure 6: Reconstruction and segmentation of a sagittal slice with white matter lesions. An acceleration factor of approximately 7.5 was used to undersample the data retrospectively (top-second column). Methods are sorted by SSIM. SSIM is computed for evaluating reconstruction performance against the ground truth (top-first column). The per lesions Dice score is computed to evaluate segmentation performance against the reference labels (bottom-first column).