REBOOT: Reuse Data for Bootstrapping Efficient Real-World Dexterous Manipulation

Abstract: Dexterous manipulation tasks involving contact-rich interactions pose a significant challenge for both model-based control systems and imitation learning algorithms. The complexity arises from the need for multi-fingered robotic hands to dynamically establish and break contacts, balance non-prehensile forces, and control large degrees of freedom. Reinforcement learning (RL) offers a promising approach due to its general applicability and capacity to autonomously acquire optimal manipulation strategies. However, its real-world application is often hindered by the necessity to generate a large number of samples, reset the environment, and obtain reward signals. In this work, we introduce an efficient system for learning dexterous manipulation skills with RL to alleviate these challenges. The main idea of our approach is the integration of recent advancements in sample-efficient RL and replay buffer bootstrapping. This unique combination allows us to utilize data from different tasks or objects as a starting point for training new tasks, significantly improving learning efficiency. Additionally, our system completes the real-world training cycle by incorporating learned resets via an imitation-based pickup policy as well as learned reward functions, eliminating the need for manual resets and reward engineering. We demonstrate the benefits of reusing past data as replay buffer initialization for new tasks, for instance, the fast acquisition of intricate manipulation skills in the real world on a four-fingered robotic hand. (Videos: https://sites.google.com/view/reboot-dexterous)

Keywords: Dexterous Manipulation, Reinforcement Learning, Sample-Efficient

1 Introduction

Dexterous manipulation tasks involving contact-rich interaction, specifically those involving multi-fingered robotic hands and underactuated objects, pose a significant challenge for both model-based control systems and imitation learning algorithms. The complexity arises from the need for multi-fingered robotic hands to dynamically establish and break contacts, balance non-prehensile forces, and control a high number of degrees of freedom. Reinforcement learning (RL) offers a promising solution for such settings. In theory, RL empowers a robot to refine its manipulation skills and balance contact forces adeptly through a process of trial-and-error, alleviating the requirement for strong modeling assumptions. However, making RL methods practical for learning such complex behaviors directly in the real world presents a number of obstacles. The main obstacle is sample efficiency: particularly for tasks that require complex interactions with many possibilities for failure (e.g., in-hand reorientation where the robot might drop the object), the number of trials needed for learning a skill with RL from scratch might be very high, requiring hours or even days of training. Additionally, real-world learning outside of the lab requires the robot to perform the entire training process using its own sensors and actuators, evaluating object state and rewards using camera observations, and resetting autonomously between trials. Because of these challenges, many prior works on RL for dexterous manipulation have explored alternative solutions, such as sim-to-

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

Figure 1: **REBOOT** System Overview: Our method learns various dexterous manipulation skills in the real world using raw image observations. This is enabled by using sample-efficient RL and bootstrapping with data from other tasks and even other objects, with autonomous resets.

real transfer [1, 2, 3], imitation learning [4, 5, 6], or the use of tools like motion capture [7, 2] or separately-engineered reset mechanisms [8, 9].

In this paper, we instead propose a system that is designed to make direct RL in the real world practical without these alternatives, so as to take a step toward robots that could one day learn under assumptions that are sufficient for autonomously acquiring new skills in open-world settings, potentially even outside the laboratory. This means that the entire learning process must be conducted using the robot's own sensors and actuators, without simulation or additional instrumentation, and be efficient enough to learn skills quickly. We believe that a key enabling factor for this goal is to reuse data from past skills, and we instantiate this with a simple buffer initialization method, where the replay buffer of each skill is initialized with data from other tasks or even other objects. In combination with a vision-based method for learning reward functions from user-provided images and a learned reset procedure to automatically pick

Figure 2: **REBOOT**: Our method utilizes an autonomous reset pipeline to train in-hand manipulation policies, where the reset and in-hand manipulation policies alternate in a forward-backward fashion.

up an object between trials, we demonstrate that our system enables a robotic hand to learn in-hand reorientation skills in just a few hours of fully autonomous training, using only camera observations and joint encoder readings.

Our main contribution is **REBOOT**, a system to **Re**use Data for **Boot**strapping Real-World Dexterous Manipulation, which we illustrate in Figure 1. By simply preloading the replay buffer using prior data from other objects and tasks, our system avoids starting from scratch for every new task. By combining recent advances in sample-efficient online RL [10] with buffer initialization to bootstrap learning from prior tasks and objects, we show that in-hand manipulation behaviors can be learned in a few hours of autonomous practicing. We additionally use learned reset skills to make training autonomous, and extend adversarially learned rewards to handle our buffer initialization method, allowing users to specify tasks with a few examples of desired object poses and without manual reward engineering. Some of the skills learned by our system, shown in Figure 3, include in-hand reorientation of a three-pronged object, handling a T-shaped pipe, and manipulating a toy football.

2   Related Work

A number of designs for anthropomorphic hands have been proposed in prior work [11, 12, 13]. Prior learning-based methods to control such hands utilize trajectory optimization [14, 15], policy search [16, 17, 18], demonstration-based learning [19, 20, 21, 22], simulation to real-world transfer [3, 23, 24, 25], reinforcement learning directly in the real world [26, 8, 27, 28, 29], or a combination of these approaches [30].

Most of the aforementioned works leveraged accurate simulations or engineered real-world state-estimation systems to provide compact state representations. In contrast, we seek to learn visuomotor policies autonomously and entirely in the real world without access to privileged state information, under assumptions that more closely reflect what robots might encounter when learning "on the job" outside of laboratory settings. Prior work has explored learning these policies in simulation [31, 32], where autonomy is not of concern due to the ability to reset the simulated environment. Most real-world methods either rely on instrumentation for state estimation [28] or deal with simpler robots and tasks [27]. An important consideration in our system is the ability to specify a task without manual reward engineering. Although task specification has been studied extensively, most prior works make a variety of assumptions, ranges from having humans-provided demonstrations for enabling imitation learning [4, 33, 34], using inverse RL [35, 36, 37], active settings where users can provide corrections [38, 39, 40], or ranking-based preferences [41, 42]. Our in-hand RL training phase learns from raw high-dimensional pixel observations in an end-to-end fashion using DrQ[43] and VICE[44], although our system could use any reward inference algorithm based upon success examples [45]. With users defining the manipulation task by providing a small number of image goals instead of full demonstrations, our method not only removes the barrier to orchestrate high-dimensional finger motions [46, 47] but also accelerates robot training progress by offering sufficient reward shaping for RL in real-world scenarios without per-task reward engineering. While AVAIL [29] also learns dexterous manipulation skills from raw images, we show in our comparison that our system is faster, and our buffer initialization approach significantly speeds up the acquisition of in-hand manipulation skills compared to starting from scratch.

Buffer initialization has also been employed by Smith et al. [48] in the context of transfer learning for robotic locomotion, where a similar approach was used to create a curriculum for locomotion skills or adapt to walking on new terrains. Our method differs in several significant ways. First, our method learns from raw image observations with learned reward functions defined through a few example images, whereas [48] uses hand-programmed rewards. Second, our focus is on learning intricate dexterous manipulation skills from scratch in the real world, whereas [48] uses initialization in simulation. Although the methodology is closely related, our proposed system extends the methodology in significant ways, enabling the use of vision and learned rewards in a very different domain.

Reset-free learning is essential for autonomous real-world training of dexterous skills (see [49] for a review of reset-free methods). Most of the prior works [27, 28, 29, 50, 51, 52, 53, 54] rely on "'backward" policies to reset the environment so the "forward" policy can continue learning the task of interest. Similarly, we divide training into two phases due to different skills having unique demands for control complexities and user-provided supervision. Specifically, the skill needed to pick up objects in reset is better studied and developed for immediate usage through imitating user-provided demonstrations [55].

3   Robot Platform and Problem Overview

In this work, we use a custom-built, 4-finger, 16-DoF robot hand mounted to a 7-DoF Sawayer robotic arm for dexterous object manipulation tasks. Our platform is shown in Figure 3. Our focus is on learning in-hand reorientation skills with reinforcement learning. During the in-hand manipulation phase, the RL policy controls the 16 degrees of freedom of the hand, setting target positions at 10 Hz, with observations provided by the joint encoders in the finger motors and two RGB cameras,

one overhead and another embedded in the palm of the hand. To facilitate autonomous training, we also use imitation learning to learn a reset policy to pick up the object from the table in-between in-hand manipulation trials. This imitation policy uses a 19-dimensional action space, controlling the end effector position of the wrist and 16 finger joints to pick up the object from any location.

Our tasks are parameterized by images of desired object poses in the palm of the hand. Since the reset policy can grasp the object in a variety of poses, the in-hand policy must learn to rotate and translate the object carefully to achieve the goal pose. We train and evaluate our method entirely in the real world. In the following sections, we describe how data from different objects can be used to bootstrap new manipulation skills for more efficient learning.

Figure 3: Depiction of our hardware platform and tasks. **(a)** custom-built 16 DoF robotic hand **(c)** tele-operation using the 3-D mouse, to interact with the following objects in-hand **(b)** blue football, **(d)** 3-pronged valve, **(e)** T-shaped pipe.

4 Reinforcement Learning with Buffer Initialization

In this work, we propose a system for efficiently learning visuomotor policies for dexterous manipulation tasks via bootstrapping with prior data. We describe our learning method and real-world considerations for our system in the following subsections.

Problem setting. Our method leverages the framework of Markov decision processes for reinforcement learning as described in [56]. In RL, the aim is to learn a policy $\pi(a_t|s_t)$ that obtains the maximum expected discounted sum of rewards $R(s_t, a_t)$ under an initial state distribution ρ_0, dynamics $\mathcal{P}(s_{t+1}|s_t, a_t)$, and discount factor γ. The formal objective is as follows:

$$J(\pi) = \mathbb{E}_{\substack{s_0 \sim \rho_0 \\ a_t \sim \pi(a_t|s_t) \\ s_{t+1} \sim \mathcal{P}(s_{t+1}|s_t, a_t)}} \left[\sum_{t=0}^{T} \gamma^t R(s_t, a_t) \right] \tag{1}$$

The particular reinforcement learning algorithm that we build on in this work is RLPD [10], a sample-efficient RL method that combines a design based on soft actor-critic (SAC) [57] with a number of design decisions to enable fast training. This approach trains a value function $Q^{\pi}(s_t, a_t)$ in combination with an actor or policy $\pi(a_t|s_t)$, though in principle our system could be compatible with a variety of off-policy RL algorithms that utilize a replay buffer. For more details on RLPD, we refer readers to prior work [10].

Reinforcement learning with buffer initialization. While using a sample-efficient RL algorithm such as RLPD to acquire in-hand manipulation skills can be feasible in the real world, the training process can take a very long time (see Section 5). A central component of our system design is to utilize data from other tasks or even other objects to bootstrap acquisition of new in-hand manipulation skills. In our experiments, we will show that a very simple procedure can make this possible: for every RL update, we sample half the batch from the growing buffer for the current task, and half the batch from a buffer containing the experience from all of the prior tasks. Thus, if $n - 1$ skills have been learned, to learn a new nth skill, we pre-load the replay buffer with trajectories from each of the $n - 1$ prior skills and sample half of each training batch from prior data and the other half from the new agent's online experience. This 50-50 sampling method has been used in some prior works, including RLPD [10, 58], in order to initialize online RL with offline data from *the same task*. However, in our system, we adapt this procedure to bootstrap a behavior from *other*

skills. Since all of the tasks use visual observations, the generalization ability of the value function and policy networks can then learn to make use of this prior experience to assist in learning the new task. Note that it is not at all obvious that prior experience like this should be directly useful, as other tasks involve visiting very different states or manipulating different objects. However, if the networks are able to extract for example a general understanding of contacts or physical interactions, then we would expect this to accelerate acquisition of the new task.

Demonstration-based reset-free learning. In-between in-hand manipulation trials, the robot may drop the object and need to pick it back up again to attempt the task again. To automate training, we must also acquire an autonomous pick-up policy to serve as a reset mechanism for the in-hand task, retrieving objects that may have fallen out of the hand during in-hand manipulation. We observe that the reset task is composed of essentially the same reaching, power grasping, and lifting up skills across different objects. Unlike complex manipulation tasks in the in-hand phase, a human operator can provide demonstrations for these skills more conveniently and effectively, overcoming the wide initial state distribution issue due to the fact that objects can fall to anywhere in the environment. As shown in prior work [27], exploration is especially challenging for RL in such settings. Thus, we use behavioral cloning (BC) to train policies for the reset phase from simple demonstrations provided with a 3D mouse and a discrete finger closing command.

Reward learning via goal images with buffer initialization. Our aim is to enable our system to learn under assumptions that are reasonable outside of the laboratory: the robot should use the sensors and actuators available to it for all parts of the learning process, including using an autonomous reset policy and eschewing ground truth state estimation (e.g., motion capture) in favor of visual observations that are used to train an end-to-end visuomotor policy. However, this requires us to be able to evaluate a reward function for the in-hand RL training process from visual observations as well, which is highly non-trivial. We therefore use an automated method that uses goal *examples* provided by a person (e.g., positioning the object into the desired pose and placing it on the hand) to learn a success classifier, which then provides a reward signal for RL. Thus, for each in-hand manipulation task $\mathcal{T}_i$, we assume a set $\mathcal{G}_i$ consisting of a few goal images depicting the successful completion of the task. Naïvely training a classifier and using it as a reward signal is vulnerable to exploitation, as RL can learn to manipulate the object so as to fool the classifier [44]. We therefore adapt VICE [44] to address this challenge, which trains an adversarial discriminator pre-defined goal images as positives ($y = 1$) and observation samples from the replay buffer as negatives ($y = 0$). However, it is necessary to adapt this method to handle our buffer initialization approach, since VICE is by design an on-policy [44]. We first summarize the VICE algorithm and the regularization techniques we employ to make it practical for vision-based training, and then discuss how we adapt it to handle buffer initialization.

A common issue with adversarial methods such as VICE is instability and mode collapse. We found strong regularization techniques based on mixup [59] and gradient penalty [60] to be essential to stabilize VICE for learning image-based tasks, and these regularizers additional aid the RL process by causing the classifier to produce a smoother, more shaped reward signal. The classifier predicts $\log p_o(s_t)$, the log-probability that the state s_t corresponds to the goal, which can then be used as a reward signal for RL training. The final VICE classifier $D_\theta(x)$'s learning objective is optimized by minimizing a regularized discriminator loss:

$$\mathcal{L}(\theta) = \lambda \cdot \mathcal{L}_\lambda(\theta) + (1 - \lambda) \cdot \mathcal{L}_{1-\lambda}(\theta) + \alpha(\|\nabla_{\hat{x}} D_\theta(\hat{x})\|_2 - 1)^2 \tag{2}$$

where $\mathcal{L}_\lambda$ and $\mathcal{L}_{1-\lambda}$ are the Binary Cross Entropy (BCE) loss terms for mixup samples and labels, $\alpha = 10$ is the weight for Gradient Penalty loss, and $\hat{x}$ is the linearly interpolated samples used in computing Gradient Penalty.

Applying this method with buffer initialization, where prior data from other tasks and objects is included in the replay buffer, requires additional care. Naïvely, if we train a new VICE classifier with user-provided goal images for the current task as positives, then almost all previous experiences from other tasks and objects is likely to be assigned a negligible reward during training, which would

Figure 4: Film strips showing successful rollouts of in-hand object manipulation policies for the three objects: purple 3-pronged object (Pose B), black T-shaped pipe, and blue football. The boxes on the right (outlined in green) are examples of user-collected goal images for each task indicating the desired pose. Note that the autonomous pickup policy picks up the object in a variety of different poses across episodes, requiring the in-hand manipulation skill to reorient it into the target pose from many starting configurations.

not result in beneficial learning signals for the RL agent. Instead, for each task in the prior dataset, rewards are labeled using a task-specific VICE classifier which was trained when that data was collected *for its own task*. These classifier rewards are computed and saved prior to training a new skill, and they remain static throughout training, in contrast to the rewards for online data which depend on the changing VICE classifier.

Intuitively, for all objects, we want the RL agent to learn useful finger gaits and behaviors such as not dropping and making frequent contact with the object. If there exist similarities/structure across objects regarding these behaviors, training a policy to maximize reward for one object/task may produce skills which are somehow useful for another object/task. This structure can be leveraged to improve sample-efficiency by training a policy which maximizes reward for multiple tasks simultaneously, which is effectively what we do when utilizing prior data statically labeled by trained VICE classifiers.

5 Experimental Results

In our experiments, we aim to answer the following questions:

1. Can our system learn dexterous manipulation skills autonomously in the real world?

2. Can prior data from one object improve the sample efficiency of learning new skills with the same object?

3. Can data from different objects be transferred to enable faster acquisition of skills with new objects?

We perform experiments with 3 objects of various shapes and colors: a purple 3-pronged object, a black T-shaped pipe, and a blue football. For each manipulation task, we collected a set of 400 goal images by placing the object in the palm of the hand in the desired pose, closing the fingers for 1 second, and executing random actions for 1.5 seconds. We repeated this procedure multiple times, collecting 25 goal images per iteration until we reach 400 total images.

We also provided demonstrations per-object for the reset policy. We began with the 3-prong object for which we collected 160 demonstrations for the reset policy. We provided only 30 additional demonstrations per new object, for a total of 220 reset demonstrations across all objects. This was sufficient to train a universal reset policy for all objects with a high enough success rate to enable in-hand training. Each demonstration takes roughly 30 seconds to collect, totaling less than 2 hours to collect the necessary demonstrations. Please check our website https://sites.google.com/view/reboot-dexterous for videos and further experimental details.

(a) Learning curve showing the performance as a function of training time of reorienting the 3-prong objects into different poses. Even though both our method and training from scratch eventually reach a success rate of 80%, our method gets there about two times faster.

(b) Bar plot displaying the training time required for each object to reach their respective target performance. Buffer initialization leads to more than a **2x** speedup across all of the objects compared to training from scratch.

Figure 5: Evaluation plots showing the performance of checkpoints at different points in training (left) and the amount of time needed to reach specific levels of performance (right).

Task transfer. To answer Question 1, we evaluated our method on each of the 3 objects with varying amounts of prior data. We first trained a 3-prong object manipulation policy (for a goal pose we call Pose A, shown in Figure 6) without prior data in order to gather data to initialize training for subsequent objects/tasks. We then trained another 3-prong manipulation policy for a different goal pose (Pose B, shown in Figure 4) as well as a T-pipe manipulation policy, both using prior data from the first 3-prong experiment. Finally, we trained a football manipulation policy using the 3-prong and T-pipe experiments as prior data. Our method's success rate is shown in Figure 5, and film strips of various manipulation policy successes during training are shown in Figure 4. Our behavior-cloned reset policy was sufficient as a reset mechanism for in-hand training. Furthermore, our in-hand policies are able to successfully pose the 3-prong and T-pipe objects more than 50% of the time.

Figure 6: Pose A for the 3-pronged object.

To answer Question 2, we consider the Pose B 3-prong experiment described previously. Since Pose A and B are both 3-prong poses offset by about 60°, we expect the task difficulty to be similar for both poses. A comparison between training Pose A from scratch and training Pose B with a pre-loaded replay buffer is shown in Figure 5a. The Pose B experiment with our method outperforms the Pose A experiments training from scratch in terms of training time. Our method reaches 80% success in around 6 hours while training from scratch yields poor performance at that point. It takes more than 10 hours for learning from scratch to achieve a comparable success rate. This suggests that our method can significantly reduce training time when using prior data from the same object for a new manipulation task.

Object transfer. To answer Question 3, we consider the T-pipe and football experiments described above. We compare our method to learning from scratch without prior data and display the results in

(a) Caption of First Image   (b) Caption of Second Image

Figure 7: Learning curve showing the performance as a function of training time for the T-pipe and football objects. In both cases, buffer initialization is about two times faster than learning from scratch, though particularly the football object is harder to reorient for all methods.

Figure 7. Our method with prior data from other objects is clearly significantly faster than learning from scratch for both objects. For the T-pipe experiments, our method achieves a 60% success rate at 6 hours compared to 13 hours for training from scratch. Furthermore, the from-scratch runs have absolutely no success in evaluation prior to 5 hours of training, while our method achieves some initial success as early as 1 hour into training. The football task appears to be significantly more challenging than the 3-prong and T-pipe tasks, as shown in Figure 7, with no methods performing above a 30% success rate. However, our method still outperforms learning from scratch, achieving a 30% success rate with 5 hours of training; the from-scratch runs required at least 16 hours of training to achieve a lower 20% success rate.

6 Discussion, Limitations, and Future Work

We presented a system for learning in-hand manipulation skills directly by training in the real world with RL, without simulation, and using only onboard sensing from encoders and cameras. Our system enables sample-efficient and autonomous learning by initializing the replay buffer of an efficient online RL method with data from other tasks and even other objects. We extend adversarially-learned classifier-based rewards into this setting to make it possible for users to define tasks with a collection of goal images, and implement automated resets using an imitation-learned reset policy, providing a pipeline for fully autonomous training. The complete system avoids any strong instrumentation assumptions, using the robot's own sensors and actuators for every part of training, providing a proof-of-concept for an efficient real-world RL system that could operate outside of laboratory conditions.

Limitations: Our experimental evaluation does have a number of limitations. Although we show that reusing data from one or two prior tasks improves learning efficiency, a more practical general-purpose robotic system might use data from tens, hundreds, or even thousands of skills. Evaluating the potential for such methods at scale might require additional technical innovations, as it is unclear if buffer initialization with very large datasets will be as effective. Additionally, our evaluation is limited to in-hand reorientation skills. While such skills exercise the robot's dexterity and physical capabilities, many other behaviors that require forceful interaction with the environment and other manipulation skills could require a different reset process or might require a different method for reward specification (for example to handle occlusions). Exploring these more diverse skills is an exciting direction for future work. The current manipulation setup is training with fairly robust objects where fragility or wear and tear are not major concerns. As we move to more dexterous tasks, a more directed approach may be required to handle fragile objects or perform tasks that require force-sensitive interaction. Studying how to integrate our system with tactile sensing is another exciting avenue to explore.

References

[1] J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pages 23–30. IEEE, 2017.

[2] X. B. Peng, M. Andrychowicz, W. Zaremba, and P. Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. In *2018 IEEE international conference on robotics and automation (ICRA)*, pages 3803–3810. IEEE, 2018.

[3] OpenAI, M. Andrychowicz, B. Baker, M. Chociej, R. Józefowicz, B. McGrew, J. W. Pachocki, J. Pachocki, A. Petron, M. Plappert, G. Powell, A. Ray, J. Schneider, S. Sidor, J. Tobin, P. Welinder, L. Weng, and W. Zaremba. Learning dexterous in-hand manipulation. *CoRR*, abs/1808.00177, 2018. URL http://arxiv.org/abs/1808.00177.

[4] B. D. Argall, S. Chernova, M. Veloso, and B. Browning. A survey of robot learning from demonstration. *Robotics and autonomous systems*, 57(5):469–483, 2009.

[5] A. Hussein, M. M. Gaber, E. Elyan, and C. Jayne. Imitation learning: A survey of learning methods. *ACM Computing Surveys (CSUR)*, 50(2):1–35, 2017.

[6] T. Osa, J. Pajarinen, G. Neumann, J. A. Bagnell, P. Abbeel, and J. Peters. An algorithmic perspective on imitation learning. *arXiv preprint arXiv:1811.06711*, 2018.

[7] V. Kumar, A. Gupta, E. Todorov, and S. Levine. Learning dexterous manipulation policies from experience and imitation. *arXiv preprint arXiv:1611.05095*, 2016.

[8] H. Zhu, A. Gupta, A. Rajeswaran, S. Levine, and V. Kumar. Dexterous manipulation with deep reinforcement learning: Efficient, general, and low-cost. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 3651–3657. IEEE, 2019.

[9] A. Nagabandi, K. Konolige, S. Levine, and V. Kumar. Deep dynamics models for learning dexterous manipulation. In *Conference on Robot Learning*, pages 1101–1112, 2020.

[10] P. J. Ball, L. Smith, I. Kostrikov, and S. Levine. Efficient online reinforcement learning with offline data, 2023.

[11] Z. Xu, V. Kumar, and E. Todorov. A low-cost and modular, 20-dof anthropomorphic robotic hand: Design, actuation and modeling. In *2013 13th IEEE-RAS International Conference on Humanoid Robots (Humanoids)*, pages 368–375. IEEE, 2013.

[12] R. Deimel and O. Brock. A novel type of compliant and underactuated robotic hand for dexterous grasping. *The International Journal of Robotics Research*, 35(1-3):161–185, 2016.

[13] R. Bhirangi, A. DeFranco, J. Adkins, C. Majidi, A. Gupta, T. Hellebrekers, and V. Kumar. All the feels: A dexterous hand with large area sensing, 2023.

[14] I. Mordatch, Z. Popović, and E. Todorov. Contact-invariant optimization for hand manipulation. In *Proceedings of the ACM SIGGRAPH/Eurographics symposium on computer animation*, pages 137–144, 2012.

[15] V. Kumar, Y. Tassa, T. Erez, and E. Todorov. Real-time behaviour synthesis for dynamic hand-manipulation. In *2014 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6808–6815. IEEE, 2014.

[16] J. Kober and J. Peters. Policy search for motor primitives in robotics. *Advances in neural information processing systems*, 21, 2008.

[17] M. Posa, C. Cantu, and R. Tedrake. A direct method for trajectory optimization of rigid bodies through contact. *The International Journal of Robotics Research*, 33(1):69–81, 2014.

[18] A. Rajeswaran, V. Kumar, A. Gupta, G. Vezzani, J. Schulman, E. Todorov, and S. Levine. Learning complex dexterous manipulation with deep reinforcement learning and demonstrations. *arXiv preprint arXiv:1709.10087*, 2017.

[19] D. Jain, A. Li, S. Singhal, A. Rajeswaran, V. Kumar, and E. Todorov. Learning deep visuomotor policies for dexterous hand manipulation. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 3636–3643. IEEE, 2019.

[20] C. Zeng, S. Li, Y. Jiang, Q. Li, Z. Chen, C. Yang, and J. Zhang. Learning compliant grasping and manipulation by teleoperation with adaptive force control, 2021.

[21] C. Zeng, S. Li, Z. Chen, C. Yang, F. Sun, and J. Zhang. Multifingered robot hand compliant manipulation based on vision-based demonstration and adaptive force control. *IEEE Transactions on Neural Networks and Learning Systems*, pages 1–12, 2022. doi:10.1109/TNNLS.2022.3184258.

[22] S. P. Arunachalam, I. Güzey, S. Chintala, and L. Pinto. Holo-dex: Teaching dexterity with immersive mixed reality, 2022.

[23] K. Lowrey, S. Kolev, J. Dao, A. Rajeswaran, and E. Todorov. Reinforcement learning for non-prehensile manipulation: Transfer from simulation to physical system. In *2018 IEEE International Conference on Simulation, Modeling, and Programming for Autonomous Robots (SIMPAR)*, pages 35–42. IEEE, 2018.

[24] B. Wu, I. Akinola, J. Varley, and P. Allen. Mat: Multi-fingered adaptive tactile grasping via deep reinforcement learning, 2019.

[25] A. Allshire, M. Mittal, V. Lodaya, V. Makoviychuk, D. Makoviichuk, F. Widmaier, M. Wüthrich, S. Bauer, A. Handa, and A. Garg. Transferring dexterous manipulation from gpu simulation to a remote real-world trifinger. *arXiv preprint arXiv:2108.09779*, 2021.

[26] H. Van Hoof, T. Hermans, G. Neumann, and J. Peters. Learning robot in-hand manipulation with tactile features. In *2015 IEEE-RAS 15th International Conference on Humanoid Robots (Humanoids)*, pages 121–127. IEEE, 2015.

[27] H. Zhu, J. Yu, A. Gupta, D. Shah, K. Hartikainen, A. Singh, V. Kumar, and S. Levine. The ingredients of real-world robotic reinforcement learning. *arXiv preprint arXiv:2004.12570*, 2020.

[28] A. Gupta, J. Yu, T. Z. Zhao, V. Kumar, A. Rovinsky, K. Xu, T. Devlin, and S. Levine. Reset-free reinforcement learning via multi-task learning: Learning dexterous manipulation behaviors without human intervention. *arXiv preprint arXiv:2104.11203*, 2021.

[29] K. Xu, Z. Hu, R. Doshi, A. Rovinsky, V. Kumar, A. Gupta, and S. Levine. Dexterous manipulation from images: Autonomous real-world rl via substep guidance, 2022.

[30] A. Gupta, C. Eppner, S. Levine, and P. Abbeel. Learning dexterous manipulation for a soft robotic hand from human demonstrations. In *2016 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 3786–3793. IEEE, 2016.

[31] P. Mandikal and K. Grauman. Learning dexterous grasping with object-centric visual affordances. *arXiv preprint arXiv:2009.01439*, 2020.

[32] I. Akinola, J. Varley, and D. Kalashnikov. Learning precise 3d manipulation from multiple uncalibrated cameras. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 4616–4622. IEEE, 2020.

[33] S. Ross, N. Melik-Barkhudarov, K. S. Shankar, A. Wendel, D. Dey, J. A. Bagnell, and M. Hebert. Learning monocular reactive UAV control in cluttered natural environments. In *2013 IEEE International Conference on Robotics and Automation*, 2013. doi:10.1109/ICRA.2013.6630809.

[34] S. Reddy, A. D. Dragan, and S. Levine. Sqil: Imitation learning via reinforcement learning with sparse rewards. *arXiv preprint arXiv:1905.11108*, 2019.

[35] B. D. Ziebart, A. L. Maas, J. A. Bagnell, and A. K. Dey. Maximum entropy inverse reinforcement learning. In *AAAI*. AAAI Press, 2008. ISBN 978-1-57735-368-3.

[36] M. Wulfmeier, P. Ondruska, and I. Posner. Maximum entropy deep inverse reinforcement learning. *arXiv preprint arXiv:1507.04888*, 2015.

[37] N. D. Ratliff, J. A. Bagnell, and M. Zinkevich. Maximum margin planning. In *Machine Learning, Proceedings of the Twenty-Third International Conference ICML*, 2006. doi:10. 1145/1143844.1143936.

[38] D. P. Losey and M. K. O'Malley. Including uncertainty when learning from human corrections. In *Conference on Robot Learning*, pages 123–132. PMLR, 2018.

[39] Y. Cui and S. Niekum. Active reward learning from critiques. In *2018 IEEE international conference on robotics and automation (ICRA)*, pages 6907–6914. IEEE, 2018.

[40] J. D. Co-Reyes, A. Gupta, S. Sanjeev, N. Altieri, J. DeNero, P. Abbeel, and S. Levine. Guiding policies with language via meta-learning. *CoRR*, abs/1811.07882, 2018. URL http://arxiv.org/abs/1811.07882.

[41] V. Myers, E. Biyik, N. Anari, and D. Sadigh. Learning multimodal rewards from rankings. In *Conference on Robot Learning*, pages 342–352. PMLR, 2022.

[42] D. S. Brown, W. Goo, and S. Niekum. Better-than-demonstrator imitation learning via automatically-ranked demonstrations. In *Conference on robot learning*, pages 330–359. PMLR, 2020.

[43] I. Kostrikov, D. Yarats, and R. Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *arXiv preprint arXiv:2004.13649*, 2020.

[44] J. Fu, A. Singh, D. Ghosh, L. Yang, and S. Levine. Variational inverse control with events: A general framework for data-driven reward definition. *arXiv preprint arXiv:1805.11686*, 2018.

[45] K. Zolna, A. Novikov, K. Konyushkova, C. Gulcehre, Z. Wang, Y. Aytar, M. Denil, N. de Freitas, and S. Reed. Offline learning from demonstrations and unlabeled experience. *arXiv preprint arXiv:2011.13885*, 2020.

[46] B. Akgun, M. Cakmak, J. W. Yoo, and A. L. Thomaz. Trajectories and keyframes for kinesthetic teaching: A human-robot interaction perspective. In *Proceedings of the seventh annual ACM/IEEE international conference on Human-Robot Interaction*, pages 391–398, 2012.

[47] V. Villani, F. Pini, F. Leali, and C. Secchi. Survey on human–robot collaboration in industrial settings: Safety, intuitive interfaces and applications. *Mechatronics*, 55:248–266, 2018.

[48] L. Smith, J. C. Kew, T. Li, L. Luu, X. B. Peng, S. Ha, J. Tan, and S. Levine. Learning and adapting agile locomotion skills by transferring experience, 2023.

[49] A. Sharma, K. Xu, N. Sardana, A. Gupta, K. Hausman, S. Levine, and C. Finn. Autonomous reinforcement learning: Formalism and benchmarking, 2022.

[50] B. Eysenbach, S. Gu, J. Ibarz, and S. Levine. Leave no trace: Learning to reset for safe and autonomous reinforcement learning. *arXiv preprint arXiv:1711.06782*, 2017.

[51] K. Xu, S. Verma, C. Finn, and S. Levine. Continual learning of control primitives: Skill discovery via reset-games. *arXiv preprint arXiv:2011.05286*, 2020.

[52] A. Sharma, A. Gupta, S. Levine, K. Hausman, and C. Finn. Autonomous reinforcement learning via subgoal curricula, 2021.

[53] W. Han, S. Levine, and P. Abbeel. Learning compound multi-step controllers under unknown dynamics. In *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 6435–6442. IEEE, 2015.

[54] A. Sharma, A. M. Ahmed, R. Ahmad, and C. Finn. Self-improving robots: End-to-end autonomous visuomotor reinforcement learning, 2023.

[55] A. Mandlekar, D. Xu, R. Martín-Martín, Y. Zhu, L. Fei-Fei, and S. Savarese. Human-in-the-loop imitation learning using remote teleoperation, 2020.

[56] R. S. Sutton and A. G. Barto. *Reinforcement learning: An introduction*. 2018.

[57] T. Haarnoja, A. Zhou, K. Hartikainen, G. Tucker, S. Ha, J. Tan, V. Kumar, H. Zhu, A. Gupta, P. Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

[58] Y. Song, Y. Zhou, A. Sekhari, J. A. Bagnell, A. Krishnamurthy, and W. Sun. Hybrid rl: Using both offline and online data can make rl efficient. *arXiv preprint arXiv:2210.06718*, 2022.

[59] H. Zhang, M. Cisse, Y. N. Dauphin, and D. Lopez-Paz. mixup: Beyond empirical risk minimization, 2018.

[60] I. Gulrajani, F. Ahmed, M. Arjovsky, V. Dumoulin, and A. Courville. Improved training of wasserstein gans, 2017.