Logarithmic Unbiased Quantization: Practical 4-bit Training in Deep Learning

Abstract

Quantization of the weights and activations is one of the main methods to reduce the computational footprint of Deep Neural Networks (DNNs) training. Current methods enable 4-bit quantization of the forward phase. However, this constitutes only a third of the training process. Reducing the computational footprint of the entire training process requires the quantization of the neural gradients, i.e., the loss gradients with respect to the outputs of intermediate neural layers. In this work, we examine the importance of having unbiased quantization in quantized neural network training, where to maintain it, and how. Based on this, we suggest a *logarithmic unbiased quantization* (LUQ) method to quantize both the forward and backward phase to 4-bit, achieving state-of-the-art results in 4-bit training. For example, in ResNet50 on ImageNet, we achieved a degradation of 1.18%; we further improve this to degradation of only 0.64% after a single epoch of high precision fine-tuning combined with a variance reduction method. Finally, we suggest a method that exploits the low precision format by avoiding multiplications during two-thirds of the training process, thus reducing by 5x the area used by the multiplier. A reference implementation is supplied in the supplementary material.

1 Introduction

Deep neural networks (DNNs) are a powerful tool that has shown superior performance in various tasks spanning computer vision, natural language processing, autonomous cars, and more. Unfortunately, their vast demand for computational resources, especially during the training process, is one of the main bottlenecks in the evolution of these models.

Training of DNNs consists of three main general-matrix-multiply (GEMM) phases: the forward phase, backward phase, and update phase. Quantization has become one of the main methods to compress DNNs and reduce the GEMM computational resources. There has been a significant advance in the quantization of the forward phase. There, it is possible to quantize the weights and activations to 4 bits while preserving model accuracy (Banner et al., 2019; Nahshan et al., 2019; Bhalgat et al., 2020; Choi et al., 2018b). Despite these advances, they only apply to a third of the training process while the backward phase and update phase are still computed with higher precision.

Recently, Sun et al. (2020) was able, for the first time, to train a DNN while reducing the numerical precision of most of its parts to 4 bits with some degradation (e.g., 2.49% error in ResNet50). To do so, Sun et al. (2020) suggested a non-standard radix-4 floating-point format, combined with double quantization of the neural gradients (called two-phase rounding). This was an impressive step forward in the ability to quantize all the training processes. However, since a radix-4 format is not aligned with conventional radix-2, any numerical conversion between the two requires an explicit multiplication to modify both the exponent and mantissa and may require additional hardware (Kupriianova et al., 2013). Thus, their non-standard quantization requires specific hardware support that can reduce the benefit of quantization to low bits.

The main challenge in reducing the numerical precision of the entire training process is quantizing the neural gradients, i.e. the backpropagated error. Specifically, Chmiel et al. (2021) showed the neural gradients have a heavy tailed near-lognormal distribution, and therefore they should be logarithmically quantized at low precision levels. For example, for FP4 the optimal format was [sign,exponent,mantissa] = [1,3,0], i.e. without mantissa bits. In contrast, that weights and activations

are well approximated with Normal or Laplacian distributions (Banner et al., 2019; Choi et al., 2018a), and therefore are better approximated using uniform quantization (e.g., INT4).

In this work, we dive deeper into understanding neural gradients' quantization. Based on the findings of Chmiel et al. (2021), we focus on the [1,3,0] FP4 format for the neural gradients. We analyze different types of quantization stochastic rounding schemes to explain the importance of having an unbiased rounding scheme for the neural gradients with such a logarithmic quantization format. We compare it with forward phase quantization, where the bias is not a critical property.

Building on this analysis, we suggest a method called *logarithmic unbiased quantization* (LUQ) for unbiased quantization of the neural gradients to the standard FP4 format of [1,3,0]. This, together with quantization of the forward phase to INT4, achieves state-of-the-art results in full training in 4 bits (e.g., 1.18% error in ResNet50), with no overhead. Moreover, we suggest two additional methods to further reduce the degradation, with some overhead: the first method reduces the quantization variance of the neural gradients, while the second is a simple method of fine-tuning in high precision. Combining LUQ with these two proposed methods we achieve, for the first time, only 0.64% error in 4-bit training of ResNet50. The overhead of our additional methods is no more than the previously presented in Sun et al. (2020).

Finally, we exploit the specific FP4 format mantissa used for the neural gradients ([1,3,0]) and suggest replacing the multiplication blocks with a proposed *multiplication free backpropagation* (MF-BPROP) block. This way we completely avoid multiplication in the backward phase and the update phase (which constitute two thirds of the training) and reduce by 5x the area which was previously used for the multiplications in these phases.

The main contributions of this paper:

- A comparison of different rounding schemes.
- We suggest a simple and hardware friendly logarithmically unbiased quantization for the neural gradients called LUQ.
- We demonstrate that two simple methods can further improve the accuracy in 4-bit training: (1) variance reduction using re-sampling and (2) high precision fine-tuning for one epoch.
- We design a modern hardware block that exploits LUQ quantization to avoid multiplication in two thirds of the training process, thus reduce by 5x the multiplier logical area.

2 ROUNDING SCHEMES COMPARISON

In this section, we study the effects of unbiased rounding for the forward and backward passes. We show that rounding-to-nearest (RDN) should be applied for the forward phase while stochastic rounding (SR) is more suitable for the backward phase. Specifically, We show that although SR is unbiased, it generically has worse mean-square-error compared to RDN.

Given that we want to quantize x in a bin with a lower limit $l(x)$ and an upper limit $u(x)$, stochastic rounding can be stated as follows:

$$\text{SR}(x) = \begin{cases} l(x), & \text{with probability } p(x) = 1 - \frac{x-l(x)}{u(x)-l(x)} \\ u(x), & \text{with probability } 1 - p(x) = \frac{x-l(x)}{u(x)-l(x)} \end{cases}. \tag{1}$$

The expected rounding value is given by

$$E[\text{SR}(x)] = l(x) \cdot p(x) + u(x) \cdot (1 - p(x)) = x, \tag{2}$$

where here and below the expectation is over the randomness of SR (i.e., x is a deterministic constant). Therefore, stochastic rounding is an unbiased approximation of x, since it has zero bias:

$$\text{Bias}[\text{SR(x)}] = E[\text{SR}(x) - x] = E[\text{SR}(x)] - x = 0. \tag{3}$$

However, stochastic rounding has variance, given by

$$\begin{aligned} \text{Var}[\text{SR}(x)] &= (l(x) - E[\text{SR}(x)])^2 \cdot p(x) + (u(x) - E[\text{SR}(x)])^2 \cdot (1 - p(x)) \\ &= (x - l(x)) \cdot (u(x) - x), \end{aligned} \tag{4}$$

where the last transition follows from substituting the terms $E[\mathrm{SR}(x)])$, and $p(x)$ into Eq. (4).

We turn to consider the round-to-nearest method (RDN). The bias of RDN is given by

$$\mathrm{Bias}[\mathrm{RDN(x)}] = \min\left(x - l(x), u(x) - x\right). \tag{5}$$

Since RDN is a deterministic method, it is evident that the variance is 0 i.e.,

$$\mathrm{Var}[\mathrm{RDN(x)}] = 0. \tag{6}$$

Finally for every value x and a rounding method $R(x)$, the mean-square-error (MSE) can be written as the sum of the rounding variance and the squared rounding bias,

$$\mathrm{MSE}[\mathrm{R(x)}] = E[R(x) - x]^2 = \mathrm{Var}[\mathrm{R(x)}] + \mathrm{Bias}^2[\mathrm{R(x)}]. \tag{7}$$

Therefore, we have the following MSE distortion when using round-to-nearest and stochastic rounding:

$$\mathrm{MSE} = \begin{cases} [\min\left(x - l(x), u(x) - x\right)]^2 & RDN(x) \\ (x - l(x)) \cdot (u(x) - x) & SR(x) \end{cases}. \tag{8}$$

Note that since $\min(a, b)^2 \le a \cdot b$ for every a, b, we have that

$$\mathrm{MSE}\left[SR\left(x\right)\right] \ge \mathrm{MSE}[RDN(x)], \quad \forall x. \tag{9}$$

In Fig. 1a we plot the mean-square-error for $x \in [0, 1]$, $l(x) = 0$, and $u(x) = 1$. While round-to-zero has a lower MSE than stochastic rounding, the former is a biased estimator.

Conclusions. It was previously proved that unbiased neural gradients quantization leads to unbiased estimate of the weight gradients (e.g., Chen et al. (2020a)), which are necessary for the proper convergence of SGD (Bottou, 2010). Thus, bias in the gradients hurts the performance and must be avoided, even at the cost of increasing the MSE. Therefore, neural gradients should be quantized using SR. However, the forward phase should be quantized deterministically (using RDN) since stochastic rounding will not make help making the loss estimate unbiased (due to the non-linearity of the loss and activation functions) while unnecessarily increasing the mean-square-error (as shown in Eq. (9)). Figs. 1b and 1c show that these theoretical observations are consistent with empirical observations favoring RDN for the forward pass and SR for the backward pass.

(a) (b) (c)

Figure 1: Comparison between stochastic rounding (SR) and round-to-nearest (RDN) quantization. In **(a)** we present the MSE of a uniform distributed tensor with the two different rounding schemes. Quantization to 4 bits of the forward phase **(b)** and backward phase **(c)** of ResNet18 - Cifar100 dataset with SR and RDN. Notice that while MSE is important in the forward phase, unbiasness achieved with SR is crucial for the backward phase.

3 LUQ - A LOGARITHMIC UNBIASED QUANTIZER

A recent work (Chmiel et al., 2021) showed that the neural gradients can be approximated with lognormal distribution. This distribution has many values concentrated around the mean but is also heavy-tailed, making the extreme values orders of magnitudes larger than the small values sampled from this distribution. They exploit this fact and showed that the neural gradients can be pruned to a high pruning ratio without accuracy degradation (e.g., 85% in ResNet18 ImageNet dataset), using an unbiased pruning method. We build on top of this pruning method, and combine it with an unbiased logarithmic quantizer, as described below.

Unbiased stochastic pruning Given an underflow threshold α we define a stochastic pruning operator, which prunes a given value x, as

$$T_\alpha(x) = \begin{cases} x & \text{, if } |x| \geq \alpha \\ \text{sign}(x) \cdot \alpha & w.p. \ \frac{|x|}{\alpha}, \text{if } |x| < \alpha \\ 0 & w.p. \ 1 - \frac{|x|}{\alpha}, \text{if } |x| < \alpha. \end{cases} \tag{10}$$

Unbiased FP quantizer Given an underflow threshold α, let $Q_\alpha(X)$ be a FP round-to-nearest b-bits quantizer with bins $\{\alpha, 2\alpha, ..., 2^{b-1}\alpha\}$. Assume, without loss of generality, $2^{n-1}\alpha < x < 2^n\alpha$ ($n \in \{0, 1..., b-1\}$). We will use the following unbiased quantizer, which is a special case of SR (Eq. (1)):

$$Q_\alpha(x) = \begin{cases} 2^{n-1}\alpha & w.p. \ \frac{2^n\alpha - x}{2^n\alpha - 2^{n-1}\alpha} \\ 2^n\alpha & w.p. \ 1 - \frac{2^n\alpha - x}{2^n\alpha - 2^{n-1}\alpha} = \frac{x - 2^{n-1}\alpha}{2^{n-1}\alpha}. \end{cases} \tag{11}$$

It is unbiased since

$$E[Q_\alpha(x)] = 2^{n-1}\alpha \cdot \frac{2^n\alpha - x}{2^n\alpha - 2^{n-1}\alpha} + 2^n\alpha \cdot \frac{x - 2^{n-1}\alpha}{2^{n-1}\alpha} = x, \tag{12}$$

and as a special case of Eq. (2).

Underflow threshold In order to create an unbiased quantizer, the largest quantization value $2^{b-1}\alpha$ should avoid of clipping any values of x, otherwise this will create a bias. Therefore, the underflow threshold α is chosen as the optimal unbiased value, i.e

$$\alpha = \frac{\max(|x|)}{2^{2^{b-1}}},$$

where $b = 3$ for FP4.

Logarithmic Rounding Traditionally, stochastic rounding as in eq. 11 is implemented by adding a uniform random noise $\epsilon \sim U[-\frac{2^{n-1}\alpha}{2}, \frac{2^{n-1}\alpha}{2}]$ to x and then use a round-to-nearest operation. In order to implement round-to-nearest directly on the exponent, we need to correct an inherent bias since $\alpha \cdot 2^{\lfloor \log(\frac{|x|}{\alpha})\rceil} \neq \alpha \cdot \lfloor 2^{\log(\frac{|x|}{\alpha})}\rceil$.

For a bin $[2^{n-1}, 2^n]$, the midpoint x_m is

$$x_m = \frac{2^n + 2^{n-1}}{2} = \frac{3}{4} \cdot 2^{n-1}. \tag{13}$$

Therefore, we can apply round-to-nearest-power (RDNP) directly on the exponent x of any value $2^{n-1} \leq 2^x \leq 2^n$ as follows:

$$\text{RDNP}(2^x) = 2^{\lfloor \log\left(\frac{4}{3} \cdot 2^x\right)\rfloor} = 2^{\lfloor x + \log\left(\frac{4}{3}\right)\rfloor} = 2^{\text{RDN}\left(x + \log\left(\frac{4}{3}\right) - \frac{1}{2}\right)} \approx 2^{\text{RDN}(x - 0.084)}. \tag{14}$$

Logarithmic unbiased quantization (LUQ) In the following, we suggest LUQ, a 4-bit unbiased estimation of neural gradients that apply stochastic pruning (Eq. (10)) to the 4-bit floating point quantizer $Q_\alpha(x)$

$$X_q = T_\alpha(Q_\alpha(x)). \tag{15}$$

Since T_α and Q_α are unbiased, it follows by the law of total expectation that X_q is an unbiased estimator for x:

$$E[X_q] = E[T_\alpha(Q_\alpha(x))] = E[E[T_\alpha(Q_\alpha(x))]|Q_\alpha(x)] = E[Q_\alpha(x)] = x, \tag{16}$$

where the expectation is over the randomness of T_α and Q_α. In Fig. 2 we show an illustration of LUQ. The first step includes stochastic pruning for the values below the pruning threshold ($|x| < \alpha$). The second step includes the logarithmic quantization with format FP4 of the values above the pruning threshold ($|x| > \alpha$).

Figure 2: The effect of LUQ on the neural gradients histograms for one layer of ResNet18 Cifar100 dataset, with the underflow threshold α (red dashed line). The first step (green arrow) represents the effect of stochastic pruning (Eq. (10)) on the neural gradient. The second step (grey arrow) represents the logarithmic unbiased quantization (Eq. (11)), that quantize all the values $|x| > \alpha$.

3.1 SMP: REDUCING THE VARIANCE WHILE KEEPING IT UNBIASED

In the previous section, we presented an unbiased method for logarithmic quantization of the neural gradients called LUQ. Following the bias-variance decomposition, if the gradients are now unbiased, then the only remaining issue should be their variance. Therefore, we suggest a method to reduce the quantization variance by repeatedly sampling from the stochastic quantizers in LUQ, and averaging the resulting samples of the final weight gradients. The a different samples can be calculated in parallel, so the only overhead on the network throughput will be the averaging operation. For N different samples, the proposed method will reduce the variance by a factor of $\frac{1}{N}$, without affecting the bias (Gilli et al., 2019). In Fig. 3b we show the effect of different number of samples (SMP) on 2-bit quantization of ResNet18 Cifar100 dataset. There, we achieve with 16 samples accuracy similar to a full-precision network. This demonstrates that the variance is the only remaining issue in neural gradient quantization using LUQ, and that the proposed averaging method can erase this variance gap, with some overhead.

Figure 3: **(a):** ResNet50 top-1 validation accuracy in ImageNet dataset with different quantization schemes for the neural gradients. SP refers to stochastic pruning (Eq. (10)). RDNP refers to round-to-nearest-power (Eq. (14)). Notice that with the suggested LUQ we are able to almost close the degradation from baseline. **(b):** ResNet18 top-1 validation accuracy in cifar100 with quantization of the neural gradients to 2-bit (FP2 - [1,1,0] format) using different samples numbers to reduce the variance. Notice that 16 samples completely close the gap to the baseline.

3.2 FNT: FINE-TUNING IN HIGH PRECISION FOR ONE EPOCH

We suggest running one additional epoch in which we increase all network parts to full-precision, except the weights which remain in low precision. We notice that with this scheme we get the best accuracy for the fine-tuned network. In Table 1 we can see the effect of the proposed fine-tuning scheme, improving the accuracy of the models by $\sim 0.4\%$.

4 EXPERIMENTS

In this section, we evaluate the proposed LUQ for 4-bit training in various DNN models. For all models, we use their default architecture, hyper-parameters, and optimizers combined with a custom-modified Pytorch framework that implemented all the low precision schemes. Additional experimental details appear in Appendix A.1.

Main results In Table 1 we show the top-1 accuracy achieved in 4-bit training using LUQ to quantize the neural gradients to FP4 and combined with a previously suggested method, SAWB (Choi et al., 2018a), to quantize the weights and activations to INT4. We compare our method with Ultra-low (Sun et al., 2020) showing better results in all the models, achieving SOTA in 4-bit training. Moreover, we improve the results with the two proposed schemes: neural gradients sampling (SMP - Section 3.1) and fine-tune in high precision (FNT - Section 3.2) achieving for the first time in 4-bit training 0.64% error in ResNet-50 ImageNet dataset, with our simple and hardware friendly methods.

Overhead of SMP and FNT We limit our experiments with the proposed SMP method to only two samples. This is to achieve a similar computational overhead as Ultra-low, with their suggested two-phase-rounding (TPR) which also generates a duplication for the neural gradient quantization. The FNT method is limited to only 1 epoch to reduce the overhead in comparison to Ultra-low, which keeps the 1x1 convolutions in 8-bit. Specifically, the throughput of a 4-bit training network is 8x in comparison to high precision training (Sun et al., 2020). This means that doing one additional epoch in high precision reduces the throughput of ResNet-50 training by $\sim 8\%$. In comparison, Ultra-low (Sun et al., 2020) does full-training with all the 1x1 convolutions in 8-bits, which reduces the throughput by $\sim 50\%$.

Table 1: Comparison of 4-bit training of the proposed method LUQ with Ultra-low (Sun et al., 2020) in various DNNs models with ImageNet dataset. FNT refers to fine-tune the trained model one additional epoch with the neural gradients at high precision (Section 3.2) and SMP refers to doing two samples of the SR quantization of neural gradients in order to reduce the variance (Section 3.1). The experiments for Mobilenet-V2 and ResNext-50 with SMP did not finish before the deadline.

Model	Baseline	Ultra-low	LUQ	LUQ + FNT	LUQ + SMP	LUQ + SMP + FNT
ResNet-18	69.7 %	68.27%	69.0%	69.39 %	69.1 %	69.47 %
ResNet-50	76.5%	74.01%	75.32 %	75.52 %	75.63 %	75.86 %
MobileNet-V2	71.9 %	68.85 %	69.69 %	69.87 %	-	-
ResNext-50	77.6 %	N/A	76.12 %	76.39 %	-	-

Forward-backward ablations In Table 2 we show the top-1 accuracy in ResNet50 with different quantization schemes. The forward phase (activations + weights) is quantized to INT4 with SAWB (Choi et al., 2018a) and the backward phase (neural gradients) to FP4 with LUQ. As expected, the network is more sensitive to the quantization of the backward phase.

Table 2: ResNet-50 accuracy with ImageNet dataset while quantization different parts of the network. The forward phase is quantized to INT4 format with SAWB (Choi et al., 2018a) while the backward phase is quantized with the proposed LUQ. As expected, the quantization of the backward phase makes more degradation to the network accuracy.

Forward	Backward	Accuracy
FP32	FP32	76.5 %
INT4	FP32	76.35 %
FP32	FP4	75.6 %
INT4	FP4	75.32 %

5 MF-BPROP: MULTIPLICATION FREE BACKPROPAGATION

The main problem of using different datatypes for the forward and backward phases is the need to cast them to a common data type — before the multiplication during the backward and update phases. In our case, the weights (W) and activations (a) are quantized to INT4 while the neural gradients ($\frac{\partial C}{\partial a}$) to FP4, where C represent the loss function. During the backward and update phases, in each layer l there are two GEMMs between different data types:

$$\textbf{[Backward]} \quad \frac{\partial C}{\partial a_{l-1}} = W_l^T \frac{\partial C}{\partial a_l} \tag{17}$$

$$\textbf{[Update]} \quad \frac{\partial C}{\partial W_l} = \frac{\partial C}{\partial a_l} a_l^T \tag{18}$$

Regularly, to calculate these GEMMs there is a need to cast both data types to a common data type (in our case, FP7 [1,4,2]), then do the GEMM and finally, the results are usually accumulated in a wide accumulator (Fig. 4a). This casting cost is not negligible. For example, casting INT4 to FP7 consumes $\sim 15\%$ of the area of an FP7 multiplier.

In our case, we are dealing with a special case where we do a GEMM between a number without mantissa (neural gradient) and a number without exponent (weights and activations), since INT4 is almost equivalent to FP4 with format [1,0,3]. We suggest transforming the standard GEMM block (Fig. 4a) to Multiplication Free BackPROP (MF-BPROP) block which contains only a transformation to standard FP7 format (see Fig. 4b) and a simple XOR operation. More details on this transformation appear in Appendix A.2. In our analysis (Appendix A.3) we show the MF-BPROP block reduces the area of the standard GEMM block by 5x. Since the FP32 accumulator is still the most expensive block when training with a few bits, we reduce the total area in our experiments by $\sim 8\%$. However, as previously showed (Wang et al., 2018) 16-bits accumulators work well with 8-bit training, so it is reasonable to think, it should work also with 4-bit training. In this case, the analysis (Appendix A.3) shows that the suggested MF-BPROP block reduces the total area by $\sim 22\%$.

6 RELATED WORKS

Neural networks Quantization has been extensively investigated in the last few years. Most of the quantization research has focused on reducing the numerical precision of the weights and activations for inference (e.g., Courbariaux et al. (2016); Rastegari et al. (2016); Banner et al. (2019); Nahshan et al. (2019); Choi et al. (2018b); Bhalgat et al. (2020); Choi et al. (2018a); Liang et al. (2021)). In standard ImageNet models, the best performing methods can achieve quantization to 4 bits with small or no degradation Choi et al. (2018a). These methods can be used to reduce the computational resources in approximately a third of the training. However, without quantizing the neural gradients, we cannot reduce the computational resources in the remaining two thirds of the training process. An orthogonal approach of quantization is low precision for the gradients of the weights in distributed training (Alistarh et al., 2016; Bernstein et al., 2018) in order to reduce the bandwidth and not the training computational resources.

Banner et al. (2018) first showed that it is possible to use INT8 quantization for the weights, activations, and neural gradients, thus reducing the computational footprint of most parts of the training process. Concurrently, Wang et al. (2018) was the first work to achieve full training in FP8 format. Additionally, they suggested a method to reduce the accumulator precision from 32bit to 16 bits, by using chunk-based accumulation and floating point stochastic rounding. Later, Wiedemann et al. (2020) showed full training in INT8 with improved convergence, by applying a stochastic quantization scheme to the neural gradients called non-subtractive-dithering (NSD) that induce sparsity followed by stochastic quantization. Also, Sun et al. (2019) presented a novel hybrid format for full training in FP8, while the weights and activations are quantized to [1,4,3] format, the neural gradients are quantized to [1,5,2] format to catch a wider dynamic range.

While it appears that it is possible to quantize to 8-bits all computational elements in the training process, 4-bits quantization of the neural gradients is still challenging. Chmiel et al. (2021) suggested that this difficulty stems from the heavy-tailed distribution of the neural gradients, which can be

(a)

(b)

Figure 4: **(a):** Standard MAC block illustration containing the two main blocks - one for GEMM and second for accumulator. The GEMM block for hybrid datatype as in our case (FP4 and INT4) requires a casting to a common datatype before being inserted into the multiplier. **(b):** The suggested MAC block, which replace the multiplier with the proposed MF-BPROP. Instead of doing an expensive casting followed by a multiplication, we propose to make only a simple XOR and a transformation (Appendix A.2) reducing the GEMM area by 5x (Appendix A.3).

approximated with a lognormal distribution. This distribution is more challenging to quantize in comparison to the normal distribution which is usually used to approximate the weights or activations (Banner et al., 2019).

Sun et al. (2020) was the first work that presented a method to reduce the numerical precision to 4-bits for the vast majority of the computations needed during DNNs training. They use known methods to quantize the forward phase to INT4 (SAWB (Choi et al., 2018a) for the weights and PACT (Choi et al., 2018b) for the activations) and suggested to quantize the neural gradients twice (one for the update and another for the next layer neural gradient) with a non standard radix-4 FP4 format. The use of the radix-4, instead of the commonly used radix-2 format, allows covering a wider dynamic range. The main problem of their method is the specific hardware support for their suggested radix-4 datatype, which may limit the practicality of implementing their suggested data type.

Chen et al. (2020b) suggested to reduce the variance in neural gradients quantization by dividing them into several blocks and quantize each to INT4 separately. Their method requires in each iteration to sort all the neural gradients and divide them into blocks, a costly operation that will affect the network throughput. Additionally, they suggested to quantize each sample separately. The multiple scales per layer in both methods don't allow the use of an efficient GEMM operation.

7 CONCLUSIONS

In this work, we analyze the difference between two rounding schemes: round-to-nearest and stochastic-rounding. We showed that, while the former has lower MSE and works better for the quantization of the forward phase (weights and activations), the latter is an unbiased approximation of the original data and works better for the quantization of the backward phase (specifically, the neural gradients).

Based on these conclusions, we propose a logarithmic unbiased quantizer (LUQ) to quantize the neural gradients to format FP4 [1,3,0]. Combined with a known method for quantizing the weights and activations to INT4 we achieved, without overhead, state-of-the-art in 4-bit training in all the models we examined, e.g., 1.18 % error in ResNet50 vs 2.49 % for the previous known SOTA (Sun et al. (2020)). Moreover, we suggest two more methods to improve the results, with overhead comparable to Sun et al. (2020). The first reduces the quantization variance, without affecting the unbiasedness of LUQ, by averaging several samples of stochastic neural gradients quantization. The second is a simple method for fine-tuning in high precision for one epoch. Combining all these methods, we were able for the first time to achieve 0.64 % error in 4-bit training of ResNet50 ImageNet dataset.

Finally, we exploit the special formats used for quantization (INT4 in the forward phase and FP4 format [1,3,0] in the backward phase) and suggest a block called MF-BPROP that avoids multiplication during two thirds of the training, thus reducing by 5x the area previously used by the multiplier.

REPRODUCIBILITY

A source code of the experiments appears in the supplementary material. Additionally, in Appendix A.1 we added the details of the experiments, including the hyper-parameters used.

REFERENCES

Dan Alistarh, Demjan Grubic, Jungshian Li, Ryota Tomioka, and M. Vojnovic. Qsgd: Communication-optimal stochastic gradient descent, with applications to training neural networks. 2016.

R. Banner, Yury Nahshan, and Daniel Soudry. Post training 4-bit quantization of convolutional networks for rapid-deployment. In *NeurIPS*, 2019.

Ron Banner, Itay Hubara, Elad Hoffer, and Daniel Soudry. Scalable methods for 8-bit training of neural networks. In *NeurIPS*, 2018.

Jeremy Bernstein, Yu-Xiang Wang, Kamyar Azizzadenesheli, and Anima Anandkumar. signsgd: compressed optimisation for non-convex problems. *ArXiv*, abs/1802.04434, 2018.

Yash Bhalgat, Jinwon Lee, Markus Nagel, Tijmen Blankevoort, and Nojun Kwak. Lsq+: Improving low-bit quantization through learnable offsets and better initialization. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, pp. 2978–2985, 2020.

Léon Bottou. Large-scale machine learning with stochastic gradient descent. In Yves Lechevallier and Gilbert Saporta (eds.), *Proceedings of COMPSTAT'2010*, pp. 177–186, Heidelberg, 2010. Physica-Verlag HD. ISBN 978-3-7908-2604-3.

Jianfei Chen, Yu Gai, Zhewei Yao, Michael W Mahoney, and Joseph E Gonzalez. A statistical framework for low-bitwidth training of deep neural networks. *arXiv preprint arXiv:2010.14298*, 2020a.

Jianfei Chen, Yujie Gai, Z. Yao, M. Mahoney, and Joseph Gonzalez. A statistical framework for low-bitwidth training of deep neural networks. In *NeurIPS*, 2020b.

Brian Chmiel, Liad Ben-Uri, Moran Shkolnik, E. Hoffer, Ron Banner, and Daniel Soudry. Neural gradients are lognormally distributed: understanding sparse and quantized training. In *ICLR*, 2021.

Jungwook Choi, P. Chuang, Zhuo Wang, Swagath Venkataramani, V. Srinivasan, and K. Gopalakrishnan. Bridging the accuracy gap for 2-bit quantized neural networks (qnn). *ArXiv*, abs/1807.06964, 2018a.

Jungwook Choi, Zhuo Wang, Swagath Venkataramani, P. Chuang, V. Srinivasan, and K. Gopalakrishnan. Pact: Parameterized clipping activation for quantized neural networks. *ArXiv*, abs/1805.06085, 2018b.

Matthieu Courbariaux, Itay Hubara, Daniel Soudry, Ran El-Yaniv, and Yoshua Bengio. Binarized Neural Networks: Training Deep Neural Networks with Weights and Activations Constrained to +1 or -1. *arXiv e-prints*, art. arXiv:1602.02830, February 2016.

Manfred Gilli, Dietmar Maringer, and Enrico Schumann. Chapter 6 - generating random numbers. In Manfred Gilli, Dietmar Maringer, and Enrico Schumann (eds.), *Numerical Methods and Optimization in Finance (Second Edition)*, pp. 103–132. Academic Press, second edition edition, 2019. ISBN 978-0-12-815065-8. doi: https://doi.org/10.1016/B978-0-12-815065-8.00017-0. URL https://www.sciencedirect.com/science/article/pii/B9780128150658000170.

Sasan Iman and Massoud Pedram. *Logic Synthesis for Low Power VLSI Designs*. Kluwer Academic Publishers, USA, 1997. ISBN 0792380762.

Olga Kupriianova, Christoph Lauter, and Jean-Michel Muller. Radix conversion for ieee754-2008 mixed radix floating-point arithmetic. *2013 Asilomar Conference on Signals, Systems and Computers*, Nov 2013. doi: 10.1109/acssc.2013.6810471. URL http://dx.doi.org/10.1109/ACSSC.2013.6810471.

Tailin Liang, C. John Glossner, Lei Wang, and Shaobo Shi. Pruning and quantization for deep neural network acceleration: A survey. *ArXiv*, abs/2101.09671, 2021.

Yury Nahshan, Brian Chmiel, Chaim Baskin, Evgenii Zheltonozhskii, Ron Banner, Alex M. Bronstein, and Avi Mendelson. Loss aware post-training quantization. *arXiv preprint arXiv:1911.07190*, 2019. URL http://arxiv.org/abs/1911.07190.

Mohammad Rastegari, Vicente Ordonez, Joseph Redmon, and Ali Farhadi. Xnor-net: Imagenet classification using binary convolutional neural networks. In *ECCV*, 2016.

Xiao Sun, Jungwook Choi, Chia-Yu Chen, Naigang Wang, Swagath Venkataramani, Vijayalakshmi Srinivasan, Xiaodong Cui, Wei Zhang, and Kailash Gopalakrishnan. Hybrid 8-bit floating point (hfp8) training and inference for deep neural networks. In *NeurIPS*, 2019.

Xiao Sun, Naigang Wang, Chia-Yu Chen, Jiamin Ni, A. Agrawal, Xiaodong Cui, Swagath Venkataramani, K. E. Maghraoui, V. Srinivasan, and K. Gopalakrishnan. Ultra-low precision 4-bit training of deep neural networks. In *NeurIPS*, 2020.

Naigang Wang, Jungwook Choi, Daniel Brand, Chia-Yu Chen, and K. Gopalakrishnan. Training deep neural networks with 8-bit floating point numbers. In *NeurIPS*, 2018.

Simon Wiedemann, Temesgen Mehari, Kevin Kepp, and W. Samek. Dithered backprop: A sparse and quantized backpropagation algorithm for more efficient deep neural network training. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, pp. 3096–3104, 2020.

A APPENDIX

A.1 EXPERIMENTS DETAILS

ResNet / ResNext We run the models ResNet-18, ResNet-50 and ResNext-50 from torchvision. We use the standard pre-processing of ImageNet ILSVRC2012 dataset. We train for 90 epochs, use an initial learning rate of 0.1 with a 0.1 decay at epochs 30,60,80. We use standard SGD with momentum of 0.9 and weight decay of 1e-4. The minibatch size used is 256. Following the DNNs quantization conventions (Banner et al., 2018; Nahshan et al., 2019; Choi et al., 2018b) we kept the first and last layer (FC) at higher precision. Additionally, similar to Sun et al. (2020) we adopt the full precision at the shortcut which constitutes only a small amount of the computations ($\sim 1\%$).

MobileNet V2 We run Mobilenet V2 model from torchvision. We use the standard pre-processing of ImageNet ILSVRC2012 dataset. We train for 150 epochs, use an initial learning rate of 0.05 with a cosine learning scheduler. We use standard SGD with momentum of 0.9 and weight decay of 4e-5. The minibatch size used is 256. Following the DNNs quantization conventions (Banner et al., 2018; Nahshan et al., 2019; Choi et al., 2018b) we kept the first and last layer (FC) at higher precision. Additionally, similar to Sun et al. (2020) we adopt the full precision at the depthwise layer which constitutes only a small amount of the computations ($\sim 3\%$).

A.2   TRANSFORM TO STANDARD FP7

We suggest a method to avoid the use of an expensive GEMM block between the INT4 (activation or weights) and FP4 (neural gradient). It includes 2 main elements: The first is a simple xor operation between the sign of the two number and second a transform block to standard FP7 format. In Fig. 5 we present an illustration of the proposed method. In the next section we analyze the area of the suggested block in comparison to the standard GEMM block, showing a 5x area reduction.

Figure 5: Illustration of MF-BPROP block which replaces a standard multiplication. It includes: (1) a simple xor operation between the sign. (2) A transform to standard FP7 format. We present the table to make this transform - E and M represent the bits of the FP4 and INT4 respectively without the sign. Exp and Mant are the bits of the output exponent (4-bit) and mantissa (2-bit) of the output in FP7 format.

A.3   BACKPROPAGATION WITHOUT MULTIPLCATION ANALYSIS

In this section, we show a rough estimation of the logical area of the proposed MF-BPROP block which avoids multiplication and compares it with the standard multiplier. In hardware design, the logical area can be a good proxy for power consumption (Iman & Pedram, 1997). Our estimation doesn't include synthesis optimization. In Table 3 we show the estimation of the number of gates of a standard multiplier, getting 264 logical gates while the proposed MF-BPROP block has an estimation of 49 gates (Table 4) achieving a $\sim 5x$ area reduction. For fair comparison we remark that in the proposed scheme the FP32 accumulator is the most expensive block with an estimation of 2453 gates, however we believe it can be reduced to a narrow accumulator such as FP16 (As previously showed in Wang et al. (2018) which have an estimated area of 731 gates. In that case, we reduce the total are by $\sim 22\%$.

Table 3: Rough estimation of the number of logical gates for a standard GEMM block which contain two blocks: a casting to FP7 and a FP7 multiplier.

Block	Operation	# Gates
Casting to FP7	Exponent 3:1 mux	12
	Mantissa 4:1 mux	18
FP7 [1,4,2] multiplier	Mantissa multiplier	99
	Exponent adder	37
	Sign xor	1
	Mantissa normalization	48
	Rounding adder	12
	Fix exponent	37
Total		**264**

Table 4: Rough estimation of the number of logical gates for the proposed MF-BPROP block.

Block	Operation	# Gates
MF-BPROP	Exponent adder	30
	Mantissa 4:1 mux	18
	Sign xor	1
Total		**49**