Lipschitz Bandits with Batched Feedback

Abstract

In this paper, we study Lipschitz bandit problems with batched feedback, where the expected reward is Lipschitz and the reward observations are communicated to the player in batches. We introduce a novel landscape-aware algorithm, called Batched Lipschitz Narrowing (BLiN), that optimally solves this problem. Specifically, we show that for a T-step problem with Lipschitz reward of zooming dimension d_z, our algorithm achieves theoretically optimal regret rate $\widetilde{\mathcal{O}}\left(T^{\frac{d_z+1}{d_z+2}}\right)$ using only $\mathcal{O}\left(\log \log T\right)$ batches. We also provide complexity analysis for this problem. Our theoretical lower bound implies that $\Omega(\log \log T)$ batches are necessary for any algorithm to achieve the optimal regret. Thus, BLiN achieves optimal regret rate using minimal communication.

1 Introduction

Multi-Armed Bandit (MAB) algorithms aim to exploit the good options while explore the decision space. These algorithms and methodologies find successful applications in artificial intelligence and reinforcement learning [e.g., 36]. While the classic MAB setting assumes that the rewards are immediately observed after each arm pull, real-world data often arrives in different patterns. For example, observations from clinical trials are often be collected in a batched fashion [33]. Another example is from online advertising, where strategies are tested on multiple customers at the same time [10]. In such cases, any observation-dependent decision-making should comply with this data-arriving pattern, including MAB algorithms.

In this paper, we study the Lipschitz bandit problem with batched feedback – a MAB problem where the expected reward is Lipschitz and the reward observations are communicated to the player in batches. In such settings, rewards are communicated only at the end of the batches, and the algorithm can only make decisions based on information up to the previous batch. Existing Lipschitz bandit algorithms heavily rely on timely access to the reward samples, since the partition of arm space may change at any time. Therefore, they can not solve the batched feedback setting. To address this difficulty, we present a novel adaptive algorithm for Lipschitz bandits with communication constraints, named *Batched Lipschitz Narrowing* (BLiN). BLiN learns the landscape of the reward by adaptively narrowing the arm set, so that regions of high reward are more frequently played. Also, BLiN determines the data collection procedure adaptively, so that only very few data communications are needed.

The above BLiN procedure achieves optimal regret rate $\widetilde{\mathcal{O}}\left(T^{\frac{d_z+1}{d_z+2}}\right)$ (d_z is the zooming dimension [25, 14]), and can be implemented in a clean and easy-to-implement form. In addition to achieving the optimal regret rate, BLiN is also optimal in the following senses:

- BLiN's communication complexity is optimal. BLiN only needs $\mathcal{O}(\log \log T)$ rounds of communications to achieve the optimal regret rate (Theorem 2), and no algorithm can achieve this rate with fewer than $\Omega(\log \log T)$ rounds of communications (Corollary 2).

- BLiN's time complexity is optimal (Remark 1): if the arithmetic operations and sampling are of complexity $\mathcal{O}(1)$, then the time complexity of BLiN is $\mathcal{O}(T)$, which improve the best known time complexity $\mathcal{O}(T \log T)$ for Lipschitz bandit problems [14].

1.1 Settings & Preliminaries

For a Lipschitz bandit problem (with communication constraints), the arm set is a compact doubling metric space $(\mathcal{A}, d_{\mathcal{A}})$. The expected reward $\mu : \mathcal{A} \to \mathbb{R}$ is 1-Lipschitz with respect to the metric $d_{\mathcal{A}}$, that is, $|\mu(x_1) - \mu(x_2)| \le d_{\mathcal{A}}(x_1, x_2)$ for any $x_1, x_2 \in \mathcal{A}$.

At time $t \le T$, the learning agent pulls an arm $x_t \in \mathcal{A}$ that yields a reward sample $y_t = \mu(x_t) + \epsilon_t$, where ϵ_t is a mean-zero independent sub-Gaussian noise. Without loss of generality, we assume that $\epsilon_t \sim \mathcal{N}(0, 1)$, since generalizations to other sub-Gaussian noises are not hard.

Similar to most bandit learning problems, the agent seeks to minimize regret in the batched feedback environment. The regret is defined as $R(T) = \sum_{t=1}^{T} (\mu^* - \mu(x_t))$, where μ^* denotes $\max_{x \in \mathcal{A}} \mu(x)$. For simplicity, we define $\Delta_x = \mu^* - \mu(x)$ (called optimality gap of x) for all $x \in \mathcal{A}$.

1.1.1 Doubling Metric Spaces and the $([0,1]^d, \|\cdot\|_\infty)$ Metric Space

By the Assouad's embedding theorem [6], the (compact) doubling metric space $(\mathcal{A}, d_{\mathcal{A}})$ can be embedded into a Euclidean space with some distortion of the metric; See [42] for more discussions in a machine learning context. Due to existence of such embedding, the metric space $([0,1]^d, \|\cdot\|_\infty)$, where metric balls are hypercubes, is sufficient for the purpose of our paper. For the rest of the paper, we will use hypercubes in algorithm design for simplicity, while our algorithmic idea generalizes to other doubling metric spaces.

1.1.2 Zooming Numbers and Zooming Dimensions

An important concept for bandit problems in metric spaces is the zooming number and the zooming dimension [25, 13, 38], which we discuss now.

Define the set of r-optimal arms as $S(r) = \{x \in \mathcal{A} : \Delta_x \le r\}$. For any $r = 2^{-i}$, the decision space $[0,1]^d$ can be equally divided into 2^{di} cubes with edge length r, which we call *standard cubes* (also referred to as dyadic cubes). The r-zooming number is defined as

$$N_r := \#\{C : C \text{ is a standard cube with edge length } r \text{ and } C \subset S(16r)\}.$$

In words, N_r is the r-packing number of the set $S(16r)$ in terms of standard cubes. The zooming dimension is then defined as

$$d_z := \min\{d \ge 0 : \exists a > 0, \ N_r \le ar^{-d}, \ \forall r = 2^{-i} \text{ for some } i \in \mathbb{N}\}.$$

Moreover, we define the zooming constant C_z as the minimal a to make the above inequality true for d_z, $C_z = \min\{a > 0 : \ N_r \le ar^{-d_z}, \ \forall r = 2^{-i} \text{ for some } i \in \mathbb{N}\}$.

Zooming dimension d_z can be significantly smaller than ambient dimension d and can be zero. For a simple example, consider a problem with ambient dimension $d = 1$ and expected reward function $\mu(x) = x$ for $0 \le x \le 1$. Then for any $r = 2^{-i}$ with $i \ge 4$, we have $S(16r) = [1 - 16r, 1]$ and $N_r = 16$. Therefore, for this problem the zooming dimension equals to 0, with zooming constant $C_z = 16$.

1.2 Batched feedback pattern and our results

In the batched feedback setting, for a T-step game, the player determines a grid $\mathcal{T} = \{t_0, \cdots, t_B\}$ *adaptively*, where $0 = t_0 < t_1 < \cdots < t_B = T$ and $B \ll T$. During the game, reward observations are communicated to the player only at the grid points $t_1, \cdots, t_B$. As a consequence, for any time t in the j-th batch, that is, $t_{j-1} < t \le t_j$, the reward y_t cannot be observed until time t_j, and the decision made at time t depends only on rewards up to time t_{j-1}. The determination of the grid $\mathcal{T}$ is adaptive in the sense that the player chooses each grid point $t_j \in \mathcal{T}$ based on the operations and observations up to the previous point t_{j-1}.

In this work, we present BLiN algorithm to solve Lipschitz bandits under batched feedback. During the learning procedure, BLiN detects and eliminates the 'bad area' of the arm set in batches and

partition the remaining area according to an appropriate *edge-length sequence*. Our first theoretical upper bound is that with simple Doubling Edge-length Sequence $r_m = 2^{-m+1}$, BLiN achieves optimal regret rate $\widetilde{\mathcal{O}}\left(T^{\frac{d_z+1}{d_z+2}}\right)$ by using $\mathcal{O}(\log T)$ batches.

Theorem 1. *With probability exceeding $1 - \frac{2}{T^6}$, the T-step total regret $R(T)$ of BLiN with Doubling Edge-length Sequence (D-BLiN) satisfies*

$$R(T) \lesssim T^{\frac{d_z+1}{d_z+2}} \cdot (\log T)^{\frac{1}{d_z+2}},$$

where d_z is the zooming dimension of the problem instance. In addition, D-BLiN only needs no more than $\mathcal{O}(\log T)$ rounds of communications to achieve this regret rate. Here and henceforth, $\lesssim$ only omits constants.

While D-BLiN is efficient for batched Lipschitz bandits, its communication complexity is not optimal. We then propose a new edge-length sequence, which we call Appropriate Combined Edge-length Sequence (ACE Sequence) to improve the algorithm. The idea behind this sequence is that by appropriately combining some batches, the algorithm can achieve better communication bound without incurring increased regret. As we shall see, BLiN with ACE Sequence (A-BLiN) achieves regret rate $\widetilde{\mathcal{O}}\left(T^{\frac{d_z+1}{d_z+2}}\right)$ with only $\mathcal{O}(\log \log T)$ batches.

Theorem 2. *With probability exceeding $1 - \frac{2}{T^6}$, the T-step total regret $R(T)$ of A-BLiN satisfies*

$$R(T) \lesssim T^{\frac{d_z+1}{d_z+2}} \cdot (\log T)^{\frac{1}{d_z+2}} \cdot \log \log T,$$

where d_z is the zooming dimension of the problem instance. In addition, Algorithm 1 only needs no more than $\mathcal{O}(\log \log T)$ rounds of communications to achieve this regret rate.

As a comparison, seminal works [25, 38, 14] show that the optimal regret bound for Lipschitz bandits without communications constraints, where the reward observations are immediately observable after each arm pull, is $R(T) \lesssim T^{\frac{d_z+1}{d_z+2}} \cdot (\log T)^{\frac{1}{d_z+2}}$ in terms of zooming dimension, and

$$R(T) \lesssim R_z(T) \triangleq \inf_{r_0} \left\{ r_0 T + \sum_{r=2^{-i}, r \geq r_0} \frac{N_r}{r} \log T \right\} \tag{1}$$

in terms of zooming number. Therefore, A-BLiN achieves optimal regret rate of Lipschitz bandits by using very few batches.

Moreover, our lower-bound analysis shows that $\Omega(\log \log T)$ batches are necessary for any algorithm to achieve the optimal regret rate. Thus, BLiN is optimal in terms of both regret and communication.

1.3 Related Works

The history of the Multi-Armed Bandit (MAB) problem can date back to Thompson [41]. Solvers for this problems include the UCB algorithms [27, 4, 7], the arm elimination method [19, 31, 35], the ϵ-greedy strategy [7, 39], the exponential weights and mirror descent framework [8].

Recently, with the prevalence of distributed computing and large-scale field experiments, the setting of batched feedback has captured attention [e.g., 16]. Perchet et al. [32] mainly consider batched bandit with two arms, and a matching lower bound for static grid is proved. It was then generalized by Gao et al. [20] to finite-armed bandit problems. In their work, the authors designed an elimination method for finite-armed bandit problem and proved matching lower bounds for both static and adaptive grid. Soon afterwards, Zhang et al. [44] studies inference for batched bandits. Esfandiari et al. [18] studies batched linear bandits and batched adversarial bandits. Han et al. [21] and Ruan et al. [34] provide solutions for batched contextual linear bandits. Li and Scarlett [28] studies batched Gaussian process bandits. Batched dueling bandits have also been studied by [2]. Parallel to the regret control regime, best arm identification with limited number of batches was studied in [1] and [22]. Top-k arm identification in the collaborative learning framework is also closely related to the batched setting, where the goal is to minimize the number of iterations (or communication steps) between agents. In this setting, tight bounds have been obtained in the recent works [40, 23]. Yet the problem of Lipschitz bandit with communication constraints remains unsolved.

The Lipschitz bandit problem is important in its own stand. The Lipschitz bandit problem was introduced as "continuum-armed bandits" [3], where the arm space is a compact interval. Along this line, bandits that are Lipschitz (or Hölder) continuous have been studied. For this problem, Kleinberg [24] proves a $\Omega(T^{2/3})$ lower bound and introduced a matching algorithm. Under extra conditions on top of Lipschitzness, regret rate of $\widetilde{\mathcal{O}}(T^{1/2})$ was achieved [9, 17]. For general (doubling) metric spaces, the Zooming bandit algorithm [25] and the Hierarchical Optimistic Optimization (HOO) algorithm [14] were developed. In more recent years, some attention has been focused on Lipschitz bandit problems with certain extra structures. To name a few, Bubeck et al. [15] study Lipschitz bandits for differentiable rewards, which enables algorithms to run without explicitly knowing the Lipschitz constants. Magureanu et al. [30] derive a new concentration inequality and study discrete Lipschitz bandits. The idea of robust mean estimators [11, 5, 12] was applied to the Lipschitz bandit problem to cope with heavy-tail rewards, leading to the development of a near-optimal algorithm for Lipschitz bandit with heavy-tailed rewards [29]. Lipschitz bandits where a clustering is used to infer the underlying metric, has been studied by [43]. Contextual Lipschitz bandits have also been studied by [38] and [26]. Yet all of the existing works for Lipschitz bandits assume that the reward sample is immediately observed after each arm pull, and none of them solve the Lipschitz bandit problem with communication constraints.

This paper is organized as follows. In section 2, we introduce the BLiN algorithm and give a visual illustration of the algorithm procedure. In section 3, we prove that BLiN with ACE Sequence achieves the optimal regret rate using only $\mathcal{O}(\log \log T)$ rounds of communications. Section 4 provides information-theoretical lower bounds for Lipschitz bandits with communication constraints, which shows that BLiN is optimal in terms of both regret and rounds of communications. Experimental results are presented in Section 5.

2 Algorithm

With communication constraints, the agent's knowledge about the environment does not accumulate within each batch. This characteristic of the problem suggests a 'uniform' type algorithm – we shall treat each step within the same batch equally. Following this intuition, in each batch, we uniformly play the remaining arms, and then eliminate arms of low reward after the observations are communicated. Next we describe the uniform play rule and the arm elimination rule.

Uniform Play Rule: At the beginning of each batch m, a collection of subsets of the arm space $\mathcal{A}_m = \{C_{m,1}, C_{m,2}, \cdots, C_{m,|\mathcal{A}_m|}\}$ is constructed. This collection of subset $\mathcal{A}_m$ consists of standard cubes, and all cubes in $\mathcal{A}_m$ have the same edge length r_m. We will detail the construction of $\mathcal{A}_m$ when we describe the arm elimination rule. We refer to cubes in $\mathcal{A}_m$ as active cubes of batch m.

During batch m, each cube in $\mathcal{A}_m$ is played $n_m := \frac{16 \log T}{r_m^2}$ times, where T is the total time horizon. More specifically, within each $C \in \mathcal{A}_m$, arms $x_{C,1}, x_{C,2}, \cdots, x_{C,n_m} \in C$ are played.[1] The reward samples $\{y_{C,1}, y_{C,2}, \cdots, y_{C,n_m}\}_{C \in \mathcal{A}_m}$ corresponding to $\{x_{C,1}, x_{C,2}, \cdots, x_{C,n_m}\}_{C \in \mathcal{A}_m}$ will be collected at the end of the this batch.

Arm Elimination Rule: At the end of batch m, information from the arm pulls is collected, and we estimate the reward of each $C \in \mathcal{A}_m$ by $\widehat{\mu}_m(C) = \frac{1}{n_m} \sum_{i=1}^{n_m} y_{C,i}$. Cubes of low estimated rewards are then eliminated, according to the following rule: a cube $C \in \mathcal{A}_m$ is eliminated if $\widehat{\mu}_m^{\max} - \widehat{\mu}_m(C) \geq 4r_m$, where $\widehat{\mu}_m^{\max} := \max_{C \in \mathcal{A}_m} \widehat{\mu}_m(C)$. After necessary removal of "bad cubes", each cube in $\mathcal{A}_m$ that survives the elimination is equally partitioned into $\left(\frac{r_m}{r_{m+1}}\right)^d$ subcubes of edge length r_{m+1}, where r_{m+1} is predetermined. These cubes (of edge length r_{m+1}) are collected to construct $\mathcal{A}_{m+1}$, and the learning process moves on to the next batch. Appropriate rounding may be required to ensure the ratio $\frac{r_m}{r_{m+1}}$ is an integer. See Remark 2 for more details.

The learning process is summarized in Algorithm 1.

The following theorem gives regret and communication upper bound of BLiN with Doubling Edge-length Sequence $r_m = 2^{-m+1}$ (see Appendix B for proof). Note that this result implies Theorem 1.

---

[1] One can arbitrarily play $x_{C,1}, x_{C,2}, \cdots, x_{C,n_m}$ as long as $x_{C,i} \in C$ for all i.

Algorithm 1 Batched Lipschitz Narrowing (BLiN)

1: **Input.** Arm set $\mathcal{A} = [0,1]^d$; time horizon T.
2: **Initialization** Number of batches B; Edge-length sequence $\{r_m\}_{m=1}^{B+1}$; The first grid point $t_0 = 0$; Equally partition $\mathcal{A}$ to r_1^d subcubes and define $\mathcal{A}_1$ as the collection of these subcubes.
3: Compute $n_m = \frac{16 \log T}{r_m^2}$ for $m = 1, \cdots, B+1$.
4: **for** $m = 1, 2, \cdots, B$ **do**
5: For each cube $C \in \mathcal{A}_m$, play arms $x_{C,1}, \cdots x_{C,n_m}$ from C.
6: Collect the rewards of all pulls up to t_m. Compute the average payoff $\widehat{\mu}_m(C) = \frac{\sum_{i=1}^{n_m} y_{C,i}}{n_m}$ for each cube $C \in \mathcal{A}_m$. Find $\widehat{\mu}_m^{max} = \max_{C \in \mathcal{A}_m} \widehat{\mu}(C)$.
7: For each cube $C \in \mathcal{A}_m$, eliminate C if $\widehat{\mu}_m^{max} - \widehat{\mu}_m(C) > 4r_m$. Let $\mathcal{A}_m^+$ be set of cubes not eliminated.
8: Compute $t_{m+1} = t_m + (r_m/r_{m+1})^d \cdot |\mathcal{A}_m^+| \cdot n_{m+1}$. If $t_{m+1} \geq T$ or $m = B$ then **break**.
9: Equally partition each cube in $\mathcal{A}_m^+$ into $(r_m/r_{m+1})^d$ subcubes and define $\mathcal{A}_{m+1}$ as the collection of these subcubes. /*See Remark 2 for more details on cases where $(r_m/r_{m+1})^d$ is not an integer.*/
10: **end for**
11: **Cleanup:** Arbitrarily play the remaining arms until all T steps are used.

Theorem 3. *With probability exceeding $1 - \frac{2}{T^6}$, the T-step total regret $R(T)$ of BLiN with Doubling Edge-length Sequence (D-BLiN) satisfies*

$$R(T) \leq 528 (\log T)^{\frac{1}{d_z+2}} \cdot T^{\frac{d_z+1}{d_z+2}},$$

where d_z is the zooming dimension of the problem instance. In addition, D-BLiN only needs no more than $\frac{\log T - \log \log T}{d_z+2} + 2$ rounds of communications to achieve this regret rate.

Although D-BLiN efficiently solves batched Lipschitz bandits, its simple partition strategy leads to suboptimal communication complexity. Now we show that by approporiately combining some batches, BLiN achieves the optimal communication bound, without incurring increasing regret. Specifically, we introduce the following edge-length sequence, which we call ACE Sequence.

Definition 1. *For a problem with ambient dimension d, zooming dimension d_z and time horizon T, we denote $c_1 = \frac{d_z+1}{(d+2)(d_z+2)} \log \frac{T}{\log T}$ and $c_{i+1} = \eta c_i$ for any $i \geq 1$, where $\eta = \frac{d+1-d_z}{d+2}$. Then the Appropriate Combined Edge-length Sequence $\{r_m\}$ is defined by $r_m = 2^{-\sum_{i=1}^m c_i}$ for any $m \geq 1$.*

We show that BLiN with ACE Sequence (A-BLiN) obtains an improved communication complexity, thus proves Theorem 2.

Theorem 4. *With probability exceeding $1 - \frac{2}{T^6}$, the T-step total regret $R(T)$ of Algorithm 1 satisfies*

$$R(T) \leq \left(\frac{128 C_z}{\log \frac{d+2}{d+1-d_z}} \cdot \log \log T + 8e \right) \cdot T^{\frac{d_z+1}{d_z+2}} (\log T)^{\frac{1}{d_z+2}}, \tag{2}$$

where d_z is the zooming dimension of the problem instance. In addition, Algorithm 1 only needs no more than $\frac{\log \log T}{\log \frac{d+2}{d+1-d_z}} + 1$ rounds of communications to achieve this regret rate.

The partition and elimination process of a real A-BLiN run is in Figure 1. In the i-th subgraph, the white cubes are those remaining after the $(i-1)$-th batch. In this experiment, we set $\mathcal{A} = [0,1]^2$, and the optimal arm is $x^* = (0.8, 0.7)$. Note that x^* is not eliminated during the game. More details of this experiment are in Section 5.

Remark 1 (Time and space complexity)**.** *The time complexity of our algorithm is $\mathcal{O}(T)$, which is better than the state of the art $\mathcal{O}(T \log T)$ in [14]. This is because that the running time of a batch j is of order $\mathcal{O}(l_j)$, where $l_j = t_j - t_{j-1}$ is number of samples in batch j. Since $\sum_j l_j = T$, the time complexity of BLiN is $\mathcal{O}(T)$. Besides, the space complexity of BLiN is also improved, because we do not need to store information of cubes in previous batches.*

Figure 1: Partition and elimination process of A-BLiN. The i-th subfigure shows the pattern before the i-th batch, which is from a real A-BLiN run on the reward function defined in Section 5. Dark gray cubes are those eliminated in the most recent batch, while the light gray ones are those eliminated in earlier batches. For the total time horizon $T = 80000$, A-BLiN needs 4 rounds of communications. For this experiment, $r_1 = \frac{1}{4}$, $r_2 = \frac{1}{8}$, $r_3 = \frac{1}{16}$, $r_4 = \frac{1}{32}$, which is the ACE sequence (rounded as in Remark 2) for $d = 2$ and $d_z = 0$.

3 Regret Analysis of A-BLiN

In this section, we provide regret analysis for A-BLiN. The highlight of the finding is that $\mathcal{O}(\log \log T)$ batches are sufficient to achieve optimal regret rate of $\widetilde{\mathcal{O}}\left(T^{\frac{d_z+1}{d_z+2}}\right)$, as summarized in Theorem 4.

To prove Theorem 4, we first show that the estimator $\widehat{\mu}$ is concentrated to the true expected reward μ (Lemma 1), and the optimal arm survives all eliminations with high probability (Lemma 2). In the following analysis, we let B_{stop} be the total number of batches of the BLiN run.

Lemma 1. *Define*
$$\mathcal{E} := \left\{ |\mu(x) - \widehat{\mu}_m(C)| \leq r_m + \sqrt{\frac{16 \log T}{n_m}}, \forall 1 \leq m \leq B_{\text{stop}} - 1, \ \forall C \in \mathcal{A}_m, \ \forall x \in C \right\}.$$

It holds that $\mathbb{P}\left(\mathcal{E}\right) \geq 1 - 2T^{-6}$.

Lemma 2. *Under event $\mathcal{E}$, the optimal arm $x^* = \arg\max \mu(x)$ is not eliminated after the first $B_{\text{stop}} - 1$ batches.*

Based on these results, we show the cubes that survive elimination are of high reward.

Lemma 3. *Under event $\mathcal{E}$, for any $1 \leq m \leq B_{\text{stop}}$, any $C \in \mathcal{A}_m$ and any $x \in C$, Δ_x satisfies*
$$\Delta_x \leq 8r_{m-1}. \tag{3}$$

The proofs of Lemma 1-3 are in Appendix A. We are now ready to prove the theorem.

Proof of Theorem 4. Let R_m denote regret of the m-th batch. Fixing any positive number B, the total regret $R(T)$ can be divided into two parts: $R(T) = \sum_{m \leq B} R_m + \sum_{m > B} R_m$. In the following, we bound these two parts separately and then determine B to obtain the upper bound of the total regret. Moreover, we show A-BLiN uses only $\mathcal{O}(\log \log T)$ rounds of communications to achieve the optimal regret.

Recall that $\mathcal{A}_m$ is set of the active cubes in the m-th batch. According to Lemma 3, for any $x \in \cup_{C \in \mathcal{A}_m} C$, we have $\Delta_x \leq 8r_{m-1}$. Let $\mathcal{A}_m^+$ be set of cubes not eliminated in batch m. Then any cube in $\mathcal{A}_{m-1}^+$ is a subset of $S(8r_{m-1})$, and thus
$$|\mathcal{A}_{m-1}^+| \leq N_{r_{m-1}} \leq C_z r_{m-1}^{-d_z}. \tag{4}$$
By definition, $r_m = r_{m-1}2^{-c_m}$, so
$$|\mathcal{A}_m| = 2^{dc_m}|\mathcal{A}_{m-1}^+|. \tag{5}$$
The total regret of the m-th batch is
$$R_m = \sum_{C \in \mathcal{A}_m} \sum_{i=1}^{n_m} \Delta_{x_{C,i}} \leq |\mathcal{A}_m| \cdot \frac{16 \log T}{r_m^2} \cdot 8r_{m-1} \stackrel{(i)}{=} 2^{dc_m} |\mathcal{A}_{m-1}^+| \cdot \frac{16 \log T}{r_m^2} \cdot 8r_{m-1}$$
$$\stackrel{(ii)}{\leq} 2^{dc_m} \cdot C_z r_{m-1}^{-d_z+1} \cdot \frac{128 \log T}{r_m^2} \stackrel{(iii)}{=} 2^{(\sum_{i=1}^{m-1} c_i)(d_z+1)+c_m(d+2)} \cdot 128 C_z \log T,$$

221 where (i) follows from (5), (ii) follows from (4), and (iii) follows from the definition of ACE Sequence.

222 Define $C_m = (\sum_{i=1}^{m-1} c_i)(d_z + 1) + c_m(d + 2)$. Since $c_m = c_{m-1} \cdot \frac{d+1-d_z}{d+2}$, calculation shows that

223 $C_m = (\sum_{i=1}^{m-2} c_i)(d_z + 1) + c_{m-1}(d + 2) + c_{m-1}(d_z + 1 - d - 2) + c_m(d + 2) = C_{m-1}$. Thus

224 for any m, we have $C_m = C_1 = c_1(d + 2)$. Hence,

$$R_m \leq 2^{c_1(d+2)} \cdot 128 C_z \log T = T^{\frac{d_z+1}{d_z+2}} \cdot 128 C_z (\log T)^{\frac{1}{d_z+2}}. \tag{6}$$

225 The inequality (6) holds even if the m-th batch does not exist (where we let $R_m = 0$) or is not

226 completed. Thus we obtain the first upper bound $\sum_{m \leq B} R_m \leq T^{\frac{d_z+1}{d_z+2}} \cdot 128 C_z \cdot B(\log T)^{\frac{1}{d_z+2}}$.

227 Lemma 3 implies that any arm x played after the first B batches satisfies $\Delta_x \leq 8 r_B$, so the total

228 regret after B batches is bounded by

$$\sum_{m > B} R_m \leq 8 r_B \cdot T = 8T \cdot 2^{-\sum_{i=1}^{B} c_i} = 8T \cdot 2^{-c_1(\frac{1-\eta^B}{1-\eta})}$$

$$= 8T^{\frac{d_z+1}{d_z+2}} (\log T)^{\frac{1}{d_z+2}} \cdot (T/\log T)^{\frac{\eta^B}{d_z+2}} \leq 8T^{\frac{d_z+1}{d_z+2}} (\log T)^{\frac{1}{d_z+2}} \cdot T^{\frac{\eta^B}{d_z+2}}.$$

229 Therefore, the total regret $R(T)$ satisfies

$$R(T) = \sum_{m \leq B} R_m + \sum_{m > B} R_m \leq \left(128 C_z \cdot B + 8T^{\frac{\eta^B}{d_z+2}} \right) \cdot T^{\frac{d_z+1}{d_z+2}} (\log T)^{\frac{1}{d_z+2}}.$$

230 This inequality holds for any positive B. Then by choosing $B^* = \frac{\log\log T - \log(d_z+2)}{\log \frac{1}{\eta}} =$

231 $\frac{\log\log T - \log(d_z+2)}{\log \frac{d+2}{d+1-d_z}}$, we have $\frac{\eta^{B^*}}{d_z+2} = \frac{1}{\log T}$ and

$$R(T) \leq \left(\frac{128 C_z \log\log T}{\log \frac{d+2}{d+1-d_z}} + 8e \right) \cdot T^{\frac{d_z+1}{d_z+2}} (\log T)^{\frac{1}{d_z+2}}.$$

232 The above analysis implies that we can achieve the optimal regret rate $\widetilde{\mathcal{O}}\left(T^{\frac{d_z+1}{d_z+2}}\right)$ by letting the

233 *for-loop* run B^* times and finishing the remaining rounds in the *Cleanup* step. In other words, $B^* + 1$

234 rounds of communications are sufficient for A-BLiN to achieve the regret bound (2). □

235 **Remark 2.** *The quantity $\frac{r_m}{r_{m+1}}$ in line 9 of Algorithm 1 may not be integers for some m. Thus,*

236 *in practice we denote $\alpha_n = \lfloor \sum_{i=1}^{n} c_i \rfloor$, $\beta_n = \lceil \sum_{i=1}^{n} c_i \rceil$, and define rounded ACE Sequence*

237 *$\{\widetilde{r}_m\}_{m \in \mathbb{N}}$ by $\widetilde{r}_m = 2^{-\alpha_k}$ for $m = 2k - 1$ and $\widetilde{r}_m = 2^{-\beta_k}$ for $m = 2k$. Then the total regret can*

238 *be divided as $R(T) = \sum_{1 \leq k \leq B^*} R_{2k-1} + \sum_{1 \leq k \leq B^*} R_{2k} + \sum_{m > 2B^*} R_m$. For the first part we*

239 *have $\widetilde{r}_{2k-2} \leq r_{k-1}$ and $\widetilde{r}_{2k-1} \geq r_k$, while for the second part we have $\frac{\widetilde{r}_{2k-1}}{\widetilde{r}_{2k}} = 2$. Therefore, by*

240 *similar argument to the proof of Theorem 4, we can bound these three parts separately, and conclude*

241 *that BLiN with rounded ACE sequence achieves the optimal regret bound $\widetilde{\mathcal{O}}(T^{\frac{d_z+1}{d_z+2}})$ by using only*

242 *$\mathcal{O}(\log\log T)$ rounds of communications. The details are in Appendix C.*

4 Lower Bounds

244 In this section, we present lower bounds for Lipschitz bandits with batched feedback, which in turn

245 gives communication lower bounds for all Lipschitz bandit algorithms. Our lower bounds depend on

246 the rounds of communications B. When B is sufficiently large, our results match the lower bound

247 for the vanilla Lipschitz bandit problem $\widetilde{\Theta}(R_z(T))$ ($R_z(T)$ is defined in Eq. 1). More importantly,

248 this dependency on B gives the minimal rounds of communications needed to achieve optimal regret

249 bound for all Lipschitz bandit algorithms, which is summarized in Corollary 2. Since this lower

250 bound matches the upper bound presented in Theorem 4, BLiN optimally solves Lipschitz bandits

251 with minimal communication.

4.1 Proof Outline

Similar to most lower bound proofs, we need to construct problem instances that are difficult to differentiate. What's different is that we need to carefully integrate batched feedback pattern [32] with the Lipschitz payoff reward [38, 29]. To capture the adaptivity in grid determination, we construct "static reference communication grids" to remove the stochasticity in grid selection [1, 20]. Below, we first consider the static grid case, where the grid is predetermined. This static grid case will provide intuition for the adaptive and more general case.

The expected reward functions of these instances are constructed as follows: we choose some 'position' and 'height', such that the expected reward function obtains local maximum of the specified 'height' at the specified 'position'. We will use the word 'peak' to refer to the local maxima. The following theorem presents the lower bound for the static grid case.

Theorem 5 (Lower Bound for Static Grid). *Consider Lipschitz bandit problems with time horizon T such that the grid of reward communication $\mathcal{T}$ is static and determined before the game. If B rounds of communications are allowed, then for any policy π, there exists a problem instance such that*

$$\mathbb{E}[R_T(\pi)] \geq c \cdot (\log T)^{-\frac{\frac{1}{d+2}}{1-\left(\frac{1}{d+2}\right)^B}} \cdot R_z(T)^{\frac{1}{1-\left(\frac{1}{d+2}\right)^B}},$$

where $c > 0$ is a numerical constant independent of B, T, π and $\mathcal{T}$, $R_z(T)$ is defined in (1), and d is the dimension of the arm space.

To prove Theorem 5, we first show that for any $k > 1$ there exists an instance such that $\mathbb{E}[R_T(\pi)] \geq \frac{t_k}{t_{k-1}^{\frac{1}{d+2}}}$. Fixing $k > 1$, we let $r_k = \frac{1}{t_{k-1}^{\frac{1}{d+2}}}$ and $M_k := t_{k-1}r_k^2 = \frac{1}{r_k^d}$. Then we construct a set of problem instances $\mathcal{I}_k = \{I_{k,1}, \cdots, I_{k,M_k}\}$, such that the gap between the highest peak and the second highest peak is about r_k for every instance in $\mathcal{I}_k$.

Based on this construction, we prove that no algorithm can distinguish instances in $\mathcal{I}_k$ from one another in the first $(k-1)$ batches, so the worst-case regret is at least $r_k t_k$, which gives the inequality we need. For the first batch $(0, t_1]$, we can easily construct a set of instances where the worst-case regret is at least t_1, since no information is available during this time. Thus, there exists a problem instance such that $\mathbb{E}[R_T(\pi)] \gtrsim \max\left\{t_1, \frac{t_2}{t_1^{\frac{1}{d+2}}}, \cdots, \frac{t_B}{t_{B-1}^{\frac{1}{d+2}}}\right\}$. Since $0 < t_1 < \cdots < t_B = T$, the inequality in Theorem 5 follows.

As a result of Theorem 5, we can derive the minimum rounds of communications needed to achieve optimal regret bound for Lipschitz bandit problem, which is stated in Corollary 1.

Corollary 1. *Any Lipschitz bandit algorithm needs $\Omega(\log \log T)$ rounds of communications to achieve the optimal regret rate, for the case that the times of reward communication are predetermined and static.*

The detailed proof of Theorem 5 and Corollary 1 are deferred to Appendix D and E.

4.2 Communication Lower Bound for BLiN

So far we have derived lower bounds for the static grid case. Yet there is a gap between the static and the adaptive case. We will close this gap in the following Theorem.

Theorem 6 (Lower Bound for Adaptive Grid). *Consider Lipschitz bandit problems with time horizon T such that the grid of reward communication $\mathcal{T}$ is adaptively determined by the player. If B rounds of communications are allowed, then for any policy π, there exists an instance such that*

$$\mathbb{E}\left[R_T(\pi)\right] \geq c\frac{1}{B^2}(\log T)^{-\frac{\frac{1}{d+2}}{1-\left(\frac{1}{d+2}\right)^B}} R_z(T)^{\frac{1}{1-\left(\frac{1}{d+2}\right)^B}},$$

where $c > 0$ is a numerical constant independent of B, T, π and $\mathcal{T}$, $R_z(T)$ is defined in (1), and d is the dimension of the arm space.

To prove Theorem 6, we consider a reference static grid $\mathcal{T}_r = \{T_0, T_1, \cdots, T_B\}$, where $T_j = T^{\frac{1-\varepsilon^j}{1-\varepsilon^B}}$ for $\varepsilon = \frac{1}{d+2}$. We construct a series of 'worlds', denoted by $\mathcal{I}_1, \cdots, \mathcal{I}_B$. Each world is a set of

294 problem instances, and each problem instance in world $\mathcal{I}_j$ is defined by peak location set $\mathcal{U}_j$ and
295 basic height r_j, where the sets $\mathcal{U}_j$ and quantities r_j for $1 \le j \le B$ are presented in Appendix F.

296 Based on these constructions, we first prove that for any adaptive grid and policy, there exists an
297 index j such that the event $A_j = \{t_{j-1} < T_{j-1}, \ t_j \ge T_j\}$ happens with sufficiently high probability
298 in world $\mathcal{I}_j$. Then similar to Theorem 5, we prove that in world $\mathcal{I}_j$ there exists a set of problem
299 instances that is difficult to differentiate in the first $j - 1$ batches. In addition, event A_j implies that
300 $t_j \ge T_j$, so the worst-case regret is at least $r_j T_j$, which gives the lower bound we need.

301 The proof of Theorem 6 is deferred to Appendix F. Similar to Corollary 1, we can prove that at least
302 $\Omega(\log \log T)$ rounds of communications are needed to achieve optimal regret bound. This result is
303 formally summarized in Corollary 2.

304 **Corollary 2.** *Any Lipschitz bandit algorithm[2] needs $\Omega(\log \log T)$ rounds of communications to*
305 *achieve the optimal regret rate.*

5 Experiments

307 In this section, we present numerical studies of A-BLiN. In the experiments, we use the arm space
308 $\mathcal{A} = [0, 1]^2$ and the expected reward function $\mu(x) = 1 - \frac{1}{2}\|x - x_1\|_2 - \frac{3}{10}\|x - x_2\|_2$, where
309 $x_1 = (0.8, \ 0.7)$ and $x_2 = (0.1, \ 0.1)$. The landscape of μ and the resulting partition is shown in
310 Figure 2(a). As can be seen, the partition is finer in the area closer to the optimal arm $x^* = (0.8, \ 0.7)$.

(a) Partition (b) Regret

Figure 2: Resulting partition and regret of A-BLiN. In Figure 2(a), we show the resulting partition
of A-BLiN. The background color denotes the true value of expected reward μ, and blue means
high values. The figure shows that the partition is finer for larger values of μ. In Figure 2(b), we
show accumulated regret of A-BLiN and zooming algorithm [25]. In the figure, different background
colors represent different batches of A-BLiN. For the total time horizon $T = 80000$, A-BLiN needs 4
rounds of communications.

311 We let the time horizon $T = 80000$, and report the accumulated regret in Figure 2(b). The regret
312 curve is sublinear, which agrees with the regret bound (2). Besides, different background colors
313 in Figure 2(b) represent different batches. For the total time horizon $T = 80000$, A-BLiN only
314 needs 4 rounds of communications. We also present regret curve of zooming algorithm [25] for
315 comparison. Different from zooming algorithm, regret curve of A-BLiN is approximately piecewise
316 linear, which is because the strategy of BLiN does not change within each batch. Results of more
317 repeated experiments are in Appendix G, as well as experimental results of D-BLiN.

6 Conclusion

319 In this paper, we study Lipschitz bandits with communication constraints, and propose the BLiN
320 algorithm as a solution. We prove that BLiN only need $\mathcal{O}(\log \log T)$ rounds of communications
321 to achieve the optimal regret rate of best previous Lipschitz bandit algorithms [25, 13] that need
322 T batches. This improvement in number of the batches significantly saves data communication
323 costs. We also provide complexity analysis for this problem. We show that $\Omega(\log \log T)$ rounds
324 of communications are necessary for any algorithm to optimally solve Lipschitz bandit problems.
325 Hence, BLiN algorithm is optimal.

---

[2]including algorithms of which the number of batches can be determined adaptively

References

[1] Arpit Agarwal, Shivani Agarwal, Sepehr Assadi, and Sanjeev Khanna. Learning with limited rounds of adaptivity: coin tossing, multi-armed bandits, and ranking from pairwise comparisons. In *Conference on Learning Theory*, pages 39–75. PMLR, 2017.

[2] Arpit Agarwal, Rohan Ghuge, and Viswanath Nagarajan. Batched dueling bandits. *arXiv preprint arXiv:2202.10660*, 2022.

[3] Rajeev Agrawal. The continuum-armed bandit problem. *SIAM Journal on Control and Optimization*, 33(6):1926–1951, 1995.

[4] Rajeev Agrawal. Sample mean based index policies by $\mathcal{O}(\log n)$ regret for the multi-armed bandit problem. *Advances in Applied Probability*, 27(4):1054–1078, 1995.

[5] Noga Alon, Yossi Matias, and Mario Szegedy. The space complexity of approximating the frequency moments. *Journal of Computer and System Sciences*, 58(1):137–147, 1999.

[6] Patrice Assouad. Plongements Lipschitziens dans $\mathbb{R}^n$. *Bulletin de la Société Mathématique de France*, 111:429–448, 1983.

[7] Peter Auer, Nicolò Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2):235–256, 2002.

[8] Peter Auer, Nicolò Cesa-Bianchi, Yoav Freund, and Robert E. Schapire. The nonstochastic multiarmed bandit problem. *SIAM journal on computing*, 32(1):48–77, 2002.

[9] Peter Auer, Ronald Ortner, and Csaba Szepesvári. Improved rates for the stochastic continuum-armed bandit problem. In *Conference on Computational Learning Theory*, pages 454–468. Springer, 2007.

[10] Dimitris Bertsimas and Adam J Mersereau. A learning approach for interactive marketing to a customer segment. *Operations Research*, 55(6):1120–1135, 2007.

[11] Peter J. Bickel. On some robust estimates of location. *The Annals of Mathematical Statistics*, pages 847–858, 1965.

[12] Sébastien Bubeck, Nicolo Cesa-Bianchi, and Gábor Lugosi. Bandits with heavy tail. *IEEE Transactions on Information Theory*, 59(11):7711–7717, 2013.

[13] Sébastien Bubeck, Rémi Munos, Gilles Stoltz, and Csaba Szepesvári. Online optimization in $\mathcal{X}$-armed bandits. *Advances in Neural Information Processing Systems*, 22:201–208, 2009.

[14] Sébastien Bubeck, Rémi Munos, Gilles Stoltz, and Csaba Szepesvári. $\mathcal{X}$-armed bandits. *Journal of Machine Learning Research*, 12(5):1655–1695, 2011.

[15] Sébastien Bubeck, Gilles Stoltz, and Jia Yuan Yu. Lipschitz bandits without the Lipschitz constant. In *International Conference on Algorithmic Learning Theory*, pages 144–158. Springer, 2011.

[16] Nicolo Cesa-Bianchi, Ofer Dekel, and Ohad Shamir. Online learning with switching costs and other adaptive adversaries. *Advances in Neural Information Processing Systems*, 26:1160–1168, 2013.

[17] Eric W. Cope. Regret and convergence bounds for a class of continuum-armed bandit problems. *IEEE Transactions on Automatic Control*, 54(6):1243–1253, 2009.

[18] Hossein Esfandiari, Amin Karbasi, Abbas Mehrabian, and Vahab Mirrokni. Regret bounds for batched bandits. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 7340–7348, 2021.

[19] Eyal Even-Dar, Shie Mannor, Yishay Mansour, and Sridhar Mahadevan. Action elimination and stopping conditions for the multi-armed bandit and reinforcement learning problems. *Journal of machine learning research*, 7(6):1079–1105, 2006.

[20] Zijun Gao, Yanjun Han, Zhimei Ren, and Zhengqing Zhou. Batched multi-armed bandits problem. *Advances in Neural Information Processing Systems*, 32:503–513, 2019.

[21] Yanjun Han, Zhengqing Zhou, Zhengyuan Zhou, Jose Blanchet, Peter W Glynn, and Yinyu Ye. Sequential batch learning in finite-action linear contextual bandits. *arXiv preprint arXiv:2004.06321*, 2020.

[22] Kwang-Sung Jun, Kevin Jamieson, Robert Nowak, and Xiaojin Zhu. Top arm identification in multi-armed bandits with batch arm pulls. In *Artificial Intelligence and Statistics*, pages 139–148. PMLR, 2016.

[23] Nikolai Karpov, Qin Zhang, and Yuan Zhou. Collaborative top distribution identifications with limited interaction. In *2020 IEEE 61st Annual Symposium on Foundations of Computer Science (FOCS)*, pages 160–171. IEEE, 2020.

[24] Robert Kleinberg. Nearly tight bounds for the continuum-armed bandit problem. *Advances in Neural Information Processing Systems*, 18:697–704, 2005.

[25] Robert Kleinberg, Aleksandrs Slivkins, and Eli Upfal. Multi-armed bandits in metric spaces. In *Proceedings of the fortieth annual ACM symposium on Theory of computing*, pages 681–690, 2008.

[26] Akshay Krishnamurthy, John Langford, Aleksandrs Slivkins, and Chicheng Zhang. Contextual bandits with continuous actions: smoothing, zooming, and adapting. In *Conference on Learning Theory*, pages 2025–2027. PMLR, 2019.

[27] Tze Leung Lai and Herbert Robbins. Asymptotically efficient adaptive allocation rules. *Advances in Applied Mathematics*, 6(1):4–22, 1985.

[28] Zihan Li and Jonathan Scarlett. Gaussian process bandit optimization with few batches. In *International Conference on Artificial Intelligence and Statistics*, pages 92–107. PMLR, 2022.

[29] Shiyin Lu, Guanghui Wang, Yao Hu, and Lijun Zhang. Optimal algorithms for Lipschitz bandits with heavy-tailed rewards. In *International Conference on Machine Learning*, pages 4154–4163, 2019.

[30] Stefan Magureanu, Richard Combes, and Alexandre Proutiere. Lipschitz bandits: Regret lower bound and optimal algorithms. In *Conference on Learning Theory*, pages 975–999. PMLR, 2014.

[31] Vianney Perchet and Philippe Rigollet. The multi-armed bandit problem with covariates. *The Annals of Statistics*, 41(2):693–721, 2013.

[32] Vianney Perchet, Philippe Rigollet, Sylvain Chassang, and Erik Snowberg. Batched bandit problems. *The Annals of Statistics*, 44(2):660–681, 2016.

[33] Stuart J. Pocock. Group sequential methods in the design and analysis of clinical trials. *Biometrika*, 64(2):191–199, 1977.

[34] Yufei Ruan, Jiaqi Yang, and Yuan Zhou. Linear bandits with limited adaptivity and learning distributional optimal design. In *Proceedings of the 53rd Annual ACM SIGACT Symposium on Theory of Computing*, pages 74–87, 2021.

[35] Sudeep Salgia, Sattar Vakili, and Qing Zhao. A domain-shrinking based bayesian optimization algorithm with order-optimal regret performance. In *Advances in Neural Information Processing Systems*, volume 34, pages 28836–28847, 2021.

[36] David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, Sander Dieleman, Dominik Grewe, John Nham, Nal Kalchbrenner, Ilya Sutskever, Timothy Lillicrap, Madeleine Leach, Koray Kavukcuoglu, Thore Graepel, and Demis Hassabis. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.

[37] Sean Sinclair, Tianyu Wang, Gauri Jain, Siddhartha Banerjee, and Christina Yu. Adaptive discretization for model-based reinforcement learning. *Advances in Neural Information Processing Systems*, 33:3858–3871, 2020.

[38] Aleksandrs Slivkins. Contextual bandits with similarity information. *Journal of Machine Learning Research*, 15(1):2533–2568, 2014.

[39] Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. MIT press, 2018.

[40] Chao Tao, Qin Zhang, and Yuan Zhou. Collaborative learning with limited interaction: tight bounds for distributed exploration in multi-armed bandits. In *2019 IEEE 60th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 126–146. IEEE, 2019.

[41] William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3/4):285–294, 1933.

[42] Tianyu Wang and Cynthia Rudin. Bandits for BMO functions. In *International Conference on Machine Learning*, pages 9996–10006. PMLR, 2020.

[43] Nirandika Wanigasekara and Christina Yu. Nonparametric contextual bandits in an unknown metric space. In *Advances in Neural Information Processing Systems*, volume 32, pages 14684–14694, 2019.

[44] Kelly Zhang, Lucas Janson, and Susan Murphy. Inference for batched bandits. *Advances in Neural Information Processing Systems*, 33:9818–9829, 2020.