Learning Efficient Vision Transformers via Fine-Grained Manifold Distillation

Abstract

In the past few years, transformers have achieved promising performances on various computer vision tasks. Unfortunately, the immense inference overhead of most existing vision transformers withholds their from being deployed on edge devices such as cell phones and smart watches. Knowledge distillation is a widely used paradigm for compressing cumbersome architectures via transferring information to a compact student. However, most of them are designed for convolutional neural networks (CNNs), which do not fully investigate the character of vision transformer (ViT). In this paper, we utilize the patch-level information and propose a fine-grained manifold distillation method. Specifically, we train a tiny student model to match a pre-trained teacher model in the patch-level manifold space. Then, we decouple the manifold matching loss into three terms with careful design to further reduce the computational costs for the patch relationship. Equipped with the proposed method, a DeiT-Tiny model containing 5M parameters achieves 76.5% top-1 accuracy on ImageNet-1k, which is +2.0% higher than previous distillation approaches. Transfer learning results on other classification benchmarks and downstream vision tasks also demonstrate the superiority of our method over the state-of-the-art algorithms.

1 Introduction

The past decade has witnessed the rise of attention-based models in the field of natural language processing (NLP) [1, 2]. Such models belonging to the transformer family [3] can effortlessly build long-range dependencies and have achieved remarkable performance. Inspired by the success in NLP, researchers have made great efforts to introduce the transformer-based architectures to vision domains and achieved promising results. In an early attempt, Dosovitskiy *et al.* [4] proposed a transformer-based vision model termed ViT, which takes split image patches as the input. Surprisingly, ViT obtains comparable performance when compared to the state-of-the-art convolutional neural networks (CNNs), demonstrating the immense potential of applying transformers to solve vision tasks. Inspired by the design of replacing the whole image with patches as input, various vision transformers have been proposed, including Swin [5], T2T [6], Twins [7], and TNT [8].

Although many transformers have shown the excellent capability for various vision tasks, they often require more parameters with large computational burden. For example, ViT-B [4], which contains 86M parameters and is well pre-trained on JFT-300M, can only achieve comparably performance when compared to a ImageNet pre-trained CNN-based architecture [9] with 5M parameters.

The requirement for large computing resource and storage prevents them from being deployed on memory-bounded edge devices such as cell phones and smart watches. To facilitate the challenges above, a series of methods have been proposed to investigate compact deep neural networks, such as network pruning [10, 11], low-bit quantization [12] and knowledge distillation [13].

(a) Image-level manifold space   (b) Patch-level manifold space

Figure 1: Comparison between (a) image-level manifold space and (b) patch-level manifold space. The patch-level manifold space containing fine-grained information facilitates knowledge transfer.

However, smaller models usually lead to performance degradation. Knowledge distillation (KD) [13] is a promising approach for inheriting information from a high-performance teacher to a compact student and maintaining the strong performance.

Touvron *et al.* [14] first proposed a KD-based compression approach for vision transformers. They trained the student transformer to match hard labels provided by a pre-trained CNN teacher. Although this approach obtains satisfying result, they ignore the intermediate-layer information inherited in vision transformers. There have been works [15, 16] proving the effectiveness of learning from intermediate layers for transformers in NLP, but these methods require teachers and students to have exactly the same embedding dimension at corresponding layers, which is a fairly tight constraint and cannot always be satisfied. Manifold learning-based KD [17, 18] can support layers with mismatching dimensions and make use of inter-sample information concurrently. However, existing manifold distillation approaches are designed for CNNs and cannot utilize the patch-level information of vision transformers. As shown in Figure 1, patches depict a manifold space in a more fine-grained way. Such information can facilitate knowledge transfer remarkably.

Based on this consideration, we propose a fine-grained patch-level manifold distillation method. In particular, we regard vision transformers as projectors mapping inputs into multiple manifold spaces layer by layer. At each layer, we collect embeddings of patches to build their manifold relation map and train the student to match the relation map of the teacher. Since the computational complexity is high, we decouple the relation maps into three parts, which reduces the complexity by around two orders of magnitude. We evaluate the proposed method on the ImageNet-1k image classification task. The proposed manifold KD outperforms the distillation method in [14] by +2.0% top-1 accuracy on DeiT-Tiny. We also conduct transfer learning experiments on CIFAR-10/100 and evaluation our method on the downstream vision task such as object detection. The proposed method outperforms its counterparts on both tasks. Our contributions are summarized as follows:

- We propose a fine-grained manifold distillation method, which transfers patch-level manifold information between vision transformers.
- We use three decoupled terms to describe the manifold space and simplify the computational complexity significantly.
- We conduct extensive experiments to verify the effectiveness of the proposed method. The results also demonstrate the importance of soft-label distillation and fixed-depth students.

2 Related works

2.1 Vision transformer

Transformer was originally designed for NLP tasks [19]. Inspired by its remarkable performance, researchers have made efforts to adopt transformer-based models in CV tasks [20, 21]. Among them, Dosovitskiy *et al.* [4] proposed to divide an image into patches and used embeddings of the patches as model input. According to their input processing scheme, many variants of vision transformers have

been proposed. For example, Han *et al.* [8] proposed TNT to model in-patch attention, Zhou *et al.* [22] and Touvron *et al.* [23] built deeper vision transformers, and some researchers [24, 5] adopted the experience in CNN to guide the design of vision transformers. However, Most well-performed vision transformers are extremely resource-consuming and should be compressed for deployment.

2.2 Knowledge distillation

KD is a model compression method proposed by Hinton *et al.* [13], which trains a lightweight student model to match soft labels given by a large pre-trained teacher model. Moreover, there are also works combining adversarial training with KD [25], or training a student with only a few samples [26]. Due to its excellent performance, KD has been adopted in various research fields, such as CV [26, 25], NLP [15], and recommendation systems [27]. To compress vision transformers, Touvron *et al.* [14] proposed a KD-based method termed DeiT. They added a distillation token into the student and train the student with hard labels provided by the teacher. Although DeiT has achieved remarkable performance, KD for vision transformers has not been well explored yet.

2.3 Manifold learning

Manifold learning is an approach for non-linear dimensionality reduction. It learns a smooth manifold embedded in the original feature space to construct low-dimensional features [28, 29]. Recently, several works introduce manifold learning in KD [17, 18]. These methods train the student to preserve relationships among samples learned by the teacher. For vision transformers, these primary attempts are coarse and can be further improved because the basic input elements are patches but not images.

3 Method

3.1 Preliminaries

Vision transformer. Vision transformers are attention-based models, and each layer of them consists of a multi-head self-attention (MSA) block and a multi-layer perceptron (MLP) block. These models take split images as input, *i.e.*, the patches. In particular, assuming the patch size is $P \times P$, an input image $\mathbf{x} \in \mathbb{R}^{H \times W \times C}$ of size $H \times W$ and channel number C is reshaped into flattened patches $\mathbf{x_p} \in \mathbb{R}^{N \times (P^2 \cdot C)}$ for processing, where $N = HW/P^2$. The patches are then projected into a D-dimension embedding space and added to positional embeddings. We denote the summation as $\mathbf{x}_e \in \mathbb{R}^{N \times D}$. Each model layer works as follows:

$$\mathbf{x}_e \leftarrow \text{MSA}(\text{LN}(\mathbf{x}_e)) + \mathbf{x}_e, \tag{1}$$

$$\mathbf{x}_e \leftarrow \text{MLP}(\text{LN}(\mathbf{x}_e)) + \mathbf{x}_e, \tag{2}$$

where LN denotes the layer normalization operation.

Knowledge Distillation. KD is a widely used model compression method, where we use predictions of a large pre-trained teacher model as the learning target of a tiny student model. Given a sample $\mathbf{x}$ corresponding to a label y, representing the prediction of the student and the teacher as $f_s(\mathbf{x})$ and $f_t(\mathbf{x})$, respectively, the loss function of KD can be formulated as:

$$\mathcal{L}_{kd} = (1 - \lambda)\mathcal{H}_{CE}(f_s(\mathbf{x}), y) + \lambda \tau^2 \mathcal{H}_{KL}(f_s(\mathbf{x})/\tau, f_t(\mathbf{x})/\tau), \tag{3}$$

where $\mathcal{H}_{CE}$ is the cross-entropy function, $\mathcal{H}_{KL}$ is the Kullback-Leibler divergence function, τ is a label smoothing hyperparameter termed temperature, and λ is a balancing hyperparameter.

Sometimes the intermediate features of the teacher can also be used for knowledge transfer. For example, Romero *et al.* [30] trained the student to output features similar to the teacher at intermediate layers. However, such methods require the teacher and the student to have the same embedding dimension. Otherwise, additional mapping layers are required for aligning, making the distillation process non-transparent. Manifold learning-based KD methods [18, 17] support mismatched embedding dimensions. They train the student to learn sample relationships predicted by the teacher but ignore patch-level information in vision transformers.

(a) Overview   (b) MD loss illustration

Figure 2: The fine-grained manifold distillation method. (a) An overview of the method. When transferring knowledge from the teacher to the student, a manifold distillation loss is adopted together with the orignal KD loss. (b) Computing of the manifold distillation loss. The loss is computed by matching feature relationships between each pair of selected teacher-student layers in manifold space.

3.2 Fine-grained manifold distillation

To utilize the patch-level information, we propose a fine-grained manifold distillation method. Unlike existing KD methods [14] for vision transformer only distilling with logits, our method distills patch-level manifolds at intermediate layers. Figure 2 provides an overview of the proposed method.

In the fine-grained manifold distillation method, we regard a vision transformer as a feature projector that embeds image patches into a series of smooth manifold space layer by layer. At each pair of manually selected teacher-student layers, we aim to teach the student layer to output features having the same patch-level manifold structure as the teacher layer. In particular, given samples of batch size B, we denote the feature of the student layer and the teacher layer as $F_T \in \mathbb{R}^{B \times N \times D_T}$ and $F_S \in \mathbb{R}^{B \times N \times D_S}$, respectively, where D_T and D_S are embedding dimensions. We first normalize the feature at the last dimension and then compute the manifold structure, or manifold relation map, as follows:

$$\mathcal{M}(\psi(F_S)) = \psi(F_S)\psi(F_S)^T, \tag{4}$$

where $\psi : \mathbb{R}^{D_1 \times D_2 \times D_3} \to \mathbb{R}^{D_1 D_2 \times D_3}$ is a tensor reshape operation. The manifold relation map of F_T can be obtained in a similar way. After that, we train the student to minimize the gap between $\mathcal{M}(\psi(F_T))$ and $\mathcal{M}(\psi(F_S))$ with the following loss:

$$\mathcal{L}_{mf} = \|\mathcal{M}(\psi(F_S)) - \mathcal{M}(\psi(F_T))\|_F^2. \tag{5}$$

However, the computation of manifold relation maps is resource-consuming. Its computational complexity is $\mathcal{O}(B^2 N^2 D)$ and a memory space of $B^2 N^2$ size is required to save the result. Taking the settings $B = 128$, $N = 196$ and $D = 192$ in the DeiT-Tiny model [14] as an example, it requires more than 240GFLOPs to compute and 2.5GB of memory space to save a single manifold relation map. The remarkable resource consumption limits the fine-grained manifold distillation method scaling up to multiple layers. Hence we must simplify the computation.

Inspired by the orthogonal decomposition of matrices, we decouple a manifold relation map into three parts: an intra-image relation map, an inter-image relation map, and a randomly sampled relation map. Figure 3 illustrates the decoupling. We compute the intra-image patch-level manifold distillation loss as follows:

$$\mathcal{L}_{intra} = \frac{1}{B} \sum_{i=0}^{B} \|\mathcal{M}(F_S[i,:,:]) - \mathcal{M}(F_T[i,:,:])\|_F^2. \tag{6}$$

	(a) Intra-image	(b) Inter-image	(c) Random

Figure 3: Illustration of the decoupled manifold relation map (4 images with 4 patches in each image): (a) intra-image relation map; (b) inter-image relation map; and (c) random sampled relation map. Manifold relation maps are computed across each group of patches filled with the same color.

Similarly, the inter-image patch-level manifold distillation loss is computed by:

$$\mathcal{L}_{inter} = \frac{1}{N} \sum_{j=0}^{N} ||\mathcal{M}(F_S[:, j, :]) - \mathcal{M}(F_T[:, j, :])||_F^2. \tag{7}$$

Moreover, to relieve the information loss caused by the decoupling, we relate the intra-image and the inter-image manifolds via a relation map computed across randomly sampled patches. Specifically, we sample K rows in the reshaped feature $\psi(F)$ to obtain $F^r \in \mathbb{R}^{K \times D_s}$, and compute the random sampled patch-level manifold distillation loss as follows:

$$\mathcal{L}_{random} = ||\mathcal{M}(F_S^r) - \mathcal{M}(F_T^r)||_F^2. \tag{8}$$

Hence, the overall loss function of our proposed method is:

$$\mathcal{L} = \mathcal{L}_{kd} + \sum_{l} \mathcal{L}_{mf-decouple}, \tag{9}$$

$$\mathcal{L}_{mf-decouple} = \alpha \mathcal{L}_{intra} + \beta \mathcal{L}_{inter} + \gamma \mathcal{L}_{random}, \tag{10}$$

where α, β, and γ are hyperparameters. The summation over l means that the manifold relation map matching is performed on multiple pairs of teacher-student layers. We will discuss the layer selecting scheme in Section 4.3.

Complexity analysis. The computational complexity of the decoupled manifold relation map is $\mathcal{O}(BN^2D + B^2ND + K^2D)$, and the memory space requirement is $BN^2 + NB^2 + K^2$. Still taking DeiT-Tiny as an example, the floating-point operations and memory space requirement reduce to 3GFLOPs and 32MB, respectively. The sampling number K is set to 192, the same as our experiments. With the decoupling scheme, fine-grained manifold distillation across multiple layers becomes feasible.

3.3 Optimization

Patch merging. Although the decoupling reduces the computation and memory space remarkably, the computing and storing overhead is still unaffordable when the patch size is too small. For instance, the patch size at the first stage of SwinTransformer [5] is 4, indicating that the total patch number N is 3136 under the input size of 224×224. Such a large patch number significantly increases the computational complexity and memory space requirement of the intra-image patch-level manifold loss $\mathcal{L}_{intra}$. To remedy this drawback, we merge adjacent patches and view them as a single patch to further simplify the computation. In particular, given a feature map $F \in \mathbb{R}^{N \times D}$, we first reshape it into $F \in \mathbb{R}^{H \times W \times D}$, where the height H and the width W are obtained following the original patch splitting operation. Then we adopt a merging setting (H', W') to merge every $(H/H') \times (W/W')$ adjacent patches in a non-overlapping manner. Zero-padding is adopted when H/H' or W/W' is not an integer. After merging, the feature map becomes $F \in \mathbb{R}^{H' \times W' \times (HWD/H'W')}$ and is finally reshaped into $F \in \mathbb{R}^{(H'W') \times (HWD/H'W')}$. By adjusting the merging setting (H', W'), we can easily strike the trade-off between the complexity and the granularity of manifold relation maps.

Table 1: Details of used teacher and student models. The input resolution is set to 224×224.

Model	Embedding	Heads	Layers	#params	FLOPs	Throughput(im/s)
RegNetY-16GF [32]	-	-	-	84M	15.9G	334.7
CaiT-S24 [23]	384	8	24	47M	9.4G	573.6
CaiT-XXS24 [23]	192	4	24	12M	2.5G	1012.8
DeiT-Small [14]	384	6	12	22M	4.6G	940.4
DeiT-Tiny [14]	192	3	12	5M	1.3G	2536.5
Swin-Small [5]	96	3	24	50M	8.7G	436.9
Swin-Tiny [5]	96	3	12	29M	4.5G	755.2

Soft distillation. Previous work [14] adds an additional distillation token into the student, and uses this token to learn hard labels provided by a CNN teacher. However, when teacher and student are both vision transformers, we propose that it is better to teach the student only with soft labels of the teacher. This design is based on the assumption that and a larger model can learn more knowledge than a smaller one, and models of the same family share the same knowledge pattern, *i.e.*, a student can learn most knowledge of a teacher. In our work, unless the student is larger than the teacher, we set the hyperparameter λ in Equation 3 to 1.

Fixed depth. Stochastic depth [31] is a regularization method that has becomes an infrastructure in training vision transformers [14, 5]. We propose that the student should not adopt this regularization when the teacher is trained with stochastic depth, since the soft labels already contain knowledge about this regularization. Otherwise, the repeated regularizations may harm the student performance. Hence, we adopt a fix-depth student in our method, *i.e.*, the stochastic depth regularization is not used for training the student.

4   Experiments

We evaluate the proposed fine-grained manifold distillation method on ImageNet-1k [33] image classification task, CIFAR-10/100 [34] transfer learning task, and COCO [35] object detection task. In the following, we first report the experiment setup and then results of these tasks.

4.1   Setup

Datasets. We evaluate the proposed method mainly on the ImageNet-1k image classification task. ImageNet-1k is a subset of the ImageNet dataset [33], which consists of more than 1.2M training images and 50K validation images from 1000 classes. To test the generalization performance of student models trained with the proposed method, we conduct transfer learning experiments on CIFAR-10 and CIFAR-100 datasets [34]. The two datasets both contain 50K training images and 10K testing images, which are categorized into 10 classes and 100 classes, respectively. Moreover, we conduct experiments on the object detection downstream task with COCO dataset [35]. We use the COCO 2017 split, which consists of 118K training images and 5K validation images containing objects from 80 categories.

Baselines & models. We compare the proposed method with DeiT [14], which adds an additional distillation token in the student model to learn hard labels from the teacher. SwinTransformer students containing no distillation token, so we compare with the original KD method [13] on these model. Table 1 summarizes the used models in our experiments.

4.2   Distillation results on ImageNet-1k

Implementation details. On the ImageNet-1k image classification task, we train DeiT students with CaiT teachers and SwinTransformer students with SwinTransformer teachers. We slightly modify the architecture of DeiT students by removing the distillation token and only using the class token. The hyperparameter λ in the KD loss is set to 1, *i.e.*, the real label is not used to train the student. When the teacher is smaller than the student, to prevent the performance degradation caused by the weak teacher, we set λ to 0.5. In the fine-grained manifold distillation loss, hyperparameters

Table 2: Distillation results on the ImageNet-1k classification task. In the first column, "Hard" refers to the hard-label distillation strategy [14], "KD" refers to the original KD method [13], and "Manifold" refers to the proposed method. The input resolution is 224×224.

Distillation method	Teacher	Top-1(%)	Student	Top-1(%)
-	-	-	DeiT-Tiny	72.2
Hard	RegNetY-16GF	82.9	DeiT-Tiny	74.5
Hard	CaiT-XXS24	78.5	DeiT-Tiny	73.9
Hard	CaiT-S24	83.4	DeiT-Tiny	74.5
Manifold	CaiT-XXS24	78.5	DeiT-Tiny	**75.5**
Manifold	CaiT-S24	83.4	DeiT-Tiny	**76.5**
-	-	-	DeiT-Small	79.9
Hard	RegNetY-16GF	82.9	DeiT-Small	81.2
Hard	CaiT-XXS24	78.5	DeiT-Small	80.1
Hard	CaiT-S24	83.4	DeiT-Small	81.3
Manifold	CaiT-XXS24	78.5	DeiT-Small	**81.3**
Manifold	CaiT-S24	83.4	DeiT-Small	**82.2**
-	-	-	Swin-Tiny	81.2
KD	Swin-Small	83.2	Swin-Tiny	81.7
Manifold	Swin-Small	83.2	Swin-Tiny	**82.2**

Table 3: Ablation study results of main components. The "✓" mark indicating that we adopt the corresponding training scheme. The opposite of soft distillation is the hard-label distillation scheme in DeiT. We adopt a CaiT-S24 teacher and a DeiT-Tiny student.

Manifold Distillation	Soft distillation	Fixed Depth	Top-1(%)
×	×	×	74.5
×	×	✓	75.5
×	✓	✓	75.8
✓	✓	✓	**76.5**

α, β, and γ are set to 4, 0.1, and 0.2, respectively. The sampling number K in loss term $\mathcal{L}_{random}$ is set to 192. We set the above hyperparameters *one by one* with the grad search method, indicating that their combination may not be optimal. We select the first 4 layers and the last 4 layers of the student and the teacher to conduct manifold distillation. Note that the class token in DeiT is ignored when computing manifold relation maps. Moreover, to train SwinTransformer students efficiently, we adopt a patch merging setting of $(14, 14)$. Other training settings follow those in DeiT [14] and SwinTransformer [5], except the stochastic depth regularization, which is not used in our experiments. Each student is trained for 300 epochs with 8 Tesla-V100 GPUs.

Results. Table 2 presents classification results on ImageNet-1k. Compared with DeiT, the proposed method achieves remarkably performance improvements, which are +2.0% on DeiT-Tiny and +0.9% on DeiT-Small with the CaiT-S24 teacher. When the teacher is the much weaker CaiT-XXS24, the improvement becomes +1.6% on DeiT-Tiny and +1.2% on DeiT-Small. Note that we report the RegNetY-16GF teacher results in DeiT for comparison, but do not conduct fine-grained manifold distillation experiments with this CNN model because the proposed method is designed for distillation between vision transformers.

Moreover, we conduct experiments on SwinTransformer, one of the state-of-the-art vision transformer architecture. When the teacher is Swin-Small and the student is Swin-Tiny, the proposed method achieves +0.5% performance improvement compared with the original KD method.

4.3 Ablation & parameter comparison

Ablation of main components. We design experiments to verify the effectiveness of the proposed fine-grained manifold distillation method, the soft distillation scheme, and the fixed student depth.

Table 4: Distillation results with different layer selecting schemes. We use a CaiT-S24 teacher and a DeiT-Tiny student to perform fine-grained manifold distillation. A total of 6 layers are selected from the "Shallow", "Medium", or "Deep" part of a model. "Uniform" refers to selecting layers across the whole model uniformly. Note that the number of select layers is different from other experiments.

Scheme	Teacher layers	Student layers	Top-1(%)
Shallow	$\{1, 2, 3, 4, 5, 6\}$	$\{1, 2, 3, 4, 5, 6\}$	75.8
Deep	$\{19, 20, 21, 22, 23, 24\}$	$\{7, 8, 9, 10, 11, 12\}$	75.5
Shallow/Deep	$\{1, 2, 3, 22, 23, 24\}$	$\{1, 2, 3, 10, 11, 12\}$	**76.3**
Shallow/Medium/Deep	$\{1, 2, 12, 13, 23, 24\}$	$\{1, 2, 6, 7, 11, 12\}$	76.2
Uniform	$\{4, 8, 12, 16, 20, 24\}$	$\{2, 4, 6, 8, 10, 12\}$	76.2

Table 5: Ablation study results of decoupled manifold loss terms. The teacher is CaiT-S24 and the student is DeiT-Tiny.

Loss term			Top-1(%)
$\mathcal{L}_{intra}$	$\mathcal{L}_{inter}$	$\mathcal{L}_{random}$	
×	×	×	75.8
✓	×	×	76.0
×	✓	×	69.6*
×	×	✓	76.2
×	✓	✓	76.1
✓	×	✓	76.4
✓	✓	×	76.0
✓	✓	✓	**76.5**

*The train fails because of a nan loss value.

Table 6: Comparison of different hyperparameter settings. The teacher is CaiT-S24 and the student is DeiT-Tiny.

Hyperparameter				Top-1(%)
α	β	γ	K	
2.0	0.1	0.2	192	76.1
8.0	0.1	0.2	192	76.1
4.0	**0.05**	0.2	192	76.2
4.0	**0.2**	0.2	192	76.2
4.0	0.1	**0.1**	192	76.2
4.0	0.1	**0.4**	192	76.2
4.0	0.1	0.2	**96**	76.0
4.0	0.1	0.2	**384**	76.3
4.0	**0.1**	**0.2**	**192**	**76.5**

Table 3 presents the results. The results demonstrates that for distillation between vision transformers, soft distillation and fixed depth are both significant. Moreover, combined with the fine-grained manifold distillation method, student performance can be further improved.

Ablation of decoupled manifold loss terms. The decoupled fine-grained manifold distillation loss consists of three terms. We study their effectiveness and report the result in Table 6. The results show that each component in the decoupled fine-grained manifold distillation loss contributes to improving the final performance.

Layers for fine-grained manifold distillation. To study the impact of different layer selections in manifold relation map matching, we evaluate 5 layer selecting schemes and compare their performance. In particular, we take CaiT-S24 as the teacher model and DeiT-Tiny as the student model. The number of selected layers is set to 6. From the results reported in Table 4, conducting fine-grained manifold distillation at the head and the tail of student models are both crucial. Hence, we speculate that the "Shallow/Deep" layer selecting scheme is the best because of its outstanding performance and ease of use.

Parameters in decoupled manifold distillation loss. There are 4 hyperparameters in decoupled manifold distillation loss: the weight of inter-image loss α, the weight of intra-image loss β, the weight of randomly sampled loss γ, and the sampling number K. We compare different settings of these parameters and report the results in Table 5. Our default setting outperforms those either increasing or reducing one of the parameters. However, due to our coarse parameter searching scheme, we believe that the performance can be further improved by setting these hyperparameters more carefully.

Table 7: Transfer learning results on CIFAR-10/100. Each student is pre-trained on ImageNet-1k and fine-tuned for 1000 epochs.

Dataset	Teacher	Student	Distillation method	Top-1(%)
CIFAR-10	-	DeiT-Tiny	-	98.19
	CaiT-S24	DeiT-Tiny	Hard	98.23
	CaiT-S24	DeiT-Tiny	Manifold	**98.48**
CIFAR-100	-	DeiT-Tiny	-	86.61
	CaiT-S24	DeiT-Tiny	Hard	87.34
	CaiT-S24	DeiT-Tiny	Manifold	**88.05**

Table 8: Object detection results on COCO 2017. Backbones are pre-trained on ImageNet-1k. The teacher is trained for 36 epochs and each student is trained for 12 epochs.

Model	#params	FLOPs	AP^{box}	AP^{box}_{50}	AP^{box}_{75}
(Teacher) Swin-Small+Mask R-CNN	69M	365G	48.5	70.2	53.5
(Student) Swin-Tiny+Mask R-CNN	48M	272G	43.7	66.6	47.7
(Manifold distilled) Swin-Tiny+Mask R-CNN	48M	272G	**44.7**	**67.1**	**48.6**

4.4 Transfer learning

To measure the generalization ability of the proposed method, we conduct transfer learning experiments. We fine-tune a DeiT-Tiny student trained with a CaiT-S24 teacher on CIFAR-10 and CIFAR-100 datasets for 1000 epochs. We adopt a batch size of 768 and an AdamW optimizer with a learning rate of 5×10^{-6}. Other settings follow DeiT [14].

Table 7 reports the transfer learning results. Students trained with the fine-grained manifold distillation method generalize better than others (+0.25% on CIFAR-10 and +0.71% on CIFAR-100), demonstrating a favorable generalization ability of the proposed method.

4.5 Downstream task

To further evaluate the effectiveness of our proposed method, we adopt the fine-grained manifold distillation to train object detection models on COCO 2017 dataset.

Implementation details. We adopt Mask R-CNN as the detection framework. The teacher backbone is Swin-Small and the student backbone is Swin-Tiny. All used backbones are pretrined on ImageNet-1k The teacher is trained for 36 epochs and each student is trained for 12 epochs. When training students with fine-grained manifold distillation, we adopt the distillation loss on outputs of the last two backbone stages and outputs of the feature pyramid network neck [36].

Results. Table 8 presents the detection results. Our manifold distilled student outperforms the student trained without distillation (+1.0% box AP), demonstrating that the proposed method benefits the object detection downstream task.

5 Conclusion

In this paper, we propose a fine-grained manifold distillation method for vision transformers. We match patch-level intermediate features of the student and the teacher in a manifold space, and decouple the matching loss into three terms to reduce the computational complexity. Moreover, we adopt a patch merging scheme to further simplify the computation. Different from previous works, we distill the student with soft labels and fixed depth. We conduct experiments on ImageNet-1k image classification, CIFAR-10/100 transfer learning, and COCO object detection, and the proposed method outperforms existing methods. We also conduct substantial ablation experiments to demonstrate the superiority of the fine-grained manifold distillation method. The large search space of hyperparameters is one of the most serious drawbacks of the proposed method. In the future, we will study to further simplify the proposed method and help it be parameter insensitive.

References

[1] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In *North American Chapter of the Association for Computational Linguistics*, 2019.

[2] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, et al. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, 2020.

[3] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, et al. Attention is all you need. In *Advances in Neural Information Processing Systems*, 2017.

[4] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021.

[5] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, et al. Swin transformer: Hierarchical vision transformer using shifted windows. In *International Conference on Computer Vision*, 2021.

[6] Li Yuan, Yunpeng Chen, Tao Wang, Weihao Yu, Yujun Shi, Francis EH Tay, Jiashi Feng, and Shuicheng Yan. Tokens-to-token vit: Training vision transformers from scratch on imagenet. *arXiv preprint arXiv:2101.11986*, 2021.

[7] Xiangxiang Chu, Zhi Tian, Yuqing Wang, Bo Zhang, Haibing Ren, Xiaolin Wei, Huaxia Xia, and Chunhua Shen. Twins: Revisiting spatial attention design in vision transformers. *arXiv preprint arXiv:2104.13840*, 2021.

[8] Kai Han, An Xiao, Enhua Wu, Jianyuan Guo, Chunjing Xu, and Yunhe Wang. Transformer in transformer. In *Advances in Neural Information Processing Systems*, 2021.

[9] Mingxing Tan and Quoc V. Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning*, 2019.

[10] Mingjian Zhu, Kai Han, Yehui Tang, and Yunhe Wang. Visual transformer pruning. *arXiv preprint arXiv:2104.08500*, 2021.

[11] Yehui Tang, Kai Han, Yunhe Wang, Chang Xu, Jianyuan Guo, Chao Xu, et al. Patch slimming for efficient vision transformers. *arXiv preprint arXiv:2106.02852*, 2021.

[12] Benoit Jacob, Skirmantas Kligys, Bo Chen, Menglong Zhu, Matthew Tang, Andrew Howard, Hartwig Adam, and Dmitry Kalenichenko. Quantization and training of neural networks for efficient integer-arithmetic-only inference. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2018.

[13] Geoffrey E. Hinton, Oriol Vinyals, and Jeffrey Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

[14] Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, 2021.

[15] Siqi Sun, Yu Cheng, Zhe Gan, and Jingjing Liu. Patient knowledge distillation for BERT model compression. In *Conference on Empirical Methods in Natural Language Processing*, 2019.

[16] Xiaoqi Jiao, Yichun Yin, Lifeng Shang, Xin Jiang, Xiao Chen, Linlin Li, et al. Tinybert: Distilling BERT for natural language understanding. In *Conference on Empirical Methods in Natural Language Processing*, 2020.

[17] Hanting Chen, Yunhe Wang, Chang Xu, Chao Xu, and Dacheng Tao. Learning student networks via feature embedding. *IEEE Trans. Neural Networks Learn. Syst.*, 32(1):25–35, 2021.

[18] Baoyun Peng, Xiao Jin, Dongsheng Li, Shunfeng Zhou, Yichao Wu, Jiaheng Liu, et al. Correlation congruence for knowledge distillation. In *International Conference on Computer Vision*, 2019.

[19] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, et al. Attention is all you need. In *Advances in Neural Information Processing Systems*, 2017.

[20] Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European Conference on Computer Vision*, 2020.

[21] Mark Chen, Alec Radford, Rewon Child, Jeffrey Wu, Heewoo Jun, David Luan, et al. Generative pretraining from pixels. In *International Conference on Machine Learning*, 2020.

[22] Daquan Zhou, Bingyi Kang, Xiaojie Jin, Linjie Yang, Xiaochen Lian, Qibin Hou, et al. Deepvit: Towards deeper vision transformer. *arXiv preprint arXiv:2103.11886*, 2021.

[23] Hugo Touvron, Matthieu Cord, Alexandre Sablayrolles, Gabriel Synnaeve, and Hervé Jégou. Going deeper with image transformers. In *International Conference on Computer Vision*, 2021.

[24] Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, et al. Pyramid vision transformer: A versatile backbone for dense prediction without convolutions. In *International Conference on Computer Vision*, 2021.

[25] Yunhe Wang, Chang Xu, Chao Xu, and Dacheng Tao. Adversarial learning of portable student networks. In *AAAI Conference on Artificial Intelligence*, 2018.

[26] Yixing Xu, Yunhe Wang, Hanting Chen, Kai Han, Chunjing Xu, Dacheng Tao, et al. Positive-unlabeled compression on the cloud. In *Advances in Neural Information Processing Systems*, 2019.

[27] Guorui Zhou, Ying Fan, Runpeng Cui, Weijie Bian, Xiaoqiang Zhu, and Kun Gai. Rocket launching: A universal and efficient framework for training well-performing light net. In *AAAI Conference on Artificial Intelligence*, 2018.

[28] Sam T Roweis and Lawrence K Saul. Nonlinear dimensionality reduction by locally linear embedding. *science*, 290(5500):2323–2326, 2000.

[29] Joshua B Tenenbaum, Vin de Silva, and John C Langford. A global geometric framework for nonlinear dimensionality reduction. *science*, 290(5500):2319–2323, 2000.

[30] Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. In *International Conference on Learning Representations*, 2015.

[31] Gao Huang, Yu Sun, Zhuang Liu, Daniel Sedra, and Kilian Q. Weinberger. Deep networks with stochastic depth. In *European Conference on Computer Vision*, 2016.

[32] Ilija Radosavovic, Raj Prateek Kosaraju, Ross B. Girshick, Kaiming He, and Piotr Dollár. Designing network design spaces. In *Computer Vision and Pattern Recognition*, 2020.

[33] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Computer Vision and Pattern Recognition*, 2009.

[34] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[35] Tsung-Yi Lin, Michael Maire, Serge J. Belongie, James Hays, Pietro Perona, Deva Ramanan, et al. Microsoft COCO: common objects in context. In *European Conference on Computer Vision*, Lecture Notes in Computer Science, 2014.

[36] Tsung-Yi Lin, Piotr Dollár, Ross B. Girshick, Kaiming He, Bharath Hariharan, and Serge J. Belongie. Feature pyramid networks for object detection. In *Computer Vision and Pattern Recognition*, 2017.