AutoSKDBERT: Learn to Stochastically Distill BERT

Abstract

In this paper, we propose AutoSKDBERT, a new knowledge distillation paradigm for BERT compression, that stochastically samples a teacher from a predefined teacher team following a categorical distribution in each step, to transfer knowledge into student. AutoSKDBERT aims to discover the optimal categorical distribution which plays an important role to achieve high performance. The optimization procedure of AutoSKDBERT can be divided into two phases: 1) phase-1 optimization distinguishes effective teachers from ineffective teachers, and 2) phase-2 optimization further optimizes the sampling weights of the effective teachers to obtain satisfactory categorical distribution. Moreover, after phase-1 optimization completion, AutoSKDBERT adopts teacher selection strategy to discard the ineffective teachers whose sampling weights are assigned to the effective teachers. Particularly, to alleviate the gap between categorical distribution optimization and evaluation, we also propose a stochastic single-weight optimization strategy which only updates the weight of the sampled teacher in each step. Extensive experiments on GLUE benchmark show that the proposed AutoSKDBERT achieves state-of-the-art score compared to previous compression approaches on several downstream tasks, including pushing MRPC F1 and accuracy to 93.2 (0.6 point absolute improvement) and 90.7 (1.2 point absolute improvement), RTE accuracy to 76.9 (2.9 point absolute improvement).

1 Introduction

BERT (Devlin et al., 2019) has brought about a sea change in the field of Natural Language Processing (NLP). Following BERT, numerous subsequent works focus on various perspectives to further improve its performance, e.g., hyper-parameter (Liu et al., 2019b), pre-training corpus (Liu et al., 2019b; Raffel et al., 2020), learnable embedding paradigm (Raffel et al., 2020), pre-training task (Clark et al., 2020), architecture (Gao et al., 2022) and self-attention (Shi et al., 2021), etc. However, there are massive redundancies in the above BERT-style models w.r.t. attention heads (Michel et al., 2019; Dong et al., 2021), weights (Gordon et al., 2020), and layers (Fan et al., 2020). Consequently, many compact BERT-style language models are proposed via pruning (Fan et al., 2020; Guo et al., 2019), quantization (Shen et al., 2020), parameter sharing (Lan et al., 2020) and Knowledge Distillation (KD) (Iandola et al., 2020; Pan et al., 2021). In this paper, we focus on the KD-based compression approaches.

From the point of view of learning procedure, KD is used in the pre-training (Turc et al., 2019; Sanh et al., 2019; Sun et al., 2020; Jiao et al., 2020) and fine-tuning phases (Sun et al., 2019; Jiao et al., 2020; Wu et al., 2021). On the other hand, from the point of view of distillation objective, KD is employed for the outputs of hidden layer (Sun et al., 2020), final layer (Wu et al., 2021), embedding (Sanh et al., 2019) and self-attention (Wang et al., 2020). Wu et al. (2021) employ multiple teachers to achieve better performance than single-teacher KD based approaches on several downstream tasks of GLUE benchmark (Wang et al., 2019). As shown in Table 1, nevertheless, the ensemble of multiple teachers are not always more effective than the single teacher for student distillation. There are two possible reasons: 1) *diversity losing* (Tran et al., 2020) and 2) *capability gap* (Mirzadeh et al., 2020). On the one hand, the ensemble prediction of multi-teacher KD loses the diversity of each teacher. On the other hand, between the large-capability teacher and small-capability student, there is a capability gap which can be prone to unsatisfactory distillation performance.

Table 1: Performances of knowledge distillation using single and multiple teachers for a 6-layer BERT-style language model on the development set of GLUE benchmark. In this experiment, we employ five teachers, i.e. T_{10} to T_{14} shown in Appendix A.1, for single-teacher distillation and multi-teacher distillation. We introduce the implementation details in Appendix B.

Task	MRPC	RTE	CoLA	SST-2	QQP	QNLI	MNLI
Metrics	$\frac{F1+acc}{2}$	acc	Mcc	acc	$\frac{F1+acc}{2}$	acc	m
Best Single Teacher	T_{13}	T_{10}	T_{10}	T_{12}	T_{11}	T_{12}	T_{14}†
Single-teacher KD	**90.0**	73.3	49.3	**93.1**	**89.0**	**91.4**	83.5
Multi-teacher KD	89.7	**73.7**	**50.1**	92.2	88.6	91.1	**83.6**
Gain	-0.3	+0.4	+0.8	-0.9	-0.4	-0.3	+0.1

† Pre-training with whole word masking.

To solve the above mentioned issues, we propose AutoSKDBERT which stochastically samples a teacher from a predefined teacher team following a categorical distribution in each step, to transfer knowledge into student. The task of AutoSKDBERT is learning the optimal categorical distribution to achieve high performance. 1) Given a teacher team which consists of multiple teachers with multi-level capacities, AutoSKDBERT optimizes an initialized categorical distribution to distinguish effective teachers from ineffective teachers in phase-1 optimization. 2) The sampling weights of the ineffective teachers are assigned to the effective teachers via teacher selection strategy after phase-1 optimization completion. 3) AutoSKDBERT further optimizes the weights of the effective teachers rather than the ineffective teachers' in phase-2 optimization. We implement extensive experiments on GLUE benchmark (Wang et al., 2019) to verify the effectiveness of the proposed AutoSKDBERT.

Our contributions are summarized as follows:

- We propose AutoSKDBERT which stochastically samples a teacher from the predefined teacher team following the categorical distribution in each step, to transfer knowledge into the student of BERT-style language model.

- We propose a two-phase optimization framework with teacher selection strategy to select effective teachers and learn the optimal categorical distribution in a differentiable way.

- We propose Stochastic Single-Weight Optimization (SSWO) strategy to alleviate the consistency gap between the categorical distribution optimization and evaluation for performance improvement.

- Extensive experiments on the GLUE benchmark show that AutoSKDBERT achieves state-of-the-art performance compared to popular BERT compression approaches. The code will will be made publicly available upon publication of the paper.

2 THE PROPOSED AUTOSKDBERT

2.1 OVERVIEW

In each step, AutoSKDBERT samples a teacher $\hat{T}$ from a teacher team which consists of n multi-level BERT-style teachers $T_{1:n}$, to transfer knowledge into student S. The objective function of AutoSKDBERT can be expressed as

$$\mathcal{L}(w) = \sum_{x \in \mathcal{X}} \mathcal{L}_d(f_{\hat{T} \in T_{1:n}}(x), f_S(x; w)), \quad (1)$$

where $\mathcal{L}_d$ represents distilled loss function to compute the difference between the student S with learnable parameter w and the sampled teacher $\hat{T}$, $\mathcal{X}$ denotes the training data, $f_{\hat{T} \in T_{1:n}}(\cdot)$ and $f_S(\cdot)$ denote the logits from $\hat{T}$ and S, respectively.

In AutoSKDBERT, a categorical distribution $\text{Cat}(\theta)$ where $\theta = \{\theta_{1:n}\}$ and $\sum_{i=1}^{n} \theta_i = 1$, is employed to sample the teacher from the teacher team. Particularly, the probability $p(T_i)$ of T_i being sampled is θ_i. We observe that $\text{Cat}(\theta)$ plays an important role for obtaining high performance of AutoSKDBERT. As a result, the task of AutoSKDBERT then turns into learning the optimal categorical distribution $\text{Cat}(\theta^*)$, as illustrated in Figure 1.

Figure 1: Two-phase optimization framework with teacher selection strategy for AutoSKDBERT. 1) For a pre-defined teacher team, AutoSKDBERT optimizes an initialized categorical distribution to distinguish effective teachers from ineffective teachers. 2) After phase-1 optimization completion, the sampling weights of the ineffective teachers are assigned to the effective teachers via teacher selection strategy. 3) AutoSKDBERT further optimizes the weights of the effective teachers rather than the ineffective teachers in phase-2 optimization. Best viewed in color.

2.2 PROBLEM FORMULATION

AutoSKDBERT has two groups of learnable parameter: 1) w of student and 2) θ of categorical distribution. We split original training data into training and validation subsets, and denote $\mathcal{L}_{train}$ and $\mathcal{L}_{val}$ as the losses on training and validation subsets, respectively. Both $\mathcal{L}_{train}$ and $\mathcal{L}_{val}$ are determined not only by $\mathrm{Cat}(\theta)$, but also by w. Particularly, AutoSKDBERT aims to learn the best categorical distribution $\mathrm{Cat}(\theta^*)$ that minimizes the validation loss $\mathcal{L}_{val}(w^*, \mathrm{Cat}(\theta))$, where the weights w^* associated with the categorical distribution $\mathrm{Cat}(\theta)$ are obtained by $\mathrm{argmin}_w \ \mathcal{L}_{train}(w, \mathrm{Cat}(\theta))$. Consequently, AutoSKDBERT can be considered as a bilevel optimization problem (Colson et al., 2007) with upper-level variable $\mathrm{Cat}(\theta)$ and lower-level variable w:

$$\min_{\mathrm{Cat}(\theta)} \quad \mathcal{L}_{val}(w^*(\mathrm{Cat}(\theta)), \mathrm{Cat}(\theta)),$$
$$\text{s.t.} \quad w^*(\mathrm{Cat}(\theta)) = \underset{w}{\mathrm{argmin}} \ \mathcal{L}_{train}(w, \mathrm{Cat}(\theta)). \tag{2}$$

We optimize w of student (see Section 2.3) and θ of categorical distribution (see Section 2.4) in an alternate and iterative way, and show the optimization algorithm in Algorithm 1.

2.3 STUDENT DISTILLATION

For student distillation, $\mathrm{Cat}(\theta)$ is frozen. Similar to Eq. 1, we utilize the following object function:

$$\mathcal{L}(w) = \sum_{x \in \mathcal{X}} \mathcal{L}_d(\hat{\theta} f_{\hat{\mathrm{T}} \in \mathrm{T}_{1:n}}(x), f_{\mathrm{S}}(x; w)), \tag{3}$$

where $\hat{\theta}$ indicates the probability of the teacher $\hat{\mathrm{T}}$ being sampled from $\mathrm{T}_{1:n}$ according to $\mathrm{Cat}(\theta)$.

Algorithm 1: Two-phase Optimization for AutoSKDBERT

Initialize categorical distribution $\mathrm{Cat}(\theta^{(1)})$ for phase-1 optimization, weights w of student, maximum step N, current step $n = 0$;

while $n < \frac{N}{2}$ **do**

    Update $\mathrm{Cat}(\theta^{(1)})$ by descending Eq. 7 ;   `// phase-1 categorical`
    `distribution optimization`

    Update w by descending Eq. 3 ;   `// phase-1 student distillation`

    $n = n + 1$;

end

Select effective teachers to generate $\mathrm{Cat}(\theta^{(2)})$ by Eq. 8;   `// teacher selection`

while $\frac{N}{2} \leq n < N$ **do**

    Update $\mathrm{Cat}(\theta^{(2)})$ by descending Eq. 7 ;   `// phase-2 categorical`
    `distribution optimization`

    Update w by descending Eq. 3 ;   `// phase-2 student distillation`

    $n = n + 1$;

end

2.4 CATEGORICAL DISTRIBUTION OPTIMIZATION

For categorical distribution optimization, w is frozen. We propose a two-phase optimization framework with teacher selection strategy to learn appropriate categorical distribution:

1. **Phase-1 Optimization** distinguishes effective teachers from ineffective teachers in the teacher team according to $\mathrm{Cat}(\theta)$;

2. **Teacher Selection** discards the ineffective teachers whose weights are assigned to the effective teachers;

3. **Phase-2 Optimization** further optimizes the weights of the effective teachers rather than the ineffective teachers;

where a Stochastic Single-Weight Optimization (SSWO) strategy is proposed for categorical distribution optimization. Below, categorical distribution optimization and teacher selection strategy are introduced in detail.

2.4.1 CATEGORICAL DISTRIBUTION OPTIMIZATION VIA STOCHASTIC SINGLE-WEIGHT OPTIMIZATION

To optimize $\mathrm{Cat}(\theta)$ in a differentiable way, Continuous Relaxation (CR) (Liu et al., 2019a) is a common technique to obtain mixture of logits w.r.t. teachers as

$$\overline{f}_{\mathrm{T}_{1:n}}(x; \mathrm{Cat}(\theta)) = \sum_{i=1}^{n} \theta_i f_{\mathrm{T}_i}(x). \tag{4}$$

Subsequently, $\mathrm{Cat}(\theta)$ can be optimized by an approximation scheme:

$$\nabla_{\mathrm{Cat}(\theta)} \mathcal{L}_{val}(w^*(\mathrm{Cat}(\theta)), \mathrm{Cat}(\theta)) \approx \nabla_{\mathrm{Cat}(\theta)} \mathcal{L}_{val}(w - \alpha \nabla_w \mathcal{L}_{train}(w, \mathrm{Cat}(\theta)), \mathrm{Cat}(\theta)), \tag{5}$$

where w and α indicate the current weights of the student and the learning rate of categorical distribution, respectively. In particular, we employ w with a single-step adapting (i.e., $w - \alpha \nabla_w \mathcal{L}_{train}(w, \mathrm{Cat}(\theta))$ to appropriate $w^*(\mathrm{Cat}(\theta))$ for avoiding the inner optimization in Eq. 2. This appropriation scheme has been widely used in meta-learning (Finn et al., 2017) and neural architecture search (Liu et al., 2019a).

However, in the case of CR, there is a consistency gap between the categorical distribution optimization and evaluation in terms of the teacher's logits. For categorical distribution optimization, $\overline{f}_{\mathrm{T}_{1:n}}(x; \mathrm{Cat}(\theta))$ is used to compute the difference between the student's logits as $\sum_{x \in \mathcal{X}} \mathcal{L}_d(\overline{f}_{\mathrm{T}_{1:n}}(x; \mathrm{Cat}(\theta)), f_{\mathrm{S}}(x; w))$. For categorical distribution evaluation, however, only the

logits of the sampled teacher $f_{\hat{T} \in T_{1:n}}(x)$ is used to obtain the difference to the student's logits as $\sum_{x \in \mathcal{X}} \mathcal{L}_d(f_{\hat{T} \in T_{1:n}}(x), f_S(x; w))$.

To alleviate the above consistency gap, we propose SSWO whose objective function can be written as

$$\mathcal{L}(w; \hat{\theta}) = \sum_{x \in \mathcal{X}} \mathcal{L}_d(\hat{\theta} f_{\hat{T} \in T_{1:n}}(x), f_S(x; w)), \tag{6}$$

where $\hat{\theta}$ plays also a role like label smoothing (Szegedy et al., 2016) which aims to reduce the confidence coefficient of the sampled teacher and avoid over fitting (Müller et al., 2019) of the categorical distribution. Moreover, the smaller the sampling weight, the more reduction the confidence coefficient of the sampled teacher. Subsequently, the sampled single-weight $\hat{\theta}$ can be optimized by

$$\nabla_{\hat{\theta} \sim \text{Cat}(\theta)} \mathcal{L}_{val}(w^*(\hat{\theta}), \hat{\theta}) \approx \nabla_{\hat{\theta} \sim \text{Cat}(\theta)} \mathcal{L}_{val}(w - \alpha \nabla_w \mathcal{L}_{train}(w, \hat{\theta}), \hat{\theta}). \tag{7}$$

In practice, the proposed SSWO achieves better performance than CR, as shown in Section 4.2.

2.4.2 TEACHER SELECTION

After phase-1 optimization completion, m ineffective teachers are separated from the teacher team according to the current categorical distribution $\text{Cat}(\theta^{(1)})$, where the smaller the weight, the more ineffective the teacher. For avoiding categorical distribution optimizing from scratch in phase-2 optimization, we present teacher selection strategy which assigns the weights of m ineffective teachers to $n-m$ effective teachers, to deliver the categorical distribution $\text{Cat}(\theta^{(2)})$ for phase-2 optimization by

$$\text{Cat}(\theta^{(2)}) = \frac{\text{Cat}(\theta^{(1)}) mask(m\_smallest(\text{Cat}(\theta^{(1)}), m))}{\max(\|\text{Cat}(\theta^{(1)}) mask(m\_smallest(\text{Cat}(\theta^{(1)}), m))\|_p, \epsilon)}, \tag{8}$$

where p (1 in this paper) denotes the exponent value in the norm formulation, ϵ is a small value (1e-12 in this paper) to avoid division by zero, $m\_smallest(\text{Cat}(\theta^{(1)}), m)$ obtains m indexes of ineffective teachers according to $\text{Cat}(\theta^{(1)})$, and $mask(\cdot)$ generates a mask where the values of m ineffective and $n - m$ effective teachers are set to 0 and 1, respectively.

3 EXPERIMENTS AND RESULTS

3.1 DATASETS AND SETTINGS

Datasets. We evaluate the proposed AutoSKDBERT on GLUE benchmark (Wang et al., 2019), including MRPC (Dolan & Brockett, 2005), RTE (Bentivogli et al., 2009), CoLA (Warstadt et al., 2019), SST-2 (Socher et al., 2013), QQP (Chen et al., 2018), QNLI (Rajpurkar et al., 2016) and MNLI (Williams et al., 2017). Moreover, STS-B (Cer et al., 2017) is not selected.

Settings. We employ the development set of GLUE benchmark dubbed as GLUE-dev, for categorical distribution evaluation of AutoSKDBERT. We employ a teacher team which consists of 14 BERT-style teachers, to distill a 6-layer BERT-style student dubbed AutoSKDBERT. The architecture information of the student and the teachers can be found in Appendix A.

3.2 TWO-PHASE OPTIMIZATION

We employ identical experimental settings for student distillation and categorical distribution optimization in both phase-1 and phase-2 optimization. The original training set is split fifty-fifty into two subsets, i.e., training subset for student distillation (see Section 2.3) and validation subset for categorical distribution optimization (see Section 2.4).

3.2.1 STUDENT DISTILLATION

We choose Adam with a weight decay of 1e-4 as the optimizer for student distillation. For various downstream tasks, we employ different batch size, learning rate and epoch number as shown in Table 2. Other hyper-parameters can be found in Appendix A.2.

Table 2: The hyper-parameters for student distillation.

Hyper-parameter	MRPC	RTE	CoLA	SST-2	QQP	QNLI	MNLI
Batch Size	32	32	16	64	32	32	32
Learning Rate	1e-5	1e-5	1e-5	1e-5	3e-5	2e-5	2e-5
Epoch Number	50	50	50	10	2	10	2

3.2.2 CATEGORICAL DISTRIBUTION OPTIMIZATION

For categorical distribution optimization, we employ other Adam with a weight decay of 1e-3 as the optimizer. There are two important hyper-parameters: 1) the number of the ineffective teacher and 2) learning rate for categorical distribution optimization. Similarly, for different downstream tasks, the above two parameters are various as shown in Table 3. Other hyper-parameters are identical to student distillation, e.g., batch size, epoch number, etc.

Table 3: The hyper-parameters for categorical distribution optimization.

Hyper-parameter	MRPC	RTE	CoLA	SST-2	QQP	QNLI	MNLI
Ineffective Teacher Number	1	9	4	10	8	1	9
Learning Rate	9e-4	1e-3	7e-4	9e-4	1e-3	6e-4	4e-4

3.3 CATEGORICAL DISTRIBUTION EVALUATION

3.3.1 IMPLEMENTATION DETAILS

AutoSKDBERT delivers 25 categorical distribution candidates in phase-2 optimization, and trains them from scratch to choose the best-performing one as the optimal categorical distribution. In addition to epoch number, other hyper-parameters (e.g., batch size, learning rate, etc.) are identical to student distillation on various downstream tasks as shown in Table 2. The epoch number is set to 15 on MRPC, RTE, CoLA tasks, and 5 on SST-2, QQP, QNLI and MNLI tasks.

3.3.2 LEARNED CATEGORICAL DISTRIBUTION

We show the categorical distributions learned by AutoSKDBERT on GLUE benchmark in Figure 2. It is obvious that each teacher shows various importances on different downstream tasks. 1) The strongest teacher T_{14} plays a dominant role on CoLA, SST-2 and QNLI tasks. 2) Low-capacity teachers, e.g., T_{02} to T_{06}, can also provide useful knowledge for student distillation on MRPC, CoLA and QNLI tasks. 3) The capacity of the effective teacher is not always larger than the discard teachers on RTE, SST-2 and QQP tasks.

Figure 2: Categorical distributions learned on GLUE benchmark.

3.4 RESULTS AND ANALYSIS ON GLUE BENCHMARK

In this paper, we choose vanilla KD (Hinton et al., 2015), Poor Man's BERT (Sajjad et al., 2020), DistilBERT (Sanh et al., 2019), LayerDrop (Fan et al., 2020), BERT-PKD (Sun et al., 2019), BERT-

Table 4: Results of AutoSKDBERT and other popular approaches on GLUE-dev. All comparative approaches have identical architecture, i.e., 6-layer BERT-style language model with 67 million parameters. † and ‡ indicate that the results are cited from Xu et al. (2020) and Zuo et al. (2022), respectively. ∗ means that the comparison between TinyBERT$_6$ and AutoSKDBERT may not be fair since the former employs extra learning procedure (e.g., GloVe word embedding (Pennington et al., 2014) based data augmentation) and distillation objective (e.g., transformer-layer distillation and embedding-layer distillation). § indicates that the result is obtained by our settings with the distillation loss described in Wu et al. (2021), and the experimental details can be found in Appendix B.

Model	MRPC F1/acc	RTE acc	CoLA Mcc	SST-2 acc	QQP F1/acc	QNLI acc	MNLI m
Vanilla KD (Hinton et al., 2015)†	86.2/-	64.9	45.1	90.5	-/88.1	88.0	80.1
Poor Man's BERT$_6$ (Sajjad et al., 2020)	-/80.2	65.0	-	90.3	-/90.4	87.6	81.1
DistilBERT$_6$ (Sanh et al., 2019)	87.5/-	59.9	51.3	92.7	-/88.5	89.2	82.2
LayerDrop (Fan et al., 2020)†	85.9/-	65.2	45.4	90.7	-/88.3	88.4	80.7
BERT-PKD (Sun et al., 2019)†	85.7/-	66.5	45.5	91.3	-/88.4	88.4	81.3
BERT-of-Theseus (Xu et al., 2020)	89.0/-	68.2	51.1	91.5	-/89.6	89.5	82.3
MiniLMv1 (Wang et al., 2020)	88.4/-	71.5	49.2	92.0	-/91.0	91.0	84.0
MiniLMv2 (Wang et al., 2020)‡	88.9/-	72.1	52.5	92.4	-/91.1	90.8	84.2
TinyBERT$_6$ (Jiao et al., 2020)∗	90.6/89.3	73.4	54.0	**93.0**	88.0/91.1	91.1	**84.5**
TinyBERT$_6$ (w/o aug) (Jiao et al., 2020)‡	88.4/-	72.2	42.8	91.6	-/90.6	90.5	83.5
MT-BERT (Wu et al., 2021)§	90.8/87.0	72.2	49.1	92.2	87.1/90.4	91.4	83.8
MoEBERT (Zuo et al., 2022)	92.6/89.5	74.0	**55.4**	**93.0**	**88.4/91.4**	91.3	**84.5**
AutoSKDBERT (Ours)	**93.2/90.7**	**76.9**	51.8	**93.0**	88.0/91.0	**91.6**	84.3

of-Theseus (Xu et al., 2020), MiniLM (Wang et al., 2020), TinyBERT (Jiao et al., 2020), MT-BERT (Wu et al., 2021) and MoEBERT (Zuo et al., 2022) as the comparative approaches.

Table 4 summarizes the performance of AutoSKDBERT and the comparative approaches on GLUE-dev. The proposed AutoSKDBERT achieves state-of-the-art performance on four out of seven tasks. Particularly, AutoSKDBERT contributes to achieving better performance on those tasks with small data size, e.g., MRPC and RTE. On MRPC, AutoSKDBERT achieves 93.2 F1 score and 90.7 accuracy score which are 0.6 and 1.2 point higher than previous state-of-the-art MoEBERT (Zuo et al., 2022), respectively. On the other hand, compared to TinyBERT (Jiao et al., 2020) and MoEBERT (Zuo et al., 2022) on RTE task, AutoSKDBERT achieves 3.5 and 2.9 point absolute improvement, respectively. Except MiniLMv2 (Wang et al., 2020), TinyBERT and MoEBERT, our approach ranks the best compared to other comparative compression approaches on all downstream tasks.

4 ABLATION STUDIES

4.1 TWO-PHASE OPTIMIZATION: PHASE-1 VERSUS PHASE-2

Similar to phase-2 optimization, AutoSKDBERT delivers also 25 categorical distribution candidates in phase-1 optimization. Subsequently, each categorical distribution candidate is trained from scratch using identical settings described in Section 3.3, and the best-performing one on each task is shown in Table 5.

Table 5: The performance of AutoSKDBERT with the best categorical distribution learned in phase-1 and phase-2 optimization on GLUE-dev.

Task	MRPC	RTE	CoLA	SST-2	QQP	QNLI	MNLI
Metrics	F1/acc	acc	Mcc	acc	F1/acc	acc	m
Phase-1	92.9/90.2	73.7	49.2	92.9	87.6/90.7	91.3	83.0
Phase-2	**93.2/90.7**	**76.9**	**51.8**	**93.0**	**88.0/91.0**	**91.6**	**84.3**
Gain	+0.3/+0.5	+1.4	+2.7	+0.1	+0.4/+0.3	+0.3	+1.3

Phase-2 optimization achieves better performance than phase-1 optimization, e.g., the absolute improvement is more than 1.3 on RTE, CoLA and MNLI tasks, where those teachers weaker than the student are prone to providing useless knowledge even noise disturbance. However, low-capacity teachers contribute to improving the performance of AutoSKDBERT on MRPC, SST-2 and QNLI tasks.

4.2 CATEGORICAL DISTRIBUTION UPDATE STRATEGY: CR-BASED VERSUS SSWO-BASED

In Section 2.4.1, we propose SSWO which stochastically samples a single-weight to optimize the categorical distribution, to alleviate the consistency gap between the categorical distribution optimization and evaluation of CR in terms of teachers' logits. For AutoSKDBERT with CR, the used hyper-parameters of categorical distribution optimization and evaluation are identical to AutoSKD-BERT with SSWO, as described in Section 3.2 and Section 3.3.

The proposed SSWO achieves better performance than CR on all tasks as shown in Table 6. Particularly, the absolute improvement is more than 1.6 point on RTE and CoLA tasks. Compared to Table 5, AutoSKDBERT with CR achieves higher performance than phase-1 AutoSKDBERT on six out of seven tasks. Consequently, useless teachers lead to more performance degradation than the consistency gap issue.

Table 6: The performance of AutoSKDBERT with the best categorical distribution learned by CR and SSWO for categorical distribution optimization on GLUE-dev.

Task	MRPC	RTE	CoLA	SST-2	QQP	QNLI	MNLI
Metrics	F1/acc	acc	Mcc	acc	F1/acc	acc	m
CR	92.9/90.2	74.7	50.2	92.7	87.9/91.0	91.5	83.9
SSWO	**93.2/90.7**	**76.9**	**51.8**	**93.0**	**88.0**/91.0	**91.6**	**84.3**
Gain	+0.3/+0.5	+2.2	+1.6	+0.3	+0.1/+0.0	+0.1	+0.4

4.3 CATEGORICAL DISTRIBUTION GENERATION: RANDOM VERSUS LEARNING

We compare two groups of implementation of AutoSKDBERT with various algorithms for categorical distribution generation, i.e., random and learning, on GLUE-dev. For random algorithm, 200 categorical distributions are randomly generated for all teacher candidates. For learning algorithm, we employ different learning rates of 3e-4 to 1e-3 with an interval of 1e-4 for categorical distribution optimization. Moreover, the ineffective teacher number is identical to Section 3.3.2 on various tasks. Subsequently, each implementation delivers 25 categorical distributions in phase-2 optimization. Consequently, 200 categorical distributions are obtained. The comparison between random and leaning algorithms is shown in Figure 3.

Figure 3: Histogram and kernel density curve of AutoSKDBERT with random and learning algorithm for categorical distribution generation on GLUE-dev. Two types of algorithm are evaluated by 200 categorical distributions. MRPC and QQP tasks are evaluated by the average of F1 score and accuracy score, CoLA task is evaluated by Matthews correlation coefficient, and other tasks are evaluated by accuracy score. Best viewed in color.

The categorical distribution generation algorithm aims to achieve more high-performance AutoSKDBERTs. As shown in Figure 3, the proposed learning algorithm contributes to obtaining better categorical distribution than those randomly generated on each downstream task. Particularly,

the learning algorithm plays a dominant role on MRPC, CoLA, QQP, QNLI and MNLI tasks. The best accuracy scores of random algorithm are 89.29 on QQP and 83.37 on MNLI, respectively. For the proposed learning algorithm, the worst accuracy scores are 89.11 on QQP and 83.44 on MNLI which rank the top 10 and the best in random algorithm, respectively.

5 RELATED WORK

5.1 PRE-TRAINED LANGUAGE MODEL

Based on the transformer-style architecture (Vaswani et al., 2017), BERT (Devlin et al., 2019) achieves state-of-the-art performance on different natural language understanding benchmarks, e.g., GLUE (Wang et al., 2019), SQuAD (Rajpurkar et al., 2016; 2018). Subsequently, a great number of variants of BERT are proposed, e.g., XLNet (Yang et al., 2019), ELECTRA (Clark et al., 2020) with new pre-training objectives, RoBERTa (Liu et al., 2019b), T5 (Raffel et al., 2020) with larger pre-training corpus, ConvBERT (Jiang et al., 2020) with various architectures and Synthesizer (Tay et al., 2020) with developed transformer-like block w.r.t. the dot-product self-attention mechanism. Besides, previous pre-trained language models often have several hundred million parameters (e.g. 335 million of BERT$_{LARGE}$ (Devlin et al., 2019), even 175 billion of GPT-3 (Brown et al., 2020)) which contribute to delivering amazing performance on downstream tasks while exponentially increasing the difficulty of deployment on resource-constrained device. ALBERT (Lan et al., 2020) adopts parameter sharing strategy to reduce the parameters, and achieves competitive performance.

5.2 KNOWLEDGE DISTILLATION FOR BERT-STYLE LANGUAGE MODEL COMPRESSION

In order to obtain device-friendly BERT-style language model, many KD-based compression approaches have been proposed. DistilBERT (Sanh et al., 2019) compresses a smaller, faster, cheaper and lighter 6-layer BERT-style language model via learning the soft target probabilities of the teacher in the pre-training stage. Sun et al. (2019) propose patient knowledge distillation which transfers knowledge from the last or every l layers, to compress BERT-style language model in the fine-tuning phase. In MobileBERT (Sun et al., 2020), an inverted-bottleneck BERT-style language model is pre-trained to transfer knowledge to task-agnostic MobileBERT in a layer-to-layer way. The student in MiniLM (Wang et al., 2020) imitates not only the attention distribution of the teacher, but also the deep self-attention knowledge which reflects the difference between values. In both the pre-training and the fine-tuning phases, TinyBERT (Jiao et al., 2020) learns various knowledge from hidden layer, final layer, embedding and self-attention to achieve high performance. Moreover, GloVe word embedding (Pennington et al., 2014) based data augmentation technique is employed to further improve the performance of TinyBERT. MT-BERT (Wu et al., 2021) employs multiple teachers to achieve better performance than single-teacher KD based approaches on several downstream tasks.

6 CONCLUSION AND FUTURE WORK

This work proposes AutoSKDBERT, which is a new paradigm of knowledge distillation for BERT model compression. In the proposed approach, a teacher is stochastically sampled from a predefined teacher team in each step to distill the student following a categorical distribution. Moreover, the teacher team consists of several multi-level teachers with different capabilities. We observe that the categorical distribution plays an important role for obtaining high-performance AutoSKDBERT. Consequently, we propose a two-phase optimization framework to learn the best categorical distribution in a differentiable way. The first phase distinguishes effective teachers from ineffective teachers. In the second phase, the effective teachers are further optimized. Moreover, before phase-2 optimization beginning, the ineffective teachers are discarded and their weights are assigned to the effective teachers via teacher selection strategy. Extensive experiments on GLUE benchmark show that the proposed AutoSKDBERT achieves state-of-the-art performance compared to popular compression approaches on several downstream tasks.

In each step, however, AutoSKDBERT employs identical categorical distribution for various mini-batch data. In the future, we will focus on learning differentially from teachers (Yuan et al., 2021) via using various categorical distributions for different mini-batch data, to further improve the robustness and performance of AutoSKDBERT.

REFERENCES

Luisa Bentivogli, Peter Clark, Ido Dagan, and Danilo Giampiccolo. The fifth pascal recognizing textual entailment challenge. In *TAC*, 2009.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pp. 1877–1901, 2020.

Daniel Cer, Mona Diab, Eneko Agirre, Inigo Lopez-Gazpio, and Lucia Specia. Semeval-2017 task 1: Semantic textual similarity-multilingual and cross-lingual focused evaluation. In *Proceedings of the 11th Inter- national Workshop on Semantic Evaluation*, 2017.

Zihan Chen, Hongbo Zhang, Xiaoji Zhang, and Leqi Zhao. Quora question pairs. *University of Waterloo*, pp. 1–7, 2018.

Kevin Clark, Minh-Thang Luong, Quoc V Le, and Christopher D Manning. ELECTRA: Pre-training text encoders as discriminators rather than generators. In *8th International Conference on Learning Representations, ICLR*, 2020.

Benoît Colson, Patrice Marcotte, and Gilles Savard. An overview of bilevel optimization. *Annals of operations research*, 153(1):235–256, 2007.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT*, volume 1, pp. 4171–4186, 2019.

Bill Dolan and Chris Brockett. Automatically constructing a corpus of sentential paraphrases. In *Third International Workshop on Paraphrasing, IWP*, 2005.

Yihe Dong, Jean-Baptiste Cordonnier, and Andreas Loukas. Attention is not all you need: Pure attention loses rank doubly exponentially with depth. In *International Conference on Machine Learning*, pp. 2793–2803. PMLR, 2021.

Angela Fan, Edouard Grave, and Armand Joulin. Reducing transformer depth on demand with structured dropout. In *8th International Conference on Learning Representations, ICLR*, 2020.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning (ICML)*, pp. 1126–1135. PMLR, 2017.

Jiahui Gao, Hang Xu, Han Shi, Xiaozhe Ren, LH Philip, Xiaodan Liang, Xin Jiang, and Zhenguo Li. AutoBERT-zero: Evolving bert backbone from scratch. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 10663–10671, 2022.

Mitchell A. Gordon, Kevin Duh, and Nicholas Andrews. Compressing BERT: studying the effects of weight pruning on transfer learning. In *Proceedings of the 5th Workshop on Representation Learning for NLP*, pp. 143–155. Association for Computational Linguistics, 2020.

Fuming Guo, Sijia Liu, Finlay S Mungall, Xue Lin, and Yanzhi Wang. Reweighted proximal pruning for large-scale language representation. *arXiv preprint arXiv:1909.12486*, 2019.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Forrest N Iandola, Albert E Shaw, Ravi Krishna, and Kurt W Keutzer. Squeezebert: What can computer vision teach nlp about efficient neural networks? *arXiv preprint arXiv:2006.11316*, 2020.

Zi-Hang Jiang, Weihao Yu, Daquan Zhou, Yunpeng Chen, Jiashi Feng, and Shuicheng Yan. Convbert: Improving bert with span-based dynamic convolution. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pp. 12837–12848, 2020.

Xiaoqi Jiao, Yichun Yin, Lifeng Shang, Xin Jiang, Xiao Chen, Linlin Li, Fang Wang, and Qun Liu. Tinybert: Distilling BERT for natural language understanding. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP*, pp. 4163–4174, 2020.

Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. ALBERT: A lite BERT for self-supervised learning of language representations. In *8th International Conference on Learning Representations, ICLR*, 2020.

Hector Levesque, Ernest Davis, and Leora Morgenstern. The winograd schema challenge. In *Thirteenth international conference on the principles of knowledge representation and reasoning*, 2012.

Hanxiao Liu, Karen Simonyan, Yiming Yang, et al. DARTS: Differentiable architecture search. In *International Conference on Learning Representations (ICLR)*, 2019a.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. RoBERTa: A robustly optimized BERT pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019b.

Paul Michel, Omer Levy, and Graham Neubig. Are sixteen heads really better than one? In *Advances in Neural Information Processing Systems, NeurIPS*, volume 32, 2019.

Seyed Iman Mirzadeh, Mehrdad Farajtabar, Ang Li, Nir Levine, Akihiro Matsukawa, and Hassan Ghasemzadeh. Improved knowledge distillation via teacher assistant. In *Proceedings of the AAAI Conference on Artificial Intelligence, AAAI*, volume 34, pp. 5191–5198, 2020.

Rafael Müller, Simon Kornblith, and Geoffrey E Hinton. When does label smoothing help? In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 32, 2019.

Haojie Pan, Chengyu Wang, Minghui Qiu, Yichang Zhang, Yaliang Li, and Jun Huang. Meta-KD: A meta knowledge distillation framework for language model compression across domains. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, ACL/IJCNLP*, pp. 3026–3036, 2021.

Jeffrey Pennington, Richard Socher, and Christopher D Manning. GloVe: Global vectors for word representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing, EMNLP*, pp. 1532–1543, 2014.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21:140:1–140:67, 2020.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100, 000+ questions for machine comprehension of text. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing, EMNLP*, pp. 2383–2392, 2016.

Pranav Rajpurkar, Robin Jia, and Percy Liang. Know what you don't know: Unanswerable questions for squad. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics, ACL*, pp. 784–789, 2018.

Hassan Sajjad, Fahim Dalvi, Nadir Durrani, and Preslav Nakov. Poor man's bert: Smaller and faster transformer models. *arXiv preprint arXiv:2004.03844*, 2020.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. DistilBERT, a distilled version of BERT: Smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*, 2019.

Sheng Shen, Zhen Dong, Jiayu Ye, Linjian Ma, Zhewei Yao, Amir Gholami, Michael W Mahoney, and Kurt Keutzer. Q-BERT: Hessian based ultra low precision quantization of BERT. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 8815–8821, 2020.

Han Shi, Jiahui Gao, Xiaozhe Ren, Hang Xu, Xiaodan Liang, Zhenguo Li, and James Tin-Yau Kwok. Sparsebert: Rethinking the importance analysis in self-attention. In *International Conference on Machine Learning, ICML*, pp. 9547–9557. PMLR, 2021.

Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D Manning, Andrew Y Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing, EMNLP*, pp. 1631–1642, 2013.

Siqi Sun, Yu Cheng, Zhe Gan, and Jingjing Liu. Patient Knowledge Distillation for BERT Model Compression. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing, EMNLP-IJCNLP*, pp. 4322–4331, 2019.

Zhiqing Sun, Hongkun Yu, Xiaodan Song, Renjie Liu, Yiming Yang, and Denny Zhou. Mobilebert: A compact task-agnostic BERT for resource-limited devices. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL*, pp. 2158–2170, 2020.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, *, pp. 2818–2826, 2016.

Y Tay, D Bahri, D Metzler, D Juan, Z Zhao, and C Zheng. Synthesizer: Rethinking self-attention in transformer models. arxiv 2020. *arXiv preprint arXiv:2005.00743*, 2, 2020.

Linh Tran, Bastiaan S Veeling, Kevin Roth, Jakub Swiatkowski, Joshua V Dillon, Jasper Snoek, Stephan Mandt, Tim Salimans, Sebastian Nowozin, and Rodolphe Jenatton. Hydra: Preserving ensemble diversity for model distillation. In *International Conference on Machine Learning Workshop on Uncertainty and Robustness in Deep Learning*, 2020.

Iulia Turc, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Well-read students learn better: The impact of student initialization on knowledge distillation. *arXiv preprint arXiv:1908.08962*, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. volume 30, 2017.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *7th International Conference on Learning Representations, ICLR*, 2019.

Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. MiniLM: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. In *Advances in Neural Information Processing Systems, NeurIPS*, volume 33, pp. 5776–5788, 2020.

Alex Warstadt, Amanpreet Singh, and Samuel R Bowman. Neural network acceptability judgments. *Transactions of the Association for Computational Linguistics*, 7:625–641, 2019.

Adina Williams, Nikita Nangia, and Samuel R Bowman. A broad-coverage challenge corpus for sentence understanding through inference. In *Proceedings of the 2017 Conference of the North American Chapter of the Association for Computational Linguistics, NAACL*, 2017.

Chuhan Wu, Fangzhao Wu, and Yongfeng Huang. One teacher is enough? pre-trained language model distillation from multiple teachers. In *Findings of the Association for Computational Linguistics: ACL/IJCNLP*, pp. 4408–4413, 2021.

Canwen Xu, Wangchunshu Zhou, Tao Ge, Furu Wei, and Ming Zhou. BERT-of-Theseus: Compressing BERT by progressive module replacing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP*, pp. 7859–7869, 2020.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. XLNet: Generalized autoregressive pretraining for language understanding. In *Advances in Neural Information Processing Systems, NeurIPS*, volume 32, 2019.

Fei Yuan, Linjun Shou, Jian Pei, Wutao Lin, Ming Gong, Yan Fu, and Daxin Jiang. Reinforced multi-teacher selection for knowledge distillation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 14284–14291, 2021.

Simiao Zuo, Qingru Zhang, Chen Liang, Pengcheng He, Tuo Zhao, and Weizhu Chen. MoEBERT: from BERT to Mixture-of-Experts via importance-guided adaptation. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL*, pp. 1610–1623, 2022.

A   DETAILS OF STUDENT AND TEACHER TEAM

A.1   ARCHITECTURE INFORMATION

The architecture information of student and teachers is shown in Table 7.

Table 7: The architecture of each student and teacher.

Model	Name	Layer	Hidden Size	Head	#Params (M)
Student	AutoSKDBERT	6	768	12	67.0
Teacher	T_{01}	8	128	2	5.6
	T_{02}	10	128	2	6.0
	T_{03}	12	128	2	6.4
	T_{04}	8	256	4	14.3
	T_{05}	10	256	4	15.9
	T_{06}	12	256	4	17.5
	T_{07}	8	512	8	41.4
	T_{08}	10	512	8	47.7
	T_{09}	12	512	8	54.0
	T_{10}	8	768	12	81.1
	T_{11}	10	768	12	95.3
	T_{12}	12	768	12	110
	T_{13}	24	1024	16	335
	T_{14}†	24	1024	16	335

† Pre-training with whole word masking.

A.2   HYPER-PARAMETERS FOR FINE-TUNING

For student and teacher team fine-tuning, we utilize the hyper-parameters shown in Table 8.

Table 8: Hyper-parameters for fine-tuning of student and teacher team.

Hyper-parameter	Value
Adam ϵ	1e-6
Adam β_1	0.9
Adam β_2	0.999
Learning rate decay	linear
Warmup fraction	0.1
Attention dropout	0.1
Dropout	0.1
Weight decay	1e-4
Batch size	32 for fine-tuning, {16, 32} for distillation
Learning rate	For T_{13} and T_{14}, {6e-6, 7e-6, 8e-6, 9e-6} on MRPC and RTE tasks, {2e-5, 3e-5, 4e-5, 5e-5} on other tasks. For student other teachers, {2e-5, 3e-5, 4e-5, 5e-5} and {1e-5, 2e-5, 3e-5} on all tasks, respectively.
Fine-tuning epochs	15 on MRPC, RTE and CoLA tasks, 5 on other tasks

A.3 Fine-tuning Performance

On the one hand, we direct treating the pre-trained model of TinyBERT$_6$[1] as the student of AutoSKDBERT. On the other hand, we choose 14 BERT models with various capabilities as the candidates for teacher team. Moreover, each pre-trained teacher can be downloaded from official implementation of BERT[2]. Furthermore, the results of the student and the teacher on GLUE-dev are shown in Table 9.

Table 9: The fine-tuning performances of student and teachers on GLUE-dev.

Model	MRPC $\frac{F1+acc}{2}$	RTE acc	CoLA Mcc	SST-2 acc	QQP $\frac{F1+acc}{2}$	QNLI acc	MNLI m	Avg
AutoSKDBERT	89.44	71.84	88.52	91.63	86.44	90.70	82.55	85.87
T_{01}	81.83	66.06	85.15	86.24	83.95	83.80	72.95	80.00
T_{02}	84.75	66.06	84.99	85.67	84.18	84.00	73.75	80.49
T_{03}	84.59	65.70	85.73	86.47	85.02	84.40	75.16	81.01
T_{04}	85.18	64.62	86.77	89.33	86.36	86.80	78.16	82.46
T_{05}	87.84	66.06	87.45	89.33	87.25	87.26	78.75	83.42
T_{06}	85.96	66.06	87.00	89.68	87.21	87.42	79.54	83.27
T_{07}	87.91	70.04	88.46	91.28	88.69	89.27	80.84	85.21
T_{08}	88.17	65.70	88.75	91.28	88.62	89.25	81.41	84.74
T_{09}	88.85	66.43	88.74	92.09	89.01	90.33	81.90	85.34
T_{10}	89.36	68.95	89.03	93.00	89.27	90.79	83.05	86.21
T_{11}	90.10	71.12	89.59	92.78	89.71	91.20	84.00	86.93
T_{12}	89.98	68.59	90.20	92.66	89.66	91.85	84.40	86.76
T_{13}	**90.60**	62.74	90.13	94.50	90.26	92.70	86.88	86.83
T_{14}	90.15	**79.06**	**91.21**	**94.72**	**90.40**	**93.89**	**87.06**	**89.50**

B Multi-teacher Knowledge Distillation for BERT Compression

For BERT-style language model compression, we verify the performance of MT-BERT (Wu et al., 2021) whose objection function can be expressed as:

$$\mathcal{L}_{\text{MTBERT}} = \sum_{i=1}^{N} \frac{\text{CE}(y_i/T, y_s/T)}{1 + \text{CE}(y, y_i)}, \tag{9}$$

where, N indicates the number of teachers, $\text{CE}(\cdot, \cdot)$ is the cross-entropy loss, T denotes the temperature, y represents the ground-truth label, y_i and y_s refer to the outputs of i-th teacher and the student, respectively.

We employ T_{10} to T_{14} as the teacher team to distill the student via Eq. 9. Particularly, we only use the weighted multi-teacher distillation loss without the multi-teacher hidden loss and the task-specific loss as in MT-BERT (Wu et al., 2021).

The hyper-parameters are given as follows:

- **Learning Rate**: {1e-5, 2e-5, 3e-5} for all tasks.
- **Batch Size**: {16, 32, 64}.
- **Epoch**: 10 for MRPC, RTE and CoLA tasks, 3 for other tasks.

Other settings are identical AutoSKDBERT.

C Details of GLUE Benchmark

GLUE consists of 9 NLP tasks: Microsoft Research Paraphrase Corpus (MRPC) (Dolan & Brockett, 2005), Recognizing Textual Entailment (RTE) (Bentivogli et al., 2009), Corpus of Linguistic Acceptability (CoLA) (Warstadt et al., 2019), Semantic Textual Similarity Benchmark (STS-B)

---

[1] https://huggingface.co/huawei-noah/TinyBERT_General_6L_768D
[2] https://github.com/google-research/bert

(Cer et al., 2017), Stanford Sentiment Treebank (SST-2) (Socher et al., 2013), Quora Question Pairs (QQP) (Chen et al., 2018), Question NLI (QNLI) (Rajpurkar et al., 2016), Multi-Genre NLI (MNLI) (Williams et al., 2017), and Winograd NLI (WNLI) (Levesque et al., 2012).

MRPC. belongs to a sentence similarity task where system aims to identify the paraphrase/semantic equivalence relationship between two sentences.

RTE. belongs to a natural language inference task where system aims to recognize the entailment relationship of given two text fragments.

CoLA. belongs to a single-sentence task where system aims to predict the grammatical correctness of an English sentence.

STS-B. belongs to a sentence similarity task where system aims to evaluate the similarity of two pieces of texts by a score from 1 to 5.

SST-2. belongs to a single-sentence task where system aims to predict the sentiment of movie reviews.

QQP. belongs to a sentence similarity task where system aims to identify the semantical equivalence of two questions from the website Quora.

QNLI. belongs to a natural language inference task where system aims to recognize that for a given pair <*question*, *context*>, the answer to the *question* whether contains in the *context*.

MNLI. belongs to a natural language inference task where system aims to predict the possible relationships (i.e., entailment, contradiction and neutral) of *hypothesis* w.r.t. *premise* for a given pair <*premise*, *hypothesis*>.

WNLI. belongs to a natural language inference task where system aims to determine the referent of a sentence's pronoun from a list of choices.