GROUP-BASED INTERLEAVED PIPELINE PARALLELISM FOR LARGE-SCALE DNN TRAINING

ABSTRACT

The recent trend of using large-scale deep neural networks (DNN) to boost performance has propelled the development of the parallel pipelining technique for efficient DNN training, which has resulted in the development of several prominent pipelines such as GPipe, PipeDream, and PipeDream-2BW. However, the current leading pipeline, PipeDream-2BW, still suffers from two major drawbacks, namely the excessive memory redundancy and the delayed weight updates across all stages. In this work, we propose a novel pipeline named WPipe, which achieves better memory efficiency and fresher weight updates. WPipe uses a novel pipelining scheme, which divides model partitions into two groups. It moves the forward pass of the next period to the front of the backward pass of the current period in the first group, retains the order in the second group, and updates each group alternatively. This will eliminate half of the delayed gradients and memory redundancy compared to PipeDream-2BW. The results of our experiments, in which large BERT language models were trained, show that compared to PipeDream-2BW, WPipe achieves $1.4\times$ acceleration, reduces the memory footprint by 36% with similar final model accuracy.

1 INTRODUCTION

Several recent lines of research Liu et al. (2019); Yang et al. (2019); Lan et al. (2019); Raffel et al. (2019); Brown et al. (2020); Lin et al. (2021) on various application domains have collectively demonstrated that larger DNN models can yield better performance. This creates an emerging trend in scaling up the number of model parameters, resulting in very large DNNs, the memory footprint of which will be beyond the limit of a single accelerator.

To resolve the aforementioned problem, researchers and practitioners focused on the use of the model-parallel technique to partition large models over multiple accelerators/workers; this allows to further scale up model parameters significantly. However, in conventional model parallelism, computing resources are severely underutilized as only one accelerator can work at a time. Recently, some studies proposed the pipeline-parallel technique to accelerate conventional model parallelism. The pipeline technique can effectively improve the utilization of computing resources by scheduling different workers to consume different mini-batches in parallel. However, naive pipelining can lead to two major problems: (1) staleness of weight updates Harlap et al. (2018), which is caused by the inconsistency of the weight versions used in a forward pass and its corresponding backward pass, and (2) excessive in-flight activations, which is caused by excessive forward passes waiting for their corresponding backward passes in pipelining.

The problem of staleness of weight updates can be solved using workable pipelines with different emphases on low memory footprint and high throughput. GPipe uses the periodic pipeline flushing technique, which maintains only one weight version. This technique can achieve a low memory footprint and almost the same weight update semantics as data parallelism, but at the cost of introducing bubble overhead Huang et al. (2019), thus limiting throughput. PipeDream uses the weights stashing Harlap et al. (2018) technique without introducing bubble overhead, resulting in higher throughput; however, the multiple weight versions incur a high memory footprint. To further reduce the excessive weight versions maintained in PipeDream, PipeDream-2BW was proposed in which the double-buffered weight update technique Narayanan et al. (2021) is used, which largely

reduces the number of weight versions and enables similar weight update semantics as that in data parallelism.

Moreover, GPipe and PipeDream-2BW use the activation recomputation technique Chen et al. (2016); Jain et al. (2019) to solve the problem of excessive in-flight activations. Recomputation enables the forward pass to function without retaining its generated activations. Instead, it will be recomputed in the corresponding backward pass. This effectively alleviates the stacking up of in-flight activations and greatly reduces the memory footprint. Notably, although both GPipe and PipeDream-2BW utilize the recomputation technique, PipeDream-2BW has less in-flight activations than GPipe owing to the more timely execution of the backward pass in its pipeline. Additionally, PipeDream does not take any measures for solving the activations problem, and therefore the training of very large models becomes difficult.

At present, PipeDream-2BW is the best pipeline-parallel system in terms of overall performance. However, it still suffers from two main problems: (1) delayed weight updates, which is to solve the problem of weight staleness Narayanan et al. (2021), and (2) excessive memory redundancy, which includes two weighted versions in 2BW Narayanan et al. (2021) and in-flight activations. In this paper, we propose a novel pipeline, named WPipe, to solve these two problems. It divides model partitions into two groups, namely G_0 and G_1, which share the same workers. In this method, the forward pass of the next period is moved to the front of the backward pass of the current period in G_0, and the order in G_1 is retained, and then, G_0 and G_1 are updated alternatively. We named the alternate update technique for the grouping weights as double-grouped weight updates (2GW). Compared to 2BW, the 2GW pipeline also does not introduce idle time, and in G_1, 2GW realizes the same weight update semantics as that in data parallelism and only maintains one weight version; in G_0, to deal with the weight staleness problem caused by the forward pass move operation, we reserve a delay item in the semantics of weight update and maintains the same weight versions. In addition, the in-flight activations of WPipe are reduced by half, because only half of the weights are involved in the training at a time. Therefore, it reduces half of the delayed gradients and memory redundancy compared to PipeDream-2BW.

Additionally, we combined the overlap of computation and communication, hybrid parallelism, and heterogeneous communication to further reduce communication overhead. Our throughput experiments show that WPipe achieves acceleration of $7.1\times$ compared to that of PipeDream and $2.1\times$ compared to that of GPipe for Bert192 with 1.4 billion parameters. When training models with up to 5.5 billion parameters, which cannot be trained by GPipe and PipeDream, WPipe is $1.4\times$ faster than PipeDream-2BW. The memory experiments show that compared to PipeDream-2BW, WPipe reduces the memory footprint by 35.8% for Bert96.

2 BACKGROUND

In this section, we briefly introduce the related techniques of model parallelism based on pipeline parallelism..

Model parallelism. Model parallelism Chen et al. (2018); Chilimbi et al. (2014); Dean et al. (2012); Jia et al. (2018) partitions large models into multiple parts and assigns them to different workers. Each worker is responsible for their weight updates and sending and receiving intermediate activations and gradients. However, as shown in Figure 1a, naive model parallelism suffers from underutilized resources, as only one worker is active at a time.

Figure 1: Timelines of model-parallel and naive pipeline-parallel executions.

Pipeline Parallelism. Pipeline parallelism can effectively improve the utilization of computing resources by scheduling different workers to consume different mini-batches simultaneously. However, naive pipeline parallelism suffers from staleness issue for weight updates. As shown in Figure 1b,

as different workers process different mini-batches simultaneously, when the backward pass of the latter mini-batch is executed, its corresponding weights could be updated by the prior mini-batch. For example, for mini-batch 2, the weights used in the backward pass were updated by mini-batch 1.

Existing solutions tackle the issue by trading off throughput and memory footprint. GPipe proposes the periodic pipeline flushing technique Huang et al. (2019). As shown in Figure 2a, it splits a mini-batch into multiple micro-batches, which are injected in the model continuously to achieve pipelining. Within each pipeline period, GPipe can accumulate gradients across micro-batches and flush synchronously. In this way, it achieves the same weight update semantics as data parallelism and only maintains a single weight version. However, in GPipe, bubble overhead Huang et al. (2019) is introduced, which limits throughput, especially when a large mini-batch cannot be supported. PipeDream-flush is essentially the same as GPipe Narayanan et al. (2021). Compared to GPipe, the main improvement is to move forward the backward pass. This can release in-flight activation as soon as possible, reducing memory footprint.

Figure 2: Timelines of various pipeline-parallel executions: (a) GPipe updates the weights in a mini-batch. (b) PipeDream-flush moves backward pass forward compared to GPipe. (c) PipeDream implements weight stashing to update the weight immediately by default. (d) PipeDream-2BW realizes periodic update through gradient accumulation, which reduces the weight version. For example, mini-batch 2 and 4 update weights.

PipeDream uses the weight stashing technique to tackle the staleness issue without introducing the bubble overhead, and thus achieves higher throughput Harlap et al. (2018). However, it must maintain a large number of weight versions. From Figure 2b worker $i(i = 0, 1, ...)$ comprises $N - i$ weight versions, where N is the number of model partitions. This results in a high memory footprint, especially when N is large. Moreover, in PipeDream, the weight update semantics has different delay terms at different stages.

PipeDream-2BW Narayanan et al. (2021), as an upgraded version of PipeDream, has higher throughput and more memory efficiency. As shown in Figure 2c, it uses double-buffered weight updates (2BW), which is combined with gradient accumulation, to reduce effectively the number of weight versions maintained on each worker from $N - i$ to 2. Notably, in 2BW, its weight update semantics has only one weight delay term across all stages.

3 SYSTEM DESIGN OF WPIPE

In this section, we first analyze the problems of 2BW. Then, we propose double-grouped weight updates (2GW), and analyze 2GW from three aspects: model partitions grouping, effective learning, and memory footprint. Finally, we introduce several communication optimization techniques.

3.1 INTRODUCTION

Figure 3: Separate two adjacent update periods in PipeDream-2BW by introducing idle time blocks.

We denote naive model-parallel timeline as V_2 (where "2" represents the number of model partitions), as shown in Figure 1a. V_2s are cross-spliced to form pipeline, as shown in Figure 1b. We denoted this process as P and its result as $P(nV_2)$ (where n represents the number of V_2). As shown in Figure 1b, P can ensure that the backward pass is executed immediately after the forward pass is completed so that the forward activations can be released in time to alleviate the stacking up of the activations. However, the raw pipeline parallelism formed by P and V_n suffers from the inconsistency issue. To address the issue, 2BW uses double weight versions and combines gradient accumulation. Where is the other weight version in 2BW used ? It is at the intersection of adjacent periods. As shown in Figure 2c, the forward pass for mini-batch 3 is executed before the backward pass for mini-batch 2, but its backward pass is executed after the backward pass for mini-batch 2. At this time, it is necessary to continue to use the old weight version in the period of mini-batches 3 and 4, and the new weight version (updated by mini-batches 2) will be used in the next period (mini-batches 5 and 6). Thus, if we want to further reduce the number of weight versions, we need to eliminate the intersections of mini-batches 2 and 3, 4 and 5, etc. To achieve this, we temporarily introduce idle time blocks, as shown in Figure 3 (its pipelining is the same as PipeDream-flush).

If these idle time blocks cannot be eliminated, can we fill them? Through the statistical analysis, we found that for a pipeline of PipeDream-2BW with n model partitions, at least the idle time blocks shaped like $P(xV_n), x >= (n-1)$ are required to eliminate the intersections. In addition, a pipeline accumulation period has at least execution time blocks shaped like $P(xV_n), x >= n$. Obviously, when $x >= n$, they have the same shape. Thus, can we fill these idle time blocks with the pipelining of another part of the weights of a model?

3.2 Double-Grouped Weight Updates (2GW)

In this subsection, we introduce the 2GW technique from model partitions grouping and weight update semantics.

Model Partitions Grouping. As shown in Figure 4a, based on Figure 1a, we further split each model partition into two and obtain twice the number of model partitions with the same number of workers. Then, we divide them into two groups, G_0 and G_1. For G_1, it is a standard V_2, which can realize continuous pipeline expansion through P. But for G_0, the forward pass and backward pass are separated, which needs to be converted into a V_2 structure before P can be processed. To achieve the transformation, we move the forward pass of G_0 of the next step to the front of the backward pass of G_0 of the current step to form a V_2, as shown in Figure 4b. Then we cross-splice G_0 and G_1 respectively to obtain $P(G_0)$ and $P(G_1)$, and then continue to cross-splice their results to obtain $P(P(G_0), P(G_1))$. For G_1, its mini-batches 2 and 3 can be well separated by the pipelining of G_0 ($P(G_0)$), as shown in Figure 4c. This also answers the question mentioned in section 3.1. The pipelining of G_0 can fill in the idle time blocks in Figure 3.

Figure 4: Derivation of WPipe pipeline: (a) Further partitioning and grouping, (b) moving the G_0 forward pass of the next step to the front of the backward pass of G_0 of the current, (c) expansion of the pipelining for (b).

Weight Update Semantics. As shown in Figure 4c, G_1 only maintains one weight version and has the same weight update semantics as data parallelism. For G_0, due to the movement operation, the intersections naturally exist, such as mini-batches 3, 4 and 2 in Figure 4. Nevertheless, G_0 only needs

Figure 5: Timeline of execution of 2GW, where only G_0 needs double weight versions.

Table 1: Details of the memory footprint of pipeline systems of GPipe, PipeDream, PipeDream-2BW, and WPipe, where we ignore the intermediate activations for recomputation.

PIPELINE	BUBBLE RATIO	THE SIZE OF ALL BUFFERS	ACTIVATIONS (NON-RECOMPUTATION)	ACTIVATIONS (RECOMPUTATION)
GPIPE	$\frac{N-1}{M+N-1}$	0	MS_a	S_a
PIPEDREAM	0	$\frac{N+1}{2}S_m$	$\frac{2M-N+1}{2}S_a$	NONE
PIPEDREAM-2BW	0	$2S_m$	$\frac{2M-N+1}{2}S_a$	S_a
WPIPE	0	$\boldsymbol{S_m}$	$\frac{4M-N+1}{4}S_a$	$\boldsymbol{0.5S_a}$

to maintain two weighted versions, and there is only one delay term in the weight update semantics, which is the same as 2BW. If using SGD optimizer, weight update semantics of 2GW are as follows:

$$w_{G_i}^{t+1} = w_{G_i}^t - \nu \cdot \nabla f(w_{G_i 1}^{(t-1+i)}, w_{G_i 2}^{(t-1+i)}, ..., w_{G_i n}^{(t-1+i)}), i \in \{0, 1\} \tag{1}$$

Other optimizers can be similarly analyzed. Figure 5 shows a more detailed pipeline-parallel timeline of 2GW.

3.3 MEMORY FOOTPRINT ANALYSIS

The memory footprint of most pipelines is mainly divided into four parts, i.e., naive model weights, weight buffers (saving history weight versions), in-flight activations, and optimizer. Since the naive model weights and optimizer are roughly the same for each pipeline method, we mainly analyze weight buffers and in-flight activations. G_1 has no weight buffer, and the size of G_0's weight buffer is 2. We use S_p to represent the size of the entire model parameters, M_{G_0} and M_{G_1} represent the sizes of G_0 and G_1, respectively. Supposing that the model is evenly divided ($M_{G_1} = M_{G_0}$), the size of weight buffer of WPipe is $M = 2M_{G_1} = M_{G_0} + M_{G_1} = S_p$. For in-flight activations, we use S_a to indicate the activations of the entire model for a mini-batch. From Figure 5, we statistically conclude that the in-flight activation amount of $stage_i$ is equal to $M * \frac{S_a}{2N}$ for G_0 and $(M-i) * \frac{S_a}{2N}$ for G_1 and of all stages is equal to:

$$\sum_{i=0}^{i=N-1} (2M - i) * \frac{S_a}{2N} = \frac{4M - N + 1}{4} * S_a, \tag{2}$$

where the N and M indicate the number of model partitions and micro-batches, respectively, and $M >= N$. The same statistical method is used for GPipe, PipeDream, and PipeDream-2BW to obtain their size of all weight buffers and in-flight activations, respectively, as shown in Table 1.

With Activation Recomputation. From Table 1, the in-flight activations increase linearly with the number of model partitions, which will become a memory bottleneck when training a large model. Thus, a pipeline system must take measures to reduce in-flight activations. The activation recomputation is an effective method widely accepted, especially for 2GW. It can eliminate the stacking up of historical in-flight activations, leaving only the activations in an active state in the system, as shown in Table 1. From the table, we can summarize the following points: (a) compared to PipeDream-2BW, the weight buffer size of WPipe is reduced by half, and the superiority is more obvious compared to PipeDream. Although GPipe has no weight buffer, it has to pay the price of introducing $\frac{N-1}{M+N-1}$ bubble overhead; (b) recomputation can significantly reduce in-flight activations for GPipe, PipeDream-2BW, and WPipe, especially for WPipe.

3.4 COMMUNICATION OPTIMIZATION

We use C_a to represent the cost of intermediate activations or gradients in one communication. With the same number of stages, model-parallel communication overheads of different pipeline systems are $C_{\text{WPipe}} = 2(2N_s - 1)C_a$, $C_{\text{2BW}} = 2(N_s - 1)C_a$, and $C_{\text{GPipe}} = 2(N_s - 1)C_a$, respectively, where N_s indicates the number of stages. The three equations show that with the same number of stages, the communication overhead of WPipe is twice that of GPipe and PipeDream-2BW due to the double number of model partitions. Nevertheless, in most cases, C_a is small and can be ignored, especially when training language models, such as Transformer Vaswani et al. (2017). When C_a is large, We have the following countermeasures:

Combination with Data Parallelism. Normally, C_a is too large because the size of batch is too large. In this case, we can reduce the size of batch and the number of the model partitions, and replicate each stage on the newly idle accelerator devices for data parallelism to increase the total batch size to the original size, as shown in Figure 6. This not only reduces the C_a, but also does not add new accelerator device and change the batch size. Of course, we need to weigh the communication overhead between model parallelism (C_{WPipe}) and data parallelism (C_{DP}). When C_{WPipe} is greater than C_{DP}, we reduce the model-parallel batch size

Figure 6: Layouts of model parallelism and data parallelism.

and the number of model partitions, and increase the number of data-parallel groups. Otherwise, we increase the model-parallel batch size and reduce the number of data-parallel groups.

Overlap of Computation and Communication. The activations or gradients communication can overlap with the forward pass, backward pass, and activation recomputation. Especially for activation recomputation, its time overhead can be offset mostly.

Heterogeneous Network Communication. Generally, the intra-machine bandwidth is higher than the inter-machine bandwidth (e.g. NVLink nvl). Thus, we allocate a higher bandwidth to the one with the larger communication volume between model parallelism and data parallelism to balance the communication overhead of the two. In addition, some communication compression techniques can also be used to reduce C_a. A simple example is listed in the appendix.

4 EXPERIMENTS

WPipe is implemented with PyTorch-1.4 Edward Z. Yang (2021) and executes on two environments, i.e., a single machine with eight 16-GB V100 GPUs (Env-1) and a private cluster with 8×8V100 GPUs (Env-2).

4.1 QUALITY OF CONVERGENCE

In this section, we compare the convergences of WPipe and PipeDream-2BW by comparing the accuracy when training the same model on the same dataset with the same hyperparameters.

Text Classification. We finetuned BERT$_{\text{BASE}}$ Devlin et al. (2018) and BERT$_{\text{LARGE}}$ Devlin et al. (2018) for WPipe, PipeDream-2BW, and data parallelism on the QQP and MNLI tasks Wang et al. (2018). We used respectively `bert-base-uncase` and `bert-large-uncase` pre-training weights from `transformers-3.5.0` Wolf et al. (2020). We used Adam optimizer, a learning rate of $8 \times 10^{-5}(\nu = 8 \times 10^{-5})$ with 1000 steps warmup($ws = 1000$) and mini-batch size of $256(b = 256)$ for BERT$_{\text{BASE}}$ and the same optimizer, $\nu = 4 \times 10^{-5}$ with $ws = 2000$ and $b = 128$ for BERT$_{\text{LARGE}}$. From Table 2, WPipe, PipeDream-2BW, and data parallelism have the similar final accuracy. For further analysis, we continue to perform image classification experiments.

Image Classification. We finetuned, respectively, the ResNeXt50 (32x4d) Xie et al. (2017) and ResNeXt101 (32x8d) Xie et al. (2017) for WPipe, PipeDream-2BW and data parallelism on the three

Table 2: The results of the convergence experiment of WPipe. We train the models three times with different seeds. Then, we calculated the means and standard deviations of the results. Where DP represents data parallelism and PD-2BW represents PipeDream-2BW.

TASKS	MODEL	METRIC	DP	WPIPE	PD-2BW
QQP	BERT$_{BASE}$	ACC	87.66 ± 0.06	$\mathbf{87.68 \pm 0.06}$	87.63 ± 0.03
		F1	$\mathbf{83.39 \pm 0.02}$	83.39 ± 0.04	83.34 ± 0.05
	BERT$_{LARGE}$	ACC	$\mathbf{87.63 \pm 0.05}$	87.59 ± 0.07	87.38 ± 0.02
		F1	$\mathbf{83.26 \pm 0.08}$	83.21 ± 0.11	82.96 ± 0.05
MNLI	BERT$_{BASE}$	ACC	82.81 ± 0.01	$\mathbf{83.05 \pm 0.19}$	82.98 ± 0.14
		M-ACC	$\mathbf{83.16 \pm 0.03}$	83.04 ± 0.29	82.82 ± 0.26
	BERT$_{LARGE}$	ACC	86.16 ± 0.12	86.25 ± 0.21	$\mathbf{86.29 \pm 0.12}$
		M-ACC	86.05 ± 0.26	$\mathbf{86.15 \pm 0.26}$	86.08 ± 0.24
OXFORD FLOWERS102	RESNEXT50_32X4D	ACC	$\mathbf{99.55 \pm 0.14}$	99.47 ± 0.14	99.51 ± 0.12
	RESNEXT101_32X8D	ACC	$\mathbf{99.39 \pm 0.21}$	99.19 ± 0.19	99.19 ± 0.19
CIFAR10	RESNEXT50_32X4D	ACC	97.15 ± 0.10	$\mathbf{97.28 \pm 0.20}$	97.26 ± 0.09
	RESNEXT101_32X8D	ACC	98.15 ± 0.07	$\mathbf{98.18 \pm 0.07}$	98.15 ± 0.07
CIFAR100	RESNEXT50_32X4D	ACC	85.67 ± 0.12	85.62 ± 0.09	$\mathbf{85.80 \pm 0.21}$
	RESNEXT101_32X8D	ACC	87.90 ± 0.30	$\mathbf{88.00 \pm 0.21}$	87.93 ± 0.18

datasets of CIFAR-10 Krizhevsky et al. (2009), CIFAR-100 Krizhevsky et al. (2009), and Oxford 102 Flowers Nilsback & Zisserman (2008). We used the pre-training weights from the `torchvision` Francisco Massa (2021), SDG optimizer, $\nu = 1 \times 10^{-2}$ with 0.05 warmup ratio and $b = 256$. From Table 2, there is still no obvious difference in their final accuracy. Thus, we continue to analyze the changes in loss of the three methods during training, while supplementing the training experiments from scratch.

Intermediate Metrics Analysis. As shown in Figures 7a-7c, although WPipe, PipeDream-2BW, and data parallelism have similar final loss and accuracy, the curve of WPipe is closer to data parallelism. Among them, the loss of data parallelism drops the fastest, and its accuracy rises the fastest, and WPipe is second only to data parallelism, which benefits from the fact that the weight update delay of WPipe is reduced by half, compared to PipeDream-2BW. For more loss curves and accuracy curves, please refer to the appendix.

(a) QQP:BERT$_{LARGE}$.   (b) MNLI:BERT$_{LARGE}$.   (c) Cifar10:ResNeXt50.

Figure 7: Part of the training loss from Table 2 and the accuracy when training ResNeXt50 from scratch with WPipe, PipeDream-2BW, and Data Parallelism (SGD with a fixed learning rate of 0.01).

4.2 THROUGHPUT

In this section, we measure the throughputs of WPipe through training the large-scale DNN models on Env-1 and Env-2 and compare them with other pipeline systems. The main factors that affect throughput are batch size (B), the ratio of model parallelism to data parallelism ($D : W$), and the possibility to recompute (S_a) as presented below:

$$T = \max(T_{s \in S_a \times S_{D:W} \times S_M}), B = b * M * W, M >= D, S_a = \{True, False\},$$
$$S_{D:W} = \{H(D : W) | D * W = N_{GPU}\}, S_M = \{D, D + 1, ...\} \tag{3}$$

where T is the optimal result in an optimization space $S_a \times S_{D:W} \times S_M$. $H(D : W)$ represents all isomers in the same $D : W$. S_M represents gradient accumulation period. With regards to the

optimal solution of T, the study in Narayanan et al. (2021) gives a workable solution, the paper does not do further research. Note that since B directly affects the accuracy of the model, it is often a given value.

4.2.1 COMPARISON WITH PIPELINED APPROACHES

As shown in Figure 8, throughput experiments are carried out through training different layers of BERT and ResNeXt models on the Env-1 and Env-2. For more throughput experiment data, please refer to the appendix. In general, the communication overhead of data parallelism is larger for BERT, and of model parallelism is larger for ResNeXt.

Comparison to PipeDream-2BW. In general, the suitable batch size is between 2^9 and 2^{11}. If it is too large or too small, it is not conducive to the convergence of the model. However, in most cases, when training large models, some methods cannot reach this batch size, as shown in Figure 8a. When in this range, as shown in Figure 8c, when $batch = 2^9$, WPipe is 1.4 times faster than PipeDream-2BW for Bert768 with 5.5 billion parameters. Compared to 2BW, WPipe not only reduces the cost of switching between weighted versions by half, but also has a larger solution space when the batch is larger. As shown in Figure 8d, when $batch = 2^9$, WPipe can run in the configuration of $D : W = 4 : 16$ in Env-2, and 2BW due to memory limitations, the model-parallel depth is at least 8, that is, $D >= 8$, so in this case, the throughput of WPipe is higher (for convolutional networks, in general, C_a is larger and C_{DP} is smaller, so $D : W$ needs to be smaller to improve throughput). From Figures 8b and 8d, it can be concluded that after communication optimization, even on a convolutional network with a larger C_a, WPipe has a throughput not lower than PiprDream-2BW.

Comparison to GPipe. For GPipe, its biggest problem is that there are idle time blocks on its execution timeline. In addition, its forward activations cannot be released in time. These factors directly or indirectly affect its throughput. Compared to GPipe, from Figure 8a- 8d, WPipe is $2.1\times$ faster for Bert192 and $2.2\times$ faster for ResNeXt302.

Comparison to PipeDream. Due to poor memory efficiency, the larger models cannot be trained using PipeDream, such as Bert384 and Bert768. Practice shows that for ResNeXt200, ResNeXt302, ResNeXt500, and ResNeXt800, PipeDream cannot automatically split them. According to existing data, WPipe is $7.1\times$ faster for Bert192.

(a) Bert192(8V100s). (b) ResNeXt302(8V100s). (c) Bert768(64V100s).

(d) ResNeXt800(64V100s). (e) Bert384(16:4, 64V100s). (f) ResNeXt500(64V100s).

Figure 8: Optimal throughput for different batches in the Env-1 and Env-2. Where $S_{M:N} = \{2 : 4, 4 : 2, 8 : 1\}$ in Env-1, $S_{M:N} = \{4 : 16, 8 : 8, 16 : 4, 32 : 2, 64 : 1\}$ in Env-2. 8e-8f show the throughput changes with different configurations.

4.2.2 COMMUNICATION OPTIMIZATION ANALYSIS

Recomputation. The activation recomputation can greatly reduce memory footprint and expand mini-batch size for pipeline systems. As shown in Figure 8e, PipeDream-2BW can expand the maximum mini-batch by 16 times, and WPipe can even expand by 44 times. WPipe has a more obvious memory advantage with activation recomputation. Although the batch size is not as large as possible, usually when training large models, the batch size must be within a certain range to have better convergence. In many cases, due to memory limitations, the effective range of the batch size cannot be reached. At this time the advantage of WPipe is crucial.

Ratio between Model and Data parallelism. As shown in Figure 8f, as $M : N$ decreases, the corresponding throughput increases for ResNeXt500. This happens because the communication overhead of data parallelism is smaller than that of model parallelism in the convolutional network. In this case, $M : N$ can be adjusted more widely, which is more conducive to improving throughput, e.g. $batch = 2^{11}$ in Figure 8f.

Table 3: The impact of network communication on throughput.

Env-2(4:16)	ResNeXt500
WPipe-R(A)	607.8/3328
WPipe-R(B)	497.3/3328

Heterogeneous Network Settings. We change the communication placement of model parallelism and data parallelism in the same $M : N$ to achieve higher throughput. A means that data-parallel communication takes place between machines and model-parallel communication takes place inside machines, while B is the opposite. As shown in Table 3, in case A, the throughput of WPipe is higher, because the model-parallel communication is the bottleneck for ResNeXt. Compared with the inter-machine, the bandwidth inside the machine is higher and the communication speed is faster. The model-parallel communication bottleneck has been better alleviated. Therefore, the throughput of A is higher.

4.3 MEMORY OPTIMIZATION ANALYSIS

In the throughput experiment, WPipe can execute on a larger batch, which also reflects the advantage of the lower memory footprint of WPipe. Here, we conduct a more detailed analysis: (1) The results of experiments show that the memory footprint of various pipeline-parallel methods is significantly reduced with activations recomputation, especially for WPipe. As shown in Figure 9, WPipe reduces the memory footprint by 65% for Bert96 on the per-GPU micro-batch of 64, and 56% for RestNeXt200 on the per-GPU micro-batch of 32. They are 47% and 29% respectively for PipeDream-2BW; (2) with the increase of batch size, the effect of recomputation on WPipe-R is more significant. From Figure 9, for Bert96, WPipe-R is reduced by -14% compared to GPipe-R on the per-GPU micro-batch of 8 (because GPipe has no weight buffer,

Figure 9: The Bert96 and ResNeXt200 memory footprint vary with batch size. We set $M : N$ as $8 : 1$ for Bert96 and $M : N$ as $2 : 4$ for ResNeXt200, which is the fastest configuration. We measured the average maximum memory footprint per GPU.

and its initial memory footprint is lower), and on the per-GPU micro-batch of 64, it increases to 28%. Compared to PipeDream-2BW-R, under the same conditions, WPipe-R increases from 21% to 36%.

5 CONCLUSIONS

In this work, we proposed and implemented WPipe, a system for group-based interleaved pipeline-parallel training. Compared to state-of-the-art approach, PipeDream-2BW, it achieves better memory efficiency, higher throughput, and fresher weight updates through the double-grouped weight updates. Specifically, (1) throughput: WPipe achieves $1.4\times$ acceleration; (2) memory footprint: WPipe-R reduces the memory footprint by 36%; and (3) convergence: although WPipe and PipeDream-2BW have similar final accuracy when training, WPipe has a weight update semantics closer to data parallelism.

REFERENCES

Nvlink. URL `https://www.nvidia.com/en-us/data-center/nvlink/`.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Chi-Chung Chen, Chia-Lin Yang, and Hsiang-Yun Cheng. Efficient and robust parallel dnn training through model parallelism on multi-gpu platform. *arXiv preprint arXiv:1809.02839*, 2018.

Tianqi Chen, Bing Xu, Chiyuan Zhang, and Carlos Guestrin. Training deep nets with sublinear memory cost. *arXiv preprint arXiv:1604.06174*, 2016.

Trishul Chilimbi, Yutaka Suzue, Johnson Apacible, and Karthik Kalyanaraman. Project adam: Building an efficient and scalable deep learning training system. In *11th {USENIX} Symposium on Operating Systems Design and Implementation ({OSDI} 14)*, pp. 571–582, 2014.

Thor Johnsen. Christian Sarofeen. Nvidia/apex. `https://github.com/NVIDIA/apex`, 2021.

Jeffrey Dean, Greg S Corrado, Rajat Monga, Kai Chen, Matthieu Devin, Quoc V Le, Mark Z Mao, Marc'Aurelio Ranzato, Andrew Senior, Paul Tucker, et al. Large scale distributed deep networks. 2012.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Soumith Chintala. Edward Z. Yang. pytorch/pytorch. `https://github.com/pytorch/pytorch`, 2021.

NicolasHug. Francisco Massa. pytorch/vision. `https://github.com/pytorch/vision`, 2021.

Aaron Harlap, Deepak Narayanan, Amar Phanishayee, Vivek Seshadri, Nikhil Devanur, Greg Ganger, and Phil Gibbons. Pipedream: Fast and efficient pipeline parallel dnn training. *arXiv preprint arXiv:1806.03377*, 2018.

Yanping Huang, Youlong Cheng, Ankur Bapna, Orhan Firat, Dehao Chen, Mia Chen, HyoukJoong Lee, Jiquan Ngiam, Quoc V Le, Yonghui Wu, et al. Gpipe: Efficient training of giant neural networks using pipeline parallelism. In *Advances in neural information processing systems*, pp. 103–112, 2019.

Paras Jain, Ajay Jain, Aniruddha Nrusimha, Amir Gholami, Pieter Abbeel, Kurt Keutzer, Ion Stoica, and Joseph E Gonzalez. Checkmate: Breaking the memory wall with optimal tensor rematerialization. *arXiv preprint arXiv:1910.02653*, 2019.

Zhihao Jia, Matei Zaharia, and Alex Aiken. Beyond data and model parallelism for deep neural networks. *arXiv preprint arXiv:1807.05358*, 2018.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations. *arXiv preprint arXiv:1909.11942*, 2019.

Junyang Lin, Rui Men, An Yang, Chang Zhou, Ming Ding, Yichang Zhang, Peng Wang, Ang Wang, Le Jiang, Xianyan Jia, et al. M6: A chinese multimodal pretrainer. *arXiv preprint arXiv:2103.00823*, 2021.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

Deepak Narayanan, Amar Phanishayee, Kaiyu Shi, Xie Chen, and Matei Zaharia. Memory-efficient pipeline-parallel dnn training. In *International Conference on Machine Learning*, pp. 7937–7947. PMLR, 2021.

M-E. Nilsback and A. Zisserman. Automated flower classification over a large number of classes. In *Proceedings of the Indian Conference on Computer Vision, Graphics and Image Processing*, Dec 2008.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *arXiv preprint arXiv:1910.10683*, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*, 2018.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 38–45, Online, October 2020. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/2020.emnlp-demos.6.

Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1492–1500, 2017.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Ruslan Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. *arXiv preprint arXiv:1906.08237*, 2019.

A APPENDIX

A.1 OTHER EXPERIMENTAL DATA OF CONVERGENCE.

Figures 10a-10h are the training loss of the remaining part of the experiment in Table 2. Figure 10i shows the F1 of BERT$_{BASE}$ training from scratch. It can be seen that WPipe and data parallelism can converge normally, but PipeDream-2BW does not.

(a) QQP:BERT$_{BASE}$. (b) MNLI:BERT$_{BASE}$. (c) Flowers102:ResNeXt50.

(d) Flowers102:ResNeXt101. (e) Cifar10:ResNeXt50. (f) Cifar10:ResNeXt101.

(g) Cifar100:ResNeXt50. (h) Cifar100:ResNeXt101. (i) QQP:BERT$_{BASE}$.

Figure 10: The remaining part of the training loss from Table2 and the F1 when training BERT$_{BASE}$ from scratch with WPipe, PipeDream-2BW, and DataParallel (Adam with a fixed learning rate of 5×10^{-6}).

A.2 THROUGHPUT

As shown in Figure 11a-11d, we continue to train Bert96 and ResNeXt200 on a single machine with WPipe, PipeDream-2BW, PipeDream, and GPipe, and train Bert384 and ResNeXt500 on multiple machines with WPipe and PipeDream-2BW. The overall conclusion is the same as the above. WPipe has a more obvious acceleration effect on Transformer series networks (Bert, GDP, etc.), but has a slight acceleration on convolutional networks, compared to PipeDream-2BW.

A.3 COMMUNICATION COMPRESSION

In this section, we use a specific example to analyze the effectiveness of the model-parallel communication compression. The main purpose of optimizing model-parallel communication is to reduce the proportion of model-parallel communication overhead in the overall training process. When this ratio

(a) Bert96(8V100s).

(b) ResNeXt200(8V100s).

(c) Bert384(64V100s).

(d) ResNeXt500(64V100s).

(e) ResNeXt800(4:16, 64V100s).

(f) Bert768(4:16, 64V100s).

Figure 11: Optimal throughput for different batches in the Env-1 and Env-2. Where $S_{M:N} = \{2 : 4, 4 : 2, 8 : 1\}$ in Env-1, $S_{M:N} = \{4 : 16, 8 : 8, 16 : 4, 32 : 2, 64 : 1\}$ in Env-2. Figures 11e-11f show the effect of compressed model-parallel communication on different models.

is less than a certain value, changes in model-parallel communication overhead will hardly affect the overall training time.

Communication Compression. With reference to the automatic mixed precision algorithm of apex Christian Sarofeen (2021), we implemented the automatic precision compression technique for intermediate activations and gradients, which reduced the communication overhead by nearly half across the pipeline. This offsets the communication overhead introduced by further splitting model partitions. As shown in Figure 12, the sender divides the intermediate activations and gradients by appropriate $scaler$s (powers of 2), and converts them into

Figure 12: The communication process of the intermediate activations and gradients using automatic precision compression.

half-precision tensors. If the conversion succeeds, the sender will transmit the half-precision tensors together with the $scaler$s to the receiver. After receiving the data, the receiver restores their original precision by the $scaler$. If the conversion fails, the sender will transmit the full precision tensors.

Automatic Precision Compression (APC). As shown in Table 4, WPipe is $1.17\times$ faster with APC when training ResNeXt500 and the batch size equals 3328. The loss (the negative value) of accuracy, which is brought by APC, does not exceed 0.1%, as shown in Table 5. However, when the communication overhead is not large, the use of APC will not speed up, but will be slower. As shown in Figure 11f, when $batch <= 2^{11}$, C_a is small, and the acceleration benefit cannot exceed the compression

Table 4: The impact of network communication on throughput.

Env-2(4:16)	ResNeXt500
WPipe-R-APC	732.6/3328
WPipe-R-NonAPC	607.8/3328

overhead. When $batch > 2^{11}$, there is positive feedback. For convolutional networks, C_a is large, and APC has always had a positive effect, but the effect is only obvious when the batch size is large enough, as shown in Figure 11e. In summary, when the batch is large, we use communication compression technique to have a positive benefit, but in many cases we do not need to use such a

large batch size to train the model, so in most cases, model-parallel communication will not be a bottleneck.

Table 5: The accuracy difference between using APC and not using APC with the same hyperparameters. We set $\nu = 8 \times 10^{-5}$, $b = 32 \times 8$, $ws = 200$, $epoch = 1$ for $\text{BERT}_{\text{BASE}}$ and $\nu = 4 \times 10^{-5}$, $b = 16 \times 8$, $ws = 100$, $epoch = 1$ for $\text{BERT}_{\text{LARGE}}$ and $\nu = 0.01$, $b = 32 \times 8$, $wr = 0.05$ for ResNeXt50_32x4d and ResNeXt101_32x8d.

	$\text{BERT}_{\text{BASE}}$	$\text{BERT}_{\text{LARGE}}$
∇ F1	-0.0003 ± 0.0011	0.0035 ± 0.0127
	RESNEXT50	RESNEXT101
∇ ACC	-0.0008 ± 0.0014	0.0012 ± 0.0012