Reinforcement Learning in Newcomblike Environments

Abstract

Newcomblike decision problems have been studied extensively in the decision theory literature, but they have so far been largely absent in the reinforcement learning literature. In this paper we study value-based reinforcement learning algorithms in the Newcomblike setting, and answer some of the fundamental theoretical questions about the behaviour of such algorithms in these environments. We show that a value-based reinforcement learning agent cannot converge to a policy that is not *ratifiable*. This gives us a powerful tool for reasoning about the limit behaviour of agents – for example, it lets us show that there are Newcomblike environments in which a reinforcement learning agent cannot converge to any optimal policy. We show that a ratifiable policy always exists in our setting, but that there are cases in which a reinforcement learning agent normally cannot converge to it (and hence cannot converge at all). We also prove several results about the possible limit behaviours of agents in cases where they do not converge to any policy.

1 Introduction

In this paper, we study decision scenarios in which outcomes depend not only on the choices made and physically implemented, but also depend directly on the agent's policy. As an example, consider an autonomous vehicle (AV) whose goal it is to arrive at target destinations quickly while minimising the probability of collisions. In practice, AVs are careful drivers. It is easy to imagine an experiment (or learning process) that might support careful driving: on each day, let the AV decide at random between a careful and a more aggressive style of driving; other drivers on the road are unaware of today's chosen driving style and therefore behave the same around the AV on both types of days. Presumably the decrease in accidents on careful days outweighs the increase in travel time.

However, imagine now that a type of AV was widely deployed (as is already the case in some places). Then many of the drivers with whom the AVs interact on the road would know a lot about how these AVs behave (e.g., from reading about AVs, or from having interacted with other AVs of the same type in the past). In particular, if the other drivers know that the AVs rarely take risks, they might (whether rationally or irrationally) cut them off more, not give them right of way, etc. relative to the above experiment. Indeed, this phenomenon – human drivers bullying timid AVs – has been reported in the real world (Condliffe, 2016; Liu et al., 2020; cf. Cooper et al., 2019). As a result, the travel times of an AV are much longer if it always follows (and is known to follow) a careful driving policy, relative to the above experiment. Moreover, some of the safety benefits of careful *choices* disappear if the AV adopts a careful *policy*.

To comfortably model situations such as this one, we introduce Newcomblike decision processes (NDPs). The name derives from Newcomb's problem (Nozick, 1969) and similar problems that have been studied in the decision-theoretic literature. NDPs are a generalisation of Markov decision

processes wherein the transition probabilities depend not only on the agent's action, but also directly on the agent's policy. Thus, for example, how aggressively other cars move depends on the timidness of the AV's policy. Similarly, we allow the reward to depend directly on the agent's policy. We describe NDPs in more detail in Sect. 1.1.

We believe that Newcomblike dynamics are commonplace when AI systems interact with other (human or artificial) agents (Cavalcanti, 2010, Sect. 5; Oesterheld, 2019, Sect. 1; Conitzer, 2019). The deployment of AVs is rife with such dynamics. Besides aggressiveness, it might matter whether a policy is simple and thus predictable to humans, for instance. Another real-world scenario is that of recommendation systems: most readers of this paper have some idea of how these systems work and make choices based on it. ("I would like to watch this cat video, but if I do, my recommendations will soon be full of them.") Thus, the success of a particular recommendation depends not only on the recommendation itself, but also on the recommendation system's policy.

We are interested in learning to play NDPs. More specifically, we study the behavior of value-based, model-free RL agents, who maintain a Q-function that assigns values to state–action pairs. We define these in more detail in Sect. 1.2. As we will see, such agents do not in general learn optimal policies in NDPs (as they do in MDPs). Nevertheless, we believe that studying them is an important first step in developing practical learning algorithms for NDPs due to the combination of the following points. A) For illustrative purposes, the examples we discuss throughout this paper are simple and emphasise the dependence of the environment on the policy. However, we think that most real-world scenarios are only partially Newcomblike. For example, most of the AV's environment changes only in response to an AV's actions and does not directly depend on the AV's policy. B) Value-based reinforcement learning algorithms are very well developed. In contrast, we would have to develop specialised learning algorithms for general NDPs from scratch. C) As our results will show, in some situations and when set up correctly (e.g., in terms of learning rates) value-based learning converges to optimal policies, or at least to reasonable policies, even under Newcomblike dynamics. For example, in a game of rock-paper-scissors against an opponent who knows the agent's policy, some value-based learning agents learn the optimal policy of mixing uniformly. In light of A–C, we think that the most realistic paths to developing learning algorithms for real-world scenarios with Newcomblike dynamics will involve value-based RL. Specifically, one avenue toward realistic algorithms is to generally use value-based RL and to determine when Newcomblike dynamics require a different mode of learning. For that, we need to understand how value-based RL behaves in NDPs.

Contributions In Sect. 2 we demonstrate that value-based RL algorithms can only converge to a policy that is *ratifiable* – that is, to a policy π for which all actions taken by π have optimal expected reward when following π. In Sect. 3, we discuss the convergence properties of agents in Newcomblike situations, and show that there are cases where value-based agents must fail to converge. The action frequencies might converge, even when the policies do not. In Sect. 4, we establish some conditions on any action frequency that an agent could converge to. We also show that there are decision problems and agents where even the action frequencies do not converge.

1.1 Newcomblike Decision Processes

A *Newcomblike decision process (NDP)* is a tuple $\langle S, A, T, R, \gamma \rangle$ where S is a finite set of *states*, A is a finite set of *actions*, $T : S \times A \times (S \rightsquigarrow A) \rightsquigarrow S$ is a nondeterministic *transition function*, $R : S \times A \times S \times (S \rightsquigarrow A) \rightsquigarrow \mathbb{R}$ is a nondeterministic *reward function*, which we assume to be bounded; and $\gamma \in [0, 1)$ is a *discount factor*.

A policy $\pi : S \rightsquigarrow A$ is a function that nondeterministically maps states to actions. We use $\pi(a \mid s)$ to denote the probability of taking action a in state s while following the policy π. T and R are functions from states, actions, and policies. In other words, they allow the outcome of a decision to depend on the distributions from which the agent draws its actions, rather than just the state and the action that is in fact taken. Also note that $T(s, a, \pi)$ and $R(s, a, s', \pi)$ are defined even if $\pi(a \mid s) = 0$. We say that an NDP is a *bandit NDP* if it has only one state. We will sometimes use $R(s, a, \pi)$ as a shorthand for $R(s, a, T(s, a, \pi), \pi)$, and we will sometimes omit the state from T, R, and π for bandit NDPs. Moreover, we normally let $\gamma = 0$ for bandit NDPs.

This framework makes it easier to formalise Newcomblike problems. For example, a version of Newcomb's Problem can be formalised as the following bandit NDP: $S = \{s\}$, $A = \{a_1, a_2\}$,

$$R(a_1, \pi) = \left\{ \begin{array}{ll} 0 & \text{w.p.} \quad \pi(a_2) \\ 10 & \text{w.p.} \quad \pi(a_1) \end{array} \right. \text{ and } R(a_2, \pi) = \left\{ \begin{array}{ll} 5 & \text{w.p.} \quad \pi(a_2) \\ 15 & \text{w.p.} \quad \pi(a_1) \end{array} \right. .$$

The key feature of this NDP is that regardless of the policy a_2 ("two-boxing") yields a higher reward than a_1 ("one-boxing"). But the expected reward of a policy increases in $\pi(a_1)$ s.t. the optimal policy is to always play a_1.[1] We can view Newcomb's problem as a simple version of the AV dynamic described in the introduction, where a_2 is a driving action that allows other drivers to cut the AV off at no risk.

We say that an NDP is *continuous* if T and R are continuous in the policy. In this paper we work mainly with continuous NDPs. This is in part because it is technically convenient, and in part because we believe that continuity is satisfied in many realistic cases.[2]

1.2 Reinforcement Learning Agents

We consider value-based reinforcement learning agents. Such agents have two main components; a *Q-function* $S \times A \to \mathbb{R}$ that predicts the expected future discounted reward conditional on taking a particular action in a particular state, and a *bandit algorithm* that is used to select actions in each state based on the Q-function. Given a policy π, we use $q_\pi(a \mid s)$ to denote the expected future discounted reward conditional on taking action a in state s while following the policy π (and conditional on all subsequent actions being chosen by π). A model-free agent will update Q over time to make it converge to q_π when following π. If Q is represented as a lookup table, the agent is said to be *tabular*. If the state space is large, it is common to instead approximate q_π (with e.g. a neural network). For simplicity, we focus mostly on tabular agents. However, some of our results (specifically, Theorems 2 and 5) only assume that Q converges to q_π (for some q_π) and therefore apply immediately to non-tabular agents, as long as it is ensured that the function approximator for q_π converges to the same q_π.

The Q-values can be updated in different ways. One method is to use the update rule

$$Q_{t+1}(a_t \mid s_t) \leftarrow (1 - \alpha_t(s_t, a_t)) \, Q_t(a_t \mid s_t) + \alpha_t(s_t, a_t)(r_t + \gamma \max_a Q_t(a \mid s_{t+1})),$$

where a_t is the action taken at time t, s_t is the state visited at time t, r_t is the reward obtained at time t, and $\alpha_t(s, a)$ is a learning rate. This update rule is known as *Q-learning* (Watkins, 1986). Another widely used update rule is

$$Q_{t+2}(a_t \mid s_t) \leftarrow (1 - \alpha_t(s_t, a_t)) \, Q_{t+1}(a_t \mid s_t) + \alpha_t(s_t, a_t)(r_t + \gamma Q_{t+1}(a_{t+1} \mid s_{t+1})).$$

This update rule is known as *SARSA* (Rummery and Niranjan, 1994). Yet another common update rule is *Expected SARSA*, which replaces $Q_t(a_{t+1} \mid s_{t+1})$ with $\mathbb{E}_{a \sim \pi}[Q_t(a \mid s_{t+1})]$ in the SARSA update rule (van Seijen et al., 2009). For the purposes of this paper it will not matter significantly how the Q-values are computed, as long as it is the case that if an agent converges to a policy π in some NDP and explores infinitely often then Q converges to q_π. We will later see that this is the case for Q-learning, SARSA, and Expected SARSA in continuous NDPs.

There are also several different bandit algorithms. Two types of agents that are widely used in practice and that we will refer to throughout the paper are *softmax agents* and ϵ-*Greedy agents*. The policy of a softmax agent with a sequence of temperatures $\beta_t \in \mathbb{R}_+$ is given by:

$$\pi_t(a \mid s) = \frac{\exp(Q_t(a \mid s)/\beta_t)}{\sum_{a' \in A} \exp(Q_t(a' \mid s)/\beta_t)}.$$

---

[1]In most versions of Newcomb's Problem, the predictor directly predicts the agent's action with some fixed accuracy, and the agent is unable to randomise in a way that is unpredictable to the environment. This version of the problem can be modeled as a regular MDP. However, we believe that our version is more realistic in the context of AI. After all, AIs can at least act pseudo-randomly, while the distribution according to which they choose is predictable if, e.g., their source code is known.

[2]For example, even if the environment has direct access to the source code of the agent, it may in general not be feasible to extract the exact action probabilities from the code. However, it is always possible to estimate the action probabilities by sampling. If this is done then T and R will depend continuously on the policy.

124 Unless otherwise stated we assume that $\beta_t \to 0$. The policy of an ϵ-Greedy agent with a sequence of
125 exploration probabilities $\epsilon_t \in [0, 1]$ is given by:

$$\pi_t(a \mid s) = \begin{cases} 1 - \epsilon_t & \text{if } a = \arg\max_{a'} Q_t(a' \mid s) \\ \epsilon_t/(|A| - 1) & \text{otherwise.} \end{cases}$$

126 Unless otherwise stated we assume that $\epsilon_t \to 0$. We assume that ϵ-Greedy breaks ties for argmax, so
127 that there is always some $a \in A$ such that $\pi(a \mid s) = 1 - \epsilon_t$. We say that an agent is *greedy in the*
128 *limit* if the probability that the agent takes an action that maximises Q converges to 1, and we say
129 that it *explores infinitely often* if it takes every action in every state infinitely many times.

1.3 Some Initial Observations

131 We here make three simple observations about NDPs that we will use to prove and understand the
132 results throughout this paper. First, a continuous NDP always has a policy π that maximises the
133 expected discounted reward $\mathbb{E}[R \mid \pi]$, since $\mathbb{E}[R \mid \pi]$ exists and is continuous in π, and since the set
134 of possible policies is a compact set. Also note that an NDP in which T or R is discontinuous may
135 not have any such policy.

136 Second, whereas all MDPs have a deterministic optimal policy, in some NDPs all optimal policies
137 randomise. To see this, consider a version of decision problem known as Death in Damascus (Gibbard
138 and Harper, 1976), which we formalise as the bandit NDP $S = \{s\}$, $A = \{a_{\text{Damascus}}, a_{\text{Aleppo}}\}$, and

$$R(a_{\text{Damascus}}, \pi) = \begin{cases} 0 & \text{w.p.} & \pi(a_{\text{Damascus}}) \\ 10 & \text{w.p.} & \pi(a_{\text{Aleppo}}) \end{cases} \quad \text{and } R(a_{\text{Aleppo}}, \pi) = \begin{cases} 10 & \text{w.p.} & \pi(a_{\text{Damascus}}) \\ 0 & \text{w.p.} & \pi(a_{\text{Aleppo}}) \end{cases}.$$

139 In this NDP, randomizing uniformly between a_{Damascus} and a_{Aleppo} is the unique optimal policy and in
140 particular outperforms both deterministic policies.

141 Note also that the Bellman optimality equation does not hold for NDPs. Even in Newcomb's Problem,
142 as described above, Bellman's optimality equation is not satisfied by the optimal policy. This is
143 because the optimal policy in Newcomb's Problem does not select optimal actions.

2 Ratifiability

145 If an agent in the limit only takes the actions with the highest Q-values and it converges to some
146 policy π_∞, then it is clear that all actions in the support of π_∞ must have equal expected utility given
147 π_∞. Otherwise, the Q-values would eventually reflect the differences in expected utility and the
148 agent would move away from π_∞. Similarly, if the algorithm explores sufficiently often, the actions
149 that are taken with limit probability 0 cannot be better given π_∞ than those taken by π_∞. After all, if
150 they were better, the agent would have eventually figured this out and assigned them large probability.

151 This condition on π_∞ resembles a well-known doctrine in philosophical decision theory: ratifica-
152 tionism (see Weirich, 2016, Sect. 3.6, for an overview). One form of ratificationism is based on a
153 distinction between a *decision* – what the agent chooses – and the *act* that is selected by that decision.
154 Very roughly, ratificationism then states that a decision is rational only if the acts it selects have the
155 highest expected utility given the decision. Concepts of causality are often invoked to formalise the
156 difference between the decision, the act, and their respective consequences. Our setup, however, has
157 such a differentiation built in: we will view the policy as the "decision" and the action sampled from
158 it as the "act".

2.1 Strong Ratifiability

160 As hinted earlier, slightly different versions of the concept of ratifiability are relevant depending on
161 how much exploration a learning algorithm guarantees. We start with the stronger version, which
162 more closely resembles what decision theorists mean when they speak about ratifiability.

163 **Definition 1.** *Let $M \subseteq S$ be a set of states. A policy π is strongly ratifiable on M if* $\text{supp}(\pi(\cdot \mid$
164 $s)) \subseteq \arg\max_{a \in A} q_\pi(a \mid s)$ *for all $s \in M$.*

165 In Newcomb's Problem the only strongly ratifiable policy is to play a_2 with probability 1. In Death in
166 Damascus, only the optimal policy (mixing uniformly) is strongly ratifiable. There can also be several

strongly ratifiable policies. For example, if you play the Coordination Game of Table 1 against an opponent who samples his action from the same policy as you then there are three strongly ratifiable policies; to select action a with probability 1, to select action b with probability 1, and to select a with probability $1/3$ and b with probability $2/3$.

Theorem 2. *Let $\mathcal{A}$ be a model-free reinforcement learning agent, and let π_t and Q_t be $\mathcal{A}$'s policy and Q-function at time t. Let $\mathcal{A}$ satisfy the following in a given NDP:*

- *$\mathcal{A}$ is greedy in the limit, i.e. for all $\delta > 0$, $\mathbb{P}\left(Q_t(\pi_t(s)) \leq \max_a Q_t(a \mid s) - \delta\right) \to 0$ as $t \to \infty$.*
- *$\mathcal{A}$'s Q-values are accurate in the limit, i.e. if $\pi_t \to \pi_\infty$ as $t \to \infty$, then $Q_t \to q_{\pi_\infty}$ as $t \to \infty$.*

Then if $\mathcal{A}$'s policy converges to π_∞ then π_∞ is strongly ratifiable on the states that are visited infinitely many times.

In Appendix A we show that the Q-values of a tabular agent are accurate in the limit in any continuous NDP if the agent updates its Q-values with SARSA, Expected SARSA, or Q-learning, given that the agent explores infinitely often and uses appropriate learning rates. This means that such an agent can only converge to a (strongly) ratifiable policy, if it converges to any policy at all. More-over, since we would expect most well-designed agents to have accurate Q-values in the limit, this result should apply very broadly. Using Kakutani's fixed-point theorem, it can be shown that every continuous NDP has a ratifiable policy.

	a	b
a	2,2	0,0
b	0,0	1,1

Table 1: The Coordination Game

Theorem 3. *Every continuous NDP has a strongly ratifiable policy.*

Of course, the fact that a ratifiable policy always exists does not necessarily mean that a reinforcement learning agent must converge to it – we will consider the question of whether or not this is the case in Sect. 3. It is also worth noting that a discontinuous NDP may not have any strongly ratifiable policy.

It is a topic of ongoing discussion among philosophical decision theorists whether (strong) ratifiability should be considered a normative principle of rationality, see Weirich (2016, Sect. 3.6) for details. In general, the policy π that maximises $\mathbb{E}[R \mid \pi]$ may or may not be ratifiable, as shown by Death in Damascus and Newcomb's problem, respectively.

There is a correspondence between ratificationism and many game-theoretic concepts. For example, if you are playing a zero-sum game against an opponent who can see your policy and plays some distribution over best responses to it then π can only be ratifiable if it is a maximin strategy. To give another example, if you are playing a symmetric game against an opponent who follows the same policy as you then π is ratifiable if and only if (π, π) is a Nash equilibrium. Joyce and Gibbard (1998, Sect. 5) discuss the relation in more detail.

2.2 Weak Ratifiability

We have seen that with sufficient exploration, the limit policy π_∞ (if it exists) must be strongly ratifiable. We will now show that even without infinite exploration, π_∞ must still satisfy a weaker notion of ratifiability.

Definition 4. *Let $M \subseteq S$ be a set of states. A policy π is weakly ratifiable on M if $q_\pi(a \mid s)$ is constant across $a \in \mathrm{supp}(\pi(s))$ for all $s \in M$.*

What makes this a weak version of ratifiability is that it does not put any requirements on the expected utility of actions that π_∞ does not take, it merely says that all actions that π_∞ takes with positive probability must have the same (actual) q-value. As a special case, this means that all deterministic policies are weakly ratifiable. This includes one-boxing in Newcomb's problem. Nonetheless, there are NDPs in which the optimal policy is not even weakly ratifiable. For example, consider a bandit NDP with actions a_1, a_2, where $R(a_1, \pi) = -100(\pi(a_1) - 1/2)^2 + 1$ and $R(a_2, \pi) = -100(\pi(a_1) - 1/2)^2$. The optimal policy mixes close to uniformly ($\pi(a_1) = 101/200$), but this is not weakly ratifiable, because $R(a_1, \pi) > R(a_2, \pi)$.

Theorem 5. *Same conditions as Theorem 2, but where $\mathcal{A}$'s Q-values are only required to be accurate in the limit for state-action pairs that $\mathcal{A}$ visits infinitely many times. Then π_∞ is weakly ratifiable on the set of states that are visited infinitely many times.*

3 Non-Convergence of Policies

We have shown that most reinforcement learning algorithms can only converge to (strongly) ratifiable policies. We now consider the question of whether they always converge to a policy at all. We find that this is not the case.

3.1 Theoretical Results

From Theorem 2, it follows that in, e.g., Death in Damascus an ϵ-Greedy agent who explores infinitely often cannot converge to any policy. After all, the only strongly ratifiable policy (and thus limit policy) is to mix uniformly and an ϵ-Greedy agent never mixes uniformly.

Perhaps more surprisingly, there are also NDPs in which a (slow-cooling) softmax agent cannot converge to any policy. As an example, consider a bandit NDP with three actions a_1, a_2, a_3, and where the rewards $R(a_i, \pi)$ have expectations

$$\pi(a_{i+1}) + 4{\cdot}13^3{\cdot}\pi(a_i)\mathbb{1}\left[\forall j{:}\pi(a_j){\geq}1/4\right] \prod_j \left(\pi(a_j){-}1/4\right). \tag{1}$$

For $i = 3$, we here let $a_{i+1} = a_1$. We also require that the rewards are stochastic with a finite set of outcomes such that the empirical Q-values are never exactly equal between different actions. We call this the *Repellor Problem*. It has only one strongly ratifiable policy (mixing uniformly), but – as illustrated by Figure 1 – when the current policy mixes close to uniformly, the softmax agent learns (in expectation) to play less uniformly.

Theorem 6. *Let $\mathcal{A}$ be an agent that plays the Repellor Problem, explores infinitely often, and updates its Q-values with a learning rate α_t that is constant across actions, and let π_t and Q_t be $\mathcal{A}$'s policy and Q-function at time t. Assume also that for $j \neq i$, if $\pi_t(a_i)$, $\pi_t(a_j)$ both converge to positive values, then*

$$\frac{\pi_t(a_i) - \pi_t(a_j)}{Q_t(a_i) - Q_t(a_j)} \underset{a.s.}{\to} \infty \tag{2}$$

as $t \to \infty$. Then π_t almost surely does not converge.

Line 2 is satisfied, for example, for softmax agents with β_t converging to 0. Recall also that e.g. Q-learning and SARSA are equivalent for bandit NDPs (if $\gamma = 0$).

3.2 Empirical Results

Empirically, softmax agents converge (to strongly ratifiable policies) in many NDPs, provided that the temperature decreases sufficiently slowly. To illustrate this we will use *Aymmetric Death in Damascus*, a version of Death in Damascus wherein the rewards of a_{Aleppo} are changed to be 5 (instead of 0) with probability $\pi(a_{\text{Aleppo}})$ and (as before) 10 with the remaining probability. This NDP has only one (strongly) ratifiable policy, namely to go to Aleppo with probability $2/3$ and Damascus with probability $1/3$. This is also the optimal policy. We use this asymmetric version to make it easier to distinguish between convergence to the ratifiable policy and the default of uniform mixing at high temperatures. Figure 2 shows the probability of converging to this policy with a softmax agent and a plot of the policy on one run. We can see that this agent reliably converges provided that the cooling is sufficiently slow.

Figure 1: The triangle shows the space of possible policies in the Repellor Problem, parameterised by the probability they assign to each of the three actions. Plotted against this space is the expected direction in which a softmax agent would change its policy if playing a particular policy.

However, there are also fairly simple games in which it seems like softmax agents cannot converge. Consider *Loss-Averse Rock-Paper-Scissors* (LARPS), the problem of playing Rock-Paper-Scissors against an opponent that selects each action with the same probability as you, and where you assign utility 1 to a win, 0 to a draw, and -10 to a loss. We conjecture that slow-cooling softmax agents do

Figure 2: The left figure plots the probability of Softmax converging in Asymmetric Death in Damascus given $\beta_n = n^{-\alpha}$ against α. More accurately it is a plot of the fraction of runs which assigned a Q-value of at least 5.5 to the action of going to Aleppo after 5000 iterations. These are empirical probabilities from 20,000 runs for every α that is a multiple of 0.025, and 510,000 runs for each α that is a multiple of 0.005 between 0.5 and 0.55. Notice the "kink" at $\alpha = 0.5$. Based on our experiments, this kink is not an artefact and shows up reliably in this kind of graph. The right-hand figure shows how the action probabilities evolve over time for a single run (chosen to converge to the mixed strategy) for $\alpha = 0.3$.

not converge in LARPS. We have unfortunately not been able to prove this formally, but Figure 3 presents some empirical data which corroborates the hypothesis.

4 Convergence of Action Frequencies

We have seen that there are NDPs in which some reinforcement learning algorithms cannot converge to any policy. But if they do not converge to any policy, what does their limit behaviour look like? We now examine whether these algorithms converge to taking each action with some limit *frequency*, and what sorts of frequencies they can converge to.

4.1 Possible Frequencies in the Bandit Case

In this section we establish a number of conditions that must be satisfied by any limit action frequency of a value-based agent. We consider agents that converge to deterministic policies (such as ϵ-Greedy agents), and we limit our analysis to the bandit case (with $\gamma = 0$).

Figure 3: This figure shows five runs of a softmax agent in LARPS, and plots $\pi(a_{\mathrm{rock}})$ against the total number of episodes played. The agent's Q-values are the historical mean rewards for each action, and $\beta_t = 1/\log t$.

Let $P_t^{\Sigma} \colon A \to [0, 1]$ be the frequency with which each action in A is taken in the first t steps (for some agent and some bandit NDP). Note that P_t^{Σ} is a random variable. By the law of large numbers, $P_t^{\Sigma}(a) - 1/t \sum_{i=0}^{t} \pi_i(a)$ converges to 0 almost surely as $t \to \infty$. Let π_a be the policy that takes action a with probability 1, and let $q_a = q_{\pi_a}$.

Theorem 7. *Assume that there is some sequence of random variables $(\epsilon_t \geq 0)_t$ s.t. $\epsilon_t \underset{t \to \infty \ a.s.}{\to} 0$ and for all $t \in \mathbb{N}$ it is*

$$\sum_{a^* \in \arg\max_a Q_t(a)} \pi_t(a^*) \geq 1 - \epsilon_t. \tag{3}$$

Let $P_t^{\Sigma} \to p^{\Sigma}$ with positive probability as $t \to \infty$. Then across all actions $a \in \mathrm{supp}(p^{\Sigma})$, $q_a(a)$ is constant.

(a) This figure plots the dynamics of LARPS for an ϵ-Greedy agent. Each point represents a triplet (f_R, f_S, f_P), where f_R denotes the fraction of past time steps at which a_R was estimated to be the best action, and similarly for f_S, f_P. Plotted against this space is the expected direction in which the frequencies will change. For instance, if in the past a_R, was mostly played, then a_P will have the highest empirical Q-values and will therefore be played more in the future.

(b) This figure shows five runs of an ϵ-Greedy agent in LARPS, and plots the proportion of past episodes in which the agent played "rock" against the total number of episodes played. The agent's Q-values are the historical mean rewards for each action, and its ϵ-value is 0.01.

Figure 4

This condition is vaguely analogous to weak ratifiability, and is proven in roughly the same way as Theorem 2.

Theorem 8. *Same assumptions as Theorem 7. If $|\mathrm{supp}(p^\Sigma)| > 1$ then for all $a \in \mathrm{supp}(p^\Sigma)$ there exists $a' \in A$ s.t. $q_a(a') \geq q_a(a)$.*

This condition is an instability condition. Say that multiple actions are taken with non-zero limit frequency, and that action a has the highest Q-value at time t. Then for other actions to be played with positive limit frequency, other actions must at some point be believed to be optimal again (since the probability of exploration goes to zero). Hence they cannot all be worse when explored while mainly playing a, since a could otherwise be played forever.

Theorem 9. *Same assumptions as Theorem 7. Let U be the Q-value $q_a(a)$ which (by Theorem 7) is constant across $a \in \mathrm{supp}(p^\Sigma)$. For any $a' \in A - \mathrm{supp}(p^\Sigma)$ that is played infinitely often, let frequency 1 of the exploratory plays of a' happen when playing a policy near elements of $\{\pi_a \mid a \in \mathrm{supp}(p^\Sigma)\}$. Then either there exists $a \in \mathrm{supp}(p^\Sigma)$ such that $q_a(a') \leq U$; or $q_{a'}(a') < U$.*

This condition puts a requirement on actions a' that are played with limit frequency zero. Roughly, there must be some explanation for why a' usually has a low Q-value. One possibility is that exploration is done only finitely many times. Moreover, if the exploration mechanism is "rigged" so that a' is mostly played when playing policies outside the proximity of $\{\pi_a \mid a \in \mathrm{supp}(p^\Sigma)\}$ then the behaviour of some zero-limit-frequency policies might lead to low Q-values. If exploration of a' is spread out more naturally then all but frequency zero of that exploration will happen near elements of $\{\pi_a \mid a \in \mathrm{supp}(p^\Sigma)\}$, and so a' may not be played with positive frequency if exploring a' near some of the elements of $\{\pi_a \mid a \in \mathrm{supp}(p^\Sigma)\}$ makes a' look poor. If that is not the case then a' will periodically seem optimal, which means that it can only be played with frequency zero if it is quickly learned to be suboptimal when it is played with high probability.

4.2 When is Frequency Convergence Possible?

We believe there are NDPs in which an ϵ-Greedy agent cannot converge to any limit action frequency. Specifically, we believe that LARPS is such an example. Figure 4a shows the directions in which the frequencies of different actions evolve. The graph seems to have no attractor and hence we believe an ϵ-Greedy agent cannot converge to any limit action frequency in this NDP. We have not been able to rigorously prove this. However, experiments seem to confirm this hypothesis. Figure 4b depicts five runs of ϵ-Greedy in LARPS. We can see that the agents oscillate between different actions, and that the periods increase in length.

5 Related Work

5.1 Learning Nash Equilibria

Games relate closely to Newcomblike problems. There is a large body of existing work on learning in the game-theoretic setting. For example, "fictitious play" (due to Brown, 1951) is when some number of players play a game repeatedly, and in each round play the best response against the empirical distribution over actions taken by their opponent — this is largely analogous to using reinforcement learning. Fudenberg and Levine (1998, Chapter 2) show that fictitious play can only converge to a Nash equilibrium, and that if fictitious play enters a Nash equilibrium it will stay there for all subsequent rounds. It has also been shown that fictitious play can fail to converge (Shapley, 1964). However, there are many special cases in which convergence is guaranteed, including two-player zero-sum games (Robinson, 1951) and generic 2×2 games (Miyasawa, 1961).

5.2 Learning and Newcomblike problems

Other authors have discussed what type of behaviour various learning algorithms give rise to in Newcomblike problems. The most common setup is one in which the learner assigns values directly to policies, or more generally to that which the agent chooses. It is then usually shown that (among the policies considered) the agent will converge to taking the one with the highest (so-called evidential) expected utility (Albert and Heiner, 2001; Mayer et al., 2016; Oesterheld, 2018). This contrasts with our setup, in which the learner selects policies but assigns values to actions. Another more sophisticated setting was studied by Oesterheld (2019).

6 Discussion and Further Work

We have seen that value-based reinforcement learning algorithms can fail to converge to any policy in some NDPs, and that when they do converge, they can only converge to *ratifiable* policies. Decision theorists have discussed whether ratifiability should be considered to be a sound normative principle. Note that (as discussed in Sect. 2) the policy π that maximises expected discounted reward $\mathbb{E}[R \mid \pi]$ is not in general ratifiable. We have also examined the limit action *frequencies* that agents can converge to (even when the policies do not converge). Still, there are NDPs in which many agents cannot converge even to any such frequency. We gave some results on what limit frequencies are possible. These results are much weaker than our results on policy convergence, because the exact frequencies depend on the details of the learning algorithm. A loose connection to ratifiability can still be drawn.

Overall, established decision-theoretical ideas can be used to understand and formally describe the behaviour of "out-of-the-box" reinforcement learning agents in NDPs. However, their behaviour is not always desirable. They may fail to converge, or they might only be able to converge to suboptimal policies. Our work elucidates these possible failures. We hope that our results will be useful in developing extensions of value-based RL that can detect and correct these failures.

Throughout the paper, we have noted specific open questions related to our results. For instance, can the results in Sect. 4.1 be generalised beyond the bandit setting? There are also many topics and questions about our setting that we have not touched on at all. For instance, our experimental results indicate that convergence is often slow (considering how simple the given problems are). It might be desirable to back up this impression with theoretical results. We have only studied simple value-based model-free algorithms – the analysis could be extended to other reinforcement learning algorithms (e.g., policy-gradient or model-based algorithms). Finally, there are further ways in which we could generalise our setting. One example is to introduce partial observability and imperfect memory into the NDPs. The latter has been studied in game and decision theory (Piccione and Rubinstein, 1997; Elga, 2000), but recently – under the name *memoryless POMDP* – also in reinforcement learning (Azizzadenesheli et al., 2016; Steckelmacher et al., 2018; cf. Conitzer, 2019). What makes this especially appealing in the NDP context is that problems related to imperfect memory relate closely to Newcomblike problems (Briggs, 2010; Schwarz, 2015). It could also be interesting to more extensively study discontinuous NDPs.

References

Albert, M. and Heiner, R. A. (2001). An indirect-evolution approach to newcomb's problem. CSLE Discussion Paper, No. 2001-01.

Azizzadenesheli, K., Lazaric, A., and Anandkumar, A. (2016). Open problem: Approximate planning of pomdps in the class of memoryless policies. In *JMLR: Workshop and Conference Proceedings*, volume 49, pages 1–4.

Briggs, R. (2010). Putting a value on beauty. In *Oxford Studies in Epistemology*, volume 3, pages 3–24. Oxford University Press.

Brown, G. W. (1951). Iterative solutions of games by fictitious play. In Koopmans, T. C., editor, *Activity Analysis of Production and Allocation*, chapter XXIV, pages 371–376. John Wiley & Sons and Chapman & Hall.

Cavalcanti, E. G. (2010). Causation, decision theory, and bell's theorem: A quantum analogue of the newcomb problem. *The British Journal for the Philosophy of Science*, 61(3):569–597.

Condliffe, J. (2016). Humans will bully mild-mannered autonomous cars. *MIT Technology Review*.

Conitzer, V. (2019). Designing preferences, beliefs, and identities for artificial intelligence. In *Proceedings of the Thirty-Third AAAI Conference on Artificial Intelligence (AAAI-19) Senior Member / Blue Sky Track*.

Cooper, M., Lee, J. K., Beck, J., Fishman, J. D., Gillett, M., Papakipos, Z., Zhang, A., Ramos, J., Shah, A., and Littman, M. L. (2019). Stackelberg punishment and bully-proofing autonomous vehicles. In *Proceedings of the 11th International Conference on Social Robotics*, volume 11876 of *Lecture Notes in Computer Science*, pages 368–377. Springer, Madrid, Spain.

Elga, A. (2000). Self-locating belief and the sleeping beauty problem. *Analysis*, 60(2):143–147.

Fudenberg, D. and Levine, D. K. (1998). *The Theory of Learning in Games*. MIT Press.

Gibbard, A. and Harper, W. (1976). Counterfactuals and two kinds of expected utility. *Foundations and Applications of Decision Theory*, 1:125–162.

Hall, P. and Heyde, C. (1980). *Martingale Limit Theory and its Applications*. New York: Academic Press.

Joyce, J. M. and Gibbard, A. (1998). Causal decision theory. In *Handbook of Utility Theory, Volume 1: Principles.*, chapter 13, pages 627–666. Kluwer.

Kakutani, S. (1941). A generalization of brouwer's fixed point theorem. *Duke Math. J.*, 8(3):457–459.

Liu, P., Du, Y., Wang, L., and Ju, D. Y. (2020). Ready to bully automated vehicles on public roads? *Accident Analysis & Prevention*, 137.

Mayer, D., Feldmaier, J., and Shen, H. (2016). Reinforcement learning in conflicting environments for autonomous vehicles. In *International Workshop on Robotics in the 21st century: Challenges and Promises*.

Miyasawa, K. (1961). On the convergence of the learning process in a 2x2 non-zero-sum two-person game.

Nozick, R. (1969). Newcomb's problem and two principles of choice. In et al., N. R., editor, *Essays in Honor of Carl G. Hempel*, pages 114–146. Springer.

Oesterheld, C. (2018). Doing what has worked well in the past leads to evidential decision theory.

Oesterheld, C. (2019). Approval-directed agency and the decision theory of newcomb-like problems. *Synthese*.

Piccione, M. and Rubinstein, A. (1997). On the interpretation of decision problems with imperfect recall. *Games and Economic Behavior*, 20:3–24.

Robinson, J. (1951). An iterative method of solving a game. *Annals of Mathematics*, 54(2):296–301.

Rummery, G. and Niranjan, M. (1994). On-line q-learning using connectionist systems. Technical report, Cambridge University Engineering Department.

Schwarz, W. (2015). Lost memories and useless coins: revisiting the absentminded driver. *Synthese*, 192(9):3011–3036.

Shapley, L. S. (1964). Some topics in two-person games. In Dresher, M., Shapley, L. S., and Tucker, A. W., editors, *Advances in Game Theory*, chapter 1. Princeton University Press.

Singh, S., Jaakkola, T., Littman, M. L., and Szepesvári, C. (2000). Convergence results for single-step on-policy reinforcement-learning algorithms. *Machine Learning*, 38:287–308.

Steckelmacher, D., Roijers, D. M., Harutyunyan, A., Vrancx, P., Plisnier, H., and Nowè, A. (2018). Reinforcement learning in pomdps with memoryless options and option-observation initiation sets. In *The Thirty-Second AAAI Conference on Artificial Intelligence (AAAI-18)*.

van Seijen, H., van Hasselt, H., Whiteson, S., and Wiering, M. (2009). A theoretical and empirical analysis of expected sarsa. In *2009 IEEE Symposium on Adaptive Dynamic Programming and Reinforcement Learning*, pages 177–184.

Watkins, C. (1986). *Learning from delayed rewards*. PhD thesis.

Weirich, P. (2016). Causal decision theory. In *The Stanford Encyclopedia of Philosophy*. Spring 2016 edition.