ACT: ASYMPTOTIC CONDITIONAL TRANSPORT

ABSTRACT

We propose conditional transport (CT) as a new divergence to measure the difference between two probability distributions. The CT divergence consists of the expected cost of a forward CT, which constructs a navigator to stochastically transport a data point of one distribution to the other distribution, and that of a backward CT which reverses the transport direction. To apply it to the distributions whose probability density functions are unknown but random samples are accessible, we further introduce asymptotic CT (ACT), whose estimation only requires access to mini-batch based discrete empirical distributions. Equipped with unbiased sample gradients that are straightforward to compute, the ACT divergence is amenable to mini-batch stochastic gradient descent based optimization. To demonstrate the efficacy of the ACT divergence in training a deep generative model, we show that it is sufficient to modify the adversarial game of an existing generative adversarial network (GAN) to a game played by a generator, a forward navigator, and a backward navigator, which try to minimize a distribution-to-distribution transport cost by optimizing both the distribution of the generator and conditional transport-path distributions specified by the navigators, versus a critic that does the opposite by inflating the point-to-point transport cost. On a wide variety of benchmark datasets for generative modeling, substituting the default statistical distance of an existing GAN with the ACT divergence is shown to consistently improve the performance.

1 INTRODUCTION

Measuring the difference between two probability distributions is a fundamental problem in statistics and machine learning (Cover, 1999; Bishop, 2006; Murphy, 2012). A variety of statistical distances have been proposed to to quantify the difference, which often serves as the first step to build a generative model. Commonly used statistical distances include the Kullback–Leibler (KL) divergence (Kullback and Leibler, 1951), Jensen–Shannon (JS) divergence (Lin, 1991), and Wasserstein distance (Kantorovich, 2006). While being widely used for generative modeling (Kingma and Welling, 2013; Goodfellow et al., 2014; Arjovsky et al., 2017), they all have their own limitations. The KL divergence is directly related to both maximum likelihood estimation and variational inference, and is amenable to mini-batch stochastic gradient descent (SGD) based optimization (Wainwright and Jordan, 2008; Hoffman et al., 2013; Blei et al., 2017). However, it requires the two probability distributions to share the same support, and is often inapplicable if either of them is an implicit distribution whose probability density function (PDF) is unknown (Mohamed and Lakshminarayanan, 2016; Huszár, 2017; Tran et al., 2017; Yin and Zhou, 2018). The JS divergence is directly related to the mini-max loss of a generative adversarial net (GAN) when the discriminator is optimal (Goodfellow et al., 2014). However, it is difficult to achieve a good balance between the generator and the discriminator, making GANs notoriously brittle to train. The Wasserstein distance is a widely used metric that allows the two distributions to have non-overlapping supports (Villani, 2008; Santambrogio, 2015; Peyré and Cuturi, 2019). However, it does not come with a simple and efficient estimation procedure, and its mini-batch based sample gradients are often biased (Arjovsky et al., 2017; Bellemare et al., 2017; Bottou et al., 2017; Bińkowski et al., 2018; Bernton et al., 2019).

To address the limitations of existing measurement methods, we introduce conditional transport (CT) as a new divergence to quantify the difference between two probability distributions. We refer to them as the source and target distributions and denote their probability density functions (PDFs) as $p_X(\boldsymbol{x})$ and $p_Y(\boldsymbol{y})$, respectively. The CT divergence is defined with a bidirectional distribution-to-distribution transport. It consists of a forward CT that transports the source to target

distribution, and a backward CT that reverses the transport direction. Our intuition is that given a source (target) point, it is more likely to be transported to a target (source) point closer to it. Denoting $d(\boldsymbol{x}, \boldsymbol{y}) = d(\boldsymbol{y}, \boldsymbol{x})$ as a learnable function and $c(\boldsymbol{x}, \boldsymbol{y}) = c(\boldsymbol{y}, \boldsymbol{x}) \geq 0$, where the equality is true when $\boldsymbol{x} = \boldsymbol{y}$, as the point-to-point transport cost, the goal is to minimize the transport cost between two distributions. The forward CT is constructed in three steps: 1) We define a forward "navigator" as $\pi(\boldsymbol{y} \,|\, \boldsymbol{x}) = e^{-d(\boldsymbol{x}, \boldsymbol{y})} p_Y(\boldsymbol{y}) / \int e^{-d(\boldsymbol{x}, \boldsymbol{y})} p_Y(\boldsymbol{y}) \mathrm{d}\boldsymbol{y}$, a conditional distribution specifying how likely a given source point $\boldsymbol{x}$ will be transported to distribution $p_Y(\boldsymbol{y})$ via path $\boldsymbol{x} \to \boldsymbol{y}$; 2) We define the cost of a forward $\boldsymbol{x}$-transporting CT as $\int c(\boldsymbol{x}, \boldsymbol{y}) \pi(\boldsymbol{y} \,|\, \boldsymbol{x}) \mathrm{d}\boldsymbol{y}$, the expected cost of employing the forward navigator to transport $\boldsymbol{x}$ to a random target point; 3) We define the total cost of the forward CT as $\int p_X(\boldsymbol{x}) \int c(\boldsymbol{x}, \boldsymbol{y}) \pi(\boldsymbol{y} \,|\, \boldsymbol{x}) \mathrm{d}\boldsymbol{y}\mathrm{d}\boldsymbol{x}$, which is the expectation of the cost of a forward $\boldsymbol{x}$-transporting CT with respect to $p_X(\boldsymbol{x})$. Similarly, we construct the backward CT by first defining a backward navigator as $\pi(\boldsymbol{x} \,|\, \boldsymbol{y}) = e^{-d(\boldsymbol{x}, \boldsymbol{y})} p_X(\boldsymbol{x}) / \int e^{-d(\boldsymbol{x}, \boldsymbol{y})} p_X(\boldsymbol{x}) \mathrm{d}\boldsymbol{x}$ and then its total cost as $\int p_Y(\boldsymbol{y}) \int c(\boldsymbol{x}, \boldsymbol{y}) \pi(\boldsymbol{x} \,|\, \boldsymbol{y}) \mathrm{d}\boldsymbol{x}\mathrm{d}\boldsymbol{y}$. Estimating the CT divergence involves both $\pi(\boldsymbol{x} \,|\, \boldsymbol{y})$ and $\pi(\boldsymbol{y} \,|\, \boldsymbol{x})$, which are generally intractable to evaluate and sample from, except for a few limited settings where both $p_X(\boldsymbol{x})$ and $p_Y(\boldsymbol{y})$ are exponential family distributions conjugate to $e^{-d(\boldsymbol{x}, \boldsymbol{y})}$. Thus despite having an instructive construction, the CT divergence in its current form is of limited use in practice.

To apply the CT divergence in a general setting where we only have access to random samples from the distributions, we introduce asymptotic CT (ACT) as a divergence measure that is friendly to mini-batch SGD based optimization. The ACT divergence is the expected value of the CT divergence, whose $p_X(\boldsymbol{x})$ and $p_Y(\boldsymbol{y})$ are both replaced with their discrete empirical distributions, respectively supported on N independent, and identically distributed (iid) random samples from $p_X(\boldsymbol{x})$ and M iid random samples from $p_Y(\boldsymbol{y})$. The ACT divergence is asymptotically equivalent to CT divergence when both $N \to \infty$ and $M \to \infty$. Intuitively, it can also be interpreted as performing both a forward one-to-M stochastic CT from the source to target and a backward one-to-N stochastic CT from the target to source, with the expected cost providing an unbiased sample estimate of the ACT divergence.

We show that similar to the KL divergence, ACT provides unbiased sample gradients, but different from it, neither $p_X(\boldsymbol{x})$ nor $p_Y(\boldsymbol{y})$ needs to be known. Similar to the Wasserstein distance, it does not require the distributions to share the same support, but different from it, the sample estimates of ACT and its gradients are unbiased and straightforward to compute. In GANs or Wasserstein GANs (Arjovsky et al., 2017), having an optimal discriminator or critic is required to unbiasedly estimate the JS divergence or Wasserstein distance and hence the gradients of the generator (Bottou et al., 2017). However, this is rarely the case in practice, motivating a common remedy to stabilize the training by carefully regularizing the gradients, such as clipping or normalizing their values (Gulrajani et al., 2017; Miyato et al., 2018). By contrast, in an adversarial game under ACT, the optimization of the critic, which manipulates the point-to-point transport cost $c(\boldsymbol{x}, \boldsymbol{y})$ but not the navigators' conditional distributions for $\boldsymbol{x} \to \boldsymbol{y}$ and $\boldsymbol{x} \leftarrow \boldsymbol{y}$, has no impact on how ACT is estimated. For this reason, the sample gradients stay unbiased regardless of how well the critic is optimized.

To demonstrate the use of the ACT (or CT) divergence, we apply it to train implicit (or explicit) distributions to model both 1D and 2D toy data, MNIST digits, and natural images. The implicit distribution is defined by a deep generative model (DGM) that is simple to sample from. We focus on adapting existing GANs, with minimal changes to their settings except for substituting the statistical distances in their loss functions with the ACT divergence. We leave tailoring the network architectures to the ACT divergence to future study. More specifically, we modify the GAN loss function to an adversarial game between a generator, a forward navigator, and a backward navigator, which try to minimize the distribution-to-distribution transport cost by optimizing both the fake data distribution $p_Y(\boldsymbol{y})$ and two conditional point-to-point navigation-path distributions $\pi(\boldsymbol{y} \,|\, \boldsymbol{x})$ and $\pi(\boldsymbol{x} \,|\, \boldsymbol{y})$, versus a critic that does the opposite by inflating the point-to-point transport cost $c(\boldsymbol{x}, \boldsymbol{y})$. Modifying an existing (Wasserstein) GAN with the ACT divergence, our experiments show consistent improvements in not only quantitative performance and generation quality, but also learning stability.

2 CONDITIONAL TRANSPORT WITH GENERATOR, NAVIGATORS, AND CRITIC

Denote $\boldsymbol{x}$ as a data taking its value in $\mathbb{R}^V$. In practice, we observe a finite set $\mathcal{X} = \{\boldsymbol{x}_i\}_{i=1}^{|\mathcal{X}|}$, consisting of $|\mathcal{X}|$ data samples assumed to be iid drawn from $p_X(\boldsymbol{x})$. Given $\mathcal{X}$, the usual task is to learn a distribution to approximate $p_X(\boldsymbol{x})$, explaining how the data in $\mathcal{X}$ are generated. To approximate $p_X(\boldsymbol{x})$, we consider a DGM defined as $\boldsymbol{y} = G_{\boldsymbol{\theta}}(\boldsymbol{\epsilon})$, $\boldsymbol{\epsilon} \sim p(\boldsymbol{\epsilon})$, where $G_{\boldsymbol{\theta}}$ is a generator that transforms

noise $\epsilon \sim p(\epsilon)$ via a deep neural network parameterized by $\boldsymbol{\theta}$ to generate random sample $\boldsymbol{y} \in \mathbb{R}^V$. While the PDF of the generator, denoted as $p_{\boldsymbol{\theta}}(\boldsymbol{y})$, is often intractable to evaluate, it is straightforward to draw $\boldsymbol{y} \sim p_{\boldsymbol{\theta}}(\boldsymbol{y})$ with $G_{\boldsymbol{\theta}}$. Denote both $\mu(\mathrm{d}\boldsymbol{x}) = p_X(\boldsymbol{x})\mathrm{d}\boldsymbol{x}$ and $\nu(\mathrm{d}\boldsymbol{y}) = p_{\boldsymbol{\theta}}(\boldsymbol{y})\mathrm{d}\boldsymbol{y}$ as continuous probability measures over $\mathbb{R}^V$, with $\mu(\mathbb{R}^V) = \int_{\mathbb{R}^V} p_X(\boldsymbol{x})\mathrm{d}\boldsymbol{x} = 1$ and $\nu(\mathbb{R}^V) = \int_{\mathbb{R}^V} p_{\boldsymbol{\theta}}(\boldsymbol{y})\mathrm{d}\boldsymbol{y} = 1$. The Wasserstein distance can be defined with Kantorovich's optimal transport problem (Kantorovich, 2006; Villani, 2008; Santambrogio, 2015; Peyré and Cuturi, 2019), expressed as

$$\mathcal{W}(\mu, \nu) = \min_{\pi \in \Pi(\mu,\nu)} \left\{ \int_{\mathbb{R}^V \times \mathbb{R}^V} c(\boldsymbol{x}, \boldsymbol{y}) \pi(\mathrm{d}\boldsymbol{x}, \mathrm{d}\boldsymbol{y}) \right\} = \min_{\pi \in \Pi(\mu,\nu)} \left\{ \mathbb{E}_{(\boldsymbol{x},\boldsymbol{y}) \sim \pi(\boldsymbol{x},\boldsymbol{y})} [c(\boldsymbol{x}, \boldsymbol{y})] \right\}, \quad (1)$$

where the minimum is taken over $\Pi(\mu, \nu)$, defined as the set of all possible joint probability measures π on $\mathbb{R}^V \times \mathbb{R}^V$, with marginals $\pi(A, \mathbb{R}^V) = \mu(A)$ and $\pi(\mathbb{R}^V, A) = \nu(A)$ for any Borel set $A \subset \mathbb{R}^V$.

2.1 FORWARD AND BACKWARD NAVIGATORS AND CONDITIONAL PATH DISTRIBUTIONS

Constraining $\pi \in \Pi(\mu, \nu)$, the Wasserstein distance satisfies $\mathcal{W}(\mu, \nu) = \mathcal{W}(\nu, \mu)$. By contrast, the proposed divergence allows $\pi \notin \Pi(\mu, \nu)$. Denote $\mathcal{T}_{\boldsymbol{\phi}}(\cdot) \in \mathbb{R}^H$ as a neural network based function, transforming its input in $\mathbb{R}^V$ into a feature vector in $\mathbb{R}^H$, and $d(\boldsymbol{h}_1, \boldsymbol{h}_2)$ as a function that measures the difference between $\boldsymbol{h}_1, \boldsymbol{h}_2 \in \mathbb{R}^H$. We introduce a forward CT, whose transport cost is defined as

$$\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \to \nu) = \mathbb{E}_{\boldsymbol{x} \sim p_X(\boldsymbol{x})} \mathbb{E}_{\boldsymbol{y} \sim \pi_{\boldsymbol{\phi}}(\boldsymbol{y} \,|\, \boldsymbol{x})} [c(\boldsymbol{x}, \boldsymbol{y})], \quad \pi_{\boldsymbol{\phi}}(\boldsymbol{y} \,|\, \boldsymbol{x}) \stackrel{\text{def.}}{=} \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))} p_{\boldsymbol{\theta}}(\boldsymbol{y})}{\int e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))} p_{\boldsymbol{\theta}}(\boldsymbol{y})\mathrm{d}\boldsymbol{y}}, \quad (2)$$

where $\pi_{\boldsymbol{\phi}}(\boldsymbol{y} \,|\, \boldsymbol{x})$ will be analogized to the forward navigator that defines the forward-path conditional distribution. Similarly, we introduce the backward CT, whose transport cost is defined as

$$\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \leftarrow \nu) = \mathbb{E}_{\boldsymbol{y} \sim p_{\boldsymbol{\theta}}(\boldsymbol{y})} \mathbb{E}_{\boldsymbol{x} \sim \pi_{\boldsymbol{\phi}}(\boldsymbol{x} \,|\, \boldsymbol{y})} [c(\boldsymbol{x}, \boldsymbol{y})], \quad \pi_{\boldsymbol{\phi}}(\boldsymbol{x} \,|\, \boldsymbol{y}) \stackrel{\text{def.}}{=} \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))} p_X(\boldsymbol{x})}{\int e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))} p_X(\boldsymbol{x})\mathrm{d}\boldsymbol{x}}, \quad (3)$$

where $\pi_{\boldsymbol{\phi}}(\boldsymbol{x} \,|\, \boldsymbol{y})$ will be analogized to a backward navigator. We now define the CT problem as

$$\min_{\boldsymbol{\phi},\boldsymbol{\theta}} \left\{ \mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu, \nu) \right\}, \quad \mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu, \nu) \stackrel{\text{def.}}{=} \tfrac{1}{2}\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \to \nu) + \tfrac{1}{2}\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \leftarrow \nu), \quad (4)$$

where $\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu, \nu) = \mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\nu, \mu)$ will be referred to as the CT divergence between μ and ν.

Lemma 1. *If $\boldsymbol{y} \sim p_{\boldsymbol{\theta}}(\boldsymbol{y})$ is equal to $\boldsymbol{x} \sim p_X(\boldsymbol{x})$ in distribution and $\mathcal{T}_{\boldsymbol{\phi}}$ is chosen such that $e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))} = \mathbf{1}(\boldsymbol{x} = \boldsymbol{y})$, where $\mathbf{1}(\cdot)$ is an indicator function, then both the the joint probability measure π defined with $p_X(\boldsymbol{x})\pi_{\boldsymbol{\phi}}(\boldsymbol{y} \,|\, \boldsymbol{x})$ in (2) and that with $p_{\boldsymbol{\theta}}(\boldsymbol{y})\pi_{\boldsymbol{\phi}}(\boldsymbol{x} \,|\, \boldsymbol{y})$ in (3) are in $\Pi(\mu, \nu)$.*

Lemma 2. *If $\boldsymbol{y} \sim p_{\boldsymbol{\theta}}(\boldsymbol{y})$ is equal to $\boldsymbol{x} \sim p_X(\boldsymbol{x})$ in distribution, then $C_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu, \nu) = \mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \to \nu) = \mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \leftarrow \nu) \geq \mathcal{W}(\mu, \nu) = 0$, where the equality can be achieved if $e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))} = \mathbf{1}(\boldsymbol{x} = \boldsymbol{y})$.*

The proofs are deferred to Appendix A. Note in general, before both $\boldsymbol{\theta}$ and $\boldsymbol{\phi}$ reach their optimums, the conditions specified in Lemmas 1 and 2 are not satisfied and the joint probability measure π defined with $p_X(\boldsymbol{x})\pi_{\boldsymbol{\phi}}(\boldsymbol{y} \,|\, \boldsymbol{x})$ or $p_{\boldsymbol{\theta}}(\boldsymbol{y})\pi_{\boldsymbol{\phi}}(\boldsymbol{x} \,|\, \boldsymbol{y})$ is not restricted to be in $\Pi(\mu, \nu)$, and hence it is possible for $\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \to \nu), \mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \leftarrow \nu)$, or $\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu, \nu)$ to go below $\mathcal{W}(\mu, \nu)$ during training.

2.2 ASYMPTOTIC CONDITIONAL TRANSPORT

Computing the CT divergence requires either knowing the PDFs of both navigators $\pi_{\boldsymbol{\phi}}(\boldsymbol{y} \,|\, \boldsymbol{x})$ and $\pi_{\boldsymbol{\phi}}(\boldsymbol{x} \,|\, \boldsymbol{y})$, or being able to draw random samples from them. However, usually neither is true unless both $p_{\boldsymbol{\theta}}(\boldsymbol{y})$ and $p_X(\boldsymbol{x})$ are known and conjugate to $e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}$. For example, if $d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y})) = \|\boldsymbol{\phi}\boldsymbol{x} - \boldsymbol{\phi}\boldsymbol{y}\|_2^2 = (\boldsymbol{x} - \boldsymbol{y})^T(\boldsymbol{\phi}^T\boldsymbol{\phi})(\boldsymbol{x} - \boldsymbol{y})$, where $\boldsymbol{\phi} \in \mathbb{R}^{V \times V}$ is a full-rank matrix, and both $p_X(\boldsymbol{x})$ and $p_{\boldsymbol{\theta}}(\boldsymbol{y})$ are multivariate Gaussian distributions, then one may show that both $\pi_{\boldsymbol{\phi}}(\boldsymbol{y} \,|\, \boldsymbol{x})$ and $\pi_{\boldsymbol{\phi}}(\boldsymbol{x} \,|\, \boldsymbol{y})$ are multivariate Gaussian distributions. In the experimental results section, we will provide a univariate normal distribution based toy examples for illustration. Below we show how to apply the CT divergence in a general setting that only requires access to random samples of both $\boldsymbol{x}$ and $\boldsymbol{y}$. While knowing neither $p_X(\boldsymbol{x})$ nor $p_{\boldsymbol{\theta}}(\boldsymbol{y})$, we can obtain mini-batch based empirical distributions $\hat{p}_N(\boldsymbol{x})$ and $\hat{p}_M(\boldsymbol{y})$, as defined below, to guide the optimization of $G_{\boldsymbol{\theta}}$ in an iterative manner. With N random observations sampled without replacement from $\mathcal{X}$, we define

$$\hat{p}_N(\boldsymbol{x}) = \tfrac{1}{N} \sum_{i=1}^{N} \delta_{\boldsymbol{x}_i}, \quad \{\boldsymbol{x}_1, \ldots, \boldsymbol{x}_N\} \subseteq \mathcal{X} \quad (5)$$

as an empirical distribution for $\boldsymbol{x}$ and denote its corresponding probability measure as $\hat{\mu}_N$, which means $\hat{\mu}_N(A) = \sum_{i=1}^N \frac{\mathbf{1}(\boldsymbol{x}_j \in A)}{N}$. Similarly, with M random samples of the generator, we define

$$\hat{p}_M(\boldsymbol{y}) = \frac{1}{M} \sum_{j=1}^M \delta_{\boldsymbol{y}_j}, \ \boldsymbol{y}_j = G_{\boldsymbol{\theta}}(\boldsymbol{\epsilon}_j), \ \boldsymbol{\epsilon}_j \overset{iid}{\sim} p(\boldsymbol{\epsilon}) \tag{6}$$

as an empirical distribution for $\boldsymbol{y}$ and denote its corresponding probability measure as $\hat{\nu}_M$. Below we assume drawing iid $\boldsymbol{x}_i$ from $p_X(\boldsymbol{x})$ can be realized by sampling them without replacement from $\mathcal{X}$.

Substituting $p_{\boldsymbol{\theta}}(\boldsymbol{y})$ in (2) with $\hat{p}_M(\boldsymbol{y})$, the continuous forward navigator becomes a discrete one as

$$\hat{\pi}_{\boldsymbol{\phi}}(\boldsymbol{y} \mid \boldsymbol{x}) = \sum_{j=1}^M \hat{\pi}_M(\boldsymbol{y}_j \mid \boldsymbol{x}, \boldsymbol{\phi}) \delta_{\boldsymbol{y}_j}, \ \hat{\pi}_M(\boldsymbol{y}_j \mid \boldsymbol{x}, \boldsymbol{\phi}) \overset{\text{def.}}{=} \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}_j))}}{\sum_{j'=1}^M e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}_{j'}))}}. \tag{7}$$

Thus drawing $\boldsymbol{y}_{1:M} \overset{iid}{\sim} p_{\boldsymbol{\theta}}(\boldsymbol{y})$ to form $\hat{\nu}_M$, the cost of a forward CT becomes

$$\mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\mu \rightarrow \hat{\nu}_M) = \mathbb{E}_{\boldsymbol{x} \sim p_X(\boldsymbol{x})} \mathbb{E}_{\boldsymbol{y} \sim \hat{\pi}_{\boldsymbol{\phi}}(\boldsymbol{y} \mid \boldsymbol{x})}[c(\boldsymbol{x}, \boldsymbol{y})] = \mathbb{E}_{\boldsymbol{x} \sim p_X(\boldsymbol{x})} \left[\mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\boldsymbol{x} \rightarrow \hat{\nu}_M)\right],$$

$$\text{where} \ \ \mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\boldsymbol{x} \rightarrow \hat{\nu}_M) \overset{\text{def.}}{=} \sum_{j=1}^M c(\boldsymbol{x}, \boldsymbol{y}_j) \hat{\pi}_M(\boldsymbol{y}_j \mid \boldsymbol{x}, \boldsymbol{\phi}). \tag{8}$$

Similarly, approximating $p_X(\boldsymbol{x})$ with $\hat{p}_N(\boldsymbol{x})$, the backward navigator becomes

$$\hat{\pi}_{\boldsymbol{\phi}}(\boldsymbol{x} \mid \boldsymbol{y}) = \sum_{i=1}^N \hat{\pi}_N(\boldsymbol{x}_i \mid \boldsymbol{y}, \boldsymbol{\phi}) \delta_{\boldsymbol{x}_i}, \ \hat{\pi}_N(\boldsymbol{x}_i \mid \boldsymbol{y}, \boldsymbol{\phi}) \overset{\text{def.}}{=} \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}_i), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}}{\sum_{i'=1}^M e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}_{i'}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}}, \tag{9}$$

and drawing $\boldsymbol{x}_{1:N} \overset{iid}{\sim} p_X(\boldsymbol{x})$ to form $\hat{\mu}_N$, the cost of a backward CT becomes

$$\mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\hat{\mu}_N \leftarrow \nu) = \mathbb{E}_{\boldsymbol{y} \sim p_{\boldsymbol{\theta}}(\boldsymbol{y})} \mathbb{E}_{\boldsymbol{x} \sim \hat{\pi}_{\boldsymbol{\phi}}(\boldsymbol{x} \mid \boldsymbol{y})}[c(\boldsymbol{x}, \boldsymbol{y})] = \mathbb{E}_{\boldsymbol{y} \sim p_{\boldsymbol{\theta}}(\boldsymbol{y})} \left[\mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\hat{\mu}_N \leftarrow \boldsymbol{y})\right],$$

$$\text{where} \ \ \mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\hat{\mu}_N \leftarrow \boldsymbol{y}) \overset{\text{def.}}{=} \sum_{i=1}^N c(\boldsymbol{x}_i, \boldsymbol{y}) \hat{\pi}_N(\boldsymbol{x}_i \mid \boldsymbol{y}, \boldsymbol{\phi}). \tag{10}$$

Combining both the forward and backward CTs, we define the asymptotic CT (ACT) problem as

$$\min_{\boldsymbol{\phi}, \boldsymbol{\theta}} \{\mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\mu, \nu, N, M)\}, \tag{11}$$

where $\mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\mu, \nu, N, M)$ is the ACT divergence defined as

$$\mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\mu, \nu, N, M) = \frac{1}{2} \mathbb{E}_{\boldsymbol{y}_{1:M} \overset{iid}{\sim} p_{\boldsymbol{\theta}}(\boldsymbol{y})} [\mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\mu \rightarrow \hat{\nu}_M)] + \frac{1}{2} \mathbb{E}_{\boldsymbol{x}_{1:N} \overset{iid}{\sim} p_X(\boldsymbol{x})} [\mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\hat{\mu}_N \leftarrow \nu)]. \tag{12}$$

Lemma 3. *The ACT divergence is asymptotic that* $\lim_{N, M \rightarrow \infty} \mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\mu, \nu, N, M) = \mathcal{C}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\mu, \nu)$.

Lemma 4. *With* $\boldsymbol{x}_{1:N} \overset{iid}{\sim} p_X(\boldsymbol{x})$ *and* $\boldsymbol{y}_{1:M} \overset{iid}{\sim} p_{\boldsymbol{\theta}}(\boldsymbol{y})$ *and drawing* $\boldsymbol{x} \sim \hat{p}_N(\boldsymbol{x})$ *and* $\boldsymbol{y} \sim \hat{p}_M(\boldsymbol{y})$, *an unbiased sample estimator of the ACT divergence can be expressed as*

$$\mathcal{L}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\boldsymbol{x}_{1:N}, \boldsymbol{y}_{1:M}) = \frac{1}{2} \sum_{j=1}^M c(\boldsymbol{x}, \boldsymbol{y}_j) \hat{\pi}_M(\boldsymbol{y}_j \mid \boldsymbol{x}, \boldsymbol{\phi}) + \frac{1}{2} \sum_{i=1}^N c(\boldsymbol{x}_i, \boldsymbol{y}) \hat{\pi}_N(\boldsymbol{x}_i \mid \boldsymbol{y}, \boldsymbol{\phi}). \tag{13}$$

Intuitively, the first term in the summation can be interpreted as the expected cost of following the forward navigator to stochastically transport a random source point $\boldsymbol{x}$ to one of the M randomly instantiated "anchors" of the target distribution. The second term shares a similar interpretation.

Lemma 5. *Another unbiased sample estimator that fully uses the data in mini-batches* $\boldsymbol{x}_{1:N}$ *and* $\boldsymbol{y}_{1:M}$ *can be expressed as*

$$\mathcal{L}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\boldsymbol{x}_{1:N}, \boldsymbol{y}_{1:M}) = \sum_{i=1}^N \sum_{j=1}^M c(\boldsymbol{x}_i, \boldsymbol{y}_j) \left(\frac{1}{2N} \hat{\pi}_M(\boldsymbol{y}_j \mid \boldsymbol{x}_i, \boldsymbol{\phi}) + \frac{1}{2M} \hat{\pi}_N(\boldsymbol{x}_i \mid \boldsymbol{y}_j, \boldsymbol{\phi})\right). \tag{14}$$

2.3 Critic based Adversarial Feature Extraction

A naive definition of the transport cost between $\boldsymbol{x}$ and $\boldsymbol{y}$ is some distance between their raw feature vectors, such as $c(\boldsymbol{x}, \boldsymbol{y}) = \|\boldsymbol{x} - \boldsymbol{y}\|_2^2$, which, however, often poorly reflects the difference between high-dimensional data residing on low-dimensional manifolds. For this reason, with cosine dissimilarity (Salimans et al., 2018), we introduce a critic $\mathcal{T}_{\boldsymbol{\eta}}(\cdot)$, parameterized by $\boldsymbol{\eta}$, to help define an adversarial transport cost between two high-dimensional data points, expressed as

$$c_{\boldsymbol{\eta}}(\boldsymbol{x}, \boldsymbol{y}) = 1 - \cos(\mathcal{T}_{\boldsymbol{\eta}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\eta}}(\boldsymbol{y})), \tag{15}$$

where $\cos(\boldsymbol{h}_1, \boldsymbol{h}_2) \overset{\text{def.}}{=} \frac{|\boldsymbol{h}_1^T \boldsymbol{h}_2|}{\sqrt{\boldsymbol{h}_1^T \boldsymbol{h}_1} \sqrt{\boldsymbol{h}_2^T \boldsymbol{h}_2}}$. Intuitively, to minimize the distribution-to-distribution transport cost, the generator tries to mimic true data and both navigators try to optimize conditional path distributions. By contrast, the critic does the opposite by inflating the point-to-point transport cost.

Figure 1: Illustration of minimizing the CT divergence $\mathcal{C}_{\phi,\theta}(\mu,\nu)$ between $\mathcal{N}(0,1)$ and $\mathcal{N}(0,e^\theta)$. *Left*: Trace plots of the CT divergence, its parameters and forward and backward costs, and corresponding Wasserstein distance; *Right*: Four different gradient plots, each shows the gradient of the forward or backward CT *w.r.t.* θ or ϕ. The horizontal and vertical dynamics are mainly driven by the gradient of the forward CT and that of the backward CT, respectively. With gradient descent starting from $(\theta, e^\phi) = (1.0, 1.0)$, both parameters converge close to their optimums. The 2D trace of (θ, e^ϕ) is marked with red arrows.

In summary, given the training data set $\mathcal{X}$, to train the generator $G_{\boldsymbol{\theta}}$, forward navigator $\pi_{\boldsymbol{\phi}}(\boldsymbol{y} \,|\, \boldsymbol{x})$, backward navigator $\pi_{\boldsymbol{\phi}}(\boldsymbol{x} \,|\, \boldsymbol{y})$, and critic $\mathcal{T}_{\boldsymbol{\eta}}$, we propose to solve a mini-max problem as

$$\max_{\boldsymbol{\eta}} \min_{\boldsymbol{\phi},\boldsymbol{\theta}} \mathbb{E}_{\boldsymbol{x}_{1:N} \subseteq \mathcal{X}, \; \boldsymbol{\epsilon}_{1:M} \overset{iid}{\sim} p(\boldsymbol{\epsilon})}[\mathcal{L}_{\boldsymbol{\phi},\boldsymbol{\theta},\boldsymbol{\eta}}(\boldsymbol{x}_{1:N}, \{G_{\boldsymbol{\theta}}(\boldsymbol{\epsilon}_j)\}_{j=1}^M)], \tag{16}$$

where $\mathcal{L}_{\boldsymbol{\phi},\boldsymbol{\theta},\boldsymbol{\eta}}$ is defined the same as in (13) or (14), except that we replace $c(\boldsymbol{x}_i, \boldsymbol{y}_j)$ in them with $c_{\boldsymbol{\eta}}(\boldsymbol{x}_i, \boldsymbol{y}_j)$ shown in (15) and draw $\boldsymbol{y}_{1:M}$ using reparameterization as in (6), which means $\boldsymbol{y}_{1:M} \overset{\text{def.}}{=} \{G_{\boldsymbol{\theta}}(\boldsymbol{\epsilon}_j)\}_{j=1}^M$. We train $\boldsymbol{\phi}$ and $\boldsymbol{\theta}$ with SGD using $\nabla_{\boldsymbol{\phi},\boldsymbol{\theta}}\mathcal{L}_{\boldsymbol{\phi},\boldsymbol{\theta},\boldsymbol{\eta}}(\boldsymbol{x}_{1:N}, \{G_{\boldsymbol{\theta}}(\boldsymbol{\epsilon}_j)\}_{j=1}^M))$ and, if the critic is employed, train $\boldsymbol{\eta}$ with stochastic gradient ascent using $\nabla_{\boldsymbol{\eta}}\mathcal{L}_{\boldsymbol{\phi},\boldsymbol{\theta},\boldsymbol{\eta}}(\boldsymbol{x}_{1:N}, \{G_{\boldsymbol{\theta}}(\boldsymbol{\epsilon}_j)\}_{j=1}^M))$.

Note in existing critic-based GANs, how well the critics are optimized are directly related to how accurate and stable the gradients can be estimated. By contrast, under the ACT divergence, regardless of how well the critic is optimized to inflate $c_{\boldsymbol{\eta}}(\boldsymbol{x}, \boldsymbol{y})$, the sample estimate $\mathcal{L}_{\boldsymbol{\phi},\boldsymbol{\theta},\boldsymbol{\eta}}(\boldsymbol{x}_{1:N}, \{G_{\boldsymbol{\theta}}(\boldsymbol{\epsilon}_j)\}_{j=1}^M)$ of the ACT divergence and its gradients stay unbiased. For this reason, one can also train the critic parameter $\boldsymbol{\eta}$ using a different loss other than (16), such as the cross-entropy discriminator loss used in vanilla GANs to discriminate between $\boldsymbol{x}$ and $G_{\boldsymbol{\theta}}(\boldsymbol{\epsilon})$. This point will be verified in our ablation study.

3 EXPERIMENTAL RESULTS

CT divergence for toy data: As a proof of concept, we illustrate optimization under the CT divergence in 1D, with $x, y, \phi, \theta \in \mathbb{R}$. We consider a univariate normal distribution based example:

$$p(x) = \mathcal{N}(0,1), \;\; p_\theta(y) = \mathcal{N}(0, e^\theta), \;\; c(x,y) = (x-y)^2, \;\; d(\mathcal{T}_\phi(x), \mathcal{T}_\phi(y)) = \frac{(x-y)^2}{2e^\phi}. \tag{17}$$

Thus $\theta = 0$ is the optimal solution that makes $\nu = \mu$. Denote $\sigma(a) = 1/(1 + e^{-a})$ as the sigmoid function, we have analytic forms of the Wasserstein distance as $\mathcal{W}_2(\mu,\nu)^2 = (1 - e^{\frac{\theta}{2}})^2$, forward and backward navigators as $\pi_\phi(y \,|\, x) = \mathcal{N}(\sigma(\theta - \phi)x, \sigma(\theta - \phi)e^\phi)$ and $\pi_\phi(x \,|\, y) = \mathcal{N}(\sigma(-\phi)y, \sigma(\phi))$, and forward and backward CT costs as $\mathcal{C}_{\phi,\theta}(\mu \to \nu) = \sigma(\phi - \theta)(e^\theta + \sigma(\phi - \theta))$ and $\mathcal{C}_{\phi,\theta}(\mu \leftarrow \nu) = \sigma(\phi)(1 + \sigma(\phi)e^\theta)$ (see Appendix B.1 for more details). Thus when applying gradient descent to minimize the CT divergence $\mathcal{C}_{\phi,\theta}(\mu,\nu)$, we expect the generator parameter $\theta \to 0$ as long as the learning rate of the navigator parameter ϕ is appropriately controlled to prevent $e^\phi \to 0$ from happening too soon. This is confirmed by Fig. 1, which shows that the learning of θ is not sensitive to that of ϕ, and long before e^ϕ approaches zero, θ has already converged close to its optimal solution at zero. This suggests that the navigator parameter ϕ mainly plays the role in assisting the learning of θ. It is also interesting to observe that the CT divergences keep descending towards zero even when $\mathcal{W}_2(\mu,\nu)^2$ has already reached close to zero. As θ and ϕ converge towards their optimal solutions under the CT divergence, we can observe that $\mathcal{C}_{\phi,\theta}(\mu \to \nu)$ and $\mathcal{C}_{\phi,\theta}(\mu \leftarrow \nu)$ are getting closer. Moreover, $\mathcal{C}_{\phi,\theta}(\mu,\nu)$ initially stays above $\mathcal{W}_2(\mu,\nu)^2 = (1 - e^{\frac{\theta}{2}})^2$ but eventually becomes very close to $\mathcal{W}_2(\mu,\nu)^2$, which agrees what Lemma 2 suggests. Each of the right four panels shows the descent trace on the gradient with respect to (*w.r.t.*) θ or ϕ of the forward or back CT cost, from which it is instructive to observe that the dynamic for x-axis movement is mainly driven by the forward CT, whose gradient contributes more to the learning of the generator parameter θ, while the backward CT provides the dynamic for y-axis movement that corresponds to the navigator parameter ϕ.

Figure 2: Illustration of how minimizing the ACT divergence between the empirical distribution of a generator and that of a bimodal Gaussian mixture, whose PDF is assumed to be unknown but random samples are given, helps optimize the generator distribution towards the true one. *Top*: Trace plots of the ACT divergence $\mathcal{C}(\hat{\mu}_N, \hat{\nu}_M)$, forward ACT cost $\mathcal{C}(\hat{\mu}_N \to \hat{\nu}_M)$, backward ACT cost $\mathcal{C}(\hat{\mu}_N \leftarrow \hat{\nu}_M)$, and Wasserstein distance $\mathcal{W}_2(\hat{\mu}_N, \hat{\nu}_M)^2$. *Bottom*: The PDF of the true data distribution $\mu(\mathrm{d}x) = p_X(x)\mathrm{d}x$ (red) and the generator distribution $\nu(\mathrm{d}y) = p_{\boldsymbol{\theta}}(y)\mathrm{d}y$ (blue, visualized via kernel density estimation) at different training iterations.

ACT for 1D toy data: We move on to model the empirical samples from a true data distribution, for which it is natural to apply the ACT divergence. To parameterize ACT, we apply a deep neural network to generator $G_{\boldsymbol{\theta}}$ and another one to $\mathcal{T}_{\boldsymbol{\phi}}$ that is shared by both navigators. We consider the squared Euclidean (*i.e.* $\mathcal{L}_2^2$) distance to define both cost $c(\boldsymbol{x}, \boldsymbol{y})$ and distance $d(\boldsymbol{h}_1, \boldsymbol{h}_2)$.

We first consider a 1D example, where $\mathcal{X}$ consists of $N = 5,000$ samples $x_i \in \mathbb{R}$ of a bimodal Gaussian mixture $p_X(x) = \frac{1}{4}\mathcal{N}(x; -5, 1) + \frac{3}{4}\mathcal{N}(x; 2, 1)$. We illustrate in Fig. 2 the training with unbiased sample gradients $\nabla_{\boldsymbol{\phi}, \boldsymbol{\theta}}\mathcal{L}_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\mathcal{X}, y_{1:M})$ of the ACT divergence shown in (14), where $y_j = G_{\boldsymbol{\theta}}(\boldsymbol{\epsilon}_j)$. The top panel shows the ACT divergence, its backward and forward costs, and Wasserstein distance between empirical probability measures $\hat{\mu}_X = \sum_{i=1}^{N} \frac{1}{N}\delta_{x_i}$ and $\hat{\nu}_Y = \sum_{j=1}^{M} \frac{1}{M}\delta_{y_j}$. We set $M = N$ and hence $\mathcal{W}_2(\hat{\mu}_X, \hat{\nu}_Y)^2$ can be exactly computed by sorting the 1D elements of $x_{1:N}$ and $y_{1:N}$ (Peyré and Cuturi, 2019). Fig. 2 (Top) shows that the ACT divergence converges close to $\mathcal{W}_2(\hat{\mu}_X, \hat{\nu}_Y)^2$ and the forward and backward costs move closer to each other and can sometime go below $\mathcal{W}_2(\hat{\mu}_X, \hat{\nu}_Y)^2$. Fig. 2 (Bottom) shows that minimizing the ACT divergence successfully drives the generator distribution towards true data density: From the left to right, we can observe that initially the generator is focused on fitting a single mode; at around the 500^{th} iteration, as the forward and backward navigators are getting better, they start to help the generator locate the missing mode and we can observe a blue density mode starts to form over there; as the generator and both navigators are getting optimized, we can observe that the generator clearly captures both modes and the fitting is getting improved further; finally the generator well approximates the data density. Under the guidance of the ACT divergence, the generator and navigators are helping each other: An optimized generator helps the two navigators to train and realize the missing mode, and the optimized navigators help the generator locate under-fitted regions and hence better fit the true data density.

ACT for 2D toy data: We further conduct experiments on four representative 2D datasets: 8-Gaussian mixture, as shown in Fig. 3, and Swiss Roll, Half Moons, and 25-Gaussian mixture, as shown in Figs. 5, 6, 7 of Appendix B.2. We apply the vanilla GAN (Goodfellow et al., 2014) and Wasserstein GAN with gradient penalty (WGAN-GP) (Gulrajani et al., 2017) as two representatives of mini-max DGMs that require solving a mini-max loss to train the generator. We then apply the generators trained under the sliced Wasserstein distance (SWD) (Deshpande et al., 2018) and ACT divergence as two representatives of mini-max-free DGMs. Compared to mini-max DGMs, which require an adversarially learned critic in order to train the generator, one clear advantage of mini-max-free DGMs is that the generator is stable to train without the need of an adversarial game. On each 2D data, we train these DGMs as one would normally do during the first $15k$ iterations. We then only train the generator and freeze all the other learnable model parameters, which means we freeze the discriminator in GAN, critic in WGAN, and the navigator parameter ϕ of the ACT divergence, for another $15k$ iterations. Fig. 3 illustrates this training process on the 8-Gaussian mixture dataset, where for both mini-max DGMs, the mode collapse issue deteriorates after the first $15k$ iterations, while the training for SWD remains stable and that for ACT continues to improve. Compared to SWD, our method covers all 8 data density modes and moves the generator much closer to the true

Figure 3: On a 8-Gaussian mixture data, comparison of generation quality and training stability between two mini-max deep generative models (DGMs), including vallina GAN and Wasserstein GAN with gradient penalty (WGAN-GP), and two mini-max-free DGMs, whose generators are trained under the sliced Wasserstein distance (SWD) and the proposed ACT divergence, respectively. The critics of GAN and WGAN-GP and the navigators of ACT are fixed after $15k$ iterations. The first column shows the true data density.

data density. On the other three datasets, the ACT divergence based DGM also exhibits good training consistency, high stability, and and close-to-optimal data generation, as shown in Appendix B.2.

ACT for natural images: We conduct a variety of experiments on natural images to evaluate the performance and reveal the properties of DGMs optimized under the ACT divergence. We consider three widely-used image datasets, including CIFAR-10 (Krizhevsky et al., 2009), CelebA (Liu et al., 2015), and LSUN-bedroom (Yu et al., 2015), and compare the results of DGMs optimized with the ACT divergence against DGMs trained with the vanilla GAN and its various generalizations.

Note different from previous experiments on toy data, where the transport cost $c(\boldsymbol{x}, \boldsymbol{y})$ can be defined by directly comparing $\boldsymbol{x}$ and $\boldsymbol{y}$, for natural images, whose differences in raw pixel values are often not that meaningful, we need to compare $\mathcal{T}_{\boldsymbol{\eta}}(\boldsymbol{x})$ and $\mathcal{T}_{\boldsymbol{\eta}}(\boldsymbol{y})$, where $\mathcal{T}_{\boldsymbol{\eta}}(\cdot)$ is a critic that plays the role of adversarial feature extraction, as discussed in Section 2.3. In particular, we use (15) to define the transport cost as $c_{\boldsymbol{\eta}}(\boldsymbol{x}, \boldsymbol{y}) = 1 - \cos(\mathcal{T}_{\boldsymbol{\eta}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\eta}}(\boldsymbol{y}))$. To parameterize the navigators, we also set $d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y})) = 1 - \cos(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}), \mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))$. We test with the architecture suggested in Radford et al. (2015) as a standard CNN backbone and also apply the architecture in Miyato et al. (2018) as the ResNet (He et al., 2016) backbone, specifically, we use the same architecture for the generator, and we slightly modify the output dimension of the discriminator architecture as 2048 for both $\mathcal{T}_{\boldsymbol{\eta}}$ of the critic and $\mathcal{T}_{\boldsymbol{\phi}}$ used by the two navigators. We train this model with (16) and (14), and to keep close to the corresponding backbone's original experiment setting, we set $N = M = 64$ for all experiments.

We summarize in Table 1 the Fréchet inception distance (FID) of Heusel et al. (2017) on all datasets and Inception Score (IS) of Salimans et al. (2016) on CIFAR-10. Both FID and IS are calculated using a pre-trained inception model (Szegedy et al., 2016). Lower FID and higher IS scores indicate better image quality. We observe that ACT-DCGAN and ACT-SNGAN, which are DCGAN and SNGAN backbones optimized with the ACT divergence, convincingly outperform DCGAN and SNGAN, respectively, suggesting that ACT is compatible with standard GANs and WGANs and generally helps improve generation quality. Moreover, ranked among the Top 3 on all datasets, ACT-SNGAN performs on par with the best benchmarks on CIFAR-10 and CelebA, while slightly worse on LSUN. The qualitative results shown in Fig. 4 are consistent with quantitative results in Table 1.

Note ACT brings consistent improvement to DCGAN and SNGAN by neither improving their network architectures nor gradient regularization. Thus it has great potential to work in conjunction with other state-of-the-art architectures or methods, such as BigGAN (Brock et al., 2018), self-attention GANs (Zhang et al., 2019), BigBiGAN (Donahue and Simonyan, 2019), progressive training (Karras et al., 2018), self-supervised learning (Chen et al., 2019), and data augmentation (Karras et al., 2020; Zhao et al., 2020a;b), which we leave for future study. As the paper is primarily focused on constructing and validating a new divergence measure, we have focused on demonstrating its efficacy on toy data and benchmark image data with moderate resolutions. We have focused on adapting DCGAN and SNGAN under ACT, and we leave to future work using the ACT to optimize a big DGM, such as BigGAN, that is often trained for high-resolution images with a substantially bigger network and larger mini-batch size and hence requires intensive computation that is not easy to afford.

Table 1: Comparison of generative models on CIFAR-10, CelebA and LSUN. (Top-3 are in bold)

Method	Fréchet Inception Distance (FID, lower is better)			Inception Score (higher is better)
	CIFAR-10	CelebA	LSUN-bedroom	CIFAR-10
WGAN (Arjovsky et al., 2017)	51.3±1.5	37.1±1.9	73.3±2.5	6.9±0.1
WGAN-GP (Gulrajani et al., 2017)	19.0±0.8	18.0±0.7	26.9±1.1	7.9±0.1
MMD-GAN (Li et al., 2017)	73.9±0.1	-	-	6.2±0.1
Cramér-GAN (Bellemare et al., 2017)	40.3±0.2	31.3±0.2	54.2±0.4	6.4±0.1
CTGAN (Wei et al., 2018)	**17.6±0.7**	15.8±0.6	**19.5±1.2**	5.1±0.1
OT-GAN (Salimans et al., 2018)	32.5±0.6	19.4±3.0	70.5±5.3	**8.5±0.1**
SWG (Deshpande et al., 2018)	33.7±1.5	21.9±2.0	67.9±2.7	-
Max-SWG (Deshpande et al., 2019)	23.6±0.5	**10.1±0.6**	40.1±4.5	-
SWGAN (Wu et al., 2019)	**17.0±1.0**	**13.2±0.7**	**14.9±1.0**	-
DCGAN (Radford et al., 2015)	30.2±0.9	52.5±2.2	61.7±2.9	6.2±0.1
DCGAN backbone + ACT divergence (ACT-DCGAN)	24.8±1.0	29.2±2.0	37.4±2.5	7.5±0.1
SNGAN (Miyato et al., 2018)	21.5±1.3	21.7±1.5	31.1±2.1	**8.2±0.1**
SNGAN backbone + ACT divergence (ACT-SNGAN)	**18.0±0.7**	**11.3±1.0**	**24.2±1.8**	**8.7±0.1**

Table 2: FID comparison for ACT-DCGAN and ACT-SNGAN on CIFAR-10 with different cost and architecture.

-Standard CNN-		transport cost $c(\boldsymbol{x},\boldsymbol{y})$				-ResNet-		transport cost $c(\boldsymbol{x},\boldsymbol{y})$			
		$\mathcal{L}_2^2$-pixel	cos-pixel	$\mathcal{L}_2^2$-feature	cos-feature			$\mathcal{L}_2^2$-pixel	cos-pixel	$\mathcal{L}_2^2$-feature	cos-feature
Navigator cost	$\mathcal{L}_2^2$	171.9	138.4	27.1	24.8	Navigator cost	$\mathcal{L}_2^2$	237.2	297.1	22.8	21.6
$d(\mathcal{T}_\phi(\boldsymbol{x}),\mathcal{T}_\phi(\boldsymbol{y}))$	cos	157.9	136.2	25.3	25.0	$d(\mathcal{T}_\phi(\boldsymbol{x}),\mathcal{T}_\phi(\boldsymbol{y}))$	cos	293.1	252.7	19.8	18.0

Figure 4: Generated samples of the deep generative model that adopts the backbone of SNGAN but is optimized with the ACT divergence on CIFAR-10, CelebA, and LSUN-Bedroom. See Appendix B for more results.

Ablation: alternative cost function We also test ACT with different configurations. As discussed in previous sections, the defined cost may also affect the training of the model. Here we vary the choice of transport cost $c_{\boldsymbol{\eta}}(\boldsymbol{x},\boldsymbol{y})$ and the navigator cost $d(\mathcal{T}_\phi(\boldsymbol{x}),\mathcal{T}_\phi(\boldsymbol{y}))$. For both cost, we test with L_2^2 distance and cosine dissimilarity. Moreover, we also compare the effects of distance in the original pixel space and the feature space (equipped with critic $\mathcal{T}_{\boldsymbol{\eta}}$). The results in Table 2 highlight the importance of the cost in the feature space when dealing with high-dimensional image data. Moreover, compared to the L_2^2 distance, the cosine dissimilarity is observed to improve the model when applied as transport and navigator cost, especially with ResNet architecture.

Ablation: alternative critic training loss Contrary to the existing critic-based GANs, the sample estimates of ACT divergence and its gradient are unbiased regardless of how well the critic is trained. We thus keep the same experiment settings and train the ACT-DCGAN model's critic with the discriminator loss of standard GANs, *i.e.* $\mathbb{E}_{x\sim\mathbb{P}_d}\left[-\log(\mathcal{T}_{\boldsymbol{\eta}}(x)\right] + \mathbb{E}_{x\sim\mathbb{P}_g}\left[-\log(1-\mathcal{T}_{\boldsymbol{\eta}}(x))\right]$. The results in Fig. 12 shows that ACT works well in conjunction with the alternative critic training.

4 CONCLUSION

We propose conditional transport (CT) as a new divergence to measure the difference between two probability distributions, via the use of both forward-path and backward-path point-to-point conditional distributions. To apply CT to two distributions that have unknown density functions but are easy to sample from, we introduce the asymptotic CT (ACT) divergence whose estimation only requires access to empirical samples. ACT provides unbiased mini-batch based sample gradients and the minimization can be achieved with the collaboration between the generator, forward navigator, and backward navigator. In addition, a critic can be integrated into the point-to-point transport cost of ACT to adversarially extract features from high-dimensional data without biasing the sample gradients. We apply ACT to train both a vanilla GAN and a Wasserstein GAN. Consistent improvement is observed in our experiments, which shows the potential of the ACT divergence in more broader settings where quantifying the difference between distributions plays an essential role.

REFERENCES

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 214–223, 2017.

Marc G Bellemare, Ivo Danihelka, Will Dabney, Shakir Mohamed, Balaji Lakshminarayanan, Stephan Hoyer, and Rémi Munos. The Cramer distance as a solution to biased Wasserstein gradients. *arXiv preprint arXiv:1705.10743*, 2017.

Espen Bernton, Pierre E Jacob, Mathieu Gerber, and Christian P Robert. On parameter estimation with the Wasserstein distance. *Information and Inference: A Journal of the IMA*, 8(4):657–676, 2019.

Christopher M Bishop. *Pattern Recognition and Machine Learning*. springer, 2006.

Mikołaj Bińkowski, Dougal J. Sutherland, Michael Arbel, and Arthur Gretton. Demystifying MMD GANs. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=r1lUOzWCW.

David M Blei, Alp Kucukelbir, and Jon D McAuliffe. Variational inference: A review for statisticians. *Journal of the American statistical Association*, 112(518):859–877, 2017.

Leon Bottou, Martin Arjovsky, David Lopez-Paz, and Maxime Oquab. Geometrical insights for implicit generative modeling. *arXiv preprint arXiv:1712.07822*, 2017.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale GAN training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096*, 2018.

Ting Chen, Xiaohua Zhai, Marvin Ritter, Mario Lucic, and Neil Houlsby. Self-supervised GANs via auxiliary rotation loss. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 12154–12163, 2019.

Thomas M Cover. *Elements of Information Theory*. John Wiley & Sons, 1999.

Ishan Deshpande, Ziyu Zhang, and Alexander G Schwing. Generative modeling using the sliced Wasserstein distance. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3483–3491, 2018.

Ishan Deshpande, Yuan-Ting Hu, Ruoyu Sun, Ayis Pyrros, Nasir Siddiqui, Sanmi Koyejo, Zhizhen Zhao, David Forsyth, and Alexander G Schwing. Max-sliced Wasserstein distance and its use for GANs. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 10648–10656, 2019.

Jeff Donahue and Karen Simonyan. Large scale adversarial representation learning. In *Advances in Neural Information Processing Systems*, pages 10542–10552, 2019.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pages 2672–2680, 2014.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of Wasserstein GANs. In *Advances in neural information processing systems*, pages 5767–5777, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs trained by a two time-scale update rule converge to a local Nash equilibrium. In *Advances in neural information processing systems*, pages 6626–6637, 2017.

Matthew D Hoffman, David M Blei, Chong Wang, and John Paisley. Stochastic variational inference. *The Journal of Machine Learning Research*, 14(1):1303–1347, 2013.

Ferenc Huszár. Variational inference using implicit distributions. *arXiv preprint arXiv:1702.08235*, 2017.

Leonid V Kantorovich. On the translocation of masses. *Journal of Mathematical Sciences*, 133(4): 1381–1382, 2006.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of GANs for improved quality, stability, and variation. In *International Conference on Learning Representations*, 2018.

Tero Karras, Miika Aittala, Janne Hellsten, Samuli Laine, Jaakko Lehtinen, and Timo Aila. Training generative adversarial networks with limited data. *arXiv preprint arXiv:2006.06676*, 2020.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun, editors, *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

Diederik P Kingma and Max Welling. Auto-encoding variational Bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Alex Krizhevsky et al. Learning multiple layers of features from tiny images. 2009.

Solomon Kullback and Richard A Leibler. On information and sufficiency. *The Annals of Mathematical Statistics*, 22(1):79–86, 1951.

Y. Lecun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, Nov 1998. ISSN 0018-9219. doi: 10.1109/5.726791.

Chun-Liang Li, Wei-Cheng Chang, Yu Cheng, Yiming Yang, and Barnabás Póczos. MMD GAN: Towards deeper understanding of moment matching network. In *Advances in Neural Information Processing Systems*, pages 2203–2213, 2017.

Jianhua Lin. Divergence measures based on the Shannon entropy. *IEEE Transactions on Information theory*, 37(1):145–151, 1991.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of the IEEE international conference on computer vision*, pages 3730–3738, 2015.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. In *International Conference on Learning Representations*, 2018.

Shakir Mohamed and Balaji Lakshminarayanan. Learning in implicit generative models. *arXiv preprint arXiv:1610.03483*, 2016.

Kevin P Murphy. *Machine Learning: A Probabilistic Perspective*. MIT Press, 2012.

Gabriel Peyré and Marco Cuturi. Computational optimal transport. *Foundations and Trends in Machine Learning*, 11(5-6):355–607, 2019.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training GANs. In *Advances in neural information processing systems*, pages 2234–2242, 2016.

Tim Salimans, Han Zhang, Alec Radford, and Dimitris Metaxas. Improving GANs using optimal transport. *arXiv preprint arXiv:1803.05573*, 2018.

Filippo Santambrogio. *Optimal Transport for Applied Mathematicians: Calculus of Variations, PDEs, and Modeling*, volume 87. Birkhäuser, 2015.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2818–2826, 2016.

Dustin Tran, Rajesh Ranganath, and David Blei. Hierarchical implicit models and likelihood-free variational inference. In *Advances in Neural Information Processing Systems*, pages 5523–5533, 2017.

Cédric Villani. *Optimal Transport: Old and New*, volume 338. Springer Science & Business Media, 2008.

Martin J Wainwright and Michael Irwin Jordan. *Graphical models, exponential families, and variational inference*. Now Publishers Inc, 2008.

Xiang Wei, Boqing Gong, Zixia Liu, Wei Lu, and Liqiang Wang. Improving the improved training of Wasserstein GANs: A consistency term and its dual effect. In *International Conference on Learning Representations*, 2018.

Jiqing Wu, Zhiwu Huang, Dinesh Acharya, Wen Li, Janine Thoma, Danda Pani Paudel, and Luc Van Gool. Sliced Wasserstein generative models. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3713–3722, 2019.

Mingzhang Yin and Mingyuan Zhou. Semi-implicit variational inference. In *International Conference on Machine Learning*, pages 5660–5669, 2018.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. LSUN: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

Han Zhang, Ian Goodfellow, Dimitris Metaxas, and Augustus Odena. Self-attention generative adversarial networks. In *International Conference on Machine Learning*, pages 7354–7363. PMLR, 2019.

Shengyu Zhao, Zhijian Liu, Ji Lin, Jun-Yan Zhu, and Song Han. Differentiable augmentation for data-efficient GAN training. *arXiv preprint arXiv:2006.10738*, 2020a.

Zhengli Zhao, Zizhao Zhang, Ting Chen, Sameer Singh, and Han Zhang. Image augmentations for GAN training. *arXiv preprint arXiv:2006.02595*, 2020b.

A PROOFS

Proof of Lemma 1. If $\boldsymbol{y} \sim p_{\boldsymbol{\theta}}(\boldsymbol{y})$ is equal to $\boldsymbol{x} \sim p_X(\boldsymbol{x})$ in distribution, then $p_X(\boldsymbol{x}) = p_{\boldsymbol{\theta}}(\boldsymbol{x})$ for any $\boldsymbol{x} \in \mathbb{R}^V$. For (2) we have $\int p_X(\boldsymbol{x})\pi_{\boldsymbol{\phi}}(\boldsymbol{y} \mid \boldsymbol{x})\mathrm{d}\boldsymbol{y} = p_X(\boldsymbol{x}) \int \pi_{\boldsymbol{\phi}}(\boldsymbol{y} \mid \boldsymbol{x})\mathrm{d}\boldsymbol{y} = p_X(\boldsymbol{x})$ and

$$
\int p_X(\boldsymbol{x})\pi_{\boldsymbol{\phi}}(\boldsymbol{y} \mid \boldsymbol{x})\mathrm{d}\boldsymbol{x} = \int p_X(\boldsymbol{x}) \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}p_{\boldsymbol{\theta}}(\boldsymbol{y})}{\int e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}p_{\boldsymbol{\theta}}(\boldsymbol{y})\mathrm{d}\boldsymbol{y}}\mathrm{d}\boldsymbol{x}
$$
$$
= p_{\boldsymbol{\theta}}(\boldsymbol{y}) \int \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}p_X(\boldsymbol{x})}{\int e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}p_{\boldsymbol{\theta}}(\boldsymbol{y})\mathrm{d}\boldsymbol{y}}\mathrm{d}\boldsymbol{x}.
$$

If $e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))} = \mathbf{1}(\boldsymbol{x} = \boldsymbol{y})$, then we further have

$$
\int \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}p_X(\boldsymbol{x})}{\int e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}p_{\boldsymbol{\theta}}(\boldsymbol{y})\mathrm{d}\boldsymbol{y}}\mathrm{d}\boldsymbol{x} = \int \frac{\mathbf{1}(\boldsymbol{x} = \boldsymbol{y})p_X(\boldsymbol{x})}{\int \mathbf{1}(\boldsymbol{x} = \boldsymbol{y})p_{\boldsymbol{\theta}}(\boldsymbol{y})\mathrm{d}\boldsymbol{y}}\mathrm{d}\boldsymbol{x} = \int \mathbf{1}(\boldsymbol{x} = \boldsymbol{y})\frac{p_X(\boldsymbol{x})}{p_{\boldsymbol{\theta}}(\boldsymbol{x})}\mathrm{d}\boldsymbol{x} = 1
$$

and hence it is true that

$$
\int p_X(\boldsymbol{x})\pi_{\boldsymbol{\phi}}(\boldsymbol{y} \mid \boldsymbol{x})\mathrm{d}\boldsymbol{x} = p_{\boldsymbol{\theta}}(\boldsymbol{y}).
$$

Similarly, for (3) we have $\int p_{\boldsymbol{\theta}}(\boldsymbol{y})\pi_{\boldsymbol{\phi}}(\boldsymbol{x} \mid \boldsymbol{y})\mathrm{d}\boldsymbol{x} = p_{\boldsymbol{\theta}}(\boldsymbol{y})$ and can prove $\int p_{\boldsymbol{\theta}}(\boldsymbol{y})\pi_{\boldsymbol{\phi}}(\boldsymbol{x} \mid \boldsymbol{y})\mathrm{d}\boldsymbol{y} = p_X(\boldsymbol{x})$ given these two conditions. $\qquad\square$

Proof of Lemma 2. Since $c(\boldsymbol{x}, \boldsymbol{y}) \geq 0$ by definition, we have $\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \rightarrow \nu) \geq 0$ and $\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \leftarrow \nu) \geq 0$. When $\mu = \nu$, it is known that $\mathcal{W}(\mu, \nu) = 0$. If $\boldsymbol{y} \sim p_{\boldsymbol{\theta}}(\boldsymbol{y})$ is equal to $\boldsymbol{x} \sim p_X(\boldsymbol{x})$ in distribution, which means $p_X(\boldsymbol{x}) = p_{\boldsymbol{\theta}}(\boldsymbol{x})$ and $p_X(\boldsymbol{y}) = p_{\boldsymbol{\theta}}(\boldsymbol{y})$ for any $\boldsymbol{x}, \boldsymbol{y} \in \mathbb{R}^V$ and $\mu = \nu$, then we have

$$
\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \rightarrow \nu) = \int \int c(\boldsymbol{x}, \boldsymbol{y})p_X(\boldsymbol{x})\pi_{\boldsymbol{\phi}}(\boldsymbol{y} \mid \boldsymbol{x})\mathrm{d}\boldsymbol{x}\mathrm{d}\boldsymbol{y}
$$
$$
= \int \int c(\boldsymbol{x}, \boldsymbol{y}) \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}p_X(\boldsymbol{x})p_{\boldsymbol{\theta}}(\boldsymbol{y})}{\int e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}p_{\boldsymbol{\theta}}(\boldsymbol{y})\mathrm{d}\boldsymbol{y}}\mathrm{d}\boldsymbol{x}\mathrm{d}\boldsymbol{y}
$$
$$
= \int \int c(\boldsymbol{y}, \boldsymbol{x}) \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}))}p_X(\boldsymbol{y})p_{\boldsymbol{\theta}}(\boldsymbol{x})}{\int e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}))}p_{\boldsymbol{\theta}}(\boldsymbol{x})\mathrm{d}\boldsymbol{x}}\mathrm{d}\boldsymbol{x}\mathrm{d}\boldsymbol{y}
$$
$$
= \int \int c(\boldsymbol{y}, \boldsymbol{x}) \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}))}p_{\boldsymbol{\theta}}(\boldsymbol{y})p_X(\boldsymbol{x})}{\int e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}))}p_X(\boldsymbol{x})\mathrm{d}\boldsymbol{x}}\mathrm{d}\boldsymbol{x}\mathrm{d}\boldsymbol{y}
$$
$$
= \int \int c(\boldsymbol{x}, \boldsymbol{y})p_{\boldsymbol{\theta}}(\boldsymbol{y}) \frac{e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}p_X(\boldsymbol{x})}{\int e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))}p_X(\boldsymbol{x})\mathrm{d}\boldsymbol{x}}\mathrm{d}\boldsymbol{x}\mathrm{d}\boldsymbol{y}
$$
$$
= \int \int c(\boldsymbol{x}, \boldsymbol{y})p_{\boldsymbol{\theta}}(\boldsymbol{y})\pi_{\boldsymbol{\phi}}(\boldsymbol{x} \mid \boldsymbol{y})\mathrm{d}\boldsymbol{x}\mathrm{d}\boldsymbol{y}
$$
$$
= \mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \leftarrow \nu)
$$

and hence $C_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu, \nu) = \mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \rightarrow \nu) = \mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \leftarrow \nu) \geq 0 = W(\mu, \nu)$.

If $e^{-d(\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{x}),\mathcal{T}_{\boldsymbol{\phi}}(\boldsymbol{y}))} = \mathbf{1}(\boldsymbol{x} = \boldsymbol{y})$, since $c(\boldsymbol{x}, \boldsymbol{x}) = 0$ by definition, we have

$$
\mathcal{C}_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mu \rightarrow \nu) = \int \int c(\boldsymbol{x}, \boldsymbol{y}) \frac{\mathbf{1}(\boldsymbol{x} = \boldsymbol{y})p_X(\boldsymbol{x})p_{\boldsymbol{\theta}}(\boldsymbol{y})}{\int \mathbf{1}(\boldsymbol{x} = \boldsymbol{y})p_{\boldsymbol{\theta}}(\boldsymbol{y})\mathrm{d}\boldsymbol{y}}\mathrm{d}\boldsymbol{x}\mathrm{d}\boldsymbol{y}
$$
$$
= \int \int c(\boldsymbol{x}, \boldsymbol{y}) \frac{\mathbf{1}(\boldsymbol{x} = \boldsymbol{y})p_X(\boldsymbol{x})p_{\boldsymbol{\theta}}(\boldsymbol{y})}{p_{\boldsymbol{\theta}}(\boldsymbol{x})}\mathrm{d}\boldsymbol{x}\mathrm{d}\boldsymbol{y}
$$
$$
= \int \int c(\boldsymbol{x}, \boldsymbol{y})\mathbf{1}(\boldsymbol{x} = \boldsymbol{y})p_{\boldsymbol{\theta}}(\boldsymbol{y})\mathrm{d}\boldsymbol{x}\mathrm{d}\boldsymbol{y}
$$
$$
= \int c(\boldsymbol{x}, \boldsymbol{x})p_{\boldsymbol{\theta}}(\boldsymbol{x})d\boldsymbol{x}
$$
$$
= 0.
$$

$\qquad\square$

Proof of Lemma 3. According to the strong law of large numbers, when $M \to \infty$, $\hat{\nu}_M(A) = \frac{1}{M}\sum_{j=1}^{M}\mathbf{1}(\boldsymbol{y}_j \in A)$ converges almost surely to

$$\frac{1}{M}\sum_{j=1}^{M}\mathbb{E}_{\boldsymbol{y}_j \sim p_{\boldsymbol{\theta}}(\boldsymbol{y})}[\mathbf{1}(\boldsymbol{y}_j \in A)] = \int_A p_{\boldsymbol{\theta}}(\boldsymbol{y})d\boldsymbol{y} = \nu(A)$$

and hence $C_{\phi,\boldsymbol{\theta}}(\mu \to \hat{\nu}_M)$ converges to $C_{\phi,\boldsymbol{\theta}}(\mu \to \nu)$. Therefore, $\mathbb{E}_{\boldsymbol{y}_{1:M} \overset{iid}{\sim} p_{\boldsymbol{\theta}}(\boldsymbol{y})}[\mathcal{C}_{\phi,\boldsymbol{\theta}}(\mu \to \hat{\nu}_M)]$ converges to $\mathcal{C}_{\phi,\boldsymbol{\theta}}(\mu \to \nu)$. Similarly, we can prove that as $N \to \infty$, $\mathbb{E}_{\boldsymbol{x}_{1:N} \overset{iid}{\sim} p_X(\boldsymbol{x})}[\mathcal{C}_{\phi,\boldsymbol{\theta}}(\hat{\mu}_N \leftarrow \nu)]$ converges to $\mathcal{C}_{\phi,\boldsymbol{\theta}}(\mu \leftarrow \nu)$. Therefore, $\mathcal{C}_{\phi,\boldsymbol{\theta}}(\mu, \nu, N, M)$ defined in (12) converges to $\frac{1}{2}\mathcal{C}_{\phi,\boldsymbol{\theta}}(\mu \to \nu) + \frac{1}{2}\mathcal{C}_{\phi,\boldsymbol{\theta}}(\mu \leftarrow \nu) = \mathcal{C}_{\phi,\boldsymbol{\theta}}(\mu, \nu)$ as $N, M \to \infty$. $\qquad\square$

Proof of Lemma 4.

$$\mathcal{C}_{\phi,\boldsymbol{\theta}}(\mu, \nu, N, M) = \frac{1}{2}\mathbb{E}_{\boldsymbol{y}_{1:M} \overset{iid}{\sim} p_{\boldsymbol{\theta}}(\boldsymbol{y})}[\mathcal{C}_{\phi,\boldsymbol{\theta}}(\mu \to \hat{\nu}_M)] + \frac{1}{2}\mathbb{E}_{\boldsymbol{x}_{1:N} \overset{iid}{\sim} p_X(\boldsymbol{x})}[\mathcal{C}_{\phi,\boldsymbol{\theta}}(\hat{\mu}_N \leftarrow \nu)]$$

$$= \frac{1}{2}\mathbb{E}_{\boldsymbol{x}\sim p_X(\boldsymbol{x}),\ \boldsymbol{y}_{1:M} \overset{iid}{\sim} p_{\boldsymbol{\theta}}(\boldsymbol{y})}[\mathcal{C}_{\phi,\boldsymbol{\theta}}(\boldsymbol{x} \to \hat{\nu}_M)] + \frac{1}{2}\mathbb{E}_{\boldsymbol{x}_{1:N} \overset{iid}{\sim} p_X(\boldsymbol{x}),\ \boldsymbol{y}\sim p_{\boldsymbol{\theta}}(\boldsymbol{y})}[\mathcal{C}_{\phi,\boldsymbol{\theta}}(\hat{\mu}_N \leftarrow \boldsymbol{y})]$$

$$= \frac{1}{2}\mathbb{E}_{\boldsymbol{x}\sim\hat{p}_N(\boldsymbol{x})}\mathbb{E}_{\boldsymbol{x}_{1:M} \overset{iid}{\sim} p_X(\boldsymbol{x}),\ \boldsymbol{y}_{1:M} \overset{iid}{\sim} p_{\boldsymbol{\theta}}(\boldsymbol{y})}[\mathcal{C}_{\phi,\boldsymbol{\theta}}(\boldsymbol{x} \to \hat{\nu}_M)]$$

$$\quad + \frac{1}{2}\mathbb{E}_{\boldsymbol{y}\sim\hat{p}_M(\boldsymbol{y})}\mathbb{E}_{\boldsymbol{x}_{1:N} \overset{iid}{\sim} p_X(\boldsymbol{x}),\ \boldsymbol{y}_{1:M} \overset{iid}{\sim} p_{\boldsymbol{\theta}}(\boldsymbol{y})}[\mathcal{C}_{\phi,\boldsymbol{\theta}}(\hat{\mu}_N \leftarrow \boldsymbol{y})]$$

$$= \mathbb{E}_{\boldsymbol{x}\sim\hat{p}_N(\boldsymbol{x}),\ \boldsymbol{y}\sim\hat{p}_M(\boldsymbol{y})}\mathbb{E}_{\boldsymbol{x}_{1:N} \overset{iid}{\sim} p_X(\boldsymbol{x}),\ \boldsymbol{y}_{1:M} \overset{iid}{\sim} p_{\boldsymbol{\theta}}(\boldsymbol{y})}\left[\tfrac{1}{2}\mathcal{C}_{\phi,\boldsymbol{\theta}}(\boldsymbol{x} \to \hat{\nu}_M) + \tfrac{1}{2}\mathcal{C}_{\phi,\boldsymbol{\theta}}(\hat{\mu}_N \leftarrow \boldsymbol{y})\right]. \quad (18)$$

Plugging (8) and (10) into the above equation concludes the proof.

$\square$

Proof of Lemma 5. Solving the first expectation of (18), we have

$$\mathcal{C}_{\phi,\boldsymbol{\theta}}(\mu, \nu, N, M)$$
$$= \mathbb{E}_{\boldsymbol{x}_{1:N} \overset{iid}{\sim} p_X(\boldsymbol{x}),\ \boldsymbol{y}_{1:M} \overset{iid}{\sim} p_{\boldsymbol{\theta}}(\boldsymbol{y})}\left[\tfrac{1}{2N}\sum_{i=1}^{N}\mathcal{C}_{\phi,\boldsymbol{\theta}}(\boldsymbol{x}_i \to \hat{\nu}_M) + \tfrac{1}{2M}\sum_{j=1}^{M}\mathcal{C}_{\phi,\boldsymbol{\theta}}(\hat{\mu}_N \leftarrow \boldsymbol{y}_j)\right].$$

Plugging (8) and (10) into the above equation concludes the proof.

$\square$

B SUPPLEMENTARY EXPERIMENT RESULTS

B.1 DERIVATION OF THE UNIVARIATE NORMAL BASED TOY EXAMPLE DEFINED IN (17)

For the toy example specified in (17), exploiting the normal-normal conjugacy, we have an analytical conditional distribution for the forward navigator as

$$\pi_\phi(y \mid x) \propto e^{-\frac{(x-y)^2}{2e^\phi}}\mathcal{N}(y; 0, e^\theta)$$
$$\propto \mathcal{N}(x; y, e^\phi)\mathcal{N}(y; 0, e^\theta)$$
$$= \mathcal{N}\left(\frac{e^\theta}{e^\theta + e^\phi}x, \frac{e^\phi e^\theta}{e^\theta + e^\phi}\right),$$

and an analytical conditional distribution for the backward navigator as

$$\pi_\phi(x \mid y) \propto e^{-\frac{(x-y)^2}{2e^\phi}}\mathcal{N}(x; 0, 1)$$
$$\propto \mathcal{N}(y; x, e^\phi)\mathcal{N}(x; 0, 1)$$
$$= \mathcal{N}\left(\frac{y}{1 + e^\phi}, \frac{e^\phi}{1 + e^\phi}\right).$$

Plugging them into (2) and (3), respectively, and solving the expectations, we have

$$\mathcal{C}_{\phi,\theta}(\mu \to \nu) = \mathbb{E}_{x \sim \mathcal{N}(0,1)} \left[\frac{e^\phi}{e^\theta + e^\phi} \left(e^\theta + \frac{e^\phi}{e^\theta + e^\phi} x^2 \right) \right]$$

$$= \frac{e^\phi}{e^\theta + e^\phi} \left(e^\theta + \frac{e^\phi}{e^\theta + e^\phi} \right),$$

$$\mathcal{C}_{\phi,\theta}(\mu \leftarrow \nu) = \mathbb{E}_{y \sim \mathcal{N}(0,e^\theta)} \left[\frac{e^\phi}{1 + e^\phi} \left(1 + \frac{e^\phi}{1 + e^\phi} y^2 \right) \right]$$

$$= \frac{e^\phi}{1 + e^\phi} \left(1 + \frac{e^\phi}{1 + e^\phi} e^\theta \right).$$

B.2   MORE RESULTS ON 2D TOY DATASETS

We visualize the results on three additional 2D toy datasets here. Compared to the 8-Gaussian mixture dataset, the mode collapse issue of both GAN and WGAN-GP becomes more severe on the Swiss-Roll, Half-Moon, and 25-Gaussian datasets, while ACT consistently shows good and stable performance on all of them.

Figure 5: Analogous plot to Fig. 3 for the Swiss-Roll dataset.

Figure 6: Analogous plot to Fig. 3 for the Half-Moon dataset.

Figure 7: Analogous plot to Fig. 3 for the 25-Gaussian mixture dataset.

We also illustrate the data points and generated samples with empirical samples, shown in Fig. 8. The first column shows the generated samples (marked in blue) and the samples from data distribution (marked in red). To visualize how the feature extractor $\mathcal{T}_\phi$ used by both navigators works, we set its output dimension as 1 and plot the logits in the third and fifth columns and map the corresponding data (in the second column) and generated samples (in the fourth column) with the same color.

Similarly, we visualize the GAN's generated samples and logits produced by its discriminator in Fig. 9. We can observe that the discriminator maps the data to very close values. Specifically, in both the 8-Gaussian mixture and 25-Gaussian mixture cases, when the mode collapse occurs, the logits of the missed modes have similar value to the those in the other modes. This property results in GAN's mode collapse problem and it is commonly observed in GANs. Different from the GAN case, the navigator in our ACT model maps the data with non-saturating logits. We can observe in various multi-mode cases, different modes are assigned with different values by the navigator. This property helps ACT to well resist the mode collapse problem and stabilize the training.

Figure 8: Visual results of *ACT* for generated samples (blue dots) compared to real samples (red dots) on Swiss Roll, Half Moons, 8-Gaussian mixture, and 25-Gaussian mixture. The second and third columns map the data points and their corresponding *navigator* logits by color; The fourth and fifth columns map the generated points and their corresponding *navigator* logits by color.

Figure 9: Visual results of *GAN* for generated samples (blue dots) compared to real samples (red dots) on Swiss Roll, Half Moons, 8-Gaussian mixture, and 25-Gaussian mixture. The second and the third columns map the data points and their corresponding *discriminator* logits by color; The fourth and fifth columns map the generated points and the corresponding *discriminator* logits by color.

B.3 Results for ablation study

Transport cost in pixel space *vs.* feature space We visualize the difference of using the transport cost in the pixel space and in the feature space here. In both Figs. 10 and 11, we test with MNSIT and CIFAR-10 data and with the $\mathcal{L}_2^2$ distance and cosine dissimilarity as the transport cost, respectively. For the MNIST dataset, due to its simple data structure, ACT can still be trained to generate meaningful digits, though some digits appear blurry. On the CIFAR-10, we can observe the model fails to generate any class of CIFAR images. As the dimensionality of the input space increases, using the distance in the pixel space as transport cost might lose the essential information for the transport and increases the training complexity of the navigator.

Figure 10: Visual results of generated samples on MNIST and CIFAR-10 using pixel-wise transport cost, with DCGAN (standard CNN) backbone.

Figure 11: Visual results of generated samples on MNIST and CIFAR-10 using pixel-wise transport cost, with SNGAN (ResNet) backbone. The Inception and FID scores are not shown due to poor visual quality.

Training the critic with the discriminator loss of a vanilla GAN The quantitative and qualitative on MNIST, CIFAR-10, CelebA, and LSUN are shown in Fig. 12. We can observe the quality of generated samples, while clearly not as good as training the critic with the ACT divergence, can still catch up with some of the benchmarks in Table 1.

Figure 12: Visual results of using a standard cross-entropy discriminator loss in lieu of ACT divergence to train the critic of ACT.

B.4 MORE RESULTS ON IMAGE DATASETS

For the experiments on the image datasets, we provide more visual results in this part. Apart from the datasets described in the experiment part, we also test the capacity of single-channel image generation with the MNIST dataset. Considering the inception score and the FID score are designed for RGB natural images, we also calculate the inception score of the real testing sets for reference. The presented methods are all able to generate meaningful digits on MNIST. If we take a closer look at the digits, the digits generated with $\mathcal{L}_2$ cost is less natural than the one with cosine cost. Moreover, we show both unconditional and conditional generation results on CIFAR-10. For both unconditional and conditional generation, our proposed method achieves good quantitative and qualitative results.

Figure 13: Unconditional generated samples and inception scores of MNIST, with DCGAN (standard CNN) backbone.

Figure 14: Unconditional generated samples and FIDs of CIFAR-10, with DCGAN (standard CNN) backbone.

Figure 15: Unconditional generated samples and FIDs of CIFAR-10, with SNGAN (ResNet) backbone.

Figure 16: Conditional generated samples and FIDs of CIFAR-10, with SNGAN (ResNet) backbone.

Figure 17: Generated samples and FIDs of CelebA, with DCGAN (standard CNN) backbone.

Figure 18: Generated samples and FIDs of CelebA, with SNGAN (ResNet) backbone.

Figure 19: Generated samples and FIDs of LSUN, with DCGAN (standard CNN) backbone.

Figure 20: Generated samples and FIDs of LSUN, with SNGAN (ResNet) backbone.

B.5 EXPERIMENT DETAILS

Preparation of datasets   We apply the commonly used training set of MNIST (50K images, 28×28 pixels) (Lecun et al., 1998), CIFAR-10 (50K images, 32×32 pixels) (Krizhevsky et al., 2009), CelebA (about 203K images, resized to 64×64 pixels) (Liu et al., 2015), and LSUN bedrooms (around 3 million images, resized to 64×64 pixels) (Yu et al., 2015). The images were scaled to range $[-1, 1]$. For MNIST, when calculate the inception score, we repeat the channel to convert each gray-scale image into a RGB format.

Network architecture and hyperparameters   For the network architectures presented here, the slopes of all lReLU functions in the networks are set to 0.1 by default. For toy experiments, typically $10,000$ update steps are sufficient. However, our experiments show that the DGM optimized with the ACT divergence can be stably trained at least over $500,000$ steps (or possibly even more if allowed to running non-stop) regardless of whether the navigators are frozen or not after a certain number of iterations, where the GAN's discriminator usually diverges long before reaching that many iterations even if we do not freeze it after a certain number of iterations. For all image experiments, the output feature dimension of the navigators and that of the critic (*i.e.*, $\mathcal{T}_{\phi}(\cdot), \mathcal{T}_{\eta}(\cdot) \in \mathbb{R}^m$) are set to $m = 2048$. All models are able to be trained on a single GPU, such as NVidia GTX 1080-TI in our experiments, with $150,000$ generator updates (for CIFAR-10 we apply $50,000$ iterations).

To keep close to the configuration of the DCGAN and SNGAN experiments setting, we use the the Adam optimizer (Kingma and Ba, 2015) with learning rate $\alpha = 2 \times 10^{-4}$ and $\beta_1 = 0.5$, $\beta_2 = 0.99$ for the parameters of the generator, navigators, and critic. On the DCGAN backbone, we let all the modules update with the same frequency; while on the SNGAN backbone, the critic is updated once per 5 generator updating steps. The performance might be further improved with more careful fine-tuning. For example, the learning rate of the navigator parameter could be made smaller than that of the generator parameter. The true data minibatch size is fixed to $N = 64$ for all experiments. Moreover, with this batch-size we let the generated sample size M the same as minibatch size N for ACT computation and we have monitored the average time for each update step on a single NVidia GTX 1080-TI GPU: On CIFAR-10, each update step takes around 0.1s and 0.2s for DCGAN and SNGAN, respectively; For DCGAN and SNGAN backbone trained with ACT divergence each update step takes around 0.4s and 0.7s. On CelebA and LSUN, each update takes 0.6s and 0.7s for DCGAN and SNGAN, respectively; when trained with ACT, the elapsed time for each update increases to 3.3s and 3.6s, respectively.

Table 3: Network architecture for toy datasets (V indicates the dimensionality of data).

(a) Generator $G_{\boldsymbol{\theta}}$
$\boldsymbol{\epsilon} \in \mathbb{R}^{50} \sim \mathcal{N}(0, 1)$
$50 \to 100$, dense, lReLU
$100 \to 50$, dense, lReLU
$50 \to V$, dense, linear

(b) Navigator $\mathcal{T}_{\phi}$
$\boldsymbol{x} \in \mathbb{R}^V$
$2 \to 100$, dense, lReLU
$100 \to 50$, dense, lReLU
$50 \to 1$, dense, linear

Table 4: DCGAN architecture for CIFAR-10 datasets ($h = w = 4$).

(a) Generator $G_{\boldsymbol{\theta}}$

$\boldsymbol{\epsilon} \in \mathbb{R}^{128} \sim \mathcal{N}(0,1)$
$128 \to 4 \times 4 \times 512$, dense, linear
4×4, stride=2 deconv. BN 256 ReLU
4×4, stride=2 deconv. BN 128 ReLU
4×4, stride=2 deconv. BN 64 ReLU
3×3, stride=1 conv. 3 Tanh

(b) Navigator $\mathcal{T}_{\boldsymbol{\phi}}$ / Critic $\mathcal{T}_{\boldsymbol{\eta}}$

$\boldsymbol{x} \in [-1,1]^{32 \times 32 \times 3}$
3×3, stride=1 conv 64 lReLU
4×4, stride=2 conv 64 lReLU
3×3, stride=1 conv 128 lReLU
4×4, stride=2 conv 128 lReLU
3×3, stride=1 conv 256 lReLU
4×4, stride=2 conv 256 lReLU
3×3, stride=1 conv. 512 lReLU
$h \times w \times 512 \to m$, dense, linear

Table 5: DCGAN architecture on for CelebA and LSUN datasets ($h = w = 4$).

(a) Generator $G_{\boldsymbol{\theta}}$

$\boldsymbol{\epsilon} \in \mathbb{R}^{128} \sim \mathcal{N}(0,1)$
$128 \to 4 \times 4 \times 1024$, dense, linear
4×4, stride=2 deconv. BN 512 ReLU
4×4, stride=2 deconv. BN 256 ReLU
4×4, stride=2 deconv. BN 128 ReLU
4×4, stride=2 deconv. BN 64 ReLU
3×3, stride=1 conv. 3 Tanh

(b) Navigator $\mathcal{T}_{\boldsymbol{\phi}}$ / Critic $\mathcal{T}_{\boldsymbol{\eta}}$

$\boldsymbol{x} \in [-1,1]^{64 \times 64 \times 3}$
4×4, stride=2 conv 64 lReLU
4×4, stride=2 conv BN 128 lReLU
4×4, stride=2 conv BN 256 lReLU
3×3, stride=1 conv BN 512 lReLU
$h \times w \times 512 \to m$, dense, linear

Table 6: ResNet architecture on for CIFAR-10 datasets.

(a) Generator $G_{\boldsymbol{\theta}}$

$\boldsymbol{\epsilon} \in \mathbb{R}^{128} \sim \mathcal{N}(0,1)$
$128 \to 4 \times 4 \times 256$, dense, linear
ResBlock up 256
ResBlock up 256
ResBlock up 256
BN, ReLU, 3×3 conv, 3 Tanh

(b) Navigator $\mathcal{T}_{\boldsymbol{\phi}}$ / Critic $\mathcal{T}_{\boldsymbol{\eta}}$

$\boldsymbol{x} \in [-1,1]^{32 \times 32 \times 3}$
ResBlock down 128
ResBlock down 128
ResBlock 128
ResBlock 128
ReLU
Global sum pooling
$h = 128 \to m$, dense, linear

Table 7: ResNet architecture on for CelebA and LSUN datasets.

(a) Generator $G_{\boldsymbol{\theta}}$

$\boldsymbol{\epsilon} \in \mathbb{R}^{128} \sim \mathcal{N}(0, 1)$
$128 \rightarrow 4 \times 4 \times 1024$, dense, linear
ResBlock up 512
ResBlock up 256
ResBlock up 128
ResBlock up 64
BN, ReLU, 3×3 conv, 3 Tanh

(b) Navigator $\mathcal{T}_{\boldsymbol{\phi}}$ / Critic $\mathcal{T}_{\boldsymbol{\eta}}$

$\boldsymbol{x} \in [-1, 1]^{64 \times 64 \times 3}$
ResBlock down 128
ResBlock down 256
ResBlock down 512
ResBlock down 1024
ReLU
Global sum pooling
$h = 1024 \rightarrow m$, dense, linear